

## Contents

<b>1</b>	<b>include/binio.hpp</b>	<b>2</b>
<b>2</b>	<b>include/codecs.hpp</b>	<b>5</b>
<b>3</b>	<b>include/integer_codes.hpp</b>	<b>6</b>
<b>4</b>	<b>test/test.cpp</b>	<b>10</b>
<b>5</b>	<b>test/testing.hpp</b>	<b>17</b>

# 1 include/binio.hpp

```
/*
 * Toy Compression - Toy Compression Code
 * Written in 2018 by Gerald Lewis <lewisgdljr@gmail.com>
 *
 * To the extent possible under law, the author(s) have dedicated all copyright
 * and related and neighboring rights to this software to the public domain
 * worldwide. This software is distributed without any warranty.
 * You should have received a copy of the CC0 Public Domain Dedication along
 * with this software. If not, see
 * <http://creativecommons.org/publicdomain/zero/1.0/>.
 */

#pragma once
#ifndef BINIO_HPP
#define BINIO_HPP

#include <cstdint>
#include <iostream>
#include <iterator>
#include <limits>
#include <utility>

namespace binio {
    template <typename Iterator, typename Iterator2>
    struct bit_reader {
        Iterator      pos;
        Iterator2     end;
        std::uint8_t   buf;
        std::uint64_t  total_count;
        unsigned int   bits_left;

        bit_reader( Iterator&& begin_, Iterator2&& end_ ) :
            pos{begin_},
            end{end_},
            buf{0},
            total_count{0},
            bits_left{0} {}

        void input_byte() {
            if ( pos == end ) {
                throw std::out_of_range(
                    "Attempt to read bits beyond end of range" );
            }
            bits_left = std::numeric_limits<std::uint8_t>::digits;
            buf       = *pos;
            ++pos;
        }

        bool read_bit() {
            if ( bits_left == 0 ) {
                input_byte();
            }
            ++total_count;
            --bits_left;
            return ( buf >> bits_left ) & 1;
        }
    };
}
```

```

    }

    template <typename T>
    T read_bits( unsigned int bits ) {
        using UT = std::make_unsigned_t<T>;
        UT temp{0};
        for ( unsigned int i = 0; i < bits; i++ ) {
            temp = ( temp << 1 ) | read_bit();
        }
        return temp;
    }
};

template <typename Iterator, typename Iterator2,
          typename
          = typename std::iterator_traits<Iterator>::iterator_category>
auto make_bit_reader( Iterator&& begin, Iterator2&& end )
    -> bit_reader<Iterator, Iterator2> {
    return bit_reader<Iterator, Iterator2>{std::forward<Iterator>( begin ),
                                           std::forward<Iterator2>( end )};
}

template <typename Container,
          typename = decltype( std::declval<Container>().cbegin() )>
auto make_bit_reader( Container const& c ) {
    return make_bit_reader( c.cbegin(), c.cend() );
}

template <typename stream_t>
auto make_bit_reader( stream_t& stream ) -> decltype(
    make_bit_reader( std::istream_iterator<unsigned char>( stream ),
                    std::istream_iterator<unsigned char>() ) ) {
    return make_bit_reader( std::istream_iterator<unsigned char>( stream ),
                           std::istream_iterator<unsigned char>() );
}

template <typename Iterator>
struct bit_writer {
    Iterator      pos;
    std::uint8_t  buf;
    std::uint64_t total_count;
    unsigned int  bits_left;
    bit_writer( Iterator&& begin_ ) :
        pos{std::forward<Iterator>( begin_ )},
        buf{0},
        total_count{0},
        bits_left{std::numeric_limits<std::uint8_t>::digits} {}
    ~bit_writer() {
        if ( bits_left != std::numeric_limits<std::uint8_t>::digits ) {
            flush();
        }
    }
    bit_writer( bit_writer const& ) = delete;
    bit_writer( bit_writer const&& ) = delete;
    operator=( bit_writer const& ) = delete;
    operator=( bit_writer const&& ) = delete;
};

```

```

void output_byte() {
    *pos = buf;
    buf = 0;
    ++pos;
    bits_left = std::numeric_limits<std::uint8_t>::digits;
}

void write_bit( bool bit ) {
    --bits_left;
    ++total_count;
    buf |= ( static_cast<std::uint8_t>( bit ) << bits_left );
    if ( bits_left == 0 ) {
        output_byte();
    }
}

template <typename T, typename UT = std::make_unsigned_t<T>>
void write_bits( T value, unsigned int num_bits ) {
    for ( int i = num_bits; i > 0; --i ) {
        UT mask = static_cast<UT>( 1 ) << ( i - 1 );
        write_bit( ( static_cast<UT>( value ) & mask ) != 0 );
    }
}

void flush() { output_byte(); }
};

template <typename Iterator,
          typename
          = typename std::iterator_traits<Iterator>::iterator_category>
auto make_bit_writer( Iterator&& begin ) -> bit_writer<Iterator> {
    return bit_writer<Iterator>{std::forward<Iterator>( begin )};
}

template <typename Container,
          typename = decltype( std::declval<Container>().begin() )>
auto make_bit_writer( Container&& c ) {
    return make_bit_writer( std::back_inserter( c ) );
}

template <typename stream_t>
auto make_bit_writer( stream_t& stream ) -> decltype(
    make_bit_writer( std::ostream_iterator<unsigned char>( stream ) ) ) {
    return make_bit_writer( std::ostream_iterator<unsigned char>( stream ) );
}
} // namespace binio

#endif // BINIO_HPP

```

## 2 include/codecs.hpp

```
/*
 * Toy Compression - Toy Compression Code
 * Written in 2018 by Gerald Lewis <lewisgdljr@gmail.com>
 *
 * To the extent possible under law, the author(s) have dedicated all copyright
 * and related and neighboring rights to this software to the public domain
 * worldwide. This software is distributed without any warranty.
 * You should have received a copy of the CC0 Public Domain Dedication along
 * with this software. If not, see
 * <http://creativecommons.org/publicdomain/zero/1.0/>.
 */

#pragma once
#ifndef CODECS_HPP_INCLUDED
#define CODECS_HPP_INCLUDED

#ifndef BINIO_HPP
#include "binio.hpp"
#endif

#ifndef INTEGER_CODES_HPP
#include "integer_codes.hpp"
#endif

#endif // CODECS_HPP_INCLUDED
```

### 3 include/integer\_codes.hpp

```
/*
 * Toy Compression - Toy Compression Code
 * Written in 2018 by Gerald Lewis <lewisgdljr@gmail.com>
 *
 * To the extent possible under law, the author(s) have dedicated all copyright
 * and related and neighboring rights to this software to the public domain
 * worldwide. This software is distributed without any warranty.
 * You should have received a copy of the CC0 Public Domain Dedication along
 * with this software. If not, see
 * <http://creativecommons.org/publicdomain/zero/1.0/>.
 */

#pragma once
#ifndef INTEGER_CODES_HPP
#define INTEGER_CODES_HPP

#include <cmath>
#include <exception>
#include <type_traits>

namespace integer_codes {
    struct unary {
        template <typename T, typename Iterator,
                  typename = std::enable_if_t<std::is_unsigned_v<T>>>
        static void encode( T x, binio::bit_writer<Iterator>& storage ) {
            if ( x == 0 ) {
                throw std::invalid_argument( "unary code can't encode 0" );
            }
            T temp{x};
            while ( temp > 1 ) {
                --temp;
                storage.write_bit( 0 );
            }
            storage.write_bit( 1 );
        }

        template <typename T, typename Iterator, typename Iterator2,
                  typename = std::enable_if_t<std::is_unsigned_v<T>>>
        static T decode( binio::bit_reader<Iterator, Iterator2>& storage ) {
            T temp{1};
            while ( !storage.read_bit() ) {
                ++temp;
            }
            return temp;
        }
    };

    struct truncated_binary {
        template <typename T, typename Iterator,
                  typename = std::enable_if_t<std::is_unsigned_v<T>>>
        static void encode( T x, T n, binio::bit_writer<Iterator>& storage ) {
            if ( n == 0 ) {
                throw std::invalid_argument(
                    "for the truncated binary code, n can't be 0" );
            }
        }
    };
}
```

```

    T    k      = static_cast<T>( std::floor( std::log2( n ) ) );
    T    u      = ( 1 << ( k + 1 ) ) - n;
    bool lesser = x < u;
    x      = lesser ? x : x + u;
    k      = lesser ? k : k + 1;
    storage.write_bits( x, k );
}

template <typename T, typename Iterator, typename Iterator2,
          typename = std::enable_if_t<std::is_unsigned_v<T>>>
static T decode( T n, binio::bit_reader<Iterator, Iterator2>& storage ) {
    if ( n == 0 ) {
        throw std::invalid_argument(
            "for the truncated binary code, n can't be 0" );
    }
    T    k      = static_cast<T>( std::floor( std::log2( n ) ) );
    T    u      = ( 1 << ( k + 1 ) ) - n;
    T    x      = storage.template read_bits<T>( k );
    bool greater_eq = x >= u;
    x = greater_eq ? ( ( x << 1 ) | storage.read_bit() ) - u : x;
    return x;
}
};

struct elias_gamma {
    template <typename T, typename Iterator,
              typename = std::enable_if_t<std::is_unsigned_v<T>>>
    static void encode( T x, binio::bit_writer<Iterator>& storage ) {
        if ( x == 0 ) {
            throw std::invalid_argument( "elias_gamma code can't encode 0" );
        }

        T b = 1 + static_cast<T>( std::floor( std::log2( x ) ) );
        unary::template encode<T>( b, storage );
        storage.write_bits( x - ( 1 << ( b - 1 ) ), b - 1 );
    }

    template <typename T, typename Iterator, typename Iterator2,
              typename = std::enable_if_t<std::is_unsigned_v<T>>>
    static T decode( binio::bit_reader<Iterator, Iterator2>& storage ) {
        T b = unary::template decode<T>( storage );
        T x = storage.template read_bits<T>( b - 1 );
        return ( 1 << ( b - 1 ) ) + x;
    }
};

struct elias_delta {
    template <typename T, typename Iterator,
              typename = std::enable_if_t<std::is_unsigned_v<T>>>
    static void encode( T x, binio::bit_writer<Iterator>& storage ) {
        if ( x == 0 ) {
            throw std::invalid_argument( "elias_delta code can't encode 0" );
        }
        T b = 1 + static_cast<T>( std::floor( std::log2( x ) ) );
        elias_gamma::template encode<T>( b, storage );
        storage.template write_bits<T>( ( x - ( 1 << ( b - 1 ) ) ), b - 1 );
    }
};

```

```

    }

    template <typename T, typename Iterator, typename Iterator2,
              typename = std::enable_if_t<std::is_unsigned_v<T>>>
    static T decode( binio::bit_reader<Iterator, Iterator2>& storage ) {
        T b = elias_gamma::template decode<T>( storage );
        T x = storage.template read_bits<T>( b - 1 );
        return ( 1 << ( b - 1 ) ) + x;
    }
};

struct golomb {
    template <typename T, typename Iterator,
              typename = std::enable_if_t<std::is_unsigned_v<T>>>
    static void encode( T x, T b, binio::bit_writer<Iterator>& storage ) {
        if ( ( x == 0 ) || ( b == 0 ) ) {
            throw std::invalid_argument(
                "golomb_code can't encode 0, and can't "
                "encode with golomb parameter 0" );
        }

        T q = ( x - 1 ) / b;
        T r = ( x - 1 ) % b;
        unary::template encode<T>( q + 1, storage );
        truncated_binary::template encode<T>( r, b, storage );
    }

    template <typename T, typename Iterator, typename Iterator2,
              typename = std::enable_if_t<std::is_unsigned_v<T>>>
    static T decode( T b, binio::bit_reader<Iterator, Iterator2>& storage ) {
        if ( b == 0 ) {
            throw std::invalid_argument(
                "golomb_code can't decode with golomb parameter 0" );
        }

        T q = unary::template decode<T>( storage ) - 1;
        T r = truncated_binary::template decode<T>( b, storage );
        return r + ( q * b ) + 1;
    }
};

struct rice {
    template <typename T, typename Iterator,
              typename = std::enable_if_t<std::is_unsigned_v<T>>>
    static void encode( T x, T k, binio::bit_writer<Iterator>& storage ) {
        if ( x == 0 ) {
            throw std::invalid_argument( "rice_code can't encode 0" );
        }

        T b = 1 << k;
        golomb::encode( x, b, storage );
    }

    template <typename T, typename Iterator, typename Iterator2,
              typename = std::enable_if_t<std::is_unsigned_v<T>>>
    static T decode( T k, binio::bit_reader<Iterator, Iterator2>& storage ) {
        T b = 1 << k;

```



```
        return golomb::template decode<T>( b, storage );
    }
};
} // namespace integer_codes
#endif // INTEGER_CODES_HPP
```

## 4 test/test.cpp

```
/*
 * Toy Compression - Toy Compression Code
 * Written in 2018 by Gerald Lewis <lewisgdljr@gmail.com>
 *
 * To the extent possible under law, the author(s) have dedicated all copyright
 * and related and neighboring rights to this software to the public domain
 * worldwide. This software is distributed without any warranty.
 * You should have received a copy of the CC0 Public Domain Dedication along
 * with this software. If not, see
 * <http://creativecommons.org/publicdomain/zero/1.0/>.
 */

#include "codecs.hpp"
#include "testing.hpp"
#include <stdint>
#include <iomanip>
#include <ios>
#include <iostream>
#include <sstream>
#include <vector>

using container = std::vector<std::uint8_t>;
using iterator = typename container::iterator;

using test_type = unsigned;

using binio::make_bit_reader;
using binio::make_bit_writer;

toy_test::test_suite bit_reader_suite
    = {"Test for bit_reader",
        {
            {"bit_reader can be created from a pair of iterators",
                [] {
                    container c( 100 );
                    (void)make_bit_reader( c.begin(), c.end() );
                    ASSERT( true );
                }},
            {"bit_reader can be created from a container",
                [] {
                    container c( 100 );
                    (void)make_bit_reader( c );
                    ASSERT( true );
                }},
            {"bit_reader can be created from an istream",
                [] {
                    std::istringstream ss;
                    (void)make_bit_reader( ss );
                    ASSERT( true );
                }},
            {"bit_reader throws exception when read from empty",
                [] {
```

```

        container c{};
        auto reader = make_bit_reader( c );
        THROWS( reader.read_bit(), std::out_of_range );
    }},

    {"bit_reader.read_bit() returns the first available bit",
     [] {
         container c{0x70};
         auto reader = make_bit_reader( c );
         ASSERT( reader.read_bit() == 0 );
     }},

    {"bit_reader.read_bits() returns multiple bits",
     [] {
         container c{0x70, 0x0f, 0x0};
         auto reader = make_bit_reader( c );
         (void)reader.read_bit();
         auto temp = reader.read_bits<test_type>( 16 );
         ASSERT( temp == 0xe01e );
     }},

    });

toy_test::test_suite bit_writer_suite
= {"Test for bit_writer",
   {
       {"bit_writer can be created from an iterator",
        [] {
            container c;
            (void)make_bit_writer( std::back_inserter( c ) );
            ASSERT( true );
        }},

       {"bit_writer can be created from a container",
        [] {
            container c;
            (void)make_bit_writer( c );
            ASSERT( true );
        }},

       {"bit_writer can be created from an ostream",
        [] {
            std::ostringstream ss;
            {
                auto writer = make_bit_writer( ss );
                for ( int i = 0; i < 10; i++ ) {
                    writer.write_bit( 1 );
                }
            }
            { (void)make_bit_writer( ss ); }

            ASSERT( true );
        }},

       {"bit_writer.write_bit() writes a bit to the buffer",
        [] {
            container c;

```

```

        auto writer = make_bit_writer( c );
        writer.write_bit( 1 );
        writer.write_bit( 1 );
        writer.write_bit( 1 );
        writer.write_bit( 0 );
        writer.flush();
        ASSERT( c[0] == 0xe0 );
    }},

    {"bit_writer.write_bits() writes a group of bits to the buffer",
     [] {
         container c;
         auto writer = make_bit_writer( c );
         writer.write_bits<test_type>( 0xfaf, 12 );
         writer.flush();
         ASSERT( ( c[0] == 0xfa ) && ( c[1] == 0xf0 ) );
     }},

    {"bit_writer flushes partial bytes to the buffer",
     [] {
         container c;
         {
             auto writer = make_bit_writer( c );
             writer.write_bit( 1 );
             writer.write_bit( 1 );
         }
         ASSERT( c[0] == 0xc0 );
     }},
    }},

void test_unary_coder( test_type value ) {
    container c;
    {
        auto writer = make_bit_writer( c );
        integer_codes::unary::encode( value, writer );
    }
    auto reader = make_bit_reader( c );
    auto decoded = integer_codes::unary::decode<test_type>( reader );
    ASSERT( decoded == value );
}

toy_test::test_suite unary_suite
= {"test_for_unary_coder",
   {
       {"throws an exception for x=0",
        [] {
            container c;
            auto writer = make_bit_writer( c );
            THROWS( integer_codes::unary::encode<test_type>( 0, writer ),
                    std::invalid_argument );
        }},
       {"encodes a one-value", [] { test_unary_coder( 1 ); }},
       {"encodes a small integer", [] { test_unary_coder( 2 ); }},
       {"encodes another small integer", [] { test_unary_coder( 5 ); }},
   }},

void test_truncated_binary_coder( test_type value, test_type n ) {

```

```

    container c;
    {
        auto writer = make_bit_writer( c );
        integer_codes::truncated_binary::encode( value, n, writer );
    }
    auto reader = make_bit_reader( c );
    auto decoded
        = integer_codes::truncated_binary::decode<test_type>( n, reader );
    ASSERT( decoded == value );
}

toy_test::test_suite truncated_binary_suite
= { "Test for truncated binary coder",
    {
        { "encode() throws an exception for n=0",
            [] {
                container c;
                auto writer = make_bit_writer( c );
                THROWS( integer_codes::truncated_binary::encode<test_type>(
                    1, 0, writer ),
                    std::invalid_argument );
            } },

        { "decode() throws an exception for n=0",
            [] {
                container c( 100 );
                auto reader = make_bit_reader( c );
                THROWS(
                    integer_codes::truncated_binary::decode<test_type>( 0, reader ),
                    std::invalid_argument );
            } },

        { "encodes a value of 3 using n=6",
            [] { test_truncated_binary_coder( 3, 6 ); } },

        { "encodes a value of 3 using n=4",
            [] { test_truncated_binary_coder( 3, 4 ); } },

        { "encodes a value of 3 using n=8",
            [] { test_truncated_binary_coder( 3, 8 ); } },

        { "encodes a value of 7 using n=8",
            [] { test_truncated_binary_coder( 7, 8 ); } },

    } },

void test_elias_gamma_coder( test_type value ) {
    container c;
    {
        auto writer = make_bit_writer( c );
        integer_codes::elias_gamma::encode( value, writer );
    }
    auto reader = make_bit_reader( c );
    auto decoded = integer_codes::elias_gamma::decode<test_type>( reader );
    ASSERT( decoded == value );
}

```

```

toy_test::test_suite elias_gamma_suite
= {"Test_for_elias_gamma_coder",
  {
    {"throws_an_exception_for_x=0",
     [] {
       container c;
       auto writer = make_bit_writer( c );
       THROWS( integer_codes::elias_gamma::encode<test_type>( 0, writer ),
               std::invalid_argument );
     }},
    {"encodes_a_value_of_2", [] { test_elias_gamma_coder( 2 ); }},
    {"encodes_a_value_of_3", [] { test_elias_gamma_coder( 3 ); }},
  }
};

void test_elias_delta_coder( test_type value ) {
  container c;
  {
    auto writer = make_bit_writer( c );
    integer_codes::elias_delta::encode( value, writer );
  }
  auto reader = make_bit_reader( c );
  auto decoded = integer_codes::elias_delta::decode<test_type>( reader );
  ASSERT( decoded == value );
}

toy_test::test_suite elias_delta_suite
= {"Test_for_elias_delta_coder",
  {
    {"throws_an_exception_for_x=0",
     [] {
       container c;
       auto writer = make_bit_writer( c );
       THROWS( integer_codes::elias_delta::encode<test_type>( 0, writer ),
               std::invalid_argument );
     }},
    {"encodes_a_value_of_1", [] { test_elias_delta_coder( 1 ); }},
    {"encodes_a_value_of_3", [] { test_elias_delta_coder( 3 ); }},
  }
};

void test_golomb( test_type x, test_type b ) {
  container c;
  {
    auto writer = make_bit_writer( c );
    integer_codes::golomb::encode( x, b, writer );
  }
  auto reader = make_bit_reader( c );
  auto result = integer_codes::golomb::template decode<test_type>( b, reader );
  ASSERT( result == x );
}

toy_test::test_suite golomb_suite
= {"Test_for_golomb_coder",
  {
    {"encode_throws_an_exception_for_x=0",
     [] {
       container c;

```

```

        auto writer = make_bit_writer( c );
        THROWS( integer_codes::golomb::encode<test_type>( 0, 5, writer ),
            std::invalid_argument );
    }},

{"encode_throws_an_exception_for_b=0",
 [] {
     container c;
     auto writer = make_bit_writer( c );
     THROWS( integer_codes::golomb::encode<test_type>( 5, 0, writer ),
         std::invalid_argument );
 }},

{"decode_throws_an_exception_for_b=0",
 [] {
     container c( 100 );
     auto reader = make_bit_reader( c );
     THROWS( integer_codes::golomb::decode<test_type>( 0, reader ),
         std::invalid_argument );
 }},

{"encodes_and_decodes_small_integers",
 [] {
     for ( test_type i = 1; i < 256; i++ ) {
         for ( test_type b = 1; b < 256; b++ ) {
             test_golomb( i, b );
         }
     }
 }},
}};

void test_rice( test_type x, test_type b ) {
    container c;
    {
        auto writer = make_bit_writer( c );
        integer_codes::rice::encode( x, b, writer );
    }
    auto reader = make_bit_reader( c );
    auto result = integer_codes::rice::template decode<test_type>( b, reader );
    ASSERT( result == x );
}

toy_test::test_suite rice_suite
= {"Test_for_rice_coder",
 {
     {"throws_an_exception_for_x=0",
      [] {
          container c( 100 );
          auto writer = make_bit_writer( c );
          THROWS( integer_codes::rice::encode<test_type>( 0, 4, writer ),
              std::invalid_argument );
      }},

{"encodes_and_decodes_small_integers",
 [] {
     for ( test_type i = 1; i < 256; i++ ) {
         for ( test_type k = 0; k < 16; k++ ) {

```

```

        test_rice( i, k );
    }
}
}},
}};

int main() {
    toy_test::run_suites( {bit_reader_suite, bit_writer_suite, unary_suite,
                           truncated_binary_suite, elias_gamma_suite,
                           elias_delta_suite, golomb_suite, rice_suite} );
}

```



## 5 test/testing.hpp

```
/*
 * Toy Test - Toy Unit Testing
 * Written in 2018 by Gerald Lewis <lewisgdljr@gmail.com>
 *
 * To the extent possible under law, the author(s) have dedicated all copyright
 * and related and neighboring rights to this software to the public domain
 * worldwide. This software is distributed without any warranty.
 * You should have received a copy of the CC0 Public Domain Dedication along
 * with this software. If not, see
 * <http://creativecommons.org/publicdomain/zero/1.0/>.
 */

#pragma once
#ifndef TESTING_HPP_INCLUDED
#define TESTING_HPP_INCLUDED

#include <functional>
#include <initializer_list>
#include <iostream>
#include <vector>

namespace toy_test {
    struct test_case {
        const char*      name;
        std::function<void()> run;
        void              operator()() const { run(); }
    };

    struct failure {
        const char* expr;
        int         line;
    };

    struct test_suite {
        const char*      name;
        std::vector<test_case> tests;

        bool run() const {
            bool ok{true};
            std::cout << "[SUITE] Running test suite: " << name << "\n"
                      << std::endl
                      << std::endl;
            for ( auto&& test : tests ) {
                try {
                    test();
                    std::cout << "[OK.] " << test.name << "\n passed."
                              << std::endl;
                } catch ( failure& caught ) {
                    ok = false;
                    std::cout << "[FAIL!] " << test.name << "\n failed."
                              << std::endl;
                    std::cout << "Failing condition: " << caught.expr
                              << "\n at line: " << caught.line << std::endl;
                }
            }
            return ok;
        }
    };
}
```

```

        if ( ok ) {
            std::cout << std::endl
                << "[OK] All tests passed for suite: \"" << name << "\""
                << std::endl;
        } else {
            std::cout << std::endl
                << "[FAIL!] Test failures detected in suite: \"" << name
                << "\"" << std::endl;
        }
        return ok;
    }
};

bool run_suite( test_suite const& suite ) { return suite.run(); }

bool run_suites( std::initializer_list<test_suite const> const suites ) {
    bool ok = true;
    for ( auto const& a : suites ) {
        ok &= run_suite( std::forward<test_suite const>( a ) );
    }

    if ( ok ) {
        std::cout << std::endl
            << "[OK] All tests passed." << std::endl
            << std::endl;
    } else {
        std::cout << std::endl
            << "[FAIL!] Test failures detected." << std::endl
            << "Check the output for details." << std::endl
            << std::endl;
    }
    return ok;
}

#define ASSERT( condition ) \
    void( ( condition ) ? 0 \
        : throw toy_test::failure( \
            {"ASSERT(" #condition ")", __LINE__} ) )

#define THROWS( expression, exception ) \
    try { \
        ( expression ); \
        throw toy_test::failure( \
            {"THROWS(" #expression ", " #exception ")", __LINE__} ); \
    } catch ( exception& ) { \
    } catch ( ... ) { \
        throw toy_test::failure( \
            {"THROWS(" #expression ", " #exception ")", __LINE__} ); \
    }
} // namespace toy_test
#endif // TESTING_HPP_INCLUDED

```