

Alfred

C-2 创建: 张林伟, 最后修改: 张林伟 2018-08-03 13:57

打开Alfred热键: alt+space

find+space+"文件名": 定位文件

open+space+"文件名": 定位并打开文件

安装workflow: 双击.workflow文件

alfred+dash

通过dash的integration快捷创建alfred和dash的workflow

dash print 或者 dash python3:print

改终端为iterm

将 Terminal 的 Application 改变为 Custom

^ 点击展开内容

^ 代码块

Plain Text

```
1 on write_to_file(this_data, target_file, append_data)
2     try
3         set the target_file to the target_file as string
4         set the open_target_file to open for access file target_file with write permission
5         if append_data is false then set eof of the open_target_file to 0
6         write this_data to the open_target_file starting at eof
7         close access the open_target_file
8         return true
9     on error
10        try
11            close access file target_file
12        end try
13        return false
14    end try
15 end write_to_file
16
17
18 on alfred_script(q)
19
20    -- Write the command to run to a file. This is done because Applescript quoting is impossible to get right, es
    backslashes.
21    set tmp_dir to path to temporary items as string from user domain
22    set applescript_alfred_file to tmp_dir & "alfredscript"
23    set alfred_file to POSIX path of applescript_alfred_file
24    write_to_file(q & return, applescript_alfred_file, false)
25
26    -- Create this file, which prevents iTerm2 from restoring a saved window arrangement.
27    do shell script "touch ~/Library/Application' Support/iTerm/quiet'"
28
29    -- Test cases:
30    -- 1. iTerm2 running, has windows open. Should open a new window for Alfred command.
31    -- 2. iTerm2 running, no windows open. Should open a new window for Alfred command.
32    -- 3. iTerm2 not running, set to restores arrangement. Should not restore arrangement but open a new window fo
    Alfred command.
33    -- 4. iTerm2 not running. No windows to restore. Should open a single window for the Alfred command.
34    -- 5. iTerm2 not running. Has windows to restore. Restores windows and then opens a new window for the Alfred
    command.
35
36    -- Compose a script. This is necessary because compiling in a 'tell application' command causes the app to be
    launched, which would happen prior to the creation of the quiet file.
37    set theScript to "tell application \"iTerm2.app\"
38    if (exists current window) then
```

```
39     tell current window to create tab with default profile
40     tell current session of current window
41         write contents of file "\"" & alfred_file & "\""
42     end tell
43 else
44     create window with default profile
45     tell current session of current window
46         write contents of file "\"" & alfred_file & "\""
47     end tell
48 end if
49 activate
50 end tell"
51
52 -- Invoke the script.
53 run script theScript
54
55 -- Clean up
56 -- do shell script "rm -f ~/Library/Application' Support/iTerm/quiet' /tmp/alfredscript"
57 end alfred_script
```

仅供内部使用，未经授权，切勿外传