


Announcements

- ❑ Quiz is due tonight
- ❑ Homework
 - HW5 is out. Due on November 16
- ❑ Project
 - Project 3 is due next Sunday at noon.
 - The new project will be next week
 - If you have a partner, both of need to submit your projects to Blackboard

CS 3568: Intelligent Systems

Hidden Markov Models (part 2)



Instructor: Tara Salman

Texas Tech University

Computer Science Department


[These slides were created by Dan Klein and Pieter Abbeel for CS188 Intro to AI at UC Berkeley (ai.berkeley.edu).]

Texas Tech University

Tara Salman

Markov Models


- Value of X at a given time is called the **state**



$$P(X_1) \quad P(X_t | X_{t-1})$$

- Parameters: called **transition probabilities** or dynamics, specify how the state evolves over time (also, initial state probabilities)
- Stationarity assumption: transition probabilities the same at all times
- Same as MDP transition model, but no choice of action

Conditional Independence



- Basic conditional independence:
 - Past and future independent given the present
 - Each time step only depends on the previous
 - This is called the (first order) Markov property

- Note that the chain is just a (growable) BN
 - We can always use generic BN reasoning on it if we truncate the chain at a fixed length


Example Markov Chain: Weather

- States: $X = \{\text{rain}, \text{sun}\}$



- Initial distribution: 1.0 sun

- CPT $P(X_t | X_{t-1})$:

X_{t-1}	X_t	$P(X_t X_{t-1})$
sun	sun	0.9
sun	rain	0.1
rain	sun	0.3
rain	rain	0.7




Two new ways of representing the same CPT



Mini-Forward Algorithm


- Question: What's $P(X)$ on some day t ?



$P(x_1) = \text{known}$

$$\begin{aligned} P(x_t) &= \sum_{x_{t-1}} P(x_{t-1}, x_t) \\ &= \sum_{x_{t-1}} P(x_t \mid x_{t-1}) P(x_{t-1}) \end{aligned}$$

Forward simulation



Example Run of Mini-Forward Algorithm

- From initial observation of sun

$$\begin{array}{ccccc} \left\langle \begin{matrix} 1.0 \\ 0.0 \end{matrix} \right\rangle & \left\langle \begin{matrix} 0.9 \\ 0.1 \end{matrix} \right\rangle & \left\langle \begin{matrix} 0.84 \\ 0.16 \end{matrix} \right\rangle & \left\langle \begin{matrix} 0.804 \\ 0.196 \end{matrix} \right\rangle & \xrightarrow{\hspace{1cm}} \left\langle \begin{matrix} 0.75 \\ 0.25 \end{matrix} \right\rangle \\ P(X_1) & P(X_2) & P(X_3) & P(X_4) & P(X_\infty) \end{array}$$

- From initial observation of rain

$$\begin{array}{ccccc} \left\langle \begin{matrix} 0.0 \\ 1.0 \end{matrix} \right\rangle & \left\langle \begin{matrix} 0.3 \\ 0.7 \end{matrix} \right\rangle & \left\langle \begin{matrix} 0.48 \\ 0.52 \end{matrix} \right\rangle & \left\langle \begin{matrix} 0.588 \\ 0.412 \end{matrix} \right\rangle & \xrightarrow{\hspace{1cm}} \left\langle \begin{matrix} 0.75 \\ 0.25 \end{matrix} \right\rangle \\ P(X_1) & P(X_2) & P(X_3) & P(X_4) & P(X_\infty) \end{array}$$

- From yet another initial distribution $P(X_1)$:

$$\begin{array}{ccc} \left\langle \begin{matrix} p \\ 1 - p \end{matrix} \right\rangle & \dots & \xrightarrow{\hspace{1cm}} \left\langle \begin{matrix} 0.75 \\ 0.25 \end{matrix} \right\rangle \\ P(X_1) & & P(X_\infty) \end{array}$$

Video of Demo Ghostbusters Basic Dynamics



Video of Demo Ghostbusters Circular Dynamics



Stationary Distributions

- For most chains:

- Influence of the initial distribution gets less and less over time.
- The distribution we end up in is independent of the initial distribution

- Stationary distribution:

- The distribution we end up with is called the **stationary distribution** P_∞ of the chain


- It satisfies

$$P_\infty(X) = P_{\infty+1}(X) = \sum_x P(X|x)P_\infty(x)$$



Example: Stationary Distributions

- Question: What's $P(X)$ at time $t = \text{infinity}$?



$$P_{\infty}(\text{sun}) = P(\text{sun}|\text{sun})P_{\infty}(\text{sun}) + P(\text{sun}|\text{rain})P_{\infty}(\text{rain})$$

$$P_{\infty}(\text{rain}) = P(\text{rain}|\text{sun})P_{\infty}(\text{sun}) + P(\text{rain}|\text{rain})P_{\infty}(\text{rain})$$


$$P_{\infty}(\text{sun}) = 0.9P_{\infty}(\text{sun}) + 0.3P_{\infty}(\text{rain})$$

$$P_{\infty}(\text{rain}) = 0.1P_{\infty}(\text{sun}) + 0.7P_{\infty}(\text{rain})$$

$$P_{\infty}(\text{sun}) = 3P_{\infty}(\text{rain})$$


$$P_{\infty}(\text{rain}) = 1/3P_{\infty}(\text{sun})$$

Also: $P_{\infty}(\text{sun}) + P_{\infty}(\text{rain}) = 1$



$$P_{\infty}(\text{sun}) = 3/4$$

$$P_{\infty}(\text{rain}) = 1/4$$




X_{t-1}	X_t	$P(X_t X_{t-1})$
sun	sun	0.9
sun	rain	0.1
rain	sun	0.3
rain	rain	0.7

Application of Stationary Distribution: Web Link Analysis

- PageRank over a web graph
 - Each web page is a state
 - Initial distribution: uniform over pages
 - Transitions:
 - With prob. c , uniform jump to a random page (dotted lines, not all shown)
 - With prob. $1-c$, follow a random outlink (solid lines)

- Stationary distribution
 - Will spend more time on highly reachable pages
 - E.g. many ways to get to the Acrobat Reader download page
 - Somewhat robust to link spam
 - Google 1.0 returned the set of pages containing all your keywords in decreasing rank, now all search engines use link analysis along with many other factors (rank actually getting less important over time)




Hidden Markov Models




Hidden Markov Models

- ❑ Markov chains not so useful for most agents
 - Need observations to update your beliefs
- ❑ Hidden Markov models (HMMs)
 - Underlying Markov chain over states X
 - You observe outputs (effects) at each time step



Example: Weather HMM





- An HMM is defined by:
 - Initial distribution: $P(X_1)$
 - Transitions: $P(X_t | X_{t-1})$
 - Emissions: $P(E_t | X_t)$

R _{t-1}	R _t	P(R _t R _{t-1})
+r	+r	0.7
+r	-r	0.3
-r	+r	0.3
-r	-r	0.7

R _t	U _t	P(U _t R _t)
+r	+u	0.9
+r	-u	0.1
-r	+u	0.2
-r	-u	0.8


Example: Ghostbusters HMM

- $P(X_1) = \text{uniform}$
- $P(X|X')$ = usually move clockwise, but sometimes move in a random direction or stay in place
- $P(R_{ij}|X)$ = same sensor model as before: red means close, green means far away.



1/9	1/9	1/9
1/9	1/9	1/9
1/9	1/9	1/9

$P(X_1)$




1/6	1/6	1/2
0	1/6	0
0	0	0

$P(X|X'=<1,2>)$

Conditional Independence

- HMMs have two important independence properties:
 - Markov hidden process: future depends on past via the present
 - Current observation independent of all else given current state



- Quiz: does this mean that evidence variables are guaranteed to be independent?
 - [No, they tend to correlate by the hidden state]

Real HMM Examples


- ❑ Speech recognition HMMs:
 - Observations are acoustic signals (continuous valued)
 - States are specific positions in specific words (so, tens of thousands)
- ❑ Machine translation HMMs:
 - Observations are words (tens of thousands)
 - States are translation options
- ❑ Robot tracking:
 - Observations are range readings (continuous)
 - States are positions on a map (continuous)

Filtering / Monitoring

- ❑ Filtering, or monitoring, is the task of tracking the distribution $B_t(X) = P_t(X_t | e_1, \dots, e_t)$ (the belief state) over time
- ❑ We start with $B_1(X)$ in an initial setting, usually uniform
- ❑ As time passes, or we get observations, we update $B(X)$

Example: Robot Localization


Example from
Michael Pfeiffer




t=0

Sensor model: can read in which directions there is a wall,
never more than 1 mistake


Motion model: may not execute action with small prob.





Example: Robot Localization





Lighter grey: was possible to get the reading, but less likely b/c required 1 mistake





Example: Robot Localization





Example: Robot Localization






Example: Robot Localization



Example: Robot Localization



Inference: Base Cases



$$P(X_1|e_1)$$

$$\begin{aligned} P(x_1|e_1) &= P(x_1, e_1)/P(e_1) \\ &\propto_{X_1} P(x_1, e_1) \\ &= P(x_1)P(e_1|x_1) \end{aligned}$$


$$P(X_2)$$

$$\begin{aligned} P(x_2) &= \sum_{x_1} P(x_1, x_2) \\ &= \sum_{x_1} P(x_1)P(x_2|x_1) \end{aligned}$$

Passage of Time

- Assume we have current belief $P(X \mid \text{evidence to date})$

$$B(X_t) = P(X_t | e_{1:t})$$



- Then, after one time step passes:

$$\begin{aligned} P(X_{t+1} | e_{1:t}) &= \sum_{x_t} P(X_{t+1}, x_t | e_{1:t}) \\ &= \sum_{x_t} P(X_{t+1} | x_t, e_{1:t}) P(x_t | e_{1:t}) \\ &= \sum_{x_t} P(X_{t+1} | x_t) P(x_t | e_{1:t}) \end{aligned}$$

■ Or compactly:

$$B'(X_{t+1}) = \sum_{x_t} P(X' | x_t) B(x_t)$$

- Basic idea: beliefs get “pushed” through the transitions


- With the “B” notation, we have to be careful about what time step t the belief is about, and what evidence it includes

Example: Passage of Time

- As time passes, uncertainty “accumulates”


<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
<0.01	<0.01	1.00	<0.01	<0.01	<0.01
<0.01	<0.01	<0.01	<0.01	<0.01	<0.01

T = 1



<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
<0.01	<0.01	0.06	<0.01	<0.01	<0.01
<0.01	0.76	0.06	0.06	<0.01	<0.01
<0.01	<0.01	0.06	<0.01	<0.01	<0.01

T = 2



(Transition model: ghosts usually go clockwise)

0.05	0.01	0.05	<0.01	<0.01	<0.01
0.02	0.14	0.11	0.35	<0.01	<0.01
0.07	0.03	0.05	<0.01	0.03	<0.01
0.03	0.03	<0.01	<0.01	<0.01	<0.01

T = 5



Observation

- Assume we have current belief $P(X \mid \text{previous evidence})$:

$$B'(X_{t+1}) = P(X_{t+1} | e_{1:t})$$

- Then, after evidence comes in:

$$P(X_{t+1} | e_{1:t+1}) = P(X_{t+1}, e_{t+1} | e_{1:t}) / P(e_{t+1} | e_{1:t})$$


$$\propto_{X_{t+1}} P(X_{t+1}, e_{t+1} | e_{1:t})$$

$$= P(e_{t+1} | e_{1:t}, X_{t+1}) B'(X_{t+1} | e_{1:t})$$

$$= P(e_{t+1} | X_{t+1}) B'(X_{t+1} | e_{1:t})$$

- Or, compactly:

$$B(X_{t+1}) \propto_{X_{t+1}} P(e_{t+1} | X_{t+1}) B'(X_{t+1})$$



- Basic idea: beliefs “reweighted” by likelihood of evidence
- Unlike passage of time, we have to renormalize

Example: Observation

- As we get observations, beliefs get reweighted, uncertainty “decreases”

0.05	0.01	0.05	<0.01	<0.01	<0.01
0.02	0.14	0.11	0.35	<0.01	<0.01
0.07	0.03	0.05	<0.01	0.03	<0.01
0.03	0.03	<0.01	<0.01	<0.01	<0.01


Before observation

<0.01	<0.01	<0.01	<0.01	0.02	<0.01
<0.01	<0.01	<0.01	0.83	0.02	<0.01
<0.01	<0.01	0.11	<0.01	<0.01	<0.01
<0.01	<0.01	<0.01	<0.01	<0.01	<0.01



After observation



$$B(X) \propto P(e|X)B'(X)$$



Example: Weather HMM



R_t	R_{t+1}	$P(R_{t+1} R_t)$
+r	+r	0.7
+r	-r	0.3
-r	+r	0.3
-r	-r	0.7

R_t	U_t	$P(U_t R_t)$
+r	+u	0.9
+r	-u	0.1
-r	+u	0.2
-r	-u	0.8

The Forward Algorithm

- We are given evidence at each time and want to know

$$B_t(X) = P(X_t|e_{1:t})$$

- We can derive the following updates

$$P(x_t|e_{1:t}) \propto_X P(x_t, e_{1:t})$$

$$= \sum_{x_{t-1}} P(x_{t-1}, x_t, e_{1:t})$$

$$= \sum_{x_{t-1}} P(x_{t-1}, e_{1:t-1}) P(x_t|x_{t-1}) P(e_t|x_t)$$

$$= P(e_t|x_t) \sum_{x_{t-1}} P(x_t|x_{t-1}) P(x_{t-1}, e_{1:t-1})$$

We can normalize as we go if we want to have $P(x|e)$ at each time step, or just once at the end...

Online Belief Updates


- ❑ Every time step, we start with current $P(X \mid \text{evidence})$
- ❑ We update for time:

$$P(x_t | e_{1:t-1}) = \sum_{x_{t-1}} P(x_{t-1} | e_{1:t-1}) \cdot P(x_t | x_{t-1})$$

- ❑ We update for evidence:

$$P(x_t | e_{1:t}) \propto_X P(x_t | e_{1:t-1}) \cdot P(e_t | x_t)$$

- ❑ The forward algorithm does both at once (and doesn't normalize)



Pacman – Sonar (P4)

