

1. Given a MoviesList component, which of the following options allows <movies-list v-bind:movies="listOfMovies">?

Parent component has the <movies-list v-bind:movies="listOfMovies">

prop called movies

Show Results

28/28 Students Answered

- A `export default {  
 name: 'movies-list',  
 data() {  
 return {  
 movies: []  
 }  
 }  
}` X
- B `export default {  
 name: 'movies-list',  
 computed: {  
 movies() {  
 return [];  
 }  
 }  
}` X
- C `export default {  
 name: 'movies-list',  
 input() {  
 return {  
 movies: []  
 }  
 }  
}` X
- D `export default {  
 name: 'movies-list',  
 props: ['movies']  
}` ← ✓

2. Given a MoviesList component, which of the following options allows <movies-list search="Club">?

Show Results

28/28 Students Answered

- A `export default {  
 name: 'movies-list',  
 data() {  
 return {  
 movies: [],  
 search: ""  
 }  
 }  
}` X
- B `export default {  
 name: 'movies-list',  
 computed: {  
 movies() {  
 return [];  
 }  
 },  
 data() {  
 return {  
 search: ""  
 }  
 }  
}` X
- C `export default {  
 name: 'movies-list',  
 input() {  
 return {  
 movies: [],  
 search: ""  
 }  
 }  
}` X
- D `export default {  
 name: 'movies-list',  
 data() {  
 return {  
 movies: []  
 }  
 }  
 props: ['search']  
}` ←

In this child component, the variable search will hold "Club"

4. Given MoviesList.vue, as declared below, which of the following do you need to do to add it into another component? (select all that apply):

```
export default {  
  name: 'movies-list'  
}
```

Show Results

28/28 Students Answered

- A `<script>  
import MoviesList from './components/MoviesList.vue';  
</script>` ← 2.
- B `<script>  
export default {  
 components: {  
 MoviesList  
 }  
};  
</script>` ← 3.
- C `<template>  
<Movies></Movies>  
</template>` X
- D `<script>  
import default {  
 modules: [  
 './MoviesList.vue'  
 ]  
};  
</script>` X
- E `<template>  
<movies-list></movies-list>  
</template>` ← 1.

5. Given the component below, how would you pass an object named productReviews into it from a parent component?

```
<template>
<div v-for="review in reviews" v-bind:key="review.id"></div>
</template>
```

```
<script>
export default {
  name: 'book-reviews',
  props: ['reviews'],
};
</script>
```

reviews in the child, but was called productReviews in the parent

Show Results

27/28 Students Answered


- A <book-reviews v-prop="productReviews"></book-reviews> 
- B <product-reviews v-bind:prop="book-reviews"></product-reviews> 
- C <book-reviews v-bind:reviews="productReviews"></book-reviews> 
- D <product-reviews v-prop="book-reviews"></product-reviews> 

i Show explanation 

7. How do you call a mutation called ADD\_REVIEW?

Show Results

27/28 Students Answered

- A this.\$store.ADD\_REVIEW();
- B this.\$store.commit('ADD\_REVIEW'); 
- C this.\$store.mutation('ADD\_REVIEW');
- D this.\$store.mutation.ADD\_REVIEW();
- E this.\$store.trigger('ADD\_REVIEW');

i Show explanation 