

Binary tree traversal

```
Subalg. onLevels(T)
  initEmpty (q)
  if not isEmpty (T) then
    enqueue(q, rootPos (T))
  endif
  while (not isEmpty(q)) do
    p := dequeue(q)
    @ process p^.info
    if (p^.left <> NIL) then
      enqueue( q, p^.left)
    endif
    if ( p^.right <> NIL) then
      dequeue( q, p^.right)
    endif
  endwhile
endWhile
endOnLevels
```

Binary tree traversal

Pre-order:

root, left-subtree, right-subtree

1. Visit the node.
2. Traverse the left subtree.
3. Traverse the right subtree.

Post-order:

left-subtree, right-subtree, root

1. Traverse the left subtree.
2. Traverse the right subtree.
3. Visit the node.

In-order:

left-subtree, root, right-subtree

1. Traverse the left subtree.
2. Visit the node.
3. Traverse the right subtree.

Binary tree parsing

Preorder

→ use stack

Subalg. preorder(p)

if $p \neq \text{NIL}$ then

 @ process $p^{\wedge}.\text{info}$

 preorder($p^{\wedge}.\text{left}$)

 preorder($p^{\wedge}.\text{right}$)

endif

endPreorder

```

Subalg. iterativePreorder(T) .
  initEmpty(s)
  if (not isEmpty(T)) then
    push(s,rootPos(T))
  endif
  while not isEmpty(s) do
    p := pop(s)
    @process p^.info
    if p^.right <>NIL then      push(s, p^.right)      endif
    if p^.left  <>NIL then      push(s, p^.left)       endif
  endwhile
end_iterativePreorder

```

Subalg. iterativeInorder(T)

▪

initEmpty (s)

p := rootPos(T)

while not (isEmpty(s) and p=NIL) do

 while (p <> NIL) do

 push(s,p)

 p := p^.left

 endwhile

 p := pop(s)

 @ process p^.info

 p:=p^.right

endWhile

end_iterativeInorder

Subalg. iterativeinorder(T)

```
initEmpty (s)
p := rootPos(T)
while not ( isEmpty(s))
  and p=NIL ) do
  while (p <> NIL) do
    push(s,p)
    p := p^.left
  endwhile
  p := pop(s)
  @ process p^.info
  p:=p^.right
endWhile
```

end_iterativeInorder

Subalg. iterativeinorder2(T)

```
▪ initEmpty (s)
  p := rootPos(T)
  while not ( isEmpty(s)) and
    p=NIL ) do
    if (p <> NIL) then
      push(s,p)
      p := p^.left
    else
      p := pop(s)
      @ process p^.info
      p:=p^.right
    endif
  endwhile
endWhile
```

end_iterativeInorder2

Subalg. iterativePostorder(T)

//use a flag: left subtree *visited*

initEmpty(s)

p:= rootPos(T) ■

while not (isEmpty(s) and p=NIL) do

 while p<>NIL do

//Traverse downwards to left

 push(s,[p,0])

 p:=p^.left

 endwhile

 [p,k]:=pop(s)

 if k=0 then

//upwards from left

 push(s,[p,1])

 p:=p^.right

 else

// upwards from right

 @ process p^.info

 p := NIL

 endif

endwhile

End_iterativePostorder

```

initEmpty(s)
pNode = NIL
cNode = rootPos(T)
while not ( isEmpty(s) and cNode = NIL)
  if parent(pNode,cNode) then    //Traverse downwards
    if (cNode^.left <>NIL) then    //More traversing to do
      push(s,cNode)
      pNode = cNode
      cNode = cNode^.left
    else if (cNode^.right <>NIL) then
      push(s,cNode)
      pNode = cNode
      cNode = cNode^.right
    else    //cNode does not have descendants: go upward
      @ process cNode^.info
      pNode = cNode
      cNode = peek(s)
    endif
  endif
endif
endif

```



```
initEmpty(s)
pNode = NIL
cNode = rootPos(T)
while not ( isEmpty(s) and cNode = NIL)
  if parent(pNode,cNode) then    //Traverse downwards
    if (cNode^.left <>NIL) then    //More traversing to do
      push(s,cNode)
      pNode = cNode
      cNode = cNode^.left
    else if (cNode^.right <>NIL) then
      push(s,cNode)
      pNode = cNode
      cNode = cNode^.right
    else    //cNode does not have descendants: go upward
      @ process cNode^.info
      pNode = cNode
      cNode = peek(s)
    endif
  endif
endif
endif
```

//continuation of iterativePostorder2(a) version 2

else //cNode is parent of pNode; traverse upwards

if (cNode^.left = pNode) and (cNode^.right <>NIL) then

//upwards from left;

//go right if possible; then downwards

pNode = cNode

cNode = cNode^.right

else // upwards from right; process & go upward

@process cNode

pop(s) //!!!

pNode = cNode

cNode = peek(s)

endif

endif

endwhile

end_iterativePostOrder2

Remark:

Define peek to return NIL if stack is empty

Binary tree examples

