
Release Notes

Three artifacts are versioned separately:

- **CLI:** `quay.io/lee_forster/mas-external-services-tool`
- **SCIM bridge:** `quay.io/lee_forster/mas-iam-scim-bridge`
- **Operator:** `quay.io/lee_forster/mas-iam-operator`, plus its `catalog-*` image

Each entry lists which versions it ships with.

v0.1.11

CLI v0.1.11 · bridge scim-bridge-v0.1.2 · operator 0.0.15

- **Fixed:** on OpenShift Data Foundation clusters, preflight recommended the `localblock` storage class, which can't provision new volumes. Accepting the default left every PVC Pending, and the install failed with deployment "mas-est-iam-openldap" exceeded its progress deadline. Preflight now never recommends a class with provisioner `kubernetes.io/no-provisioner`, and prefers the Ceph RBD class.

v0.1.10

CLI v0.1.10 · bridge scim-bridge-v0.1.2 · operator 0.0.15

- **Fixed:** an in-cluster install with MAS auth but without the SCIM component ignored `--workspace-id`, so self-registered users landed in a workspace named `workspace` and couldn't open Manage. The Job now receives the workspace, interactive installs ask for it when auth is chosen without SCIM, and non-interactive installs require it.
- **Fixed:** `mas-est ldap-info` listed four LDAP users that don't exist (`alex.manager`, `jane.doe`, `joe.bloggs`, `sysadmin`). Only `ldap.user1` and `ldap.user2` are seeded. Existing installs keep the stale names until the next `mas-est install`.
- New docs: `docs/ANNOUNCEMENT.md`, `docs/TROUBLESHOOTING.md` and `docs/KNOWN-LIMITATIONS.md`; `docs/GUIDE.md` is now task-only.

v0.1.9

CLI v0.1.9 · bridge scim-bridge-v0.1.2 · operator 0.0.15

- **Fixed:** the upgrade command in v0.1.8's version-check error left out `bootstrap --force`, so it failed for anyone who already had a runtime. The error message and all documented bootstrap commands now include `--force`. It's also safe on a first install.

v0.1.8

CLI v0.1.8 · bridge scim-bridge-v0.1.2 · operator 0.0.15

- `install` prints `[version] mas-est vX.Y.Z` first.
- `install` fails if `MAS_EST_IMAGE` names a different version than the extracted CLI, because exporting a new image doesn't replace the binary and an old binary applies old installer permissions. `--skip-version-check` bypasses it. `mas-est version` now shows when the runtime was extracted.

v0.1.7

CLI v0.1.7 · bridge scim-bridge-v0.1.2 · operator 0.0.15

- **Fixed:** on a MAS instance with no SCIM profile yet, some SCIM users were created before the profile existed. They got no entitlement, never appeared in Manage, and MAS still reported sync SUCCESS. The install now creates the profile before it starts the SCIM bridge. Reinstalls were never affected.

v0.1.6

CLI v0.1.6 · bridge scim-bridge-v0.1.2 · operator 0.0.15

- **Fixed:** installs with S3 or SMTP failed creating Routes (spec.host: Forbidden). The installer Job now has the routes/custom-host permission.

v0.1.5

CLI v0.1.5 · bridge scim-bridge-v0.1.2 · operator 0.0.15

- **Fixed:** installs with S3 or SMTP failed reading the cluster's default IngressController. The installer Job can now read it.

v0.1.4

CLI v0.1.4 · bridge scim-bridge-v0.1.2 · operator 0.0.15

- **Change:** install now runs as a Kubernetes Job in the cluster by default, so a closed laptop or dropped VPN doesn't kill it. Use `--local` for the old behaviour.
- **Fixed:** the OpenLDAP PVC ignored `--storage-class` and hung on clusters with no default StorageClass.
- Preflight warns when the install would overwrite existing MAS providers with the default ID.

Operator 0.0.15

- **Fixed:** the MasIamStack went Irreconcilable (PASSWORDS ERROR) straight after every install, so later changes were never applied. It was caused by the Bitnami PostgreSQL chart's password check under helm-operator. Don't set `spec.postgresql.auth.password: ""` in the CR, as that brings the failure back.

v0.1.3

CLI v0.1.3 · bridge scim-bridge-v0.1.2

- SCIM users are linked to SAML when OIDC isn't configured, for example on MAS 9.0.
- New preflight checks:
 - `mas-oidc-endpoint` fails early on MAS 9.0, which has no OIDC.
 - `mas-api-key` fails early when the key lacks `userAdmin` and `systemAdmin`.
- The SCIM bridge syncs users by Keycloak group (SCIM_BRIDGE_INCLUDE_GROUPS, default `mas-scim-users`) as well as the username prefix, removing the 50-user limit.
- Users removed from the group are deactivated in MAS, and reactivated if added back. This is experimental.

v0.1.2

- Preflight finds MAS API routes the same way `install` does, and pre-fills the SCIM URL.

v0.1.1

- **Fixed:** deselecting options in the interactive install prompts had no effect. For example, OIDC stayed selected, which broke installs on MAS 9.0.

v0.1.0

First release. Validated end to end on MAS 9.1.19 and 9.1.4:

- Install of all components
- All four login paths (LDAP, OIDC, SAML, SCIM via OIDC)
- Manage sync for every demo user
- `S3 ObjectStorageCfg` reaching Ready