
Troubleshooting

Search this page for the error text you see. Each row gives the cause and the fix.

Bootstrap and upgrade · Preflight · Install · Login · SCIM and Manage sync · S3 and doclinks

<instance> is your MAS instance ID and <workspace> the MAS workspace ID.

Bootstrap and upgrade

Error	Cause	Fix
/tmp/mas-est already exists; rerun with --force to overwrite	A runtime is already extracted	Add bootstrap --force after the image name.
mas-est: command not found	The extracted directory isn't on your PATH	export PATH="\$HOME/mas-est:\$PATH"
stale local runtime detected	MAS_EST_IMAGE names a different version than the extracted binary	mas-est update --version <tag>, or re-run the bootstrap podman run line. Then mas-est version. If you just ran mas-est update, export the new MAS_EST_IMAGE it printed.
warning: MAS_EST_IMAGE requests <tag> but this binary is v<version> from mas-est version	Same as above	Same as above.
unknown command "update"	CLI v0.1.13 or earlier, which has no update	Re-run the bootstrap podman run line with the new tag once. update works from then on.
look up the newest release from mas-est update	Quay isn't reachable from your machine (offline, proxy)	mas-est update --version vX.Y.Z skips the lookup.
mas-est update only works from a bootstrapped mas-est	The binary wasn't started through the ~/mas-est/mas-est launcher	Run the mas-est from your bootstrap directory, or re-run bootstrap.
mas-est update needs podman or docker on PATH	No container engine found	Install podman, or pass --engine <path>. On macOS, also podman machine start.

Preflight

Check names appear as [error] <name>: in the output.

Error	Cause	Fix
mas-api-key: MAS API key <name> authenticated but is not authorized for the SCIM API (HTTP 403 AIUC01003E)	The key lacks a permission	Recreate the key with userAdmin and systemAdmin .
mas-api-key: MAS API key <name> failed to authenticate (HTTP 401)	Wrong key name or value	Check both against the key in MAS administration.
mas-oidc-endpoint: MAS at <host> does not expose the OIDC external-IdP API (HTTP 404 AIUC01022E; requires MAS 9.1+)	MAS 9.0	Leave oidc out of the providers.
mas-idpcfg-overwrite: <n> existing IDPCfg(s) in namespace mas-<instance>-core will be OVERWRITTEN in place	MAS already has providers named default	Back them up with <code>oc get idpcfg -n mas-<instance>-core -o yaml</code> , or keep them by installing without those providers.
mas-base-url: MAS base URL must include /scim/v2	URL typo	Use <code>https://api.<instance>.<cluster-domain>/scim/v2</code> .
cluster-login: cluster login check failed; run 'oc login' first	Not logged in	<code>oc login</code> , then retry.

Install

The install log is at `mas-est logs --component install-job`.

Error	Cause	Fix
job/mas-est-install already exists in namespace mas-est and has already finished	A previous Job is still there	<code>oc delete job mas-est-install -n mas-est</code> , then re-run. Interactive installs offer to do this.
--uninstall-first cannot run in the cluster	The Job would delete its own namespace	Run <code>mas-est uninstall</code> first, or add <code>--local</code> .
Forbidden in the install log	The Job's permissions were applied by an older CLI	Re-run bootstrap, delete the Job, re-run install.
[mas-est] FATAL: installer image / CLI skew - refusing to run	The Job image doesn't match the CLI	Delete the Job. Re-run bootstrap so the CLI and its default image match.

Error	Cause	Fix
job/mas-est-install in namespace mas-est produced no logs within 15m0s	The Job pod never started	<code>oc describe job mas-est-install -n mas-est</code> . Look for image pull errors or a Pending pod.
CatalogSource mas-iam-operator did not report READY within 5m	The operator catalog image can't be pulled	<code>oc get catalogsource mas-iam-operator -n openshift-marketplace -o yaml</code> and check the status.
timed out waiting for the condition on jobs/scim-bridge-keycloak-route-cert, and its pod shows ImagePullBackOff for registry.redhat.io/openshift4/ose-cli	CLI v0.1.11 or earlier. Red Hat no longer serves that image untagged.	Upgrade to v0.1.12 or later, then <code>mas-est uninstall</code> and install again.
command terminated with exit code 1 right after Seeding 6 grouped demo users, and the Keycloak log shows Connection refused for LDAP	CLI v0.1.12 or earlier. OpenLDAP was still generating its TLS parameters on first start, which can take several minutes.	Upgrade to v0.1.13 or later, which waits for LDAP. Then <code>mas-est uninstall</code> and install again.
timed out waiting for the MAS EST IAM operator CSV to reach Succeeded deployment	OLM didn't install the operator	<code>oc get csv,sub,installplan -n mas-est</code> . Look for image pull or resolution errors.
"mas-est-iam-openldap" exceeded its progress deadline, or timed out waiting for <kind>/<name> in namespace mas-est, and a PVC is Pending	The chosen storage class can't provision a volume. A class with provisioner kubernetes.io/no-provisioner, such as ODF's localblock, never binds a new PVC.	<code>oc get sc</code> , pick a dynamic block class such as ocs-storagecluster-ceph-rbd, then <code>mas-est uninstall</code> and reinstall with <code>--storage-class</code> and <code>--scim-bridge-storage-class</code> set to it.
timed out waiting 10m0s for <type>/default to become Ready	MAS didn't reconcile the provider	<code>oc get pods -n mas-<instance>-core \</code> <code>grep entitymgr-idpcfg</code> . If it shows OOMKilled, the memory bump didn't apply: check <code>oc get suite <instance> -n mas-<instance>-core -o json-path='{.spec.podTemplates}'</code> .
setOIDCConfig default: ... MAS does not expose the OIDC external-IdP API	MAS 9.0 with oidc selected	Re-run with <code>--mas-auth-providers ldap,saml</code> .

Error	Cause	Fix
[mas-auth] WARN: link-scim-users-oidc step failed (non-fatal)	The install couldn't reach MongoDB to link the SCIM users	Re-run <code>mas-est mas-auth apply --mas-instance-id <instance> --self-reg-workspace <workspace></code> once the install finishes.

Login

Symptom	Cause	Fix
The wrong user is signed in, or AIUOM0100E, after switching provider	Keycloak kept the previous session	Use a private browser window for each login.
First SAML login fails with AIUSC0019I Self Registration configuration either not setup or not enabled	MAS 9.1.20 loads the self-registration config lazily	Log in again. Don't restart <instance>-coreidp; that brings the failure back.
CWIML4537E or "invalid username or password" for a user Keycloak or LDAP accepted	A MongoDB user record left over from an earlier install	Delete that user's document from <code>mas_<instance>_core.User</code> and log in again.
A user logs in but can't open Manage	Self-registration used the wrong workspace	<code>oc get cm <instance>-selfreg -n mas-<instance>-core -o yaml</code> . If workspaces shows workspace, re-run <code>mas-est mas-auth apply --mas-instance-id <instance> --self-reg-workspace <workspace></code> .

SCIM and Manage sync

Start with `mas-est logs --component bridge --tail 300` and `mas-est config view`.

Symptom or log line	Cause	Fix
no users matched filters or no users returned from Keycloak	No user is both in group <code>mas-scim-users</code> and named <code>scim.*</code>	Fix the user in Keycloak. Both conditions apply.
group "mas-scim-users" not found in realm maximo	The group was deleted	Recreate it in Keycloak.

Symptom or log line	Cause	Fix
MAS returned unauthorized; refreshing token and retrying once, repeated	The MAS API key was rotated or revoked	<code>mas-est config set mas-api-token --token-name '<name>' --token-value '<value>'</code>
MAS create failed with <code>status_code=404</code>	Wrong SCIM URL or profile ID	Compare <code>SCIM_BRIDGE_MAS_BASE_URL</code> and <code>SCIM_BRIDGE_MAS_PROFILE_ID</code> in <code>mas-est config view</code> with MAS.
<code>dry-run create</code>	The bridge is in dry-run mode	Set <code>SCIM_BRIDGE_BRIDGE_DRY_RUN</code> to false in <code>configmap/scim-bridge-config</code> , then <code>mas-est restart bridge</code> .
skip update due to prior MAS error	An earlier MAS error is stuck in the bridge's state file	Fix the cause shown in <code>last_error</code> , then <code>mas-est restart bridge</code> .
A SCIM user can't log in, or has only a <code>_local</code> identity in MAS	Created in Keycloak after the install, so never linked	<code>mas-est mas-auth apply --mas-instance-id <instance> --self-reg-workspace <workspace></code>
The user is in MAS but not in Manage, and <code>entitlement.application</code> is <code>NONE</code>	The user was created before the SCIM profile existed. Fixed for new installs in v0.1.7.	Set the user's entitlement and workspace in MAS, then set <code>sync.status</code> to <code>PENDING</code> .
Manage sync fails with <code>AIUI1101E: 500</code>	A leftover <code>MAXIMO.PERSONANCESTOR</code> row	Delete the row for that <code>PERSONID</code> , then set the user's <code>sync.status</code> and <code>applications.manage.sync.state</code> to <code>PENDING</code> .
Manage sync fails with <code>BMXAA10249E ... DEFLTREG security group</code>	A leftover <code>MAXIMO.GROUPUSER</code> row. The message is misleading.	Delete that user's <code>GROUPUSER</code> rows, then set <code>sync.status</code> to <code>PENDING</code> .

S3 and doclinks

Symptom	Cause	Fix
<code>SignatureDoesNotMatch</code> on every attachment	<code>mxe.cosregion</code> isn't set	Add it as <code>us-east-1</code> . See Connect S3 to Manage.
HTTP 503 or a certificate error on upload	<code>mxe.cosendpointuri</code> points at the MinIO route	Set it to <code>http://mas-est.svc.cluster.local:9000</code> .

Symptom	Cause	Fix
BMXAA4195E on upload	Wrong bucket, key or endpoint	Check every property in Connect S3 to Manage.
SignatureDoesNotMatch from the LOADFLATOBJECT cron task while attachments work	That cron task ignores the region	Harmless. Disable the cron task to silence it.
ObjectStorageCfg not Ready	MinIO didn't finish starting	<code>mas-est logs --component minio</code> and <code>--component minio-init</code> .

Collect evidence

`mas-est support-bundle`

Attach the directory it creates when reporting a problem.