
Known limitations

One entry per limitation, with the workaround. `<instance>` is your MAS instance ID and `<workspace>` the MAS workspace ID.

Not a replacement for Entra or Okta. There are no vendor-specific provisioning rules or expression mappings. Use `mas-est` to narrow the problem, then confirm vendor behaviour in the customer's own tenant.

MAS 9.0 has no OIDC API. `install` stops at preflight with `AIUC01022E`. Install with `--mas-auth-providers ldap,saml`, or leave `oidc` unselected.

Logging out of MAS doesn't log you out of Keycloak. The next login in the same browser returns the previous user. Use a private window per login, or open `https://<keycloak-host>/realms/maximo/protocol/openid-connect/logout`.

MAS 9.1.20: the first SAML self-registration after the `<instance>-coreidp` pod starts fails once with `AIUSC0019I`. This is a MAS bug in `samlresolver` 4.0.43, which loads the self-registration config lazily. Log in again. Don't restart the pod, because that resets the problem. MAS 9.1.19 and earlier, and OIDC, are unaffected.

SCIM users added after the install aren't linked to a login identity. They can't log in or reach Manage until you run `mas-est mas-auth apply --mas-instance-id <instance> --self-reg-workspace <workspace>`.

Deactivating users removed from `mas-scim-users` is experimental. The bridge sets them inactive in MAS, and reactivates them when they're added back. This has never been validated on a cluster. Check the user in MAS after relying on it.

One SCIM profile. Every synced user lands in profile demo. To route a user elsewhere, set the Keycloak user attribute `masProfile` and map it with `SCIM_BRIDGE_MAS_PROFILE_MAP`.

Mailpit and Manage doclinks aren't connected automatically. Both are manual steps in the Guide. Mail from MAS into Mailpit hasn't been tested end to end.

`uninstall` leaves MAS-side state behind: the login providers, the self-registration `ConfigMap`, user records in MongoDB and Manage, the installer's cluster-scoped RBAC, the operator CRD and the `CatalogSource`. The list and the cleanup commands are in the Guide.

The install Job needs permissions close to cluster-admin, including reading secrets in the MAS namespaces and `pods/exec` on MongoDB. If your cluster's policy forbids this, install with `--local`.