# Word Embeddings

Luís Filipe da Costa Cunha

# Natural Language Processing

- Rule Based Approach
- Dictionary Based Approach
- Machine learning



# Words Representations

- ML can’t  process words
- Numeric Vocabulary
- Bag of Words
- Word Embeddings



# Bag of Words (BOW)

Review 1: Game of Thrones is an amazing tv series!

Review 2: Game of Thrones is the best tv series!

Review 3: Game of Thrones is so great

| | amazing | an | best | game | great | is | of | series | so | the | thrones | tv |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **0** | 1 | 1 | 0 | 1 | 0 | 1 | 1 | 1 | 0 | 0 | 1 | 1 |
| **1** | 0 | 0 | 1 | 1 | 0 | 1 | 1 | 1 | 0 | 1 | 1 | 1 |
| **2** | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 1 | 0 | 1 | 0 |

- Tokenization
- Stop words
- Punctuation
- Count word occurrences

| | amazing tv | best tv | game thrones | thrones amazing | thrones best | thrones great | tv series |
|---|---|---|---|---|---|---|---|
| **0** | 1 | 0 | 1 | 1 | 0 | 0 | 1 |
| **1** | 0 | 1 | 1 | 0 | 1 | 0 | 1 |
| **2** | 0 | 0 | 1 | 0 | 0 | 1 | 0 |

# Bag of Words (BOW)

- Vector Length N (100k)
- Sparse Vectors
- [0, 0, 0, 1, 0, .... 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
- Large memory usage and expensive computation

| | amazing | an | best | game | great | is | of | series | so | the | thrones | tv |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **0** | 1 | 1 | 0 | 1 | 0 | 1 | 1 | 1 | 0 | 0 | 1 | 1 |
| **1** | 0 | 0 | 1 | 1 | 0 | 1 | 1 | 1 | 0 | 1 | 1 | 1 |
| **2** | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 1 | 0 | 1 | 0 |

# Bag of Words (BOW)

- Sequence order is lost
  - Trabalhar para viver
  - Viver para trabalhar
- N-grams . Vector Dimensionality = V^N
- Vocabulary trigrams = 10^15
- 1000,000,000,000,000
- Semantic Meaning of the words lost
- Context is lost

| | amazing | an | best | game | great | is | of | series | so | the | thrones | tv |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **0** | 1 | 1 | 0 | 1 | 0 | 1 | 1 | 1 | 0 | 0 | 1 | 1 |
| **1** | 0 | 0 | 1 | 1 | 0 | 1 | 1 | 1 | 0 | 1 | 1 | 1 |
| **2** | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 1 | 0 | 1 | 0 |

| | amazing tv | best tv | game thrones | thrones amazing | thrones best | thrones great | tv series |
|---|---|---|---|---|---|---|---|
| **0** | 1 | 0 | 1 | 1 | 0 | 0 | 1 |
| **1** | 0 | 1 | 1 | 0 | 1 | 0 | 1 |
| **2** | 0 | 0 | 1 | 0 | 0 | 1 | 0 |

# Word Embeddings

| | |
|---|---|
| Openness to experience | 79 out of 100 |
| Agreeableness | 75 out of 100 |
| Conscientiousness | 42 out of 100 |
| Negative emotionality | 50 out of 100 |
| Extraversion | 58 out of 100 |






# Word Embeddings

- Dense
- Multidimensional
- length (50-1000)
- Words with similar meaning have similar numeric representation

**A 4-dimensional embedding**

| | | | | |
|---|---|---|---|---|
| **cat** => | 1.2 | -0.1 | 4.3 | 3.2 |
| **mat** => | 0.4 | 2.5 | -0.9 | 0.5 |
| **on** => | 2.1 | 0.3 | 0.1 | 0.4 |







"In practice, short dense vectors work better"


queen
woman
girl
boy
man
king
queen
water

# Reusing Word Embeddings (Transfer Learning)

- Train embeddings in and embedding layer
- Use pré-trained word Embeddings
  - Glove
  - Word2vec



# Embedding Layer

- Tokenization
- Create numeric vocabulary (*N* size)
- Create data batches
- Truncate and Padding

```
{'Data': 1, 'Local': 2, 'O': 3, 'Organizacao': 4, 'Pessoa': 5, 'Profissao': 6}
```

```
{'de': 1,
'e': 2,
'do': 3,
'ou': 4,
'em': 5,
'a': 6,
'da': 7,
'Maria': 8,
'concelho': 9,
'país': 10,
'actual': 11,
'residente': 12,
'Natural': 13,
'Filiação': 14,
'distrito': 15,
'º': 16,
'o': 17,
'n': 18,
'que': 19,
'Registo': 20,
'Manuel': 21,
'Pai': 22,
'Mãe': 23,
'para': 24,
(...)
'Meringolo': 9177,
'Pardo': 9178,
'2633': 9179,
'2016': 9180,
'Atente': 9181,
'Joanesburgo': 9182,
'Gavela': 9183,
'Calanga': 9184,
'Mambiça': 9185,
'Sotero': 9186,
'1951': 9187,
'Bairros': 9188,
'Adelina': 9189,
'Lbânia': 9190,
'Rufino': 9191,
'Espírito': 9192,
'Prazeres': 9193,
'Etelvina': 9194,
'1933': 9195,
'1988': 9196,
'Jesuína': 9197,
'Sara': 9198,
'Libânia': 9199
'terceiras': 9200}
```

```
words = [[2125, 1, 1482, 2, 2126, 695, 426, 1, 165, 1, 560, 1, 2755, 271, 1038, 347, 2, 225, 8,
    357, 2, 958, 106, 2, (...), 0, 0, 0, 0, 0], (...)]

labels = [[3, 3, 3, 3, 3, 3, 3, 3, 1, 1, 1, 1, 1, 3, 5, 5, 3, 3, 5, 5, 3, 5, 5, 3, (...), 0, 0,
    0, 0, 0], (...)]
```

# Word2Vec

- Trained to predict if a word belongs to the context
- "You shall know a word by the company it keeps" - John Rupert Firth
- Milk is a likely word given "The cat was drinking"
- king - man + woman = queen



# Word2Vec



INPUT
PROJECTION
OUTPUT
w(t-2)
w(t-1)
SUM
w(t)
w(t+1)
w(t+2)
CBOW
INPUT
PROJECTION
OUTPUT
w(t)
w(t-2)
w(t-1)
w(t+1)
w(t+2)
Skip-gram

# Word2Vec

king − man + woman ~= queen

# Limitations

- One vector per word (even if the word has multiple senses)
- ##Word embeddings can only represent low level features of the vocabulary.
- Inability to handle unknown or OOV
- Scaling to new languages requires new embedding matrices
- Embeddings reflect cultural bias implicit in training text

# BIAS

- Ask “Paris : France :: Tokyo : x”
    - x = Japan
- Ask “father : doctor :: mother : x”
    - x = nurse
- Ask “man : computer programmer :: woman : x”
    - x = homemaker

# GPT-3 BIAS

- GPT-3 model presented biases towards gender, race, and religion (Brown et. al., 2020)
- Words suchs as "Islam" are associated with "terrorism".
- The word "female" word was usually associated with "naughty" or "beautiful"
- The “male” word is associated with  “large", and "lazy".

# GPT3-Chat bot



# GPT3-Chat bot



# Word Embeddings

Luís Filipe da Costa Cunha