Word Embeddings

Luís Filipe Cunha
lfc@di.uminho.pt

José João Almeida
jj@di.uminho.pt

Nuno Guimarães
INESC TEC

Natural Language Processing

- Manual feature identification
  - Rule-based approaches
  - statistical models
- Deep Learning
  - Just feed the input data
  - Automatic feature learning



Words Representations

- ML algorithms prefer well defined fixed-length inputs and outputs
- ML algorithms cannot work with raw text directly
- Numeric Vocabulary
- Bag of Words
- Word Embeddings



Bag of Words (BOW)

Review 1: Game of Thrones is an amazing tv series!

Review 2: Game of Thrones is the best tv series!

Review 3: Game of Thrones is so great

	amazing	an	best	game	great	is	of	series	so	the	thrones	tv
0	1	1	0	1	0	1	1	1	0	0	1	1
1	0	0	1	1	0	1	1	1	0	1	1	1
2	0	0	0	1	1	1	1	0	1	0	1	0

- Tokenization
- Stop words
- Punctuation
- Ignore case
- Reducing words to their lemma
  - (e.g. “play” from “playing”)

Limitations

- **Vocabulary:** Vector Length N (100k)
- **Sparsity:** Sparse Vectors
  - [0, 0, 0, 1, 0, …. 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
  - Large memory usage and expensive computation
- **Unknown words:** Words outside of vocabulary are ignored

	amazing	an	best	game	great	is	of	series	so	the	thrones	tv
0	1	1	0	1	0	1	1	1	0	0	1	1
1	0	0	1	1	0	1	1	1	0	1	1	1
2	0	0	0	1	1	1	1	0	1	0	1	0

Bag of Words (BOW)

- Sequence order is lost
  - Trabalhar para viver
  - Viver para trabalhar
- N-grams . Vector Dimensionality = V^N
- Vocabulary trigrams = 100k^3
- 1.000,000,000,000,000
- Semantic Meaning of the words lost
- Context is lost

	amazing	an	best	game	great	is	of	series	so	the	thrones	tv
0	1	1	0	1	0	1	1	1	0	0	1	1
1	0	0	1	1	0	1	1	1	0	1	1	1
2	0	0	0	1	1	1	1	0	1	0	1	0

	amazing tv	best tv	game thrones	thrones amazing	thrones best	thrones great	tv series
0	1	0	1	1	0	0	1
1	0	1	1	0	1	0	1
2	0	0	1	0	0	1	0

Word Embeddings

Openness to experience	79 out of 100
Agreeableness	75 out of 100
Conscientiousness	42 out of 100
Negative emotionality	50 out of 100
Extraversion	58 out of 100





Word Embeddings

- Dense
- Multidimensional
- length (50-1000)
- Words with similar meaning have similar numeric representation

A 4-dimensional embedding

cat =>	1.2	-0.1	4.3	3.2
mat =>	0.4	2.5	-0.9	0.5
on =>	2.1	0.3	0.1	0.4



"In practice, short dense vectors work better"

Word2Vec

- Trained to predict if a word belongs to the context
- “You shall know a word by the company it keeps” - John Rupert Firth
- Milk is a likely word given “The cat was drinking”



Word2Vec



CBOW



Skip-gram

To grasp a word's meaning, Language Models first observe it in context using enormous sets of training data, taking note of nearby words.



Eventually, we end up with a huge set of the words found alongside work in the training data, as well as those that weren't found near it

As the model processes this set of words, it produces a vector — or list of values — and adjusts it based on each word's proximity to work in the training data. This vector is known as a word embedding.



A word embedding can have hundreds of values, each representing a different aspect of a word's meaning.

We don't know exactly what each value represents, but words we expect to be used in comparable ways often have similar-looking embeddings.




0
1
sea
ocean
football
soccer
I
we

The way these characteristics are derived means we don't know exactly what each value represents, but words we expect to be used in comparable ways often have similar-looking embeddings.

A pair of words like **sea** and **ocean** for example, may not be used in identical contexts ('all at ocean' isn't a direct substitute for 'all at sea'), but their meanings are close to each other, and embeddings allow us to quantify that closeness.




queen
woman
girl
boy
man
king
queen
water

Embedding Layer

- Tokenization
- Create numeric vocabulary (*N* size)
- Create data batches
- Truncate and Padding

```
{'Data': 1, 'Local': 2, 'O': 3, 'Organizacao': 4, 'Pessoa': 5, 'Profissao': 6}
```

```
{'de': 1,          'Natural': 13,          'Meringolo': 9177,    'Adelina': 9189,
'e': 2,            'Filiação': 14,         'Pardo': 9178,        'Lbânia': 9190,
'do': 3,           'distrito': 15,         '2633': 9179,         'Rufino': 9191,
'ou': 4,           'º': 16,                '2016': 9180,         'Espírito': 9192,
'em': 5,           'o': 17,                'Atente': 9181,       'Prazeres': 9193,
'a': 6,            'n': 18,        (...)   'Joanesburgo': 9182,  'Etelvina': 9194,
'da': 7,           'que': 19,              'Gavela': 9183,       '1933': 9195,
'Maria': 8,        'Registo': 20,          'Calanga': 9184,      '1988': 9196,
'concelho': 9,     'Manuel': 21,           'Mambiça': 9185,      'Jesuína': 9197,
'país': 10,        'Pai': 22,              'Sotero': 9186,       'Sara': 9198,
'actual': 11,      'Mãe': 23,              '1951': 9187,         'Libânia': 9199
'residente': 12,   'para': 24,             'Bairros': 9188,      'terceiras': 9200}
```

```
words = [[2125, 1, 1482, 2, 2126, 695, 426, 1, 165, 1, 560, 1, 2755, 271, 1038, 347, 2, 225, 8,
    357, 2, 958, 106, 2, (...), 0, 0, 0, 0, 0], (...)]

labels = [[3, 3, 3, 3, 3, 3, 3, 3, 1, 1, 1, 1, 1, 3, 5, 5, 3, 3, 5, 5, 3, 5, 5, 3, (...), 0, 0,
    0, 0, 0], (...)]
```

Similarity


exam
australia
germany
france
test
university
homework
fiji
problem
hungary
china
water
horse
ape
monkey
wolf
parrot
cat
dog
lizard
wombat
kangaroo
koala
tea
champagne
coffee
brandy
rum
beer
spaghetti
sushi
hamburger
falafel
1.5
1.0
0.5
0.0
−0.5
−1.0
−1.5
−1.0
−0.5
0.0
0.5
1.0
1.5
2.0
2.5


Jay
Person #1
cosine_similarity(
-0.4
0.8
,
-0.3
0.2
) = 0.87
Jay
Person #2
cosine_similarity(
-0.4
0.8
,
-0.5
-0.4
) = -0.20

Analogies

king - man + woman ~= queen

Reusing Word Embeddings (Transfer Learning)

- Train embeddings
- Use pre-trained word Embeddings
    - Glove
    - Word2vec



Limitations

- One vector per word (even if the word has multiple senses)
- Inability to handle unknown or OOV
- Scaling to new languages requires new embedding matrices
- Embeddings reflect cultural bias implicit in training text

BIAS

- Ask “Paris : France :: Tokyo : x”
  - x = Japan
- Ask “father : doctor :: mother : x”
  - x = nurse
- Ask “man : computer programmer :: woman : x”
  - x = homemaker

GPT-3 BIAS

- GPT-3 model presented biases towards gender, race, and religion (Brown et. al., 2020)
- Words such as "Islam" are associated with "terrorism".
- The word "female" word was usually associated with "naughty" or "beautiful"
- The “male” word is associated with “large", and "lazy".

GPT3-Chat bot



GPT3-Chat bot



Data Visualization





Dimension Reduction

- PCA: Principal Component Analysis
- t-SNE: t-Distributed Stochastic Neighbor Embedding



Principal Component Analysis (PCA)

- Dimensionality-reduction method
- Identifying patterns
- Trade a little accuracy for simplicity
- Preserving as much information as possible

1. Standardize the Dataset
2. Calculate the covariance matrix
3. Calculate the eigenvectors and eigenvalues
4. Choose Principal Components
5. Deriving the new data set (reorient the data)

Standardize the Dataset

$$z = \frac{value - mean}{standard\ deviation}$$

		f1	f2	f3	f4
μ	=	4	3	3	3.4
σ	=	3	1.58114	1.73205	2.30217

f1	f2	f3	f4
1	2	3	4
5	5	6	7
1	4	2	3
5	3	2	1
8	1	2	2

f1	f2	f3	f4
-1	-0.63246	0	0.26062
0.33333	1.26491	1.73205	1.56374
-1	0.63246	-0.57735	-0.17375
0.33333	0	-0.57735	-1.04249
1.33333	-1.26491	-0.57735	-0.60812

Calculate the covariance matrix

Understand how the variables of the input data set are varying from the mean

Variables highly correlated can contain redundant information

p × p symmetric matrix (where p is the number of dimensions) that has as entries the covariances associated with all possible pairs of the initial variables

(Cov(a,a)=Var(a)), (Cov(a,b)=Cov(b,a))

$$var(X) = \frac{\sum_{i=1}^{n}(X_i - \bar{X})(X_i - \bar{X})}{(n-1)}$$

$$cov(X,Y) = \frac{\sum_{i=1}^{n}(X_i - \bar{X})(Y_i - \bar{Y})}{(n-1)}$$

$$\begin{bmatrix} Cov(x,x) & Cov(x,y) & Cov(x,z) \\ Cov(y,x) & Cov(y,y) & Cov(y,z) \\ Cov(z,x) & Cov(z,y) & Cov(z,z) \end{bmatrix}$$

Covariance and Correlation

- if positive then : the two variables increase or decrease together (correlated)
- if negative then : One increases when the other decreases (Inversely correlated)
- covariance matrix summaries the correlations between all the possible pairs of variables.



$$cov = \begin{pmatrix} .616555556 & .615444444 \\ .615444444 & .716555556 \end{pmatrix}$$

Calculate the eigenvectors and eigenvalues

$$Av = \lambda v$$

- Eigenvectors of the Covariance matrix are the directions of the axes where there is the most variance (information)
- Eigenvalues give the amount of variance

$$\begin{pmatrix} 2 & 3 \\ 2 & 1 \end{pmatrix} \times \begin{pmatrix} 1 \\ 3 \end{pmatrix} = \begin{pmatrix} 11 \\ 5 \end{pmatrix}$$

$$\begin{pmatrix} 2 & 3 \\ 2 & 1 \end{pmatrix} \times \begin{pmatrix} 3 \\ 2 \end{pmatrix} = \begin{pmatrix} 12 \\ 8 \end{pmatrix} = 4 \times \begin{pmatrix} 3 \\ 2 \end{pmatrix}$$

Calculate the eigenvectors and eigenvalues

- Provide information about patterns in the data.
- Line that best fits the data.
- Allow to create lines that characterise the data.



Calculate the eigenvectors and eigenvalues

- 1st Eigenvector shows how the two sets of points are related along the line.
- 2nd Eigenvector shows that the points are off to the side of the main line by some amount (less important).
- Eigenvectors are pendicular to each other. (non correlated)



Principal Components

$$eigenvalues = \begin{pmatrix} .0490833989 \\ 1.28402771 \end{pmatrix}$$

$$eigenvectors = \begin{pmatrix} -.735178656 & -.677873399 \\ .677873399 & -.735178656 \end{pmatrix}$$

- Order them by eigenvalue, highest to lowest.
- Components in order of significance.
- Information loss, however, if the eigenvalues are small, we don't lose much.



Deriving the new data set

- Reorient the data from the original axes to the ones represented by the principal components

x
-.827970186
1.77758033
-.992197494
-.274210416
-1.67580142
-.912949103
.0991094375
1.14457216
.438046137
1.22382056



$$FinalDataSet = FeatureVector^T * StandardizedOriginalDataSet^T$$

PCA


faculdade
universidade
exame
problema
colegio
aula
escola
trabalho
tarefa
gorila
cachorro
gato
sapo
lagarto
papagaio
coelho
chá
hamburger
koala
cafe
bife
sushi
cao
agua
cerveja
champagne
australia
vinho
pão
spaghetti
rum
frança
espanha
china
alemanha
arroz
kangaroo
hungria
batata


exam
australia
germany
france
test
university
homework
fiji
problem
hungary
china
horse
water
ape
monkey
wolf
parrot
cat
dog
lizard
wombat
frog
kangaroo
koala
tea
champagne
coffee
brandy
rum
beer
spaghetti
sushi
hamburger
falafel

t-Distributed Stochastic Neighbor Embedding

- Discover natural clusters
- Preserve the neighborhood
- Distant points correspond to dissimilar objects

1. Calculate similarity of points in High Dimension
2. Project all the points in the low dim space randomly
3. Calculate similarity of points in Low Dimension
4. Cost Function and gradient descendant

t-Distributed Stochastic Neighbor Embedding



Calculate similarity of points in High Dimension

- Calculate similarity of points in High Dimension
- Calculate similarity of points in Low Dimension

$$p_{ij} = \frac{exp(-||x_i - x_j||^2/2\sigma^2)}{\sum_{k \neq l} exp(-||x_l - x_k||^2/2\sigma^2)}$$

$$q_{ij} = \frac{(1 + ||y_i - y_j||^2)^{-1}}{\sum_{k \neq l}(1 + ||y_k - y_l||^2)^{-1}}$$

Cost Function

Kullback Leibler Divergence
Given two probabilities P and Q the KL divergence measures the how much does P as a distribution diverges from Q

Large Pij modeled by small qij: Large penalty

Small pij modeled by large qij: Small penalty

Minimization of the cost function
Gradient descent

KL(P || Q)

$$C = KL(P||Q) = \sum_i \sum_j p_{ij} log \frac{p_{ij}}{q_{ij}}$$

$$\frac{\delta C}{\delta y_i} = 2 \sum_j (p_{j|i} - q_{j|i} + p_{i|j} - q_{i|j})(y_i - y_j).$$



The crowding problem



There is much more space in high dimensions.

Blue = Gaussian
Red = Student's T



The crowding problem





Student-t distribution has heavier tails.

The crowding problem



(a) Gradient of SNE. (b) Gradient of UNI-SNE. (c) Gradient of t-SNE.

t-SNE introduces strong repulsions between dissimilar datapoints that are





https://distill.pub/2016/misread-tsne/



TSNE


hungria
espanha
china
alemanha
franca
universidade
faculdade
escola
tarefa
aula
agua
chouriça
batata
rá
cao
spaghetti
kangaroo
australia
cafe
rum
champagne
hamburger
sushi
koala
colegio
trabalho
cavalo
exame
teste
vinho
pão
arroz
bife
papagaio
gato
cachorro
problema
gorila
macaco
macaco
sapo
lagarto
coelho
lobo
chá
150
100
50
0
−50
−100
−100
−50
0
50
100


australia
france
germany
china
fiji
parrot
institute
hungary
ape
problem
assignment
university
wolf
frog
lizard
test
class
college
monkey
toad
monkey
exam
school
cat
homework
dog
kangaroo
water
spaghetti
horse
sushi
meatballs
falafel
pizza
tea
borscht
coffee
hamburger
beer
wine
brandy
champagne
200
100
0
−100
−200
−300
−200
−100
0
100
200
300

Dimension Reduction



PCA: Principal Component Analysis

- Preserve the global structure of the data
- Deterministic
- Preserves variance

t-SNE: t-Distributed Stochastic Neighbor Embedding

- Preserve the local structure of data.
- Non-deterministic
- Preserves distance


0
1
2
3
4
5
6
7
8
9


y
0
1
2
3
4
5
6
7
8
9
pca-two
pca-one
6
4
2
0
−2
−4
−6
−4
−2
0
2
4
6
8
10


label
0
1
2
3
4
5
6
7
8
9
60
40
20
0
−20
−40
−60
−60
−40
−20
0
20
40
60

Data Visualization



olhar
boca
harri



Word Embeddings

Luís Filipe Cunha
lfc@di.uminho.pt

José João Almeida
jj@di.uminho.pt