# ■ Guia de Estudos — Shortbeyond

Manual de Referência Indexado por Commits do Git

**Autor:** Luis Fernando Brandão
**Repositório:** shortbeyond
**Total de Commits Indexados:** 26 commits
**Total de Seções / Diretórios:** 2
**Descrição:** Guia gerado automaticamente a partir dos commits do repositório, contendo código adicionado, arquivos alterados e histórico do Git.

### Resumo das Seções Indexadas:

| Seção / Diretório | Qtd Commits |
|---|---|
| Diretório: Shortbeyond (shortbeyond) | 23 |
| Geral / Raiz do Projeto | 3 |

# Diretório: Shortbeyond (shortbeyond)

## ■ 4-Configurando seu Ambiente de Teste com Podman

***Commit:*** *2bb99fb* | ***Data:*** *2026-08-25 17:48* | ***Arquivos:*** *.DS_Store, shortbeyond/shortbeyond.yaml*

```
# Feito com Muito S2 e Muito Café :)
apiVersion: v1
kind: Pod
metadata:
  name: shortbeyond
  labels:
    app: shortbeyond
spec:
  containers:
    - name: shortb-db
      image: postgres:15
      ports:
        - containerPort: 5432
          hostPort: 5432
      env:
        - name: POSTGRES_USER
          value: "dba"
        - name: POSTGRES_PASSWORD
          value: "dba"
        - name: POSTGRES_DB
          value: "ShortDB"
        - name: TZ
          value: "America/Sao_Paulo"
    - name: shortb-adminer
      image: adminer
      ports:
        - containerPort: 8080
          hostPort: 8080
    - name: shortb-api
      image: beyondtest/shortb-api:beta
      ports:
        - containerPort: 3333
          hostPort: 3333
      env:
        - name: PORT
// ... [10 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 5-Testes Preliminares com Swagger e Bruno

***Commit:*** *3a091a2* | ***Data:*** *2026-08-25 18:32* | ***Arquivos:*** *.DS_Store, shortbeyond/.gitignore, "shortbeyond/docs/auth/Cadastro de usu\303\241rios.yml", "shortbeyond/docs/auth/Login do usu\303\241rio.yml", shortbeyond/docs/auth/folder.yml, shortbeyond/docs/opencollection.yml*

```
# Secrets
.env*

# Dependencies
node_modules

# OS files
.DS_Store
Thumbs.db
info:
  name: Cadastro de usuários
  type: http
  seq: 1

http:
  method: POST
  url: http://localhost:3333/api/auth/register
  body:
    type: json
    data: |-
      {
        "name": "João Silva",
        "email": "joao@email.com",
        "password": "123456"
      }
  auth: inherit

settings:
  encodeUrl: true
  timeout: 0
  followRedirects: true
  maxRedirects: 5
  forwardAuthorizationHeader: false
info:
  name: Login do usuário
// ... [38 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 6. Setup do Playwright para Testes de API

***Commit:*** *b8d5f3f* | ***Data:*** *2026-08-25 19:01* | ***Arquivos:*** *shortbeyond/.DS_Store, shortbeyond/.gitignore, shortbeyond/docs/health/Verifica status.yml, shortbeyond/docs/health/folder.yml, shortbeyond/package-lock.json, shortbeyond/package.json, shortbeyond/playwright.config.js, shortbeyond/playwright/e2e/health.spec.js*

```
# Playwright
node_modules/
/test-results/
/playwright-report/
/blob-report/
/playwright/.cache/
/playwright/.auth/
info:
  name: Verifica status
  type: http
  seq: 1

http:
  method: GET
  url: http://localhost:3333/health
  auth: inherit

settings:
  encodeUrl: true
  timeout: 0
  followRedirects: true
  maxRedirects: 5
  forwardAuthorizationHeader: false
info:
  name: health
  type: folder
  seq: 2

request:
  auth: inherit
{
  "name": "shortbeyond",
  "version": "1.0.0",
  "lockfileVersion": 3,
  "requires": true,
// ... [204 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ Testando POST de Ponta a Ponta

***Commit:*** *bb1427f* | ***Data:*** *2026-08-26 17:02* | ***Arquivos:*** *shortbeyond/package-lock.json, shortbeyond/package.json, shortbeyond/playwright/e2e/auth/register.spec.js*

```
"@faker-js/faker": "^10.6.0",
    "node_modules/@faker-js/faker": {
      "version": "10.6.0",
      "resolved": "https://registry.npmjs.org/@faker-js/faker/-/faker-10.6.0.tgz",
      "integrity": "sha512-3RQHgEtvL1Frl/d1cSreo7qhJ3Gk1OdNUai/CtZ8G+wYeRQnJih3s9xJ9/kgYekPQRdwgh0HXRPqMl
zWGwivIQ==",
      "dev": true,
      "funding": [
        {
          "type": "opencollective",
          "url": "https://opencollective.com/fakerjs"
        }
      ],
      "license": "MIT",
      "engines": {
        "node": "^20.19.0 || ^22.13.0 || ^23.5.0 || >=24.0.0",
        "npm": ">=10"
      }
    },
    "@faker-js/faker": "^10.6.0",
import { test, expect } from "@playwright/test";
import { faker } from "@faker-js/faker";

test.describe("POST /auth/register", () => {
  test("deve cadastrar um novo usuario", async ({ request }) => {
    const firstName = faker.person.firstName();
    const lastName = faker.person.lastName();

    const user = {
      name: `${firstName} ${lastName}`,
      email: faker.internet
        .email({
          firstName: firstName,
          lastName: lastName,
        })
        .toLowerCase(),
// ... [25 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ Os testes devem ser independentes

***Commit:*** *66ecd47* | ***Data:*** *2026-08-26 17:41* | ***Arquivos:*** *shortbeyond/playwright/e2e/auth/register.spec.js*

```
test("não deve cadastrar quando o email ja estiver em uso", async ({
    request,
  }) => {
    const firstName = faker.person.firstName();
    const lastName = faker.person.lastName();

    const user = {
      name: `${firstName} ${lastName}`,
      email: faker.internet
        .email({
          firstName: firstName,
          lastName: lastName,
        })
        .toLowerCase(),
      password: "pwd123",
    };

    const preCondition = await request.post(
      "http://localhost:3333/api/auth/register",
      {
        data: user,
      },
    );

    expect(preCondition.status()).toBe(201);

    const response = await request.post(
      "http://localhost:3333/api/auth/register",
      {
        data: user,
      },
    );

    expect(response.status()).toBe(400);

// ... [111 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 10. Trabalhando com Factories

***Commit:*** *5525a88* | ***Data:*** *2026-08-26 18:03* | ***Arquivos:*** *shortbeyond/playwright/e2e/auth/register.spec.js, shortbeyond/playwright/support/factories/user.js*

```
import { getUser } from "../../support/factories/user";
    const user = getUser();
    const user = getUser();
import { faker } from "@faker-js/faker";

export const getUser = () => {
  const firstName = faker.person.firstName();
  const lastName = faker.person.lastName();

  return {
    name: `${firstName} ${lastName}`,
    email: faker.internet
      .email({
        firstName: firstName,
        lastName: lastName,
      })
      .toLowerCase(),
    password: "pwd123",
  };
};
```

## ■ 11. Trabalhando com Hooks

***Commit:*** *02dba72* | ***Data:*** *2026-08-26 18:37* | ***Arquivos:*** *shortbeyond/playwright/e2e/auth/register.spec.js, shortbeyond/playwright/support/services/register.js*

```
import { registerService } from "../../support/services/register";
  let register;

  test.beforeEach(({ request }) => {
    register = registerService(request);
  });

    // Preparação
    // Ação
    const response = await register.createUser(user);
    // Resultado Esperado
    const preCondition = await register.createUser(user);
    const response = await register.createUser(user);
    const response = await register.createUser(user);
    const response = await register.createUser(user);
    const response = await register.createUser(user);
    const response = await register.createUser(user);
export const registerService = (request) => {
  const createUser = async (user) => {
    return await request.post("http://localhost:3333/api/auth/register", {
      data: user,
    });
  };

  return {
    createUser,
  };
};
```

## ■ 12. Testando Login e verificando a existência do Token

***Commit:*** *233ccae* | ***Data:*** *2026-08-27 16:50* | ***Arquivos:*** *shortbeyond/playwright/e2e/auth/login.spec.js, shortbeyond/playwright/e2e/auth/register.spec.js, shortbeyond/playwright/support/services/auth.js, shortbeyond/playwright/support/services/register.js*

```
import { test, expect } from "@playwright/test";
import { authService } from "../../support/services/auth";
import { getUser } from "../../support/factories/user";

test.describe("POST /auth/login", () => {
  let auth;
  test.beforeEach(({ request }) => {
    auth = authService(request);
  });

  test("deve fazer login com sucesso", async ({ page }) => {
    const user = getUser();

    const respCreate = await auth.createUser(user);
    expect(respCreate.status()).toBe(201);

    const response = await auth.login(user);

    expect(response.status()).toBe(200);

    const body = await response.json();

    expect(body).toHaveProperty("message", "Login realizado com sucesso");
    expect(body.data).toHaveProperty("token");
    expect(body.data.user).toHaveProperty("id");
    expect(body.data.user).toHaveProperty("name", user.name);
    expect(body.data.user).toHaveProperty("email", user.email);
    expect(body.data.user).not.toHaveProperty("password");
  });

  test("não deve fazer login com senha incorreta", async ({ page }) => {
    const user = getUser();

    const respCreate = await auth.createUser(user);
    expect(respCreate.status()).toBe(201);
// ... [86 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 13. Testando o Endpoint do Encurtador de Links

***Commit:*** *520baa1* | ***Data:*** *2026-08-28 13:51* | ***Arquivos:*** *shortbeyond/docs/links/Criar novo link.yml, shortbeyond/docs/links/folder.yml, shortbeyond/playwright/e2e/links/post.spec.js, shortbeyond/playwright/support/factories/user.js, shortbeyond/playwright/support/services/auth.js, shortbeyond/playwright/support/services/links.js*

```
info:
  name: Criar novo link
  type: http
  seq: 1

http:
  method: POST
  url: http://localhost:3333/api/links
  headers:
    - name: Authorization
      value: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1c2VyX2lkIjoiMDFNMFdWUVZES01LTVBZWjA0Ujc3WlhY
MjIiLCJleHAiOjE3ODc5OTgyNTcsImlhdCI6MTc4NzkxMTg1N30.jOa69GVcSJgTdwv-akumTLPdk1313gDxJLf03J7QAPc
  body:
    type: json
    data: |-
      {
        "original_url": "https://www.instagram/papitoqa",
        "title": "Meu Instagram"
      }
  auth: inherit

settings:
  encodeUrl: true
  timeout: 0
  followRedirects: true
  maxRedirects: 5
  forwardAuthorizationHeader: false
info:
  name: links
  type: folder
  seq: 3

request:
  auth: inherit
import { test, expect } from "@playwright/test";
import { authService } from "../../support/services/auth";
// ... [63 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 14. Reuso de Codigo

***Commit:*** *96a1e2b* | ***Data:*** *2026-08-28 17:14* | ***Arquivos:*** *shortbeyond/playwright/e2e/links/post.spec.js*

```
const user = getUserWithLink();
  let auth, link, token;
  test.beforeEach(async ({ request }) => {
    auth = authService(request);
    link = linksService(request);
    token = await auth.getToken(user);
  });
  test("deve encurtar um novo link", async ({ request }) => {

  test("não deve encurtar quando a url original não é informada", async ({
    request,
  }) => {
    const response = await link.createLink(
      { ...user.link, original_url: "" },
      token,
    );

    expect(response.status()).toBe(400);
    const { message } = await response.json();
    expect(message).toBe(`O campo 'OriginalURL' é obrigatório`);
  });

  test("não deve encurtar quando titulo não é informado", async ({
    request,
  }) => {
    const response = await link.createLink({ ...user.link, title: "" }, token);

    expect(response.status()).toBe(400);
    const { message } = await response.json();
    expect(message).toBe(`O campo 'Title' é obrigatório`);
  });

  test("não deve encurtar quando a url original não é invalida", async ({
    request,
  }) => {
// ... [9 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 15. Trabalhando com Fixtures

***Commit:*** *040b68e* | ***Data:*** *2026-08-28 17:44* | ***Arquivos:*** *shortbeyond/playwright/e2e/auth/login.spec.js, shortbeyond/playwright/e2e/auth/register.spec.js, shortbeyond/playwright/e2e/links/post.spec.js, shortbeyond/playwright/support/fixtures/index.js*

```
import { test, expect } from "../../support/fixtures";
  test("deve fazer login com sucesso", async ({ auth }) => {
  test("não deve fazer login com senha incorreta", async ({ auth }) => {
  test("não deve logar com email que não foi cadastrado", async ({ auth }) => {
  test("não deve logar quando o email não é informado", async ({ auth }) => {
  test("não deve logar quando a senha não é informada", async ({ auth }) => {
import { test, expect } from "../../support/fixtures";
  test("deve cadastrar um novo usuario", async ({ auth }) => {
    auth,
  test("não deve cadastrar quando o email é incorreto", async ({ auth }) => {
  test("não deve cadastrar quando o nome não é informado", async ({ auth }) => {
    auth,
    auth,
import { test, expect } from "../../support/fixtures";
  let token;
  test.beforeEach(async ({ auth }) => {

  test("deve encurtar um novo link", async ({ links }) => {
    const response = await links.createLink(user.link, token);
    links,
    const response = await links.createLink(
  test("não deve encurtar quando titulo não é informado", async ({ links }) => {
    const response = await links.createLink({ ...user.link, title: "" }, token);
    links,
    const response = await links.createLink(
import { test as baseTest, expect } from "@playwright/test";

import { authService } from "../services/auth";
import { linksService } from "../services/links";

const test = baseTest.extend({
  auth: async ({ request }, use) => {
    const auth = authService(request);
    await use(auth);
  },
// ... [7 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 16. Testando GET de Ponta a Ponta

***Commit:*** *deba7b5* | ***Data:*** *2026-08-31 11:52* | ***Arquivos:*** *shortbeyond/docs/links/Obter lista de links.yml, shortbeyond/playwright/e2e/links/get.spec.js, shortbeyond/playwright/support/factories/user.js, shortbeyond/playwright/support/services/links.js*

```
info:
  name: Obter lista de links
  type: http
  seq: 2

http:
  method: GET
  url: http://localhost:3333/api/links
  headers:
    - name: Authorization
      value: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1c2VyX2lkIjoiMDFNMFdWUVZES01LTVBZWjA0Ujc3WlhY
MjIiLCJleHAiOjE3ODgyNTIwNjIsImlhdCI6MTc4ODE2NTY2Mn0.WkpKqJRcQEiD5lubAj-7YZP69rxNmRQRSAKp_MaTHys
  auth: inherit

settings:
  encodeUrl: true
  timeout: 0
  followRedirects: true
  maxRedirects: 5
  forwardAuthorizationHeader: false
import { test, expect } from "../../support/fixtures";
import { getUser, getUserWithLinks } from "../../support/factories/user";

test("deve retornar uma lista de links pré-encurtados", async ({
  auth,
  links,
}) => {
  const user = getUserWithLinks();

  await auth.createUser(user);
  const token = await auth.getToken(user);

  for (const link of user.links) {
    await links.createLink(link, token);
  }

// ... [67 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 18. Testando DELETE de Ponta a Ponta

***Commit:*** *567fb7d* | ***Data:*** *2026-08-31 13:12* | ***Arquivos:*** *shortbeyond/docs/links/Remove um link encurtado.yml, shortbeyond/playwright/e2e/links/delete.spec.js, shortbeyond/playwright/e2e/links/get.spec.js, shortbeyond/playwright/support/factories/utils.js, shortbeyond/playwright/support/services/links.js*

```
info:
  name: Remove um link encurtado
  type: http
  seq: 3

http:
  method: DELETE
  url: http://localhost:3333/api/links
  headers:
    - name: Authorization
      value: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1c2VyX2lkIjoiMDFNMFdWUVZES01LTVBZWjA0Ujc3WlhY
MjIiLCJleHAiOjE3ODgyNTIwNjIsImlhdCI6MTc4ODE2NTY2Mn0.WkpKqJRcQEiD5lubAj-7YZP69rxNmRQRSAKp_MaTHys
  auth: inherit

settings:
  encodeUrl: true
  timeout: 0
  followRedirects: true
  maxRedirects: 5
  forwardAuthorizationHeader: false
import { test, expect } from "../../support/fixtures";
import { getUserWithLink } from "../../support/factories/user";
import { generateULID } from "../../support/factories/utils";

test.describe("DELETE /link/:id", () => {
  const user = getUserWithLink();
  let token;

  test.beforeEach(async ({ auth }) => {
    await auth.createUser(user);
    token = await auth.getToken(user);
  });

  test("deve remover um link encurtado", async ({ links }) => {
    const linkId = await links.createAndReturnLinkId(user.link, token);

// ... [106 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 17. Regressão Completa pela CLI do Playwright

***Commit:*** *abe412e* | ***Data:*** *2026-08-31 17:28* | ***Arquivos:*** *shortbeyond/shortbeyond.yaml*

```
image: beyondtest/shortb-api:hotfix
```

## ■ 19. URL Base da API com Dotenv

***Commit:*** *8a9bb54* | ***Data:*** *2026-08-31 17:37* | ***Arquivos:*** *shortbeyond/package-lock.json, shortbeyond/package.json, shortbeyond/playwright.config.js, shortbeyond/playwright/support/services/auth.js, shortbeyond/playwright/support/services/links.js*

```
"@types/node": "^26.3.0",
        "dotenv": "^17.4.2"
    "node_modules/dotenv": {
      "version": "17.4.2",
      "resolved": "https://registry.npmjs.org/dotenv/-/dotenv-17.4.2.tgz",
      "integrity": "sha512-nI4U3TottKAcAD9LLud4Cb7b2QztQMUEfHbvhTH09bqXTxnSie8WnjPALV/WMCrJZ6UV/qHJ6L03Oq
O3LcdYZw==",
      "dev": true,
      "license": "BSD-2-Clause",
      "engines": {
        "node": ">=12"
      },
      "funding": {
        "url": "https://dotenvx.com"
      }
    },
    "@types/node": "^26.3.0",
    "dotenv": "^17.4.2"
import dotenv from "dotenv";
dotenv.config();
    baseURL: process.env.BASE_API,
    return await request.post("/api/auth/register", {
    return await request.post("/api/auth/login", {
    return await request.post("/api/links", {
    return await request.get("/api/links", {
    return await request.delete(`/api/links/${linkId}`, {
```

## ■ 20. Como Desabilitar o Show Report em Casos de Falha

***Commit:*** *0d6840d* | ***Data:*** *2026-08-31 17:42* | ***Arquivos:*** *shortbeyond/playwright.config.js*

```
reporter: [["html", { open: "never" }]],
```

## ■ 21. Explorando os Diferentes Tipos de Relatórios

***Commit:*** *8de177c* | ***Data:*** *2026-08-31 17:47* | ***Arquivos:*** *shortbeyond/playwright.config.js*

```
reporter: [["html", { open: "never" }], ["dot"]],
  // reporter: [["html", { open: "never" }], ["list"]], list para lista e dot para ver o report no termin
al com pontos
```

## ■ 22. Faker Lotou o Banco? Resolva com Global Setup

***Commit:*** *52434ba* | ***Data:*** *2026-08-31 18:29* | ***Arquivos:*** *shortbeyond/global-setup.js, shortbeyond/package-lock.json, shortbeyond/package.json, shortbeyond/playwright.config.js, shortbeyond/playwright/support/factories/user.js, shortbeyond/playwright/support/services/database.js, shortbeyond/prompt-topico 22*

```
const { cleanupTestData } = require("./playwright/support/services/database");

module.exports = async () => {
  console.log("Limpando os dados de teste antes da execução...");
  await cleanupTestData();
  console.log("Limpesa concluída com sucesso.");
};
        "dotenv": "^17.4.2",
        "pg": "^8.23.0"
    "node_modules/pg": {
      "version": "8.23.0",
      "resolved": "https://registry.npmjs.org/pg/-/pg-8.23.0.tgz",
      "integrity": "sha512-Ip2EQCngowJLGOfCwkFhPXU7/ljlhn6Rxlmy4XYfL2Y+vyRM59+8uR2xqRWKdYmbXmxCFOAmKxBuSU
CdF34qLg==",
      "dev": true,
      "license": "MIT",
      "dependencies": {
        "pg-connection-string": "^2.14.0",
        "pg-pool": "^3.14.0",
        "pg-protocol": "^1.16.0",
        "pg-types": "2.2.0",
        "pgpass": "1.0.5"
      },
      "engines": {
        "node": ">= 16.0.0"
      },
      "optionalDependencies": {
        "pg-cloudflare": "^1.4.0"
      },
      "peerDependencies": {
        "pg-native": ">=3.0.1"
      },
      "peerDependenciesMeta": {
        "pg-native": {
          "optional": true
        }
// ... [252 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 24. Introdução ao Artillery: Seu Primeiro Teste de Carga

***Commit:*** *dfcc63d* | ***Data:*** *2026-09-01 10:48* | ***Arquivos:*** *shortbeyond/package-lock.json, shortbeyond/package.json, shortbeyond/performance/tests/health.yaml, shortbeyond/prompt-topico_2_section_3.md*

```
"artillery": "^2.0.34",
    "node_modules/@artilleryio/sketches-js": {
      "version": "2.1.1",
      "resolved": "https://registry.npmjs.org/@artilleryio/sketches-js/-/sketches-js-2.1.1.tgz",
      "integrity": "sha512-H3D50vDb37E3NGYXY0eUFAm5++moElaqoAu0MWYZhgzaA3IT2E67bRCL8U4LKHuVf/MgDZk14uawIj
c4WVjOUQ==",
      "dev": true,
      "license": "Apache-2.0"
    },
    "node_modules/@aws-sdk/checksums": {
      "version": "3.1000.29",
      "resolved": "https://registry.npmjs.org/@aws-sdk/checksums/-/checksums-3.1000.29.tgz",
      "integrity": "sha512-Dtu0gr4dnATZAPwEYbpCsG+MpLM7OAliy2gTepEFQwl1vZ6DL3QMH2FveMa3HLvPsOdhJsPRB3KtxV
hph9T75A==",
      "dev": true,
      "license": "Apache-2.0",
      "dependencies": {
        "@aws-sdk/core": "^3.977.9",
        "@aws-sdk/types": "^3.974.5",
        "@smithy/core": "^3.33.3",
        "@smithy/types": "^4.17.2",
        "tslib": "^2.6.2"
      },
      "engines": {
        "node": ">=20.0.0"
      }
    },
    "node_modules/@aws-sdk/client-cloudwatch": {
      "version": "3.1123.0",
      "resolved": "https://registry.npmjs.org/@aws-sdk/client-cloudwatch/-/client-cloudwatch-3.1123.0.tgz
",
      "integrity": "sha512-2ND1AiQ1MO00rz8GSg3o18/h6ykC+TEinCrDmDqUReW5Ww8d+cljqonY/xN1jEGF9BpyLpqQ7S5VwL
tLOBInnQ==",
      "dev": true,
      "license": "Apache-2.0",
      "dependencies": {
        "@aws-sdk/core": "^3.977.9",
        "@aws-sdk/credential-provider-node": "^3.972.82",
        "@aws-sdk/types": "^3.974.5",
// ... [6568 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 25. Usando IA para interpretar Relatórios do Artillery

***Commit:*** *9288993* | ***Data:*** *2026-09-01 11:46* | ***Arquivos:*** *shortbeyond/.DS_Store, shortbeyond/.gitignore, shortbeyond/notes.txt, shortbeyond/performance/reports/cadastro.json, shortbeyond/performance/tests/cadastro.yaml, shortbeyond/prompt-analise-performance-tests_section_3.md*

```
../.DS_Store
Artillery

para criar reports : npx artillery run performance/tests/cadastro.yaml --output performance/reports/cadas
tro.json
{
  "aggregate": {
    "period": 1788254970000,
    "counters": {
      "vusers.created_by_name.Cadastro com Sucesso": 106,
      "vusers.created": 135,
      "http.requests": 135,
      "http.codes.201": 106,
      "http.responses": 135,
      "http.downloaded_bytes": 24733,
      "plugins.metrics-by-endpoint./api/auth/register.codes.201": 106,
      "vusers.failed": 0,
      "vusers.completed": 135,
      "vusers.created_by_name.Email Duplicado": 29,
      "http.codes.400": 29,
      "plugins.metrics-by-endpoint./api/auth/register.codes.400": 29
    },
    "rates": {
      "http.request_rate": 3
    },
    "firstCounterAt": 1788254926522,
    "firstHistogramAt": 1788254926631,
    "lastCounterAt": 1788254970694,
    "lastHistogramAt": 1788254970694,
    "firstMetricAt": 1788254926522,
    "lastMetricAt": 1788254970694,
    "summaries": {
      "http.response_time": {
        "min": 1,
        "max": 117,
        "count": 135,
// ... [1186 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 25. Usando IA para interpretar Relatórios do Artillery-2

***Commit:*** *f0d511e* | ***Data:*** *2026-09-01 11:48* | ***Arquivos:*** *shortbeyond/.env, shortbeyond/performance/.DS_Store*

```
BASE_API=http://localhost:3333
DB_HOST=localhost
DB_PORT=5432
DB_USER=dba
DB_PASS=dba
DB_NAME=ShortDB
```

## ■ 26. Executando Testes de Carga

***Commit:*** *a190ac3* | ***Data:*** *2026-09-01 12:54* | ***Arquivos:*** *shortbeyond/performance/README.md, shortbeyond/performance/data/usuarios.csv, shortbeyond/performance/reports/login.json, shortbeyond/performance/tests/login.yaml, shortbeyond/performance/tests/pre-cadastro.yaml, shortbeyond/prompt-analise-performance-tests_section_3.md*

```
# ■ Resumo do Módulo: Testes de Performance com Artillery & Análise com IA

Este documento consolida todas as atividades, arquivos, comandos, arquitetura dos testes de carga, pontos
 fortes e lições aprendidas desenvolvidas durante o módulo de testes de performance da API **ShortBeyond*
*.

---

## ■ 1. Estrutura de Arquivos do Módulo

```text
performance/
■■■ data/
■   ■■■ usuarios.csv            # Massa de testes com 100 usuários únicos
■■■ reports/
■   ■■■ cadastro.json           # Relatório JSON do teste de cadastro
■   ■■■ login.json              # Relatório JSON do teste de login
■■■ tests/
    ■■■ health.yaml             # Teste de carga do endpoint /health
    ■■■ cadastro.yaml           # Teste de performance de cadastro (80% sucesso / 20% duplicado)
    ■■■ pre-cadastro.yaml       # Script de carga inicial/seeding (100 cadastros a partir do CSV)
    ■■■ login.yaml              # Teste de performance de login (70% sucesso / 30% erro 401)
```

---

## ■■ 2. Comandos Executados

### 2.1. Geração de Massa de Dados (CSV)
Geração de 100 usuários com nomes, e-mails únicos com domínio `@lfernandobra.dev` e senhas padrão via Nod
e.js:
```bash
node -e '
const { faker } = require("@faker-js/faker");
const fs = require("fs");
const path = require("path");

const dataDir = path.join("performance", "data");
// ... [1617 linhas omitidas para manter a legibilidade do PDF] ...
```

## ■ 27. Spike Tests + Database

***Commit:*** *838b376* | ***Data:*** *2026-09-01 14:04* | ***Arquivos:*** *shortbeyond/package-lock.json, shortbeyond/package.json, shortbeyond/performance/data/usuarios.csv, shortbeyond/performance/insert-users.js, shortbeyond/performance/reports/spike.json, shortbeyond/performance/tests/spike.yaml, shortbeyond/playwright/support/services/database.js, shortbeyond/prompt-analise-performance-tests_section_3.md*
```

```
"bcrypt": "^6.0.0",
        "bcryptjs": "^3.0.3",
        "pg": "^8.23.0",
        "ulid": "^3.0.2"
    "node_modules/bcrypt": {
      "version": "6.0.0",
      "resolved": "https://registry.npmjs.org/bcrypt/-/bcrypt-6.0.0.tgz",
      "integrity": "sha512-cU8v/EGSrnH+HnxV2z0J7/blxH8gq7Xh2JFT6Aroax7UohdmiJJlxApMxtKfuI7z68NvvVcmR78k2L
bT6efhRg==",
      "dev": true,
      "hasInstallScript": true,
      "license": "MIT",
      "dependencies": {
        "node-addon-api": "^8.3.0",
        "node-gyp-build": "^4.8.4"
      },
      "engines": {
        "node": ">= 18"
      }
    },
    "node_modules/bcryptjs": {
      "version": "3.0.3",
      "resolved": "https://registry.npmjs.org/bcryptjs/-/bcryptjs-3.0.3.tgz",
      "integrity": "sha512-GlF5wPWnSa/X5LKM1o0wz0suXIINz1iHRLvTS+sLyi7XPbe5ycmYI3DlZqVGZZtDgl4DmasFg7gOB3
JYbphV5g==",
      "dev": true,
      "license": "BSD-3-Clause",
      "bin": {
        "bcrypt": "bin/bcrypt"
      }
    },
    "node_modules/node-addon-api": {
      "version": "8.9.2",
      "resolved": "https://registry.npmjs.org/node-addon-api/-/node-addon-api-8.9.2.tgz",
      "integrity": "sha512-VijLXbi3UACN69I0JVXJsX4tjACjNoQDgv2gTF6sx2wWEi8tkSg2eX8p5gSIFi8z2+DL3oHmY6OyKc
e38SDolg==",
      "dev": true,
      "license": "MIT",
// ... [6535 linhas omitidas para manter a legibilidade do PDF] ...
```

## Geral / Raiz do Projeto

### ■ 5.1-Movendo .gitignore

***Commit:*** *839a38a* | ***Data:*** *2026-08-25 18:37* | ***Arquivos:*** *.gitignore*

```
// (Nenhuma alteração de código ou apenas arquivos binários/deletados)
```

### ■ Merge pull request #1 from lfernandobra/section-2

***Commit:*** *572cc00* | ***Data:*** *2026-08-31 18:30* | ***Arquivos:*** *Nenhum*

```
// (Nenhuma alteração de código ou apenas arquivos binários/deletados)
```

### ■ chore: remove .DS_Store e .gitignore do versionamento

***Commit:*** *256015e* | ***Data:*** *2026-09-01 11:52* | ***Arquivos:*** *.DS_Store, .gitignore*

```
// (Nenhuma alteração de código ou apenas arquivos binários/deletados)
```