




# JAVA SEMINAR

DAY 10 - THE BAKERY



\* apprendre autrement

# JAVA SEMINAR

## Contents

- ✓ Contents
  - Exercise 01
    - \* Food
    - \* Bread
    - \* Drink - Sandwich - Dessert
  - Exercise 02
    - \* Menu
  - Exercise 03

You already know a lot about programming.

Let's put it all together today to create a simple program to manage a bakery shop.  
Everybody likes pastries.



## Exercise 01

**Delivery:** ./Food.java, ./Bread.java, ./FrenchBaguette.java, ./SoftBread.java, ./Drink.java, ./AppleSmoothie.java, ./Coke.java, ./Sandwich.java, ./HamSandwich.java, ./Panini.java, ./Dessert.java, ./Cookie.java, ./CheeseCake.java

First, create the food items.

### Food

---

Create a `Food` interface.

Add the `getPrice` (float) and `getCalories` (int) public methods to your interface.

### Bread

---

Create a `Bread` abstract class which implements `Food`.

This class must have a `price` and a `calories` attributes.

These two attributes must be passed as parameters to the constructor.

Your class must also have a `bakingTime` attribute (int). By default, it is set to 0.

Every attribute has a getter but no setter.

Now, create two classes `FrenchBaguette` and `SoftBread` which both inherit from `Bread`.

Their constructors take no parameters.

attribute	FrenchBaguette	SoftBread
price	0.80	1.20
calories	700	500
bakingTime	20	30

```
public class Example {  
    public static void main(String[] args) {  
        Food bread = new SoftBread();  
        System.out.println("The softbread costs " + bread.getPrice() + " euros and  
            contains " + bread.getCalories() + " calories.");  
    }  
}
```

```
Terminal  
T-JAV-500> java Example  
The softbread costs 1.2 euros and contains 500 calories.
```

## Drink - Sandwich - Dessert

---

Create three abstract classes named `Drink`, `Sandwich` and `Dessert` which all implements `Food`.

The `Drink` class must have a boolean attribute `aCan`, set to false by default, and his getter `isACan`.  
The `Sandwich` class has a boolean attribute `vegetarian`, also set to false by default.  
It also has a *List of String* which describes the `ingredients` of the sandwich.  
Each attribute should have its getter: `isVegetarian`, `getIngredients`.

Create the `AppleSmoothie` and the `Coke` classes, inherited from `Drink`, with the attributes:

attribute	AppleSmoothie	Coke
price	1.50	1.20
calories	431	105
aCan	false	true

Create the `HamSandwich` and the `Panini` classes, inherited from `Sandwich`, with the attributes:

attribute	HamSandwich	Panini
price	4.00	3.50
calories	230	120
vegetarian	false	true
ingredients	tomato salad cheese ham butter	tomato salad cucumber avocado cheese

Create the `Cookie` and the `CheeseCake` classes, inherited from `Dessert`, with the attributes:

attribute	Cookie	CheeseCake
price	0.90	2.10
calories	502	321



Sure, that's a lot of classes, but at least you have a good level of abstraction.

## Exercise 02

**Delivery:** `./Food.java`, `./Bread.java`, `./FrenchBaguette.java`, `./SoftBread.java`, `./Drink.java`, `./AppleSmoothie.java`, `./Coke.java`, `./Sandwich.java`, `./HamSandwich.java`, `./Panini.java`, `./Dessert.java`, `./Cookie.java`, `./CheeseCake.java`, `./Menu.java`, `./Breakfast.java`, `./Lunch.java`, `./AfternoonTea.java`

### Menu

---

Add a `Menu` generic abstract class which must have two attributes, `drink` and `meal`, of a templated type that implement `Food`. Every attribute has a getter but no setter.

It will also have a public `getPrice` function which returns a float representing the sum of the `drink` price and `meal` price, the total diminished by 10%.

Now create some real implementations of `Menu`, such as `Breakfast`, `Lunch` and `AfternoonTea`.

we should only be able to instantiate:

- ✓ a `Breakfast` with a `drink` subclass of `Drink` and a `meal` subclass of `Bread` ;
- ✓ a `Lunch` with a `drink` subclass of `Drink` and a `meal` subclass of `Sandwich` ;
- ✓ a `AfternoonTea` with a `drink` subclass of `Drink` and a `meal` subclass of `Dessert`.

## Exercise 03

**Delivery:** `./Food.java, ./Bread.java, ./FrenchBaguette.java, ./SoftBread.java, ./Drink.java, ./AppleSmoothie.java, ./Coke.java, ./Sandwich.java, ./HamSandwich.java, ./Panini.java, ./Dessert.java, ./Cookie.java, ./CheeseCake.java, ./Menu.java, ./Breakfast.java, ./Lunch.java, ./AfternoonTea.java, ./Stock.java, ./NoSuchFoodException.java, ./CustomerOrder.java`

Now you have your products to sell, you need a business logic to register the sales.

To do so, let's create the logic side of a cash register application (you can imagine that it will be linked to a GUI and used in a store). First, create a `Stock` class to register the stocks.

This class has `Map<Class<? extends Food>, Integer>` attribute to store the number of items for each type of food in a generic way.

Using the default constructor, each of the known food product of the stock should have 100 items.

It has various methods, such as:

- ✓ `int getNumberOf(Class<? extends Food>)` to retrieve the number of items for a specific food ;
- ✓ `boolean add(Class<? extends Food>)` to increment the counter by one ;
- ✓ `boolean remove(<?Class extends Food>)` to decrement the counter by one.

If the stock doesn't contain the food type given in parameter, these methods should throw a `NoSuchFoodException` exception containing the message `No such food type: [class name]`.



`add` and `remove` return `true` if the operation was successful.



Your stock can't go below 0!

Now, create a `CustomerOrder` class that contains the following methods:

- ✓ `boolean addItem(Food):`
  - returns whether it has been added or not ;
  - removes a food item from the stock ;
  - adds a food item to the order.

- ✓ `boolean removeItem(Food):`
  - returns false if the item wasn't in the order ;
  - removes a food item from the order ;
  - adds a food item to the stock.
- ✓ `float getPrice():`
  - returns the total price of the order.
- ✓ `boolean addMenu(Menu):`
  - add the menu to the order ;
  - returns true if the stock had enough items to make this menu ;
  - all the item composing the menu should be removed from the stock.
- ✓ `boolean removeMenu(Menu):`
  - removes the menu from the order.
- ✓ `void printOrder():`
  - pretty print the order.

```
public class Example {  
    public static void main(String args[]) {  
        Breakfast<AppleSmoothie, SoftBread> breakfast = new Breakfast<>(new AppleSmoothie  
            (), new SoftBread());  
        Food food = new Cookie();  
        Stock stock = new Stock();  
        CustomerOrder order = new CustomerOrder(stock);  
        try {  
            order.addItem(food);  
            order.addMenu(breakfast);  
        } catch (NoSuchFoodException e) {  
            System.out.println(e.getMessage());  
        }  
        order.printOrder();  
    }  
}
```

```
Terminal  
T-JAV-500> java Example  
Your order is composed of:  
- Breakfast menu (2.43 euros)  
-> drink: AppleSmoothie  
-> meal: SoftBread  
- Cookie (0.9 euros)  
For a total of 3.33 euros.
```





{EPITECH}  
LEARN DIFFERENT\*

\* apprendre autrement