Z3-Noodler - An Automata based String Solver Theory and Practice of SMT Solving

Luís Felipe Ramos Ferreira

► Fork of the Z3 theorem prover

- ► Fork of the Z3 theorem prover
- ► String theory solver replaced by *Noodler*

- ► Fork of the Z3 theorem prover
- ► String theory solver replaced by *Noodler*
 - Stabilization-based procedure

- ► Fork of the Z3 theorem prover
- ► String theory solver replaced by *Noodler*
 - Stabilization-based procedure
 - ► Heavy usage of non deterministic automata

► Hard task

- ► Hard task
- Mata library

- ► Hard task
- ► Mata library
 - ▶ Union, concatenation, intersection, etc

- ► Hard task
- Mata library
 - ▶ Union, concatenation, intersection, etc
- Very efficient and optimized

Architecture

lacktriangle Takes advantage of Z3's whole DPLL(\mathcal{T}) architecture

Architecture

- ightharpoonup Takes advantage of Z3's whole DPLL(\mathcal{T}) architecture
- ► Parser, rewriter and LIA solver

Architecture




Figure 1: Z3-Noodler architecture

► Axiom Saturation

- ► Axiom Saturation
- Decision Procedures

- Axiom Saturation
- Decision Procedures
- Preprocessing

- Axiom Saturation
- Decision Procedures
- Preprocessing
- Supoorted String Predicates and Limitations

► Goal: optimize the use of Z3's internal LIA solver

- ► Goal: optimize the use of Z3's internal LIA solver
- ► Happens during preprocessing (before SAT solver first assignment)

- Goal: optimize the use of Z3's internal LIA solver
- ► Happens during preprocessing (before SAT solver first assignment)
- $ightharpoonup len(t_1) >= 0, len(t_1.t_2) = len(t_1) + len(t_2)$

- Goal: optimize the use of Z3's internal LIA solver
- ► Happens during preprocessing (before SAT solver first assignment)
- \blacktriangleright $len(t_1) >= 0, len(t_1.t_2) = len(t_1) + len(t_2)$

► Goal: deal with string functions/predicates

- ► Goal: deal with string functions/predicates
- ➤ Saturates the original formula with an equivalent one composed of:

- ► Goal: deal with string functions/predicates
- Saturates the original formula with an equivalent one composed of:
 - Word (dis)equations

- ► Goal: deal with string functions/predicates
- Saturates the original formula with an equivalent one composed of:
 - Word (dis)equations
 - Regular constraints

- ► Goal: deal with string functions/predicates
- Saturates the original formula with an equivalent one composed of:
 - ► Word (dis)equations
 - Regular constraints
- ▶ ¬contains(s, "abc") becomes $s \notin \Sigma^*$ abc Σ^*

$$ightharpoonup zyx = xxz \land x \in a^* \land y \in a^+b^+ \land z \in b^*$$

- $ightharpoonup zyx = xxz \land x \in a^* \land y \in a^+b^+ \land z \in b^*$

- $ightharpoonup zyx = xxz \land x \in a^* \land y \in a^+b^+ \land z \in b^*$
- $ightharpoonup zy = z \wedge y \in a^+b^+ \wedge z \in b^*$
- ► Regular constraints enforce *UNSAT*

► Solves word (dis)equations with regular and length constraints

- Solves word (dis)equations with regular and length constraints
- ► For every variable, creates a NFA enconding regular contraints of the variable

- Solves word (dis)equations with regular and length constraints
- ► For every variable, creates a NFA enconding regular contraints of the variable
- Iteratively refines the NFA according to word equations until stability is achieved

- ► Solves word (dis)equations with regular and length constraints
- ► For every variable, creates a NFA enconding regular contraints of the variable
- Iteratively refines the NFA according to word equations until stability is achieved
- Stability: for every word equation $s_1 = s_2$, the language of the NFA of s_1 equals the language of the NFA of s_2

- ► Solves word (dis)equations with regular and length constraints
- ► For every variable, creates a NFA enconding regular contraints of the variable
- Iteratively refines the NFA according to word equations until stability is achieved
- Stability: for every word equation $s_1 = s_2$, the language of the NFA of s_1 equals the language of the NFA of s_2
- After stability, length constraints are added and fed to the LIA solver

Decision Procedures: Nielsen Transformation

► Efficient for quadratic equations

Decision Procedures: Nielsen Transformation

- Efficient for quadratic equations
- ▶ Creates a graph encoding the system and reason about it

Decision Procedures: Nielsen Transformation

- Efficient for quadratic equations
- Creates a graph encoding the system and reason about it
- Complex

Preprocessing

► Each DP aforementioned employs different preprocessing steps

Preprocessing

- ► Each DP aforementioned employs different preprocessing steps
- ► Simple unsatisfiable patterns are checked for early termination

Preprocessing

- ► Each DP aforementioned employs different preprocessing steps
- Simple unsatisfiable patterns are checked for early termination
- $ightharpoonup xy = zw \land len(x) = len(z) \implies y = w$

► replace, substr, at, indexof, prefix, suffix, contains

- ► replace, substr, at, indexof, prefix, suffix, contains
- ► Limited support for ¬contains

- replace, substr, at, indexof, prefix, suffix, contains
- ► Limited support for ¬contains
- Don't support replace_all and to/from_int

- replace, substr, at, indexof, prefix, suffix, contains
- ► Limited support for ¬contains
- Don't support replace_all and to/from_int
- Z3-Noodler is complete for the chain-free fragment with unbounded disequations, regular constraints and quadratic equations

- replace, substr, at, indexof, prefix, suffix, contains
- ► Limited support for ¬contains
- Don't support replace_all and to/from_int
- Z3-Noodler is complete for the chain-free fragment with unbounded disequations, regular constraints and quadratic equations
- Outside of this, the theory is sound but not complete

► Three sets of benchmarks: Regex, Equations and Predicates Small

- ► Three sets of benchmarks: Regex, Equations and Predicates Small
- ➤ Z3-Noodler is good in the *Regex* group in number of solved instances as well in average runtime

- ► Three sets of benchmarks: Regex, Equations and Predicates Small
- Z3-Noodler is good in the Regex group in number of solved instances as well in average runtime
- ▶ The same happens in the *Equations* group

- ► Three sets of benchmarks: Regex, Equations and Predicates Small
- Z3-Noodler is good in the Regex group in number of solved instances as well in average runtime
- ► The same happens in the *Equations* group
- cvc5 is the best one in *Predicates Small*, while Z3-Noodler performed poorly

- ► Three sets of benchmarks: Regex, Equations and Predicates Small
- Z3-Noodler is good in the Regex group in number of solved instances as well in average runtime
- ▶ The same happens in the *Equations* group
- cvc5 is the best one in *Predicates Small*, while Z3-Noodler performed poorly
- Z3-Noodler could, however, be further improved by proper axiom saturation for predicates or lazy predicate evaluation

The end

► Thanks!