

Pergunta 1

Correta

Pontuação
0,500

Destacar
pergunta

Write a regular expression that matches if the input **CONTAINS** a date in the format **YYYY-MM-DD**, where:

- **YYYY** is exactly four digits,
- **MM** is exactly two digits, and the first digit is either **0** or **1**,
- **DD** is exactly two digits, and the first digit is **0**, **1**, **2**, or **3**,

The date may appear **anywhere** in the input string.

Your answer should **consist of the regular expression only**, with no delimiters or quotes.

Por exemplo:

Teste	Resultado
["Today is 2024-05-28.", "1999-12-31 was New Year's Eve.", "The date 2024-5-8 is invalid.", "No date here.", "Ends with date 2024-07-20", "Start2023-01-01Middle"]	[true, true, false, false, true, true]

Resposta: (regime de penalização: 0 %)

\d{4}-(0[1-9]|1[0-2])-(0[1-9]|[12][0-9]|3[01])

Submeter

Pergunta 2

Correta

Pontuação
0,500

Destacar
pergunta

Write a regex that checks if the input **IS** a valid **postal code**. A postal code can either be in the format:

- **XXXX** (exactly 4 digits),
- or **XXXX-YYY** (4 digits, a hyphen, then exactly 3 digits),

where **X** and **Y** represent digits (**0-9**). For example, **"4100-123"** and **"5000"** are valid postal codes, but **"50000"** or **"4100-12a"** are not.

Your answer should **consist of the regular expression only**, with no delimiters or quotes.

Por exemplo:

Teste	Resultado
["4100-123", "5000", "1234-567", "123-4567", "abcd-123"]	[true, true, true, false, false]

Resposta: (regime de penalização: 0 %)

^\d{4}(-\d{3})?\$

Submeter

Pergunta 3

Por responder

Pontuação
2,000

🚩 Destacar
pergunta

Consider the following HTML and CSS codes:

```
<div id="main">
  <ul class="menu" data-type="primary">
    <li class="item active">Home</li>
    <li class="item">About</li>
    <li class="item special">Services</li>
  </ul>
</div>

li { color: black; }
.menu > li.active { color: blue; }
ul[data-type="primary"] li.item { color: green; }
#main li.item:nth-child(2) { color: red; }
.menu li.item.special:hover { color: purple; }
li.item:nth-child(2) { color: orange; }
```

During this exercise, don't forget to:

- Identify precisely **which elements** are targeted by each selector.
- Calculate the **specificity** of each selector.
- Take into consideration the **CSS inheritance** rules (cascading).

What will be the color of the `<li>` containing the text **ABOUT** when the **mouse pointer is on top of it**?

- ☒ a. red
- ☐ b. blue
- ☐ c. green
- ☐ d. purple
- ☐ e. black
- ☐ f. orange

Pergunta 4

Por responder

Pontuação
0,500

🚩 Destacar
pergunta

Which one of the following is the **semantically correct** tag to use for an element containing **ads** for other websites?

- ☐ a. <sidebar>
- ☒ b. <aside>
- ☐ c. <ads>
- ☐ d. <nav>

Pergunta 5

Correta

Pontuação
1,000

🚩 Destacar
pergunta

Write a PHP function named **drawAuthor** that receives an **associative array** with the following structure:

```
[
  'name' => 'Author Name',
  'birthYear' => 1950,
  'books' => [
    'Book Title 1',
    'Book Title 2',
    // ...
  ]
]
```

The function should print an HTML block containing:

- An **<h3>** element with the author’s name.
- A **<p>** paragraph with the text: "Born in {birthYear}".
- An **unordered list** with all book titles, each inside an element. For example, calling the function as:

```
drawAuthor([
  'name' => 'José Saramago',
  'birthYear' => 1922,
  'books' => [
    'Blindness',
    'The Gospel According to Jesus Christ'
  ]
]);
```

Should output the following HTML:

```
<h3>José Saramago</h3>
<p>Born in 1922</p>
<ul>
  <li>Blindness</li>
  <li>The Gospel According to Jesus Christ</li>
</ul>
```

Por exemplo:

Teste	Resultado
<pre>['name' => 'José Saramago', 'birthYear' => 1922, 'books' => ['Blindness', 'The Gospel According to Jesus Christ']]</pre>	<pre><h3>JoséSaramago</h3><p>Bornin1922</p>BlindnessTheGospelAcc</pre>

Resposta: (regime de penalização: 0 %)

Limpar resposta

```
<?php
function drawAuthor($author) {
echo "<h3>" . htmlspecialchars($author['name']) . "</h3>";
echo "<p>Born in " . htmlspecialchars($author['birthYear']) . "</p>";
echo "<ul>";
foreach ($author['books'] as $book) {
    echo "<li>" . htmlspecialchars($book) . "</li>";
}
echo "</ul>";
}
?>
```

Submeter

	Teste	Esperado
✓	['name' => 'José Saramago', 'birthYear' => 1922, 'books' => ['Blindness', 'The Gospel According to Jesus Christ']]	JoséSaramago Bornin1922 Blindness TheGo

Passou em todos os testes! ✓