

Formal Languages Homework 10

Liam Dillingham

April 29, 2019

1 Problem 9.1.1

What strings are:

1.1 w_{37} ?

37 in binary is 100101. then $1w = 100101$, so $w = 00101$.

1.2 w_{100} ?

100 in binary is 1100100. then $1w = 1100100$, so $w = 100100$.

2 Problem 9.2.1

Show that the halting problem, the set of (M, w) pairs such that M halts (with or without accepting) when given input w is r.e. but not recursive

For a given input w , the TM M must decide whether or not the string is in the language. Let L_u be the set of pairs of (M, w) such that M halts on w . By encoding M , then we can rename our set X to L_u , that is, $L_u(M, w) = \{(M, w) \mid M \text{ halts on } w\}$. Then $\overline{L_u}$ is the set of pairs of (M, w) such that M does *not* halt on w . If L_u is recursive, then all pairs of (M, w) are in L_u , since a recursive language always halts. However, $\overline{L_u}$ would have to be recursive as well, since the compliment of a recursive language must also be recursive. Yet $\overline{L_u}$ is precisely the language of the pairs of (M, w) which do not halt. Since a recursive language must halt eventually, then determining the set of pairs which halt is recursively enumerable, since determining which ones do not halt requires infinite computation.

3 Problem 9.2.2

Using *Ackermann's function*:

1. $A(0, y) = 1$ for any $y \geq 0$
2. $A(1, 0) = 2$
3. $A(x, 0) = x + 2$ for $x \geq 2$
4. $A(x + 1, y + 1) = A(A(x, y + 1), y)$ for any $x \geq 0$, and $y \geq 0$

3.1 a). Evaluate $A(2, 1)$

$A(2, 1) = A(1 + 1, 0 + 1)$ Rule #4 $\Rightarrow A(1 + 1, 0 + 1) = A(A(1, 0 + 1), 0)$
 $A(1 + 1, 0 + 1) = A(A(1, 0 + 1), 0) = A(A(1, 1), 0)$
 $A(1, 1) = A(0 + 1, 0 + 1) = A(A(0, 0 + 1), 0) = A(A(0, 1), 0)$
 $A(0, 1) = 1$. Now substitute
 $A(1, 1) = A(0 + 1, 0 + 1) = A(A(0, 1), 0) = A(1, 0) = 2$. And substituting again,
 $A(2, 1) = A(1 + 1, 0 + 1) = A(A(1, 0 + 1), 0) = A(A(1, 1), 0) = A(2, 0) = x + 2 = 4$

3.2 b). What function of x is $A(x, 2)$?

After running a python script I wrote, I got the answers for the following input:
 $A(0, 1) = 1$; $A(1, 1) = 2$; $A(2, 1) = 4$; $A(3, 1) = 6$; $A(4, 1) = 8$. In addition, the value of y does not affect the output of the function, it merely adds unnecessary complexity. By observation, we can see that the only variable in the entire rules list is x . Everything else is a constant. Thus the function of x is $2x$.

3.3 c). Evaluate $A(4, 3)$

Note to grader: I initially computed this by hand for some time, but after deriving the truth of the function, it is as simple as plugging in the x value
Using the derived function of x from the previous question, $A(4, 3) = 8$

```
import sys
sys.setrecursionlimit(8000)

def A(x, y):
```

```
    # rule 1
    if x == 0 and y >= 0:
        return 1

    # rule 2
    if x == 1 and y == 0:
        return 2

    # rule 3
    if x >= 2 and y == 0:
        return x + 2
```

```
# rule 4
if x >= 0 and y >= 0:
    x = x - 1
    y = y - 1

    return A(A(x, y + 1), y)

raise Exception('Something_terrible_happened!')

print(A(16,2))
```