

Overcoming Catastrophic Forgetting by augmenting clustering algorithm and Embedding NET

2021. 06. 24.

Sungkyunkwan Univ.

Yeongseok Yun

Contents


- ✓ Background and Motivation
- ✓ Previous Researches
- ✓ Research Objectives
- ✓ Experiments
- ✓ Future Work

Background and Motivation

A series of horizontal lines in teal and light blue colors, with varying lengths and offsets, creating a modern, layered effect across the middle of the slide.

Incremental Learning


Task 1 - train



개

고양이


Task 1 - test



개

고양이



Task 2 - train



사과

오렌지

Task 2 - test





개?

고양이?

사과

오렌지

Catastrophic forgetting




[1]

➤ Accuracy rate for training data is constantly decreasing over time and number of tasks.

Incremental Learning situation


- Data is constantly growing over time.
 - Data/class is subdivided based on research direction or market demand
 - Grant new tasks according to changed data/classes

ImageNet
22,000 classes




[2]

ImageNet
100,000 classes




Embedding NET : PCA

- Primal Component Analysis : One of dimensionality reduction technique




CNN's Feature distribution during learning




Previous Research

A decorative graphic consisting of several horizontal lines of varying lengths and colors (teal, light blue, and white) extending from the left side of the slide towards the right, positioned below the title.

EWC : Parameter regularization



[1]




$$L(\theta) = L_B(\theta) + \sum_i \frac{\lambda}{2} F_i (\theta_i - \theta_{A,i}^*)^2$$

$$F_i = \frac{1}{N} \sum_i \nabla \log(p_i | \theta) \nabla \log(p_i | \theta)^T$$


- It difficult to control the movement by filtering out exactly desired parameters.
- Performance is worse than ordinary neural network in Last task
 - Change of parameter is constrained

Knowledge Distillation



$$p_i = \frac{\exp(z_i)}{\sum_j \exp(z_j)}$$

$$\begin{bmatrix} \text{Bear} \\ \text{Cat} \\ \text{Dog} \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix}$$





$$p_i = \frac{\exp(\frac{z_i}{T})}{\sum_j \exp(\frac{z_j}{T})}$$

$$\begin{bmatrix} \text{Bear} \\ \text{Cat} \\ \text{Dog} \end{bmatrix} = \begin{bmatrix} 0.05 \\ 0.2 \\ 0.75 \end{bmatrix}$$

- It is difficult to outperform the teacher network's performance.

[3]

MBPA - Testing Setting



[4]


- Large memory module to store all training examples
- Vulnerable to negative transfer through local adaptation step
 - Negative Transfer : A phenomenon in which existing knowledge inappropriately influences learning new knowledge.

Research Objectives

A series of horizontal lines in teal and light blue colors, with varying lengths and offsets, creating a modern, layered effect across the middle of the slide.

Problem Statements


Learning
Previous Task




Embedding NET







Problem
Statements




Experience
Rehearsal




New Task
Training






Proposed
Method




Experience
Rehearsal



New Task
Training



Our goal : Moving Embedded Clusters(MEC)



➤ Preserve previous knowledge

➤ Restrict old cluster's moving during new task learning

$$➤ L_{old}^t = \sum_{j=0}^i (\text{mean}_j^{t-1} - \text{mean}_j^{ex})$$

➤ Adapting new knowledge

➤ Keep current cluster far away from old cluster's position on embedded space

$$➤ L_{cur}^t = -\sum_{j=0}^i (\text{mean}_j^{t-1} - \text{mean}_j^{cur})$$

Experiments

A series of horizontal lines in teal and light blue colors, some solid and some dashed, extending across the bottom of the slide.

Backbone Network : ResNet






Figure 2. Residual learning: a building block.

Embedding NET : Siamese Network

- Two images are utilized as inputs and return similarity between two features.
- Consequently, Siamese NET converts input data into embedding.
 - Usually used in pre-processing of Natural Language Processing



Dataset : CIFAR-10

- CIFAR-10 : 10 classes(5000 train images/class, 1000 test images/class), size(32*32)

airplane



automobile



bird



cat



deer




dog



frog



horse



ship



truck



Preliminary Results

- Accuracy upon testing data at the end of the learning task
 - Epoch : 60, Learning rate : 0.1
 - Backbone Network : ResNet-32
 - Baseline : Knowledge Distillation(KD) / Proposed Method : KD + MEC

KD

	Task 1	Task 2
Iter 1	79.4	
Iter 2	65.93	83.46
diff	13.47	-

KD + MEC
(proposed method)

	Task 1	Task 2
Iter 1	77.62	
Iter 2	65.62	85.16
diff	12.03	-

Future Work

A series of horizontal lines in teal and light blue colors, with varying lengths and offsets, creating a modern, layered effect across the middle of the slide.

Future work

- Validate robustness upon 3 or more tasks
- Force shape of feature distribution like cluster.
- Comparison of the cluster's state
 - e.g. KL-divergence
- Consider application : Contact point of pneumatic and parallel gripper grasping
 - 공압NET, 페러렐 NET
- Balancing old task and current one
 - Hyperparameter analysis

Thanks for your attention

A series of horizontal lines in teal and light blue colors, with varying lengths and offsets, creating a modern, layered effect across the middle of the slide.

Reference

1. Deng, Jia, et al. "Imagenet: A large-scale hierarchical image database." *2009 IEEE conference on computer vision and pattern recognition*. Ieee, 2009.
2. Kirkpatrick, James, et al. "Overcoming catastrophic forgetting in neural networks." *Proceedings of the national academy of sciences* 114.13 (2017): 3521-3526.
3. Hinton, Geoffrey, Oriol Vinyals, and Jeff Dean. "Distilling the knowledge in a neural network." *arXiv preprint arXiv:1503.02531* (2015).
4. Sprechmann, Pablo, et al. "Memory-based parameter adaptation." *arXiv preprint arXiv:1802.10542* (2018).