

25 YEARS ANNIVERSARY
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

HA NOI UNIVERSITY OF SCIENCE AND TECHNOLOGY
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY



HA NOI UNIVERSITY OF SCIENCE AND TECHNOLOGY
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

FUNDAMENTALS OF OPTIMIZATION

Modelling

CONTENT


- Optimization problems
- Modelling overview
- Examples

Optimization problems

- Maximize or minimize some function relative to some set (range of choices)
- The function represents the quality of the choice, indicating which is the “best”

Modelling overview

- Modelling consists of specifying
 - Decision variables
 - Constraints
 - Objective functions
- A problem can be modelled in different ways (how to define variables)
- Take into account the modelling languages of software tools
 - Constraint Programming solvers: constraints can be stated in flexible ways



Constraint linearization

Simplex method: $\text{I} \ L P \leq \text{II} \ L P \leq \boxed{\text{Linear Solver}}$

- Motivation

- Linear Programming solvers are very efficient

- Examples

- How to model $X = \min\{x_1, x_2\}$?

$$C: f(x_1, \dots, x_n)$$

$\Leftarrow P$ Linear form

$$t \leq a_1 x_1 + a_2 x_2 + \dots + a_n x_n \leq u$$

not linear.

Constraint linearization

- Motivation
 - Linear Programming solvers are very efficient
- Examples
 - How to model $X = \min\{x_1, x_2\}$?

$$X = \min\{x_1, x_2\}$$

$$\begin{cases} X \leq x_1 \\ X \leq x_2 \end{cases}$$

$$\begin{cases} X \geq x_1 \\ X \leq x_2 \end{cases}$$

{0, 1}

↓

Solution: define an auxiliary binary variable y , use big constant M

- $x_1 \geq X$
- $x_2 \geq X$
- $X \geq x_1 - M(1-y)$
- $X \geq x_2 - My$

$$\begin{cases} \text{if } y = 0 \\ X \geq x_1 - M(1-0) \\ X \geq x_2 - M \cdot 0 = x_2 \end{cases} \quad \checkmark$$

$$X = x_2.$$

$$\begin{cases} X \geq x_1 - M \cdot (1-1) \\ X \geq x_2 - M \cdot 1 \end{cases}$$

$$\begin{cases} y = 1 \Leftrightarrow \begin{cases} X \geq x_1 \\ X \geq x_2 - M \end{cases} \\ X = x_1 \end{cases}$$

Constraint linearization

Linear form -

$$x = 1$$

$$\{0, 1\}$$

- Examples

- How to model $(x = 1) \Rightarrow (z \geq y)$ where x is binary variable, y and z are real variables ?

Constraint linearization

- Examples

- How to model $(x = 1) \Rightarrow (z \geq y)$ where x is binary variable, y and z are real variables ?

each values of (x, y, z)

Solution: use big constant M

$$\boxed{M(x-1) + y \leq z}$$

$$M(0-1) + y \leq z \quad \checkmark \text{ True}$$

$$M(1-1) + y \leq z$$

$$M \cdot 0 + y \leq z$$

$$\boxed{y \leq z}$$

if $x = 1$,

$\boxed{z \geq y}$ must be True

each value (x, y, z)

Constraint linearization

- Example

- ~~$(x > 0) \Rightarrow (z \geq y)$~~ in which x , y and z are real variables (and $x \geq 0$) ?

$$\left(\frac{x}{|x|} - 1 \right) M + y S z$$

$x = 0, y = 10^6, z = 1$

$$C_1 \Rightarrow C_2$$

\downarrow

$$(x_1 \dots x_n)$$

$$\underline{z \geq y + M(1-x)}$$

$$\begin{aligned} z &\geq y + Mx + N \\ Mx + y - z &\geq 0 \end{aligned}$$

$$Mx\cancel{+}y - z \geq 0$$

$$Mx\cancel{+}y - z \geq 0$$

$$\left(\begin{array}{l} x=0, \\ y=2, \\ z=3 \end{array} \right)$$

on-tools

[0, . . .]

$$l_1 \{ a_1 x_1 + a_2 x_2 - \underline{a_n x_n} \leq u$$

$$\boxed{x*(y-z) > 0}$$

$$z \geq y - Mx$$

$$z \geq y - M \cdot x$$

$$\begin{cases} x = 1 \\ y = 10, z = 2 \end{cases}$$

$$\frac{M(x+x_2) + y}{M(1+0.5)} + 2 \leq 3$$

$$\begin{array}{r} \cancel{z \geq y - M_1 x - N} \\ \hline \cancel{2 \geq 3 - M_1} = N \end{array}$$

$$z \geq y - N$$
$$1 \geq 10^6 - N$$



Constraint linearization

- Example


- $(x > 0) \Rightarrow (z \geq y)$ in which x , y and z are real variables (and $x \geq 0$) ?

Solution:

- Let M be a very big constant,
- Introduce a binary variable $t \in \{0,1\}$:
 - $t = 1$ indicates that $x > 0$, and $t = 0$ indicates that $x = 0$
- Equivalent linear constraints
 - $x \leq M.t$
 - $z + (1-t)M \geq y$
 - $x \geq t/M$

Balanced Course Assignment Problem

- At the beginning of the semester, the head of a computer science department D have to assign courses to teachers in a balanced way. The department D has m teachers $T=\{0, 1, \dots, m-1\}$ and n courses $C=\{0, 1, \dots, n-1\}$.
 - Each teacher $t \in T$ has a preference list which is a list of courses he/she can teach depending on his/her specialization. The preference information is represented by a $0-1$ matrix $A_{m \times n}$ in which $A(t,c) = 1$ indicates that teacher t can teach the course c and $A(t,c) = 0$, otherwise
 - We know a set B of pairs of conflicting two courses that cannot be assigned to the same teacher as these courses have been already scheduled in the same slot of the timetable. (i, j)
 - The load of a teacher is the number of courses assigned to her/him. How to assign n courses to m teacher such that each course assigned to a teacher is in his/her preference list, no two conflicting courses are assigned to the same teacher, and the maximal load among teachers is minimal.



Balanced Course Assignment Problem

- Example

Course	0	1	2	3	4	5	6	7	8	9	10	11	12
credits	3	3	4	3	4	3	3	3	4	3	3	4	4

Teachers	Preference Courses
0	0, 2, 3, 4, 8, 10
1	0, 1, 3, 5, 6, 7, 8
2	1, 2, 3, 7, 9, 11, 12

Conflicting courses

0	2
0	4
0	8
1	4
1	10
3	7
3	9
5	11
5	12
6	8
6	12

Balanced Course Assignment Problem

- Example

Course	0	1	2	3	4	5	6	7	8	9	10	11	12
credits	3	3	4	3	4	3	3	3	4	3	3	4	4

Teachers	Preference Courses
0	0, 2, 3, 4, 8, 10
1	0, 1, 3, 5, 6, 7, 8
2	1, 2, 3, 7, 9, 11, 12

Conflicting courses

0	2
0	4
0	8
1	4
1	10
3	7
3	9
5	11
5	12
6	8
6	12

Teacher	Assigned courses	Load
0	2, 4, 8, 10	15
1	0, 1, 3, 5, 6	15
2	7, 9, 11, 12	14

Balanced Course Assignment: CP model

- Decision variables
 - $X(i)$: teacher assigned to course i , $\forall i \in C$, domain $D(X(i)) = \{t \in T \mid A(t,i) = 1\}$
 - $Y(i)$: load of teacher i , domain $D(Y(i)) = \{0, 1, \dots, n-1\}$
 - Z : maximum load among teachers
- Constraints
 - $X(i) \neq X(j), \forall (i,j) \in B$
 - $Y(i) = \sum_{j \in C} (X(j) = i), \forall i \in T$
 - $Z \geq Y(i), \forall i \in T$
- Objective function to be minimized: Z

CP control.

Balanced Course Assignment: ILP model

- Decision variables

- $X(i,j) = 1$: teacher i is assigned to course j , and $X(i,j) = 0$, otherwise,
 $\forall i \in T, j \in C$, domain $D(X(i,j)) = \{0,1\}$
- $Y(i)$: load of teacher i , domain $D(Y(i)) = \{0,1,\dots,n\}$
- Z : maximum load among teachers

- Constraints

- $\sum_{i \in T} X(i,j) = 1, \forall j \in C$
- $X(t,i) + X(t,j) \leq 1, \forall (i,j) \in B, t \in T$
- $Y(i) = \sum_{j \in C} X(i,j), \forall i \in T$
- $Z \geq Y(i), \forall i \in T$

- Objective function to be minimized: Z

$$f(x, y, z) = z \rightarrow \min$$

X	0	1	2	3	4	5
0	1	0	0	0	0	0
1	0	1	1	0	1	0
2	1	0	0	1	0	0
3	0	1	0	0	0	1


Travelling Salesman Problem (TSP)

- A salesman departs from point 1, visiting $N-1$ points $2, \dots, N$ and comes back to the point 1. The travelling distance from point i and point j is $d(i,j)$, $i,j = 1,\dots,N$. Compute the route of minimal total travelling distance

Travelling Salesman Problem (TSP)

- Decision variables

- Binary variable $X(i,j) = 1$ if the route traverses from point i to point j , and $X(i,j) = 0$, otherwise.




- Constraints

- $\sum_{j=1}^N X(i,j) = \sum_{j=1}^N X(j,i) = 1, \forall i \in \{1, 2, \dots, N\}$

- $\sum_{(i,j) \in S} X(i,j) \leq |S| - 1, \forall S \subseteq \{1, 2, \dots, N\} \text{ and } |S| < N$ SEC

- Objective function to be minimized



$$f(X) = \sum_{j=1}^N \sum_{i=1}^N d(i,j) X(i,j)$$



Capacitated Vehicle Routing

- A fleet of K trucks $1, 2, \dots, K$ must be scheduled to visit N customers $1, 2, \dots, N$ for collecting items
 - Customer i located at point i and requests to be collected $r(i)$ items, $i = 1, 2, \dots, N$
 - Truck k ($k = 1, \dots, K$)
 - Departs from point $N+k$ and terminates at point $N + K + k$ ($N+k$ and $N+K+k$ might refer to the central depot)
 - has capacity $c(k)$ which is the maximum number of items it can carry at a time \rightarrow *Ton trung*.
 - Travel distance from point i to point j is $d(i,j)$, $i, j = 1, \dots, N + 2K$
- Compute the delivery solution such that the total travelling distance is minimal
 - Satisfy capacity constraints
 - Each customer is visited exactly once by exactly one truck



Capacitated Vehicle Routing Problem



$K = 2, N = 4$ feasible



	1	2	3	4	5	6	7	8
1	0	2	3	4	3	3	3	3
2	4	0	2	6	1	1	1	1
3	2	4	0	2	1	1	1	1
4	5	7	7	0	4	4	4	4
5	3	1	5	7	0	0	0	0
6	3	1	5	7	0	0	0	0
7	3	1	5	7	0	0	0	0
8	3	1	5	7	0	0	0	0



Capacitated Vehicle Routing Problem

- Notations

~~graph~~

~~Opt~~

~~h+k-1~~

Model ?


TSP

F

N, K, d
 c, r

- $B = \{1, \dots, N+2K\}$
- $F_1 = \{(i, k+N) \mid i \in B, k \in \{1, \dots, K\}\}$
- $F_2 = \{(k+N, i) \mid i \in B, k \in \{1, \dots, K\}\}$
- $F_3 = \{(i, i) \mid i \in B\}$
- $A = B^2 \setminus F_1 \setminus F_2 \setminus F_3$
- $A^+(i) = \{j \mid (i, j) \in A\}, A^-(i) = \{j \mid (j, i) \in A\}$



i




ILP model.

decision variables (i, j)
constraints

objective function.



- Variables :
- $X(k, i, j) \in \{0, 1\}$
 - $\gamma(i)$: số items tích lũy trên route
 - $z(i)$: chi tiêu của xe di qua điểm i ($1, \dots, K$)




Constraints : Balance flow constraints

- $\sum_{k=1}^K \sum_{j \in A^+(i)} X(k, i, j) = \sum_{k=1}^K \sum_{j \in A^-(i)} X(k, i, j) \quad \forall i \in \{1, \dots, N\}$
 - $\sum_{j \in A^+(i)} X(k, i, j) = \sum_{j \in A^-(i)} X(k, i, j) \quad \forall i \in \{1, \dots, N\}$
 - $\sum_{j=1}^N X(k, k+N, j) = \sum_{j=1}^N X(k, j, k+K+N) = 1, \quad \forall k \in \{1, \dots, K\}$
 - $Y(k+K+N) \leq c(k), \quad \forall k \in \{1, \dots, K\}$
 - $z(k+N) = z(k+K+N) = k, \quad \forall k \in \{1, \dots, K\}$
 - $M(1 - X(k, i, j)) + Y(j) \geq Y(i) + r(j) \quad \forall k, i, j$
 - $M(X(k, i, j) - 1) + Y(j) \leq Y(i) + r(j)$
 - $M(1 - X(k, i, j)) + z(j) \geq z(i) \quad \forall k, i, j$
 - $M(X(k, i, j) - 1) + z(j) \leq z(i) \quad \forall k, i, j$
- Objective
- $$\sum_{k=1}^K \sum_{(i,j) \in A} d(i,j) \times X(k, i, j) \rightarrow \min$$

MultiCast Routing Problem

- Given a network $V = \{1, \dots, N\}$ is the set of nodes, $E \subseteq V^2$ is the set of links between nodes. A node $s \in V$ is the source node which will transmit a package to others nodes. A node receiving the package can continue transmitting this package to adjacent nodes.
 - $t(i,j)$ and $c(i,j)$ are transmission time and transmission cost when transmitting the package from node i to node j
- Compute the set of links used for broadcasting the package from the source node to all other nodes such that
 - Total transmission time from s to any node cannot exceed a given value L
 - Total transmission cost is minimal



Facility Location

- There are M sites 1, 2, ..., M that can be used to open facility for servicing N customers 1, 2, ..., N .
 - $f(i)$ is the cost for opening the site i
 - $Q(i)$ is the capacity of site i (maximum amount of good it can serve customers)
 - $c(i,j)$ is the cost for transporting unit of good from site i to customer j
 - $d(j)$ is the total demand (amount of goods) of customer j
- Compute a planning (which site to be opened and amount of good each opened site serves a customer) such that
 - Capacity constraint is satisfied
 - Total cost is minimal



25
YEARS ANNIVERSARY
SOICT

VIỆN CÔNG NGHỆ THÔNG TIN VÀ TRUYỀN THÔNG
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

**Thank you
for your
attentions!**

