

The Complexity of Verifying Boolean Programs as Differentially Private

Ludmila Glinskih

Joint work with Mark Bun and Marco Gaboardi

CSF 2022

Haifa, Israel

August 10, 2022

Plan of the talk


1. Prior work

- How hard is it to verify whether a program is DP for
 - Turing-complete languages
 - Boolean languages with bounded memory without loops

2. Our results and proof ideas

- BPWhile: Boolean language with loops and finite memory
- PSPACE-completeness of verifying DP for BPWhile
- PSPACE-hardness: reduction from TQBF
- PSPACE algorithm based on computing hitting probabilities in a Markov chain


Differential Privacy



C is (ϵ, δ) -differentially private if for every set of possible outputs O , and for every neighboring x, x' :

$$P[C(x) \in O] \leq e^\epsilon \cdot P[C(x') \in O] + \delta$$


Differential Privacy



C is (ϵ, δ) -differentially private if for every set of possible outputs O , and for every neighboring x, x' :

$$P[C(x) \in O] \leq e^\epsilon \cdot P[C(x') \in O] + \delta$$

Differential Privacy




C is (ϵ, δ) -differentially private if for every set of possible outputs O , and for every neighboring x, x' :

$$P[C(x) \in O] \leq e^\epsilon \cdot P[C(x') \in O] + \delta$$


Neighboring relation we consider:

- Inputs are bit strings which differ in one bit
- Can be extended to any bounded polyspace computable relation

Verification of Differential Privacy




Verification of Differential Privacy



Complexity of verification depends on the expressivity of the language used to implement A:

Verification of Differential Privacy




Complexity of verification depends on the expressivity of the language used to implement A:

- Undecidable for languages working with infinite data
 - Undecidable for Turing-complete languages

[Barthe, Chadha, Jagannath, Sistla, Viswanathan'20]

Verification of Differential Privacy



Complexity of verification depends on the expressivity of the language used to implement A:

- Undecidable for languages working with infinite data
 - Undecidable for Turing-complete languages

[Barthe, Chadha, Jagannath, Sistla, Viswanathan'20]

- For a simple Boolean language with **bounded memory**, if statements and **random assignments**, but **without loops**
 - $coNP^{\#P}$ -completeness for $(\epsilon, 0)$ -DP
 - Reduction from All-Min-SAT
 - $coNP^{\#P}$ -hard and in $coNP^{\#P^{\#P}}$ for (ϵ, δ) -DP

[Gaboardi, Nissim, Purser'20]

Verification of DP: Black box vs White box

Complexity also depends on the type of access to the code:

Verification of DP: Black box vs White box

Complexity also depends on the type of access to the code:

- **Black box:** no information about the algorithm, query access
 - Impossible to verify $(\epsilon, 0)$ -DP

[Gilbert, McMillan'19]

Verification of DP: Black box vs White box

Complexity also depends on the type of access to the code:

- **Black box:** no information about the algorithm, query access
 - Impossible to verify $(\epsilon, 0)$ -DP
- **White box:** full access to the code/representation:
 - Linear-time algorithm in the size of automaton
 - For pure-DP

[Gilbert, McMillan'19]

[Chadha, Sistla, Viswanathan'21]

Verification of DP: Black box vs White box

Complexity also depends on the type of access to the code:

- **Black box:** no information about the algorithm, query access
 - Impossible to verify $(\epsilon, 0)$ -DP
- **White box:** full access to the code/representation:
 - Linear-time algorithm in the size of automaton
 - For pure-DP
 - #P-hardness for approximating parameters in labelled Markov chains
 - For approximate-DP
 - Undecidable to compute exactly

[Gilbert, McMillan'19]

[Chadha, Sistla, Viswanathan'21]

[Chistikov, Murawski, Purser'19]

Verification of DP: Black box vs White box

Complexity also depends on the type of access to the code:

- **Black box:** no information about the algorithm, query access
 - Impossible to verify $(\epsilon, 0)$ -DP
- **White box:** full access to the code/representation:
 - Linear-time algorithm in the size of automaton
 - For pure-DP
 - #P-hardness for approximating parameters in labelled Markov chains
 - For approximate-DP
 - Undecidable to compute exactly

[Gilbert, McMillan'19]

[Chadha, Sistla, Viswanathan'21]

[Chistikov, Murawski, Purser'19]

In this work: **white-box** model, full access to the code

BPWhile: Boolean language with While loops

We design a language to meet the following goals:

- Captures classical computations on real computers
- Simple to analyze

BPWhile: Boolean language with While loops

We design a language to meet the following goals:

- Captures classical computations on real computers
- Simple to analyze

$x ::= [a - z]^+$ Variable identifiers

BPWhile: Boolean language with While loops

We design a language to meet the following goals:

- Captures classical computations on real computers
- Simple to analyze

$x ::= [a - z]^+$ Variable identifiers

$b ::= \text{true} \mid \text{false} \mid \text{random} \mid x \mid b \wedge b \mid b \vee b \mid !b$

Boolean expressions

BPWhile: Boolean language with While loops

We design a language to meet the following goals:

- Captures classical computations on real computers
- Simple to analyze

$x ::= [a - z]^+$ Variable identifiers

$b ::= \text{true} \mid \text{false} \mid \text{random} \mid x \mid b \wedge b \mid b \vee b \mid !b$ Boolean expressions

$c ::= \text{skip} \mid x := b \mid c; c \mid \text{if } b \text{ then } c \text{ else } c \mid \text{while } b \text{ then } c$ Commands

BPWhile: Boolean language with While loops

We design a language to meet the following goals:

- Captures classical computations on real computers
- Simple to analyze

$x ::= [a - z]^+$ Variable identifiers

$b ::= \text{true} \mid \text{false} \mid \text{random} \mid x \mid b \wedge b \mid b \vee b \mid !b$ Boolean expressions

$c ::= \text{skip} \mid x := b \mid c; c \mid \text{if } b \text{ then } c \text{ else } c \mid \text{while } b \text{ then } c$ Commands

$t ::= x \mid t, x$ List of Boolean variables

BPWhile: Boolean language with While loops

We design a language to meet the following goals:

- Captures classical computations on real computers
- Simple to analyze

$x ::= [a - z]^+$ Variable identifiers

$b ::= \text{true} \mid \text{false} \mid \text{random} \mid x \mid b \wedge b \mid b \vee b \mid !b$ Boolean expressions

$c ::= \text{skip} \mid x := b \mid c; c \mid \text{if } b \text{ then } c \text{ else } c \mid \text{while } b \text{ then } c$ Commands

$t ::= x \mid t, x$ List of Boolean variables

$p ::= \text{input}(t); c; \text{return}(t)$ Programs

BPWhile: Boolean language with While loops

We design a language to meet the following goals:

- Captures classical computations on real computers
- Simple to analyze

$x ::= [a - z]^+$

Variable identifiers

$b ::= \text{true} \mid \text{false} \mid \text{random} \mid x \mid b \wedge b \mid b \vee b \mid !b$

Boolean expressions

$c ::= \text{skip} \mid x := b \mid c; c \mid \text{if } b \text{ then } c \text{ else } c \mid \textbf{while } b \textbf{ then } c$

Commands

$t ::= x \mid t, x$

List of Boolean variables

$p ::= \text{input}(t); c; \text{return}(t)$

Programs

Numbers of variables and input bits are fixed in the definition of the program

⇒ Length of the program is an upper bound on the size of the memory that the program uses

Example of a BPWhile program:

```
0.  input( $\vec{c}, \epsilon$ );
1.   $\vec{k} := \lceil \log(2/\epsilon) \rceil$ ;
2.   $\vec{d} := (2^{\vec{k}+1} + 1)(2^{\vec{k}} + 1)^{n-1}$ ;
3.   $\vec{u} := \text{uniform}(0, \vec{d}]$ ;
4.   $\vec{z} := 0$ ;
5.   $\vec{r} := n$ ;
6.  while  $\vec{z} < \vec{n} \wedge \vec{r} = n$  then
7.    if  $\vec{z} < \vec{c}$  then
8.      if  $\vec{u} \leq 2^{\vec{k}(\vec{c}-\vec{z})}(2^{\vec{k}} + 1)^{n-(\vec{c}-\vec{z})}$ 
9.        then  $\vec{r} := \vec{z}$ 
10.     else skip
11.   else
12.     if  $\vec{u} \leq d - 2^{\vec{k}(\vec{z}-\vec{c}+1)}(2^{\vec{k}} + 1)^{n-1-(\vec{z}-\vec{c})}$ 
13.       then  $\vec{r} := \vec{z}$ 
14.     else skip
15.    $\vec{z} = \vec{z} + 1$ ;
16. return( $\vec{z}$ );
```

Implementation of the Bounded
Geometric Mechanism in finite
precision arithmetic

[Ghosh, Roughgarden,
Sundararajan'09]

[Balcer, Vadhan'17]

Our results

Main result: if A is a BPWhile program, then the problem of verifying whether A is differentially private is PSPACE-complete.

Our results


Main result: if A is a BPWhile program, then the problem of verifying whether A is differentially private is PSPACE-complete.

It holds for the following notions of differential privacy:

- $(\epsilon, 0)$ -DP
- (ϵ, δ) -DP
- (ϵ, δ) -DP parameters approximation
- Renyi-DP
- Zero-Concentrated-DP
- Truncated Concentrated-DP

PSPACE-completeness


PSPACE-completeness of a problem A implies:



PSPACE-completeness

PSPACE-completeness of a problem A implies:


- A is solvable by a TM that uses polynomial space



PSPACE-completeness

PSPACE-completeness of a problem A implies:


- A is solvable by a TM that uses polynomial space
- A is solvable in exponential time



PSPACE-completeness

PSPACE-completeness of a problem A implies:


- A is solvable by a TM that uses polynomial space
- A is solvable in exponential time
- A is at least as hard as any problem solvable in polyspace



PSPACE-completeness

PSPACE-completeness of a problem A implies:

- A is solvable by a TM that uses polynomial space
- A is solvable in exponential time
- A is at least as hard as any problem solvable in polyspace
- No polytime algorithm for A , unless $P = PSPACE$
 - That is widely believed not to be true




PSPACE-completeness

PSPACE-completeness of a problem A implies:

- A is solvable by a TM that uses polynomial space
- A is solvable in exponential time
- A is at least as hard as any problem solvable in polyspace
- No polytime algorithm for A , unless $P = PSPACE$
 - That is widely believed not to be true

To show PSPACE completeness we need:




PSPACE-completeness

PSPACE-completeness of a problem A implies:

- A is solvable by a TM that uses polynomial space
- A is solvable in exponential time
- A is at least as hard as any problem solvable in polyspace
- No polytime algorithm for A , unless $P = PSPACE$
 - That is widely believed not to be true

To show PSPACE completeness we need:

1. Show hardness: construct sequence of reductions from TQBF




PSPACE-completeness

PSPACE-completeness of a problem A implies:


- A is solvable by a TM that uses polynomial space
- A is solvable in exponential time
- A is at least as hard as any problem solvable in polyspace
- No polytime algorithm for A, unless $P = PSPACE$
 - That is widely believed not to be true

To show PSPACE completeness we need:


1. Show hardness: construct sequence of reductions from TQBF
2. Construct polynomial-space algorithm: analyze Markov chain based on the state graph of the program




PSPACE-hardness




PSPACE-hardness




PSPACE-hardness



Polyspace membership: algorithm for $(\epsilon, 0)$ -DP



Polyspace membership: algorithm for $(\epsilon, 0)$ -DP



PSPACE membership: state graph

State graph depends on the input values

D(b=1):


```
1. input(b);  
2. if b == 1 then  
3.     r = rand();  
4.     if r == 0 then  
5.         while true  
6.             skip;  
7.     else skip;  
8. else skip;  
9. return(1)
```

PSPACE membership: state graph

State graph depends on the input values

D(b=1):

```
1. input(b);  
2. if b == 1 then  
3.     r = rand();  
4.     if r == 0 then  
5.         while true  
6.             skip;  
7.     else skip;  
8. else skip;  
9. return(1)
```




PSPACE membership: state graph

State graph depends on the input values

D(b=1):

```
1. input(b);  
2. if b == 1 then  
3.     r = rand();  
4.     if r == 0 then  
5.         while true  
6.             skip;  
7.     else skip;  
8. else skip;  
9. return(1)
```




PSPACE membership: state graph

State graph depends on the input values

D(b=1):

```
1. input(b);  
2. if b == 1 then  
3.     r = rand();  
4.     if r == 0 then  
5.         while true  
6.             skip;  
7.     else skip;  
8. else skip;  
9. return(1)
```




PSPACE membership: state graph

State graph depends on the input values

D(b=1):


```
1. input(b);  
2. if b == 1 then  
3.     r = rand();  
4.     if r == 0 then  
5.         while true  
6.             skip;  
7.     else skip;  
8. else skip;  
9. return(1)
```



PSPACE membership: state graph

D(b=0):


```
1. input(b);  
2. if b == 1 then  
3.     r = rand();  
4.     if r == 0 then  
5.         while true  
6.             skip;  
7.     else skip;  
8. else skip;  
9. return(1)
```



PSPACE membership: algorithm for $(\epsilon, 0)$ -DP

For a program D and all neighboring inputs x, x' :

- Construct the Markov chain for $D(x)$ and $D(x')$
- Compute and compare hitting probabilities




PSPACE membership: algorithm for $(\epsilon, 0)$ -DP

For a program D and all neighboring inputs x, x' :

- Construct the Markov chain for $D(x)$ and $D(x')$
- Compute and compare hitting probabilities

Problem: Markov chain has exp-many states \Rightarrow cannot store it explicitly




PSPACE membership: algorithm for $(\epsilon, 0)$ -DP

For a program D and all neighboring inputs x, x' :

- Construct the Markov chain for $D(x)$ and $D(x')$
- Compute and compare hitting probabilities

Problem: Markov chain has exp-many states \Rightarrow cannot store it explicitly

Need **space-efficient** algorithm for computing hitting probabilities with **implicit access** to the Markov chain



Polyspace algorithm for computing hitting probabilities in a Markov chain

Lemma [Simon'81]: If M is a Markov chain with at most 2^L states

- the initial distribution places all mass on one state,
- there is a set F of final states each with only one self-transition,
- every non-final state has outgoing transition probability 0 or $\frac{1}{2}$.

Then there is an $O(L^6)$ -space deterministic algorithm that computes the hitting probability of every state in F .

Polyspace algorithm for computing hitting probabilities in a Markov chain

Lemma [Simon'81]: If M is a Markov chain with at most 2^L states

- the initial distribution places all mass on one state,
- there is a set F of final states each with only one self-transition,
- every non-final state has outgoing transition probability 0 or $\frac{1}{2}$.

Then there is an $O(L^6)$ -space deterministic algorithm that computes the hitting probability of every state in F .

Note: to use the algorithm, we need to replace all transitions labelled by 1 in the state graph of the BPWhile program:

Polyspace algorithm for computing hitting probabilities in a Markov chain


Lemma [Simon'81]: If M is a Markov chain with at most 2^L states

- the initial distribution places all mass on one state,
- there is a set F of final states each with only one self-transition,
- every non-final state has outgoing transition probability 0 or $\frac{1}{2}$.

Then there is an $O(L^6)$ -space deterministic algorithm that computes the hitting probability of every state in F .

Note: to use the algorithm, we need to replace all transitions labelled by 1 in the state graph of the BPWhile program:

- Clone all states
- For each state a with outgoing edge w.p. 1 replace it by two edges:
 - Edge (a,b) with weight $\frac{1}{2}$ to original state
 - Edge (a,b') with weight $\frac{1}{2}$ to the clone-state b' of b



PSPACE membership: exponentially long numbers


For a program D

for all neighboring inputs x, x' :

- Construct the Markov chain for $D(x)$ and $D(x')$
- Compare hitting probabilities of the final states with the same values

Problem:

Markov chain has exp -many states



PSPACE membership: exponentially long numbers


For a program D

for all neighboring inputs x, x' :

- Construct the Markov chain for $D(x)$ and $D(x')$
- Compare hitting probabilities of the final states with the same values

Problem:

Markov chain has exp -many states
 \Rightarrow hitting probabilities can be as small as $\frac{1}{2^{exp}}$



PSPACE membership: exponentially long numbers

For a program D


for all neighboring inputs x, x' :

- Construct the Markov chain for $D(x)$ and $D(x')$
- Compare hitting probabilities of the final states with the same values

Problem:

Markov chain has exp -many states
 \Rightarrow hitting probabilities can be as small as $\frac{1}{2^{exp}}$

\Rightarrow numbers are exponentially long



Operations with exponentially long numbers

$$\begin{array}{cccccccccc} 1 & 0 & 1 & 1 & 1 & \dots & 1 & 0 & 0 & 1 \\ + & 0 & 0 & 1 & 0 & 1 & \dots & 1 & 1 & 1 & 1 \\ \hline 1 & 1 & 1 & 0 & 1 & \dots & 1 & 0 & 0 & 0 \end{array}$$

Operations with exponentially long numbers

$$\begin{array}{cccccccccc} 1 & 0 & 1 & 1 & 1 & \dots & 1 & 0 & 0 & 1 \\ + & 0 & 0 & 1 & 0 & 1 & \dots & 1 & 1 & 1 & 1 \\ \hline 1 & 1 & 1 & 0 & 1 & \dots & 1 & 0 & 0 & 0 \end{array}$$

Uniform family of log-depth circuits:

- One logspace algorithm provides implicit access to the circuits
- Each circuit has log-depth and poly size

Operations with exponentially long numbers

$$\begin{array}{r} \begin{array}{|c|c|c|c|c|c|c|c|c|c|} \hline 1 & 0 & 1 & 1 & 1 & \dots & 1 & 0 & 0 & 1 \\ \hline \end{array} \\ + \\ \begin{array}{|c|c|c|c|c|c|c|c|c|c|} \hline 0 & 0 & 1 & 0 & 1 & \dots & 1 & 1 & 1 & 1 \\ \hline \end{array} \\ \hline \begin{array}{|c|c|c|c|c|c|c|c|c|c|} \hline 1 & 1 & 1 & 0 & 1 & \dots & 1 & 0 & 0 & 0 \\ \hline \end{array} \end{array}$$

Uniform family of log-depth circuits:


- One logspace algorithm provides implicit access to the circuits
- Each circuit has log-depth and poly size

Lemma:


Uniform families of log-depth circuits exist for:

- Comparison
- Addition
- Multiplication by a fixed rational number
- Multiplication [Ofman'62]
- Square roots [Reif'86]


Polyspace membership algorithm for $(\epsilon, 0)$ -DP




Polyspace membership algorithm for $(\epsilon, 0)$ -DP



Polyspace membership algorithm for $(\epsilon, 0)$ -DP



Polyspace membership algorithm for $(\epsilon, 0)$ -DP



Results and future work

- We showed PSPACE-completeness for the problems of checking:
 - Pure-DP
 - Approximate-DP
 - Gap-RDP
 - Gap-zCDP
 - Gap-TCDP

Results and future work

- We showed PSPACE-completeness for the problems of checking:
 - Pure-DP
 - Approximate-DP
 - Gap-RDP
 - Gap-zCDP
 - Gap-TCDP
- Possibly can extend the result to show PSPACE-completeness of verifying accuracy

Results and future work

- We showed PSPACE-completeness for the problems of checking:
 - Pure-DP
 - Approximate-DP
 - Gap-RDP
 - Gap-zCDP
 - Gap-TCDP
- Possibly can extend the result to show PSPACE-completeness of verifying accuracy
- Improve the exact polynomial in the space complexity of the algorithm
 - Improved analysis and more efficient algorithms for Markov chains analysis and long-numbers arithmetic operations are needed for tighter results

