BFS: An R package to Search and Download Swiss Federal Statistical Office Data

Félix Luginbühl¹ (www.felixluginbuhl.com)

1. Fachstelle für Statistik Kanton SG (August to October 2023).

Abstract

The BFS R package allows to search and download data from the Swiss Federal Statistical APIs in a dynamic and reproducible way.

Install and Load

```
install.packages("BFS")
#devtools::install_github("lgnbhl/BFS") # install from GitHub
library(BFS)
```

Search the Data Catalog

Display a list of all available datasets from the PXWeb data catalog with metadata in any language ("de", "fr", "it" or "en").

Download Data in Any Language

Get a dataset from the official PXWeb API by BFS number (FSO number).

bfs_get_data(number_bfs = "px-x-1502040100_131", language = "en")

Access all metadata information with bfs_get_asset_metadata().

meta_students <- bfs_get_asset_metadata(number_asset = "24367729")</pre>

Query Specific Dimensions

Get variable and category code names using bfs_get_metadata().

Access only specific dimensions of a dataset using the PXWeb API query.

```
bfs_get_data(
    number_bfs = "px-x-1502040100_131",
    number_bfs = "px-x-1502
```



Search and Download BFS Data in Any Language with 1 Line of Code

Access the full documentation: www.felixluginbuhl.com/BFS

Let's get in touch:

- in linkedin.com/in/felixluginbuhl
- # www.felixluginbuhl.com



Swiss Geodata

Get the Geodata Catalog

Display geo-information catalog of the Swiss Official STAC API.

Explore the Catalog

Download geodata

For example get information about the Generalised borders G1 dataset.

```
geo_gl <- "Generalised borders G1 and area with urban character"

catalog_geodata |>
    dplyr::filter(title == geo_gl)

## # A tibble: 1 × 12
## collection_id type href title description created updated generalise. A public type href title description created updated generalise. A public type href title description created updated generalise. A public type href title description created updated generalise. A public type href title description created updated generalise. A public type href title description created updated generalise. A public type href title description created updated generalise. A public type href title description created updated generalise. A public type href title description created updated generalise. A public type href title description created updated generalise. A public type href title description created updated generalise type href title description created updated generalise. A public type href title description created updated generalise type href title description created generalise type href title description created updated generalise type href title description created generalise type href type href
```

Download geographic assets by collection id from the official STAC API.

```
coll_id <- "ch.bfs.generalisierte-grenzen_agglomerationen_g1"
bfs_download_geodata(collection_id = coll_id)</pre>
```

Cartographic base maps

You can get cartographic base maps from the ThemaKart project using bfs_get_base_maps().



A Use Case Example

 Swiss City Statistics App: choose an indicator, two cities, and have fun trying to guess which city has the highest indicator value.

Webpage: www.felixluginbuhl.com/applications/city-statistics