

# How to Use arxiv Class

Saber <sup>*†</sup>	Lancer <sup>†</sup>	Rider <sup>*</sup>
<a href="mailto:saber@fate.org">saber@fate.org</a>	<a href="mailto:lancer@fate.org">lancer@fate.org</a>	<a href="mailto:rider@fate.org">rider@fate.org</a>
Archer <sup>†</sup>	Gilgamesh <sup>*</sup>	Berserker <sup>†</sup>
<a href="mailto:caster@fate.org">caster@fate.org</a>	<a href="mailto:gilgamesh@fate.org">gilgamesh@fate.org</a>	<a href="mailto:berserker@fate.org">berserker@fate.org</a>
<sup>*</sup> Fate/Zero		<sup>†</sup> Fate/Stay Night

January 1, 2018

## Abstract

This article gives you a clear view of how to use the arxiv class to provide high quality LATEX submission for arXiv. arxiv is a simple extension of `article.cls`. This document is an example provided using arxiv class.

## 1 Introduction

The motivation of creating this LATEX class is to make life simpler when dealing with arXiv submissions.

## 2 Class Options

All options work for `article.cls` also work for this class. For example,

```
\documentclass[onecolumn]{arxiv}
```

## 3 “Clever” Cross Reference

This class provides `autoref` for referencing following LaTeX entities shown in [Table 1](#).

## 4 Theorem-like Environments

This class defines the following theorem-like environments:

- Theorem: `\begin{theorem}...\end{theorem}`
- Corollary: `\begin{corollary}...\end{corollary}`
- Lemma: `\begin{lemma}...\end{lemma}`
- Proposition: `\begin{proposition}...\end{proposition}`

Table 1: Entities that have “clever” cross reference.

Entity	LATEX Command	Result
Figure	<code>\autoref{fig: custom-author-layout}</code>	Figure 1
Subfigure	<code>\autoref{subfig: author-customization-one}</code>	Figure 1a
Table	<code>\autoref{tab: autoref}</code>	Table 1
Equation	<code>\autoref{eq: myeq}</code>	(1)
Theorem	<code>\autoref{thm: positive-recurrent}</code>	Theorem 2
Proposition/Lemma/Corollary	<code>\autoref{coro: compact}</code>	Corollary 3
Definition/Claim/Assumption	<code>\autoref{def: borel}</code>	Definition 1
Section	<code>\autoref{sec:introduction}</code>	§1
Section in Appendix	<code>\autoref{appsec: others}</code>	Appendix A
SubSection in Appendix	<code>\autoref{appsubsec: custom-author}</code>	Appendix A.1

All of them share the same counter, but as shown in §3, they have different `autorefname`. Besides, we also provide the following ones, whereas each of them has its own counter.

- Definition: `\begin{definition}...\end{definition}`
- Claim: `\begin{claim}...\end{claim}`
- Assumption: `\begin{Assumption}...\end{Assumption}`
- Fact: `\begin{fact}...\end{fact}`

#### 4.1 Some Examples

**Proposition 1.** *If  $S$  is finite, then not all states can be transient.*

**Theorem 2.** *Suppose that Markov chain is irreducible and aperiodic and that a stationary distribution  $\pi$  exists with*

$$\pi^T = \pi^T P, \quad (1)$$

and

$$\sum_{j \in S} \pi_j = 1, \quad \pi_j \geq 0. \quad (2)$$

*Then the Markov chain is **positive recurrent**.*

**Corollary 3.** *If  $K_1, K_2, \dots, K_N \in \mathbb{R}^n$  are compact, disjoint sets, then*

$$\left| \bigcup_{j=1}^N K_j \right|_e = \sum_{j=1}^N |K_j|_e$$

**Definition 1** (Borel  $\sigma$ -algebra). *The Borel  $\sigma$ -algebra in  $\mathbb{R}^d$  is the smallest  $\sigma$ -algebra that contains all open sets in  $\mathbb{R}^d$ .*

## 5 Packages Included & Marcos Defined

### 5.1 Packages Included

This class has included the following packages: `ifthen`, `latexsym`, `amsmath`, `amssymb`, `amsthm`, `graphicx`, `subfig`, `xcolor`, `cite`, `fullpage`, `verbatim`, `multirow`, `booktabs`, `url`, `etoolbox`, `appendix`, `aliascnt`.

### 5.2 Macros Defined

This class defined the following macros: `\code` (similar to `\it`), `\email` (*e.g.*, `\email{saber@gmail.com}`), `\authormark` (alias of `\footnotemark`).

## A Others

In the section, we will introduce some tricks that are applicable to L<sup>A</sup>T<sub>E</sub>X classes not limited to arxiv.

### A.1 Customize Author Layout

```
\author{%
  \begin{tabular}{*{6}{c}}
    Saber & Lancer & Rider & Caster & Gilgamesh & Berserker \tabularnewline
    \email{saber@fate.org} & \email{lancer@fate.org} & \email{rider@fate.org} & \\
    & \email{caster@fate.org} & \email{gilgamesh@fate.org} & & \\
    & \email{berserker@fate.org} \tabularnewline
    \multicolumn{6}{c}{Fate Series Heroes} \tabularnewline
  \end{tabular}
}
```

The above code will give a result shown in [Figure 1a](#).

```
\author{%
  \begin{tabular}{*{3}{c}}
    Saber \authormark[1] \authormark[2] & Lancer \authormark[2] & \\
    Rider \authormark[1] \tabularnewline
    \email{saber@fate.org} & \email{lancer@fate.org} & \\
    \email{rider@fate.org} \tabularnewline
    Archer \authormark[2] & Gilgamesh \authormark[1] & \\
    Berserker \authormark[2] \tabularnewline
    \email{caster@fate.org} & \email{gilgamesh@fate.org} & \\
    \email{berserker@fate.org} \tabularnewline
    \authormark[1] Fate/Zero & \authormark[2] Fate/Stay Night \tabularnewline
  \end{tabular}
}
```

The above code will give a result shown in [Figure 1b](#).

## How to Use arxiv Class

Saber	Lancer	Rider	Caster	Gilgamesh	Berserker
<a href="mailto:saber@fate.org">saber@fate.org</a>	<a href="mailto:lancer@fate.org">lancer@fate.org</a>	<a href="mailto:rider@fate.org">rider@fate.org</a>	<a href="mailto:caster@fate.org">caster@fate.org</a>	<a href="mailto:gilgamesh@fate.org">gilgamesh@fate.org</a>	<a href="mailto:berserker@fate.org">berserker@fate.org</a>
Fate Series Heroes					

(a) Example One.

## How to Use arxiv Class

Saber <sup>*†</sup>	Lancer <sup>†</sup>	Rider <sup>*</sup>
<a href="mailto:saber@fate.org">saber@fate.org</a>	<a href="mailto:lancer@fate.org">lancer@fate.org</a>	<a href="mailto:rider@fate.org">rider@fate.org</a>
Archer <sup>†</sup>	Gilgamesh <sup>*</sup>	Berserker <sup>†</sup>
<a href="mailto:caster@fate.org">caster@fate.org</a>	<a href="mailto:gilgamesh@fate.org">gilgamesh@fate.org</a>	<a href="mailto:berserker@fate.org">berserker@fate.org</a>
<sup>*</sup> Fate/Zero		<sup>†</sup> Fate/Stay night

(b) Example Two.

Figure 1: Customized author layout.