



Lab 10 - Role-Playing Game

Git Commit ID Form: <https://goo.gl/forms/UetDDCfsV6DrDrRX2>

23 Points

Introduction

This lab is the culmination of everything you've learned in CMPE-13/L. You are going to program a playable dungeon crawler role playing game (RPG). Files are provided in a directory (that you will copy) that contains information about a series of rooms making up a dungeon. Each file consists of room descriptions, any items contained inside, and how each room is connected to its neighbors. This lab will be programmed on the UNIX servers (as opposed to the embedded hardware), and you will be using the keyboard to read user input and display output on a terminal using standard VT100 commands.

Reading

- **K&R** – Chapter 7.5

Concepts

- File I/O

Provided files

- **Player.h** - Describes the functions necessary for the inventory management functionality necessary for the player in this RPG. You will implement the described functions within the corresponding Player.c file.
- **Game.h** - This library controls the game state and handles inter-room navigation. You will implement the described functions within the corresponding Game.c file.
- **rpg.c** - This file contains main(). Any functions you need to create that aren't related to either of the two libraries (Player.c/h and Game.c/h) should be placed in this file.
- **UNIXBOARD.h** – Contains Standard #defines and system libraries used. Also includes the standard fixed-width datatypes and error return values. This is to replace the BOARD.c/h files that you have been using on the embedded processor.

Assignment requirements

- **Player library:** Implement all of the functions defined in Player.h. This library is used exclusively by the Game.c/h library and will not be called directly from rpg.c.
- **Game library:** Implement all of the functions defined in Game.h.
- **main():** Your main() within rpg.c must implement the following functionality using the provided code along with the two libraries you will have implemented. You are also free to use any functions within the C standard library.
 - All Information for the user will be displayed in the terminal. You will need to use VT-100 commands to do so (see below).
 - The room title should be formatted with both fore and background colors and appears on the first line.
 - The room description goes below the title with default formatting.
 - At the bottom of the screen should be a prompt for the next direction. This spacing should be done exclusively using VT-100 commands, not newlines. Additionally this should work correctly for terminal sizes anywhere between 24-44 lines long (yes, we will check).
 - Available exits from the current room are indicated in a compass pattern above the direction prompt (north on top, west east, south on bottom). Movable directions should be printed in green with non-movable directions in red.
 - User input is captured using getchar(). This function blocks until it receives a newline. You should respond only to valid directions (n,e,s,w) or q and ignore all other inputs, clearing them from the display. Only one direction can be taken at a time and longer strings should be ignored as well.
 - Receiving q should exit the program using the exit() function with the SUCCESS code.
 - The player has an inventory where they store things that are found in the rooms. These items can alter the room description and the available exits. This should be implemented as well.¹
- **Code requirements:** When implementing this lab, your code should adhere to the following restrictions.
 - Use fread() and fgetc() to read the different parts of the file. fseek() can be used as well to skip over parts of the file.
 - All constants should be enums or macro constants.

¹ That is, you might get a different room description depending on what is in your inventory list. This will need to be checked so that you print the correct description.

- A struct is used in Game.c to hold the title, description, and all 4 exits for the current room.
- The GameGo*() functions all open the next room file, process the data and load the room struct with the correct information, and then close the file.
- No more than one file should ever be open at a time and files should not be used outside of the GameGo*() functions.
- All GameGet*() functions should extract the correct data from the room struct; they should NOT reopen/reparse the file.
- A single event loop should be created within main() for processing all events (getchar).
- If GameInit() fails when called within main(), the FATAL_ERROR() macro should be called.
- Inventory management must be done through the Player library.
- All code that utilizes macro constants should work if the macro constant value were to be changed.
- All external variables must be limited to module-scope by using the static keyword. NO GLOBALS!
- All calls to fopen() should be checked for failure, with FATAL_ERROR() called if they do.
- No heap use in this lab (i.e.: no calls to malloc()).
- A properly made makefile which supports both generating the executable and cleaning up both the object files and the executable. This makefile cannot have macros to illustrate that the proper targets have been made correctly.
- **Extra credit (1 point):** The dungeon that you have been provided could use a good map. Provide a PDF of a map of the entire dungeon. It should include the room titles, room numbers, and how rooms are connected. Use arrow heads on your lines to indicate which direction rooms can be reached from (trap rooms can't reach any other rooms for example). Additionally rooms should display their names and the map should be oriented with north being the top of the page and east being the right-hand side.²
- **Code style:** Follow the standard style formatting procedures for syntax, variable names, and comments.
 - Add the following to the top of every file you submit as comments:
 - Your name
 - The names of colleagues who you have collaborated with

² This should either be computer generated, or very neatly hand drawn. We have to grade this and cannot decipher your scribbles.

- **Readme:** Create a file named README.txt containing the following items. Note that spelling and grammar count as part of your grade so you'll want to proof-read this before submitting. This will follow the same rough outline as a lab report for a regular science class. It should be on the order of three to four paragraphs with several sentences in each paragraph.
 - First you should list your name and the names of anyone else who you have collaborated with.³
 - In the next section you should provide a summary of the lab in your own words. Highlight what you thought were the important aspects of the lab. If these differ from how the lab manual presents things, make a note of that.
 - The following section should describe your approach to the lab. What was your general approach to the lab? Did you read the manual first or what were your first steps? What went wrong as you worked through it? What worked well? How would you approach this lab differently if you were to do it again? Did you work with anyone else in the class? How did you work with them and what did you find helpful/unhelpful?
 - The final section should describe the results of you implementing the lab. How did it end up finally? How many hours did you end up spending on it? What'd you like about it? What did you dislike? Was this a worthwhile lab? Do you have any suggestions for altering it to make it better? What were the hardest parts of it? Did the point distribution for the grading seem appropriate? Did the lab manual cover the material in enough detail to start you off? Did examples or discussions during class help your understanding of this lab or would more teaching on the concepts in this lab help?
- **Submission:**
 - Submit your files (Player.c, Game.c, rpg.c, README.txt, makefile, and your map as a PDF named map.pdf (if you do the extra credit).

Grading

This assignment consists of 23 points:

- 8 points - Game library
- 4 points - Player library
- 4 points - RPG functionality
- 4 points – Program requirements
- 1 point – README (you lose this point if you fail to submit README.txt)
- 1 point – Style
- 1 point – GIT hygiene

³ NOTE: collaboration != copying. If you worked with someone else, be DETAILED in your description of what you did together. If you get flagged by the code checker, this is what will save you.

- **Extra credit:** 1 point - Create a map of all of the rooms.

You will lose points for the following:

- No credit for any sections where libraries/code doesn't compile.
- -2 points: Any warnings when compiling all code together
- -4 points: For file access outside the GameGo*() functions.

Room description files

This lab relies extensively on reading files from the file system. These files contain all of the information for the dungeon of the RPG. These files are all organized in a subdirectory of the system (specified in Linux as "RoomFiles/"). Their file names are room1.txt through room65.txt. When accessing these files with the file functions, their full filename will be required (e.g.: "RoomFiles/room1.txt"). You will need to copy the Roomfiles directory given to your local directory where you will run your code. DO NOT use a switch statement to individually select the proper room name; use a function like sprintf() to generate the necessary filename.

The files are binary files (so be sure to open them in binary mode!) and are encrypted using XOR to prevent people from cheating at the game. To decrypt a file a key is needed and is unique for each file. We generate this key by adding the #define *DECRYPTION_BASE_KEY* and the room number.

As a simple example, if the *DECRYPTION_BASE_KEY* was 122, then the decryption key for room32.txt is (32+122=154). The encrypted raw values and decrypted results are shown below for title length and title.

95	CE	F2	FF	BA	CE	F2	E8	F5	F4	FF	BA	C8	F5	F5	F7
F	54	68	65	20	54	68	72	6F	6E	65	20	52	6F	6F	6D
15	T	h	e		T	h	r	o	n	e		R	o	o	m

Once decrypted, the file is laid out to have a title first, then a repeating list of room properties; these properties are dependent on the player's inventories for whether or not they should be displayed. Note that these values are always repeated the same way in order.

Title	Item requirements	Description	Items contained	Exits
	(repeated)			

The first section of the file is the title. This is stored as a byte holding the length of the string and then that many ASCII characters (each is one byte). There is no NULL-character terminating this string!⁴

Title	Item requirements	Description	Items contained	Exits
	(repeated)			

Following the title is a repeating group of values representing the portion of the room that can vary: item requirements, description, items contained, and the exits. The first of these, the item requirements, is a sequence of bytes containing the number of the item that is required for this version of the room to be displayed. This list of bytes is prepended by the length of this list. So if the room has a single item, item #3, that is required, the file would have a byte of value 1 followed by a byte of value 3 for this section. If multiple items are listed here, all of the items must be present in the player's inventory for this room version to be displayed. If not items are required, then the prepended list length is 0.

Title	Item requirements	Description	Items contained	Exits
	(repeated)			

The description follows a similar layout to the Title in that it is a sequence of ASCII characters that are not NULL-terminated but are prepended with the length of the string. Again, similar care needs to be taken when using these as strings.

Title	Item requirements	Description	Items contained	Exits
	(repeated)			

Following are the items that are contained within this room. This follows the same format as the item requirements: 1 byte indicating length as a uint8 followed by that many bytes representing item numbers of the items found within the room.

Title	Item requirements	Description	Items contained	Exits
	(repeated)			

⁴ Be careful with this. If you want to treat the title as a string (e.g. for use in printf) you will need to store the characters into a character array and then append a '\0' to the end.

Next four bytes represent the room numbers of the available exits for this room version. They are ordered as north, east, south, west exits (clockwise from north). A 0 indicates that there is no exit or any connected room in that direction.

At this point it is either the end of the file (EOF) or another set of item requirements meaning that there is another room version available (if you have the right items). The versions are always specified in order of decreasing item requirements. There should also always be a final room version with 0 item requirements which is the version that will be displayed if no other versions passed their item requirements check.

As a simple example, “/room1.txt” looks like the following:

1. **Title**, 16 characters, “Council chambers”
2. **Version 1**
 - a. Item requirement: None (0x00)
 - b. Description: 214 characters long
 - c. Items contained: None (0x00)
 - d. Exits: East is room 2 (0x00, 0x02, 0x00, 0x00)

A more complicated example is “/room32.txt”, which looks like the following:

1. **Title**, 15 characters, “The throne room”
2. **Version 1**
 - a. Item requirement: 3 (0x01, 0x03)
 - b. Description: 169 characters long
 - c. Items contained: None (0x00)
 - d. Exits: South is room 30 (0x00, 0x00, 0x1E, 0x00)
3. **Version 2**
 - a. Item requirements: None (0x00)
 - b. Description: 238 characters long
 - c. Items contained: 3 (0x01, 0x03)
 - d. Exits: South is room 30 (0x00, 0x00, 0x1E, 0x00)

File API

Read the standard library documentation for all of the file functions that you’d like to use (look up `stdio.h`). You should know and handle any and all failure cases. Also read all of the documentation for the functions, as some have additional requirements that need to be met before they are useable.






VT-100 Terminal Commands (ASCII Escape Codes)

As part of the submittal process for the previous labs, you have already interacted with the unix terminals and git. Unlike the serial programs we have written so far, these system terminals can modify colors and cursors for greater usability. While many frameworks exist to help in this operation, in this lab we will use VT-100 codes to alter the relevant terminal properties.

Each VT-100 sequence starts with the ESC character (0x1b), and is followed by xxx where the xxx is the command to the terminal. For example, printing the sequence “\x1b[2J” will clear the screen (that is, after the ESC the command is [2J) . Similarly the “\x1b[31m” will turn the text color to red. You should refer to:

http://www.ccs.neu.edu/research/gpc/Msim/vona/terminal/VT100_Escape_Codes.html

For information on escape codes in general and to the Wikipedia page on colors: (https://en.wikipedia.org/wiki/ANSI_escape_code#Colors) for color codes. Examples of code and corresponding output are shown below.

<pre>printf("\033[2J\n"); //clear the screen</pre>	
<pre>printf("\033[31mR\033[32mG\033[34mB\n\n\033[0mforeground\n");</pre>	
<pre>printf("\033[41mR\033[42mG\033[44mB\033[0m\n\nbackground\n");</pre>	
<pre>printf("start\033[3B3 lines down\n");</pre>	
<pre>printf("start\033[10C10 columns right\n");</pre>	

Makefiles

Throughout this class you have been using MPLABX IDE to both write and compile your code. While IDE's exist for generic C code, for this lab you will compile the code directly. The standard call to gcc (our UNIX compiler) is shown below:

```
gcc Simple.c -o Simple
```

This will compile the source given into an executable with name “Simple”. If you do not give the -o option it will generate an executable of name “a”. A more complex program that involves multiple source files can call gcc with multiple files like the example below.


```
gcc Game.c Player.c rpg.c
```

While this is possible to do this for any project it is unwieldly and forces all of your files to be compiled for every change. For large projects a full compile can take hours to perform. Instead of compiling every file, gcc supports the generation of object files. These object files contain compiled C code for the file but not the library code. For example, the object file for rpg.c will contain references to GameGetCurrentRoomExits() but not its definition. At the same time changes to rpg.c will not require recompilation of Game.c. Object files are generated with the command below

```
gcc -c Player.c
```

A set of object files can then be combined to form an executable

```
gcc Player.o Game.o rpg.o -o rpg
```

While these commands are all runnable within the terminal directly, combining them within a makefile allows them to be consolidated and easily reused. When you hit make inside MPLABX it is calling its own makefile to generate the hex file.

Makefiles are text files containing commands that are parsed by the make command. To use the makefile you simply call “make” on the terminal. A Sample makefile is shown below.

```
All: Simple
Simple.o: Simple.c
        gcc -c Simple.c
Simple: Simple.o
        gcc Simple.o -o Simple
```

The first line, “all: Simple” consists of two parts: target, a desired item to create; and a dependency, the requirements to make the desired target. This is also a special case as calling “make” is the same as calling “make all”. The other targets follow the same format but also have commands associated with them to generate that specific target.

When make is called, it will follow the dependency chain as needed to build the requested target. Additionally it will only perform the action if the dependencies are newer than the target. For example, this means that it will only compile new .o files as needed, not every time.

As make can also call targets directly, auxiliary commands can be made such as the “make clean” command below.

```
clean:
        rm *.o Simple
```