

LinksPlatform's Platform.Data.Doublets Class Library

1.1 ./csharp/Platform.Data.Doublets/CriterionMatchers/TargetMatcher.cs

```
1 using System.Collections.Generic;
2 using System.Runtime.CompilerServices;
3 using Platform.Interfaces;
4
5 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7 namespace Platform.Data.Doublets.CriterionMatchers
8 {
9     /// <summary>
10    /// <para>
11    /// Represents the target matcher.
12    /// </para>
13    /// <para></para>
14    /// </summary>
15    /// <seealso cref="LinksOperatorBase{TLinkAddress}"/>
16    /// <seealso cref="ICriterionMatcher{TLinkAddress}"/>
17    public class TargetMatcher<TLinkAddress> : LinksOperatorBase<TLinkAddress>,
18    ↪ ICriterionMatcher<TLinkAddress> where TLinkAddress : struct
19    {
20        private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
21        ↪ EqualityComparer<TLinkAddress>.Default;
22        private readonly TLinkAddress _targetToMatch;
23
24        /// <summary>
25        /// <para>
26        /// Initializes a new <see cref="TargetMatcher"/> instance.
27        /// </para>
28        /// <para></para>
29        /// </summary>
30        /// <param name="links">
31        /// <para>A links.</para>
32        /// </param>
33        /// <param name="targetToMatch">
34        /// <para>A target to match.</para>
35        /// </param>
36        [MethodImpl(MethodImplOptions.AggressiveInlining)]
37        public TargetMatcher(ILinks<TLinkAddress> links, TLinkAddress targetToMatch) :
38        ↪ base(links) => _targetToMatch = targetToMatch;
39
40        /// <summary>
41        /// <para>
42        /// Determines whether this instance is matched.
43        /// </para>
44        /// <para></para>
45        /// </summary>
46        /// <param name="link">
47        /// <para>The link.</para>
48        /// </param>
49        /// <returns>
50        /// <para>The bool</para>
51        /// <para></para>
52        /// </returns>
53        [MethodImpl(MethodImplOptions.AggressiveInlining)]
54        public bool IsMatched(TLinkAddress link) =>
55        ↪ _equalityComparer.Equals(_links.GetTarget(link), _targetToMatch);
56    }
```

1.2 ./csharp/Platform.Data.Doublets/Decorators/LinksCascadeUniquenessAndUsagesResolver.cs

```
1 using System;
2 using System.Collections.Generic;
3 using System.Runtime.CompilerServices;
4 using Platform.Delegates;
5
6 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8 namespace Platform.Data.Doublets.Decorators
9 {
10    /// <summary>
11    /// <para>
12    /// Represents the links cascade uniqueness and usages resolver.
13    /// </para>
14    /// <para></para>
15    /// </summary>
```

```

16  /// <seealso cref="LinksUniquenessResolver{TLinkAddress}"/>
17  public class LinksCascadeUniquenessAndUsagesResolver<TLinkAddress> :
    ↳ LinksUniquenessResolver<TLinkAddress> where TLinkAddress : struct
18  {
19      /// <summary>
20      /// <para>
21      /// Initializes a new <see cref="LinksCascadeUniquenessAndUsagesResolver"/> instance.
22      /// </para>
23      /// <para></para>
24      /// </summary>
25      /// <param name="links">
26      /// <para>A links.</para>
27      /// <para></para>
28      /// </param>
29      [MethodImpl(MethodImplOptions.AggressiveInlining)]
30      public LinksCascadeUniquenessAndUsagesResolver(ILinks<TLinkAddress> links) : base(links)
        ↳ { }
31
32      /// <summary>
33      /// <para>
34      /// Resolves the address change conflict using the specified old link address.
35      /// </para>
36      /// <para></para>
37      /// </summary>
38      /// <param name="oldLinkAddress">
39      /// <para>The old link address.</para>
40      /// <para></para>
41      /// </param>
42      /// <param name="newLinkAddress">
43      /// <para>The new link address.</para>
44      /// <para></para>
45      /// </param>
46      /// <returns>
47      /// <para>The link</para>
48      /// <para></para>
49      /// </returns>
50      [MethodImpl(MethodImplOptions.AggressiveInlining)]
51      protected override TLinkAddress ResolveAddressChangeConflict(TLinkAddress
        ↳ oldLinkAddress, TLinkAddress newLinkAddress, WriteHandler<TLinkAddress>? handler)
52      {
53          var constants = _links.Constants;
54          WriteHandlerState<TLinkAddress> handlerState = new(constants.Continue,
        ↳ constants.Break, handler);
55          // Use Facade (the last decorator) to ensure recursion working correctly
56          handlerState.Apply(_facade.MergeUsages(oldLinkAddress, newLinkAddress,
        ↳ handlerState.Handler));
57          handlerState.Apply(base.ResolveAddressChangeConflict(oldLinkAddress, newLinkAddress,
        ↳ handlerState.Handler));
58          return handlerState.Result;
59      }
60  }
61 }

```

1.3 ./csharp/Platform.Data.Doublets/Decorators/LinksCascadeUsagesResolver.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Delegates;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Decorators
9  {
10     /// <remarks>
11     /// <para>Must be used in conjunction with NonNullContentsLinkDeletionResolver.</para>
12     /// <para>Должен использоваться вместе с NonNullContentsLinkDeletionResolver.</para>
13     /// </remarks>
14     public class LinksCascadeUsagesResolver<TLinkAddress> : LinksDecoratorBase<TLinkAddress>
        ↳ where TLinkAddress : struct
15     {
16         /// <summary>
17         /// <para>
18         /// Initializes a new <see cref="LinksCascadeUsagesResolver"/> instance.
19         /// </para>
20         /// <para></para>
21         /// </summary>
22         /// <param name="links">
23         /// <para>A links.</para>

```

```

24     /// <para></para>
25     /// </param>
26     [MethodImpl(MethodImplOptions.AggressiveInlining)]
27     public LinksCascadeUsagesResolver(ILinks<TLinkAddress> links) : base(links) { }
28
29     /// <summary>
30     /// <para>
31     /// Deletes the restriction.
32     /// </para>
33     /// <para></para>
34     /// </summary>
35     /// <param name="restriction">
36     /// <para>The restriction.</para>
37     /// <para></para>
38     /// </param>
39     [MethodImpl(MethodImplOptions.AggressiveInlining)]
40     public override TLinkAddress Delete(IList<TLinkAddress>? restriction,
41     ↪ WriteHandler<TLinkAddress>? handler)
42     {
43         var constants = _links.Constants;
44         WriteHandlerState<TLinkAddress> handlerState = new(constants.Continue,
45         ↪ constants.Break, handler);
46         var linkIndex = _links.GetIndex(restriction);
47         // Use Facade (the last decorator) to ensure recursion working correctly
48         handlerState.Apply(_facade.DeleteAllUsages(linkIndex, handlerState.Handler));
49         handlerState.Apply(_links.Delete(restriction, handlerState.Handler));
50         return handlerState.Result;
51     }
52 }

```

1.4 ./csharp/Platform.Data.Doublets/Decorators/LinksDecoratorBase.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Delegates;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Decorators
9  {
10     /// <summary>
11     /// <para>
12     /// Represents the links decorator base.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     /// <seealso cref="LinksOperatorBase{TLinkAddress}"/>
17     /// <seealso cref="ILinks{TLinkAddress}"/>
18     public abstract class LinksDecoratorBase<TLinkAddress> : LinksOperatorBase<TLinkAddress>,
19     ↪ ILinks<TLinkAddress>
20     {
21         /// <summary>
22         /// <para>
23         /// The constants.
24         /// </para>
25         /// <para></para>
26         /// </summary>
27         protected readonly LinksConstants<TLinkAddress> _constants;
28
29         /// <summary>
30         /// <para>
31         /// Gets the constants value.
32         /// </para>
33         /// <para></para>
34         /// </summary>
35         public LinksConstants<TLinkAddress> Constants
36         {
37             [MethodImpl(MethodImplOptions.AggressiveInlining)]
38             get => _constants;
39         }
40
41         /// <summary>
42         /// <para>
43         /// The facade.
44         /// </para>
45         /// <para></para>
46         /// </summary>
47         protected ILinks<TLinkAddress> _facade;

```

```

47
48 /// <summary>
49 /// <para>
50 /// Gets or sets the facade value.
51 /// </para>
52 /// <para></para>
53 /// </summary>
54 public ILinks<TLinkAddress> Facade
55 {
56     [MethodImpl(MethodImplOptions.AggressiveInlining)]
57     get => _facade;
58     [MethodImpl(MethodImplOptions.AggressiveInlining)]
59     set
60     {
61         _facade = value;
62         if (_links is LinksDecoratorBase<TLinkAddress> decorator)
63         {
64             decorator.Facade = value;
65         }
66     }
67 }
68
69 /// <summary>
70 /// <para>
71 /// Initializes a new <see cref="LinksDecoratorBase"/> instance.
72 /// </para>
73 /// <para></para>
74 /// </summary>
75 /// <param name="links">
76 /// <para>A links.</para>
77 /// <para></para>
78 /// </param>
79 [MethodImpl(MethodImplOptions.AggressiveInlining)]
80 protected LinksDecoratorBase(ILinks<TLinkAddress> links) : base(links)
81 {
82     _constants = links.Constants;
83     Facade = this;
84 }
85
86 /// <summary>
87 /// <para>
88 /// Counts the restriction.
89 /// </para>
90 /// <para></para>
91 /// </summary>
92 /// <param name="restriction">
93 /// <para>The restriction.</para>
94 /// <para></para>
95 /// </param>
96 /// <returns>
97 /// <para>The link</para>
98 /// <para></para>
99 /// </returns>
100 [MethodImpl(MethodImplOptions.AggressiveInlining)]
101 public virtual TLinkAddress Count(ICollection<TLinkAddress>? restriction) =>
102     ↪ _links.Count(restriction);
103
104 /// <summary>
105 /// <para>
106 /// Eaches the handler.
107 /// </para>
108 /// <para></para>
109 /// </summary>
110 /// <param name="handler">
111 /// <para>The handler.</para>
112 /// <para></para>
113 /// </param>
114 /// <param name="restriction">
115 /// <para>The restriction.</para>
116 /// <para></para>
117 /// </param>
118 /// <returns>
119 /// <para>The link</para>
120 /// <para></para>
121 /// </returns>
122 [MethodImpl(MethodImplOptions.AggressiveInlining)]
123 public virtual TLinkAddress Each(ICollection<TLinkAddress>? restriction,
124     ↪ ReadHandler<TLinkAddress>? handler) => _links.Each(restriction, handler);

```

```

123
124     /// <summary>
125     /// <para>
126     /// Creates the restriction.
127     /// </para>
128     /// <para></para>
129     /// </summary>
130     /// <param name="restriction">
131     /// <para>The restriction.</para>
132     /// <para></para>
133     /// </param>
134     /// <returns>
135     /// <para>The link</para>
136     /// <para></para>
137     /// </returns>
138     [MethodImpl(MethodImplOptions.AggressiveInlining)]
139     public virtual TLinkAddress Create(IList<TLinkAddress>? substitution,
140     ↪ WriteHandler<TLinkAddress>? handler) => _links.Create(substitution, handler);
141
142     /// <summary>
143     /// <para>
144     /// Updates the restriction.
145     /// </para>
146     /// <para></para>
147     /// </summary>
148     /// <param name="restriction">
149     /// <para>The restriction.</para>
150     /// <para></para>
151     /// </param>
152     /// <param name="substitution">
153     /// <para>The substitution.</para>
154     /// <para></para>
155     /// </param>
156     /// <returns>
157     /// <para>The link</para>
158     /// <para></para>
159     /// </returns>
160     [MethodImpl(MethodImplOptions.AggressiveInlining)]
161     public virtual TLinkAddress Update(IList<TLinkAddress>? restriction,
162     ↪ IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler) =>
163     ↪ _links.Update(restriction, substitution, handler);
164
165     /// <summary>
166     /// <para>
167     /// Deletes the restriction.
168     /// </para>
169     /// <para></para>
170     /// </summary>
171     /// <param name="restriction">
172     /// <para>The restriction.</para>
173     /// <para></para>
174     /// </param>
175     [MethodImpl(MethodImplOptions.AggressiveInlining)]
176     public virtual TLinkAddress Delete(IList<TLinkAddress>? restriction,
177     ↪ WriteHandler<TLinkAddress>? handler) => _links.Delete(restriction, handler);
178 }

```

1.5 ./csharp/Platform.Data.Doublets/Decorators/LinksDisposableDecoratorBase.cs

```

1 using System.Runtime.CompilerServices;
2 using Platform.Disposables;
3
4 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5 #pragma warning disable CA1063 // Implement IDisposable Correctly
6
7 namespace Platform.Data.Doublets.Decorators
8 {
9     /// <summary>
10     /// <para>
11     /// Represents the links disposable decorator base.
12     /// </para>
13     /// <para></para>
14     /// </summary>
15     /// <seealso cref="LinksDecoratorBase{TLinkAddress}"/>
16     /// <seealso cref="ILinks{TLinkAddress}"/>
17     /// <seealso cref="System.IDisposable"/>
18     public abstract class LinksDisposableDecoratorBase<TLinkAddress> :
19     ↪ LinksDecoratorBase<TLinkAddress>, ILinks<TLinkAddress>, System.IDisposable

```

```

19 {
20     /// <summary>
21     /// <para>
22     /// Represents the disposable with multiple calls allowed.
23     /// </para>
24     /// <para></para>
25     /// </summary>
26     /// <seealso cref="Disposable"/>
27     protected class DisposableWithMultipleCallsAllowed : Disposable
28     {
29         /// <summary>
30         /// <para>
31         /// Initializes a new <see cref="DisposableWithMultipleCallsAllowed"/> instance.
32         /// </para>
33         /// <para></para>
34         /// </summary>
35         /// <param name="disposal">
36         /// <para>A disposal.</para>
37         /// <para></para>
38         /// </param>
39         [MethodImpl(MethodImplOptions.AggressiveInlining)]
40         public DisposableWithMultipleCallsAllowed(Disposal disposal) : base(disposal) { }
41
42         /// <summary>
43         /// <para>
44         /// Gets the allow multiple dispose calls value.
45         /// </para>
46         /// <para></para>
47         /// </summary>
48         protected override bool AllowMultipleDisposeCalls
49         {
50             [MethodImpl(MethodImplOptions.AggressiveInlining)]
51             get => true;
52         }
53     }
54
55     /// <summary>
56     /// <para>
57     /// The disposable.
58     /// </para>
59     /// <para></para>
60     /// </summary>
61     protected readonly DisposableWithMultipleCallsAllowed Disposable;
62
63     /// <summary>
64     /// <para>
65     /// Initializes a new <see cref="LinksDisposableDecoratorBase"/> instance.
66     /// </para>
67     /// <para></para>
68     /// </summary>
69     /// <param name="links">
70     /// <para>A links.</para>
71     /// <para></para>
72     /// </param>
73     [MethodImpl(MethodImplOptions.AggressiveInlining)]
74     protected LinksDisposableDecoratorBase(ILinks<TLinkAddress> links) : base(links) =>
75     ↪ Disposable = new DisposableWithMultipleCallsAllowed(Dispose);
76
77     [MethodImpl(MethodImplOptions.AggressiveInlining)]
78     ~LinksDisposableDecoratorBase() => Disposable.Destruct();
79
80     /// <summary>
81     /// <para>
82     /// Disposes this instance.
83     /// </para>
84     /// <para></para>
85     /// </summary>
86     [MethodImpl(MethodImplOptions.AggressiveInlining)]
87     public void Dispose() => Disposable.Dispose();
88
89     /// <summary>
90     /// <para>
91     /// Disposes the manual.
92     /// </para>
93     /// <para></para>
94     /// </summary>
95     /// <param name="manual">
96     /// <para>The manual.</para>

```

```

96     /// <para></para>
97     /// </param>
98     /// <param name="wasDisposed">
99     /// <para>The was disposed.</para>
100    /// <para></para>
101    /// </param>
102    [MethodImpl(MethodImplOptions.AggressiveInlining)]
103    protected virtual void Dispose(bool manual, bool wasDisposed)
104    {
105        if (!wasDisposed)
106        {
107            _links.DisposeIfPossible();
108        }
109    }
110 }
111 }

```

1.6 ./csharp/Platform.Data.Doublets/Decorators/LinksInnerReferenceExistenceValidator.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Delegates;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Decorators
9  {
10     // TODO: Make LinksExternalReferenceValidator. A layer that checks each link to exist or to
11     // ↳ be external (hybrid link's raw number).
12     /// <summary>
13     /// <para>
14     /// Represents the links inner reference existence validator.
15     /// </para>
16     /// <para></para>
17     /// </summary>
18     /// <seealso cref="LinksDecoratorBase{TLinkAddress}"/>
19     public class LinksInnerReferenceExistenceValidator<TLinkAddress> :
20     // ↳ LinksDecoratorBase<TLinkAddress> where TLinkAddress : struct
21     {
22         /// <summary>
23         /// <para>
24         /// Initializes a new <see cref="LinksInnerReferenceExistenceValidator"/> instance.
25         /// </para>
26         /// <para></para>
27         /// </summary>
28         /// <param name="links">
29         /// <para>A links.</para>
30         /// <para></para>
31         /// </param>
32         [MethodImpl(MethodImplOptions.AggressiveInlining)]
33         public LinksInnerReferenceExistenceValidator(ILinks<TLinkAddress> links) : base(links) {
34         // ↳ }
35
36         /// <summary>
37         /// <para>
38         /// Eaches the handler.
39         /// </para>
40         /// <para></para>
41         /// </summary>
42         /// <param name="handler">
43         /// <para>The handler.</para>
44         /// <para></para>
45         /// </param>
46         /// <param name="restriction">
47         /// <para>The restriction.</para>
48         /// <para></para>
49         /// </param>
50         /// <returns>
51         /// <para>The link</para>
52         /// <para></para>
53         /// </returns>
54         [MethodImpl(MethodImplOptions.AggressiveInlining)]
55         public override TLinkAddress Each(ICollection<TLinkAddress>? restriction,
56         // ↳ ReadHandler<TLinkAddress>? handler)
57         {
58             var links = _links;
59             links.EnsureInnerReferenceExists(restriction, nameof(restriction));
60             return links.Each(restriction, handler);
61         }
62     }
63 }

```

```

57     }
58
59     /// <summary>
60     /// <para>
61     /// Updates the restriction.
62     /// </para>
63     /// <para></para>
64     /// </summary>
65     /// <param name="restriction">
66     /// <para>The restriction.</para>
67     /// <para></para>
68     /// </param>
69     /// <param name="substitution">
70     /// <para>The substitution.</para>
71     /// <para></para>
72     /// </param>
73     /// <returns>
74     /// <para>The link</para>
75     /// <para></para>
76     /// </returns>
77     [MethodImpl(MethodImplOptions.AggressiveInlining)]
78     public override TLinkAddress Update(IList<TLinkAddress>? restriction,
79     ↪  IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler)
80     {
81         // TODO: Possible values: null, ExistentLink or NonExistentHybrid(ExternalReference)
82         var links = _links;
83         links.EnsureInnerReferenceExists(restriction, nameof(restriction));
84         links.EnsureInnerReferenceExists(substitution, nameof(substitution));
85         return links.Update(restriction, substitution, handler);
86     }
87
88     /// <summary>
89     /// <para>
90     /// Deletes the restriction.
91     /// </para>
92     /// <para></para>
93     /// </summary>
94     /// <param name="restriction">
95     /// <para>The restriction.</para>
96     /// <para></para>
97     /// </param>
98     [MethodImpl(MethodImplOptions.AggressiveInlining)]
99     public override TLinkAddress Delete(IList<TLinkAddress>? restriction,
100     ↪  WriteHandler<TLinkAddress>? handler)
101     {
102         var links = _links;
103         var link = links.GetIndex(restriction);
104         links.EnsureLinkExists(link, nameof(link));
105         return links.Delete(restriction, handler);
106     }
107 }

```

1.7 ./csharp/Platform.Data.Doublets/Decorators/LinksItselfConstantToSelfReferenceResolver.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Delegates;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Decorators
9  {
10     /// <summary>
11     /// <para>
12     /// Represents the links itself constant to self reference resolver.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     /// <seealso cref="LinksDecoratorBase{TLinkAddress}"/>
17     public class LinksItselfConstantToSelfReferenceResolver<TLinkAddress> :
18     ↪  LinksDecoratorBase<TLinkAddress> where TLinkAddress : struct
19     {
20         private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
21         ↪  EqualityComparer<TLinkAddress>.Default;
22
23         /// <summary>
24         /// <para>
25         /// Initializes a new <see cref="LinksItselfConstantToSelfReferenceResolver"/> instance.

```



```

24     /// </para>
25     /// <para></para>
26     /// </summary>
27     /// <param name="links">
28     /// <para>A links.</para>
29     /// <para></para>
30     /// </param>
31     [MethodImpl(MethodImplOptions.AggressiveInlining)]
32     public LinksItselfConstantToSelfReferenceResolver(ILinks<TLinkAddress> links) :
        ↳ base(links) { }
33
34     /// <summary>
35     /// <para>
36     /// Eaches the handler.
37     /// </para>
38     /// <para></para>
39     /// </summary>
40     /// <param name="handler">
41     /// <para>The handler.</para>
42     /// <para></para>
43     /// </param>
44     /// <param name="restriction">
45     /// <para>The restriction.</para>
46     /// <para></para>
47     /// </param>
48     /// <returns>
49     /// <para>The link</para>
50     /// <para></para>
51     /// </returns>
52     [MethodImpl(MethodImplOptions.AggressiveInlining)]
53     public override TLinkAddress Each(IList<TLinkAddress>? restriction,
        ↳ ReadHandler<TLinkAddress>? handler)
54     {
55         var constants = _constants;
56         var itselfConstant = constants.Itself;
57         if (!_equalityComparer.Equals(constants.Any, itselfConstant) &&
            ↳ restriction.Contains(itselfConstant))
58         {
59             // Itself constant is not supported for Each method right now, skipping execution
60             return constants.Continue;
61         }
62         return _links.Each(restriction, handler);
63     }
64
65     /// <summary>
66     /// <para>
67     /// Updates the restriction.
68     /// </para>
69     /// <para></para>
70     /// </summary>
71     /// <param name="restriction">
72     /// <para>The restriction.</para>
73     /// <para></para>
74     /// </param>
75     /// <param name="substitution">
76     /// <para>The substitution.</para>
77     /// <para></para>
78     /// </param>
79     /// <returns>
80     /// <para>The link</para>
81     /// <para></para>
82     /// </returns>
83     [MethodImpl(MethodImplOptions.AggressiveInlining)]
84     public override TLinkAddress Update(IList<TLinkAddress>? restriction,
        ↳ IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler) =>
        ↳ _links.Update(restriction, _links.ResolveConstantAsSelfReference(_constants.Itself,
            ↳ restriction, substitution), handler);
85     }
86 }

```

1.8 ./csharp/Platform.Data.Doublets/Decorators/LinksNonExistentDependenciesCreator.cs

```

1 using System;
2 using System.Collections.Generic;
3 using System.Runtime.CompilerServices;
4 using Platform.Delegates;
5
6 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7

```

```

8 namespace Platform.Data.Doublets.Decorators
9 {
10     /// <remarks>
11     /// Not practical if newSource and newTarget are too big.
12     /// To be able to use practical version we should allow to create link at any specific
13     /// ↪ location inside ResizableDirectMemoryLinks.
14     /// This in turn will require to implement not a list of empty links, but a list of ranges
15     /// ↪ to store it more efficiently.
16     /// </remarks>
17     public class LinksNonExistentDependenciesCreator<TLinkAddress> :
18     ↪ LinksDecoratorBase<TLinkAddress> where TLinkAddress : struct
19     {
20         /// <summary>
21         /// <para>
22         /// Initializes a new <see cref="LinksNonExistentDependenciesCreator"/> instance.
23         /// </para>
24         /// <para></para>
25         /// </summary>
26         /// <param name="links">
27         /// <para>A links.</para>
28         /// <para></para>
29         /// </param>
30         [MethodImpl(MethodImplOptions.AggressiveInlining)]
31         public LinksNonExistentDependenciesCreator(ILinks<TLinkAddress> links) : base(links) { }
32
33         /// <summary>
34         /// <para>
35         /// Updates the restriction.
36         /// </para>
37         /// <para></para>
38         /// </summary>
39         /// <param name="restriction">
40         /// <para>The restriction.</para>
41         /// <para></para>
42         /// </param>
43         /// <param name="substitution">
44         /// <para>The substitution.</para>
45         /// <para></para>
46         /// </param>
47         /// <returns>
48         /// <para>The link</para>
49         /// <para></para>
50         /// </returns>
51         [MethodImpl(MethodImplOptions.AggressiveInlining)]
52         public override TLinkAddress Update(IList<TLinkAddress>? restriction,
53         ↪ IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler)
54         {
55             var constants = _constants;
56             var links = _links;
57             links.EnsureCreated(links.GetSource(substitution), links.GetTarget(substitution));
58             return links.Update(restriction, substitution, handler);
59         }
60     }
61 }

```

1.9 ./csharp/Platform.Data.Doublets/Decorators/LinksNullConstantToSelfReferenceResolver.cs

```

1 using System;
2 using System.Collections.Generic;
3 using System.Runtime.CompilerServices;
4 using Platform.Delegates;
5
6 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8 namespace Platform.Data.Doublets.Decorators
9 {
10     /// <summary>
11     /// <para>
12     /// Represents the links null constant to self reference resolver.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     /// <seealso cref="LinksDecoratorBase{TLinkAddress}"/>
17     public class LinksNullConstantToSelfReferenceResolver<TLinkAddress> :
18     ↪ LinksDecoratorBase<TLinkAddress> where TLinkAddress : struct
19     {
20         /// <summary>
21         /// <para>
22         /// Initializes a new <see cref="LinksNullConstantToSelfReferenceResolver"/> instance.
23         /// </para>

```

```

23     /// <para></para>
24     /// </summary>
25     /// <param name="links">
26     /// <para>A links.</para>
27     /// <para></para>
28     /// </param>
29     [MethodImpl(MethodImplOptions.AggressiveInlining)]
30     public LinksNullConstantToSelfReferenceResolver(ILinks<TLinkAddress> links) :
        ↪ base(links) { }
31
32     /// <summary>
33     /// <para>
34     /// Creates the substitution.
35     /// </para>
36     /// <para></para>
37     /// </summary>
38     /// <param name="substitution">
39     /// <para>The substitution.</para>
40     /// <para></para>
41     /// </param>
42     /// <returns>
43     /// <para>The link</para>
44     /// <para></para>
45     /// </returns>
46     [MethodImpl(MethodImplOptions.AggressiveInlining)]
47     public override TLinkAddress Create(IList<TLinkAddress>? substitution,
        ↪ WriteHandler<TLinkAddress>? handler)
48     {
49         return _links.CreatePoint(handler);
50     }
51
52     /// <summary>
53     /// <para>
54     /// Updates the substitution.
55     /// </para>
56     /// <para></para>
57     /// </summary>
58     /// <param name="restriction">
59     /// <para>The substitution.</para>
60     /// <para></para>
61     /// </param>
62     /// <param name="substitution">
63     /// <para>The substitution.</para>
64     /// <para></para>
65     /// </param>
66     /// <returns>
67     /// <para>The link</para>
68     /// <para></para>
69     /// </returns>
70     [MethodImpl(MethodImplOptions.AggressiveInlining)]
71     public override TLinkAddress Update(IList<TLinkAddress>? restriction,
        ↪ IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler) =>
        ↪ _links.Update(restriction, _links.ResolveConstantAsSelfReference(_constants.Null,
        ↪ restriction, substitution), handler);
72 }
73 }

```

1.10 ./csharp/Platform.Data.Doublets/Decorators/LinksUniquenessResolver.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Delegates;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Decorators
9  {
10     /// <summary>
11     /// <para>
12     /// Represents the links uniqueness resolver.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     /// <seealso cref="LinksDecoratorBase{TLinkAddress}" />
17     public class LinksUniquenessResolver<TLinkAddress> : LinksDecoratorBase<TLinkAddress> where
        ↪ TLinkAddress : struct
18     {
19         private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
        ↪ EqualityComparer<TLinkAddress>.Default;

```

```

20
21 /// <summary>
22 /// <para>
23 /// Initializes a new <see cref="LinksUniquenessResolver"/> instance.
24 /// </para>
25 /// <para></para>
26 /// </summary>
27 /// <param name="links">
28 /// <para>A links.</para>
29 /// <para></para>
30 /// </param>
31 [MethodImpl(MethodImplOptions.AggressiveInlining)]
32 public LinksUniquenessResolver(ILinks<TLinkAddress> links) : base(links) { }
33
34 /// <summary>
35 /// <para>
36 /// Updates the restriction.
37 /// </para>
38 /// <para></para>
39 /// </summary>
40 /// <param name="restriction">
41 /// <para>The restriction.</para>
42 /// <para></para>
43 /// </param>
44 /// <param name="substitution">
45 /// <para>The substitution.</para>
46 /// <para></para>
47 /// </param>
48 /// <returns>
49 /// <para>The link</para>
50 /// <para></para>
51 /// </returns>
52 [MethodImpl(MethodImplOptions.AggressiveInlining)]
53 public override TLinkAddress Update(IList<TLinkAddress>? restriction,
54 ↪ IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler)
55 {
56     var constants = _constants;
57     var links = _links;
58     var newLinkAddress = links.SearchOrDefault(links.GetSource(substitution),
59 ↪ links.GetTarget(substitution));
60     if (_equalityComparer.Equals(newLinkAddress, default))
61     {
62         return links.Update(restriction, substitution, handler);
63     }
64     return ResolveAddressChangeConflict(links.GetIndex(restriction), newLinkAddress,
65 ↪ handler);
66 }
67
68 /// <summary>
69 /// <para>
70 /// Resolves the address change conflict using the specified old link address.
71 /// </para>
72 /// <para></para>
73 /// </summary>
74 /// <param name="oldLinkAddress">
75 /// <para>The old link address.</para>
76 /// <para></para>
77 /// </param>
78 /// <param name="newLinkAddress">
79 /// <para>The new link address.</para>
80 /// <para></para>
81 /// </param>
82 /// <returns>
83 /// <para>The new link address.</para>
84 /// <para></para>
85 /// </returns>
86 [MethodImpl(MethodImplOptions.AggressiveInlining)]
87 protected virtual TLinkAddress ResolveAddressChangeConflict(TLinkAddress oldLinkAddress,
88 ↪ TLinkAddress newLinkAddress, WriteHandler<TLinkAddress>? handler)
89 {
90     if (!_equalityComparer.Equals(oldLinkAddress, newLinkAddress) &&
91 ↪ _links.Exists(oldLinkAddress))
92     {
93         return _facade.Delete(oldLinkAddress, handler);
94     }
95     return _links.Constants.Continue;
96 }
97

```

```

92     }
93 }

```

1.11 ./csharp/Platform.Data.Doublets/Decorators/LinksUniquenessValidator.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Delegates;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Decorators
9  {
10     /// <summary>
11     /// <para>
12     /// Represents the links uniqueness validator.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     /// <seealso cref="LinksDecoratorBase{TLinkAddress}" />
17     public class LinksUniquenessValidator<TLinkAddress> : LinksDecoratorBase<TLinkAddress> where
18         ↪ TLinkAddress : struct
19     {
20         /// <summary>
21         /// <para>
22         /// Initializes a new <see cref="LinksUniquenessValidator" /> instance.
23         /// </para>
24         /// <para></para>
25         /// </summary>
26         /// <param name="links">
27         /// <para>A links.</para>
28         /// <para></para>
29         /// </param>
30         [MethodImpl(MethodImplOptions.AggressiveInlining)]
31         public LinksUniquenessValidator(ILinks<TLinkAddress> links) : base(links) { }
32
33         /// <summary>
34         /// <para>
35         /// Updates the restriction.
36         /// </para>
37         /// <para></para>
38         /// </summary>
39         /// <param name="restriction">
40         /// <para>The restriction.</para>
41         /// <para></para>
42         /// </param>
43         /// <param name="substitution">
44         /// <para>The substitution.</para>
45         /// <para></para>
46         /// </param>
47         /// <returns>
48         /// <para>The link</para>
49         /// <para></para>
50         /// </returns>
51         [MethodImpl(MethodImplOptions.AggressiveInlining)]
52         public override TLinkAddress Update(ICollection<TLinkAddress>? restriction,
53         ↪ ICollection<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler)
54         {
55             var links = _links;
56             var constants = _constants;
57             links.EnsureDoesNotExists(links.GetSource(substitution),
58             ↪ links.GetTarget(substitution));
59             return links.Update(restriction, substitution, handler);
60         }
61     }
62 }

```

1.12 ./csharp/Platform.Data.Doublets/Decorators/LinksUsagesValidator.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Delegates;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Decorators
9  {
10     /// <summary>
11     /// <para>

```

```

12  /// Represents the links usages validator.
13  /// </para>
14  /// <para></para>
15  /// </summary>
16  /// <seealso cref="LinksDecoratorBase{TLinkAddress}"/>
17  public class LinksUsagesValidator<TLinkAddress> : LinksDecoratorBase<TLinkAddress> where
    ↪ TLinkAddress : struct
18  {
19      /// <summary>
20      /// <para>
21      /// Initializes a new <see cref="LinksUsagesValidator"/> instance.
22      /// </para>
23      /// <para></para>
24      /// </summary>
25      /// <param name="links">
26      /// <para>A links.</para>
27      /// <para></para>
28      /// </param>
29      [MethodImpl(MethodImplOptions.AggressiveInlining)]
30      public LinksUsagesValidator(ILinks<TLinkAddress> links) : base(links) { }
31
32      /// <summary>
33      /// <para>
34      /// Updates the restriction.
35      /// </para>
36      /// <para></para>
37      /// </summary>
38      /// <param name="restriction">
39      /// <para>The restriction.</para>
40      /// <para></para>
41      /// </param>
42      /// <param name="substitution">
43      /// <para>The substitution.</para>
44      /// <para></para>
45      /// </param>
46      /// <returns>
47      /// <para>The link</para>
48      /// <para></para>
49      /// </returns>
50      [MethodImpl(MethodImplOptions.AggressiveInlining)]
51      public override TLinkAddress Update(IList<TLinkAddress>? restriction,
    ↪ IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler)
52      {
53          var links = _links;
54          links.EnsureNoUsages(links.GetIndex(restriction));
55          return links.Update(restriction, substitution, handler);
56      }
57
58      /// <summary>
59      /// <para>
60      /// Deletes the restriction.
61      /// </para>
62      /// <para></para>
63      /// </summary>
64      /// <param name="restriction">
65      /// <para>The restriction.</para>
66      /// <para></para>
67      /// </param>
68      [MethodImpl(MethodImplOptions.AggressiveInlining)]
69      public override TLinkAddress Delete(IList<TLinkAddress>? restriction,
    ↪ WriteHandler<TLinkAddress>? handler)
70      {
71          var links = _links;
72          var link = links.GetIndex(restriction);
73          links.EnsureNoUsages(link);
74          return links.Delete(restriction, handler);
75      }
76  }
77  }

```

1.13 ./csharp/Platform.Data.Doublets/Decorators/LoggingDecorator.cs

```

1  using System.Collections.Generic;
2  using System.IO;
3  using Platform.Delegates;
4
5  namespace Platform.Data.Doublets.Decorators
6  {
7      public class LoggingDecorator<TLinkAddress> : LinksDecoratorBase<TLinkAddress> where
    ↪ TLinkAddress : struct

```

```

8 {
9     private readonly Stream _logStream;
10    private readonly StreamWriter _logStreamWriter;
11    public LoggingDecorator(ILinks<TLinkAddress> links, Stream logStream) : base(links)
12    {
13        _logStream = logStream;
14        _logStreamWriter = new StreamWriter(_logStream);
15        _logStreamWriter.AutoFlush = true;
16    }
17
18    public override TLinkAddress Create(IList<TLinkAddress>? substitution,
19    ↪ WriteHandler<TLinkAddress>? handler)
20    {
21        WriteHandlerState<TLinkAddress> handlerState = new(_constants.Continue,
22    ↪ _constants.Break, handler);
23        return base.Create(substitution, (before, after) =>
24        {
25            handlerState.Handle(before, after);
26            _logStreamWriter.WriteLine($"Create. Before: {new Link<TLinkAddress>(before)}.
27    ↪ After: {new Link<TLinkAddress>(after)}");
28            return _constants.Continue;
29        });
30    }
31
32    public override TLinkAddress Update(IList<TLinkAddress>? restriction,
33    ↪ IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler)
34    {
35        WriteHandlerState<TLinkAddress> handlerState = new(_constants.Continue,
36    ↪ _constants.Break, handler);
37        return base.Update(restriction, substitution, (before, after) =>
38        {
39            handlerState.Handle(before, after);
40            _logStreamWriter.WriteLine($"Update. Before: {new Link<TLinkAddress>(before)}.
41    ↪ After: {new Link<TLinkAddress>(after)}");
42            return _constants.Continue;
43        });
44    }
45
46    public override TLinkAddress Delete(IList<TLinkAddress>? restriction,
47    ↪ WriteHandler<TLinkAddress>? handler)
48    {
49        WriteHandlerState<TLinkAddress> handlerState = new(_constants.Continue,
50    ↪ _constants.Break, handler);
51        return base.Delete(restriction, (before, after) =>
52        {
53            handlerState.Handle(before, after);
54            _logStreamWriter.WriteLine($"Delete. Before: {new Link<TLinkAddress>(before)}.
55    ↪ After: {new Link<TLinkAddress>(after)}");
56            return _constants.Continue;
57        });
58    }
59 }

```

1.14 ./csharp/Platform.Data.Doublets/Decorators/NonNullContentsLinkDeletionResolver.cs

```

1 using System;
2 using System.Collections.Generic;
3 using System.Runtime.CompilerServices;
4 using Platform.Delegates;
5
6 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8 namespace Platform.Data.Doublets.Decorators
9 {
10     /// <summary>
11     /// <para>
12     /// Represents the non null contents link deletion resolver.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     /// <seealso cref="LinksDecoratorBase{TLinkAddress}"/>
17     public class NonNullContentsLinkDeletionResolver<TLinkAddress> :
18     ↪ LinksDecoratorBase<TLinkAddress> where TLinkAddress : struct
19     {
20         /// <summary>
21         /// <para>
22         /// Initializes a new <see cref="NonNullContentsLinkDeletionResolver"/> instance.
23         /// </para>

```

```

23     /// <para></para>
24     /// </summary>
25     /// <param name="links">
26     /// <para>A links.</para>
27     /// <para></para>
28     /// </param>
29     [MethodImpl(MethodImplOptions.AggressiveInlining)]
30     public NonNullContentsLinkDeletionResolver(ILinks<TLinkAddress> links) : base(links) { }
31
32     /// <summary>
33     /// <para>
34     /// Deletes the restriction.
35     /// </para>
36     /// <para></para>
37     /// </summary>
38     /// <param name="restriction">
39     /// <para>The restriction.</para>
40     /// <para></para>
41     /// </param>
42     [MethodImpl(MethodImplOptions.AggressiveInlining)]
43     public override TLinkAddress Delete(IList<TLinkAddress>? restriction,
44     ↪ WriteHandler<TLinkAddress>? handler)
45     {
46         var linkIndex = _links.GetIndex(restriction);
47         var constants = _links.Constants;
48         WriteHandlerState<TLinkAddress> handlerResult = new(constants.Continue,
49         ↪ constants.Break, handler);
50         handlerResult.Apply(_links.EnforceResetValues(linkIndex, handlerResult.Handler));
51         handlerResult.Apply(_links.Delete(restriction, handlerResult.Handler));
52         return handlerResult.Result;
53     }
54 }

```

1.15 ./csharp/Platform.Data.Doublets/Decorators/UInt32Links.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Delegates;
5  using TLinkAddress = System.UInt32;
6
7  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
8
9  namespace Platform.Data.Doublets.Decorators
10 {
11     /// <summary>
12     /// <para>
13     /// Represents the int 32 links.
14     /// </para>
15     /// <para></para>
16     /// </summary>
17     /// <seealso cref="LinksDisposableDecoratorBase{TLinkAddress}"/>
18     public class UInt32Links : LinksDisposableDecoratorBase<TLinkAddress>
19     {
20         /// <summary>
21         /// <para>
22         /// Initializes a new <see cref="UInt32Links"/> instance.
23         /// </para>
24         /// <para></para>
25         /// </summary>
26         /// <param name="links">
27         /// <para>A links.</para>
28         /// <para></para>
29         /// </param>
30         [MethodImpl(MethodImplOptions.AggressiveInlining)]
31         public UInt32Links(ILinks<TLinkAddress> links) : base(links) { }
32
33         /// <summary>
34         /// <para>
35         /// Creates the substitution.
36         /// </para>
37         /// <para></para>
38         /// </summary>
39         /// <param name="substitution">
40         /// <para>The substitution.</para>
41         /// <para></para>
42         /// </param>
43         /// <returns>
44         /// <para>The link</para>

```



```

45     /// <para></para>
46     /// </returns>
47     [MethodImpl(MethodImplOptions.AggressiveInlining)]
48     public override TLinkAddress Create(ICollection<TLinkAddress>? substitution,
49     ↪ WriteHandler<TLinkAddress>? handler) => _links.CreatePoint(handler);
50
51     /// <summary>
52     /// <para>
53     /// Updates the substitution.
54     /// </para>
55     /// </summary>
56     /// <param name="restriction">
57     /// <para>The substitution.</para>
58     /// </para>
59     /// </param>
60     /// <param name="substitution">
61     /// <para>The substitution.</para>
62     /// </para>
63     /// </param>
64     /// </returns>
65     /// <para>The link</para>
66     /// </returns>
67     [MethodImpl(MethodImplOptions.AggressiveInlining)]
68     public override TLinkAddress Update(ICollection<TLinkAddress>? restriction,
69     ↪ ICollection<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler)
70     {
71         var constants = _constants;
72         var indexPartConstant = constants.IndexPart;
73         var sourcePartConstant = constants.SourcePart;
74         var targetPartConstant = constants.TargetPart;
75         var nullConstant = constants.Null;
76         var itselfConstant = constants.Itself;
77         var existedLink = nullConstant;
78         var updatedLink = restriction[indexPartConstant];
79         var newSource = substitution[sourcePartConstant];
80         var newTarget = substitution[targetPartConstant];
81         var links = _links;
82         if (newSource != itselfConstant && newTarget != itselfConstant)
83         {
84             existedLink = links.SearchOrDefault(newSource, newTarget);
85         }
86         if (existedLink == nullConstant)
87         {
88             var before = links.GetLink(updatedLink);
89             if (before[sourcePartConstant] != newSource || before[targetPartConstant] !=
90             ↪ newTarget)
91             {
92                 var source = newSource == itselfConstant ? updatedLink : newSource;
93                 var target = newTarget == itselfConstant ? updatedLink : newTarget;
94                 return links.Update(new Link<TLinkAddress>(updatedLink, source, target),
95                 ↪ handler);
96             }
97             return _links.Constants.Continue;
98         }
99         else
100         {
101             return _facade.MergeAndDelete(updatedLink, existedLink, handler);
102         }
103     }
104
105     /// <summary>
106     /// <para>
107     /// Deletes the substitution.
108     /// </para>
109     /// </summary>
110     /// <param name="restriction">
111     /// <para>The substitution.</para>
112     /// </para>
113     /// </param>
114     [MethodImpl(MethodImplOptions.AggressiveInlining)]
115     public override TLinkAddress Delete(ICollection<TLinkAddress>? restriction,
116     ↪ WriteHandler<TLinkAddress>? handler)
117     {
118         var linkIndex = _links.GetIndex(restriction);
119         var constants = _links.Constants;

```

```

118         WriteHandlerState<TLinkAddress> handlerState = new(constants.Continue,
            ↪ constants.Break, handler);
119         handlerState.Apply(_links.EnforceResetValues(linkIndex, handlerState.Handler));
120         handlerState.Apply(_facade.DeleteAllUsages(linkIndex, handlerState.Handler));
121         handlerState.Apply(_links.Delete(restriction, handlerState.Handler));
122         return handlerState.Result;
123     }
124 }
125 }

```

1.16 ./csharp/Platform.Data.Doublets/Decorators/UInt64Links.cs

```

1  using System.Collections.Generic;
2  using System.Net.Security;
3  using System.Runtime.CompilerServices;
4  using Platform.Delegates;
5  using TLinkAddress = System.UInt64;
6
7  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
8
9  namespace Platform.Data.Doublets.Decorators
10 {
11     /// <summary>
12     /// <para>Represents a combined decorator that implements the basic logic for interacting
13     ↪ with the links storage for links with addresses represented as <see cref="System.UInt64"
14     ↪ />.</para>
15     /// <para>Представляет комбинированный декоратор, реализующий основную логику по
16     ↪ взаимодействию с хранилищем связей, для связей с адресами представленными в виде <see
17     ↪ cref="System.UInt64"/>.</para>
18     /// </summary>
19     /// <remarks>
20     /// Возможные оптимизации:
21     /// Объединение в одном поле Source и Target с уменьшением до 32 бит.
22     /// + меньше объём БД
23     /// - меньше производительность
24     /// - больше ограничение на количество связей в БД)
25     /// Ленивое хранение размеров поддеревьев (расчитываемое по мере использования БД)
26     /// + меньше объём БД
27     /// - больше сложность
28     ///
29     /// Текущее теоретическое ограничение на индекс связи, из-за использования 5 бит в размере
30     ↪ поддеревьев для AVL баланса и флагов нитей: 2 в степени(64 минус 5 равно 59 ) равно 576
31     ↪ 460 752 303 423 488
32     /// Желательно реализовать поддержку переключения между деревьями и битовыми индексами
33     ↪ (битовыми строками) - вариант матрицы (выстраиваемой лениво).
34     ///
35     /// Решить отключать ли проверки при компиляции под Release. Т.е. исключения будут
36     ↪ выбрасываться только при #if DEBUG
37     /// </remarks>
38     public class UInt64Links : LinksDisposableDecoratorBase<TLinkAddress>
39     {
40         /// <summary>
41         /// <para>
42         /// Initializes a new <see cref="UInt64Links"/> instance.
43         /// </para>
44         /// <para></para>
45         /// </summary>
46         /// <param name="links">
47         /// <para>A links.</para>
48         /// <para></para>
49         /// </param>
50         [MethodImpl(MethodImplOptions.AggressiveInlining)]
51         public UInt64Links(ILinks<TLinkAddress> links) : base(links) { }
52
53         /// <summary>
54         /// <para>
55         /// Creates the substitution.
56         /// </para>
57         /// <para></para>
58         /// </summary>
59         /// <param name="substitution">
60         /// <para>The substitution.</para>
61         /// <para></para>
62         /// </param>
63         /// <returns>
64         /// <para>The TLinkAddress</para>
65         /// <para></para>
66         /// </returns>
67         [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

60 public override TLinkAddress Create(IList<TLinkAddress>? substitution,
    ↳ WriteHandler<TLinkAddress>? handler) => _links.CreatePoint(handler);
61
62 /// <summary>
63 /// <para>
64 /// Updates the substitution.
65 /// </para>
66 /// <para></para>
67 /// </summary>
68 /// <param name="restriction">
69 /// <para>The substitution.</para>
70 /// <para></para>
71 /// </param>
72 /// <param name="substitution">
73 /// <para>The substitution.</para>
74 /// <para></para>
75 /// </param>
76 /// <returns>
77 /// <para>The TLinkAddress</para>
78 /// <para></para>
79 /// </returns>
80 [MethodImpl(MethodImplOptions.AggressiveInlining)]
81 public override TLinkAddress Update(IList<TLinkAddress>? restriction,
    ↳ IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler)
82 {
83     var constants = _constants;
84     var indexPartConstant = constants.IndexPart;
85     var sourcePartConstant = constants.SourcePart;
86     var targetPartConstant = constants.TargetPart;
87     var nullConstant = constants.Null;
88     var itselfConstant = constants.Itself;
89     var existedLink = nullConstant;
90     var updatedLink = restriction[indexPartConstant];
91     var newSource = substitution[sourcePartConstant];
92     var newTarget = substitution[targetPartConstant];
93     var links = _links;
94     if (newSource != itselfConstant && newTarget != itselfConstant)
95     {
96         existedLink = links.SearchOrDefault(newSource, newTarget);
97     }
98     if (existedLink == nullConstant)
99     {
100         var before = links.GetLink(updatedLink);
101         if (before[sourcePartConstant] != newSource || before[targetPartConstant] !=
            ↳ newTarget)
102         {
103             var source = newSource == itselfConstant ? updatedLink : newSource;
104             var target = newTarget == itselfConstant ? updatedLink : newTarget;
105             return links.Update(new Link<TLinkAddress>(updatedLink, source, target),
                ↳ handler);
106         }
107         return _links.Constants.Continue;
108     }
109     else
110     {
111         return _facade.MergeAndDelete(updatedLink, existedLink, handler);
112     }
113 }
114
115 /// <summary>
116 /// <para>
117 /// Deletes the substitution.
118 /// </para>
119 /// <para></para>
120 /// </summary>
121 /// <param name="restriction">
122 /// <para>The substitution.</para>
123 /// <para></para>
124 /// </param>
125 [MethodImpl(MethodImplOptions.AggressiveInlining)]
126 public override TLinkAddress Delete(IList<TLinkAddress>? restriction,
    ↳ WriteHandler<TLinkAddress>? handler)
127 {
128     var linkIndex = _links.GetIndex(restriction);
129     var constants = _links.Constants;
130     WriteHandlerState<TLinkAddress> handlerState = new(constants.Continue,
        ↳ constants.Break, handler);
131     handlerState.Apply(_links.EnforceResetValues(linkIndex, handlerState.Handler));

```

```

132         handlerState.Apply(_facade.DeleteAllUsages(linkIndex, handlerState.Handler));
133         handlerState.Apply(_links.Delete(restriction, handlerState.Handler));
134         return handlerState.Result;
135     }
136 }
137 }

```

1.17 ./csharp/Platform.Data.Doublets/Decorators/UniLinks.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Linq;
4  using Platform.Collections;
5  using Platform.Collections.Lists;
6  using Platform.Data.Universal;
7  using Platform.Delegates;
8
9  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
10
11 namespace Platform.Data.Doublets.Decorators
12 {
13     /// <remarks>
14     /// What does empty pattern (for condition or substitution) mean? Nothing or Everything?
15     /// Now we go with nothing. And nothing is something one, but empty, and cannot be changed
16     /// ↪ by itself. But can cause creation (update from nothing) or deletion (update to nothing).
17     ///
18     /// TODO: Decide to change to IDoubletLinks or not to change. (Better to create
19     /// ↪ DefaultUniLinksBase, that contains logic itself and can be implemented using both
20     /// ↪ IDoubletLinks and ILinks.)
21     /// </remarks>
22     internal class UniLinks<TLinkAddress> : LinksDecoratorBase<TLinkAddress>,
23     ↪ IUniLinks<TLinkAddress> where TLinkAddress : struct
24     {
25         private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
26         ↪ EqualityComparer<TLinkAddress>.Default;
27
28         /// <summary>
29         /// <para>
30         /// Initializes a new <see cref="UniLinks"/> instance.
31         /// </para>
32         /// <para></para>
33         /// </summary>
34         /// <param name="links">
35         /// <para>A links.</para>
36         /// <para></para>
37         /// </param>
38         public UniLinks(ILinks<TLinkAddress> links) : base(links) { }
39         private struct Transition
40         {
41             /// <summary>
42             /// <para>
43             /// The before.
44             /// </para>
45             /// <para></para>
46             /// </summary>
47             public IList<TLinkAddress>? Before;
48             /// <summary>
49             /// <para>
50             /// The after.
51             /// </para>
52             /// <para></para>
53             /// </summary>
54             public IList<TLinkAddress>? After;
55
56             /// <summary>
57             /// <para>
58             /// Initializes a new <see cref="Transition"/> instance.
59             /// </para>
60             /// <para></para>
61             /// </summary>
62             /// <param name="before">
63             /// <para>A before.</para>
64             /// <para></para>
65             /// </param>
66             /// <param name="after">
67             /// <para>A after.</para>
68             /// <para></para>
69             /// </param>
70             public Transition(IList<TLinkAddress>? before, IList<TLinkAddress>? after)
71             {

```

```

67         Before = before;
68         After = after;
69     }
70 }
71
72 //public static readonly TLinkAddress NullConstant =
73     ↳ Use<LinksConstants<TLinkAddress>>.Single.Null;
74 //public static readonly IReadOnlyList<TLinkAddress> NullLink = new
75     ↳ ReadOnlyCollection<TLinkAddress>(new List<TLinkAddress> { NullConstant,
76     ↳ NullConstant, NullConstant });
77
78 // TODO: Подумать о том, как реализовать древовидный Restriction и Substitution
79     ↳ (Links-Expression)
80 /// <summary>
81 /// <para>
82 /// Triggers the restriction.
83 /// </para>
84 /// <para></para>
85 /// </summary>
86 /// <param name="restriction">
87 /// <para>The restriction.</para>
88 /// <para></para>
89 /// </param>
90 /// <param name="matchedHandler">
91 /// <para>The matched handler.</para>
92 /// <para></para>
93 /// </param>
94 /// <param name="substitution">
95 /// <para>The substitution.</para>
96 /// <para></para>
97 /// </param>
98 /// <param name="substitutedHandler">
99 /// <para>The substituted handler.</para>
100 /// <para></para>
101 /// </param>
102 /// <returns>
103 /// <para>The link</para>
104 /// <para></para>
105 /// </returns>
106 public TLinkAddress Trigger(IList<TLinkAddress>? restriction,
107     ↳ WriteHandler<TLinkAddress>? matchedHandler, IList<TLinkAddress>? substitution,
108     ↳ WriteHandler<TLinkAddress>? substitutedHandler)
109 {
110     ///List<Transition> transitions = null;
111     ///if (!restriction.IsNullOrEmpty())
112     ///{
113     ///    // Есть причина делать проход (чтение)
114     ///    if (matchedHandler != null)
115     ///    {
116     ///        if (!substitution.IsNullOrEmpty())
117     ///        {
118     ///            // restriction => { 0, 0, 0 } | { 0 } // Create
119     ///            // substitution => { itself, 0, 0 } | { itself, itself, itself } //
120     ↳ Create / Update
121     ///            // substitution => { 0, 0, 0 } | { 0 } // Delete
122     ///            transitions = new List<Transition>();
123     ///            if (Equals(substitution[Constants.IndexPart], Constants.Null))
124     ///            {
125     ///                // If index is Null, that means we always ignore every other
126     ↳ value (they are also Null by definition)
127     ///                var matchDecision = matchedHandler(, NullLink);
128     ///                if (Equals(matchDecision, Constants.Break))
129     ///                    return false;
130     ///                if (!Equals(matchDecision, Constants.Skip))
131     ///                    transitions.Add(new Transition(matchedLink, newValue));
132     ///            }
133     ///            else
134     ///            {
135     ///                Func<T, bool> handler;
136     ///                handler = link =>
137     ///                {
138     ///                    var matchedLink = Memory.GetLinkValue(link);
139     ///                    var newValue = Memory.GetLinkValue(link);
140     ///                    newValue[Constants.IndexPart] = Constants.Itself;
141     ///                    newValue[Constants.SourcePart] =
142     ↳ Equals(substitution[Constants.SourcePart], Constants.Itself) ?
143     ↳ matchedLink[Constants.IndexPart] : substitution[Constants.SourcePart];

```

```

134      newLink[Constants.TargetPart] =
135      ↪ Equals(substitution[Constants.TargetPart], Constants.Itself) ?
136      ↪ matchedLink[Constants.IndexPart] : substitution[Constants.TargetPart];
137      var matchDecision = matchedHandler(matchedLink, newValue);
138      if (Equals(matchDecision, Constants.Break))
139      return false;
140      if (!Equals(matchDecision, Constants.Skip))
141      transitions.Add(new Transition(matchedLink, newValue));
142      return true;
143      };
144      if (!Memory.Each(handler, restriction))
145      return Constants.Break;
146      }
147      }
148      else
149      {
150      Func<T, bool> handler = link =>
151      {
152      var matchedLink = Memory.GetLinkValue(link);
153      var matchDecision = matchedHandler(matchedLink, matchedLink);
154      return !Equals(matchDecision, Constants.Break);
155      };
156      if (!Memory.Each(handler, restriction))
157      return Constants.Break;
158      }
159      }
160      else
161      {
162      if (substitution != null)
163      {
164      transitions = new List<ILink<T>>();
165      Func<T, bool> handler = link =>
166      {
167      var matchedLink = Memory.GetLinkValue(link);
168      transitions.Add(matchedLink);
169      return true;
170      };
171      if (!Memory.Each(handler, restriction))
172      return Constants.Break;
173      }
174      else
175      {
176      return Constants.Continue;
177      }
178      }
179      }
180      }
181      }
182      }
183      }
184      }
185      }
186      }
187      }
188      }
189      }
190      }
191      }
192      }
193      }
194      }
195      }
196      }
197      }
198      }
199      }
200      }
201      }
202      }
203      }
204      }
205      }
206      }
207      }

```

```

208 // {
209 //     // List<IList<T>> matchedLinks = null;
210 //     if (matchedHandler != null)
211 //     {
212 //         matchedLinks = new List<IList<T>>();
213 //         Func<T, bool> handler = link =>
214 //         {
215 //             var matchedLink = Memory.GetLinkValue(link);
216 //             var matchDecision = matchedHandler(matchedLink);
217 //             if (Equals(matchDecision, Constants.Break))
218 //                 return false;
219 //             if (!Equals(matchDecision, Constants.Skip))
220 //                 matchedLinks.Add(matchedLink);
221 //             return true;
222 //         };
223 //         if (!Memory.Each(handler, restriction))
224 //             return Constants.Break;
225 //     }
226 //     if (!matchedLinks.IsNullOrEmpty())
227 //     {
228 //         var totalMatchedLinks = matchedLinks.Count;
229 //         for (var i = 0; i < totalMatchedLinks; i++)
230 //         {
231 //             var matchedLink = matchedLinks[i];
232 //             if (substitutedHandler != null)
233 //             {
234 //                 var newValue = new List<T>(); // TODO: Prepare value to update here
235 //                 // TODO: Decide is it actually needed to use Before and After
236 //                 ↪ substitution handling.
237 //                 var substitutedDecision = substitutedHandler(matchedLink,
238 //                 ↪ newValue);
239 //                 if (Equals(substitutedDecision, Constants.Break))
240 //                     return Constants.Break;
241 //                 if (Equals(substitutedDecision, Constants.Continue))
242 //                 {
243 //                     // Actual update here
244 //                     Memory.SetLinkValue(newValue);
245 //                 }
246 //                 if (Equals(substitutedDecision, Constants.Skip))
247 //                 {
248 //                     // Cancel the update. TODO: decide use separate Cancel
249 //                     ↪ constant or Skip is enough?
250 //                 }
251 //             }
252 //         }
253 //     }
254 // }
255 return _constants.Continue;
256 }
257
258 /// <summary>
259 /// <para>
260 /// Triggers the pattern or condition.
261 /// </para>
262 /// <para></para>
263 /// </summary>
264 /// <param name="patternOrCondition">
265 /// <para>The pattern or condition.</para>
266 /// </param>
267 /// <param name="matchHandler">
268 /// <para>The match handler.</para>
269 /// </param>
270 /// <param name="substitution">
271 /// <para>The substitution.</para>
272 /// </param>
273 /// <param name="substitutionHandler">
274 /// <para>The substitution handler.</para>
275 /// </param>
276 /// <exception cref="NotImplementedException">
277 /// <para></para>
278 /// </exception>
279 /// <exception cref="NotSupportedException">
280 /// <para></para>
281 /// </exception>
282

```

```

283     /// <para></para>
284     /// </exception>
285     /// <exception cref="NotSupportedException">
286     /// <para></para>
287     /// <para></para>
288     /// </exception>
289     /// <exception cref="NotSupportedException">
290     /// <para></para>
291     /// <para></para>
292     /// </exception>
293     /// <exception cref="NotSupportedException">
294     /// <para></para>
295     /// <para></para>
296     /// </exception>
297     /// <returns>
298     /// <para>The link</para>
299     /// <para></para>
300     /// </returns>
301 public TLinkAddress Trigger(ICollection<TLinkAddress>? patternOrCondition,
    ↪ ReadHandler<TLinkAddress>? matchHandler, ICollection<TLinkAddress>? substitution,
    ↪ WriteHandler<TLinkAddress>? substitutionHandler)
302 {
303     var constants = _constants;
304     if (patternOrCondition.IsNullOrEmpty() && substitution.IsNullOrEmpty())
305     {
306         return constants.Continue;
307     }
308     else if (patternOrCondition.EqualTo(substitution)) // Should be Each here TODO:
    ↪ Check if it is a correct condition
309     {
310         // Or it only applies to trigger without matchHandler.
311         throw new NotImplementedException();
312     }
313     else if (!substitution.IsNullOrEmpty()) // Creation
314     {
315         var before = Array.Empty<TLinkAddress>();
316         // Что должно означать False здесь? Остановиться (перестать идти) или пропустить
    ↪ (пройти мимо) или пустить (взять)?
317         if (matchHandler != null && _equalityComparer.Equals(matchHandler(before),
    ↪ constants.Break))
318         {
319             return constants.Break;
320         }
321         var after = (ICollection<TLinkAddress>?)substitution.ToArray();
322         if (_equalityComparer.Equals(after[0], default))
323         {
324             var newLink = _links.Create();
325             after[0] = newLink;
326         }
327         if (substitution.Count == 1)
328         {
329             after = _links.GetLink(substitution[0]);
330         }
331         else if (substitution.Count == 3)
332         {
333             //Links.Create(after);
334         }
335         else
336         {
337             throw new NotSupportedException();
338         }
339         return matchHandler != null ? substitutionHandler(before, after) :
    ↪ constants.Continue;
340     }
341     else if (!patternOrCondition.IsNullOrEmpty()) // Deletion
342     {
343         if (patternOrCondition.Count == 1)
344         {
345             var linkToDelete = patternOrCondition[0];
346             var before = _links.GetLink(linkToDelete);
347             if (matchHandler != null && _equalityComparer.Equals(matchHandler(before),
    ↪ constants.Break))
348             {
349                 return constants.Break;
350             }
351             var after = Array.Empty<TLinkAddress>();
352             _links.Update(linkToDelete, constants.Null, constants.Null);
353             _links.Delete(linkToDelete);

```



```

354         return matchHandler != null ? substitutionHandler(before, after) :
           ↪ constants.Continue;
355     }
356     else
357     {
358         throw new NotSupportedException();
359     }
360 }
361 else // Replace / Update
362 {
363     if (patternOrCondition.Count == 1) //-V3125
364     {
365         var linkToUpdate = patternOrCondition[0];
366         var before = _links.GetLink(linkToUpdate);
367         if (matchHandler != null && _equalityComparer.Equals(matchHandler(before),
           ↪ constants.Break))
368         {
369             return constants.Break;
370         }
371         var after = (IList<TLinkAddress>?)substitution.ToArray(); //-V3125
372         if (_equalityComparer.Equals(after[0], default))
373         {
374             after[0] = linkToUpdate;
375         }
376         if (substitution.Count == 1)
377         {
378             if (!_equalityComparer.Equals(substitution[0], linkToUpdate))
379             {
380                 after = _links.GetLink(substitution[0]);
381                 _links.Update(linkToUpdate, constants.Null, constants.Null);
382                 _links.Delete(linkToUpdate);
383             }
384         }
385         else if (substitution.Count == 3)
386         {
387             //Links.Update(after);
388         }
389         else
390         {
391             throw new NotSupportedException();
392         }
393         return matchHandler != null ? substitutionHandler(before, after) :
           ↪ constants.Continue;
394     }
395     else
396     {
397         throw new NotSupportedException();
398     }
399 }
400 }
401
402 /// <remarks>
403 /// IList[IList[IList[T]]]
404 /// |         |         |         |
405 /// |         |         |         |
406 /// |         |         |         |
407 /// |         |         |         |
408 /// |         |         |         |
409 /// |         |         |         |
410 /// |         |         |         |
411 /// |         |         |         |
412 public IList<IList<IList<TLinkAddress>?>> Trigger(IList<TLinkAddress>? condition,
           ↪ IList<TLinkAddress>? substitution)
413 {
414     var changes = new List<IList<IList<TLinkAddress>?>>();
415     var @continue = _constants.Continue;
416     Trigger(condition, AlwaysContinue, substitution, (before, after) =>
417     {
418         var change = new[] { before, after };
419         changes.Add(change);
420         return @continue;
421     });
422     return changes;
423 }
424 private TLinkAddress AlwaysContinue(IList<TLinkAddress>? linkToMatch) =>
           ↪ _constants.Continue;
425 }
426 }

```

1.18 ./csharp/Platform.Data.Doublets/Doublet.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4
5  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7  namespace Platform.Data.Doublets
8  {
9
10     /// <summary>
11     /// <para>.</para>
12     /// <para>.</para>
13     /// </summary>
14     /// <typeparam>
15     /// <para>.</para>
16     /// <para>.</para>
17     /// </typeparam>
18     public struct Doublet<T> : IEquatable<Doublet<T>>
19     {
20         private static readonly EqualityComparer<T> _equalityComparer =
21             ↪ EqualityComparer<T>.Default;
22
23         /// <summary>
24         /// <para>.</para>
25         /// <para>.</para>
26         /// </summary>
27         /// <typeparam name="T">
28         /// <para>.</para>
29         /// <para>.</para>
30         /// </typeparam>
31         public readonly T Source;
32
33         /// <summary>
34         /// <para>.</para>
35         /// <para>.</para>
36         /// </summary>
37         /// <typeparam name="T">
38         /// <para>.</para>
39         /// <para>.</para>
40         /// </typeparam>
41         public readonly T Target;
42
43         /// <summary>
44         /// <para>.</para>
45         /// <para>.</para>
46         /// </summary>
47         /// <typeparam name="T">
48         /// <para>.</para>
49         /// <para>.</para>
50         /// </typeparam>
51         /// <param name="source">
52         /// <para>.</para>
53         /// <para>.</para>
54         /// </param>
55         /// <param name="target">
56         /// <para>.</para>
57         /// <para>.</para>
58         /// </param>
59         [MethodImpl(MethodImplOptions.AggressiveInlining)]
60         public Doublet(T source, T target)
61         {
62             Source = source;
63             Target = target;
64         }
65
66         /// <summary>
67         /// <para>.</para>
68         /// <para>.</para>
69         /// </summary>
70         /// <returns>
71         /// <para>.</para>
72         /// <para>.</para>
73         /// </returns>
74         [MethodImpl(MethodImplOptions.AggressiveInlining)]
75         public override string ToString() => $"{Source}->{Target}";
76
77         /// <summary>
78         /// <para>.</para>

```

```

78     /// <para>.</para>
79     /// </summury>
80     /// <typeparam>
81     /// <para>.</para>
82     /// <para>.</para>
83     /// </typeparam>
84     /// <param name="other">
85     /// <para>.</para>
86     /// <para>.</para>
87     /// </param>
88     /// <returns>
89     /// <para>.</para>
90     /// <para>.</para>
91     /// </returns>
92     [MethodImpl(MethodImplOptions.AggressiveInlining)]
93     public bool Equals(Doublet<T> other) => _equalityComparer.Equals(Source, other.Source)
94     ↪ && _equalityComparer.Equals(Target, other.Target);
95
96     /// <summury>
97     /// <para>.</para>
98     /// <para>.</para>
99     /// </summury>
100    /// <typeparam>
101    /// <para>.</para>
102    /// <para>.</para>
103    /// </typeparam>
104    /// <param name="obj">
105    /// <para>.</para>
106    /// <para>.</para>
107    /// </param>
108    /// <returns>
109    /// <para>.</para>
110    /// <para>.</para>
111    /// </returns>
112    [MethodImpl(MethodImplOptions.AggressiveInlining)]
113    public override bool Equals(object obj) => obj is Doublet<T> doublet ?
114    ↪ base.Equals(doublet) : false;
115
116    /// <summury>
117    /// <para>.</para>
118    /// <para>.</para>
119    /// </summury>
120    /// <returns>
121    /// <para>.</para>
122    /// <para>.</para>
123    /// </returns>
124    [MethodImpl(MethodImplOptions.AggressiveInlining)]
125    public override int GetHashCode() => (Source, Target).GetHashCode();
126
127    /// <summury>
128    /// <para>.</para>
129    /// <para>.</para>
130    /// </summury>
131    /// <param name="left">
132    /// <para>.</para>
133    /// <para>.</para>
134    /// </param>
135    /// <param name="right">
136    /// <para>.</para>
137    /// <para>.</para>
138    /// </param>
139    /// <returns>
140    /// <para>.</para>
141    /// <para>.</para>
142    /// </returns>
143    [MethodImpl(MethodImplOptions.AggressiveInlining)]
144    public static bool operator ==(Doublet<T> left, Doublet<T> right) => left.Equals(right);
145
146    /// <summury>
147    /// <para>.</para>
148    /// <para>.</para>
149    /// </summury>
150    /// <param name="left">
151    /// <para>.</para>
152    /// <para>.</para>
153    /// </param>
154    /// <param name="right">
155    /// <para>.</para>

```

```

154     /// <para>.</para>
155     /// </param>
156     /// <returns>
157     /// <para>.</para>
158     /// <para>.</para>
159     /// </returns>
160     [MethodImpl(MethodImplOptions.AggressiveInlining)]
161     public static bool operator !=(Doublet<T> left, Doublet<T> right) => !(left == right);
162 }
163 }

```

1.19 ./csharp/Platform.Data.Doublets/DoubletComparer.cs

```

1 using System.Collections.Generic;
2 using System.Runtime.CompilerServices;
3
4 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6 namespace Platform.Data.Doublets
7 {
8     /// <remarks>
9     /// TODO: Может стоит попробовать ref во всех методах (IRefEqualityComparer)
10    /// 2x faster with comparer
11    /// </remarks>
12    public class DoubletComparer<T> : IEqualityComparer<Doublet<T>>
13    {
14        /// <summary>
15        /// <para>
16        /// The .
17        /// </para>
18        /// <para></para>
19        /// </summary>
20        public static readonly DoubletComparer<T> Default = new DoubletComparer<T>();
21
22        /// <summary>
23        /// <para>
24        /// Determines whether this instance equals.
25        /// </para>
26        /// <para></para>
27        /// </summary>
28        /// <param name="x">
29        /// <para>The .</para>
30        /// <para></para>
31        /// </param>
32        /// <param name="y">
33        /// <para>The .</para>
34        /// <para></para>
35        /// </param>
36        /// <returns>
37        /// <para>The bool</para>
38        /// <para></para>
39        /// </returns>
40        [MethodImpl(MethodImplOptions.AggressiveInlining)]
41        public bool Equals(Doublet<T> x, Doublet<T> y) => x.Equals(y);
42
43        /// <summary>
44        /// <para>
45        /// Gets the hash code using the specified obj.
46        /// </para>
47        /// <para></para>
48        /// </summary>
49        /// <param name="obj">
50        /// <para>The obj.</para>
51        /// <para></para>
52        /// </param>
53        /// <returns>
54        /// <para>The int</para>
55        /// <para></para>
56        /// </returns>
57        [MethodImpl(MethodImplOptions.AggressiveInlining)]
58        public int GetHashCode(Doublet<T> obj) => obj.GetHashCode();
59    }
60 }

```

1.20 ./csharp/Platform.Data.Doublets/FFI/UInt32UnitedMemoryLinks.cs

```

1 using System;
2 using System.Collections.Generic;
3 using System.Linq;
4 using System.Runtime.InteropServices;

```

```

5 using Platform.Converters;
6 using Platform.Delegates;
7 using Platform.Disposables;
8
9 namespace Platform.Data.Doublets.FFI
10 {
11     using TLinkAddress = System.UInt32;
12
13     public class UInt32UnitedMemoryLinks : DisposableBase, ILinks<TLinkAddress>
14     {
15         public LinksConstants<TLinkAddress> Constants { get; }
16
17         private readonly unsafe void* _ptr;
18
19         public UInt32UnitedMemoryLinks(string path)
20         {
21             unsafe
22             {
23                 _ptr = Methods.UInt32UnitedMemoryLinks_New(path);
24
25                 // TODO: Update api
26                 Constants = new LinksConstants<TLinkAddress>(enableExternalReferencesSupport:
27                     ↪ true);
28             }
29
30             public TLinkAddress Count(IList<TLinkAddress>? restriction)
31             {
32                 unsafe
33                 {
34                     var array = stackalloc uint[restriction.Count];
35                     for (var i = 0; i < restriction.Count; i++)
36                     {
37                         array[i] = restriction[i];
38                     }
39                     return Methods.UInt32UnitedMemoryLinks_Count(_ptr, array,
40                         ↪ (nuint)(restriction?.Count ?? 0));
41                 }
42
43                 public TLinkAddress Each(IList<TLinkAddress>? restriction, ReadHandler<TLinkAddress>?
44                     ↪ handler)
45                 {
46                     unsafe
47                     {
48                         Methods.EachCallback_UInt32 callback = (link) => handler?.Invoke(new
49                             ↪ Link<TLinkAddress>(link.Index, link.Source, link.Target)) ??
50                             ↪ Constants.Continue;
51                         var array = stackalloc uint[restriction.Count];
52                         for (var i = 0; i < restriction.Count; i++)
53                         {
54                             array[i] = restriction[i];
55                         }
56                         return Methods.UInt32UnitedMemoryLinks_Each(_ptr, array,
57                             ↪ (nuint)(restriction?.Count ?? 0), callback);
58                     }
59                 }
60
61                 public TLinkAddress Create(IList<TLinkAddress>? substitution,
62                     ↪ WriteHandler<TLinkAddress>? handler)
63                 {
64                     unsafe
65                     {
66                         Methods.CreateCallback_UInt32 callback = (before, after) => handler?.Invoke(new
67                             ↪ Link<TLinkAddress>(before.Index, before.Source, before.Target), new
68                             ↪ Link<TLinkAddress>(after.Index, after.Source, after.Target)) ??
69                             ↪ Constants.Continue;
70                         fixed (uint* substitutionPtr = (uint[])substitution)
71                         {
72                             return Methods.UInt32UnitedMemoryLinks_Create(_ptr, substitutionPtr,
73                                 ↪ (nuint)(substitution?.Count ?? 0), callback);
74                         }
75                     }
76                 }
77
78                 public TLinkAddress Update(IList<TLinkAddress>? restriction, IList<TLinkAddress>?
79                     ↪ substitution, WriteHandler<TLinkAddress>? handler)
80                 {
81                     unsafe

```

```

72     {
73         var restrictionArray = stackalloc uint[restriction.Count];
74         for (var i = 0; i < restriction.Count; i++)
75         {
76             restrictionArray[i] = restriction[i];
77         }
78         var substitutionArray = stackalloc uint[substitution.Count];
79         for (var i = 0; i < restriction.Count; i++)
80         {
81             substitutionArray[i] = restriction[i];
82         }
83         Methods.UpdateCallback_UInt32 callback = (before, after) => handler?.Invoke(new
            ↪ Link<TLinkAddress>(before.Index, before.Source, before.Target), new
            ↪ Link<TLinkAddress>(after.Index, after.Source, after.Target)) ??
            ↪ Constants.Continue;
84         return Methods.UInt32UnitedMemoryLinks_Update(_ptr, restrictionArray,
            ↪ (nuint)(restriction?.Count ?? 0), substitutionArray,
            ↪ (nuint)(substitution?.Count ?? 0), callback);
85     }
86 }
87
88 public TLinkAddress Delete(ICollection<TLinkAddress>? restriction, WriteHandler<TLinkAddress>?
    ↪ handler)
89 {
90     unsafe
91     {
92         var restrictionArray = stackalloc uint[restriction.Count];
93         for (var i = 0; i < restriction.Count; i++)
94         {
95             restrictionArray[i] = restriction[i];
96         }
97         Methods.DeleteCallback_UInt32 callback = (before, after) => handler?.Invoke(new
            ↪ Link<TLinkAddress>(before.Index, before.Source, before.Target), new
            ↪ Link<TLinkAddress>(after.Index, after.Source, after.Target)) ??
            ↪ Constants.Continue;
98         return Methods.UInt32UnitedMemoryLinks_Delete(_ptr, restrictionArray,
            ↪ (nuint)(restriction?.Count ?? 0), callback);
99     }
100 }
101
102 protected override void Dispose(bool manual, bool wasDisposed)
103 {
104     unsafe
105     {
106         if (wasDisposed || _ptr == null)
107         {
108             return;
109         }
110         Methods.UInt32UnitedMemoryLinks_Drop(_ptr);
111     }
112 }
113 }
114 }

```

1.21 ./csharp/Platform.Data.Doublets/FFI/UnitedMemoryLinks.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Linq;
4  using System.Runtime.InteropServices;
5  using Platform.Converters;
6  using Platform.Delegates;
7  using Platform.Disposables;
8
9  namespace Platform.Data.Doublets.FFI
10 {
11     struct FfiLink_UInt8
12     {
13         public Byte Index;
14         public Byte Source;
15         public Byte Target;
16     }
17
18     struct FfiLink_UInt16
19     {
20         public UInt16 Index;
21         public UInt16 Source;
22         public UInt16 Target;
23     }
24 }

```

```

25 struct FfiLink_UInt32
26 {
27     public UInt32 Index;
28     public UInt32 Source;
29     public UInt32 Target;
30 }
31
32 struct FfiLink_UInt64
33 {
34     public UInt64 Index;
35     public UInt64 Source;
36     public UInt64 Target;
37 }
38
39 unsafe static class Methods
40 {
41     private const string DllName = "Platform.Doublets";
42
43     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
44     public delegate Byte EachCallback_UInt8(FfiLink_UInt8 link);
45
46     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
47     public delegate UInt16 EachCallback_UInt16(FfiLink_UInt16 link);
48
49     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
50     public delegate UInt32 EachCallback_UInt32(FfiLink_UInt32 link);
51
52     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
53     public delegate UInt64 EachCallback_UInt64(FfiLink_UInt64 link);
54
55     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
56     public delegate Byte CreateCallback_UInt8(FfiLink_UInt8 before, FfiLink_UInt8 after);
57
58     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
59     public delegate UInt16 CreateCallback_UInt16(FfiLink_UInt16 before, FfiLink_UInt16
60         ↪ after);
61
62     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
63     public delegate UInt32 CreateCallback_UInt32(FfiLink_UInt32 before, FfiLink_UInt32
64         ↪ after);
65
66     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
67     public delegate UInt64 CreateCallback_UInt64(FfiLink_UInt64 before, FfiLink_UInt64
68         ↪ after);
69
70     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
71     public delegate Byte UpdateCallback_UInt8(FfiLink_UInt8 before, FfiLink_UInt8 after);
72
73     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
74     public delegate UInt16 UpdateCallback_UInt16(FfiLink_UInt16 before, FfiLink_UInt16
75         ↪ after);
76
77     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
78     public delegate UInt32 UpdateCallback_UInt32(FfiLink_UInt32 before, FfiLink_UInt32
79         ↪ after);
80
81     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
82     public delegate UInt64 UpdateCallback_UInt64(FfiLink_UInt64 before, FfiLink_UInt64
83         ↪ after);
84
85     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
86     public delegate Byte DeleteCallback_UInt8(FfiLink_UInt8 before, FfiLink_UInt8 after);
87
88     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
89     public delegate UInt16 DeleteCallback_UInt16(FfiLink_UInt16 before, FfiLink_UInt16
90         ↪ after);
91
92     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
93     public delegate UInt32 DeleteCallback_UInt32(FfiLink_UInt32 before, FfiLink_UInt32
94         ↪ after);
95
96     [UnmanagedFunctionPointer(CallingConvention.Cdecl)]
97     public delegate UInt64 DeleteCallback_UInt64(FfiLink_UInt64 before, FfiLink_UInt64
98         ↪ after);
99
100     [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
101     public static extern void* ByteUnitedMemoryLinks_New(string path);
102
103     [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]

```

```

95 public static extern void* UInt16UnitedMemoryLinks_New(string path);
96
97 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
98 public static extern void* UInt32UnitedMemoryLinks_New(string path);
99
100 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
101 public static extern void* UInt64UnitedMemoryLinks_New(string path);
102
103 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
104 public static extern void ByteUnitedMemoryLinks_Drop(void* self);
105
106 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
107 public static extern void UInt16UnitedMemoryLinks_Drop(void* self);
108
109 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
110 public static extern void UInt32UnitedMemoryLinks_Drop(void* self);
111
112 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
113 public static extern void UInt64UnitedMemoryLinks_Drop(void* self);
114
115 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
116 public static extern byte ByteUnitedMemoryLinks_Create(void* self, byte* substitution,
117     ↳ nuint substitutionLength, CreateCallback_UInt8 callback);
118
119 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
120 public static extern ushort UInt16UnitedMemoryLinks_Create(void* self, ushort*
121     ↳ substitution, nuint substitutionLength, CreateCallback_UInt16 callback);
122
123 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
124 public static extern uint UInt32UnitedMemoryLinks_Create(void* self, uint* substitution,
125     ↳ nuint substitutionLength, CreateCallback_UInt32 callback);
126
127 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
128 public static extern ulong UInt64UnitedMemoryLinks_Create(void* self, ulong*
129     ↳ substitution, nuint substitutionLength, CreateCallback_UInt64 callback);
130
131 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
132 public static extern byte ByteUnitedMemoryLinks_Count(void* self, byte* restriction,
133     ↳ nuint len);
134
135 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
136 public static extern ushort UInt16UnitedMemoryLinks_Count(void* self, ushort*
137     ↳ restriction, nuint len);
138
139 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
140 public static extern uint UInt32UnitedMemoryLinks_Count(void* self, uint* restriction,
141     ↳ nuint len);
142
143 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
144 public static extern ulong UInt64UnitedMemoryLinks_Count(void* self, ulong* restriction,
145     ↳ nuint len);
146
147 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
148 public static extern byte ByteUnitedMemoryLinks_Each(void* self, byte* restriction,
149     ↳ nuint len, EachCallback_UInt8 callback);
150
151 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
152 public static extern ushort UInt16UnitedMemoryLinks_Each(void* self, ushort*
153     ↳ restriction, nuint len, EachCallback_UInt16 callback);
154
155 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
156 public static extern uint UInt32UnitedMemoryLinks_Each(void* self, uint* restriction,
157     ↳ nuint len, EachCallback_UInt32 callback);
158
159 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
160 public static extern ulong UInt64UnitedMemoryLinks_Each(void* self, ulong* restriction,
161     ↳ nuint len, EachCallback_UInt64 callback);
162
163 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
164 public static extern byte ByteUnitedMemoryLinks_Update(void* self, byte* restriction,
165     ↳ nuint restrictionLength, byte* substitution, nuint substitutionLength,
166     ↳ UpdateCallback_UInt8 callback);
167
168 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
169 public static extern ushort UInt16UnitedMemoryLinks_Update(void* self, ushort*
170     ↳ restriction, nuint restrictionLength, ushort* substitution, nuint
171     ↳ substitutionLength, UpdateCallback_UInt16 callback);

```



```

157 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
158 public static extern uint UInt32UnitedMemoryLinks_Update(void* self, uint* restriction,
    ↳ nuint restrictionLength, uint* substitution, nuint substitutionLength,
    ↳ UpdateCallback_UInt32 callback);

159
160 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
161 public static extern ulong UInt64UnitedMemoryLinks_Update(void* self, ulong*
    ↳ restriction, nuint restrictionLength, ulong* substitution, nuint
    ↳ substitutionLength, UpdateCallback_UInt64 callback);

162
163 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
164 public static extern byte ByteUnitedMemoryLinks_Delete(void* self, byte* restriction,
    ↳ nuint restrictionLength, DeleteCallback_UInt8 callback);

165
166 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
167 public static extern ushort UInt16UnitedMemoryLinks_Delete(void* self, ushort*
    ↳ restriction, nuint len, DeleteCallback_UInt16 callback);

168
169 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
170 public static extern uint UInt32UnitedMemoryLinks_Delete(void* self, uint* restriction,
    ↳ nuint len, DeleteCallback_UInt32 callback);

171
172 [DllImport(DllName, CallingConvention = CallingConvention.Cdecl)]
173 public static extern ulong UInt64UnitedMemoryLinks_Delete(void* self, ulong*
    ↳ restriction, nuint len, DeleteCallback_UInt64 callback);

174 }

175
176 public class UnitedMemoryLinks<TLinkAddress> : DisposableBase, ILinks<TLinkAddress> where
    ↳ TLinkAddress : struct
177 {
178     private static readonly UncheckedConverter<byte, TLinkAddress> from_u8 =
    ↳ UncheckedConverter<byte, TLinkAddress>.Default;
179     private static readonly UncheckedConverter<ushort, TLinkAddress> from_u16 =
    ↳ UncheckedConverter<ushort, TLinkAddress>.Default;
180     private static readonly UncheckedConverter<uint, TLinkAddress> from_u32 =
    ↳ UncheckedConverter<uint, TLinkAddress>.Default;
181     private static readonly UncheckedConverter<ulong, TLinkAddress> from_u64 =
    ↳ UncheckedConverter<ulong, TLinkAddress>.Default;
182     private static readonly UncheckedConverter<TLinkAddress, ulong> from_t =
    ↳ UncheckedConverter<TLinkAddress, ulong>.Default;

183
184     public LinksConstants<TLinkAddress> Constants { get; }
185
186     private readonly unsafe void* _ptr;
187
188     public UnitedMemoryLinks(string path)
189     {
190         TLinkAddress t = default;
191         unsafe
192         {
193             _ptr = t switch
194             {
195                 byte => Methods.ByteUnitedMemoryLinks_New(path),
196                 ushort => Methods.UInt16UnitedMemoryLinks_New(path),
197                 uint => Methods.UInt32UnitedMemoryLinks_New(path),
198                 ulong => Methods.UInt64UnitedMemoryLinks_New(path),
199                 _ => throw new NotImplementedException()
200             };
201
202             // TODO: Update api
203             Constants = new LinksConstants<TLinkAddress>(enableExternalReferencesSupport:
    ↳ true);
204         }
205     }

206
207     public TLinkAddress Count(ICollection<TLinkAddress>? restriction)
208     {
209         var restrictionLength = restriction?.Count ?? 0;
210         unsafe
211         {
212             TLinkAddress t = default;
213             switch (t)
214             {
215                 case byte:
216                 {
217                     var restrictionArray = stackalloc byte[restrictionLength];
218                     var byteRestrictionArray = (ICollection<byte>)restriction;
219                     for (var i = 0; i < restrictionLength; i++)
220                     {

```

```

221         restrictionArray[i] = byteRestrictionArray[i];
222     }
223     return from_u8.Convert(Methods.ByteUnitedMemoryLinks_Count(_ptr,
224         ↪ restrictionArray, (nuint)restrictionLength));
225 }
226 case ushort:
227 {
228     var restrictionArray = stackalloc ushort[restrictionLength];
229     var ushortRestrictionArray = (IList<ushort>)restriction;
230     for (var i = 0; i < restrictionLength; i++)
231     {
232         restrictionArray[i] = ushortRestrictionArray[i];
233     }
234     return from_u16.Convert(Methods.UInt16UnitedMemoryLinks_Count(_ptr,
235         ↪ restrictionArray, (nuint)restrictionLength));
236 }
237 case uint:
238 {
239     var restrictionArray = stackalloc uint[restrictionLength];
240     var uintRestrictionArray = (IList<uint>)restriction;
241     for (var i = 0; i < restrictionLength; i++)
242     {
243         restrictionArray[i] = uintRestrictionArray[i];
244     }
245     return from_u32.Convert(Methods.UInt32UnitedMemoryLinks_Count(_ptr,
246         ↪ restrictionArray, (nuint)restrictionLength));
247 }
248 case ulong:
249 {
250     {
251         var restrictionArray = stackalloc ulong[restrictionLength];
252         var ulongRestrictionArray = (IList<ulong>)restriction;
253         for (var i = 0; i < restrictionLength; i++)
254         {
255             restrictionArray[i] = ulongRestrictionArray[i];
256         }
257         return from_u64.Convert(Methods.UInt64UnitedMemoryLinks_Count(_ptr,
258             ↪ restrictionArray, (nuint)restrictionLength));
259     }
260 }
261 default:
262 {
263     throw new NotImplementedException();
264 }
265 }
266 }
267
268 public TLinkAddress Each(IList<TLinkAddress>? restriction, ReadHandler<TLinkAddress>?
269     ↪ handler)
270 {
271     var restrictionLength = restriction?.Count ?? 0;
272     unsafe
273     {
274         TLinkAddress t = default;
275         switch (t)
276         {
277             case byte:
278             {
279                 byte Callback(FfiLink_UInt8 link) =>
280                 (byte)from_t.Convert(handler?.Invoke(new
281                     ↪ Link<TLinkAddress>(from_u8.Convert(link.Index),
282                     ↪ from_u8.Convert(link.Source), from_u8.Convert(link.Target))) ??
283                     ↪ Constants.Continue);
284                 var restrictionArray = stackalloc byte[restrictionLength];
285                 var byteRestrictionArray = (IList<byte>)restriction;
286                 for (var i = 0; i < restrictionLength; i++)
287                 {
288                     restrictionArray[i] = byteRestrictionArray[i];
289                 }
290                 return from_u8.Convert(Methods.ByteUnitedMemoryLinks_Each(_ptr,
291                     ↪ restrictionArray, (nuint)restrictionLength, Callback));
292             }
293             case ushort:
294             {

```

```

286         ushort Callback(FfiLink_UInt16 link) =>
287             ↪ (ushort)from_t.Convert(handler?.Invoke(new
288             ↪ Link<TLinkAddress>(from_u16.Convert(link.Index),
289             ↪ from_u16.Convert(link.Source), from_u16.Convert(link.Target))) ??
290             ↪ Constants.Continue);
291     var restrictionArray = stackalloc ushort[restrictionLength];
292     var ushortRestrictionArray = (IList<ushort>)restriction;
293     for (var i = 0; i < restrictionLength; i++)
294     {
295         restrictionArray[i] = ushortRestrictionArray[i];
296     }
297     return from_u16.Convert(Methods.UInt16UnitedMemoryLinks_Each(_ptr,
298         ↪ restrictionArray, (nuint)restrictionLength, Callback));
299 }
300 case uint:
301 {
302     uint Callback(FfiLink_UInt32 link) =>
303         ↪ (uint)from_t.Convert(handler?.Invoke(new
304         ↪ Link<TLinkAddress>(from_u32.Convert(link.Index),
305         ↪ from_u32.Convert(link.Source), from_u32.Convert(link.Target))) ??
306         ↪ Constants.Continue);
307     var restrictionArray = stackalloc uint[restrictionLength];
308     var uintRestrictionArray = (IList<uint>)restriction;
309     for (var i = 0; i < restrictionLength; i++)
310     {
311         restrictionArray[i] = uintRestrictionArray[i];
312     }
313     return from_u32.Convert(Methods.UInt32UnitedMemoryLinks_Each(_ptr,
314         ↪ restrictionArray, (nuint)restrictionLength, Callback));
315 }
316 case ulong:
317 {
318     {
319         ulong Callback(FfiLink_UInt64 link) =>
320             ↪ from_t.Convert(handler?.Invoke(new
321             ↪ Link<TLinkAddress>(from_u64.Convert(link.Index),
322             ↪ from_u64.Convert(link.Source), from_u64.Convert(link.Target)))
323             ↪ ?? Constants.Continue);
324         var restrictionArray = stackalloc UInt64[restrictionLength];
325         var ulongRestrictionArray = (IList<ulong>)restriction;
326         for (var i = 0; i < restrictionLength; i++)
327         {
328             restrictionArray[i] = ulongRestrictionArray[i];
329         }
330         return from_u64.Convert(Methods.UInt64UnitedMemoryLinks_Each(_ptr,
331             ↪ restrictionArray, (nuint)restrictionLength, Callback));
332     }
333 }
334 default:
335 {
336     throw new NotImplementedException();
337 }
338 }
339 }
340 }
341
342 public TLinkAddress Create(IList<TLinkAddress>? substitution,
343     ↪ WriteHandler<TLinkAddress>? handler)
344 {
345     var substitutionLength = substitution?.Count ?? 0;
346     unsafe
347     {
348         TLinkAddress t = default;
349         switch (t)
350         {
351             case byte:
352             {
353                 byte Callback(FfiLink_UInt8 before, FfiLink_UInt8 after) =>
354                     ↪ (byte)from_t.Convert(handler?.Invoke(new
355                     ↪ Link<TLinkAddress>(from_u8.Convert(before.Index),
356                     ↪ from_u8.Convert(before.Source), from_u8.Convert(before.Target)), new
357                     ↪ Link<TLinkAddress>(from_u8.Convert(after.Index),
358                     ↪ from_u8.Convert(after.Source), from_u8.Convert(after.Target))) ??
359                     ↪ Constants.Continue);
360                 var substitutionArray = stackalloc byte[substitutionLength];
361                 var byteSubstitutionArray = (IList<byte>)substitution;
362                 for (var i = 0; i < substitutionLength; i++)
363                 {

```

```

342         substitutionArray[i] = byteSubstitutionArray[i];
343     }
344     return from_u8.Convert(Methods.ByteUnitedMemoryLinks_Create(_ptr,
345         ↳ substitutionArray, (nuint)(substitution?.Count ?? 0), Callback));
346 }
347 case ushort:
348 {
349     ushort Callback(FfiLink_UInt16 before, FfiLink_UInt16 after) =>
350     ↳ (ushort)from_t.Convert(handler?.Invoke(new
351     ↳ Link<TLinkAddress>(from_u16.Convert(before.Index),
352     ↳ from_u16.Convert(before.Source), from_u16.Convert(before.Target)),
353     ↳ new Link<TLinkAddress>(from_u16.Convert(after.Index),
354     ↳ from_u16.Convert(after.Source), from_u16.Convert(after.Target))) ??
355     ↳ Constants.Continue);
356     var substitutionArray = stackalloc ushort[substitutionLength];
357     var ushortSubstitutionArray = (IList<ushort>)substitution;
358     for (var i = 0; i < substitutionLength; i++)
359     {
360         substitutionArray[i] = ushortSubstitutionArray[i];
361     }
362     return from_u16.Convert(Methods.UInt16UnitedMemoryLinks_Create(_ptr,
363         ↳ substitutionArray, (nuint)(substitution?.Count ?? 0), Callback));
364 }
365 case uint:
366 {
367     uint Callback(FfiLink_UInt32 before, FfiLink_UInt32 after) =>
368     ↳ (uint)from_t.Convert(handler?.Invoke(new
369     ↳ Link<TLinkAddress>(from_u32.Convert(before.Index),
370     ↳ from_u32.Convert(before.Source), from_u32.Convert(before.Target)),
371     ↳ new Link<TLinkAddress>(from_u32.Convert(after.Index),
372     ↳ from_u32.Convert(after.Source), from_u32.Convert(after.Target))) ??
373     ↳ Constants.Continue);
374     var substitutionArray = stackalloc uint[substitutionLength];
375     var uintSubstitutionArray = (IList<uint>)substitution;
376     for (var i = 0; i < substitutionLength; i++)
377     {
378         substitutionArray[i] = uintSubstitutionArray[i];
379     }
380     return from_u32.Convert(Methods.UInt32UnitedMemoryLinks_Create(_ptr,
381         ↳ substitutionArray, (nuint)(substitution?.Count ?? 0), Callback));
382 }
383 case ulong:
384 {
385     ulong Callback(FfiLink_UInt64 before, FfiLink_UInt64 after) =>
386     ↳ (ulong)from_t.Convert(handler?.Invoke(new
387     ↳ Link<TLinkAddress>(from_u64.Convert(before.Index),
388     ↳ from_u64.Convert(before.Source), from_u64.Convert(before.Target)),
389     ↳ new Link<TLinkAddress>(from_u64.Convert(after.Index),
390     ↳ from_u64.Convert(after.Source), from_u64.Convert(after.Target))) ??
391     ↳ Constants.Continue);
392     var substitutionArray = stackalloc ulong[substitutionLength];
393     var ulongSubstitutionArray = (IList<ulong>)substitution;
394     for (var i = 0; i < substitutionLength; i++)
395     {
396         substitutionArray[i] = ulongSubstitutionArray[i];
397     }
398     return from_u64.Convert(Methods.UInt64UnitedMemoryLinks_Create(_ptr,
399         ↳ substitutionArray, (nuint)(substitution?.Count ?? 0), Callback));
400 }
401 default:
402 {
403     throw new NotImplementedException();
404 }
405 };
406 }
407 }
408
409 public TLinkAddress Update(IList<TLinkAddress>? restriction, IList<TLinkAddress>?
410     ↳ substitution, WriteHandler<TLinkAddress>? handler)
411 {
412     var restrictionLength = restriction?.Count ?? 0;
413     var substitutionLength = substitution?.Count ?? 0;
414     unsafe
415     {
416         TLinkAddress t = default;
417         switch (t)

```

```

397 {
398     case byte:
399     {
400         var restrictionArray = stackalloc byte[restrictionLength];
401         var byteRestrictionArray = (IList<byte>)restriction;
402         for (var i = 0; i < restrictionLength; i++)
403         {
404             restrictionArray[i] = byteRestrictionArray[i];
405         }
406         var substitutionArray = stackalloc byte[substitutionLength];
407         var byteSubstitutionArray = (IList<byte>)substitution;
408         for (var i = 0; i < substitutionLength; i++)
409         {
410             substitutionArray[i] = byteSubstitutionArray[i];
411         }
412         byte Callback(FfiLink_UInt8 before, FfiLink_UInt8 after) =>
413         {
414             (byte)from_t.Convert(handler?.Invoke(new
415                 ↳ Link<TLinkAddress>(from_u8.Convert(before.Index),
416                 ↳ from_u8.Convert(before.Source), from_u8.Convert(before.Target)), new
417                 ↳ Link<TLinkAddress>(from_u8.Convert(after.Index),
418                 ↳ from_u8.Convert(after.Source), from_u8.Convert(after.Target))) ??
419                 ↳ Constants.Continue);
420             return from_u8.Convert(Methods.ByteUnitedMemoryLinks_Update(_ptr,
421                 ↳ restrictionArray, (nuint)restrictionLength, substitutionArray,
422                 ↳ (nuint)(substitution?.Count ?? 0), Callback));
423         }
424     }
425     case ushort:
426     {
427         var restrictionArray = stackalloc ushort[restrictionLength];
428         var ushortRestrictionArray = (IList<ushort>)restriction;
429         for (var i = 0; i < restrictionLength; i++)
430         {
431             restrictionArray[i] = ushortRestrictionArray[i];
432         }
433         var substitutionArray = stackalloc ushort[substitutionLength];
434         var ushortSubstitutionArray = (IList<ushort>)substitution;
435         for (var i = 0; i < substitutionLength; i++)
436         {
437             substitutionArray[i] = ushortSubstitutionArray[i];
438         }
439         ushort Callback(FfiLink_UInt16 before, FfiLink_UInt16 after) =>
440         {
441             (ushort)from_t.Convert(handler?.Invoke(new
442                 ↳ Link<TLinkAddress>(from_u16.Convert(before.Index),
443                 ↳ from_u16.Convert(before.Source), from_u16.Convert(before.Target)),
444                 ↳ new Link<TLinkAddress>(from_u16.Convert(after.Index),
445                 ↳ from_u16.Convert(after.Source), from_u16.Convert(after.Target))) ??
446                 ↳ Constants.Continue);
447             return from_u16.Convert(Methods.UInt16UnitedMemoryLinks_Update(_ptr,
448                 ↳ restrictionArray, (nuint)restrictionLength, substitutionArray,
449                 ↳ (nuint)(substitution?.Count ?? 0), Callback));
450         }
451     }
452     case uint:
453     {
454         var restrictionArray = stackalloc uint[restrictionLength];
455         var uintRestrictionArray = (IList<uint>)restriction;
456         for (var i = 0; i < restrictionLength; i++)
457         {
458             restrictionArray[i] = uintRestrictionArray[i];
459         }
460         var substitutionArray = stackalloc uint[substitutionLength];
461         var uintSubstitutionArray = (IList<uint>)substitution;
462         for (var i = 0; i < substitutionLength; i++)
463         {
464             substitutionArray[i] = uintSubstitutionArray[i];
465         }
466         uint Callback(FfiLink_UInt32 before, FfiLink_UInt32 after) =>
467         {
468             (uint)from_t.Convert(handler?.Invoke(new
469                 ↳ Link<TLinkAddress>(from_u32.Convert(before.Index),
470                 ↳ from_u32.Convert(before.Source), from_u32.Convert(before.Target)),
471                 ↳ new Link<TLinkAddress>(from_u32.Convert(after.Index),
472                 ↳ from_u32.Convert(after.Source), from_u32.Convert(after.Target))) ??
473                 ↳ Constants.Continue);
474             return from_u32.Convert(Methods.UInt32UnitedMemoryLinks_Update(_ptr,
475                 ↳ restrictionArray, (nuint)restrictionLength, substitutionArray,
476                 ↳ (nuint)(substitution?.Count ?? 0), Callback));
477         }
478     }
479     case ulong:

```

```

450     {
451         var restrictionArray = stackalloc ulong[restrictionLength];
452         var ulongRestrictionArray = (IList<ulong>)restriction;
453         for (var i = 0; i < restrictionLength; i++)
454         {
455             restrictionArray[i] = ulongRestrictionArray[i];
456         }
457         var substitutionArray = stackalloc ulong[substitutionLength];
458         var ulongSubstitutionArray = (IList<ulong>)substitution;
459         for (var i = 0; i < substitutionLength; i++)
460         {
461             substitutionArray[i] = ulongSubstitutionArray[i];
462         }
463         ulong Callback(FfiLink_UInt64 before, FfiLink_UInt64 after) =>
464         {
465             (ulong)from_t.Convert(handler?.Invoke(new
466                 ↪ Link<TLinkAddress>(from_u64.Convert(before.Index),
467                 ↪ from_u64.Convert(before.Source), from_u64.Convert(before.Target)),
468                 ↪ new Link<TLinkAddress>(from_u64.Convert(after.Index),
469                 ↪ from_u64.Convert(after.Source), from_u64.Convert(after.Target))) ??
470                 ↪ Constants.Continue);
471             return from_u64.Convert(Methods.UInt64UnitedMemoryLinks_Update(_ptr,
472                 ↪ restrictionArray, (nuint)restrictionLength, substitutionArray,
473                 ↪ (nuint)(substitution?.Count ?? 0), Callback));
474         }
475     }
476     default:
477     {
478         throw new NotImplementedException();
479     }
480 }
481 }
482 }
483
484 public TLinkAddress Delete(IList<TLinkAddress>? restriction, WriteHandler<TLinkAddress>?
485     ↪ handler)
486 {
487     var restrictionLength = restriction?.Count ?? 0;
488     unsafe
489     {
490         TLinkAddress t = default;
491         switch (t)
492         {
493             case byte:
494             {
495                 var restrictionArray = stackalloc byte[restrictionLength];
496                 var byteRestrictionArray = (IList<byte>)restriction;
497                 for (var i = 0; i < restrictionLength; i++)
498                 {
499                     restrictionArray[i] = byteRestrictionArray[i];
500                 }
501                 byte Callback(FfiLink_UInt8 before, FfiLink_UInt8 after) =>
502                 {
503                     (byte)from_t.Convert(handler?.Invoke(new
504                         ↪ Link<TLinkAddress>(from_u8.Convert(before.Index),
505                         ↪ from_u8.Convert(before.Source), from_u8.Convert(before.Target)), new
506                         ↪ Link<TLinkAddress>(from_u8.Convert(after.Index),
507                         ↪ from_u8.Convert(after.Source), from_u8.Convert(after.Target))) ??
508                         ↪ Constants.Continue);
509                     return (TLinkAddress)(object)Methods.ByteUnitedMemoryLinks_Delete(_ptr,
510                         ↪ restrictionArray, (nuint)restrictionLength, Callback);
511                 }
512             case ushort:
513             {
514                 var restrictionArray = stackalloc ushort[restrictionLength];
515                 var ushortRestrictionArray = (IList<ushort>)restriction;
516                 for (var i = 0; i < restrictionLength; i++)
517                 {
518                     restrictionArray[i] = ushortRestrictionArray[i];
519                 }
520                 ushort Callback(FfiLink_UInt16 before, FfiLink_UInt16 after) =>
521                 {
522                     (ushort)from_t.Convert(handler?.Invoke(new
523                         ↪ Link<TLinkAddress>(from_u16.Convert(before.Index),
524                         ↪ from_u16.Convert(before.Source), from_u16.Convert(before.Target)),
525                         ↪ new Link<TLinkAddress>(from_u16.Convert(after.Index),
526                         ↪ from_u16.Convert(after.Source), from_u16.Convert(after.Target))) ??
527                         ↪ Constants.Continue);
528                     return
529                         ↪ (TLinkAddress)(object)Methods.UInt16UnitedMemoryLinks_Delete(_ptr,
530                         ↪ restrictionArray, (nuint)restrictionLength, Callback);
531                 }
532             }
533         }
534     }

```

```

504     case uint:
505     {
506         var restrictionArray = stackalloc uint[restrictionLength];
507         var uintRestrictionArray = (IList<uint>)restriction;
508         for (var i = 0; i < restrictionLength; i++)
509         {
510             restrictionArray[i] = uintRestrictionArray[i];
511         }
512         uint Callback(FfiLink_UInt32 before, FfiLink_UInt32 after) =>
513             (uint)from_t.Convert(handler?.Invoke(new
514                 ↳ Link<TLinkAddress>(from_u32.Convert(before.Index),
515                 ↳ from_u32.Convert(before.Source), from_u32.Convert(before.Target)),
516                 ↳ new Link<TLinkAddress>(from_u32.Convert(after.Index),
517                 ↳ from_u32.Convert(after.Source), from_u32.Convert(after.Target))) ??
518                 ↳ Constants.Continue);
519         return
520             ↳ (TLinkAddress)(object)Methods.UInt32UnitedMemoryLinks_Delete(_ptr,
521             ↳ restrictionArray, (nuint)restrictionLength, Callback);
522     }
523     case ulong:
524     {
525         var restrictionArray = stackalloc ulong[restrictionLength];
526         var ulongRestrictionArray = (IList<ulong>)restriction;
527         for (var i = 0; i < restrictionLength; i++)
528         {
529             restrictionArray[i] = ulongRestrictionArray[i];
530         }
531         ulong Callback(FfiLink_UInt64 before, FfiLink_UInt64 after) =>
532             (ulong)from_t.Convert(handler?.Invoke(new
533                 ↳ Link<TLinkAddress>(from_u64.Convert(before.Index),
534                 ↳ from_u64.Convert(before.Source), from_u64.Convert(before.Target)),
535                 ↳ new Link<TLinkAddress>(from_u64.Convert(after.Index),
536                 ↳ from_u64.Convert(after.Source), from_u64.Convert(after.Target))) ??
537                 ↳ Constants.Continue);
538         return
539             ↳ (TLinkAddress)(object)Methods.UInt64UnitedMemoryLinks_Delete(_ptr,
540             ↳ restrictionArray, (nuint)restrictionLength, Callback);
541     }
542     default:
543     {
544         throw new NotImplementedException();
545     }
546 }
547 }
548 }
549 }
550 }
551 }
552 }
553 }
554 }
555 }
556 }
557 }
558 }
559 }
560 }
561 }
562 }
563 }
protected override void Dispose(bool manual, bool wasDisposed)
{
    unsafe
    {
        if (wasDisposed && _ptr != null)
        {
            return;
        }
        TLinkAddress t = default;
        switch (t)
        {
            case byte:
                Methods.ByteUnitedMemoryLinks_Drop(_ptr);
                break;
            case ushort:
                Methods.UInt16UnitedMemoryLinks_Drop(_ptr);
                break;
            case uint:
                Methods.UInt32UnitedMemoryLinks_Drop(_ptr);
                break;
            case ulong:
                Methods.UInt64UnitedMemoryLinks_Drop(_ptr);
                break;
            default:
                throw new NotImplementedException();
        }
    }
}

```

1.22 ./csharp/Platform.Data.Doublets/ILinks.cs

```
1  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
2
3  using System.Collections.Generic;
4
5  namespace Platform.Data.Doublets
6  {
7      /// <summary>
8      /// <para>
9      /// Defines the links.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="ILinks{TLinkAddress, LinksConstants{TLinkAddress}}"/>
14     public interface ILinks<TLinkAddress> : ILinks<TLinkAddress, LinksConstants<TLinkAddress>>
15     {
16     }
17 }
```

1.23 ./csharp/Platform.Data.Doublets/ILinksExtensions.cs

```
1  using System;
2  using System.Collections;
3  using System.Collections.Generic;
4  using System.Linq;
5  using System.Runtime.CompilerServices;
6  using Platform.Ranges;
7  using Platform.Collections.Lists;
8  using Platform.Random;
9  using Platform.Setters;
10 using Platform.Converters;
11 using Platform.Numbers;
12 using Platform.Data.Exceptions;
13 using Platform.Data.Doublets.Decorators;
14 using Platform.Delegates;
15
16 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
17
18 namespace Platform.Data.Doublets
19 {
20     /// <summary>
21     /// <para>
22     /// Represents the links extensions.
23     /// </para>
24     /// <para></para>
25     /// </summary>
26     public static class ILinksExtensions
27     {
28         /// <summary>
29         /// <para>
30         /// Runs the random creations using the specified links.
31         /// </para>
32         /// <para></para>
33         /// </summary>
34         /// <typeparam name="TLinkAddress">
35         /// <para>The link.</para>
36         /// <para></para>
37         /// </typeparam>
38         /// <param name="links">
39         /// <para>The links.</para>
40         /// <para></para>
41         /// </param>
42         /// <param name="amountOfCreations">
43         /// <para>The amount of creations.</para>
44         /// <para></para>
45         /// </param>
46         [MethodImpl(MethodImplOptions.AggressiveInlining)]
47         public static void RunRandomCreations<TLinkAddress>(this ILinks<TLinkAddress> links,
48             ↪ ulong amountOfCreations) where TLinkAddress : struct
49         {
50             var random = RandomHelpers.Default;
51             var addressToUInt64Converter = UncheckedConverter<TLinkAddress, ulong>.Default;
52             var uint64ToAddressConverter = UncheckedConverter<ulong, TLinkAddress>.Default;
53             for (var i = 0UL; i < amountOfCreations; i++)
54             {
55                 var linksAddressRange = new Range<ulong>(0,
56                     ↪ addressToUInt64Converter.Convert(links.Count()));
57                 var source =
58                     ↪ uint64ToAddressConverter.Convert(random.NextUInt64(linksAddressRange));
59                 var target =
58                     ↪ uint64ToAddressConverter.Convert(random.NextUInt64(linksAddressRange));
59             }
60         }
61     }
62 }
```



```

57         links.GetOrCreate(source, target);
58     }
59 }
60
61 /// <summary>
62 /// <para>
63 /// Runs the random searches using the specified links.
64 /// </para>
65 /// <para></para>
66 /// </summary>
67 /// <typeparam name="TLinkAddress">
68 /// <para>The link.</para>
69 /// <para></para>
70 /// </typeparam>
71 /// <param name="links">
72 /// <para>The links.</para>
73 /// <para></para>
74 /// </param>
75 /// <param name="amountOfSearches">
76 /// <para>The amount of searches.</para>
77 /// <para></para>
78 /// </param>
79 [MethodImpl(MethodImplOptions.AggressiveInlining)]
80 public static void RunRandomSearches<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↪ ulong amountOfSearches) where TLinkAddress : struct
81 {
82     var random = RandomHelpers.Default;
83     var addressToUInt64Converter = UncheckedConverter<TLinkAddress, ulong>.Default;
84     var uInt64ToAddressConverter = UncheckedConverter<ulong, TLinkAddress>.Default;
85     for (var i = 0UL; i < amountOfSearches; i++)
86     {
87         var linksAddressRange = new Range<ulong>(0,
            ↪ addressToUInt64Converter.Convert(links.Count()));
88         var source =
            ↪ uInt64ToAddressConverter.Convert(random.NextUInt64(linksAddressRange));
89         var target =
            ↪ uInt64ToAddressConverter.Convert(random.NextUInt64(linksAddressRange));
90         links.SearchOrDefault(source, target);
91     }
92 }
93
94 /// <summary>
95 /// <para>
96 /// Runs the random deletions using the specified links.
97 /// </para>
98 /// <para></para>
99 /// </summary>
100 /// <typeparam name="TLinkAddress">
101 /// <para>The link.</para>
102 /// <para></para>
103 /// </typeparam>
104 /// <param name="links">
105 /// <para>The links.</para>
106 /// <para></para>
107 /// </param>
108 /// <param name="amountOfDeletions">
109 /// <para>The amount of deletions.</para>
110 /// <para></para>
111 /// </param>
112 [MethodImpl(MethodImplOptions.AggressiveInlining)]
113 public static void RunRandomDeletions<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↪ ulong amountOfDeletions) where TLinkAddress : struct
114 {
115     var random = RandomHelpers.Default;
116     var addressToUInt64Converter = UncheckedConverter<TLinkAddress, ulong>.Default;
117     var uInt64ToAddressConverter = UncheckedConverter<ulong, TLinkAddress>.Default;
118     var linksCount = addressToUInt64Converter.Convert(links.Count());
119     var min = amountOfDeletions > linksCount ? 0UL : linksCount - amountOfDeletions;
120     for (var i = 0UL; i < amountOfDeletions; i++)
121     {
122         linksCount = addressToUInt64Converter.Convert(links.Count());
123         if (linksCount <= min)
124         {
125             break;
126         }
127         var linksAddressRange = new Range<ulong>(min, linksCount);
128         var link =
            ↪ uInt64ToAddressConverter.Convert(random.NextUInt64(linksAddressRange));

```

```

129         links.Delete(link);
130     }
131 }
132
133 /// <summary>
134 /// <para>
135 /// Deletes the links.
136 /// </para>
137 /// <para></para>
138 /// </summary>
139 /// <typeparam name="TLinkAddress">
140 /// <para>The link.</para>
141 /// <para></para>
142 /// </typeparam>
143 /// <param name="links">
144 /// <para>The links.</para>
145 /// <para></para>
146 /// </param>
147 /// <param name="linkToDelete">
148 /// <para>The link to delete.</para>
149 /// <para></para>
150 /// </param>
151 [MethodImpl(MethodImplOptions.AggressiveInlining)]
152 public static TLinkAddress Delete<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↪ TLinkAddress linkToDelete, WriteHandler<TLinkAddress>? handler) where TLinkAddress :
    ↪ struct
153 {
154     if (links.Exists(linkToDelete))
155     {
156         links.EnforceResetValues(linkToDelete, handler);
157     }
158     return links.Delete(new LinkAddress<TLinkAddress>(linkToDelete), handler);
159 }
160
161 /// <remarks>
162 /// TODO: Возможно есть очень простой способ это сделать.
163 /// (Например просто удалить файл, или изменить его размер таким образом,
164 /// чтобы удалился весь контент)
165 /// Например через _header->AllocatedLinks в ResizableDirectMemoryLinks
166 /// </remarks>
167 [MethodImpl(MethodImplOptions.AggressiveInlining)]
168 public static void DeleteAll<TLinkAddress>(this ILinks<TLinkAddress> links) where
    ↪ TLinkAddress : struct
169 {
170     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
171     var comparer = Comparer<TLinkAddress>.Default;
172     for (var i = links.Count(); comparer.Compare(i, default) > 0; i =
    ↪ Arithmetic.Decrement(i))
173     {
174         links.Delete(i);
175         if (!equalityComparer.Equals(links.Count(), Arithmetic.Decrement(i)))
176         {
177             i = links.Count();
178         }
179     }
180 }
181
182 /// <summary>
183 /// <para>
184 /// Firsts the links.
185 /// </para>
186 /// <para></para>
187 /// </summary>
188 /// <typeparam name="TLinkAddress">
189 /// <para>The link.</para>
190 /// <para></para>
191 /// </typeparam>
192 /// <param name="links">
193 /// <para>The links.</para>
194 /// <para></para>
195 /// </param>
196 /// <exception cref="InvalidOperationException">
197 /// <para>В процессе поиска по хранилищу не было найдено связей.</para>
198 /// <para></para>
199 /// </exception>
200 /// <exception cref="InvalidOperationException">
201 /// <para>В хранилище нет связей.</para>
202 /// <para></para>

```

```

203 /// </exception>
204 /// <returns>
205 /// <para>The first link.</para>
206 /// <para></para>
207 /// </returns>
208 [MethodImpl(MethodImplOptions.AggressiveInlining)]
209 public static TLinkAddress First<TLinkAddress>(this ILinks<TLinkAddress> links) where
    ↳ TLinkAddress : struct
210 {
211     TLinkAddress firstLink = default;
212     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
213     if (equalityComparer.Equals(links.Count(), default))
214     {
215         throw new InvalidOperationException("В хранилище нет связей.");
216     }
217     links.Each(links.Constants.Any, links.Constants.Any, link =>
218     {
219         firstLink = link[links.Constants.IndexPart];
220         return links.Constants.Break;
221     });
222     if (equalityComparer.Equals(firstLink, default))
223     {
224         throw new InvalidOperationException("В процессе поиска по хранилищу не было
            ↳ найдено связей.");
225     }
226     return firstLink;
227 }
228
229 /// <summary>
230 /// <para>
231 /// Singles the or default using the specified links.
232 /// </para>
233 /// <para></para>
234 /// </summary>
235 /// <typeparam name="TLinkAddress">
236 /// <para>The link.</para>
237 /// <para></para>
238 /// </typeparam>
239 /// <param name="links">
240 /// <para>The links.</para>
241 /// <para></para>
242 /// </param>
243 /// <param name="query">
244 /// <para>The query.</para>
245 /// <para></para>
246 /// </param>
247 /// <returns>
248 /// <para>The result.</para>
249 /// <para></para>
250 /// </returns>
251 [MethodImpl(MethodImplOptions.AggressiveInlining)]
252 public static IList<TLinkAddress>? SingleOrDefault<TLinkAddress>(this
    ↳ ILinks<TLinkAddress> links, IList<TLinkAddress>? query) where TLinkAddress : struct
253 {
254     IList<TLinkAddress>? result = null;
255     var count = 0;
256     var constants = links.Constants;
257     var @continue = constants.Continue;
258     var @break = constants.Break;
259     links.Each(query, linkHandler);
260     return result;
261
262     TLinkAddress linkHandler(IList<TLinkAddress>? link)
263     {
264         if (count == 0)
265         {
266             result = link;
267             count++;
268             return @continue;
269         }
270         else
271         {
272             result = null;
273             return @break;
274         }
275     }
276 }
277
278 #region Paths

```

```

279 /// <remarks>
280 /// TODO: Как так? Как то что ниже может быть корректно?
281 /// Скорее всего практически не применимо
282 /// Предполагалось, что можно было конвертировать формируемый в проходе через
283   ↳ SequenceWalker
284 /// Stack в конкретный путь из Source, Target до связи, но это не всегда так.
285 /// TODO: Возможно нужен метод, который именно выбрасывает исключения (EnsurePathExists)
286 /// </remarks>
287 [MethodImpl(MethodImplOptions.AggressiveInlining)]
288 public static bool CheckPathExistance<TLinkAddress>(this ILinks<TLinkAddress> links,
289   ↳ params TLinkAddress[] path) where TLinkAddress : struct
290 {
291     var current = path[0];
292     //EnsureLinkExists(current, "path");
293     if (!links.Exists(current))
294     {
295         return false;
296     }
297     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
298     var constants = links.Constants;
299     for (var i = 1; i < path.Length; i++)
300     {
301         var next = path[i];
302         var values = links.GetLink(current);
303         var source = links.GetSource(values);
304         var target = links.GetTarget(values);
305         if (equalityComparer.Equals(source, target) && equalityComparer.Equals(source,
306           ↳ next))
307         {
308             //throw new InvalidOperationException(string.Format("Невозможно выбрать
309             ↳ путь, так как и Source и Target совпадают с элементом пути {0}.", next));
310             return false;
311         }
312         if (!equalityComparer.Equals(next, source) && !equalityComparer.Equals(next,
313           ↳ target))
314         {
315             //throw new InvalidOperationException(string.Format("Невозможно продолжить
316             ↳ путь через элемент пути {0}", next));
317             return false;
318         }
319         current = next;
320     }
321     return true;
322 }
323
324 /// <remarks>
325 /// Может потребовать дополнительного стека для PathElement's при использовании
326   ↳ SequenceWalker.
327 /// </remarks>
328 [MethodImpl(MethodImplOptions.AggressiveInlining)]
329 public static TLinkAddress GetByKeys<TLinkAddress>(this ILinks<TLinkAddress> links,
330   ↳ TLinkAddress root, params int[] path) where TLinkAddress : struct
331 {
332     links.EnsureLinkExists(root, "root");
333     var currentLink = root;
334     for (var i = 0; i < path.Length; i++)
335     {
336         currentLink = links.GetLink(currentLink)[path[i]];
337     }
338     return currentLink;
339 }
340
341 /// <summary>
342 /// <para>
343 /// Gets the square matrix sequence element by index using the specified links.
344 /// </para>
345 /// </summary>
346 /// <typeparam name="TLinkAddress">
347 /// <para>The link.</para>
348 /// </typeparam>
349 /// <param name="links">
350 /// <para>The links.</para>
351 /// </param>
352 /// <param name="root">

```

```

349 /// <para>The root.</para>
350 /// <para></para>
351 /// </param>
352 /// <param name="size">
353 /// <para>The size.</para>
354 /// <para></para>
355 /// </param>
356 /// <param name="index">
357 /// <para>The index.</para>
358 /// <para></para>
359 /// </param>
360 /// <exception cref="ArgumentOutOfRangeException">
361 /// <para>Sequences with sizes other than powers of two are not supported.</para>
362 /// <para></para>
363 /// </exception>
364 /// <returns>
365 /// <para>The current link.</para>
366 /// <para></para>
367 /// </returns>
368 [MethodImpl(MethodImplOptions.AggressiveInlining)]
369 public static TLinkAddress GetSquareMatrixSequenceElementByIndex<TLinkAddress>(this
    ↳ ILinks<TLinkAddress> links, TLinkAddress root, ulong size, ulong index) where
    ↳ TLinkAddress : struct
370 {
371     var constants = links.Constants;
372     var source = constants.SourcePart;
373     var target = constants.TargetPart;
374     if (!Platform.Numbers.Math.IsPowerOfTwo(size))
375     {
376         throw new ArgumentOutOfRangeException(nameof(size), "Sequences with sizes other
            ↳ than powers of two are not supported.");
377     }
378     var path = new BitArray(BitConverter.GetBytes(index));
379     var length = Bit.GetLowestPosition(size);
380     links.EnsureLinkExists(root, "root");
381     var currentLink = root;
382     for (var i = length - 1; i >= 0; i--)
383     {
384         currentLink = links.GetLink(currentLink)[path[i] ? target : source];
385     }
386     return currentLink;
387 }
388
389 #endregion
390
391 /// <summary>
392 /// Возвращает индекс указанной связи.
393 /// </summary>
394 /// <param name="links">Хранилище связей.</param>
395 /// <param name="link">Связь представленная списком, состоящим из её адреса и
    ↳ содержимого.</param>
396 /// <returns>Индекс начальной связи для указанной связи.</returns>
397 [MethodImpl(MethodImplOptions.AggressiveInlining)]
398 public static TLinkAddress GetIndex<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ IList<TLinkAddress>? link) where TLinkAddress : struct =>
    ↳ link[links.Constants.IndexPart];
399
400 /// <summary>
401 /// Возвращает индекс начальной (Source) связи для указанной связи.
402 /// </summary>
403 /// <param name="links">Хранилище связей.</param>
404 /// <param name="link">Индекс связи.</param>
405 /// <returns>Индекс начальной связи для указанной связи.</returns>
406 [MethodImpl(MethodImplOptions.AggressiveInlining)]
407 public static TLinkAddress GetSource<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ TLinkAddress link) where TLinkAddress : struct =>
    ↳ links.GetLink(link)[links.Constants.SourcePart];
408
409 /// <summary>
410 /// Возвращает индекс начальной (Source) связи для указанной связи.
411 /// </summary>
412 /// <param name="links">Хранилище связей.</param>
413 /// <param name="link">Связь представленная списком, состоящим из её адреса и
    ↳ содержимого.</param>
414 /// <returns>Индекс начальной связи для указанной связи.</returns>
415 [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

416 public static TLinkAddress GetSource<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ IList<TLinkAddress>? link) where TLinkAddress : struct =>
    ↳ link[links.Constants.SourcePart];

417
418 /// <summary>
419 /// Возвращает индекс конечной (Target) связи для указанной связи.
420 /// </summary>
421 /// <param name="links">Хранилище связей.</param>
422 /// <param name="link">Индекс связи.</param>
423 /// <returns>Индекс конечной связи для указанной связи.</returns>
424 [MethodImpl(MethodImplOptions.AggressiveInlining)]
425 public static TLinkAddress GetTarget<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ TLinkAddress link) where TLinkAddress : struct =>
    ↳ links.GetLink(link)[links.Constants.TargetPart];

426
427 /// <summary>
428 /// Возвращает индекс конечной (Target) связи для указанной связи.
429 /// </summary>
430 /// <param name="links">Хранилище связей.</param>
431 /// <param name="link">Связь представленная списком, состоящим из её адреса и
    ↳ содержимого.</param>
432 /// <returns>Индекс конечной связи для указанной связи.</returns>
433 [MethodImpl(MethodImplOptions.AggressiveInlining)]
434 public static TLinkAddress GetTarget<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ IList<TLinkAddress>? link) where TLinkAddress : struct =>
    ↳ link[links.Constants.TargetPart];

435
436 /// <summary>
437 /// Выполняет проход по всем связям, соответствующим шаблону, вызывая обработчик
    ↳ (handler) для каждой подходящей связи.
438 /// </summary>
439 /// <param name="links">Хранилище связей.</param>
440 /// <param name="handler">Обработчик каждой подходящей связи.</param>
441 /// <param name="restriction">Ограничения на содержимое связей. Каждое ограничение может
    ↳ иметь значения: Constants.Null - 0-я связь, обозначающая ссылку на пустоту, Any -
    ↳ отсутствие ограничения, 1..∞ конкретный адрес связи.</param>
442 /// <returns>True, в случае если проход по связям не был прерван и False в обратном
    ↳ случае.</returns>
443 [MethodImpl(MethodImplOptions.AggressiveInlining)]
444 public static bool Each<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ ReadHandler<TLinkAddress>? handler, params TLinkAddress[] restriction) where
    ↳ TLinkAddress : struct
    ↳ => links.Each(handler, (IList<TLinkAddress>)restriction);

445
446 public static bool Each<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ ReadHandler<TLinkAddress>? handler, IList<TLinkAddress> restriction) where
    ↳ TLinkAddress : struct
    ↳ => EqualityComparer<TLinkAddress>.Default.Equals(links.Each(restriction, handler),
    ↳ links.Constants.Continue);

447
448 public static bool Each<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ Func<TLinkAddress, bool> handler, TLinkAddress source, TLinkAddress target) where
    ↳ TLinkAddress : struct => links.Each(source, target, handler);

449
450
451
452 /// <summary>
453 /// Выполняет проход по всем связям, соответствующим шаблону, вызывая обработчик
    ↳ (handler) для каждой подходящей связи.
454 /// </summary>
455 /// <param name="links">Хранилище связей.</param>
456 /// <param name="source">Значение, определяющее соответствующие шаблону связи.
    ↳ (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве начала,
    ↳ Constants.Any - любое начало, 1..∞ конкретное начало)</param>
457 /// <param name="target">Значение, определяющее соответствующие шаблону связи.
    ↳ (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве конца,
    ↳ Constants.Any - любой конец, 1..∞ конкретный конец)</param>
458 /// <param name="handler">Обработчик каждой подходящей связи.</param>
459 /// <returns>True, в случае если проход по связям не был прерван и False в обратном
    ↳ случае.</returns>
460 [MethodImpl(MethodImplOptions.AggressiveInlining)]
461 public static bool Each<TLinkAddress>(this ILinks<TLinkAddress> links, TLinkAddress
    ↳ source, TLinkAddress target, Func<TLinkAddress, bool> handler) where TLinkAddress :
    ↳ struct
462 {
463     var constants = links.Constants;
464     return links.Each(link => handler(links.GetIndex(link)) ? constants.Continue :
    ↳ constants.Break, constants.Any, source, target);
465

```

```

466 }
467
468 public static bool Each<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ ReadHandler<TLinkAddress>? handler, TLinkAddress source, TLinkAddress target) where
    ↳ TLinkAddress : struct => links.Each(source, target, handler);
469
470
471 /// <summary>
472 /// Выполняет проход по всем связям, соответствующим шаблону, вызывая обработчик
    ↳ (handler) для каждой подходящей связи.
473 /// </summary>
474 /// <param name="links">Хранилище связей.</param>
475 /// <param name="source">Значение, определяющее соответствующие шаблону связи.
    ↳ (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве начала,
    ↳ Constants.Any - любое начало, 1..∞ конкретное начало)</param>
476 /// <param name="target">Значение, определяющее соответствующие шаблону связи.
    ↳ (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве конца,
    ↳ Constants.Any - любой конец, 1..∞ конкретный конец)</param>
477 /// <param name="handler">Обработчик каждой подходящей связи.</param>
478 /// <returns>True, в случае если проход по связям не был прерван и False в обратном
    ↳ случае.</returns>
479 [MethodImpl(MethodImplOptions.AggressiveInlining)]
480 public static bool Each<TLinkAddress>(this ILinks<TLinkAddress> links, TLinkAddress
    ↳ source, TLinkAddress target, ReadHandler<TLinkAddress>? handler) where TLinkAddress
    ↳ : struct => links.Each(handler, links.Constants.Any, source, target);
481
482 /// <summary>
483 /// <para>
484 /// Alls the links.
485 /// </para>
486 /// <para></para>
487 /// </summary>
488 /// <typeparam name="TLinkAddress">
489 /// <para>The link.</para>
490 /// <para></para>
491 /// </typeparam>
492 /// <param name="links">
493 /// <para>The links.</para>
494 /// <para></para>
495 /// </param>
496 /// <param name="restriction">
497 /// <para>The restriction.</para>
498 /// <para></para>
499 /// </param>
500 /// <returns>
501 /// <para>A list of i list t link</para>
502 /// <para></para>
503 /// </returns>
504 [MethodImpl(MethodImplOptions.AggressiveInlining)]
505 public static IList<IList<TLinkAddress>?> All<TLinkAddress>(this ILinks<TLinkAddress>
    ↳ links, params TLinkAddress[] restriction) where TLinkAddress : struct
506 {
507     var allLinks = new List<IList<TLinkAddress>?>();
508     var filler = new ListFiller<IList<TLinkAddress>?, TLinkAddress>(allLinks,
        ↳ links.Constants.Continue);
509     links.Each(filler.AddAndReturnConstant, restriction);
510     return allLinks;
511 }
512
513 /// <summary>
514 /// <para>
515 /// Alls the indices using the specified links.
516 /// </para>
517 /// <para></para>
518 /// </summary>
519 /// <typeparam name="TLinkAddress">
520 /// <para>The link.</para>
521 /// <para></para>
522 /// </typeparam>
523 /// <param name="links">
524 /// <para>The links.</para>
525 /// <para></para>
526 /// </param>
527 /// <param name="restriction">
528 /// <para>The restriction.</para>
529 /// <para></para>
530 /// </param>

```

```

531 /// <returns>
532 /// <para>A list of t link</para>
533 /// <para></para>
534 /// </returns>
535 [MethodImpl(MethodImplOptions.AggressiveInlining)]
536 public static IList<TLinkAddress>? AllIndices<TLinkAddress>(this ILinks<TLinkAddress>
    ↳ links, params TLinkAddress[] restriction) where TLinkAddress : struct
537 {
538     var allIndices = new List<TLinkAddress>();
539     var filler = new ListFiller<TLinkAddress, TLinkAddress>(allIndices,
        ↳ links.Constants.Continue);
540     links.Each(filler.AddFirstAndReturnConstant, restriction);
541     return allIndices;
542 }
543
544 /// <summary>
545 /// Возвращает значение, определяющее существует ли связь с указанными началом и концом
    ↳ в хранилище связей.
546 /// </summary>
547 /// <param name="links">Хранилище связей.</param>
548 /// <param name="source">Начало связи.</param>
549 /// <param name="target">Конец связи.</param>
550 /// <returns>Значение, определяющее существует ли связь.</returns>
551 [MethodImpl(MethodImplOptions.AggressiveInlining)]
552 public static bool Exists<TLinkAddress>(this ILinks<TLinkAddress> links, TLinkAddress
    ↳ source, TLinkAddress target) where TLinkAddress : struct =>
    ↳ Comparer<TLinkAddress>.Default.Compare(links.Count(links.Constants.Any, source,
    ↳ target), default) > 0;
553
554 #region Ensure
555 // TODO: May be move to EnsureExtensions or make it both there and here
556
557 /// <summary>
558 /// <para>
559 /// Ensures the link exists using the specified links.
560 /// </para>
561 /// <para></para>
562 /// </summary>
563 /// <typeparam name="TLinkAddress">
564 /// <para>The link.</para>
565 /// <para></para>
566 /// </typeparam>
567 /// <param name="links">
568 /// <para>The links.</para>
569 /// <para></para>
570 /// </param>
571 /// <param name="restriction">
572 /// <para>The restriction.</para>
573 /// <para></para>
574 /// </param>
575 /// <exception cref="ArgumentLinkDoesNotExistsException{TLinkAddress}">
576 /// <para>sequence[{i}]</para>
577 /// <para></para>
578 /// </exception>
579 [MethodImpl(MethodImplOptions.AggressiveInlining)]
580 public static void EnsureLinkExists<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ IList<TLinkAddress>? restriction) where TLinkAddress : struct
581 {
582     for (var i = 0; i < restriction.Count; i++)
583     {
584         if (!links.Exists(restriction[i]))
585         {
586             throw new ArgumentLinkDoesNotExistsException<TLinkAddress>(restriction[i],
                ↳ $"sequence[{i}]");
587         }
588     }
589 }
590
591 /// <summary>
592 /// <para>
593 /// Ensures the inner reference exists using the specified links.
594 /// </para>
595 /// <para></para>
596 /// </summary>
597 /// <typeparam name="TLinkAddress">
598 /// <para>The link.</para>
599 /// <para></para>

```



```

600    /// </typeparam>
601    /// <param name="links">
602    /// <para>The links.</para>
603    /// <para></para>
604    /// </param>
605    /// <param name="reference">
606    /// <para>The reference.</para>
607    /// <para></para>
608    /// </param>
609    /// <param name="argumentName">
610    /// <para>The argument name.</para>
611    /// <para></para>
612    /// </param>
613    /// <exception cref="ArgumentLinkDoesNotExistsException{TLinkAddress}">
614    /// <para></para>
615    /// <para></para>
616    /// </exception>
617    [MethodImpl(MethodImplOptions.AggressiveInlining)]
618    public static void EnsureInnerReferenceExists<TLinkAddress>(this ILinks<TLinkAddress>
    ↪ links, TLinkAddress reference, string argumentName) where TLinkAddress : struct
619    {
620        if (links.Constants.IsInternalReference(reference) && !links.Exists(reference))
621        {
622            throw new ArgumentLinkDoesNotExistsException<TLinkAddress>(reference,
    ↪ argumentName);
623        }
624    }
625
626    /// <summary>
627    /// <para>
628    /// Ensures the inner reference exists using the specified links.
629    /// </para>
630    /// <para></para>
631    /// </summary>
632    /// <typeparam name="TLinkAddress">
633    /// <para>The link.</para>
634    /// <para></para>
635    /// </typeparam>
636    /// <param name="links">
637    /// <para>The links.</para>
638    /// <para></para>
639    /// </param>
640    /// <param name="restriction">
641    /// <para>The restriction.</para>
642    /// <para></para>
643    /// </param>
644    /// <param name="argumentName">
645    /// <para>The argument name.</para>
646    /// <para></para>
647    /// </param>
648    [MethodImpl(MethodImplOptions.AggressiveInlining)]
649    public static void EnsureInnerReferenceExists<TLinkAddress>(this ILinks<TLinkAddress>
    ↪ links, IList<TLinkAddress>? restriction, string argumentName) where TLinkAddress :
    ↪ struct
650    {
651        for (int i = 0; i < restriction.Count; i++)
652        {
653            links.EnsureInnerReferenceExists(restriction[i], argumentName);
654        }
655    }
656
657    /// <summary>
658    /// <para>
659    /// Ensures the link is any or exists using the specified links.
660    /// </para>
661    /// <para></para>
662    /// </summary>
663    /// <typeparam name="TLinkAddress">
664    /// <para>The link.</para>
665    /// <para></para>
666    /// </typeparam>
667    /// <param name="links">
668    /// <para>The links.</para>
669    /// <para></para>
670    /// </param>
671    /// <param name="restriction">
672    /// <para>The restriction.</para>
673    /// <para></para>

```

```

674 /// </param>
675 /// <exception cref="ArgumentLinkDoesNotExistsException{TLinkAddress}">
676 /// <para>sequence[{i}]</para>
677 /// <para></para>
678 /// </exception>
679 [MethodImpl(MethodImplOptions.AggressiveInlining)]
680 public static void EnsureLinkIsAnyOrExists<TLinkAddress>(this ILinks<TLinkAddress>
681 ↪ links, IList<TLinkAddress>? restriction) where TLinkAddress : struct
682 {
683     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
684     var any = links.Constants.Any;
685     for (var i = 0; i < restriction.Count; i++)
686     {
687         if (!equalityComparer.Equals(restriction[i], any) &&
688             ↪ !links.Exists(restriction[i]))
689         {
690             throw new ArgumentLinkDoesNotExistsException<TLinkAddress>(restriction[i],
691                 ↪ $"sequence[{i}]");
692         }
693     }
694 }
695
696 /// <summary>
697 /// <para>
698 /// Ensures the link is any or exists using the specified links.
699 /// </para>
700 /// <para></para>
701 /// </summary>
702 /// <typeparam name="TLinkAddress">
703 /// <para>The link.</para>
704 /// </typeparam>
705 /// <param name="links">
706 /// <para>The links.</para>
707 /// </param>
708 /// <param name="link">
709 /// <para>The link.</para>
710 /// </param>
711 /// <param name="argumentName">
712 /// <para>The argument name.</para>
713 /// </param>
714 /// <exception cref="ArgumentLinkDoesNotExistsException{TLinkAddress}">
715 /// <para></para>
716 /// <para></para>
717 /// </exception>
718 [MethodImpl(MethodImplOptions.AggressiveInlining)]
719 public static void EnsureLinkIsAnyOrExists<TLinkAddress>(this ILinks<TLinkAddress>
720 ↪ links, TLinkAddress link, string argumentName) where TLinkAddress : struct
721 {
722     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
723     if (!equalityComparer.Equals(link, links.Constants.Any) && !links.Exists(link))
724     {
725         throw new ArgumentLinkDoesNotExistsException<TLinkAddress>(link, argumentName);
726     }
727 }
728
729 /// <summary>
730 /// <para>
731 /// Ensures the link is itself or exists using the specified links.
732 /// </para>
733 /// <para></para>
734 /// </summary>
735 /// <typeparam name="TLinkAddress">
736 /// <para>The link.</para>
737 /// </typeparam>
738 /// <param name="links">
739 /// <para>The links.</para>
740 /// </param>
741 /// <param name="link">
742 /// <para>The link.</para>
743 /// </param>
744 /// <param name="argumentName">

```

```

748 /// <para>The argument name.</para>
749 /// <para></para>
750 /// </param>
751 /// <exception cref="ArgumentLinkDoesNotExistsException{TLinkAddress}">
752 /// <para></para>
753 /// <para></para>
754 /// </exception>
755 [MethodImpl(MethodImplOptions.AggressiveInlining)]
756 public static void EnsureLinkIsItselfOrExists<TLinkAddress>(this ILinks<TLinkAddress>
    ↳ links, TLinkAddress link, string argumentName) where TLinkAddress : struct
757 {
758     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
759     if (!equalityComparer.Equals(link, links.Constants.Itself) && !links.Exists(link))
760     {
761         throw new ArgumentLinkDoesNotExistsException<TLinkAddress>(link, argumentName);
762     }
763 }
764
765 /// <param name="links">Хранилище связей.</param>
766 [MethodImpl(MethodImplOptions.AggressiveInlining)]
767 public static void EnsureDoesNotExists<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ TLinkAddress source, TLinkAddress target) where TLinkAddress : struct
768 {
769     if (links.Exists(source, target))
770     {
771         throw new LinkWithSameValueAlreadyExistsException();
772     }
773 }
774
775 /// <param name="links">Хранилище связей.</param>
776 [MethodImpl(MethodImplOptions.AggressiveInlining)]
777 public static void EnsureNoUsages<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ TLinkAddress link) where TLinkAddress : struct
778 {
779     if (links.HasUsages(link))
780     {
781         throw new ArgumentLinkHasDependenciesException<TLinkAddress>(link);
782     }
783 }
784
785 /// <param name="links">Хранилище связей.</param>
786 [MethodImpl(MethodImplOptions.AggressiveInlining)]
787 public static void EnsureCreated<TLinkAddress>(this ILinks<TLinkAddress> links, params
    ↳ TLinkAddress[] addresses) where TLinkAddress : struct =>
    ↳ links.EnsureCreated(links.Create, addresses);
788
789 /// <param name="links">Хранилище связей.</param>
790 [MethodImpl(MethodImplOptions.AggressiveInlining)]
791 public static void EnsurePointsCreated<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ params TLinkAddress[] addresses) where TLinkAddress : struct =>
    ↳ links.EnsureCreated(links.CreatePoint, addresses);
792
793 /// <param name="links">Хранилище связей.</param>
794 [MethodImpl(MethodImplOptions.AggressiveInlining)]
795 public static void EnsureCreated<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ Func<TLinkAddress> creator, params TLinkAddress[] addresses) where TLinkAddress :
    ↳ struct
796 {
797     var addressToUInt64Converter = CheckedConverter<TLinkAddress, ulong>.Default;
798     var uInt64ToAddressConverter = CheckedConverter<ulong, TLinkAddress>.Default;
799     var nonExistentAddresses = new HashSet<TLinkAddress>(addresses.Where(x =>
    ↳ !links.Exists(x)));
800     if (nonExistentAddresses.Count > 0)
801     {
802         var max = nonExistentAddresses.Max();
803         max = uInt64ToAddressConverter.Convert(System.Math.Min(addressToUInt64Converter.
    ↳ Convert(max),
    ↳ addressToUInt64Converter.Convert(links.Constants.InternalReferencesRange.Max,
    ↳ imum)));
804         var createdLinks = new List<TLinkAddress>();
805         var equalityComparer = EqualityComparer<TLinkAddress>.Default;
806         TLinkAddress createdLink = creator();
807         while (!equalityComparer.Equals(createdLink, max))
808         {
809             createdLinks.Add(createdLink);
810         }
811         for (var i = 0; i < createdLinks.Count; i++)
812         {

```

```

813         if (!nonExistentAddresses.Contains(createdLinks[i]))
814         {
815             links.Delete(createdLinks[i]);
816         }
817     }
818 }
819 }
820
821 #endregion
822
823 /// <param name="links">Хранилище связей.</param>
824 [MethodImpl(MethodImplOptions.AggressiveInlining)]
825 public static TLinkAddress CountUsages<TLinkAddress>(this ILinks<TLinkAddress> links,
826     ↪ TLinkAddress link) where TLinkAddress : struct
827 {
828     var constants = links.Constants;
829     var values = links.GetLink(link);
830     TLinkAddress usagesAsSource = links.Count(new Link<TLinkAddress>(constants.Any,
831     ↪ link, constants.Any));
832     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
833     if (equalityComparer.Equals(links.GetSource(values), link))
834     {
835         usagesAsSource = Arithmetic<TLinkAddress>.Decrement(usagesAsSource);
836     }
837     TLinkAddress usagesAsTarget = links.Count(new Link<TLinkAddress>(constants.Any,
838     ↪ constants.Any, link));
839     if (equalityComparer.Equals(links.GetTarget(values), link))
840     {
841         usagesAsTarget = Arithmetic<TLinkAddress>.Decrement(usagesAsTarget);
842     }
843     return Arithmetic<TLinkAddress>.Add(usagesAsSource, usagesAsTarget);
844 }
845
846 /// <param name="links">Хранилище связей.</param>
847 [MethodImpl(MethodImplOptions.AggressiveInlining)]
848 public static bool HasUsages<TLinkAddress>(this ILinks<TLinkAddress> links, TLinkAddress
849     ↪ link) where TLinkAddress : struct =>
850     ↪ Comparer<TLinkAddress>.Default.Compare(links.CountUsages(link), default) > 0;
851
852 /// <param name="links">Хранилище связей.</param>
853 [MethodImpl(MethodImplOptions.AggressiveInlining)]
854 public static bool Equals<TLinkAddress>(this ILinks<TLinkAddress> links, TLinkAddress
855     ↪ link, TLinkAddress source, TLinkAddress target) where TLinkAddress : struct
856 {
857     var constants = links.Constants;
858     var values = links.GetLink(link);
859     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
860     return equalityComparer.Equals(links.GetSource(values), source) &&
861     ↪ equalityComparer.Equals(links.GetTarget(values), target);
862 }
863
864 /// <summary>
865 /// Выполняет поиск связи с указанными Source (началом) и Target (концом).
866 /// </summary>
867 /// <param name="links">Хранилище связей.</param>
868 /// <param name="source">Индекс связи, которая является началом для искомой
869     ↪ связи.</param>
870 /// <param name="target">Индекс связи, которая является концом для искомой связи.</param>
871 /// <returns>Индекс искомой связи с указанными Source (началом) и Target
872     ↪ (концом).</returns>
873 [MethodImpl(MethodImplOptions.AggressiveInlining)]
874 public static TLinkAddress SearchOrDefault<TLinkAddress>(this ILinks<TLinkAddress>
875     ↪ links, TLinkAddress source, TLinkAddress target) where TLinkAddress : struct
876 {
877     var constants = links.Constants;
878     var setter = new Setter<TLinkAddress, TLinkAddress>(constants.Continue,
879     ↪ constants.Break, default);
880     links.Each(setter.SetFirstAndReturnFalse, constants.Any, source, target);
881     return setter.Result;
882 }
883
884 public static TLinkAddress CreatePoint<TLinkAddress>(this ILinks<TLinkAddress> links)
885     ↪ where TLinkAddress : struct
886 {
887     var constants = links.Constants;
888     var setter = new Setter<TLinkAddress, TLinkAddress>(constants.Continue,
889     ↪ constants.Break);
890     links.CreatePoint(setter.SetFirstFromSecondListAndReturnTrue);
891 }

```

```

878         return setter.Result;
879     }
880
881     /// <param name="links">Хранилище связей.</param>
882     [MethodImpl(MethodImplOptions.AggressiveInlining)]
883     public static TLinkAddress CreatePoint<TLinkAddress>(this ILinks<TLinkAddress> links,
884     ↪ WriteHandler<TLinkAddress>? handler) where TLinkAddress : struct
885     {
886         var constants = links.Constants;
887         WriteHandlerState<TLinkAddress> handlerState = new(constants.Continue,
888         ↪ constants.Break, handler);
889         TLinkAddress link = default;
890         TLinkAddress HandlerWrapper(IList<TLinkAddress>? before, IList<TLinkAddress>? after)
891         {
892             link = links.GetIndex(after);
893             return handlerState.Handle(before, after);
894         }
895         handlerState.Apply(links.Create(null, HandlerWrapper));
896         handlerState.Apply(links.Update(link, link, link, HandlerWrapper));
897         return handlerState.Result;
898     }
899
900     public static TLinkAddress CreateAndUpdate<TLinkAddress>(this ILinks<TLinkAddress>
901     ↪ links, TLinkAddress source, TLinkAddress target) where TLinkAddress : struct
902     {
903         var constants = links.Constants;
904         var setter = new Setter<TLinkAddress, TLinkAddress>(constants.Continue,
905         ↪ constants.Break);
906         links.CreateAndUpdate(source, target, setter.SetFirstFromSecondListAndReturnTrue);
907         return setter.Result;
908     }
909
910     /// <param name="links">Хранилище связей.</param>
911     [MethodImpl(MethodImplOptions.AggressiveInlining)]
912     public static TLinkAddress CreateAndUpdate<TLinkAddress>(this ILinks<TLinkAddress>
913     ↪ links, TLinkAddress source, TLinkAddress target, WriteHandler<TLinkAddress>?
914     ↪ handler) where TLinkAddress : struct
915     {
916         var constants = links.Constants;
917         TLinkAddress createdLink = default;
918         WriteHandlerState<TLinkAddress> handlerState = new(constants.Continue,
919         ↪ constants.Break, handler);
920         handlerState.Apply(links.Create(null, (before, after) =>
921         {
922             createdLink = links.GetIndex(after);
923             return handlerState.Handle(before, after);
924         })));
925         handlerState.Apply(links.Update(createdLink, source, target, handler));
926         return handlerState.Result;
927     }
928
929     /// <summary>
930     /// Обновляет связь с указанными началом (Source) и концом (Target)
931     /// на связь с указанными началом (NewSource) и концом (NewTarget).
932     /// </summary>
933     /// <param name="links">Хранилище связей.</param>
934     /// <param name="link">Индекс обновляемой связи.</param>
935     /// <param name="newSource">Индекс связи, которая является началом связи, на которую
936     ↪ выполняется обновление.</param>
937     /// <param name="newTarget">Индекс связи, которая является концом связи, на которую
938     ↪ выполняется обновление.</param>
939     /// <returns>Индекс обновлённой связи.</returns>
940     [MethodImpl(MethodImplOptions.AggressiveInlining)]
941     public static TLinkAddress Update<TLinkAddress>(this ILinks<TLinkAddress> links,
942     ↪ TLinkAddress link, TLinkAddress newSource, TLinkAddress newTarget) where
943     ↪ TLinkAddress : struct => links.Update(new Link<TLinkAddress>(link), new
944     ↪ Link<TLinkAddress>(link, newSource, newTarget));
945
946     public static TLinkAddress Update<TLinkAddress>(this ILinks<TLinkAddress> links, params
947     ↪ TLinkAddress[] restriction) where TLinkAddress : struct => links.Update(restriction,
948     ↪ null);
949
950     public static TLinkAddress Update<TLinkAddress>(this ILinks<TLinkAddress> links,
951     ↪ WriteHandler<TLinkAddress>? handler, params TLinkAddress[] restriction) where
952     ↪ TLinkAddress : struct => links.Update(restriction, handler);
953
954
955
956
957
958

```

```

939 public static TLinkAddress Update<TLinkAddress>(this ILinks<TLinkAddress> links,
940     ↳ IList<TLinkAddress>? restriction) where TLinkAddress : struct
941 {
942     var constants = links.Constants;
943     var setter = new Setter<TLinkAddress, TLinkAddress>(constants.Continue,
944         ↳ constants.Break);
945     links.Update(restriction, setter.SetFirstFromSecondListAndReturnTrue);
946     return setter.Result;
947 }
948
949 /// <summary>
950 /// Обновляет связь с указанными началом (Source) и концом (Target)
951 /// на связь с указанными началом (NewSource) и концом (NewTarget).
952 /// </summary>
953 /// <param name="links">Хранилище связей.</param>
954 /// <param name="restriction">Ограничения на содержимое связей. Каждое ограничение может
955     ↳ иметь значения: Constants.Null - 0-я связь, обозначающая ссылку на пустоту, Itself -
956     ↳ требование установить ссылку на себя, 1.. $\infty$  конкретный адрес другой связи.</param>
957 /// <returns>Индекс обновлённой связи.</returns>
958 [MethodImpl(MethodImplOptions.AggressiveInlining)]
959 public static TLinkAddress Update<TLinkAddress>(this ILinks<TLinkAddress> links,
960     ↳ IList<TLinkAddress>? restriction, WriteHandler<TLinkAddress>? handler) where
961     ↳ TLinkAddress : struct
962 {
963     return restriction.Count switch
964     {
965         2 => links.MergeAndDelete(restriction[0], restriction[1], handler),
966         4 => links.UpdateOrCreateOrGet(restriction[0], restriction[1], restriction[2],
967             ↳ restriction[3], handler),
968         _ => links.Update(restriction[0], restriction[1], restriction[2], handler)
969     };
970 }
971
972 public static TLinkAddress Update<TLinkAddress>(this ILinks<TLinkAddress> links,
973     ↳ TLinkAddress link, TLinkAddress newSource, TLinkAddress newTarget,
974     ↳ WriteHandler<TLinkAddress>? handler) where TLinkAddress : struct => links.Update(new
975     ↳ LinkAddress<TLinkAddress>(link), new Link<TLinkAddress>(link, newSource, newTarget),
976     ↳ handler);
977
978 /// <summary>
979 /// <para>
980 /// Resolves the constant as self reference using the specified links.
981 /// </para>
982 /// <para></para>
983 /// </summary>
984 /// <typeparam name="TLinkAddress">
985 /// <para>The link.</para>
986 /// <para></para>
987 /// </typeparam>
988 /// <param name="links">
989 /// <para>The links.</para>
990 /// <para></para>
991 /// </param>
992 /// <param name="constant">
993 /// <para>The constant.</para>
994 /// <para></para>
995 /// </param>
996 /// <param name="restriction">
997 /// <para>The restriction.</para>
998 /// <para></para>
999 /// </param>
1000 /// <param name="substitution">
1001 /// <para>The substitution.</para>
1002 /// <para></para>
1003 /// </param>
1004 /// <returns>
1005 /// <para>A list of t link</para>
1006 /// <para></para>
1007 /// </returns>
1008 [MethodImpl(MethodImplOptions.AggressiveInlining)]
1009 public static IList<TLinkAddress>? ResolveConstantAsSelfReference<TLinkAddress>(this
1010     ↳ ILinks<TLinkAddress> links, TLinkAddress constant, IList<TLinkAddress>? restriction,
1011     ↳ IList<TLinkAddress>? substitution) where TLinkAddress : struct
1012 {
1013     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
1014     var constants = links.Constants;
1015     var restrictionIndex = links.GetIndex(restriction);

```

```

1004     var substitutionIndex = links.GetIndex(substitution);
1005     if (equalityComparer.Equals(substitutionIndex, default))
1006     {
1007         substitutionIndex = restrictionIndex;
1008     }
1009     var source = links.GetSource(substitution);
1010     var target = links.GetTarget(substitution);
1011     source = equalityComparer.Equals(source, constant) ? substitutionIndex : source;
1012     target = equalityComparer.Equals(target, constant) ? substitutionIndex : target;
1013     return new Link<TLinkAddress>(substitutionIndex, source, target);
1014 }
1015
1016 /// <summary>
1017 /// Создаёт связь (если она не существовала), либо возвращает индекс существующей связи
1018   ↳ с указанными Source (началом) и Target (концом).
1019 /// </summary>
1020 /// <param name="links">Хранилище связей.</param>
1021 /// <param name="source">Индекс связи, которая является началом на создаваемой
1022   ↳ связи.</param>
1023 /// <param name="target">Индекс связи, которая является концом для создаваемой
1024   ↳ связи.</param>
1025 /// <returns>Индекс связи, с указанным Source (началом) и Target (концом)</returns>
1026 [MethodImpl(MethodImplOptions.AggressiveInlining)]
1027 public static TLinkAddress GetOrCreate<TLinkAddress>(this ILinks<TLinkAddress> links,
1028   ↳ TLinkAddress source, TLinkAddress target) where TLinkAddress : struct
1029 {
1030     var link = links.SearchOrDefault(source, target);
1031     if (EqualityComparer<TLinkAddress>.Default.Equals(link, default))
1032     {
1033         link = links.CreateAndUpdate(source, target);
1034     }
1035     return link;
1036 }
1037
1038 public static TLinkAddress UpdateOrCreateOrGet<TLinkAddress>(this ILinks<TLinkAddress>
1039   ↳ links, TLinkAddress source, TLinkAddress target, TLinkAddress newSource,
1040   ↳ TLinkAddress newTarget) where TLinkAddress : struct
1041 {
1042     var constants = links.Constants;
1043     var setter = new Setter<TLinkAddress, TLinkAddress>(constants.Continue,
1044       ↳ constants.Break);
1045     links.UpdateOrCreateOrGet(source, target, newSource, newTarget,
1046       ↳ setter.SetFirstFromSecondListAndReturnTrue);
1047     return setter.Result;
1048 }
1049
1050 /// <summary>
1051 /// Обновляет связь с указанными началом (Source) и концом (Target)
1052   ↳ на связь с указанными началом (NewSource) и концом (NewTarget).
1053 /// </summary>
1054 /// <param name="links">Хранилище связей.</param>
1055 /// <param name="source">Индекс связи, которая является началом обновляемой
1056   ↳ связи.</param>
1057 /// <param name="target">Индекс связи, которая является концом обновляемой связи.</param>
1058 /// <param name="newSource">Индекс связи, которая является началом связи, на которую
1059   ↳ выполняется обновление.</param>
1060 /// <param name="newTarget">Индекс связи, которая является концом связи, на которую
1061   ↳ выполняется обновление.</param>
1062 /// <returns>Индекс обновлённой связи.</returns>
1063 [MethodImpl(MethodImplOptions.AggressiveInlining)]
1064 public static TLinkAddress UpdateOrCreateOrGet<TLinkAddress>(this ILinks<TLinkAddress>
1065   ↳ links, TLinkAddress source, TLinkAddress target, TLinkAddress newSource,
1066   ↳ TLinkAddress newTarget, WriteHandler<TLinkAddress>? handler) where TLinkAddress :
1067   ↳ struct
1068 {
1069     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
1070     var link = links.SearchOrDefault(source, target);
1071     if (equalityComparer.Equals(link, default))
1072     {
1073         return links.CreateAndUpdate(newSource, newTarget, handler);
1074     }
1075     if (equalityComparer.Equals(newSource, source) && equalityComparer.Equals(newTarget,
1076       ↳ target))
1077     {
1078         var linkStruct = new Link<TLinkAddress>(link, source, target);
1079         return link;
1080     }
1081 }

```

```

1066         return links.Update(link, newSource, newTarget, handler);
1067     }
1068
1069     /// <summary>Удаляет связь с указанными началом (Source) и концом (Target).</summary>
1070     /// <param name="links">Хранилище связей.</param>
1071     /// <param name="source">Индекс связи, которая является началом удаляемой связи.</param>
1072     /// <param name="target">Индекс связи, которая является концом удаляемой связи.</param>
1073     [MethodImpl(MethodImplOptions.AggressiveInlining)]
1074     public static TLinkAddress DeleteIfExists<TLinkAddress>(this ILinks<TLinkAddress> links,
1075         ↪ TLinkAddress source, TLinkAddress target) where TLinkAddress : struct
1076     {
1077         var link = links.SearchOrDefault(source, target);
1078         if (!EqualityComparer<TLinkAddress>.Default.Equals(link, default))
1079         {
1080             links.Delete(link);
1081             return link;
1082         }
1083         return default;
1084     }
1085
1086     /// <summary>Удаляет несколько связей.</summary>
1087     /// <param name="links">Хранилище связей.</param>
1088     /// <param name="deletedLinks">Список адресов связей к удалению.</param>
1089     [MethodImpl(MethodImplOptions.AggressiveInlining)]
1090     public static void DeleteMany<TLinkAddress>(this ILinks<TLinkAddress> links,
1091         ↪ IList<TLinkAddress>? deletedLinks) where TLinkAddress : struct
1092     {
1093         for (int i = 0; i < deletedLinks.Count; i++)
1094         {
1095             links.Delete(deletedLinks[i]);
1096         }
1097     }
1098
1099     public static void DeleteAllUsages<TLinkAddress>(this ILinks<TLinkAddress> links,
1100         ↪ TLinkAddress linkIndex) where TLinkAddress : struct =>
1101         ↪ links.DeleteAllUsages(linkIndex, null);
1102
1103     /// <remarks>Before execution of this method ensure that deleted link is detached (all
1104     ↪ values - source and target are reset to null) or it might enter into infinite
1105     ↪ recursion.</remarks>
1106     [MethodImpl(MethodImplOptions.AggressiveInlining)]
1107     public static TLinkAddress DeleteAllUsages<TLinkAddress>(this ILinks<TLinkAddress>
1108         ↪ links, TLinkAddress linkIndex, WriteHandler<TLinkAddress>? handler) where
1109         ↪ TLinkAddress : struct
1110     {
1111         var constants = links.Constants;
1112         var any = constants.Any;
1113         var equalityComparer = EqualityComparer<TLinkAddress>.Default;
1114         var usagesAsSourceQuery = new Link<TLinkAddress>(any, linkIndex, any);
1115         var usagesAsTargetQuery = new Link<TLinkAddress>(any, any, linkIndex);
1116         var usages = new List<IList<TLinkAddress>?>();
1117         var usagesFiller = new ListFiller<IList<TLinkAddress>?, TLinkAddress>(usages,
1118             ↪ constants.Continue);
1119         links.Each(usagesFiller.AddAndReturnConstant, usagesAsSourceQuery);
1120         links.Each(usagesFiller.AddAndReturnConstant, usagesAsTargetQuery);
1121         WriteHandlerState<TLinkAddress> handlerState = new(constants.Continue,
1122             ↪ constants.Break, handler);
1123         foreach (var usage in usages)
1124         {
1125             if (equalityComparer.Equals(links.GetIndex(usage), linkIndex) ||
1126                 ↪ !links.Exists(links.GetIndex(usage)))
1127             {
1128                 continue;
1129             }
1130             handlerState.Apply(links.Delete(links.GetIndex(usage), handlerState.Handler));
1131         }
1132         return handlerState.Result;
1133     }
1134
1135     /// <summary>
1136     /// <para>
1137     /// Deletes the by query using the specified links.
1138     /// </para>
1139     /// <para></para>
1140     /// </summary>
1141     /// <typeparam name="TLinkAddress">
1142     /// <para>The link.</para>
1143     /// <para></para>

```



```

1133 /// </typeparam>
1134 /// <param name="links">
1135 /// <para>The links.</para>
1136 /// <para></para>
1137 /// </param>
1138 /// <param name="query">
1139 /// <para>The query.</para>
1140 /// <para></para>
1141 /// </param>
1142 [MethodImpl(MethodImplOptions.AggressiveInlining)]
1143 public static void DeleteByQuery<TLinkAddress>(this ILinks<TLinkAddress> links,
1144   ↳ Link<TLinkAddress> query) where TLinkAddress : struct
1145 {
1146     var queryResult = new List<TLinkAddress>();
1147     var queryResultFiller = new ListFiller<TLinkAddress, TLinkAddress>(queryResult,
1148   ↳ links.Constants.Continue);
1149     links.Each(queryResultFiller.AddFirstAndReturnConstant, query);
1150     foreach (var link in queryResult)
1151     {
1152         links.Delete(link);
1153     }
1154 }
1155
1156 // TODO: Move to Platform.Data
1157 /// <summary>
1158 /// <para>
1159 /// Determines whether are values reset.
1160 /// </para>
1161 /// <para></para>
1162 /// </summary>
1163 /// <typeparam name="TLinkAddress">
1164 /// <para>The link.</para>
1165 /// <para></para>
1166 /// </typeparam>
1167 /// <param name="links">
1168 /// <para>The links.</para>
1169 /// <para></para>
1170 /// </param>
1171 /// <param name="linkIndex">
1172 /// <para>The link index.</para>
1173 /// <para></para>
1174 /// </param>
1175 /// <returns>
1176 /// <para>The bool</para>
1177 /// <para></para>
1178 /// </returns>
1179 [MethodImpl(MethodImplOptions.AggressiveInlining)]
1180 public static bool AreValuesReset<TLinkAddress>(this ILinks<TLinkAddress> links,
1181   ↳ TLinkAddress linkIndex) where TLinkAddress : struct
1182 {
1183     var nullConstant = links.Constants.Null;
1184     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
1185     var link = links.GetLink(linkIndex);
1186     for (int i = 1; i < link.Count; i++)
1187     {
1188         if (!equalityComparer.Equals(link[i], nullConstant))
1189         {
1190             return false;
1191         }
1192     }
1193     return true;
1194 }
1195
1196 public static void ResetValues<TLinkAddress>(this ILinks<TLinkAddress> links,
1197   ↳ TLinkAddress linkIndex) where TLinkAddress : struct => links.ResetValues(linkIndex,
1198   ↳ null);
1199
1200 // TODO: Create a universal version of this method in Platform.Data (with using of for
1201   ↳ loop)
1202 /// <summary>
1203 /// <para>
1204 /// Resets the values using the specified links.
1205 /// </para>
1206 /// <para></para>
1207 /// </summary>
1208 /// <typeparam name="TLinkAddress">
1209 /// <para>The link.</para>
1210 /// <para></para>
1211 /// </typeparam>

```

```

1205 /// </typeparam>
1206 /// <param name="links">
1207 /// <para>The links.</para>
1208 /// <para></para>
1209 /// </param>
1210 /// <param name="linkIndex">
1211 /// <para>The link index.</para>
1212 /// <para></para>
1213 /// </param>
1214 [MethodImpl(MethodImplOptions.AggressiveInlining)]
1215 public static TLinkAddress ResetValues<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ TLinkAddress linkIndex, WriteHandler<TLinkAddress>? handler) where TLinkAddress :
    ↳ struct
1216 {
1217     var nullConstant = links.Constants.Null;
1218     var updateRequest = new Link<TLinkAddress>(linkIndex, nullConstant, nullConstant);
1219     return links.Update(updateRequest, handler);
1220 }
1221
1222 public static void EnforceResetValues<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ TLinkAddress linkIndex) where TLinkAddress : struct =>
    ↳ links.EnforceResetValues(linkIndex, null);
1223
1224
1225 // TODO: Create a universal version of this method in Platform.Data (with using of for
    ↳ loop)
1226 /// <summary>
1227 /// <para>
1228 /// Enforces the reset values using the specified links.
1229 /// </para>
1230 /// <para></para>
1231 /// </summary>
1232 /// <typeparam name="TLinkAddress">
1233 /// <para>The link.</para>
1234 /// <para></para>
1235 /// </typeparam>
1236 /// <param name="links">
1237 /// <para>The links.</para>
1238 /// <para></para>
1239 /// </param>
1240 /// <param name="linkIndex">
1241 /// <para>The link index.</para>
1242 /// <para></para>
1243 /// </param>
1244 [MethodImpl(MethodImplOptions.AggressiveInlining)]
1245 public static TLinkAddress EnforceResetValues<TLinkAddress>(this ILinks<TLinkAddress>
    ↳ links, TLinkAddress linkIndex, WriteHandler<TLinkAddress>? handler) where
    ↳ TLinkAddress : struct
1246 {
1247     if (!links.AreValuesReset(linkIndex))
1248     {
1249         return links.ResetValues(linkIndex, handler);
1250     }
1251     return links.Constants.Continue;
1252 }
1253
1254 public static void MergeUsages<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ TLinkAddress oldLinkIndex, TLinkAddress newLinkIndex) where TLinkAddress : struct =>
    ↳ links.MergeUsages(oldLinkIndex, newLinkIndex, null);
1255
1256 /// <summary>
1257 /// Merging two usages graphs, all children of old link moved to be children of new link
    ↳ or deleted.
1258 /// </summary>
1259 [MethodImpl(MethodImplOptions.AggressiveInlining)]
1260 public static TLinkAddress MergeUsages<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↳ TLinkAddress oldLinkIndex, TLinkAddress newLinkIndex, WriteHandler<TLinkAddress>?
    ↳ handler) where TLinkAddress : struct
1261 {
1262     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
1263     if (equalityComparer.Equals(oldLinkIndex, newLinkIndex))
1264     {
1265         return newLinkIndex;
1266     }
1267     var constants = links.Constants;
1268     var usagesAsSource = links.All(new Link<TLinkAddress>(constants.Any, oldLinkIndex,
    ↳ constants.Any));

```

```

1269 WriteHandlerState<TLinkAddress> handlerState = new(constants.Continue,
1270     ↳ constants.Break, handler);
1271 for (var i = 0; i < usagesAsSource.Count; i++)
1272 {
1273     var usageAsSource = usagesAsSource[i];
1274     if (equalityComparer.Equals(links.GetIndex(usageAsSource), oldLinkIndex))
1275     {
1276         continue;
1277     }
1278     var restriction = new LinkAddress<TLinkAddress>(links.GetIndex(usageAsSource));
1279     var substitution = new Link<TLinkAddress>(newLinkIndex,
1280     ↳ links.GetTarget(usageAsSource));
1281     handlerState.Apply(links.Update(restriction, substitution,
1282     ↳ handlerState.Handler));
1283 }
1284 var usagesAsTarget = links.All(new Link<TLinkAddress>(constants.Any, constants.Any,
1285     ↳ oldLinkIndex));
1286 for (var i = 0; i < usagesAsTarget.Count; i++)
1287 {
1288     var usageAsTarget = usagesAsTarget[i];
1289     if (equalityComparer.Equals(links.GetIndex(usageAsTarget), oldLinkIndex))
1290     {
1291         continue;
1292     }
1293     var restriction = links.GetLink(links.GetIndex(usageAsTarget));
1294     var substitution = new Link<TLinkAddress>(links.GetTarget(usageAsTarget),
1295     ↳ newLinkIndex);
1296     handlerState.Apply(links.Update(restriction, substitution,
1297     ↳ handlerState.Handler));
1298 }
1299 return handlerState.Result;
1300 }
1301
1302 public static TLinkAddress MergeAndDelete<TLinkAddress>(this ILinks<TLinkAddress> links,
1303     ↳ TLinkAddress oldLinkIndex, TLinkAddress newLinkIndex) where TLinkAddress : struct
1304 {
1305     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
1306     if (!equalityComparer.Equals(oldLinkIndex, newLinkIndex))
1307     {
1308         links.MergeUsages(oldLinkIndex, newLinkIndex);
1309         links.Delete(oldLinkIndex);
1310     }
1311     return newLinkIndex;
1312 }
1313
1314 /// <summary>
1315 /// Replace one link with another (replaced link is deleted, children are updated or
1316     ↳ deleted).
1317 /// </summary>
1318 [MethodImpl(MethodImplOptions.AggressiveInlining)]
1319 public static TLinkAddress MergeAndDelete<TLinkAddress>(this ILinks<TLinkAddress> links,
1320     ↳ TLinkAddress oldLinkIndex, TLinkAddress newLinkIndex, WriteHandler<TLinkAddress>?
1321     ↳ handler) where TLinkAddress : struct
1322 {
1323     var equalityComparer = EqualityComparer<TLinkAddress>.Default;
1324     var constants = links.Constants;
1325     WriteHandlerState<TLinkAddress> handlerState = new(constants.Continue,
1326     ↳ constants.Break, handler);
1327     if (!equalityComparer.Equals(oldLinkIndex, newLinkIndex))
1328     {
1329         handlerState.Apply(links.MergeUsages(oldLinkIndex, newLinkIndex,
1330         ↳ handlerState.Handler));
1331         handlerState.Apply(links.Delete(oldLinkIndex, handlerState.Handler));
1332     }
1333     return handlerState.Result;
1334 }
1335
1336 /// <summary>
1337 /// <para>
1338 /// Decorates the with automatic uniqueness and usages resolution using the specified
1339     ↳ links.
1340 /// </para>
1341 /// <para></para>
1342 /// </summary>
1343 /// <typeparam name="TLinkAddress">
1344 /// <para>The link.</para>
1345 /// <para></para>
1346 /// </typeparam>

```

```

1334    /// <param name="links">
1335    /// <para>The links.</para>
1336    /// <para></para>
1337    /// </param>
1338    /// <returns>
1339    /// <para>The links.</para>
1340    /// <para></para>
1341    /// </returns>
1342    [MethodImpl(MethodImplOptions.AggressiveInlining)]
1343    public static ILinks<TLinkAddress>
        ↳ DecorateWithAutomaticUniquenessAndUsagesResolution<TLinkAddress>(this
        ↳ ILinks<TLinkAddress> links) where TLinkAddress : struct
1344    {
1345        links = new LinksCascadeUsagesResolver<TLinkAddress>(links);
1346        links = new NonNullContentsLinkDeletionResolver<TLinkAddress>(links);
1347        links = new LinksCascadeUniquenessAndUsagesResolver<TLinkAddress>(links);
1348        return links;
1349    }
1350
1351    /// <summary>
1352    /// <para>
1353    /// Formats the links.
1354    /// </para>
1355    /// <para></para>
1356    /// </summary>
1357    /// <typeparam name="TLinkAddress">
1358    /// <para>The link.</para>
1359    /// <para></para>
1360    /// </typeparam>
1361    /// <param name="links">
1362    /// <para>The links.</para>
1363    /// <para></para>
1364    /// </param>
1365    /// <param name="link">
1366    /// <para>The link.</para>
1367    /// <para></para>
1368    /// </param>
1369    /// <returns>
1370    /// <para>The string</para>
1371    /// <para></para>
1372    /// </returns>
1373    [MethodImpl(MethodImplOptions.AggressiveInlining)]
1374    public static string Format<TLinkAddress>(this ILinks<TLinkAddress> links,
        ↳ IList<TLinkAddress>? link) where TLinkAddress : struct
1375    {
1376        var constants = links.Constants;
1377        return $"({links.GetIndex(link)}: {links.GetSource(link)} {links.GetTarget(link)})";
1378    }
1379
1380    /// <summary>
1381    /// <para>
1382    /// Formats the links.
1383    /// </para>
1384    /// <para></para>
1385    /// </summary>
1386    /// <typeparam name="TLinkAddress">
1387    /// <para>The link.</para>
1388    /// <para></para>
1389    /// </typeparam>
1390    /// <param name="links">
1391    /// <para>The links.</para>
1392    /// <para></para>
1393    /// </param>
1394    /// <param name="link">
1395    /// <para>The link.</para>
1396    /// <para></para>
1397    /// </param>
1398    /// <returns>
1399    /// <para>The string</para>
1400    /// <para></para>
1401    /// </returns>
1402    [MethodImpl(MethodImplOptions.AggressiveInlining)]
1403    public static string Format<TLinkAddress>(this ILinks<TLinkAddress> links, TLinkAddress
        ↳ link) where TLinkAddress : struct => links.Format(links.GetLink(link));
1404    }
1405    }

```

1.24 ./csharp/Platform.Data.Doublets/ISynchronizedLinks.cs

```
1  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
2
3  namespace Platform.Data.Doublets
4  {
5      /// <summary>
6      /// <para>
7      /// Defines the synchronized links.
8      /// </para>
9      /// <para></para>
10     /// </summary>
11     /// <seealso cref="ISynchronizedLinks{TLinkAddress, ILinks{TLinkAddress}},
12     ↪ LinksConstants{TLinkAddress}" />
13     /// <seealso cref="ILinks{TLinkAddress}" />
14     public interface ISynchronizedLinks<TLinkAddress> : ISynchronizedLinks<TLinkAddress,
15     ↪ ILinks<TLinkAddress>, LinksConstants<TLinkAddress>>, ILinks<TLinkAddress>
16     {
17     }
```

1.25 ./csharp/Platform.Data.Doublets/Link.cs

```
1  using Platform.Collections.Lists;
2  using Platform.Exceptions;
3  using Platform.Ranges;
4  using Platform.Singletons;
5  using System;
6  using System.Collections;
7  using System.Collections.Generic;
8  using System.Runtime.CompilerServices;
9
10 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
11
12 namespace Platform.Data.Doublets
13 {
14     /// <summary>
15     /// Структура описывающая уникальную связь.
16     /// </summary>
17     public struct Link<TLinkAddress> : IEquatable<Link<TLinkAddress>>,
18     ↪ IReadOnlyList<TLinkAddress>, IList<TLinkAddress>
19     {
20         /// <summary>
21         /// <para>
22         /// The link.
23         /// </para>
24         /// <para></para>
25         /// </summary>
26         public static readonly Link<TLinkAddress> Null = new Link<TLinkAddress>();
27         private static readonly LinksConstants<TLinkAddress> _constants =
28         ↪ Default<LinksConstants<TLinkAddress>>.Instance;
29         private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
30         ↪ EqualityComparer<TLinkAddress>.Default;
31         private const int Length = 3;
32
33         /// <summary>
34         /// <para>
35         /// The index.
36         /// </para>
37         /// <para></para>
38         /// </summary>
39         public readonly TLinkAddress Index;
40
41         /// <summary>
42         /// <para>
43         /// The source.
44         /// </para>
45         /// <para></para>
46         /// </summary>
47         public readonly TLinkAddress Source;
48
49         /// <summary>
50         /// <para>
51         /// The target.
52         /// </para>
53         /// <para></para>
54         /// </summary>
55         public readonly TLinkAddress Target;
```

```

56     /// <para></para>
57     /// </summary>
58     /// <param name="values">
59     /// <para>A values.</para>
60     /// <para></para>
61     /// </param>
62     [MethodImpl(MethodImplOptions.AggressiveInlining)]
63     public Link(params TLinkAddress[] values) => SetValues(values, out Index, out Source,
64         ↪ out Target);
65
66     /// <summary>
67     /// <para>
68     /// Initializes a new <see cref="Link"/> instance.
69     /// </para>
70     /// <para></para>
71     /// </summary>
72     /// <param name="values">
73     /// <para>A values.</para>
74     /// <para></para>
75     /// </param>
76     [MethodImpl(MethodImplOptions.AggressiveInlining)]
77     public Link(ICollection<TLinkAddress>? values) => SetValues(values, out Index, out Source, out
78         ↪ Target);
79
80     /// <summary>
81     /// <para>
82     /// Initializes a new <see cref="Link"/> instance.
83     /// </para>
84     /// <para></para>
85     /// </summary>
86     /// <param name="other">
87     /// <para>A other.</para>
88     /// <para></para>
89     /// </param>
90     /// <exception cref="NotSupportedException">
91     /// <para></para>
92     /// <para></para>
93     /// </exception>
94     [MethodImpl(MethodImplOptions.AggressiveInlining)]
95     public Link(object other)
96     {
97         if (other is Link<TLinkAddress> otherLink)
98         {
99             SetValues(ref otherLink, out Index, out Source, out Target);
100         }
101         else if (other is ICollection<TLinkAddress> otherList)
102         {
103             SetValues(otherList, out Index, out Source, out Target);
104         }
105         else
106         {
107             throw new NotSupportedException();
108         }
109     }
110
111     /// <summary>
112     /// <para>
113     /// Initializes a new <see cref="Link"/> instance.
114     /// </para>
115     /// <para></para>
116     /// </summary>
117     /// <param name="other">
118     /// <para>A other.</para>
119     /// <para></para>
120     /// </param>
121     [MethodImpl(MethodImplOptions.AggressiveInlining)]
122     public Link(ref Link<TLinkAddress> other) => SetValues(ref other, out Index, out Source,
123         ↪ out Target);
124
125     /// <summary>
126     /// <para>
127     /// Initializes a new <see cref="Link"/> instance.
128     /// </para>
129     /// <para></para>
130     /// </summary>
131     /// <param name="index">
132     /// <para>A index.</para>
133     /// <para></para>

```

```

131     /// </param>
132     /// <param name="source">
133     /// <para>A source.</para>
134     /// <para></para>
135     /// </param>
136     /// <param name="target">
137     /// <para>A target.</para>
138     /// <para></para>
139     /// </param>
140     [MethodImpl(MethodImplOptions.AggressiveInlining)]
141     public Link(TLinkAddress index, TLinkAddress source, TLinkAddress target)
142     {
143         Index = index;
144         Source = source;
145         Target = target;
146     }
147     [MethodImpl(MethodImplOptions.AggressiveInlining)]
148     private static void SetValues(ref Link<TLinkAddress> other, out TLinkAddress index, out
149     ↪ TLinkAddress source, out TLinkAddress target)
150     {
151         index = other.Index;
152         source = other.Source;
153         target = other.Target;
154     }
155     [MethodImpl(MethodImplOptions.AggressiveInlining)]
156     private static void SetValues(IList<TLinkAddress>? values, out TLinkAddress index, out
157     ↪ TLinkAddress source, out TLinkAddress target)
158     {
159         if (values == null)
160         {
161             index = default;
162             source = default;
163             target = default;
164             return;
165         }
166         switch (values.Count)
167         {
168             case 3:
169                 index = values[0];
170                 source = values[1];
171                 target = values[2];
172                 break;
173             case 2:
174                 index = values[0];
175                 source = values[1];
176                 target = default;
177                 break;
178             case 1:
179                 index = values[0];
180                 source = default;
181                 target = default;
182                 break;
183             default:
184                 index = default;
185                 source = default;
186                 target = default;
187                 break;
188         }
189     }
190     /// <summary>
191     /// <para>
192     /// Gets the hash code.
193     /// </para>
194     /// </summary>
195     /// <returns>
196     /// <para>The int</para>
197     /// <para></para>
198     /// </returns>
199     [MethodImpl(MethodImplOptions.AggressiveInlining)]
200     public override int GetHashCode() => (Index, Source, Target).GetHashCode();
201
202     /// <summary>
203     /// <para>
204     /// Determines whether this instance is null.
205     /// </para>
206     /// <para></para>
207     /// </summary>
208     /// <returns>

```

```

209    /// <para>The bool</para>
210    /// <para></para>
211    /// </returns>
212    [MethodImpl(MethodImplOptions.AggressiveInlining)]
213    public bool IsNull() => _equalityComparer.Equals(Index, _constants.Null)
214        && _equalityComparer.Equals(Source, _constants.Null)
215        && _equalityComparer.Equals(Target, _constants.Null);
216
217    /// <summary>
218    /// <para>
219    /// Determines whether this instance equals.
220    /// </para>
221    /// <para></para>
222    /// </summary>
223    /// <param name="other">
224    /// <para>The other.</para>
225    /// <para></para>
226    /// </param>
227    /// <returns>
228    /// <para>The bool</para>
229    /// <para></para>
230    /// </returns>
231    [MethodImpl(MethodImplOptions.AggressiveInlining)]
232    public override bool Equals(object other) => other is Link<TLinkAddress> &&
233        ↪ Equals((Link<TLinkAddress>)other);
234
235    /// <summary>
236    /// <para>
237    /// Determines whether this instance equals.
238    /// </para>
239    /// <para></para>
240    /// </summary>
241    /// <param name="other">
242    /// <para>The other.</para>
243    /// <para></para>
244    /// </param>
245    /// <returns>
246    /// <para>The bool</para>
247    /// <para></para>
248    /// </returns>
249    [MethodImpl(MethodImplOptions.AggressiveInlining)]
250    public bool Equals(Link<TLinkAddress> other) => _equalityComparer.Equals(Index,
251        ↪ other.Index)
252        && _equalityComparer.Equals(Source, other.Source)
253        && _equalityComparer.Equals(Target, other.Target);
254
255    /// <summary>
256    /// <para>
257    /// Returns the string using the specified index.
258    /// </para>
259    /// <para></para>
260    /// </summary>
261    /// <param name="index">
262    /// <para>The index.</para>
263    /// <para></para>
264    /// </param>
265    /// <param name="source">
266    /// <para>The source.</para>
267    /// <para></para>
268    /// </param>
269    /// <param name="target">
270    /// <para>The target.</para>
271    /// <para></para>
272    /// </param>
273    /// <returns>
274    /// <para>The string</para>
275    /// <para></para>
276    /// </returns>
277    [MethodImpl(MethodImplOptions.AggressiveInlining)]
278    public static string ToString(TLinkAddress index, TLinkAddress source, TLinkAddress
279        ↪ target) => $"({index}: {source}->{target})";
280
281    /// <summary>
282    /// <para>
283    /// Returns the string using the specified source.
284    /// </para>
285    /// <para></para>
286    /// </summary>

```



```

284     /// <param name="source">
285     /// <para>The source.</para>
286     /// <para></para>
287     /// </param>
288     /// <param name="target">
289     /// <para>The target.</para>
290     /// <para></para>
291     /// </param>
292     /// <returns>
293     /// <para>The string</para>
294     /// <para></para>
295     /// </returns>
296     [MethodImpl(MethodImplOptions.AggressiveInlining)]
297     public static string ToString(TLinkAddress source, TLinkAddress target) =>
298         ↪ $"{source}->{target}";
299
300     [MethodImpl(MethodImplOptions.AggressiveInlining)]
301     public static implicit operator TLinkAddress[] (Link<TLinkAddress> link) =>
302         ↪ link.ToArray();
303
304     [MethodImpl(MethodImplOptions.AggressiveInlining)]
305     public static implicit operator Link<TLinkAddress>(TLinkAddress[] linkArray) => new
306         ↪ Link<TLinkAddress>(linkArray);
307
308     /// <summary>
309     /// <para>
310     /// Returns the string.
311     /// </para>
312     /// <para></para>
313     /// </summary>
314     /// <returns>
315     /// <para>The string</para>
316     /// <para></para>
317     /// </returns>
318     [MethodImpl(MethodImplOptions.AggressiveInlining)]
319     public override string ToString() => _equalityComparer.Equals(Index, _constants.Null) ?
320         ↪ ToString(Source, Target) : ToString(Index, Source, Target);
321
322     #region IList
323
324     /// <summary>
325     /// <para>
326     /// Gets the count value.
327     /// </para>
328     /// <para></para>
329     /// </summary>
330     public int Count
331     {
332         [MethodImpl(MethodImplOptions.AggressiveInlining)]
333         get => Length;
334     }
335
336     /// <summary>
337     /// <para>
338     /// Gets the is read only value.
339     /// </para>
340     /// <para></para>
341     /// </summary>
342     public bool IsReadOnly
343     {
344         [MethodImpl(MethodImplOptions.AggressiveInlining)]
345         get => true;
346     }
347
348     /// <summary>
349     /// <para>
350     /// The not supported exception.
351     /// </para>
352     /// <para></para>
353     /// </summary>
354     public TLinkAddress this[int index]
355     {
356         [MethodImpl(MethodImplOptions.AggressiveInlining)]
357         get
358         {
359             Ensure.OnDebug.ArgumentInRange(index, new Range<int>(0, Length - 1),
360                 ↪ nameof(index));
361             if (index == _constants.IndexPart)

```

```

357         {
358             return Index;
359         }
360         if (index == _constants.SourcePart)
361         {
362             return Source;
363         }
364         if (index == _constants.TargetPart)
365         {
366             return Target;
367         }
368         throw new NotSupportedException(); // Impossible path due to
        ↪ Ensure.ArgumentInRange
369     }
370     [MethodImpl(MethodImplOptions.AggressiveInlining)]
371     set => throw new NotSupportedException();
372 }
373
374 /// <summary>
375 /// <para>
376 /// Gets the enumerator.
377 /// </para>
378 /// <para></para>
379 /// </summary>
380 /// <returns>
381 /// <para>The enumerator</para>
382 /// <para></para>
383 /// </returns>
384 [MethodImpl(MethodImplOptions.AggressiveInlining)]
385 IEnumerator IEnumerable.GetEnumerator() => GetEnumerator();
386
387 /// <summary>
388 /// <para>
389 /// Gets the enumerator.
390 /// </para>
391 /// <para></para>
392 /// </summary>
393 /// <returns>
394 /// <para>An enumerator of t link</para>
395 /// <para></para>
396 /// </returns>
397 [MethodImpl(MethodImplOptions.AggressiveInlining)]
398 public IEnumerator<TLinkAddress> GetEnumerator()
399 {
400     yield return Index;
401     yield return Source;
402     yield return Target;
403 }
404
405 /// <summary>
406 /// <para>
407 /// Adds the item.
408 /// </para>
409 /// <para></para>
410 /// </summary>
411 /// <param name="item">
412 /// <para>The item.</para>
413 /// <para></para>
414 /// </param>
415 [MethodImpl(MethodImplOptions.AggressiveInlining)]
416 public void Add(TLinkAddress item) => throw new NotSupportedException();
417
418 /// <summary>
419 /// <para>
420 /// Clears this instance.
421 /// </para>
422 /// <para></para>
423 /// </summary>
424 [MethodImpl(MethodImplOptions.AggressiveInlining)]
425 public void Clear() => throw new NotSupportedException();
426
427 /// <summary>
428 /// <para>
429 /// Determines whether this instance contains.
430 /// </para>
431 /// <para></para>
432 /// </summary>
433 /// <param name="item">

```

```

434    /// <para>The item.</para>
435    /// <para></para>
436    /// </param>
437    /// <returns>
438    /// <para>The bool</para>
439    /// <para></para>
440    /// </returns>
441    [MethodImpl(MethodImplOptions.AggressiveInlining)]
442    public bool Contains(TLinkAddress item) => IndexOf(item) >= 0;
443
444    /// <summary>
445    /// <para>
446    /// Copies the to using the specified array.
447    /// </para>
448    /// <para></para>
449    /// </summary>
450    /// <param name="array">
451    /// <para>The array.</para>
452    /// <para></para>
453    /// </param>
454    /// <param name="arrayIndex">
455    /// <para>The array index.</para>
456    /// <para></para>
457    /// </param>
458    /// <exception cref="InvalidOperationException">
459    /// <para></para>
460    /// <para></para>
461    /// </exception>
462    [MethodImpl(MethodImplOptions.AggressiveInlining)]
463    public void CopyTo(TLinkAddress[] array, int arrayIndex)
464    {
465        Ensure.OnDebug.ArgumentNotNull(array, nameof(array));
466        Ensure.OnDebug.ArgumentInRange(arrayIndex, new Range<int>(0, array.Length - 1),
467            ↪ nameof(arrayIndex));
468        if (arrayIndex + Length > array.Length)
469        {
470            throw new InvalidOperationException();
471        }
472        array[arrayIndex++] = Index;
473        array[arrayIndex++] = Source;
474        array[arrayIndex] = Target;
475    }
476
477    /// <summary>
478    /// <para>
479    /// Determines whether this instance remove.
480    /// </para>
481    /// <para></para>
482    /// </summary>
483    /// <param name="item">
484    /// <para>The item.</para>
485    /// <para></para>
486    /// </param>
487    /// <returns>
488    /// <para>The bool</para>
489    /// <para></para>
490    /// </returns>
491    [MethodImpl(MethodImplOptions.AggressiveInlining)]
492    public bool Remove(TLinkAddress item) => Throw.A.NotSupportedExceptionAndReturn<bool>();
493
494    /// <summary>
495    /// <para>
496    /// Indexes the of using the specified item.
497    /// </para>
498    /// <para></para>
499    /// </summary>
500    /// <param name="item">
501    /// <para>The item.</para>
502    /// <para></para>
503    /// </param>
504    /// <returns>
505    /// <para>The int</para>
506    /// <para></para>
507    /// </returns>
508    [MethodImpl(MethodImplOptions.AggressiveInlining)]
509    public int IndexOf(TLinkAddress item)
510    {
511        if (_equalityComparer.Equals(Index, item))

```

```

511         {
512             return _constants.IndexPart;
513         }
514         if (_equalityComparer.Equals(Source, item))
515         {
516             return _constants.SourcePart;
517         }
518         if (_equalityComparer.Equals(Target, item))
519         {
520             return _constants.TargetPart;
521         }
522         return -1;
523     }
524
525     /// <summary>
526     /// <para>
527     /// Inserts the index.
528     /// </para>
529     /// <para></para>
530     /// </summary>
531     /// <param name="index">
532     /// <para>The index.</para>
533     /// <para></para>
534     /// </param>
535     /// <param name="item">
536     /// <para>The item.</para>
537     /// <para></para>
538     /// </param>
539     [MethodImpl(MethodImplOptions.AggressiveInlining)]
540     public void Insert(int index, TLinkAddress item) => throw new NotSupportedException();
541
542     /// <summary>
543     /// <para>
544     /// Removes the at using the specified index.
545     /// </para>
546     /// <para></para>
547     /// </summary>
548     /// <param name="index">
549     /// <para>The index.</para>
550     /// <para></para>
551     /// </param>
552     [MethodImpl(MethodImplOptions.AggressiveInlining)]
553     public void RemoveAt(int index) => throw new NotSupportedException();
554
555     [MethodImpl(MethodImplOptions.AggressiveInlining)]
556     public static bool operator ==(Link<TLinkAddress> left, Link<TLinkAddress> right) =>
557         ↪ left.Equals(right);
558
559     [MethodImpl(MethodImplOptions.AggressiveInlining)]
560     public static bool operator !=(Link<TLinkAddress> left, Link<TLinkAddress> right) =>
561         ↪ !(left == right);
562
563     #endregion
564 }
565 }

```

1.26 ./csharp/Platform.Data.Doublets/LinkExtensions.cs

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the link extensions.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     public static class LinkExtensions
14     {
15         /// <summary>
16         /// <para>
17         /// Determines whether is full point.
18         /// </para>
19         /// <para></para>
20         /// </summary>
21         /// <typeparam name="TLinkAddress">
22         /// <para>The link.</para>

```

```

23     /// <para></para>
24     /// </typeparam>
25     /// <param name="link">
26     /// <para>The link.</para>
27     /// <para></para>
28     /// </param>
29     /// <returns>
30     /// <para>The bool</para>
31     /// <para></para>
32     /// </returns>
33     [MethodImpl(MethodImplOptions.AggressiveInlining)]
34     public static bool IsFullPoint<TLinkAddress>(this Link<TLinkAddress> link) =>
        ⇨ Point<TLinkAddress>.IsFullPoint(link);
35
36     /// <summary>
37     /// <para>
38     /// Determines whether is partial point.
39     /// </para>
40     /// <para></para>
41     /// </summary>
42     /// <typeparam name="TLinkAddress">
43     /// <para>The link.</para>
44     /// <para></para>
45     /// </typeparam>
46     /// <param name="link">
47     /// <para>The link.</para>
48     /// <para></para>
49     /// </param>
50     /// <returns>
51     /// <para>The bool</para>
52     /// <para></para>
53     /// </returns>
54     [MethodImpl(MethodImplOptions.AggressiveInlining)]
55     public static bool IsPartialPoint<TLinkAddress>(this Link<TLinkAddress> link) =>
        ⇨ Point<TLinkAddress>.IsPartialPoint(link);
56 }
57 }

```

1.27 ./csharp/Platform.Data.Doublets/LinksOperatorBase.cs

```

1 using System.Runtime.CompilerServices;
2
3 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5 namespace Platform.Data.Doublets
6 {
7     /// <summary>
8     /// <para>
9     /// Represents the links operator base.
10    /// </para>
11    /// <para></para>
12    /// </summary>
13    public abstract class LinksOperatorBase<TLinkAddress>
14    {
15        /// <summary>
16        /// <para>
17        /// The links.
18        /// </para>
19        /// <para></para>
20        /// </summary>
21        protected readonly ILinks<TLinkAddress> _links;
22
23        /// <summary>
24        /// <para>
25        /// Gets the links value.
26        /// </para>
27        /// <para></para>
28        /// </summary>
29        public ILinks<TLinkAddress> Links
30        {
31            [MethodImpl(MethodImplOptions.AggressiveInlining)]
32            get => _links;
33        }
34
35        /// <summary>
36        /// <para>
37        /// Initializes a new <see cref="LinksOperatorBase"/> instance.
38        /// </para>
39        /// <para></para>

```

```

40     /// </summary>
41     /// <param name="links">
42     /// <para>A links.</para>
43     /// <para></para>
44     /// </param>
45     [MethodImpl(MethodImplOptions.AggressiveInlining)]
46     protected LinksOperatorBase(ILinks<TLinkAddress> links) => _links = links;
47 }
48 }

```

1.28 ./csharp/Platform.Data.Doublets/Memory/ILinksListMethods.cs

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory
6  {
7      /// <summary>
8      /// <para>
9      /// Defines the links list methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     public interface ILinksListMethods<TLinkAddress>
14     {
15         /// <summary>
16         /// <para>
17         /// Detaches the free link.
18         /// </para>
19         /// <para></para>
20         /// </summary>
21         /// <param name="freeLink">
22         /// <para>The free link.</para>
23         /// <para></para>
24         /// </param>
25         [MethodImpl(MethodImplOptions.AggressiveInlining)]
26         void Detach(TLinkAddress freeLink);
27
28         /// <summary>
29         /// <para>
30         /// Attaches the as first using the specified link.
31         /// </para>
32         /// <para></para>
33         /// </summary>
34         /// <param name="link">
35         /// <para>The link.</para>
36         /// <para></para>
37         /// </param>
38         [MethodImpl(MethodImplOptions.AggressiveInlining)]
39         void AttachAsFirst(TLinkAddress link);
40     }
41 }

```

1.29 ./csharp/Platform.Data.Doublets/Memory/ILinksTreeMethods.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Delegates;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Memory
9  {
10     /// <summary>
11     /// <para>
12     /// Defines the links tree methods.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     public interface ILinksTreeMethods<TLinkAddress>
17     {
18         /// <summary>
19         /// <para>
20         /// Counts the usages using the specified root.
21         /// </para>
22         /// <para></para>
23         /// </summary>
24         /// <param name="root">

```

```

25     /// <para>The root.</para>
26     /// <para></para>
27     /// </param>
28     /// <returns>
29     /// <para>The link</para>
30     /// <para></para>
31     /// </returns>
32     [MethodImpl(MethodImplOptions.AggressiveInlining)]
33     TLinkAddress CountUsages(TLinkAddress root);
34
35     /// <summary>
36     /// <para>
37     /// Searches the source.
38     /// </para>
39     /// <para></para>
40     /// </summary>
41     /// <param name="source">
42     /// <para>The source.</para>
43     /// <para></para>
44     /// </param>
45     /// <param name="target">
46     /// <para>The target.</para>
47     /// <para></para>
48     /// </param>
49     /// <returns>
50     /// <para>The link</para>
51     /// <para></para>
52     /// </returns>
53     [MethodImpl(MethodImplOptions.AggressiveInlining)]
54     TLinkAddress Search(TLinkAddress source, TLinkAddress target);
55
56     /// <summary>
57     /// <para>
58     /// Eaches the usage using the specified root.
59     /// </para>
60     /// <para></para>
61     /// </summary>
62     /// <param name="root">
63     /// <para>The root.</para>
64     /// <para></para>
65     /// </param>
66     /// <param name="handler">
67     /// <para>The handler.</para>
68     /// <para></para>
69     /// </param>
70     /// <returns>
71     /// <para>The link</para>
72     /// <para></para>
73     /// </returns>
74     [MethodImpl(MethodImplOptions.AggressiveInlining)]
75     TLinkAddress EachUsage(TLinkAddress root, ReadHandler<TLinkAddress>? handler);
76
77     /// <summary>
78     /// <para>
79     /// Detaches the root.
80     /// </para>
81     /// <para></para>
82     /// </summary>
83     /// <param name="root">
84     /// <para>The root.</para>
85     /// <para></para>
86     /// </param>
87     /// <param name="linkIndex">
88     /// <para>The link index.</para>
89     /// <para></para>
90     /// </param>
91     [MethodImpl(MethodImplOptions.AggressiveInlining)]
92     void Detach(ref TLinkAddress root, TLinkAddress linkIndex);
93
94     /// <summary>
95     /// <para>
96     /// Attaches the root.
97     /// </para>
98     /// <para></para>
99     /// </summary>
100    /// <param name="root">
101    /// <para>The root.</para>
102    /// <para></para>

```

```

103     /// </param>
104     /// <param name="linkIndex">
105     /// <para>The link index.</para>
106     /// <para></para>
107     /// </param>
108     [MethodImpl(MethodImplOptions.AggressiveInlining)]
109     void Attach(ref TLinkAddress root, TLinkAddress linkIndex);
110 }
111 }

```

1.30 ./csharp/Platform.Data.Doublets/Memory/IndexTreeType.cs

```

1  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
2
3  namespace Platform.Data.Doublets.Memory
4  {
5      /// <summary>
6      /// <para>
7      /// The index tree type enum.
8      /// </para>
9      /// <para></para>
10     /// </summary>
11     public enum IndexTreeType
12     {
13         /// <summary>
14         /// <para>
15         /// The default index tree type.
16         /// </para>
17         /// <para></para>
18         /// </summary>
19         Default = 0,
20         /// <summary>
21         /// <para>
22         /// The size balanced tree index tree type.
23         /// </para>
24         /// <para></para>
25         /// </summary>
26         SizeBalancedTree = 1,
27         /// <summary>
28         /// <para>
29         /// The recursionless size balanced tree index tree type.
30         /// </para>
31         /// <para></para>
32         /// </summary>
33         RecursionlessSizeBalancedTree = 2,
34         /// <summary>
35         /// <para>
36         /// The sized and threaded avl balanced tree index tree type.
37         /// </para>
38         /// <para></para>
39         /// </summary>
40         SizedAndThreadedAVLBalancedTree = 3
41     }
42 }

```

1.31 ./csharp/Platform.Data.Doublets/Memory/LinksHeader.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Unsafe;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Memory
9  {
10     /// <summary>
11     /// <para>
12     /// The links header.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     public struct LinksHeader<TLinkAddress> : IEquatable<LinksHeader<TLinkAddress>>
17     {
18         private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
19             ↪ EqualityComparer<TLinkAddress>.Default;
20
21         /// <summary>
22         /// <para>
23         /// The size.
24         /// </para>

```



```

24     /// <para></para>
25     /// </summary>
26     public static readonly long SizeInBytes = Structure<LinksHeader<TLinkAddress>>.Size;
27
28     /// <summary>
29     /// <para>
30     /// The allocated links.
31     /// </para>
32     /// <para></para>
33     /// </summary>
34     public TLinkAddress AllocatedLinks;
35     /// <summary>
36     /// <para>
37     /// The reserved links.
38     /// </para>
39     /// <para></para>
40     /// </summary>
41     public TLinkAddress ReservedLinks;
42     /// <summary>
43     /// <para>
44     /// The free links.
45     /// </para>
46     /// <para></para>
47     /// </summary>
48     public TLinkAddress FreeLinks;
49     /// <summary>
50     /// <para>
51     /// The first free link.
52     /// </para>
53     /// <para></para>
54     /// </summary>
55     public TLinkAddress FirstFreeLink;
56     /// <summary>
57     /// <para>
58     /// The root as source.
59     /// </para>
60     /// <para></para>
61     /// </summary>
62     public TLinkAddress RootAsSource;
63     /// <summary>
64     /// <para>
65     /// The root as target.
66     /// </para>
67     /// <para></para>
68     /// </summary>
69     public TLinkAddress RootAsTarget;
70     /// <summary>
71     /// <para>
72     /// The last free link.
73     /// </para>
74     /// <para></para>
75     /// </summary>
76     public TLinkAddress LastFreeLink;
77     /// <summary>
78     /// <para>
79     /// The reserved.
80     /// </para>
81     /// <para></para>
82     /// </summary>
83     public TLinkAddress Reserved8;
84
85     /// <summary>
86     /// <para>
87     /// Determines whether this instance equals.
88     /// </para>
89     /// <para></para>
90     /// </summary>
91     /// <param name="obj">
92     /// <para>The obj.</para>
93     /// <para></para>
94     /// </param>
95     /// <returns>
96     /// <para>The bool</para>
97     /// <para></para>
98     /// </returns>
99     [MethodImpl(MethodImplOptions.AggressiveInlining)]
100     public override bool Equals(object obj) => obj is LinksHeader<TLinkAddress> linksHeader
        ↪ ? Equals(linksHeader) : false;

```

```

101     /// <summary>
102     /// <para>
103     /// Determines whether this instance equals.
104     /// </para>
105     /// <para></para>
106     /// </summary>
107     /// <param name="other">
108     /// <para>The other.</para>
109     /// <para></para>
110     /// </param>
111     /// <returns>
112     /// <para>The bool</para>
113     /// <para></para>
114     /// </returns>
115     [MethodImpl(MethodImplOptions.AggressiveInlining)]
116     public bool Equals(LinksHeader<TLinkAddress> other)
117     => _equalityComparer.Equals(AllocatedLinks, other.AllocatedLinks)
118     && _equalityComparer.Equals(ReservedLinks, other.ReservedLinks)
119     && _equalityComparer.Equals(FreeLinks, other.FreeLinks)
120     && _equalityComparer.Equals(FirstFreeLink, other.FirstFreeLink)
121     && _equalityComparer.Equals(RootAsSource, other.RootAsSource)
122     && _equalityComparer.Equals(RootAsTarget, other.RootAsTarget)
123     && _equalityComparer.Equals(LastFreeLink, other.LastFreeLink)
124     && _equalityComparer.Equals(Reserved8, other.Reserved8);
125
126     /// <summary>
127     /// <para>
128     /// Gets the hash code.
129     /// </para>
130     /// <para></para>
131     /// </summary>
132     /// <returns>
133     /// <para>The int</para>
134     /// <para></para>
135     /// </returns>
136     [MethodImpl(MethodImplOptions.AggressiveInlining)]
137     public override int GetHashCode() => (AllocatedLinks, ReservedLinks, FreeLinks,
138     ↪ FirstFreeLink, RootAsSource, RootAsTarget, LastFreeLink, Reserved8).GetHashCode();
139
140     [MethodImpl(MethodImplOptions.AggressiveInlining)]
141     public static bool operator ==(LinksHeader<TLinkAddress> left, LinksHeader<TLinkAddress>
142     ↪ right) => left.Equals(right);
143
144     [MethodImpl(MethodImplOptions.AggressiveInlining)]
145     public static bool operator !=(LinksHeader<TLinkAddress> left, LinksHeader<TLinkAddress>
146     ↪ right) => !(left == right);
147 }
148 }

```

1.32 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksRecursionlessSizeBalancedTreeMethods

```

1  using System;
2  using System.Text;
3  using System.Collections.Generic;
4  using System.Runtime.CompilerServices;
5  using Platform.Collections.Methods.Trees;
6  using Platform.Converters;
7  using Platform.Delegates;
8  using static System.Runtime.CompilerServices.Unsafe;
9
10 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
11
12 namespace Platform.Data.Doublets.Memory.Split.Generic
13 {
14     /// <summary>
15     /// <para>
16     /// Represents the external links recursionless size balanced tree methods base.
17     /// </para>
18     /// <para></para>
19     /// </summary>
20     /// <seealso cref="RecursionlessSizeBalancedTreeMethods{TLinkAddress}"/>
21     /// <seealso cref="ILinksTreeMethods{TLinkAddress}"/>
22     public unsafe abstract class
23     ↪ ExternalLinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress> :
24     ↪ RecursionlessSizeBalancedTreeMethods<TLinkAddress>, ILinksTreeMethods<TLinkAddress>
25     {
26         private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
27         ↪ = UncheckedConverter<TLinkAddress, long>.Default;
28     }
29 }

```

```

26     /// <summary>
27     /// <para>
28     /// The break.
29     /// </para>
30     /// <para></para>
31     /// </summary>
32     protected readonly TLinkAddress Break;
33     /// <summary>
34     /// <para>
35     /// The continue.
36     /// </para>
37     /// <para></para>
38     /// </summary>
39     protected readonly TLinkAddress Continue;
40     /// <summary>
41     /// <para>
42     /// The links data parts.
43     /// </para>
44     /// <para></para>
45     /// </summary>
46     protected readonly byte* LinksDataParts;
47     /// <summary>
48     /// <para>
49     /// The links index parts.
50     /// </para>
51     /// <para></para>
52     /// </summary>
53     protected readonly byte* LinksIndexParts;
54     /// <summary>
55     /// <para>
56     /// The header.
57     /// </para>
58     /// <para></para>
59     /// </summary>
60     protected readonly byte* Header;
61
62     /// <summary>
63     /// <para>
64     /// Initializes a new <see
65     ↪ cref="ExternalLinksRecursionlessSizeBalancedTreeMethodsBase"/> instance.
66     /// </para>
67     /// <para></para>
68     /// </summary>
69     /// <param name="constants">
70     /// <para>A constants.</para>
71     /// </param>
72     /// <param name="linksDataParts">
73     /// <para>A links data parts.</para>
74     /// <para></para>
75     /// </param>
76     /// <param name="linksIndexParts">
77     /// <para>A links index parts.</para>
78     /// <para></para>
79     /// </param>
80     /// <param name="header">
81     /// <para>A header.</para>
82     /// <para></para>
83     /// </param>
84     [MethodImpl(MethodImplOptions.AggressiveInlining)]
85     protected
86     ↪ ExternalLinksRecursionlessSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress>
87     ↪ constants, byte* linksDataParts, byte* linksIndexParts, byte* header)
88     {
89         LinksDataParts = linksDataParts;
90         LinksIndexParts = linksIndexParts;
91         Header = header;
92         Break = constants.Break;
93         Continue = constants.Continue;
94     }
95
96     /// <summary>
97     /// <para>
98     /// Gets the tree root.
99     /// </para>
100    /// <para></para>
101    /// </summary>
102    /// <returns>
103    /// <para>The link</para>

```

```

102     /// <para></para>
103     /// </returns>
104     [MethodImpl(MethodImplOptions.AggressiveInlining)]
105     protected abstract TLinkAddress GetTreeRoot();
106
107     /// <summary>
108     /// <para>
109     /// Gets the base part value using the specified link.
110     /// </para>
111     /// <para></para>
112     /// </summary>
113     /// <param name="link">
114     /// <para>The link.</para>
115     /// <para></para>
116     /// </param>
117     /// <returns>
118     /// <para>The link</para>
119     /// <para></para>
120     /// </returns>
121     [MethodImpl(MethodImplOptions.AggressiveInlining)]
122     protected abstract TLinkAddress GetBasePartValue(TLinkAddress link);
123
124     /// <summary>
125     /// <para>
126     /// Determines whether this instance first is to the right of second.
127     /// </para>
128     /// <para></para>
129     /// </summary>
130     /// <param name="source">
131     /// <para>The source.</para>
132     /// <para></para>
133     /// </param>
134     /// <param name="target">
135     /// <para>The target.</para>
136     /// <para></para>
137     /// </param>
138     /// <param name="rootSource">
139     /// <para>The root source.</para>
140     /// <para></para>
141     /// </param>
142     /// <param name="rootTarget">
143     /// <para>The root target.</para>
144     /// <para></para>
145     /// </param>
146     /// <returns>
147     /// <para>The bool</para>
148     /// <para></para>
149     /// </returns>
150     [MethodImpl(MethodImplOptions.AggressiveInlining)]
151     protected abstract bool FirstIsToTheRightOfSecond(TLinkAddress source, TLinkAddress
        ↪ target, TLinkAddress rootSource, TLinkAddress rootTarget);
152
153     /// <summary>
154     /// <para>
155     /// Determines whether this instance first is to the left of second.
156     /// </para>
157     /// <para></para>
158     /// </summary>
159     /// <param name="source">
160     /// <para>The source.</para>
161     /// <para></para>
162     /// </param>
163     /// <param name="target">
164     /// <para>The target.</para>
165     /// <para></para>
166     /// </param>
167     /// <param name="rootSource">
168     /// <para>The root source.</para>
169     /// <para></para>
170     /// </param>
171     /// <param name="rootTarget">
172     /// <para>The root target.</para>
173     /// <para></para>
174     /// </param>
175     /// <returns>
176     /// <para>The bool</para>
177     /// <para></para>
178     /// </returns>

```

```

179 [MethodImpl(MethodImplOptions.AggressiveInlining)]
180 protected abstract bool FirstIsToTheLeftOfSecond(TLinkAddress source, TLinkAddress
    → target, TLinkAddress rootSource, TLinkAddress rootTarget);
181
182 /// <summary>
183 /// <para>
184 /// Gets the header reference.
185 /// </para>
186 /// <para></para>
187 /// </summary>
188 /// <returns>
189 /// <para>A ref links header of t link</para>
190 /// <para></para>
191 /// </returns>
192 [MethodImpl(MethodImplOptions.AggressiveInlining)]
193 protected virtual ref LinksHeader<TLinkAddress> GetHeaderReference() => ref
    → AsRef<LinksHeader<TLinkAddress>>(Header);
194
195 /// <summary>
196 /// <para>
197 /// Gets the link data part reference using the specified link.
198 /// </para>
199 /// <para></para>
200 /// </summary>
201 /// <param name="link">
202 /// <para>The link.</para>
203 /// <para></para>
204 /// </param>
205 /// <returns>
206 /// <para>A ref raw link data part of t link</para>
207 /// <para></para>
208 /// </returns>
209 [MethodImpl(MethodImplOptions.AggressiveInlining)]
210 protected virtual ref RawLinkDataPart<TLinkAddress>
    → GetLinkDataPartReference(TLinkAddress link) => ref
    → AsRef<RawLinkDataPart<TLinkAddress>>(LinksDataParts +
    → (RawLinkDataPart<TLinkAddress>.SizeInBytes *
    → _addressToInt64Converter.Convert(link)));
211
212 /// <summary>
213 /// <para>
214 /// Gets the link index part reference using the specified link.
215 /// </para>
216 /// <para></para>
217 /// </summary>
218 /// <param name="link">
219 /// <para>The link.</para>
220 /// <para></para>
221 /// </param>
222 /// <returns>
223 /// <para>A ref raw link index part of t link</para>
224 /// <para></para>
225 /// </returns>
226 [MethodImpl(MethodImplOptions.AggressiveInlining)]
227 protected virtual ref RawLinkIndexPart<TLinkAddress>
    → GetLinkIndexPartReference(TLinkAddress link) => ref
    → AsRef<RawLinkIndexPart<TLinkAddress>>(LinksIndexParts +
    → (RawLinkIndexPart<TLinkAddress>.SizeInBytes *
    → _addressToInt64Converter.Convert(link)));
228
229 /// <summary>
230 /// <para>
231 /// Gets the link values using the specified link index.
232 /// </para>
233 /// <para></para>
234 /// </summary>
235 /// <param name="linkIndex">
236 /// <para>The link index.</para>
237 /// <para></para>
238 /// </param>
239 /// <returns>
240 /// <para>A list of t link</para>
241 /// <para></para>
242 /// </returns>
243 [MethodImpl(MethodImplOptions.AggressiveInlining)]
244 protected virtual IList<TLinkAddress>? GetLinkValues(TLinkAddress linkIndex)
245 {
246     ref var link = ref GetLinkDataPartReference(linkIndex);

```

```

247     return new Link<TLinkAddress>(linkIndex, link.Source, link.Target);
248 }
249
250 /// <summary>
251 /// <para>
252 /// Determines whether this instance first is to the left of second.
253 /// </para>
254 /// <para></para>
255 /// </summary>
256 /// <param name="first">
257 /// <para>The first.</para>
258 /// <para></para>
259 /// </param>
260 /// <param name="second">
261 /// <para>The second.</para>
262 /// <para></para>
263 /// </param>
264 /// <returns>
265 /// <para>The bool</para>
266 /// <para></para>
267 /// </returns>
268 [MethodImpl(MethodImplOptions.AggressiveInlining)]
269 protected override bool FirstIsToTheLeftOfSecond(TLinkAddress first, TLinkAddress second)
270 {
271     ref var firstLink = ref GetLinkDataPartReference(first);
272     ref var secondLink = ref GetLinkDataPartReference(second);
273     return FirstIsToTheLeftOfSecond(firstLink.Source, firstLink.Target,
274         ↪ secondLink.Source, secondLink.Target);
275 }
276
277 /// <summary>
278 /// <para>
279 /// Determines whether this instance first is to the right of second.
280 /// </para>
281 /// <para></para>
282 /// </summary>
283 /// <param name="first">
284 /// <para>The first.</para>
285 /// <para></para>
286 /// </param>
287 /// <param name="second">
288 /// <para>The second.</para>
289 /// <para></para>
290 /// </param>
291 /// <returns>
292 /// <para>The bool</para>
293 /// <para></para>
294 /// </returns>
295 [MethodImpl(MethodImplOptions.AggressiveInlining)]
296 protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
297     ↪ second)
298 {
299     ref var firstLink = ref GetLinkDataPartReference(first);
300     ref var secondLink = ref GetLinkDataPartReference(second);
301     return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
302         ↪ secondLink.Source, secondLink.Target);
303 }
304
305 /// <summary>
306 /// <para>
307 /// The zero.
308 /// </para>
309 /// <para></para>
310 /// </summary>
311 public TLinkAddress this[TLinkAddress index]
312 {
313     [MethodImpl(MethodImplOptions.AggressiveInlining)]
314     get
315     {
316         var root = GetTreeRoot();
317         if (GreaterOrEqualThan(index, GetSize(root)))
318         {
319             return Zero;
320         }
321         while (!EqualToZero(root))
322         {
323             var left = GetLeftOrDefault(root);
324             var leftSize = GetSizeOrZero(left);

```

```

322         if (LessThan(index, leftSize))
323         {
324             root = left;
325             continue;
326         }
327         if (AreEqual(index, leftSize))
328         {
329             return root;
330         }
331         root = GetRightOrDefault(root);
332         index = Subtract(index, Increment(leftSize));
333     }
334     return Zero; // TODO: Impossible situation exception (only if tree structure
335                 ↳ broken)
336 }
337
338 /// <summary>
339 /// Выполняет поиск и возвращает индекс связи с указанными Source (началом) и Target
340 ↳ (концом).
341 /// </summary>
342 /// <param name="source">Индекс связи, которая является началом на искомой связи.</param>
343 /// <param name="target">Индекс связи, которая является концом на искомой связи.</param>
344 /// <returns>Индекс искомой связи.</returns>
345 [MethodImpl(MethodImplOptions.AggressiveInlining)]
346 public TLinkAddress Search(TLinkAddress source, TLinkAddress target)
347 {
348     var root = GetTreeRoot();
349     while (!EqualToZero(root))
350     {
351         ref var rootLink = ref GetLinkDataPartReference(root);
352         var rootSource = rootLink.Source;
353         var rootTarget = rootLink.Target;
354         if (FirstIsToTheLeftOfSecond(source, target, rootSource, rootTarget)) //
355             ↳ node.Key < root.Key
356         {
357             root = GetLeftOrDefault(root);
358         }
359         else if (FirstIsToTheRightOfSecond(source, target, rootSource, rootTarget)) //
360             ↳ node.Key > root.Key
361         {
362             root = GetRightOrDefault(root);
363         }
364         else // node.Key == root.Key
365         {
366             return root;
367         }
368     }
369     return Zero;
370 }
371
372 // TODO: Return indices range instead of references count
373 /// <summary>
374 /// <para>
375 /// Counts the usages using the specified link.
376 /// </para>
377 /// <para></para>
378 /// </summary>
379 /// <param name="link">
380 /// <para>The link.</para>
381 /// <para></para>
382 /// </param>
383 /// <returns>
384 /// <para>The link</para>
385 /// <para></para>
386 /// </returns>
387 [MethodImpl(MethodImplOptions.AggressiveInlining)]
388 public TLinkAddress CountUsages(TLinkAddress link)
389 {
390     var root = GetTreeRoot();
391     var total = GetSize(root);
392     var totalRightIgnore = Zero;
393     while (!EqualToZero(root))
394     {
395         var @base = GetBasePartValue(root);
396         if (LessOrEqualThan(@base, link))
397         {
398             root = GetRightOrDefault(root);
399         }
400     }
401     return total - totalRightIgnore;
402 }

```

```

396     }
397     else
398     {
399         totalRightIgnore = Add(totalRightIgnore, Increment(GetRightSize(root)));
400         root = GetLeftOrDefault(root);
401     }
402 }
403 root = GetTreeRoot();
404 var totalLeftIgnore = Zero;
405 while (!EqualToZero(root))
406 {
407     var @base = GetBasePartValue(root);
408     if (GreaterOrEqualThan(@base, link))
409     {
410         root = GetLeftOrDefault(root);
411     }
412     else
413     {
414         totalLeftIgnore = Add(totalLeftIgnore, Increment(GetLeftSize(root)));
415         root = GetRightOrDefault(root);
416     }
417 }
418 return Subtract(Subtract(total, totalRightIgnore), totalLeftIgnore);
419 }
420
421 /// <summary>
422 /// <para>
423 /// Eaches the usage using the specified base.
424 /// </para>
425 /// <para></para>
426 /// </summary>
427 /// <param name="@base">
428 /// <para>The base.</para>
429 /// <para></para>
430 /// </param>
431 /// <param name="handler">
432 /// <para>The handler.</para>
433 /// <para></para>
434 /// </param>
435 /// <returns>
436 /// <para>The link</para>
437 /// <para></para>
438 /// </returns>
439 [MethodImpl(MethodImplOptions.AggressiveInlining)]
440 public TLinkAddress EachUsage(TLinkAddress @base, ReadHandler<TLinkAddress>? handler) =>
441     ↳ EachUsageCore(@base, GetTreeRoot(), handler);
442
443 // TODO: 1. Move target, handler to separate object. 2. Use stack or walker 3. Use
444 ↳ low-level MSIL stack.
445 [MethodImpl(MethodImplOptions.AggressiveInlining)]
446 private TLinkAddress EachUsageCore(TLinkAddress @base, TLinkAddress link,
447     ↳ ReadHandler<TLinkAddress>? handler)
448 {
449     var @continue = Continue;
450     if (EqualToZero(link))
451     {
452         return @continue;
453     }
454     var linkBasePart = GetBasePartValue(link);
455     var @break = Break;
456     if (GreaterThan(linkBasePart, @base))
457     {
458         if (AreEqual(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))
459         {
460             return @break;
461         }
462     }
463     else if (LessThan(linkBasePart, @base))
464     {
465         if (AreEqual(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
466         {
467             return @break;
468         }
469     }
470     else //if (linkBasePart == @base)
471     {
472         if (AreEqual(handler(GetLinkValues(link)), @break))
473         {

```



```

471         return @break;
472     }
473     if (AreEqual(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))
474     {
475         return @break;
476     }
477     if (AreEqual(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
478     {
479         return @break;
480     }
481 }
482 return @continue;
483 }
484
485 /// <summary>
486 /// <para>
487 /// Prints the node value using the specified node.
488 /// </para>
489 /// <para></para>
490 /// </summary>
491 /// <param name="node">
492 /// <para>The node.</para>
493 /// <para></para>
494 /// </param>
495 /// <param name="sb">
496 /// <para>The sb.</para>
497 /// <para></para>
498 /// </param>
499 [MethodImpl(MethodImplOptions.AggressiveInlining)]
500 protected override void PrintNodeValue(TLinkAddress node, StringBuilder sb)
501 {
502     ref var link = ref GetLinkDataPartReference(node);
503     sb.Append(' ');
504     sb.Append(link.Source);
505     sb.Append(' - ');
506     sb.Append(' > ');
507     sb.Append(link.Target);
508 }
509 }
510 }

```

1.33 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksSizeBalancedTreeMethodsBase.cs

```

1 using System;
2 using System.Text;
3 using System.Collections.Generic;
4 using System.Runtime.CompilerServices;
5 using Platform.Collections.Methods.Trees;
6 using Platform.Converters;
7 using Platform.Delegates;
8 using static System.Runtime.CompilerServices.Unsafe;
9
10 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
11
12 namespace Platform.Data.Doublets.Memory.Split.Generic
13 {
14     /// <summary>
15     /// <para>
16     /// Represents the external links size balanced tree methods base.
17     /// </para>
18     /// <para></para>
19     /// </summary>
20     /// <seealso cref="SizeBalancedTreeMethods{TLinkAddress}"/>
21     /// <seealso cref="ILinksTreeMethods{TLinkAddress}"/>
22     public unsafe abstract class ExternalLinksSizeBalancedTreeMethodsBase<TLinkAddress> :
23     ↪ SizeBalancedTreeMethods<TLinkAddress>, ILinksTreeMethods<TLinkAddress>
24     {
25         private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
26         ↪ = UncheckedConverter<TLinkAddress, long>.Default;
27
28         /// <summary>
29         /// <para>
30         /// The break.
31         /// </para>
32         /// <para></para>
33         /// </summary>
34         protected readonly TLinkAddress Break;
35         /// <summary>
36         /// <para>
37         /// The continue.

```

```

36    /// </para>
37    /// <para></para>
38    /// </summary>
39    protected readonly TLinkAddress Continue;
40    /// <summary>
41    /// <para>
42    /// The links data parts.
43    /// </para>
44    /// <para></para>
45    /// </summary>
46    protected readonly byte* LinksDataParts;
47    /// <summary>
48    /// <para>
49    /// The links index parts.
50    /// </para>
51    /// <para></para>
52    /// </summary>
53    protected readonly byte* LinksIndexParts;
54    /// <summary>
55    /// <para>
56    /// The header.
57    /// </para>
58    /// <para></para>
59    /// </summary>
60    protected readonly byte* Header;
61
62    /// <summary>
63    /// <para>
64    /// Initializes a new <see cref="ExternalLinksSizeBalancedTreeMethodsBase"/> instance.
65    /// </para>
66    /// <para></para>
67    /// </summary>
68    /// <param name="constants">
69    /// <para>A constants.</para>
70    /// <para></para>
71    /// </param>
72    /// <param name="linksDataParts">
73    /// <para>A links data parts.</para>
74    /// <para></para>
75    /// </param>
76    /// <param name="linksIndexParts">
77    /// <para>A links index parts.</para>
78    /// <para></para>
79    /// </param>
80    /// <param name="header">
81    /// <para>A header.</para>
82    /// <para></para>
83    /// </param>
84    [MethodImpl(MethodImplOptions.AggressiveInlining)]
85    protected ExternalLinksSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress>
86    ↪ constants, byte* linksDataParts, byte* linksIndexParts, byte* header)
87    {
88        LinksDataParts = linksDataParts;
89        LinksIndexParts = linksIndexParts;
90        Header = header;
91        Break = constants.Break;
92        Continue = constants.Continue;
93    }
94    /// <summary>
95    /// <para>
96    /// Gets the tree root.
97    /// </para>
98    /// <para></para>
99    /// </summary>
100    /// <returns>
101    /// <para>The link</para>
102    /// <para></para>
103    /// </returns>
104    [MethodImpl(MethodImplOptions.AggressiveInlining)]
105    protected abstract TLinkAddress GetTreeRoot();
106
107    /// <summary>
108    /// <para>
109    /// Gets the base part value using the specified link.
110    /// </para>
111    /// <para></para>
112    /// </summary>

```

```

113     /// <param name="link">
114     /// <para>The link.</para>
115     /// <para></para>
116     /// </param>
117     /// <returns>
118     /// <para>The link</para>
119     /// <para></para>
120     /// </returns>
121     [MethodImpl(MethodImplOptions.AggressiveInlining)]
122     protected abstract TLinkAddress GetBasePartValue(TLinkAddress link);
123
124     /// <summary>
125     /// <para>
126     /// Determines whether this instance first is to the right of second.
127     /// </para>
128     /// <para></para>
129     /// </summary>
130     /// <param name="source">
131     /// <para>The source.</para>
132     /// <para></para>
133     /// </param>
134     /// <param name="target">
135     /// <para>The target.</para>
136     /// <para></para>
137     /// </param>
138     /// <param name="rootSource">
139     /// <para>The root source.</para>
140     /// <para></para>
141     /// </param>
142     /// <param name="rootTarget">
143     /// <para>The root target.</para>
144     /// <para></para>
145     /// </param>
146     /// <returns>
147     /// <para>The bool</para>
148     /// <para></para>
149     /// </returns>
150     [MethodImpl(MethodImplOptions.AggressiveInlining)]
151     protected abstract bool FirstIsToTheRightOfSecond(TLinkAddress source, TLinkAddress
        ↪ target, TLinkAddress rootSource, TLinkAddress rootTarget);
152
153     /// <summary>
154     /// <para>
155     /// Determines whether this instance first is to the left of second.
156     /// </para>
157     /// <para></para>
158     /// </summary>
159     /// <param name="source">
160     /// <para>The source.</para>
161     /// <para></para>
162     /// </param>
163     /// <param name="target">
164     /// <para>The target.</para>
165     /// <para></para>
166     /// </param>
167     /// <param name="rootSource">
168     /// <para>The root source.</para>
169     /// <para></para>
170     /// </param>
171     /// <param name="rootTarget">
172     /// <para>The root target.</para>
173     /// <para></para>
174     /// </param>
175     /// <returns>
176     /// <para>The bool</para>
177     /// <para></para>
178     /// </returns>
179     [MethodImpl(MethodImplOptions.AggressiveInlining)]
180     protected abstract bool FirstIsToTheLeftOfSecond(TLinkAddress source, TLinkAddress
        ↪ target, TLinkAddress rootSource, TLinkAddress rootTarget);
181
182     /// <summary>
183     /// <para>
184     /// Gets the header reference.
185     /// </para>
186     /// <para></para>
187     /// </summary>
188     /// <returns>

```

```

189    /// <para>A ref links header of t link</para>
190    /// <para></para>
191    /// </returns>
192    [MethodImpl(MethodImplOptions.AggressiveInlining)]
193    protected virtual ref LinksHeader<TLinkAddress> GetHeaderReference() => ref
    ↪ AsRef<LinksHeader<TLinkAddress>>(Header);

194
195    /// <summary>
196    /// <para>
197    /// Gets the link data part reference using the specified link.
198    /// </para>
199    /// <para></para>
200    /// </summary>
201    /// <param name="link">
202    /// <para>The link.</para>
203    /// <para></para>
204    /// </param>
205    /// <returns>
206    /// <para>A ref raw link data part of t link</para>
207    /// <para></para>
208    /// </returns>
209    [MethodImpl(MethodImplOptions.AggressiveInlining)]
210    protected virtual ref RawLinkDataPart<TLinkAddress>
    ↪ GetLinkDataPartReference(TLinkAddress link) => ref
    ↪ AsRef<RawLinkDataPart<TLinkAddress>>(LinksDataParts +
    ↪ (RawLinkDataPart<TLinkAddress>.SizeInBytes *
    ↪ _addressToInt64Converter.Convert(link)));

211
212    /// <summary>
213    /// <para>
214    /// Gets the link index part reference using the specified link.
215    /// </para>
216    /// <para></para>
217    /// </summary>
218    /// <param name="link">
219    /// <para>The link.</para>
220    /// <para></para>
221    /// </param>
222    /// <returns>
223    /// <para>A ref raw link index part of t link</para>
224    /// <para></para>
225    /// </returns>
226    [MethodImpl(MethodImplOptions.AggressiveInlining)]
227    protected virtual ref RawLinkIndexPart<TLinkAddress>
    ↪ GetLinkIndexPartReference(TLinkAddress link) => ref
    ↪ AsRef<RawLinkIndexPart<TLinkAddress>>(LinksIndexParts +
    ↪ (RawLinkIndexPart<TLinkAddress>.SizeInBytes *
    ↪ _addressToInt64Converter.Convert(link)));

228
229    /// <summary>
230    /// <para>
231    /// Gets the link values using the specified link index.
232    /// </para>
233    /// <para></para>
234    /// </summary>
235    /// <param name="linkIndex">
236    /// <para>The link index.</para>
237    /// <para></para>
238    /// </param>
239    /// <returns>
240    /// <para>A list of t link</para>
241    /// <para></para>
242    /// </returns>
243    [MethodImpl(MethodImplOptions.AggressiveInlining)]
244    protected virtual IList<TLinkAddress>? GetLinkValues(TLinkAddress linkIndex)
245    {
246        ref var link = ref GetLinkDataPartReference(linkIndex);
247        return new Link<TLinkAddress>(linkIndex, link.Source, link.Target);
248    }

249
250    /// <summary>
251    /// <para>
252    /// Determines whether this instance first is to the left of second.
253    /// </para>
254    /// <para></para>
255    /// </summary>
256    /// <param name="first">
257    /// <para>The first.</para>

```

```

258     /// <para></para>
259     /// </param>
260     /// <param name="second">
261     /// <para>The second.</para>
262     /// <para></para>
263     /// </param>
264     /// <returns>
265     /// <para>The bool</para>
266     /// <para></para>
267     /// </returns>
268     [MethodImpl(MethodImplOptions.AggressiveInlining)]
269     protected override bool FirstIsToLeftOfSecond(TLinkAddress first, TLinkAddress second)
270     {
271         ref var firstLink = ref GetLinkDataPartReference(first);
272         ref var secondLink = ref GetLinkDataPartReference(second);
273         return FirstIsToLeftOfSecond(firstLink.Source, firstLink.Target,
274             ↪ secondLink.Source, secondLink.Target);
275     }
276     /// <summary>
277     /// <para>
278     /// Determines whether this instance first is to the right of second.
279     /// </para>
280     /// <para></para>
281     /// </summary>
282     /// <param name="first">
283     /// <para>The first.</para>
284     /// <para></para>
285     /// </param>
286     /// <param name="second">
287     /// <para>The second.</para>
288     /// <para></para>
289     /// </param>
290     /// <returns>
291     /// <para>The bool</para>
292     /// <para></para>
293     /// </returns>
294     [MethodImpl(MethodImplOptions.AggressiveInlining)]
295     protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
296     ↪ second)
297     {
298         ref var firstLink = ref GetLinkDataPartReference(first);
299         ref var secondLink = ref GetLinkDataPartReference(second);
300         return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
301             ↪ secondLink.Source, secondLink.Target);
302     }
303     /// <summary>
304     /// <para>
305     /// The zero.
306     /// </para>
307     /// <para></para>
308     /// </summary>
309     public TLinkAddress this[TLinkAddress index]
310     {
311         [MethodImpl(MethodImplOptions.AggressiveInlining)]
312         get
313         {
314             var root = GetTreeRoot();
315             if (GreaterOrEqualThan(index, GetSize(root)))
316             {
317                 return Zero;
318             }
319             while (!EqualToZero(root))
320             {
321                 var left = GetLeftOrDefault(root);
322                 var leftSize = GetSizeOrZero(left);
323                 if (LessThan(index, leftSize))
324                 {
325                     root = left;
326                     continue;
327                 }
328                 if (AreEqual(index, leftSize))
329                 {
330                     return root;
331                 }
332                 root = GetRightOrDefault(root);
333                 index = Subtract(index, Increment(leftSize));

```

```

333     }
334     return Zero; // TODO: Impossible situation exception (only if tree structure
    ↪ broken)
335 }
336 }
337
338 /// <summary>
339 /// Выполняет поиск и возвращает индекс связи с указанными Source (началом) и Target
    ↪ (концом).
340 /// </summary>
341 /// <param name="source">Индекс связи, которая является началом на искомой связи.</param>
342 /// <param name="target">Индекс связи, которая является концом на искомой связи.</param>
343 /// <returns>Индекс искомой связи.</returns>
344 [MethodImpl(MethodImplOptions.AggressiveInlining)]
345 public TLinkAddress Search(TLinkAddress source, TLinkAddress target)
346 {
347     var root = GetTreeRoot();
348     while (!EqualToZero(root))
349     {
350         ref var rootLink = ref GetLinkDataPartReference(root);
351         var rootSource = rootLink.Source;
352         var rootTarget = rootLink.Target;
353         if (FirstIsToTheLeftOfSecond(source, target, rootSource, rootTarget)) //
            ↪ node.Key < root.Key
354         {
355             root = GetLeftOrDefault(root);
356         }
357         else if (FirstIsToTheRightOfSecond(source, target, rootSource, rootTarget)) //
            ↪ node.Key > root.Key
358         {
359             root = GetRightOrDefault(root);
360         }
361         else // node.Key == root.Key
362         {
363             return root;
364         }
365     }
366     return Zero;
367 }
368
369 // TODO: Return indices range instead of references count
370 /// <summary>
371 /// <para>
372 /// Counts the usages using the specified link.
373 /// </para>
374 /// <para></para>
375 /// </summary>
376 /// <param name="link">
377 /// <para>The link.</para>
378 /// <para></para>
379 /// </param>
380 /// <returns>
381 /// <para>The link</para>
382 /// <para></para>
383 /// </returns>
384 [MethodImpl(MethodImplOptions.AggressiveInlining)]
385 public TLinkAddress CountUsages(TLinkAddress link)
386 {
387     var root = GetTreeRoot();
388     var total = GetSize(root);
389     var totalRightIgnore = Zero;
390     while (!EqualToZero(root))
391     {
392         var @base = GetBasePartValue(root);
393         if (LessOrEqualThan(@base, link))
394         {
395             root = GetRightOrDefault(root);
396         }
397         else
398         {
399             totalRightIgnore = Add(totalRightIgnore, Increment(GetRightSize(root)));
400             root = GetLeftOrDefault(root);
401         }
402     }
403     root = GetTreeRoot();
404     var totalLeftIgnore = Zero;
405     while (!EqualToZero(root))
406     {

```

```

407     var @base = GetBasePartValue(root);
408     if (GreaterOrEqualThan(@base, link))
409     {
410         root = GetLeftOrDefault(root);
411     }
412     else
413     {
414         totalLeftIgnore = Add(totalLeftIgnore, Increment(GetLeftSize(root)));
415         root = GetRightOrDefault(root);
416     }
417 }
418 return Subtract(Subtract(total, totalRightIgnore), totalLeftIgnore);
419 }
420
421 /// <summary>
422 /// <para>
423 /// Eaches the usage using the specified base.
424 /// </para>
425 /// <para></para>
426 /// </summary>
427 /// <param name="@base">
428 /// <para>The base.</para>
429 /// <para></para>
430 /// </param>
431 /// <param name="handler">
432 /// <para>The handler.</para>
433 /// <para></para>
434 /// </param>
435 /// <returns>
436 /// <para>The link</para>
437 /// <para></para>
438 /// </returns>
439 [MethodImpl(MethodImplOptions.AggressiveInlining)]
440 public TLinkAddress EachUsage(TLinkAddress @base, ReadHandler<TLinkAddress>? handler) =>
441     ↳ EachUsageCore(@base, GetTreeRoot(), handler);
442
443 // TODO: 1. Move target, handler to separate object. 2. Use stack or walker 3. Use
444 ↳ low-level MSIL stack.
445 [MethodImpl(MethodImplOptions.AggressiveInlining)]
446 private TLinkAddress EachUsageCore(TLinkAddress @base, TLinkAddress link,
447     ↳ ReadHandler<TLinkAddress>? handler)
448 {
449     var @continue = Continue;
450     if (EqualToZero(link))
451     {
452         return @continue;
453     }
454     var linkBasePart = GetBasePartValue(link);
455     var @break = Break;
456     if (GreaterThan(linkBasePart, @base))
457     {
458         if (AreEqual(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))
459         {
460             return @break;
461         }
462     }
463     else if (LessThan(linkBasePart, @base))
464     {
465         if (AreEqual(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
466         {
467             return @break;
468         }
469     }
470     else //if (linkBasePart == @base)
471     {
472         if (AreEqual(handler(GetLinkValues(link)), @break))
473         {
474             return @break;
475         }
476         if (AreEqual(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))
477         {
478             return @break;
479         }
480         if (AreEqual(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
481         {
482             return @break;
483         }
484     }
485 }

```

```

482         return @continue;
483     }
484
485     /// <summary>
486     /// <para>
487     /// Prints the node value using the specified node.
488     /// </para>
489     /// <para></para>
490     /// </summary>
491     /// <param name="node">
492     /// <para>The node.</para>
493     /// <para></para>
494     /// </param>
495     /// <param name="sb">
496     /// <para>The sb.</para>
497     /// <para></para>
498     /// </param>
499     [MethodImpl(MethodImplOptions.AggressiveInlining)]
500     protected override void PrintNodeValue(TLinkAddress node, StringBuilder sb)
501     {
502         ref var link = ref GetLinkDataPartReference(node);
503         sb.Append(' ');
504         sb.Append(link.Source);
505         sb.Append('-');
506         sb.Append('>');
507         sb.Append(link.Target);
508     }
509 }
510 }

```

1.34 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksSourcesRecursionlessSizeBalancedTree

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.Split.Generic
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the external links sources recursionless size balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="ExternalLinksRecursionlessSizeBalancedTreeMethodsBase{TLinkAddress}"/>
14     public unsafe class ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods<TLinkAddress> :
15         ↪ ExternalLinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress>
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see
20         ↪ cref="ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods"/> instance.
21         /// </para>
22         /// <para></para>
23         /// </summary>
24         /// <param name="constants">
25         /// <para>A constants.</para>
26         /// <para></para>
27         /// </param>
28         /// <param name="linksDataParts">
29         /// <para>A links data parts.</para>
30         /// <para></para>
31         /// </param>
32         /// <param name="linksIndexParts">
33         /// <para>A links index parts.</para>
34         /// <para></para>
35         /// </param>
36         /// <param name="header">
37         /// <para>A header.</para>
38         /// <para></para>
39         /// </param>
40         [MethodImpl(MethodImplOptions.AggressiveInlining)]
41         public ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddr_
42         ↪ ess> constants, byte* linksDataParts, byte* linksIndexParts, byte* header) :
43         ↪ base(constants, linksDataParts, linksIndexParts, header) { }
44
45         /// <summary>
46         /// <para>
47         /// Gets the left reference using the specified node.

```



```

44    /// </para>
45    /// <para></para>
46    /// </summary>
47    /// <param name="node">
48    /// <para>The node.</para>
49    /// <para></para>
50    /// </param>
51    /// <returns>
52    /// <para>The ref link</para>
53    /// <para></para>
54    /// </returns>
55    [MethodImpl(MethodImplOptions.AggressiveInlining)]
56    protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪ GetLinkIndexPartReference(node).LeftAsSource;

57
58    /// <summary>
59    /// <para>
60    /// Gets the right reference using the specified node.
61    /// </para>
62    /// <para></para>
63    /// </summary>
64    /// <param name="node">
65    /// <para>The node.</para>
66    /// <para></para>
67    /// </param>
68    /// <returns>
69    /// <para>The ref link</para>
70    /// <para></para>
71    /// </returns>
72    [MethodImpl(MethodImplOptions.AggressiveInlining)]
73    protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ GetLinkIndexPartReference(node).RightAsSource;

74
75    /// <summary>
76    /// <para>
77    /// Gets the left using the specified node.
78    /// </para>
79    /// <para></para>
80    /// </summary>
81    /// <param name="node">
82    /// <para>The node.</para>
83    /// <para></para>
84    /// </param>
85    /// <returns>
86    /// <para>The link</para>
87    /// <para></para>
88    /// </returns>
89    [MethodImpl(MethodImplOptions.AggressiveInlining)]
90    protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ GetLinkIndexPartReference(node).LeftAsSource;

91
92    /// <summary>
93    /// <para>
94    /// Gets the right using the specified node.
95    /// </para>
96    /// <para></para>
97    /// </summary>
98    /// <param name="node">
99    /// <para>The node.</para>
100    /// <para></para>
101    /// </param>
102    /// <returns>
103    /// <para>The link</para>
104    /// <para></para>
105    /// </returns>
106    [MethodImpl(MethodImplOptions.AggressiveInlining)]
107    protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↪ GetLinkIndexPartReference(node).RightAsSource;

108
109    /// <summary>
110    /// <para>
111    /// Sets the left using the specified node.
112    /// </para>
113    /// <para></para>
114    /// </summary>
115    /// <param name="node">
116    /// <para>The node.</para>
117    /// <para></para>

```

```

118     /// </param>
119     /// <param name="left">
120     /// <para>The left.</para>
121     /// <para></para>
122     /// </param>
123     [MethodImpl(MethodImplOptions.AggressiveInlining)]
124     protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
125         ↪ GetLinkIndexPartReference(node).LeftAsSource = left;
126
127     /// <summary>
128     /// <para>
129     /// Sets the right using the specified node.
130     /// </para>
131     /// <para></para>
132     /// </summary>
133     /// <param name="node">
134     /// <para>The node.</para>
135     /// <para></para>
136     /// </param>
137     /// <param name="right">
138     /// <para>The right.</para>
139     /// <para></para>
140     /// </param>
141     [MethodImpl(MethodImplOptions.AggressiveInlining)]
142     protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
143         ↪ GetLinkIndexPartReference(node).RightAsSource = right;
144
145     /// <summary>
146     /// <para>
147     /// Gets the size using the specified node.
148     /// </para>
149     /// <para></para>
150     /// </summary>
151     /// <param name="node">
152     /// <para>The node.</para>
153     /// <para></para>
154     /// </param>
155     /// <returns>
156     /// <para>The link</para>
157     /// <para></para>
158     /// </returns>
159     [MethodImpl(MethodImplOptions.AggressiveInlining)]
160     protected override TLinkAddress GetSize(TLinkAddress node) =>
161         ↪ GetLinkIndexPartReference(node).SizeAsSource;
162
163     /// <summary>
164     /// <para>
165     /// Sets the size using the specified node.
166     /// </para>
167     /// <para></para>
168     /// </summary>
169     /// <param name="node">
170     /// <para>The node.</para>
171     /// <para></para>
172     /// </param>
173     /// <param name="size">
174     /// <para>The size.</para>
175     /// <para></para>
176     /// </param>
177     [MethodImpl(MethodImplOptions.AggressiveInlining)]
178     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
179         ↪ GetLinkIndexPartReference(node).SizeAsSource = size;
180
181     /// <summary>
182     /// <para>
183     /// Gets the tree root.
184     /// </para>
185     /// <para></para>
186     /// </summary>
187     /// <returns>
188     /// <para>The link</para>
189     /// <para></para>
190     /// </returns>
191     [MethodImpl(MethodImplOptions.AggressiveInlining)]
192     protected override TLinkAddress GetTreeRoot() => GetHeaderReference().RootAsSource;

```

```

192     /// Gets the base part value using the specified link.
193     /// </para>
194     /// <para></para>
195     /// </summary>
196     /// <param name="link">
197     /// <para>The link.</para>
198     /// <para></para>
199     /// </param>
200     /// <returns>
201     /// <para>The link</para>
202     /// <para></para>
203     /// </returns>
204     [MethodImpl(MethodImplOptions.AggressiveInlining)]
205     protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
206         ↪ GetLinkDataPartReference(link).Source;
207
208     /// <summary>
209     /// <para>
210     /// Determines whether this instance first is to the left of second.
211     /// </para>
212     /// <para></para>
213     /// </summary>
214     /// <param name="firstSource">
215     /// <para>The first source.</para>
216     /// <para></para>
217     /// </param>
218     /// <param name="firstTarget">
219     /// <para>The first target.</para>
220     /// <para></para>
221     /// </param>
222     /// <param name="secondSource">
223     /// <para>The second source.</para>
224     /// <para></para>
225     /// </param>
226     /// <param name="secondTarget">
227     /// <para>The second target.</para>
228     /// <para></para>
229     /// </param>
230     /// <returns>
231     /// <para>The bool</para>
232     /// <para></para>
233     /// </returns>
234     [MethodImpl(MethodImplOptions.AggressiveInlining)]
235     protected override bool FirstIsToTheLeftOfSecond(TLinkAddress firstSource, TLinkAddress
236         ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
237         ↪ LessThan(firstSource, secondSource) || (AreEqual(firstSource, secondSource) &&
238         ↪ LessThan(firstTarget, secondTarget));
239
240     /// <summary>
241     /// <para>
242     /// Determines whether this instance first is to the right of second.
243     /// </para>
244     /// <para></para>
245     /// </summary>
246     /// <param name="firstSource">
247     /// <para>The first source.</para>
248     /// <para></para>
249     /// </param>
250     /// <param name="firstTarget">
251     /// <para>The first target.</para>
252     /// <para></para>
253     /// </param>
254     /// <param name="secondSource">
255     /// <para>The second source.</para>
256     /// <para></para>
257     /// </param>
258     /// <param name="secondTarget">
259     /// <para>The second target.</para>
260     /// <para></para>
261     /// </param>
262     /// <returns>
263     /// <para>The bool</para>
264     /// <para></para>
265     /// </returns>
266     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

263     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
    ↪ GreaterThan(firstSource, secondSource) || (AreEqual(firstSource, secondSource) &&
    ↪ GreaterThan(firstTarget, secondTarget));
264
265     /// <summary>
266     /// <para>
267     /// Clears the node using the specified node.
268     /// </para>
269     /// <para></para>
270     /// </summary>
271     /// <param name="node">
272     /// <para>The node.</para>
273     /// <para></para>
274     /// </param>
275     [MethodImpl(MethodImplOptions.AggressiveInlining)]
276     protected override void ClearNode(TLinkAddress node)
277     {
278         ref var link = ref GetLinkIndexPartReference(node);
279         link.LeftAsSource = Zero;
280         link.RightAsSource = Zero;
281         link.SizeAsSource = Zero;
282     }
283 }
284 }

```

1.35 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksSourcesSizeBalancedTreeMethods.cs

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.Split.Generic
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the external links sources size balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="ExternalLinksSizeBalancedTreeMethodsBase{TLinkAddress}"/>
14     public unsafe class ExternalLinksSourcesSizeBalancedTreeMethods<TLinkAddress> :
    ↪ ExternalLinksSizeBalancedTreeMethodsBase<TLinkAddress>
15     {
16         /// <summary>
17         /// <para>
18         /// Initializes a new <see cref="ExternalLinksSourcesSizeBalancedTreeMethods"/> instance.
19         /// </para>
20         /// <para></para>
21         /// </summary>
22         /// <param name="constants">
23         /// <para>A constants.</para>
24         /// <para></para>
25         /// </param>
26         /// <param name="linksDataParts">
27         /// <para>A links data parts.</para>
28         /// <para></para>
29         /// </param>
30         /// <param name="linksIndexParts">
31         /// <para>A links index parts.</para>
32         /// <para></para>
33         /// </param>
34         /// <param name="header">
35         /// <para>A header.</para>
36         /// <para></para>
37         /// </param>
38         [MethodImpl(MethodImplOptions.AggressiveInlining)]
39         public ExternalLinksSourcesSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
    ↪ constants, byte* linksDataParts, byte* linksIndexParts, byte* header) :
    ↪ base(constants, linksDataParts, linksIndexParts, header) { }
40
41         /// <summary>
42         /// <para>
43         /// Gets the left reference using the specified node.
44         /// </para>
45         /// <para></para>
46         /// </summary>
47         /// <param name="node">
48         /// <para>The node.</para>

```

```

49    /// <para></para>
50    /// </param>
51    /// <returns>
52    /// <para>The ref link</para>
53    /// <para></para>
54    /// </returns>
55    [MethodImpl(MethodImplOptions.AggressiveInlining)]
56    protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪ GetLinkIndexPartReference(node).LeftAsSource;
57
58    /// <summary>
59    /// <para>
60    /// Gets the right reference using the specified node.
61    /// </para>
62    /// <para></para>
63    /// </summary>
64    /// <param name="node">
65    /// <para>The node.</para>
66    /// <para></para>
67    /// </param>
68    /// <returns>
69    /// <para>The ref link</para>
70    /// <para></para>
71    /// </returns>
72    [MethodImpl(MethodImplOptions.AggressiveInlining)]
73    protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ GetLinkIndexPartReference(node).RightAsSource;
74
75    /// <summary>
76    /// <para>
77    /// Gets the left using the specified node.
78    /// </para>
79    /// <para></para>
80    /// </summary>
81    /// <param name="node">
82    /// <para>The node.</para>
83    /// <para></para>
84    /// </param>
85    /// <returns>
86    /// <para>The link</para>
87    /// <para></para>
88    /// </returns>
89    [MethodImpl(MethodImplOptions.AggressiveInlining)]
90    protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ GetLinkIndexPartReference(node).LeftAsSource;
91
92    /// <summary>
93    /// <para>
94    /// Gets the right using the specified node.
95    /// </para>
96    /// <para></para>
97    /// </summary>
98    /// <param name="node">
99    /// <para>The node.</para>
100    /// <para></para>
101    /// </param>
102    /// <returns>
103    /// <para>The link</para>
104    /// <para></para>
105    /// </returns>
106    [MethodImpl(MethodImplOptions.AggressiveInlining)]
107    protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↪ GetLinkIndexPartReference(node).RightAsSource;
108
109    /// <summary>
110    /// <para>
111    /// Sets the left using the specified node.
112    /// </para>
113    /// <para></para>
114    /// </summary>
115    /// <param name="node">
116    /// <para>The node.</para>
117    /// <para></para>
118    /// </param>
119    /// <param name="left">
120    /// <para>The left.</para>
121    /// <para></para>
122    /// </param>

```

```

123 [MethodImpl(MethodImplOptions.AggressiveInlining)]
124 protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
    ↳ GetLinkIndexPartReference(node).LeftAsSource = left;

125
126 /// <summary>
127 /// <para>
128 /// Sets the right using the specified node.
129 /// </para>
130 /// <para></para>
131 /// </summary>
132 /// <param name="node">
133 /// <para>The node.</para>
134 /// <para></para>
135 /// </param>
136 /// <param name="right">
137 /// <para>The right.</para>
138 /// <para></para>
139 /// </param>
140 [MethodImpl(MethodImplOptions.AggressiveInlining)]
141 protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
    ↳ GetLinkIndexPartReference(node).RightAsSource = right;

142
143 /// <summary>
144 /// <para>
145 /// Gets the size using the specified node.
146 /// </para>
147 /// <para></para>
148 /// </summary>
149 /// <param name="node">
150 /// <para>The node.</para>
151 /// <para></para>
152 /// </param>
153 /// <returns>
154 /// <para>The link</para>
155 /// <para></para>
156 /// </returns>
157 [MethodImpl(MethodImplOptions.AggressiveInlining)]
158 protected override TLinkAddress GetSize(TLinkAddress node) =>
    ↳ GetLinkIndexPartReference(node).SizeAsSource;

159
160 /// <summary>
161 /// <para>
162 /// Sets the size using the specified node.
163 /// </para>
164 /// <para></para>
165 /// </summary>
166 /// <param name="node">
167 /// <para>The node.</para>
168 /// <para></para>
169 /// </param>
170 /// <param name="size">
171 /// <para>The size.</para>
172 /// <para></para>
173 /// </param>
174 [MethodImpl(MethodImplOptions.AggressiveInlining)]
175 protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
    ↳ GetLinkIndexPartReference(node).SizeAsSource = size;

176
177 /// <summary>
178 /// <para>
179 /// Gets the tree root.
180 /// </para>
181 /// <para></para>
182 /// </summary>
183 /// <returns>
184 /// <para>The link</para>
185 /// <para></para>
186 /// </returns>
187 [MethodImpl(MethodImplOptions.AggressiveInlining)]
188 protected override TLinkAddress GetTreeRoot() => GetHeaderReference().RootAsSource;

189
190 /// <summary>
191 /// <para>
192 /// Gets the base part value using the specified link.
193 /// </para>
194 /// <para></para>
195 /// </summary>
196 /// <param name="link">

```

```

197    /// <para>The link.</para>
198    /// <para></para>
199    /// </param>
200    /// <returns>
201    /// <para>The link</para>
202    /// <para></para>
203    /// </returns>
204    [MethodImpl(MethodImplOptions.AggressiveInlining)]
205    protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
206        ↪ GetLinkDataPartReference(link).Source;
207
208    /// <summary>
209    /// <para>
210    /// Determines whether this instance first is to the left of second.
211    /// </para>
212    /// <para></para>
213    /// </summary>
214    /// <param name="firstSource">
215    /// <para>The first source.</para>
216    /// <para></para>
217    /// </param>
218    /// <param name="firstTarget">
219    /// <para>The first target.</para>
220    /// <para></para>
221    /// </param>
222    /// <param name="secondSource">
223    /// <para>The second source.</para>
224    /// <para></para>
225    /// </param>
226    /// <param name="secondTarget">
227    /// <para>The second target.</para>
228    /// <para></para>
229    /// </param>
230    /// <returns>
231    /// <para>The bool</para>
232    /// <para></para>
233    /// </returns>
234    [MethodImpl(MethodImplOptions.AggressiveInlining)]
235    protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
236        ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
237        ↪ LessThan(firstSource, secondSource) || (AreEqual(firstSource, secondSource) &&
238        ↪ LessThan(firstTarget, secondTarget));
239
240    /// <summary>
241    /// <para>
242    /// Determines whether this instance first is to the right of second.
243    /// </para>
244    /// <para></para>
245    /// </summary>
246    /// <param name="firstSource">
247    /// <para>The first source.</para>
248    /// <para></para>
249    /// </param>
250    /// <param name="firstTarget">
251    /// <para>The first target.</para>
252    /// <para></para>
253    /// </param>
254    /// <param name="secondSource">
255    /// <para>The second source.</para>
256    /// <para></para>
257    /// </param>
258    /// <param name="secondTarget">
259    /// <para>The second target.</para>
260    /// <para></para>
261    /// </param>
262    /// <returns>
263    /// <para>The bool</para>
264    /// <para></para>
265    /// </returns>
266    [MethodImpl(MethodImplOptions.AggressiveInlining)]
267    protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
268        ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
269        ↪ GreaterThan(firstSource, secondSource) || (AreEqual(firstSource, secondSource) &&
270        ↪ GreaterThan(firstTarget, secondTarget));
271
272    /// <summary>
273    /// <para>

```

```

267     /// Clears the node using the specified node.
268     /// </para>
269     /// <para></para>
270     /// </summary>
271     /// <param name="node">
272     /// <para>The node.</para>
273     /// <para></para>
274     /// </param>
275     [MethodImpl(MethodImplOptions.AggressiveInlining)]
276     protected override void ClearNode(TLinkAddress node)
277     {
278         ref var link = ref GetLinkIndexPartReference(node);
279         link.LeftAsSource = Zero;
280         link.RightAsSource = Zero;
281         link.SizeAsSource = Zero;
282     }
283 }
284 }

```

1.36 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksTargetsRecursionlessSizeBalancedTree

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.Split.Generic
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the external links targets recursionless size balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="ExternalLinksRecursionlessSizeBalancedTreeMethodsBase{TLinkAddress}"/>
14     public unsafe class ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods<TLinkAddress> :
15     ↪ ExternalLinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress>
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see
20         ↪ cref="ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods"/> instance.
21         /// </para>
22         /// <para></para>
23         /// </summary>
24         /// <param name="constants">
25         /// <para>A constants.</para>
26         /// <para></para>
27         /// </param>
28         /// <param name="linksDataParts">
29         /// <para>A links data parts.</para>
30         /// <para></para>
31         /// </param>
32         /// <param name="linksIndexParts">
33         /// <para>A links index parts.</para>
34         /// <para></para>
35         /// </param>
36         /// <param name="header">
37         /// <para>A header.</para>
38         /// <para></para>
39         /// </param>
40         [MethodImpl(MethodImplOptions.AggressiveInlining)]
41         public ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddr
42         ↪ ess> constants, byte* linksDataParts, byte* linksIndexParts, byte* header) :
43         ↪ base(constants, linksDataParts, linksIndexParts, header) { }
44
45         /// <summary>
46         /// <para>
47         /// Gets the left reference using the specified node.
48         /// </para>
49         /// <para></para>
50         /// </summary>
51         /// <param name="node">
52         /// <para>The node.</para>
53         /// <para></para>
54         /// </param>
55         /// <returns>
56         /// <para>The ref link</para>
57         /// <para></para>
58         /// </returns>

```



```

55 [MethodImpl(MethodImplOptions.AggressiveInlining)]
56 protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪ GetLinkIndexPartReference(node).LeftAsTarget;
57
58 /// <summary>
59 /// <para>
60 /// Gets the right reference using the specified node.
61 /// </para>
62 /// <para></para>
63 /// </summary>
64 /// <param name="node">
65 /// <para>The node.</para>
66 /// <para></para>
67 /// </param>
68 /// <returns>
69 /// <para>The ref link</para>
70 /// <para></para>
71 /// </returns>
72 [MethodImpl(MethodImplOptions.AggressiveInlining)]
73 protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ GetLinkIndexPartReference(node).RightAsTarget;
74
75 /// <summary>
76 /// <para>
77 /// Gets the left using the specified node.
78 /// </para>
79 /// <para></para>
80 /// </summary>
81 /// <param name="node">
82 /// <para>The node.</para>
83 /// <para></para>
84 /// </param>
85 /// <returns>
86 /// <para>The link</para>
87 /// <para></para>
88 /// </returns>
89 [MethodImpl(MethodImplOptions.AggressiveInlining)]
90 protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ GetLinkIndexPartReference(node).LeftAsTarget;
91
92 /// <summary>
93 /// <para>
94 /// Gets the right using the specified node.
95 /// </para>
96 /// <para></para>
97 /// </summary>
98 /// <param name="node">
99 /// <para>The node.</para>
100 /// <para></para>
101 /// </param>
102 /// <returns>
103 /// <para>The link</para>
104 /// <para></para>
105 /// </returns>
106 [MethodImpl(MethodImplOptions.AggressiveInlining)]
107 protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↪ GetLinkIndexPartReference(node).RightAsTarget;
108
109 /// <summary>
110 /// <para>
111 /// Sets the left using the specified node.
112 /// </para>
113 /// <para></para>
114 /// </summary>
115 /// <param name="node">
116 /// <para>The node.</para>
117 /// <para></para>
118 /// </param>
119 /// <param name="left">
120 /// <para>The left.</para>
121 /// <para></para>
122 /// </param>
123 [MethodImpl(MethodImplOptions.AggressiveInlining)]
124 protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
    ↪ GetLinkIndexPartReference(node).LeftAsTarget = left;
125
126 /// <summary>

```

```

127    /// <para>
128    /// Sets the right using the specified node.
129    /// </para>
130    /// <para></para>
131    /// </summary>
132    /// <param name="node">
133    /// <para>The node.</para>
134    /// <para></para>
135    /// </param>
136    /// <param name="right">
137    /// <para>The right.</para>
138    /// <para></para>
139    /// </param>
140    [MethodImpl(MethodImplOptions.AggressiveInlining)]
141    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
142        ↪ GetLinkIndexPartReference(node).RightAsTarget = right;
143
144    /// <summary>
145    /// <para>
146    /// Gets the size using the specified node.
147    /// </para>
148    /// </summary>
149    /// <param name="node">
150    /// <para>The node.</para>
151    /// <para></para>
152    /// </param>
153    /// <returns>
154    /// <para>The link</para>
155    /// <para></para>
156    /// </returns>
157    [MethodImpl(MethodImplOptions.AggressiveInlining)]
158    protected override TLinkAddress GetSize(TLinkAddress node) =>
159        ↪ GetLinkIndexPartReference(node).SizeAsTarget;
160
161    /// <summary>
162    /// <para>
163    /// Sets the size using the specified node.
164    /// </para>
165    /// <para></para>
166    /// </summary>
167    /// <param name="node">
168    /// <para>The node.</para>
169    /// <para></para>
170    /// </param>
171    /// <param name="size">
172    /// <para>The size.</para>
173    /// <para></para>
174    /// </param>
175    [MethodImpl(MethodImplOptions.AggressiveInlining)]
176    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
177        ↪ GetLinkIndexPartReference(node).SizeAsTarget = size;
178
179    /// <summary>
180    /// <para>
181    /// Gets the tree root.
182    /// </para>
183    /// <para></para>
184    /// </summary>
185    /// <returns>
186    /// <para>The link</para>
187    /// <para></para>
188    /// </returns>
189    [MethodImpl(MethodImplOptions.AggressiveInlining)]
190    protected override TLinkAddress GetTreeRoot() => GetHeaderReference().RootAsTarget;
191
192    /// <summary>
193    /// <para>
194    /// Gets the base part value using the specified link.
195    /// </para>
196    /// <para></para>
197    /// </summary>
198    /// <param name="link">
199    /// <para>The link.</para>
200    /// <para></para>
201    /// </param>
202    /// <returns>
203    /// <para>The link</para>

```

```

202    /// <para></para>
203    /// </returns>
204    [MethodImpl(MethodImplOptions.AggressiveInlining)]
205    protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
206        ↪ GetLinkDataPartReference(link).Target;
207
208    /// <summary>
209    /// <para>
210    /// Determines whether this instance first is to the left of second.
211    /// </para>
212    /// <para></para>
213    /// </summary>
214    /// <param name="firstSource">
215    /// <para>The first source.</para>
216    /// </param>
217    /// <param name="firstTarget">
218    /// <para>The first target.</para>
219    /// <para></para>
220    /// </param>
221    /// <param name="secondSource">
222    /// <para>The second source.</para>
223    /// <para></para>
224    /// </param>
225    /// <param name="secondTarget">
226    /// <para>The second target.</para>
227    /// <para></para>
228    /// </param>
229    /// <returns>
230    /// <para>The bool</para>
231    /// <para></para>
232    /// </returns>
233    [MethodImpl(MethodImplOptions.AggressiveInlining)]
234    protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
235        ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
236        ↪ LessThan(firstTarget, secondTarget) || (AreEqual(firstTarget, secondTarget) &&
237        ↪ LessThan(firstSource, secondSource));
238
239    /// <summary>
240    /// <para>
241    /// Determines whether this instance first is to the right of second.
242    /// </para>
243    /// <para></para>
244    /// </summary>
245    /// <param name="firstSource">
246    /// <para>The first source.</para>
247    /// <para></para>
248    /// </param>
249    /// <param name="firstTarget">
250    /// <para>The first target.</para>
251    /// <para></para>
252    /// </param>
253    /// <param name="secondSource">
254    /// <para>The second source.</para>
255    /// <para></para>
256    /// </param>
257    /// <param name="secondTarget">
258    /// <para>The second target.</para>
259    /// <para></para>
260    /// </param>
261    /// <returns>
262    /// <para>The bool</para>
263    /// <para></para>
264    /// </returns>
265    [MethodImpl(MethodImplOptions.AggressiveInlining)]
266    protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
267        ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
268        ↪ GreaterThan(firstTarget, secondTarget) || (AreEqual(firstTarget, secondTarget) &&
269        ↪ GreaterThan(firstSource, secondSource));
270
271    /// <summary>
272    /// <para>
273    /// Clears the node using the specified node.
274    /// </para>
275    /// <para></para>
276    /// </summary>
277    /// <param name="node">

```

```

272     /// <para>The node.</para>
273     /// <para></para>
274     /// </param>
275     [MethodImpl(MethodImplOptions.AggressiveInlining)]
276     protected override void ClearNode(TLinkAddress node)
277     {
278         ref var link = ref GetLinkIndexPartReference(node);
279         link.LeftAsTarget = Zero;
280         link.RightAsTarget = Zero;
281         link.SizeAsTarget = Zero;
282     }
283 }
284 }

```

1.37 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksTargetsSizeBalancedTreeMethods.cs

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.Split.Generic
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the external links targets size balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="ExternalLinksSizeBalancedTreeMethodsBase{TLinkAddress}"/>
14     public unsafe class ExternalLinksTargetsSizeBalancedTreeMethods<TLinkAddress> :
15         ↪ ExternalLinksSizeBalancedTreeMethodsBase<TLinkAddress>
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see cref="ExternalLinksTargetsSizeBalancedTreeMethods"/> instance.
20         /// </para>
21         /// <para></para>
22         /// </summary>
23         /// <param name="constants">
24         /// <para>A constants.</para>
25         /// <para></para>
26         /// </param>
27         /// <param name="linksDataParts">
28         /// <para>A links data parts.</para>
29         /// <para></para>
30         /// </param>
31         /// <param name="linksIndexParts">
32         /// <para>A links index parts.</para>
33         /// <para></para>
34         /// </param>
35         /// <param name="header">
36         /// <para>A header.</para>
37         /// <para></para>
38         /// </param>
39         [MethodImpl(MethodImplOptions.AggressiveInlining)]
40         public ExternalLinksTargetsSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
41             ↪ constants, byte* linksDataParts, byte* linksIndexParts, byte* header) :
42             ↪ base(constants, linksDataParts, linksIndexParts, header) { }
43
44         /// <summary>
45         /// <para>
46         /// Gets the left reference using the specified node.
47         /// </para>
48         /// <para></para>
49         /// </summary>
50         /// <param name="node">
51         /// <para>The node.</para>
52         /// <para></para>
53         /// </param>
54         /// <returns>
55         /// <para>The ref link</para>
56         /// <para></para>
57         /// </returns>
58         [MethodImpl(MethodImplOptions.AggressiveInlining)]
59         protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
60             ↪ GetLinkIndexPartReference(node).LeftAsTarget;
61
62         /// <summary>
63         /// <para>

```

```

60     /// Gets the right reference using the specified node.
61     /// </para>
62     /// <para></para>
63     /// </summary>
64     /// <param name="node">
65     /// <para>The node.</para>
66     /// <para></para>
67     /// </param>
68     /// <returns>
69     /// <para>The ref link</para>
70     /// <para></para>
71     /// </returns>
72     [MethodImpl(MethodImplOptions.AggressiveInlining)]
73     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
74     ↪ GetLinkIndexPartReference(node).RightAsTarget;
75
76     /// <summary>
77     /// <para>
78     /// Gets the left using the specified node.
79     /// </para>
80     /// <para></para>
81     /// </summary>
82     /// <param name="node">
83     /// <para>The node.</para>
84     /// <para></para>
85     /// </param>
86     /// <returns>
87     /// <para>The link</para>
88     /// <para></para>
89     /// </returns>
90     [MethodImpl(MethodImplOptions.AggressiveInlining)]
91     protected override TLinkAddress GetLeft(TLinkAddress node) =>
92     ↪ GetLinkIndexPartReference(node).LeftAsTarget;
93
94     /// <summary>
95     /// <para>
96     /// Gets the right using the specified node.
97     /// </para>
98     /// <para></para>
99     /// </summary>
100    /// <param name="node">
101    /// <para>The node.</para>
102    /// <para></para>
103    /// </param>
104    /// <returns>
105    /// <para>The link</para>
106    /// <para></para>
107    /// </returns>
108    [MethodImpl(MethodImplOptions.AggressiveInlining)]
109    protected override TLinkAddress GetRight(TLinkAddress node) =>
110    ↪ GetLinkIndexPartReference(node).RightAsTarget;
111
112    /// <summary>
113    /// <para>
114    /// Sets the left using the specified node.
115    /// </para>
116    /// <para></para>
117    /// </summary>
118    /// <param name="node">
119    /// <para>The node.</para>
120    /// <para></para>
121    /// </param>
122    /// <param name="left">
123    /// <para>The left.</para>
124    /// <para></para>
125    /// </param>
126    [MethodImpl(MethodImplOptions.AggressiveInlining)]
127    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
128    ↪ GetLinkIndexPartReference(node).LeftAsTarget = left;
129
130    /// <summary>
131    /// <para>
132    /// Sets the right using the specified node.
133    /// </para>
134    /// <para></para>
135    /// </summary>
136    /// <param name="node">
137    /// <para>The node.</para>

```

```

134    /// <para></para>
135    /// </param>
136    /// <param name="right">
137    /// <para>The right.</para>
138    /// <para></para>
139    /// </param>
140    [MethodImpl(MethodImplOptions.AggressiveInlining)]
141    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
142        ↪ GetLinkIndexPartReference(node).RightAsTarget = right;
143
144    /// <summary>
145    /// <para>
146    /// Gets the size using the specified node.
147    /// </para>
148    /// </summary>
149    /// <param name="node">
150    /// <para>The node.</para>
151    /// <para></para>
152    /// </param>
153    /// <returns>
154    /// <para>The link</para>
155    /// <para></para>
156    /// </returns>
157    [MethodImpl(MethodImplOptions.AggressiveInlining)]
158    protected override TLinkAddress GetSize(TLinkAddress node) =>
159        ↪ GetLinkIndexPartReference(node).SizeAsTarget;
160
161    /// <summary>
162    /// <para>
163    /// Sets the size using the specified node.
164    /// </para>
165    /// </summary>
166    /// <param name="node">
167    /// <para>The node.</para>
168    /// <para></para>
169    /// </param>
170    /// <param name="size">
171    /// <para>The size.</para>
172    /// <para></para>
173    /// </param>
174    [MethodImpl(MethodImplOptions.AggressiveInlining)]
175    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
176        ↪ GetLinkIndexPartReference(node).SizeAsTarget = size;
177
178    /// <summary>
179    /// <para>
180    /// Gets the tree root.
181    /// </para>
182    /// </summary>
183    /// <returns>
184    /// <para>The link</para>
185    /// <para></para>
186    /// </returns>
187    [MethodImpl(MethodImplOptions.AggressiveInlining)]
188    protected override TLinkAddress GetTreeRoot() => GetHeaderReference().RootAsTarget;
189
190    /// <summary>
191    /// <para>
192    /// Gets the base part value using the specified link.
193    /// </para>
194    /// </summary>
195    /// <param name="link">
196    /// <para>The link.</para>
197    /// <para></para>
198    /// </param>
199    /// <returns>
200    /// <para>The link</para>
201    /// <para></para>
202    /// </returns>
203    [MethodImpl(MethodImplOptions.AggressiveInlining)]
204    protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
205        ↪ GetLinkDataPartReference(link).Target;
206
207    /// <summary>

```

```

208    /// <para>
209    /// Determines whether this instance first is to the left of second.
210    /// </para>
211    /// <para></para>
212    /// </summary>
213    /// <param name="firstSource">
214    /// <para>The first source.</para>
215    /// <para></para>
216    /// </param>
217    /// <param name="firstTarget">
218    /// <para>The first target.</para>
219    /// <para></para>
220    /// </param>
221    /// <param name="secondSource">
222    /// <para>The second source.</para>
223    /// <para></para>
224    /// </param>
225    /// <param name="secondTarget">
226    /// <para>The second target.</para>
227    /// <para></para>
228    /// </param>
229    /// <returns>
230    /// <para>The bool</para>
231    /// <para></para>
232    /// </returns>
233    [MethodImpl(MethodImplOptions.AggressiveInlining)]
234    protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
    ↪ LessThan(firstTarget, secondTarget) || (AreEqual(firstTarget, secondTarget) &&
    ↪ LessThan(firstSource, secondSource));

235
236    /// <summary>
237    /// <para>
238    /// Determines whether this instance first is to the right of second.
239    /// </para>
240    /// <para></para>
241    /// </summary>
242    /// <param name="firstSource">
243    /// <para>The first source.</para>
244    /// <para></para>
245    /// </param>
246    /// <param name="firstTarget">
247    /// <para>The first target.</para>
248    /// <para></para>
249    /// </param>
250    /// <param name="secondSource">
251    /// <para>The second source.</para>
252    /// <para></para>
253    /// </param>
254    /// <param name="secondTarget">
255    /// <para>The second target.</para>
256    /// <para></para>
257    /// </param>
258    /// <returns>
259    /// <para>The bool</para>
260    /// <para></para>
261    /// </returns>
262    [MethodImpl(MethodImplOptions.AggressiveInlining)]
263    protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
    ↪ GreaterThan(firstTarget, secondTarget) || (AreEqual(firstTarget, secondTarget) &&
    ↪ GreaterThan(firstSource, secondSource));

264
265    /// <summary>
266    /// <para>
267    /// Clears the node using the specified node.
268    /// </para>
269    /// <para></para>
270    /// </summary>
271    /// <param name="node">
272    /// <para>The node.</para>
273    /// <para></para>
274    /// </param>
275    [MethodImpl(MethodImplOptions.AggressiveInlining)]
276    protected override void ClearNode(TLinkAddress node)
277    {
278        ref var link = ref GetLinkIndexPartReference(node);

```

```

279         link.LeftAsTarget = Zero;
280         link.RightAsTarget = Zero;
281         link.SizeAsTarget = Zero;
282     }
283 }
284 }

```

1.38 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksRecursionlessSizeBalancedTreeMethod

```

1  using System;
2  using System.Text;
3  using System.Collections.Generic;
4  using System.Runtime.CompilerServices;
5  using Platform.Collections.Methods.Trees;
6  using Platform.Converters;
7  using Platform.Delegates;
8  using static System.Runtime.CompilerServices.Unsafe;
9
10 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
11
12 namespace Platform.Data.Doublets.Memory.Split.Generic
13 {
14     /// <summary>
15     /// <para>
16     /// Represents the internal links recursionless size balanced tree methods base.
17     /// </para>
18     /// <para></para>
19     /// </summary>
20     /// <seealso cref="RecursionlessSizeBalancedTreeMethods{TLinkAddress}"/>
21     /// <seealso cref="ILinksTreeMethods{TLinkAddress}"/>
22     public unsafe abstract class
23     ↪ InternalLinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress> :
24     ↪ RecursionlessSizeBalancedTreeMethods<TLinkAddress>, ILinksTreeMethods<TLinkAddress>
25     {
26         private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
27         ↪ = UncheckedConverter<TLinkAddress, long>.Default;
28
29         /// <summary>
30         /// <para>
31         /// The break.
32         /// </para>
33         /// <para></para>
34         /// </summary>
35         protected readonly TLinkAddress Break;
36
37         /// <summary>
38         /// <para>
39         /// The continue.
40         /// </para>
41         /// <para></para>
42         /// </summary>
43         protected readonly TLinkAddress Continue;
44
45         /// <summary>
46         /// <para>
47         /// The links data parts.
48         /// </para>
49         /// <para></para>
50         /// </summary>
51         protected readonly byte* LinksDataParts;
52
53         /// <summary>
54         /// <para>
55         /// The links index parts.
56         /// </para>
57         /// <para></para>
58         /// </summary>
59         protected readonly byte* LinksIndexParts;
60
61         /// <summary>
62         /// <para>
63         /// The header.
64         /// </para>
65         /// <para></para>
66         /// </summary>
67         protected readonly byte* Header;
68
69         /// <summary>
70         /// <para>
71         /// Initializes a new <see
72         ↪ cref="InternalLinksRecursionlessSizeBalancedTreeMethodsBase"/> instance.
73         /// </para>
74         /// <para></para>
75         /// </summary>
76         /// <param name="constants">

```



```

69     /// <para>A constants.</para>
70     /// <para></para>
71     /// </param>
72     /// <param name="linksDataParts">
73     /// <para>A links data parts.</para>
74     /// <para></para>
75     /// </param>
76     /// <param name="linksIndexParts">
77     /// <para>A links index parts.</para>
78     /// <para></para>
79     /// </param>
80     /// <param name="header">
81     /// <para>A header.</para>
82     /// <para></para>
83     /// </param>
84     [MethodImpl(MethodImplOptions.AggressiveInlining)]
85     protected
86     ↪ InternalLinksRecursionlessSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress>
87     ↪ constants, byte* linksDataParts, byte* linksIndexParts, byte* header)
88     {
89         LinksDataParts = linksDataParts;
90         LinksIndexParts = linksIndexParts;
91         Header = header;
92         Break = constants.Break;
93         Continue = constants.Continue;
94     }
95
96     /// <summary>
97     /// <para>
98     /// Gets the tree root using the specified link.
99     /// </para>
100    /// <para></para>
101    /// </summary>
102    /// <param name="link">
103    /// <para>The link.</para>
104    /// <para></para>
105    /// </param>
106    /// <returns>
107    /// <para>The link</para>
108    /// <para></para>
109    /// </returns>
110    [MethodImpl(MethodImplOptions.AggressiveInlining)]
111    protected abstract TLinkAddress GetTreeRoot(TLinkAddress link);
112
113    /// <summary>
114    /// <para>
115    /// Gets the base part value using the specified link.
116    /// </para>
117    /// <para></para>
118    /// </summary>
119    /// <param name="link">
120    /// <para>The link.</para>
121    /// <para></para>
122    /// </param>
123    /// <returns>
124    /// <para>The link</para>
125    /// <para></para>
126    /// </returns>
127    [MethodImpl(MethodImplOptions.AggressiveInlining)]
128    protected abstract TLinkAddress GetBasePartValue(TLinkAddress link);
129
130    /// <summary>
131    /// <para>
132    /// Gets the key part value using the specified link.
133    /// </para>
134    /// <para></para>
135    /// </summary>
136    /// <param name="link">
137    /// <para>The link.</para>
138    /// <para></para>
139    /// </param>
140    /// <returns>
141    /// <para>The link</para>
142    /// <para></para>
143    /// </returns>
144    [MethodImpl(MethodImplOptions.AggressiveInlining)]
145    protected abstract TLinkAddress GetKeyPartValue(TLinkAddress link);

```

```

145     /// <summary>
146     /// <para>
147     /// Gets the link data part reference using the specified link.
148     /// </para>
149     /// <para></para>
150     /// </summary>
151     /// <param name="link">
152     /// <para>The link.</para>
153     /// <para></para>
154     /// </param>
155     /// <returns>
156     /// <para>A ref raw link data part of t link</para>
157     /// <para></para>
158     /// </returns>
159     [MethodImpl(MethodImplOptions.AggressiveInlining)]
160     protected virtual ref RawLinkDataPart<TLinkAddress>
161     ↪ GetLinkDataPartReference(TLinkAddress link) => ref
162     ↪ AsRef<RawLinkDataPart<TLinkAddress>>(LinksDataParts +
163     ↪ (RawLinkDataPart<TLinkAddress>.SizeInBytes *
164     ↪ _addressToInt64Converter.Convert(link)));
165
166     /// <summary>
167     /// <para>
168     /// Gets the link index part reference using the specified link.
169     /// </para>
170     /// <para></para>
171     /// </summary>
172     /// <param name="link">
173     /// <para>The link.</para>
174     /// <para></para>
175     /// </param>
176     /// <returns>
177     /// <para>A ref raw link index part of t link</para>
178     /// <para></para>
179     /// </returns>
180     [MethodImpl(MethodImplOptions.AggressiveInlining)]
181     protected virtual ref RawLinkIndexPart<TLinkAddress>
182     ↪ GetLinkIndexPartReference(TLinkAddress link) => ref
183     ↪ AsRef<RawLinkIndexPart<TLinkAddress>>(LinksIndexParts +
184     ↪ (RawLinkIndexPart<TLinkAddress>.SizeInBytes *
185     ↪ _addressToInt64Converter.Convert(link)));
186
187     /// <summary>
188     /// <para>
189     /// Determines whether this instance first is to the left of second.
190     /// </para>
191     /// <para></para>
192     /// </summary>
193     /// <param name="first">
194     /// <para>The first.</para>
195     /// <para></para>
196     /// </param>
197     /// <param name="second">
198     /// <para>The second.</para>
199     /// <para></para>
200     /// </param>
201     /// <returns>
202     /// <para>The bool</para>
203     /// <para></para>
204     /// </returns>
205     [MethodImpl(MethodImplOptions.AggressiveInlining)]
206     protected override bool FirstIsToLeftOfSecond(TLinkAddress first, TLinkAddress
207     ↪ second) => LessThan(GetKeyPartValue(first), GetKeyPartValue(second));
208
209     /// <summary>
210     /// <para>
211     /// Determines whether this instance first is to the right of second.
212     /// </para>
213     /// <para></para>
214     /// </summary>
215     /// <param name="first">
216     /// <para>The first.</para>
217     /// <para></para>
218     /// </param>
219     /// <param name="second">
220     /// <para>The second.</para>
221     /// <para></para>
222     /// </param>
223     /// <returns>

```

```

214    /// <returns>
215    /// <para>The bool</para>
216    /// <para></para>
217    /// </returns>
218    [MethodImpl(MethodImplOptions.AggressiveInlining)]
219    protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
    ↪ second) => GreaterThan(GetKeyPartValue(first), GetKeyPartValue(second));

220
221    /// <summary>
222    /// <para>
223    /// Gets the link values using the specified link index.
224    /// </para>
225    /// <para></para>
226    /// </summary>
227    /// <param name="linkIndex">
228    /// <para>The link index.</para>
229    /// <para></para>
230    /// </param>
231    /// <returns>
232    /// <para>A list of t link</para>
233    /// <para></para>
234    /// </returns>
235    [MethodImpl(MethodImplOptions.AggressiveInlining)]
236    protected virtual IList<TLinkAddress>? GetLinkValues(TLinkAddress linkIndex)
237    {
238        ref var link = ref GetLinkDataPartReference(linkIndex);
239        return new Link<TLinkAddress>(linkIndex, link.Source, link.Target);
240    }
241
242    /// <summary>
243    /// <para>
244    /// The zero.
245    /// </para>
246    /// <para></para>
247    /// </summary>
248    public TLinkAddress this[TLinkAddress link, TLinkAddress index]
249    {
250        [MethodImpl(MethodImplOptions.AggressiveInlining)]
251        get
252        {
253            var root = GetTreeRoot(link);
254            if (GreaterOrEqualThan(index, GetSize(root)))
255            {
256                return Zero;
257            }
258            while (!EqualToZero(root))
259            {
260                var left = GetLeftOrDefault(root);
261                var leftSize = GetSizeOrZero(left);
262                if (LessThan(index, leftSize))
263                {
264                    root = left;
265                    continue;
266                }
267                if (AreEqual(index, leftSize))
268                {
269                    return root;
270                }
271                root = GetRightOrDefault(root);
272                index = Subtract(index, Increment(leftSize));
273            }
274            return Zero; // TODO: Impossible situation exception (only if tree structure
    ↪ broken)
275        }
276    }
277
278    /// <summary>
279    /// Выполняет поиск и возвращает индекс связи с указанными Source (началом) и Target
    ↪ (концом).
280    /// </summary>
281    /// <param name="source">Индекс связи, которая является началом на искомой связи.</param>
282    /// <param name="target">Индекс связи, которая является концом на искомой связи.</param>
283    /// <returns>Индекс искомой связи.</returns>
284    [MethodImpl(MethodImplOptions.AggressiveInlining)]
285    public abstract TLinkAddress Search(TLinkAddress source, TLinkAddress target);
286
287    /// <summary>
288    /// <para>

```

```

289     /// Searches the core using the specified root.
290     /// </para>
291     /// <para></para>
292     /// </summary>
293     /// <param name="root">
294     /// <para>The root.</para>
295     /// <para></para>
296     /// </param>
297     /// <param name="key">
298     /// <para>The key.</para>
299     /// <para></para>
300     /// </param>
301     /// <returns>
302     /// <para>The zero.</para>
303     /// <para></para>
304     /// </returns>
305     [MethodImpl(MethodImplOptions.AggressiveInlining)]
306     protected TLinkAddress SearchCore(TLinkAddress root, TLinkAddress key)
307     {
308         while (!EqualToZero(root))
309         {
310             var rootKey = GetKeyPartValue(root);
311             if (LessThan(key, rootKey)) // node.Key < root.Key
312             {
313                 root = GetLeftOrDefault(root);
314             }
315             else if (GreaterThan(key, rootKey)) // node.Key > root.Key
316             {
317                 root = GetRightOrDefault(root);
318             }
319             else // node.Key == root.Key
320             {
321                 return root;
322             }
323         }
324         return Zero;
325     }
326
327     // TODO: Return indices range instead of references count
328     /// <summary>
329     /// <para>
330     /// Counts the usages using the specified link.
331     /// </para>
332     /// <para></para>
333     /// </summary>
334     /// <param name="link">
335     /// <para>The link.</para>
336     /// <para></para>
337     /// </param>
338     /// <returns>
339     /// <para>The link</para>
340     /// <para></para>
341     /// </returns>
342     [MethodImpl(MethodImplOptions.AggressiveInlining)]
343     public TLinkAddress CountUsages(TLinkAddress link) => GetSizeOrZero(GetTreeRoot(link));
344
345     /// <summary>
346     /// <para>
347     /// Eaches the usage using the specified base.
348     /// </para>
349     /// <para></para>
350     /// </summary>
351     /// <param name="@base">
352     /// <para>The base.</para>
353     /// <para></para>
354     /// </param>
355     /// <param name="handler">
356     /// <para>The handler.</para>
357     /// <para></para>
358     /// </param>
359     /// <returns>
360     /// <para>The link</para>
361     /// <para></para>
362     /// </returns>
363     [MethodImpl(MethodImplOptions.AggressiveInlining)]
364     public TLinkAddress EachUsage(TLinkAddress @base, ReadHandler<TLinkAddress>? handler) =>
365         ↪ EachUsageCore(@base, GetTreeRoot(@base), handler);

```

```

366 // TODO: 1. Move target, handler to separate object. 2. Use stack or walker 3. Use
367 ↪ low-level MSIL stack.
368 [MethodImpl(MethodImplOptions.AggressiveInlining)]
369 private TLinkAddress EachUsageCore(TLinkAddress @base, TLinkAddress link,
370 ↪ ReadHandler<TLinkAddress>? handler)
371 {
372     var @continue = Continue;
373     if (EqualToZero(link))
374     {
375         return @continue;
376     }
377     var @break = Break;
378     if (AreEqual(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))
379     {
380         return @break;
381     }
382     if (AreEqual(handler(GetLinkValues(link)), @break))
383     {
384         return @break;
385     }
386     if (AreEqual(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
387     {
388         return @break;
389     }
390     return @continue;
391 }
392
393 /// <summary>
394 /// <para>
395 /// Prints the node value using the specified node.
396 /// </para>
397 /// </summary>
398 /// <param name="node">
399 /// <para>The node.</para>
400 /// </param>
401 /// <param name="sb">
402 /// <para>The sb.</para>
403 /// </param>
404 [MethodImpl(MethodImplOptions.AggressiveInlining)]
405 protected override void PrintNodeValue(TLinkAddress node, StringBuilder sb)
406 {
407     ref var link = ref GetLinkDataPartReference(node);
408     sb.Append(' ');
409     sb.Append(link.Source);
410     sb.Append('-');
411     sb.Append('>');
412     sb.Append(link.Target);
413 }
414 }
415 }
416 }

```

1.39 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksSizeBalancedTreeMethodsBase.cs

```

1 using System;
2 using System.Text;
3 using System.Collections.Generic;
4 using System.Runtime.CompilerServices;
5 using Platform.Collections.Methods.Trees;
6 using Platform.Converters;
7 using Platform.Delegates;
8 using static System.Runtime.CompilerServices.Unsafe;
9
10 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
11
12 namespace Platform.Data.Doublets.Memory.Split.Generic
13 {
14     /// <summary>
15     /// <para>
16     /// Represents the internal links size balanced tree methods base.
17     /// </para>
18     /// </summary>
19     /// <seealso cref="SizeBalancedTreeMethods{TLinkAddress}"/>
20     /// <seealso cref="ILinksTreeMethods{TLinkAddress}"/>
21     public unsafe abstract class InternalLinksSizeBalancedTreeMethodsBase<TLinkAddress> :
22     ↪ SizeBalancedTreeMethods<TLinkAddress>, ILinksTreeMethods<TLinkAddress>
23     {

```

```

24 private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
    ↪ = UncheckedConverter<TLinkAddress, long>.Default;
25
26 /// <summary>
27 /// <para>
28 /// The break.
29 /// </para>
30 /// <para></para>
31 /// </summary>
32 protected readonly TLinkAddress Break;
33 /// <summary>
34 /// <para>
35 /// The continue.
36 /// </para>
37 /// <para></para>
38 /// </summary>
39 protected readonly TLinkAddress Continue;
40 /// <summary>
41 /// <para>
42 /// The links data parts.
43 /// </para>
44 /// <para></para>
45 /// </summary>
46 protected readonly byte* LinksDataParts;
47 /// <summary>
48 /// <para>
49 /// The links index parts.
50 /// </para>
51 /// <para></para>
52 /// </summary>
53 protected readonly byte* LinksIndexParts;
54 /// <summary>
55 /// <para>
56 /// The header.
57 /// </para>
58 /// <para></para>
59 /// </summary>
60 protected readonly byte* Header;
61
62 /// <summary>
63 /// <para>
64 /// Initializes a new <see cref="InternalLinksSizeBalancedTreeMethodsBase"/> instance.
65 /// </para>
66 /// <para></para>
67 /// </summary>
68 /// <param name="constants">
69 /// <para>A constants.</para>
70 /// <para></para>
71 /// </param>
72 /// <param name="linksDataParts">
73 /// <para>A links data parts.</para>
74 /// <para></para>
75 /// </param>
76 /// <param name="linksIndexParts">
77 /// <para>A links index parts.</para>
78 /// <para></para>
79 /// </param>
80 /// <param name="header">
81 /// <para>A header.</para>
82 /// <para></para>
83 /// </param>
84 [MethodImpl(MethodImplOptions.AggressiveInlining)]
85 protected InternalLinksSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress>
    ↪ constants, byte* linksDataParts, byte* linksIndexParts, byte* header)
86 {
87     LinksDataParts = linksDataParts;
88     LinksIndexParts = linksIndexParts;
89     Header = header;
90     Break = constants.Break;
91     Continue = constants.Continue;
92 }
93
94 /// <summary>
95 /// <para>
96 /// Gets the tree root using the specified link.
97 /// </para>
98 /// <para></para>
99 /// </summary>
100 /// <param name="link">

```

```

101    /// <para>The link.</para>
102    /// <para></para>
103    /// </param>
104    /// <returns>
105    /// <para>The link</para>
106    /// <para></para>
107    /// </returns>
108    [MethodImpl(MethodImplOptions.AggressiveInlining)]
109    protected abstract TLinkAddress GetTreeRoot(TLinkAddress link);
110
111    /// <summary>
112    /// <para>
113    /// Gets the base part value using the specified link.
114    /// </para>
115    /// <para></para>
116    /// </summary>
117    /// <param name="link">
118    /// <para>The link.</para>
119    /// <para></para>
120    /// </param>
121    /// <returns>
122    /// <para>The link</para>
123    /// <para></para>
124    /// </returns>
125    [MethodImpl(MethodImplOptions.AggressiveInlining)]
126    protected abstract TLinkAddress GetBasePartValue(TLinkAddress link);
127
128    /// <summary>
129    /// <para>
130    /// Gets the key part value using the specified link.
131    /// </para>
132    /// <para></para>
133    /// </summary>
134    /// <param name="link">
135    /// <para>The link.</para>
136    /// <para></para>
137    /// </param>
138    /// <returns>
139    /// <para>The link</para>
140    /// <para></para>
141    /// </returns>
142    [MethodImpl(MethodImplOptions.AggressiveInlining)]
143    protected abstract TLinkAddress GetKeyPartValue(TLinkAddress link);
144
145    /// <summary>
146    /// <para>
147    /// Gets the link data part reference using the specified link.
148    /// </para>
149    /// <para></para>
150    /// </summary>
151    /// <param name="link">
152    /// <para>The link.</para>
153    /// <para></para>
154    /// </param>
155    /// <returns>
156    /// <para>A ref raw link data part of t link</para>
157    /// <para></para>
158    /// </returns>
159    [MethodImpl(MethodImplOptions.AggressiveInlining)]
160    protected virtual ref RawLinkDataPart<TLinkAddress>
161    ↪ GetLinkDataPartReference(TLinkAddress link) => ref
162    ↪ AsRef<RawLinkDataPart<TLinkAddress>>(LinksDataParts +
163    ↪ (RawLinkDataPart<TLinkAddress>.SizeInBytes *
164    ↪ _addressToInt64Converter.Convert(link)));
165
166    /// <summary>
167    /// <para>
168    /// Gets the link index part reference using the specified link.
169    /// </para>
170    /// <para></para>
171    /// </summary>
172    /// <param name="link">
173    /// <para>The link.</para>
174    /// <para></para>
175    /// </param>
176    /// <returns>
177    /// <para>A ref raw link index part of t link</para>
178    /// <para></para>
179    /// </returns>

```

```

175     /// </returns>
176     [MethodImpl(MethodImplOptions.AggressiveInlining)]
177     protected virtual ref RawLinkIndexPart<TLinkAddress>
    ↪ GetLinkIndexPartReference(TLinkAddress link) => ref
    ↪ AsRef<RawLinkIndexPart<TLinkAddress>>(LinksIndexParts +
    ↪ (RawLinkIndexPart<TLinkAddress>.SizeInBytes *
    ↪ _addressToInt64Converter.Convert(link)));

178
179     /// <summary>
180     /// <para>
181     /// Determines whether this instance first is to the left of second.
182     /// </para>
183     /// <para></para>
184     /// </summary>
185     /// <param name="first">
186     /// <para>The first.</para>
187     /// <para></para>
188     /// </param>
189     /// <param name="second">
190     /// <para>The second.</para>
191     /// <para></para>
192     /// </param>
193     /// <returns>
194     /// <para>The bool</para>
195     /// <para></para>
196     /// </returns>
197     [MethodImpl(MethodImplOptions.AggressiveInlining)]
198     protected override bool FirstIsToTheLeftOfSecond(TLinkAddress first, TLinkAddress
    ↪ second) => LessThan(GetKeyPartValue(first), GetKeyPartValue(second));

199
200     /// <summary>
201     /// <para>
202     /// Determines whether this instance first is to the right of second.
203     /// </para>
204     /// <para></para>
205     /// </summary>
206     /// <param name="first">
207     /// <para>The first.</para>
208     /// <para></para>
209     /// </param>
210     /// <param name="second">
211     /// <para>The second.</para>
212     /// <para></para>
213     /// </param>
214     /// <returns>
215     /// <para>The bool</para>
216     /// <para></para>
217     /// </returns>
218     [MethodImpl(MethodImplOptions.AggressiveInlining)]
219     protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
    ↪ second) => GreaterThan(GetKeyPartValue(first), GetKeyPartValue(second));

220
221     /// <summary>
222     /// <para>
223     /// Gets the link values using the specified link index.
224     /// </para>
225     /// <para></para>
226     /// </summary>
227     /// <param name="linkIndex">
228     /// <para>The link index.</para>
229     /// <para></para>
230     /// </param>
231     /// <returns>
232     /// <para>A list of t link</para>
233     /// <para></para>
234     /// </returns>
235     [MethodImpl(MethodImplOptions.AggressiveInlining)]
236     protected virtual IList<TLinkAddress>? GetLinkValues(TLinkAddress linkIndex)
237     {
238         ref var link = ref GetLinkDataPartReference(linkIndex);
239         return new Link<TLinkAddress>(linkIndex, link.Source, link.Target);
240     }

241
242     /// <summary>
243     /// <para>
244     /// The zero.
245     /// </para>
246     /// <para></para>

```



```

247 /// </summary>
248 public TLinkAddress this[TLinkAddress link, TLinkAddress index]
249 {
250     [MethodImpl(MethodImplOptions.AggressiveInlining)]
251     get
252     {
253         var root = GetTreeRoot(link);
254         if (GreaterOrEqualThan(index, GetSize(root)))
255         {
256             return Zero;
257         }
258         while (!EqualToZero(root))
259         {
260             var left = GetLeftOrDefault(root);
261             var leftSize = GetSizeOrZero(left);
262             if (LessThan(index, leftSize))
263             {
264                 root = left;
265                 continue;
266             }
267             if (AreEqual(index, leftSize))
268             {
269                 return root;
270             }
271             root = GetRightOrDefault(root);
272             index = Subtract(index, Increment(leftSize));
273         }
274         return Zero; // TODO: Impossible situation exception (only if tree structure
275                     ↪ broken)
276     }
277 }
278
279 /// <summary>
280 /// Выполняет поиск и возвращает индекс связи с указанными Source (началом) и Target
281 /// ↪ (концом).
282 /// </summary>
283 /// <param name="source">Индекс связи, которая является началом на искомой связи.</param>
284 /// <param name="target">Индекс связи, которая является концом на искомой связи.</param>
285 /// <returns>Индекс искомой связи.</returns>
286 [MethodImpl(MethodImplOptions.AggressiveInlining)]
287 public abstract TLinkAddress Search(TLinkAddress source, TLinkAddress target);
288
289 /// <summary>
290 /// <para>
291 /// Searches the core using the specified root.
292 /// </para>
293 /// <para></para>
294 /// </summary>
295 /// <param name="root">
296 /// <para>The root.</para>
297 /// <para></para>
298 /// </param>
299 /// <param name="key">
300 /// <para>The key.</para>
301 /// <para></para>
302 /// </param>
303 /// <returns>
304 /// <para>The zero.</para>
305 /// <para></para>
306 /// </returns>
307 [MethodImpl(MethodImplOptions.AggressiveInlining)]
308 protected TLinkAddress SearchCore(TLinkAddress root, TLinkAddress key)
309 {
310     while (!EqualToZero(root))
311     {
312         var rootKey = GetKeyPartValue(root);
313         if (LessThan(key, rootKey) // node.Key < root.Key
314         {
315             root = GetLeftOrDefault(root);
316         }
317         else if (GreaterThan(key, rootKey) // node.Key > root.Key
318         {
319             root = GetRightOrDefault(root);
320         }
321         else // node.Key == root.Key
322         {
323             return root;
324         }
325     }
326 }

```

```

323     }
324     return Zero;
325 }
326
327 // TODO: Return indices range instead of references count
328 /// <summary>
329 /// <para>
330 /// Counts the usages using the specified link.
331 /// </para>
332 /// <para></para>
333 /// </summary>
334 /// <param name="link">
335 /// <para>The link.</para>
336 /// <para></para>
337 /// </param>
338 /// <returns>
339 /// <para>The link</para>
340 /// <para></para>
341 /// </returns>
342 [MethodImpl(MethodImplOptions.AggressiveInlining)]
343 public TLinkAddress CountUsages(TLinkAddress link) => GetSizeOrZero(GetTreeRoot(link));
344
345 /// <summary>
346 /// <para>
347 /// Eaches the usage using the specified base.
348 /// </para>
349 /// <para></para>
350 /// </summary>
351 /// <param name="@base">
352 /// <para>The base.</para>
353 /// <para></para>
354 /// </param>
355 /// <param name="handler">
356 /// <para>The handler.</para>
357 /// <para></para>
358 /// </param>
359 /// <returns>
360 /// <para>The link</para>
361 /// <para></para>
362 /// </returns>
363 [MethodImpl(MethodImplOptions.AggressiveInlining)]
364 public TLinkAddress EachUsage(TLinkAddress @base, ReadHandler<TLinkAddress>? handler) =>
365     ↳ EachUsageCore(@base, GetTreeRoot(@base), handler);
366
367 // TODO: 1. Move target, handler to separate object. 2. Use stack or walker 3. Use
368     ↳ low-level MSIL stack.
369 [MethodImpl(MethodImplOptions.AggressiveInlining)]
370 private TLinkAddress EachUsageCore(TLinkAddress @base, TLinkAddress link,
371     ↳ ReadHandler<TLinkAddress>? handler)
372 {
373     var @continue = Continue;
374     if (EqualToZero(link))
375     {
376         return @continue;
377     }
378     var @break = Break;
379     if (AreEqual(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))
380     {
381         return @break;
382     }
383     if (AreEqual(handler(GetLinkValues(link)), @break))
384     {
385         return @break;
386     }
387     if (AreEqual(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
388     {
389         return @break;
390     }
391     return @continue;
392 }
393
394 /// <summary>
395 /// <para>
396 /// Prints the node value using the specified node.
397 /// </para>
398 /// <para></para>
399 /// </summary>
400 /// <param name="node">

```

```

398     /// <para>The node.</para>
399     /// <para></para>
400     /// </param>
401     /// <param name="sb">
402     /// <para>The sb.</para>
403     /// <para></para>
404     /// </param>
405     [MethodImpl(MethodImplOptions.AggressiveInlining)]
406     protected override void PrintNodeValue(TLinkAddress node, StringBuilder sb)
407     {
408         ref var link = ref GetLinkDataPartReference(node);
409         sb.Append(' ');
410         sb.Append(link.Source);
411         sb.Append('-');
412         sb.Append('>');
413         sb.Append(link.Target);
414     }
415 }
416 }

```

1.40 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksSourcesLinkedListMethods.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Collections.Methods.Lists;
5  using Platform.Converters;
6  using Platform.Delegates;
7  using static System.Runtime.CompilerServices.Unsafe;
8
9  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
10
11 namespace Platform.Data.Doublets.Memory.Split.Generic
12 {
13     /// <summary>
14     /// <para>
15     /// Represents the internal links sources linked list methods.
16     /// </para>
17     /// <para></para>
18     /// </summary>
19     /// <seealso cref="RelativeCircularDoublyLinkedListMethods{TLinkAddress}"/>
20     public unsafe class InternalLinksSourcesLinkedListMethods<TLinkAddress> :
21         ↳ RelativeCircularDoublyLinkedListMethods<TLinkAddress>
22     {
23         private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
24             ↳ = UncheckedConverter<TLinkAddress, long>.Default;
25         private readonly byte* _linksDataParts;
26         private readonly byte* _linksIndexParts;
27         /// <summary>
28         /// <para>
29         /// The break.
30         /// </para>
31         /// <para></para>
32         /// </summary>
33         protected readonly TLinkAddress Break;
34         /// <summary>
35         /// <para>
36         /// The continue.
37         /// </para>
38         /// <para></para>
39         /// </summary>
40         protected readonly TLinkAddress Continue;
41
42         /// <summary>
43         /// <para>
44         /// Initializes a new <see cref="InternalLinksSourcesLinkedListMethods"/> instance.
45         /// </para>
46         /// <para></para>
47         /// </summary>
48         /// <param name="constants">
49         /// <para>A constants.</para>
50         /// <para></para>
51         /// </param>
52         /// <param name="linksDataParts">
53         /// <para>A links data parts.</para>
54         /// <para></para>
55         /// </param>
56         /// <param name="linksIndexParts">
57         /// <para>A links index parts.</para>
58         /// <para></para>
59         /// </param>

```

```

57     /// </param>
58     [MethodImpl(MethodImplOptions.AggressiveInlining)]
59     public InternalLinksSourcesLinkedListMethods(LinksConstants<TLinkAddress> constants,
60         ↳ byte* linksDataParts, byte* linksIndexParts)
61     {
62         _linksDataParts = linksDataParts;
63         _linksIndexParts = linksIndexParts;
64         Break = constants.Break;
65         Continue = constants.Continue;
66     }
67     /// <summary>
68     /// <para>
69     /// Gets the link data part reference using the specified link.
70     /// </para>
71     /// <para></para>
72     /// </summary>
73     /// <param name="link">
74     /// <para>The link.</para>
75     /// <para></para>
76     /// </param>
77     /// <returns>
78     /// <para>A ref raw link data part of t link</para>
79     /// <para></para>
80     /// </returns>
81     [MethodImpl(MethodImplOptions.AggressiveInlining)]
82     protected virtual ref RawLinkDataPart<TLinkAddress>
83         ↳ GetLinkDataPartReference(TLinkAddress link) => ref
84         ↳ AsRef<RawLinkDataPart<TLinkAddress>>(_linksDataParts +
85         ↳ (RawLinkDataPart<TLinkAddress>.SizeInBytes *
86         ↳ _addressToInt64Converter.Convert(link)));
87     /// <summary>
88     /// <para>
89     /// Gets the link index part reference using the specified link.
90     /// </para>
91     /// <para></para>
92     /// </summary>
93     /// <param name="link">
94     /// <para>The link.</para>
95     /// <para></para>
96     /// </param>
97     /// <returns>
98     /// <para>A ref raw link index part of t link</para>
99     /// <para></para>
100    /// </returns>
101    [MethodImpl(MethodImplOptions.AggressiveInlining)]
102    protected virtual ref RawLinkIndexPart<TLinkAddress>
103        ↳ GetLinkIndexPartReference(TLinkAddress link) => ref
104        ↳ AsRef<RawLinkIndexPart<TLinkAddress>>(_linksIndexParts +
105        ↳ (RawLinkIndexPart<TLinkAddress>.SizeInBytes *
106        ↳ _addressToInt64Converter.Convert(link)));
107    /// <summary>
108    /// <para>
109    /// Gets the first using the specified head.
110    /// </para>
111    /// <para></para>
112    /// </summary>
113    /// <param name="head">
114    /// <para>The head.</para>
115    /// <para></para>
116    /// </param>
117    /// <returns>
118    /// <para>The link</para>
119    /// <para></para>
120    /// </returns>
121    [MethodImpl(MethodImplOptions.AggressiveInlining)]
122    protected override TLinkAddress GetFirst(TLinkAddress head) =>
123        ↳ GetLinkIndexPartReference(head).RootAsSource;
124    /// <summary>
125    /// <para>
126    /// Gets the last using the specified head.
127    /// </para>
128    /// <para></para>
129    /// </summary>
130    /// <param name="head">

```

```

125    /// <para>The head.</para>
126    /// <para></para>
127    /// </param>
128    /// <returns>
129    /// <para>The link</para>
130    /// <para></para>
131    /// </returns>
132    [MethodImpl(MethodImplOptions.AggressiveInlining)]
133    protected override TLinkAddress GetLast(TLinkAddress head)
134    {
135        var first = GetLinkIndexPartReference(head).RootAsSource;
136        if (EqualToZero(first))
137        {
138            return first;
139        }
140        else
141        {
142            return GetPrevious(first);
143        }
144    }
145
146    /// <summary>
147    /// <para>
148    /// Gets the previous using the specified element.
149    /// </para>
150    /// <para></para>
151    /// </summary>
152    /// <param name="element">
153    /// <para>The element.</para>
154    /// <para></para>
155    /// </param>
156    /// <returns>
157    /// <para>The link</para>
158    /// <para></para>
159    /// </returns>
160    [MethodImpl(MethodImplOptions.AggressiveInlining)]
161    protected override TLinkAddress GetPrevious(TLinkAddress element) =>
162        ↪ GetLinkIndexPartReference(element).LeftAsSource;
163
164    /// <summary>
165    /// <para>
166    /// Gets the next using the specified element.
167    /// </para>
168    /// <para></para>
169    /// </summary>
170    /// <param name="element">
171    /// <para>The element.</para>
172    /// <para></para>
173    /// </param>
174    /// <returns>
175    /// <para>The link</para>
176    /// <para></para>
177    /// </returns>
178    [MethodImpl(MethodImplOptions.AggressiveInlining)]
179    protected override TLinkAddress GetNext(TLinkAddress element) =>
180        ↪ GetLinkIndexPartReference(element).RightAsSource;
181
182    /// <summary>
183    /// <para>
184    /// Gets the size using the specified head.
185    /// </para>
186    /// <para></para>
187    /// </summary>
188    /// <param name="head">
189    /// <para>The head.</para>
190    /// <para></para>
191    /// </param>
192    /// <returns>
193    /// <para>The link</para>
194    /// <para></para>
195    /// </returns>
196    [MethodImpl(MethodImplOptions.AggressiveInlining)]
197    protected override TLinkAddress GetSize(TLinkAddress head) =>
198        ↪ GetLinkIndexPartReference(head).SizeAsSource;
199
200    /// <summary>
201    /// <para>
202    /// Sets the first using the specified head.

```

```

200    /// </para>
201    /// <para></para>
202    /// </summary>
203    /// <param name="head">
204    /// <para>The head.</para>
205    /// <para></para>
206    /// </param>
207    /// <param name="element">
208    /// <para>The element.</para>
209    /// <para></para>
210    /// </param>
211    [MethodImpl(MethodImplOptions.AggressiveInlining)]
212    protected override void SetFirst(TLinkAddress head, TLinkAddress element) =>
213        ↪ GetLinkIndexPartReference(head).RootAsSource = element;
214
215    /// <summary>
216    /// <para>
217    /// Sets the last using the specified head.
218    /// </para>
219    /// <para></para>
220    /// </summary>
221    /// <param name="head">
222    /// <para>The head.</para>
223    /// <para></para>
224    /// </param>
225    /// <param name="element">
226    /// <para>The element.</para>
227    /// <para></para>
228    /// </param>
229    [MethodImpl(MethodImplOptions.AggressiveInlining)]
230    protected override void SetLast(TLinkAddress head, TLinkAddress element)
231    {
232        //var first = GetLinkIndexPartReference(head).RootAsSource;
233        //if (EqualToZero(first))
234        //{
235            SetFirst(head, element);
236        //}
237        //else
238        //{
239            SetPrevious(first, element);
240        //}
241    }
242
243    /// <summary>
244    /// <para>
245    /// Sets the previous using the specified element.
246    /// </para>
247    /// <para></para>
248    /// </summary>
249    /// <param name="element">
250    /// <para>The element.</para>
251    /// <para></para>
252    /// </param>
253    /// <param name="previous">
254    /// <para>The previous.</para>
255    /// <para></para>
256    /// </param>
257    [MethodImpl(MethodImplOptions.AggressiveInlining)]
258    protected override void SetPrevious(TLinkAddress element, TLinkAddress previous) =>
259        ↪ GetLinkIndexPartReference(element).LeftAsSource = previous;
260
261    /// <summary>
262    /// <para>
263    /// Sets the next using the specified element.
264    /// </para>
265    /// <para></para>
266    /// </summary>
267    /// <param name="element">
268    /// <para>The element.</para>
269    /// <para></para>
270    /// </param>
271    /// <param name="next">
272    /// <para>The next.</para>
273    /// <para></para>
274    /// </param>
275    [MethodImpl(MethodImplOptions.AggressiveInlining)]
276    protected override void SetNext(TLinkAddress element, TLinkAddress next) =>
277        ↪ GetLinkIndexPartReference(element).RightAsSource = next;

```

```

275
276    /// <summary>
277    /// <para>
278    /// Sets the size using the specified head.
279    /// </para>
280    /// <para></para>
281    /// </summary>
282    /// <param name="head">
283    /// <para>The head.</para>
284    /// <para></para>
285    /// </param>
286    /// <param name="size">
287    /// <para>The size.</para>
288    /// <para></para>
289    /// </param>
290    [MethodImpl(MethodImplOptions.AggressiveInlining)]
291    protected override void SetSize(TLinkAddress head, TLinkAddress size) =>
292        ↪ GetLinkIndexPartReference(head).SizeAsSource = size;
293
294    /// <summary>
295    /// <para>
296    /// Counts the usages using the specified head.
297    /// </para>
298    /// <para></para>
299    /// </summary>
300    /// <param name="head">
301    /// <para>The head.</para>
302    /// <para></para>
303    /// </param>
304    /// <returns>
305    /// <para>The link</para>
306    /// <para></para>
307    /// </returns>
308    [MethodImpl(MethodImplOptions.AggressiveInlining)]
309    public TLinkAddress CountUsages(TLinkAddress head) => GetSize(head);
310
311    /// <summary>
312    /// <para>
313    /// Gets the link values using the specified link index.
314    /// </para>
315    /// <para></para>
316    /// </summary>
317    /// <param name="linkIndex">
318    /// <para>The link index.</para>
319    /// <para></para>
320    /// </param>
321    /// <returns>
322    /// <para>A list of t link</para>
323    /// <para></para>
324    /// </returns>
325    [MethodImpl(MethodImplOptions.AggressiveInlining)]
326    protected virtual IList<TLinkAddress>? GetLinkValues(TLinkAddress linkIndex)
327    {
328        ref var link = ref GetLinkDataPartReference(linkIndex);
329        return new Link<TLinkAddress>(linkIndex, link.Source, link.Target);
330    }
331
332    /// <summary>
333    /// <para>
334    /// Eaches the usage using the specified source.
335    /// </para>
336    /// <para></para>
337    /// </summary>
338    /// <param name="source">
339    /// <para>The source.</para>
340    /// <para></para>
341    /// </param>
342    /// <param name="handler">
343    /// <para>The handler.</para>
344    /// <para></para>
345    /// </param>
346    /// <returns>
347    /// <para>The continue.</para>
348    /// <para></para>
349    /// </returns>
350    [MethodImpl(MethodImplOptions.AggressiveInlining)]
351    public TLinkAddress EachUsage(TLinkAddress source, ReadHandler<TLinkAddress>? handler)
352    {

```

```

352     var @continue = Continue;
353     var @break = Break;
354     var current = GetFirst(source);
355     var first = current;
356     while (!EqualToZero(current))
357     {
358         if (AreEqual(handler(GetLinkValues(current)), @break))
359         {
360             return @break;
361         }
362         current = GetNext(current);
363         if (AreEqual(current, first))
364         {
365             return @continue;
366         }
367     }
368     return @continue;
369 }
370 }
371 }

```

1.41 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksSourcesRecursionlessSizeBalancedTree

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.Split.Generic
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the internal links sources recursionless size balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="InternalLinksRecursionlessSizeBalancedTreeMethodsBase{TLinkAddress}"/>
14     public unsafe class InternalLinksSourcesRecursionlessSizeBalancedTreeMethods<TLinkAddress> :
15         InternalLinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress>
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see
20         ↪ cref="InternalLinksSourcesRecursionlessSizeBalancedTreeMethods"/> instance.
21         /// </para>
22         /// <para></para>
23         /// </summary>
24         /// <param name="constants">
25         /// <para>A constants.</para>
26         /// <para></para>
27         /// </param>
28         /// <param name="linksDataParts">
29         /// <para>A links data parts.</para>
30         /// <para></para>
31         /// </param>
32         /// <param name="linksIndexParts">
33         /// <para>A links index parts.</para>
34         /// <para></para>
35         /// </param>
36         /// <param name="header">
37         /// <para>A header.</para>
38         /// <para></para>
39         /// </param>
40         [MethodImpl(MethodImplOptions.AggressiveInlining)]
41         public InternalLinksSourcesRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddr_
42         ↪ ess> constants, byte* linksDataParts, byte* linksIndexParts, byte* header) :
43         ↪ base(constants, linksDataParts, linksIndexParts, header) { }
44
45         /// <summary>
46         /// <para>
47         /// Gets the left reference using the specified node.
48         /// </para>
49         /// <para></para>
50         /// </summary>
51         /// <param name="node">
52         /// <para>The node.</para>
53         /// <para></para>
54         /// </param>
55         /// <returns>
56         /// <para>The ref link</para>

```



```

53     /// <para></para>
54     /// </returns>
55     [MethodImpl(MethodImplOptions.AggressiveInlining)]
56     protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
57         ↪ GetLinkIndexPartReference(node).LeftAsSource;
58
59     /// <summary>
60     /// <para>
61     /// Gets the right reference using the specified node.
62     /// </para>
63     /// <para></para>
64     /// </summary>
65     /// <param name="node">
66     /// <para>The node.</para>
67     /// </param>
68     /// <returns>
69     /// <para>The ref link</para>
70     /// <para></para>
71     /// </returns>
72     [MethodImpl(MethodImplOptions.AggressiveInlining)]
73     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
74         ↪ GetLinkIndexPartReference(node).RightAsSource;
75
76     /// <summary>
77     /// <para>
78     /// Gets the left using the specified node.
79     /// </para>
80     /// <para></para>
81     /// </summary>
82     /// <param name="node">
83     /// <para>The node.</para>
84     /// </param>
85     /// <returns>
86     /// <para>The link</para>
87     /// <para></para>
88     /// </returns>
89     [MethodImpl(MethodImplOptions.AggressiveInlining)]
90     protected override TLinkAddress GetLeft(TLinkAddress node) =>
91         ↪ GetLinkIndexPartReference(node).LeftAsSource;
92
93     /// <summary>
94     /// <para>
95     /// Gets the right using the specified node.
96     /// </para>
97     /// <para></para>
98     /// </summary>
99     /// <param name="node">
100    /// <para>The node.</para>
101    /// </param>
102    /// <returns>
103    /// <para>The link</para>
104    /// <para></para>
105    /// </returns>
106    [MethodImpl(MethodImplOptions.AggressiveInlining)]
107    protected override TLinkAddress GetRight(TLinkAddress node) =>
108        ↪ GetLinkIndexPartReference(node).RightAsSource;
109
110    /// <summary>
111    /// <para>
112    /// Sets the left using the specified node.
113    /// </para>
114    /// <para></para>
115    /// </summary>
116    /// <param name="node">
117    /// <para>The node.</para>
118    /// </param>
119    /// <param name="left">
120    /// <para>The left.</para>
121    /// </param>
122    [MethodImpl(MethodImplOptions.AggressiveInlining)]
123    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
124        ↪ GetLinkIndexPartReference(node).LeftAsSource = left;

```

```

125
126    /// <summary>
127    /// <para>
128    /// Sets the right using the specified node.
129    /// </para>
130    /// <para></para>
131    /// </summary>
132    /// <param name="node">
133    /// <para>The node.</para>
134    /// <para></para>
135    /// </param>
136    /// <param name="right">
137    /// <para>The right.</para>
138    /// <para></para>
139    /// </param>
140    [MethodImpl(MethodImplOptions.AggressiveInlining)]
141    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
142        ↪ GetLinkIndexPartReference(node).RightAsSource = right;
143
144    /// <summary>
145    /// <para>
146    /// Gets the size using the specified node.
147    /// </para>
148    /// <para></para>
149    /// </summary>
150    /// <param name="node">
151    /// <para>The node.</para>
152    /// <para></para>
153    /// </param>
154    /// <returns>
155    /// <para>The link</para>
156    /// <para></para>
157    /// </returns>
158    [MethodImpl(MethodImplOptions.AggressiveInlining)]
159    protected override TLinkAddress GetSize(TLinkAddress node) =>
160        ↪ GetLinkIndexPartReference(node).SizeAsSource;
161
162    /// <summary>
163    /// <para>
164    /// Sets the size using the specified node.
165    /// </para>
166    /// <para></para>
167    /// </summary>
168    /// <param name="node">
169    /// <para>The node.</para>
170    /// <para></para>
171    /// </param>
172    /// <param name="size">
173    /// <para>The size.</para>
174    /// <para></para>
175    /// </param>
176    [MethodImpl(MethodImplOptions.AggressiveInlining)]
177    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
178        ↪ GetLinkIndexPartReference(node).SizeAsSource = size;
179
180    /// <summary>
181    /// <para>
182    /// Gets the tree root using the specified link.
183    /// </para>
184    /// <para></para>
185    /// </summary>
186    /// <param name="link">
187    /// <para>The link.</para>
188    /// <para></para>
189    /// </param>
190    /// <returns>
191    /// <para>The link</para>
192    /// <para></para>
193    /// </returns>
194    [MethodImpl(MethodImplOptions.AggressiveInlining)]
195    protected override TLinkAddress GetTreeRoot(TLinkAddress link) =>
196        ↪ GetLinkIndexPartReference(link).RootAsSource;
197
198    /// <summary>
199    /// <para>
200    /// Gets the base part value using the specified link.
201    /// </para>
202    /// <para></para>

```

```

199     /// </summary>
200     /// <param name="link">
201     /// <para>The link.</para>
202     /// <para></para>
203     /// </param>
204     /// <returns>
205     /// <para>The link</para>
206     /// <para></para>
207     /// </returns>
208     [MethodImpl(MethodImplOptions.AggressiveInlining)]
209     protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
210         ↪ GetLinkDataPartReference(link).Source;
211
212     /// <summary>
213     /// <para>
214     /// Gets the key part value using the specified link.
215     /// </para>
216     /// <para></para>
217     /// </summary>
218     /// <param name="link">
219     /// <para>The link.</para>
220     /// <para></para>
221     /// </param>
222     /// <returns>
223     /// <para>The link</para>
224     /// <para></para>
225     /// </returns>
226     [MethodImpl(MethodImplOptions.AggressiveInlining)]
227     protected override TLinkAddress GetKeyPartValue(TLinkAddress link) =>
228         ↪ GetLinkDataPartReference(link).Target;
229
230     /// <summary>
231     /// <para>
232     /// Clears the node using the specified node.
233     /// </para>
234     /// <para></para>
235     /// </summary>
236     /// <param name="node">
237     /// <para>The node.</para>
238     /// <para></para>
239     /// </param>
240     [MethodImpl(MethodImplOptions.AggressiveInlining)]
241     protected override void ClearNode(TLinkAddress node)
242     {
243         ref var link = ref GetLinkIndexPartReference(node);
244         link.LeftAsSource = Zero;
245         link.RightAsSource = Zero;
246         link.SizeAsSource = Zero;
247     }
248
249     /// <summary>
250     /// <para>
251     /// Searches the source.
252     /// </para>
253     /// <para></para>
254     /// </summary>
255     /// <param name="source">
256     /// <para>The source.</para>
257     /// <para></para>
258     /// </param>
259     /// <param name="target">
260     /// <para>The target.</para>
261     /// <para></para>
262     /// </param>
263     /// <returns>
264     /// <para>The link</para>
265     /// <para></para>
266     /// </returns>
267     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
268         ↪ SearchCore(GetTreeRoot(source), target);
269 }

```

1.42 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksSourcesSizeBalancedTreeMethods.cs

```

1 using System.Runtime.CompilerServices;
2
3 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4

```

```

5 namespace Platform.Data.Doublets.Memory.Split.Generic
6 {
7     /// <summary>
8     /// <para>
9     /// Represents the internal links sources size balanced tree methods.
10    /// </para>
11    /// <para></para>
12    /// </summary>
13    /// <seealso cref="InternalLinksSizeBalancedTreeMethodsBase{TLinkAddress}"/>
14    public unsafe class InternalLinksSourcesSizeBalancedTreeMethods<TLinkAddress> :
15        InternalLinksSizeBalancedTreeMethodsBase<TLinkAddress>
16    {
17        /// <summary>
18        /// <para>
19        /// Initializes a new <see cref="InternalLinksSourcesSizeBalancedTreeMethods"/> instance.
20        /// </para>
21        /// <para></para>
22        /// </summary>
23        /// <param name="constants">
24        /// <para>A constants.</para>
25        /// <para></para>
26        /// </param>
27        /// <param name="linksDataParts">
28        /// <para>A links data parts.</para>
29        /// <para></para>
30        /// </param>
31        /// <param name="linksIndexParts">
32        /// <para>A links index parts.</para>
33        /// <para></para>
34        /// </param>
35        /// <param name="header">
36        /// <para>A header.</para>
37        /// <para></para>
38        /// </param>
39        [MethodImpl(MethodImplOptions.AggressiveInlining)]
40        public InternalLinksSourcesSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
41            constants, byte* linksDataParts, byte* linksIndexParts, byte* header) :
42            base(constants, linksDataParts, linksIndexParts, header) { }
43
44        /// <summary>
45        /// <para>
46        /// Gets the left reference using the specified node.
47        /// </para>
48        /// <para></para>
49        /// </summary>
50        /// <param name="node">
51        /// <para>The node.</para>
52        /// <para></para>
53        /// </param>
54        /// <returns>
55        /// <para>The ref link</para>
56        /// <para></para>
57        /// </returns>
58        [MethodImpl(MethodImplOptions.AggressiveInlining)]
59        protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
60            GetLinkIndexPartReference(node).LeftAsSource;
61
62        /// <summary>
63        /// <para>
64        /// Gets the right reference using the specified node.
65        /// </para>
66        /// <para></para>
67        /// </summary>
68        /// <param name="node">
69        /// <para>The node.</para>
70        /// <para></para>
71        /// </param>
72        /// <returns>
73        /// <para>The ref link</para>
74        /// <para></para>
75        /// </returns>
76        [MethodImpl(MethodImplOptions.AggressiveInlining)]
77        protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
78            GetLinkIndexPartReference(node).RightAsSource;
79
80        /// <summary>
81        /// <para>
82        /// Gets the left using the specified node.
83        /// </para>
84        /// <para></para>
85        /// </summary>
86        /// <param name="node">
87        /// <para>The node.</para>
88        /// <para></para>
89        /// </param>
90        /// <returns>
91        /// <para>The ref link</para>
92        /// <para></para>
93        /// </returns>
94        [MethodImpl(MethodImplOptions.AggressiveInlining)]
95        protected override ref TLinkAddress GetLeftUsingNode(TLinkAddress node) => ref
96            GetLinkIndexPartReference(node).LeftAsSource;
97
98        /// <summary>
99        /// <para>
100       /// Gets the right using the specified node.
101       /// </para>
102       /// <para></para>
103       /// </summary>
104       /// <param name="node">
105       /// <para>The node.</para>
106       /// <para></para>
107       /// </param>
108       /// <returns>
109       /// <para>The ref link</para>
110       /// <para></para>
111       /// </returns>
112       [MethodImpl(MethodImplOptions.AggressiveInlining)]
113       protected override ref TLinkAddress GetRightUsingNode(TLinkAddress node) => ref
114           GetLinkIndexPartReference(node).RightAsSource;
115
116       /// <summary>
117       /// <para>
118       /// Gets the left using the specified node.
119       /// </para>
120       /// <para></para>
121       /// </summary>
122       /// <param name="node">
123       /// <para>The node.</para>
124       /// <para></para>
125       /// </param>
126       /// <returns>
127       /// <para>The ref link</para>
128       /// <para></para>
129       /// </returns>
130       [MethodImpl(MethodImplOptions.AggressiveInlining)]
131       protected override ref TLinkAddress GetLeftUsingNode(TLinkAddress node) => ref
132           GetLinkIndexPartReference(node).LeftAsSource;
133
134       /// <summary>
135       /// <para>
136       /// Gets the right using the specified node.
137       /// </para>
138       /// <para></para>
139       /// </summary>
140       /// <param name="node">
141       /// <para>The node.</para>
142       /// <para></para>
143       /// </param>
144       /// <returns>
145       /// <para>The ref link</para>
146       /// <para></para>
147       /// </returns>
148       [MethodImpl(MethodImplOptions.AggressiveInlining)]
149       protected override ref TLinkAddress GetRightUsingNode(TLinkAddress node) => ref
150           GetLinkIndexPartReference(node).RightAsSource;
151
152       /// <summary>
153       /// <para>
154       /// Gets the left using the specified node.
155       /// </para>
156       /// <para></para>
157       /// </summary>
158       /// <param name="node">
159       /// <para>The node.</para>
160       /// <para></para>
161       /// </param>
162       /// <returns>
163       /// <para>The ref link</para>
164       /// <para></para>
165       /// </returns>
166       [MethodImpl(MethodImplOptions.AggressiveInlining)]
167       protected override ref TLinkAddress GetLeftUsingNode(TLinkAddress node) => ref
168           GetLinkIndexPartReference(node).LeftAsSource;
169
170       /// <summary>
171       /// <para>
172       /// Gets the right using the specified node.
173       /// </para>
174       /// <para></para>
175       /// </summary>
176       /// <param name="node">
177       /// <para>The node.</para>
178       /// <para></para>
179       /// </param>
180       /// <returns>
181       /// <para>The ref link</para>
182       /// <para></para>
183       /// </returns>
184       [MethodImpl(MethodImplOptions.AggressiveInlining)]
185       protected override ref TLinkAddress GetRightUsingNode(TLinkAddress node) => ref
186           GetLinkIndexPartReference(node).RightAsSource;
187
188       /// <summary>
189       /// <para>
190       /// Gets the left using the specified node.
191       /// </para>
192       /// <para></para>
193       /// </summary>
194       /// <param name="node">
195       /// <para>The node.</para>
196       /// <para></para>
197       /// </param>
198       /// <returns>
199       /// <para>The ref link</para>
200       /// <para></para>
201       /// </returns>
202       [MethodImpl(MethodImplOptions.AggressiveInlining)]
203       protected override ref TLinkAddress GetLeftUsingNode(TLinkAddress node) => ref
204           GetLinkIndexPartReference(node).LeftAsSource;
205
206       /// <summary>
207       /// <para>
208       /// Gets the right using the specified node.
209       /// </para>
210       /// <para></para>
211       /// </summary>
212       /// <param name="node">
213       /// <para>The node.</para>
214       /// <para></para>
215       /// </param>
216       /// <returns>
217       /// <para>The ref link</para>
218       /// <para></para>
219       /// </returns>
220       [MethodImpl(MethodImplOptions.AggressiveInlining)]
221       protected override ref TLinkAddress GetRightUsingNode(TLinkAddress node) => ref
222           GetLinkIndexPartReference(node).RightAsSource;
223
224       /// <summary>
225       /// <para>
226       /// Gets the left using the specified node.
227       /// </para>
228       /// <para></para>
229       /// </summary>
230       /// <param name="node">
231       /// <para>The node.</para>
232       /// <para></para>
233       /// </param>
234       /// <returns>
235       /// <para>The ref link</para>
236       /// <para></para>
237       /// </returns>
238       [MethodImpl(MethodImplOptions.AggressiveInlining)]
239       protected override ref TLinkAddress GetLeftUsingNode(TLinkAddress node) => ref
240           GetLinkIndexPartReference(node).LeftAsSource;
241
242       /// <summary>
243       /// <para>
244       /// Gets the right using the specified node.
245       /// </para>
246       /// <para></para>
247       /// </summary>
248       /// <param name="node">
249       /// <para>The node.</para>
250       /// <para></para>
251       /// </param>
252       /// <returns>
253       /// <para>The ref link</para>
254       /// <para></para>
255       /// </returns>
256       [MethodImpl(MethodImplOptions.AggressiveInlining)]
257       protected override ref TLinkAddress GetRightUsingNode(TLinkAddress node) => ref
258           GetLinkIndexPartReference(node).RightAsSource;
259
260       /// <summary>
261       /// <para>
262       /// Gets the left using the specified node.
263       /// </para>
264       /// <para></para>
265       /// </summary>
266       /// <param name="node">
267       /// <para>The node.</para>
268       /// <para></para>
269       /// </param>
270       /// <returns>
271       /// <para>The ref link</para>
272       /// <para></para>
273       /// </returns>
274       [MethodImpl(MethodImplOptions.AggressiveInlining)]
275       protected override ref TLinkAddress GetLeftUsingNode(TLinkAddress node) => ref
276           GetLinkIndexPartReference(node).LeftAsSource;
277
278       /// <summary>
279       /// <para>
280       /// Gets the right using the specified node.
281       /// </para>
282       /// <para></para>
283       /// </summary>
284       /// <param name="node">
285       /// <para>The node.</para>
286       /// <para></para>
287       /// </param>
288       /// <returns>
289       /// <para>The ref link</para>
290       /// <para></para>
```

```

78     /// </para>
79     /// <para></para>
80     /// </summary>
81     /// <param name="node">
82     /// <para>The node.</para>
83     /// <para></para>
84     /// </param>
85     /// <returns>
86     /// <para>The link</para>
87     /// <para></para>
88     /// </returns>
89     [MethodImpl(MethodImplOptions.AggressiveInlining)]
90     protected override TLinkAddress GetLeft(TLinkAddress node) =>
91         ↪ GetLinkIndexPartReference(node).LeftAsSource;
92
93     /// <summary>
94     /// <para>
95     /// Gets the right using the specified node.
96     /// </para>
97     /// <para></para>
98     /// </summary>
99     /// <param name="node">
100    /// <para>The node.</para>
101    /// <para></para>
102    /// </param>
103    /// <returns>
104    /// <para>The link</para>
105    /// <para></para>
106    /// </returns>
107    [MethodImpl(MethodImplOptions.AggressiveInlining)]
108    protected override TLinkAddress GetRight(TLinkAddress node) =>
109        ↪ GetLinkIndexPartReference(node).RightAsSource;
110
111    /// <summary>
112    /// <para>
113    /// Sets the left using the specified node.
114    /// </para>
115    /// <para></para>
116    /// </summary>
117    /// <param name="node">
118    /// <para>The node.</para>
119    /// <para></para>
120    /// </param>
121    /// <param name="left">
122    /// <para>The left.</para>
123    /// <para></para>
124    /// </param>
125    [MethodImpl(MethodImplOptions.AggressiveInlining)]
126    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
127        ↪ GetLinkIndexPartReference(node).LeftAsSource = left;
128
129    /// <summary>
130    /// <para>
131    /// Sets the right using the specified node.
132    /// </para>
133    /// <para></para>
134    /// </summary>
135    /// <param name="node">
136    /// <para>The node.</para>
137    /// <para></para>
138    /// </param>
139    /// <param name="right">
140    /// <para>The right.</para>
141    /// <para></para>
142    /// </param>
143    [MethodImpl(MethodImplOptions.AggressiveInlining)]
144    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
145        ↪ GetLinkIndexPartReference(node).RightAsSource = right;
146
147    /// <summary>
148    /// <para>
149    /// Gets the size using the specified node.
150    /// </para>
151    /// <para></para>
152    /// </summary>
153    /// <param name="node">
154    /// <para>The node.</para>
155    /// <para></para>
156    /// </param>

```

```

152     /// </param>
153     /// <returns>
154     /// <para>The link</para>
155     /// <para></para>
156     /// </returns>
157     [MethodImpl(MethodImplOptions.AggressiveInlining)]
158     protected override TLinkAddress GetSize(TLinkAddress node) =>
159         ↪ GetLinkIndexPartReference(node).SizeAsSource;
160
161     /// <summary>
162     /// <para>
163     /// Sets the size using the specified node.
164     /// </para>
165     /// <para></para>
166     /// </summary>
167     /// <param name="node">
168     /// <para>The node.</para>
169     /// <para></para>
170     /// </param>
171     /// <param name="size">
172     /// <para>The size.</para>
173     /// <para></para>
174     /// </param>
175     [MethodImpl(MethodImplOptions.AggressiveInlining)]
176     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
177         ↪ GetLinkIndexPartReference(node).SizeAsSource = size;
178
179     /// <summary>
180     /// <para>
181     /// Gets the tree root using the specified link.
182     /// </para>
183     /// <para></para>
184     /// </summary>
185     /// <param name="link">
186     /// <para>The link.</para>
187     /// <para></para>
188     /// </param>
189     /// <returns>
190     /// <para>The link</para>
191     /// <para></para>
192     /// </returns>
193     [MethodImpl(MethodImplOptions.AggressiveInlining)]
194     protected override TLinkAddress GetTreeRoot(TLinkAddress link) =>
195         ↪ GetLinkIndexPartReference(link).RootAsSource;
196
197     /// <summary>
198     /// <para>
199     /// Gets the base part value using the specified link.
200     /// </para>
201     /// <para></para>
202     /// </summary>
203     /// <param name="link">
204     /// <para>The link.</para>
205     /// <para></para>
206     /// </param>
207     /// <returns>
208     /// <para>The link</para>
209     /// <para></para>
210     /// </returns>
211     [MethodImpl(MethodImplOptions.AggressiveInlining)]
212     protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
213         ↪ GetLinkDataPartReference(link).Source;
214
215     /// <summary>
216     /// <para>
217     /// Gets the key part value using the specified link.
218     /// </para>
219     /// <para></para>
220     /// </summary>
221     /// <param name="link">
222     /// <para>The link.</para>
223     /// <para></para>
224     /// </param>
225     /// <returns>
226     /// <para>The link</para>
227     /// <para></para>
228     /// </returns>
229     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

226     protected override TLinkAddress GetKeyPartValue(TLinkAddress link) =>
227         ↪ GetLinkDataPartReference(link).Target;
228
229     /// <summary>
230     /// <para>
231     /// Clears the node using the specified node.
232     /// </para>
233     /// </summary>
234     /// <param name="node">
235     /// <para>The node.</para>
236     /// </param>
237     [MethodImpl(MethodImplOptions.AggressiveInlining)]
238     protected override void ClearNode(TLinkAddress node)
239     {
240         ref var link = ref GetLinkIndexPartReference(node);
241         link.LeftAsSource = Zero;
242         link.RightAsSource = Zero;
243         link.SizeAsSource = Zero;
244     }
245
246     /// <summary>
247     /// <para>
248     /// Searches the source.
249     /// </para>
250     /// </summary>
251     /// <param name="source">
252     /// <para>The source.</para>
253     /// </param>
254     /// <param name="target">
255     /// <para>The target.</para>
256     /// </param>
257     /// <returns>
258     /// <para>The link</para>
259     /// </returns>
260     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
261         ↪ SearchCore(GetTreeRoot(source), target);
262
263 }
264
265 }

```

1.43 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksTargetsRecursionlessSizeBalancedTree

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.Split.Generic
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the internal links targets recursionless size balanced tree methods.
10     /// </para>
11     /// </summary>
12     /// <seealso cref="InternalLinksRecursionlessSizeBalancedTreeMethodsBase{TLinkAddress}"/>
13     public unsafe class InternalLinksTargetsRecursionlessSizeBalancedTreeMethods<TLinkAddress> :
14         ↪ InternalLinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress>
15     {
16         /// <summary>
17         /// <para>
18         /// Initializes a new <see
19         ↪ cref="InternalLinksTargetsRecursionlessSizeBalancedTreeMethods"/> instance.
20         /// </para>
21         /// </summary>
22         /// <param name="constants">
23         /// <para>A constants.</para>
24         /// </param>
25         /// <param name="linksDataParts">
26         /// <para>A links data parts.</para>
27         /// </param>
28         /// <param name="linksIndexParts">

```

```

31    /// <para>A links index parts.</para>
32    /// <para></para>
33    /// </param>
34    /// <param name="header">
35    /// <para>A header.</para>
36    /// <para></para>
37    /// </param>
38    [MethodImpl(MethodImplOptions.AggressiveInlining)]
39    public InternalLinksTargetsRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddr_
    ↪     ss> constants, byte* linksDataParts, byte* linksIndexParts, byte* header) :
    ↪     base(constants, linksDataParts, linksIndexParts, header) { }

40
41    /// <summary>
42    /// <para>
43    /// Gets the left reference using the specified node.
44    /// </para>
45    /// <para></para>
46    /// </summary>
47    /// <param name="node">
48    /// <para>The node.</para>
49    /// <para></para>
50    /// </param>
51    /// <returns>
52    /// <para>The ref link</para>
53    /// <para></para>
54    /// </returns>
55    [MethodImpl(MethodImplOptions.AggressiveInlining)]
56    protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪     GetLinkIndexPartReference(node).LeftAsTarget;

57
58    /// <summary>
59    /// <para>
60    /// Gets the right reference using the specified node.
61    /// </para>
62    /// <para></para>
63    /// </summary>
64    /// <param name="node">
65    /// <para>The node.</para>
66    /// <para></para>
67    /// </param>
68    /// <returns>
69    /// <para>The ref link</para>
70    /// <para></para>
71    /// </returns>
72    [MethodImpl(MethodImplOptions.AggressiveInlining)]
73    protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪     GetLinkIndexPartReference(node).RightAsTarget;

74
75    /// <summary>
76    /// <para>
77    /// Gets the left using the specified node.
78    /// </para>
79    /// <para></para>
80    /// </summary>
81    /// <param name="node">
82    /// <para>The node.</para>
83    /// <para></para>
84    /// </param>
85    /// <returns>
86    /// <para>The link</para>
87    /// <para></para>
88    /// </returns>
89    [MethodImpl(MethodImplOptions.AggressiveInlining)]
90    protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪     GetLinkIndexPartReference(node).LeftAsTarget;

91
92    /// <summary>
93    /// <para>
94    /// Gets the right using the specified node.
95    /// </para>
96    /// <para></para>
97    /// </summary>
98    /// <param name="node">
99    /// <para>The node.</para>
100    /// <para></para>
101    /// </param>
102    /// <returns>

```



```

103     /// <para>The link</para>
104     /// <para></para>
105     /// </returns>
106     [MethodImpl(MethodImplOptions.AggressiveInlining)]
107     protected override TLinkAddress GetRight(TLinkAddress node) =>
108         ↪ GetLinkIndexPartReference(node).RightAsTarget;
109
110     /// <summary>
111     /// <para>
112     /// Sets the left using the specified node.
113     /// </para>
114     /// <para></para>
115     /// </summary>
116     /// <param name="node">
117     /// <para>The node.</para>
118     /// <para></para>
119     /// </param>
120     /// <param name="left">
121     /// <para>The left.</para>
122     /// <para></para>
123     /// </param>
124     [MethodImpl(MethodImplOptions.AggressiveInlining)]
125     protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
126         ↪ GetLinkIndexPartReference(node).LeftAsTarget = left;
127
128     /// <summary>
129     /// <para>
130     /// Sets the right using the specified node.
131     /// </para>
132     /// <para></para>
133     /// </summary>
134     /// <param name="node">
135     /// <para>The node.</para>
136     /// <para></para>
137     /// </param>
138     /// <param name="right">
139     /// <para>The right.</para>
140     /// <para></para>
141     /// </param>
142     [MethodImpl(MethodImplOptions.AggressiveInlining)]
143     protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
144         ↪ GetLinkIndexPartReference(node).RightAsTarget = right;
145
146     /// <summary>
147     /// <para>
148     /// Gets the size using the specified node.
149     /// </para>
150     /// <para></para>
151     /// </summary>
152     /// <param name="node">
153     /// <para>The node.</para>
154     /// <para></para>
155     /// </param>
156     /// <returns>
157     /// <para>The link</para>
158     /// <para></para>
159     /// </returns>
160     [MethodImpl(MethodImplOptions.AggressiveInlining)]
161     protected override TLinkAddress GetSize(TLinkAddress node) =>
162         ↪ GetLinkIndexPartReference(node).SizeAsTarget;
163
164     /// <summary>
165     /// <para>
166     /// Sets the size using the specified node.
167     /// </para>
168     /// <para></para>
169     /// </summary>
170     /// <param name="node">
171     /// <para>The node.</para>
172     /// <para></para>
173     /// </param>
174     /// <param name="size">
175     /// <para>The size.</para>
176     /// <para></para>
177     /// </param>
178     [MethodImpl(MethodImplOptions.AggressiveInlining)]
179     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
180         ↪ GetLinkIndexPartReference(node).SizeAsTarget = size;

```

```

176
177     /// <summary>
178     /// <para>
179     /// Gets the tree root using the specified link.
180     /// </para>
181     /// <para></para>
182     /// </summary>
183     /// <param name="link">
184     /// <para>The link.</para>
185     /// <para></para>
186     /// </param>
187     /// <returns>
188     /// <para>The link</para>
189     /// <para></para>
190     /// </returns>
191     [MethodImpl(MethodImplOptions.AggressiveInlining)]
192     protected override TLinkAddress GetTreeRoot(TLinkAddress link) =>
193         ↪ GetLinkIndexPartReference(link).RootAsTarget;
194
195     /// <summary>
196     /// <para>
197     /// Gets the base part value using the specified link.
198     /// </para>
199     /// <para></para>
200     /// </summary>
201     /// <param name="link">
202     /// <para>The link.</para>
203     /// <para></para>
204     /// </param>
205     /// <returns>
206     /// <para>The link</para>
207     /// <para></para>
208     /// </returns>
209     [MethodImpl(MethodImplOptions.AggressiveInlining)]
210     protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
211         ↪ GetLinkDataPartReference(link).Target;
212
213     /// <summary>
214     /// <para>
215     /// Gets the key part value using the specified link.
216     /// </para>
217     /// <para></para>
218     /// </summary>
219     /// <param name="link">
220     /// <para>The link.</para>
221     /// <para></para>
222     /// </param>
223     /// <returns>
224     /// <para>The link</para>
225     /// <para></para>
226     /// </returns>
227     [MethodImpl(MethodImplOptions.AggressiveInlining)]
228     protected override TLinkAddress GetKeyPartValue(TLinkAddress link) =>
229         ↪ GetLinkDataPartReference(link).Source;
230
231     /// <summary>
232     /// <para>
233     /// Clears the node using the specified node.
234     /// </para>
235     /// <para></para>
236     /// </summary>
237     /// <param name="node">
238     /// <para>The node.</para>
239     /// <para></para>
240     /// </param>
241     [MethodImpl(MethodImplOptions.AggressiveInlining)]
242     protected override void ClearNode(TLinkAddress node)
243     {
244         ref var link = ref GetLinkIndexPartReference(node);
245         link.LeftAsTarget = Zero;
246         link.RightAsTarget = Zero;
247         link.SizeAsTarget = Zero;
248     }
249
250     /// <summary>
251     /// <para>
252     /// Searches the source.
253     /// </para>

```

```

251     /// <para></para>
252     /// </summary>
253     /// <param name="source">
254     /// <para>The source.</para>
255     /// <para></para>
256     /// </param>
257     /// <param name="target">
258     /// <para>The target.</para>
259     /// <para></para>
260     /// </param>
261     /// <returns>
262     /// <para>The link</para>
263     /// <para></para>
264     /// </returns>
265     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
        ↪ SearchCore(GetTreeRoot(target), source);
266 }
267 }

```

1.44 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksTargetsSizeBalancedTreeMethods.cs

```

1 using System.Runtime.CompilerServices;
2
3 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5 namespace Platform.Data.Doublets.Memory.Split.Generic
6 {
7     /// <summary>
8     /// <para>
9     /// Represents the internal links targets size balanced tree methods.
10    /// </para>
11    /// <para></para>
12    /// </summary>
13    /// <seealso cref="InternalLinksSizeBalancedTreeMethodsBase{TLinkAddress}"/>
14    public unsafe class InternalLinksTargetsSizeBalancedTreeMethods<TLinkAddress> :
        ↪ InternalLinksSizeBalancedTreeMethodsBase<TLinkAddress>
15    {
16        /// <summary>
17        /// <para>
18        /// Initializes a new <see cref="InternalLinksTargetsSizeBalancedTreeMethods"/> instance.
19        /// </para>
20        /// <para></para>
21        /// </summary>
22        /// <param name="constants">
23        /// <para>A constants.</para>
24        /// <para></para>
25        /// </param>
26        /// <param name="linksDataParts">
27        /// <para>A links data parts.</para>
28        /// <para></para>
29        /// </param>
30        /// <param name="linksIndexParts">
31        /// <para>A links index parts.</para>
32        /// <para></para>
33        /// </param>
34        /// <param name="header">
35        /// <para>A header.</para>
36        /// <para></para>
37        /// </param>
38        [MethodImpl(MethodImplOptions.AggressiveInlining)]
39        public InternalLinksTargetsSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
        ↪ constants, byte* linksDataParts, byte* linksIndexParts, byte* header) :
        ↪ base(constants, linksDataParts, linksIndexParts, header) { }
40
41        /// <summary>
42        /// <para>
43        /// Gets the left reference using the specified node.
44        /// </para>
45        /// <para></para>
46        /// </summary>
47        /// <param name="node">
48        /// <para>The node.</para>
49        /// <para></para>
50        /// </param>
51        /// <returns>
52        /// <para>The ref link</para>
53        /// <para></para>
54        /// </returns>
55        [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

56     protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
57         ↪ GetLinkIndexPartReference(node).LeftAsTarget;
58
59     /// <summary>
60     /// <para>
61     /// Gets the right reference using the specified node.
62     /// </para>
63     /// </summary>
64     /// <param name="node">
65     /// <para>The node.</para>
66     /// </param>
67     /// </returns>
68     /// <para>The ref link</para>
69     /// </returns>
70     [MethodImpl(MethodImplOptions.AggressiveInlining)]
71     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
72         ↪ GetLinkIndexPartReference(node).RightAsTarget;
73
74     /// <summary>
75     /// <para>
76     /// Gets the left using the specified node.
77     /// </para>
78     /// </summary>
79     /// <param name="node">
80     /// <para>The node.</para>
81     /// </param>
82     /// </returns>
83     /// <para>The link</para>
84     /// </returns>
85     [MethodImpl(MethodImplOptions.AggressiveInlining)]
86     protected override TLinkAddress GetLeft(TLinkAddress node) =>
87         ↪ GetLinkIndexPartReference(node).LeftAsTarget;
88
89     /// <summary>
90     /// <para>
91     /// Gets the right using the specified node.
92     /// </para>
93     /// </summary>
94     /// <param name="node">
95     /// <para>The node.</para>
96     /// </param>
97     /// </returns>
98     /// <para>The link</para>
99     /// </returns>
100     [MethodImpl(MethodImplOptions.AggressiveInlining)]
101     protected override TLinkAddress GetRight(TLinkAddress node) =>
102         ↪ GetLinkIndexPartReference(node).RightAsTarget;
103
104     /// <summary>
105     /// <para>
106     /// Sets the left using the specified node.
107     /// </para>
108     /// </summary>
109     /// <param name="node">
110     /// <para>The node.</para>
111     /// </param>
112     /// <param name="left">
113     /// <para>The left.</para>
114     /// </param>
115     [MethodImpl(MethodImplOptions.AggressiveInlining)]
116     protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
117         ↪ GetLinkIndexPartReference(node).LeftAsTarget = left;
118
119     /// <summary>
120     /// <para>
121     ///
122     /// </para>

```

```

128     /// Sets the right using the specified node.
129     /// </para>
130     /// <para></para>
131     /// </summary>
132     /// <param name="node">
133     /// <para>The node.</para>
134     /// <para></para>
135     /// </param>
136     /// <param name="right">
137     /// <para>The right.</para>
138     /// <para></para>
139     /// </param>
140     [MethodImpl(MethodImplOptions.AggressiveInlining)]
141     protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
142         ↪ GetLinkIndexPartReference(node).RightAsTarget = right;
143
144     /// <summary>
145     /// <para>
146     /// Gets the size using the specified node.
147     /// </para>
148     /// <para></para>
149     /// </summary>
150     /// <param name="node">
151     /// <para>The node.</para>
152     /// <para></para>
153     /// </param>
154     /// <returns>
155     /// <para>The link</para>
156     /// <para></para>
157     /// </returns>
158     [MethodImpl(MethodImplOptions.AggressiveInlining)]
159     protected override TLinkAddress GetSize(TLinkAddress node) =>
160         ↪ GetLinkIndexPartReference(node).SizeAsTarget;
161
162     /// <summary>
163     /// <para>
164     /// Sets the size using the specified node.
165     /// </para>
166     /// <para></para>
167     /// </summary>
168     /// <param name="node">
169     /// <para>The node.</para>
170     /// <para></para>
171     /// </param>
172     /// <param name="size">
173     /// <para>The size.</para>
174     /// <para></para>
175     /// </param>
176     [MethodImpl(MethodImplOptions.AggressiveInlining)]
177     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
178         ↪ GetLinkIndexPartReference(node).SizeAsTarget = size;
179
180     /// <summary>
181     /// <para>
182     /// Gets the tree root using the specified link.
183     /// </para>
184     /// <para></para>
185     /// </summary>
186     /// <param name="link">
187     /// <para>The link.</para>
188     /// <para></para>
189     /// </param>
190     /// <returns>
191     /// <para>The link</para>
192     /// <para></para>
193     /// </returns>
194     [MethodImpl(MethodImplOptions.AggressiveInlining)]
195     protected override TLinkAddress GetTreeRoot(TLinkAddress link) =>
196         ↪ GetLinkIndexPartReference(link).RootAsTarget;
197
198     /// <summary>
199     /// <para>
200     /// Gets the base part value using the specified link.
201     /// </para>
202     /// <para></para>
203     /// </summary>
204     /// <param name="link">
205     /// <para>The link.</para>
206     /// <para></para>
207     /// </param>
208     /// <returns>
209     /// <para>The link</para>
210     /// <para></para>
211     /// </returns>

```

```

202     /// <para></para>
203     /// </param>
204     /// <returns>
205     /// <para>The link</para>
206     /// <para></para>
207     /// </returns>
208     [MethodImpl(MethodImplOptions.AggressiveInlining)]
209     protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
210         ↪ GetLinkDataPartReference(link).Target;
211
212     /// <summary>
213     /// <para>
214     /// Gets the key part value using the specified link.
215     /// </para>
216     /// <para></para>
217     /// </summary>
218     /// <param name="link">
219     /// <para>The link.</para>
220     /// <para></para>
221     /// </param>
222     /// <returns>
223     /// <para>The link</para>
224     /// <para></para>
225     /// </returns>
226     [MethodImpl(MethodImplOptions.AggressiveInlining)]
227     protected override TLinkAddress GetKeyPartValue(TLinkAddress link) =>
228         ↪ GetLinkDataPartReference(link).Source;
229
230     /// <summary>
231     /// <para>
232     /// Clears the node using the specified node.
233     /// </para>
234     /// <para></para>
235     /// </summary>
236     /// <param name="node">
237     /// <para>The node.</para>
238     /// <para></para>
239     /// </param>
240     [MethodImpl(MethodImplOptions.AggressiveInlining)]
241     protected override void ClearNode(TLinkAddress node)
242     {
243         ref var link = ref GetLinkIndexPartReference(node);
244         link.LeftAsTarget = Zero;
245         link.RightAsTarget = Zero;
246         link.SizeAsTarget = Zero;
247     }
248
249     /// <summary>
250     /// <para>
251     /// Searches the source.
252     /// </para>
253     /// <para></para>
254     /// </summary>
255     /// <param name="source">
256     /// <para>The source.</para>
257     /// <para></para>
258     /// </param>
259     /// <param name="target">
260     /// <para>The target.</para>
261     /// <para></para>
262     /// </param>
263     /// <returns>
264     /// <para>The link</para>
265     /// <para></para>
266     /// </returns>
267     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
268         ↪ SearchCore(GetTreeRoot(target), source);
269 }

```

1.45 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/SplitMemoryLinks.cs

```

1 using System;
2 using System.Runtime.CompilerServices;
3 using Platform.Singletons;
4 using Platform.Memory;
5 using static System.Runtime.CompilerServices.Unsafe;
6
7 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

```

```

8
9 namespace Platform.Data.Doublets.Memory.Split.Generic
10 {
11     /// <summary>
12     /// <para>
13     /// Represents the split memory links.
14     /// </para>
15     /// <para></para>
16     /// </summary>
17     /// <seealso cref="SplitMemoryLinksBase{TLinkAddress}"/>
18     public unsafe class SplitMemoryLinks<TLinkAddress> : SplitMemoryLinksBase<TLinkAddress>
19     {
20         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createInternalSourceTreeMethods;
21         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createExternalSourceTreeMethods;
22         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createInternalTargetTreeMethods;
23         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createExternalTargetTreeMethods;
24         private byte* _header;
25         private byte* _linksDataParts;
26         private byte* _linksIndexParts;
27
28         /// <summary>
29         /// <para>
30         /// Initializes a new <see cref="SplitMemoryLinks"/> instance.
31         /// </para>
32         /// <para></para>
33         /// </summary>
34         /// <param name="dataMemory">
35         /// <para>A data memory.</para>
36         /// <para></para>
37         /// </param>
38         /// <param name="indexMemory">
39         /// <para>A index memory.</para>
40         /// <para></para>
41         /// </param>
42         [MethodImpl(MethodImplOptions.AggressiveInlining)]
43         public SplitMemoryLinks(string dataMemory, string indexMemory) : this(new
44             ↪ FileMappedResizableDirectMemory(dataMemory), new
45             ↪ FileMappedResizableDirectMemory(indexMemory)) { }
46
47         /// <summary>
48         /// <para>
49         /// Initializes a new <see cref="SplitMemoryLinks"/> instance.
50         /// </para>
51         /// <para></para>
52         /// </summary>
53         /// <param name="dataMemory">
54         /// <para>A data memory.</para>
55         /// <para></para>
56         /// </param>
57         /// <param name="indexMemory">
58         /// <para>A index memory.</para>
59         /// <para></para>
60         /// </param>
61         [MethodImpl(MethodImplOptions.AggressiveInlining)]
62         public SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
63             ↪ indexMemory) : this(dataMemory, indexMemory, DefaultLinksSizeStep) { }
64
65         /// <summary>
66         /// <para>
67         /// Initializes a new <see cref="SplitMemoryLinks"/> instance.
68         /// </para>
69         /// <para></para>
70         /// </summary>
71         /// <param name="dataMemory">
72         /// <para>A data memory.</para>
73         /// <para></para>
74         /// </param>
75         /// <param name="indexMemory">
76         /// <para>A index memory.</para>
77         /// <para></para>
78         /// </param>
79         /// <param name="memoryReservationStep">
80         /// <para>A memory reservation step.</para>
81         /// <para></para>
82         /// </param>
83         [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

81 public SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
    ↳ indexMemory, long memoryReservationStep) : this(dataMemory, indexMemory,
    ↳ memoryReservationStep, Default<LinksConstants<TLinkAddress>>.Instance,
    ↳ IndexTreeType.Default, useLinkedList: true) { }
82
83 /// <summary>
84 /// <para>
85 /// Initializes a new <see cref="SplitMemoryLinks"/> instance.
86 /// </para>
87 /// </summary>
88 /// <param name="dataMemory">
89 /// <para>A data memory.</para>
90 /// </param>
91 /// <param name="indexMemory">
92 /// <para>A index memory.</para>
93 /// </param>
94 /// <param name="memoryReservationStep">
95 /// <para>A memory reservation step.</para>
96 /// </param>
97 /// <param name="constants">
98 /// <para>A constants.</para>
99 /// </param>
100 [MethodImpl(MethodImplOptions.AggressiveInlining)]
101 public SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
    ↳ indexMemory, long memoryReservationStep, LinksConstants<TLinkAddress> constants) :
    ↳ this(dataMemory, indexMemory, memoryReservationStep, constants,
    ↳ IndexTreeType.Default, useLinkedList: true) { }
102
103 /// <summary>
104 /// <para>
105 /// Initializes a new <see cref="SplitMemoryLinks"/> instance.
106 /// </para>
107 /// </summary>
108 /// <param name="dataMemory">
109 /// <para>A data memory.</para>
110 /// </param>
111 /// <param name="indexMemory">
112 /// <para>A index memory.</para>
113 /// </param>
114 /// <param name="memoryReservationStep">
115 /// <para>A memory reservation step.</para>
116 /// </param>
117 /// <param name="constants">
118 /// <para>A constants.</para>
119 /// </param>
120 /// <param name="indexTreeType">
121 /// <para>A index tree type.</para>
122 /// </param>
123 /// <param name="useLinkedList">
124 /// <para>A use linked list.</para>
125 /// </param>
126 [MethodImpl(MethodImplOptions.AggressiveInlining)]
127 public SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
    ↳ indexMemory, long memoryReservationStep, LinksConstants<TLinkAddress> constants,
    ↳ IndexTreeType indexTreeType, bool useLinkedList) : base(dataMemory, indexMemory,
    ↳ memoryReservationStep, constants, useLinkedList)
128 {
129     if (indexTreeType == IndexTreeType.SizeBalancedTree)
130     {
131         _createInternalSourceTreeMethods = () => new
            ↳ InternalLinksSourcesSizeBalancedTreeMethods<TLinkAddress>(Constants,
            ↳ _linksDataParts, _linksIndexParts, _header);
132         _createExternalSourceTreeMethods = () => new
            ↳ ExternalLinksSourcesSizeBalancedTreeMethods<TLinkAddress>(Constants,
            ↳ _linksDataParts, _linksIndexParts, _header);
133     }
134 }
135
136
137
138
139
140
141
142
143
144

```



```

145         _createInternalTargetTreeMethods = () => new
            ↳ InternalLinksTargetsSizeBalancedTreeMethods<TLinkAddress>(Constants,
            ↳ _linksDataParts, _linksIndexParts, _header);
146         _createExternalTargetTreeMethods = () => new
            ↳ ExternalLinksTargetsSizeBalancedTreeMethods<TLinkAddress>(Constants,
            ↳ _linksDataParts, _linksIndexParts, _header);
147     }
148     else
149     {
150         _createInternalSourceTreeMethods = () => new InternalLinksSourcesRecursionlessSi
            ↳ zeBalancedTreeMethods<TLinkAddress>(Constants, _linksDataParts,
            ↳ _linksIndexParts, _header);
151         _createExternalSourceTreeMethods = () => new ExternalLinksSourcesRecursionlessSi
            ↳ zeBalancedTreeMethods<TLinkAddress>(Constants, _linksDataParts,
            ↳ _linksIndexParts, _header);
152         _createInternalTargetTreeMethods = () => new InternalLinksTargetsRecursionlessSi
            ↳ zeBalancedTreeMethods<TLinkAddress>(Constants, _linksDataParts,
            ↳ _linksIndexParts, _header);
153         _createExternalTargetTreeMethods = () => new ExternalLinksTargetsRecursionlessSi
            ↳ zeBalancedTreeMethods<TLinkAddress>(Constants, _linksDataParts,
            ↳ _linksIndexParts, _header);
154     }
155     Init(dataMemory, indexMemory);
156 }
157
158 /// <summary>
159 /// <para>
160 /// Sets the pointers using the specified data memory.
161 /// </para>
162 /// <para></para>
163 /// </summary>
164 /// <param name="dataMemory">
165 /// <para>The data memory.</para>
166 /// <para></para>
167 /// </param>
168 /// <param name="indexMemory">
169 /// <para>The index memory.</para>
170 /// <para></para>
171 /// </param>
172 [MethodImpl(MethodImplOptions.AggressiveInlining)]
173 protected override void SetPointers(IResizableDirectMemory dataMemory,
    ↳ IResizableDirectMemory indexMemory)
174 {
175     _linksDataParts = (byte*)dataMemory.Pointer;
176     _linksIndexParts = (byte*)indexMemory.Pointer;
177     _header = _linksIndexParts;
178     if (_useLinkedList)
179     {
180         InternalSourcesListMethods = new
            ↳ InternalLinksSourcesLinkedListMethods<TLinkAddress>(Constants,
            ↳ _linksDataParts, _linksIndexParts);
181     }
182     else
183     {
184         InternalSourcesTreeMethods = _createInternalSourceTreeMethods();
185     }
186     ExternalSourcesTreeMethods = _createExternalSourceTreeMethods();
187     InternalTargetsTreeMethods = _createInternalTargetTreeMethods();
188     ExternalTargetsTreeMethods = _createExternalTargetTreeMethods();
189     UnusedLinksListMethods = new UnusedLinksListMethods<TLinkAddress>(_linksDataParts,
        ↳ _header);
190 }
191
192 /// <summary>
193 /// <para>
194 /// Resets the pointers.
195 /// </para>
196 /// <para></para>
197 /// </summary>
198 [MethodImpl(MethodImplOptions.AggressiveInlining)]
199 protected override void ResetPointers()
200 {
201     base.ResetPointers();
202     _linksDataParts = null;
203     _linksIndexParts = null;
204     _header = null;
205 }
206

```

```

207     /// <summary>
208     /// <para>
209     /// Gets the header reference.
210     /// </para>
211     /// <para></para>
212     /// </summary>
213     /// <returns>
214     /// <para>A ref links header of t link</para>
215     /// <para></para>
216     /// </returns>
217     [MethodImpl(MethodImplOptions.AggressiveInlining)]
218     protected override ref LinksHeader<TLinkAddress> GetHeaderReference() => ref
        ↳ AsRef<LinksHeader<TLinkAddress>>(_header);
219
220     /// <summary>
221     /// <para>
222     /// Gets the link data part reference using the specified link index.
223     /// </para>
224     /// <para></para>
225     /// </summary>
226     /// <param name="linkIndex">
227     /// <para>The link index.</para>
228     /// <para></para>
229     /// </param>
230     /// <returns>
231     /// <para>A ref raw link data part of t link</para>
232     /// <para></para>
233     /// </returns>
234     [MethodImpl(MethodImplOptions.AggressiveInlining)]
235     protected override ref RawLinkDataPart<TLinkAddress>
        ↳ GetLinkDataPartReference(TLinkAddress linkIndex) => ref
        ↳ AsRef<RawLinkDataPart<TLinkAddress>>(_linksDataParts + (LinkDataPartSizeInBytes *
        ↳ ConvertToInt64(linkIndex)));
236
237     /// <summary>
238     /// <para>
239     /// Gets the link index part reference using the specified link index.
240     /// </para>
241     /// <para></para>
242     /// </summary>
243     /// <param name="linkIndex">
244     /// <para>The link index.</para>
245     /// <para></para>
246     /// </param>
247     /// <returns>
248     /// <para>A ref raw link index part of t link</para>
249     /// <para></para>
250     /// </returns>
251     [MethodImpl(MethodImplOptions.AggressiveInlining)]
252     protected override ref RawLinkIndexPart<TLinkAddress>
        ↳ GetLinkIndexPartReference(TLinkAddress linkIndex) => ref
        ↳ AsRef<RawLinkIndexPart<TLinkAddress>>(_linksIndexParts + (LinkIndexPartSizeInBytes *
        ↳ ConvertToInt64(linkIndex)));
253 }
254 }

```

1.46 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/SplitMemoryLinksBase.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Disposables;
5  using Platform.Singletons;
6  using Platform.Converters;
7  using Platform.Numbers;
8  using Platform.Memory;
9  using Platform.Data.Exceptions;
10 using Platform.Delegates;
11
12 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
13
14 namespace Platform.Data.Doublets.Memory.Split.Generic
15 {
16     /// <summary>
17     /// <para>
18     /// Represents the split memory links base.
19     /// </para>
20     /// <para></para>
21     /// </summary>
22     /// <seealso cref="DisposableBase"/>

```

```

23  /// <seealso cref="TLinks{TLinkAddress}"/>
24  public abstract class SplitMemoryLinksBase<TLinkAddress> : DisposableBase,
    ↳ ILinks<TLinkAddress> where TLinkAddress : struct
25  {
26      private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
    ↳ EqualityComparer<TLinkAddress>.Default;
27      private static readonly Comparer<TLinkAddress> _comparer =
    ↳ Comparer<TLinkAddress>.Default;
28      private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
    ↳ = UncheckedConverter<TLinkAddress, long>.Default;
29      private static readonly UncheckedConverter<long, TLinkAddress> _int64ToAddressConverter
    ↳ = UncheckedConverter<long, TLinkAddress>.Default;
30      private static readonly TLinkAddress _zero = default;
31      private static readonly TLinkAddress _one = Arithmetic.Increment(_zero);
32
33      /// <summary>Возвращает размер одной связи в байтах.</summary>
34      /// <remarks>
35      /// Используется только во вне класса, не рекомендуется использовать внутри.
36      /// Так как во вне не обязательно будет доступен unsafe C#.
37      /// </remarks>
38      public static readonly long LinkDataPartSizeInBytes =
    ↳ RawLinkDataPart<TLinkAddress>.SizeInBytes;
39
40      /// <summary>
41      /// <para>
42      /// The size in bytes.
43      /// </para>
44      /// <para></para>
45      /// </summary>
46      public static readonly long LinkIndexPartSizeInBytes =
    ↳ RawLinkIndexPart<TLinkAddress>.SizeInBytes;
47
48      /// <summary>
49      /// <para>
50      /// The size in bytes.
51      /// </para>
52      /// <para></para>
53      /// </summary>
54      public static readonly long LinkHeaderSizeInBytes =
    ↳ LinksHeader<TLinkAddress>.SizeInBytes;
55
56      /// <summary>
57      /// <para>
58      /// The default links size step.
59      /// </para>
60      /// <para></para>
61      /// </summary>
62      public static readonly long DefaultLinksSizeStep = 1 * 1024 * 1024;
63
64      /// <summary>
65      /// <para>
66      /// The data memory.
67      /// </para>
68      /// <para></para>
69      /// </summary>
70      protected readonly IResizableDirectMemory _dataMemory;
71      /// <summary>
72      /// <para>
73      /// The index memory.
74      /// </para>
75      /// <para></para>
76      /// </summary>
77      protected readonly IResizableDirectMemory _indexMemory;
78      /// <summary>
79      /// <para>
80      /// The use linked list.
81      /// </para>
82      /// <para></para>
83      /// </summary>
84      protected readonly bool _useLinkedList;
85      /// <summary>
86      /// <para>
87      /// The data memory reservation step in bytes.
88      /// </para>
89      /// <para></para>
90      /// </summary>
91      protected readonly long _dataMemoryReservationStepInBytes;
92      /// <summary>
93      /// <para>

```

```

94     /// The index memory reservation step in bytes.
95     /// </para>
96     /// <para></para>
97     /// </summary>
98     protected readonly long _indexMemoryReservationStepInBytes;
99
100    /// <summary>
101    /// <para>
102    /// The internal sources list methods.
103    /// </para>
104    /// <para></para>
105    /// </summary>
106    protected InternalLinksSourcesLinkedListMethods<TLinkAddress> InternalSourcesListMethods;
107    /// <summary>
108    /// <para>
109    /// The internal sources tree methods.
110    /// </para>
111    /// <para></para>
112    /// </summary>
113    protected ILinksTreeMethods<TLinkAddress> InternalSourcesTreeMethods;
114    /// <summary>
115    /// <para>
116    /// The external sources tree methods.
117    /// </para>
118    /// <para></para>
119    /// </summary>
120    protected ILinksTreeMethods<TLinkAddress> ExternalSourcesTreeMethods;
121    /// <summary>
122    /// <para>
123    /// The internal targets tree methods.
124    /// </para>
125    /// <para></para>
126    /// </summary>
127    protected ILinksTreeMethods<TLinkAddress> InternalTargetsTreeMethods;
128    /// <summary>
129    /// <para>
130    /// The external targets tree methods.
131    /// </para>
132    /// <para></para>
133    /// </summary>
134    protected ILinksTreeMethods<TLinkAddress> ExternalTargetsTreeMethods;
135    /// TODO: Возможно чтобы гарантированно проверять на то, является ли связь удалённой,
136    //      → нужно использовать не список а дерево, так как так можно быстрее проверить на
137    //      → наличие связи внутри
138    /// <summary>
139    /// <para>
140    /// The unused links list methods.
141    /// </para>
142    /// <para></para>
143    /// </summary>
144    protected ILinksListMethods<TLinkAddress> UnusedLinksListMethods;
145
146    /// <summary>
147    /// Возвращает общее число связей находящихся в хранилище.
148    /// </summary>
149    protected virtual TLinkAddress Total
150    {
151        [MethodImpl(MethodImplOptions.AggressiveInlining)]
152        get
153        {
154            ref var header = ref GetHeaderReference();
155            return Subtract(header.AllocatedLinks, header.FreeLinks);
156        }
157    }
158
159    /// <summary>
160    /// <para>
161    /// Gets the constants value.
162    /// </para>
163    /// <para></para>
164    /// </summary>
165    public virtual LinksConstants<TLinkAddress> Constants
166    {
167        [MethodImpl(MethodImplOptions.AggressiveInlining)]
168        get;
169    }
170
171    /// <summary>
172    /// <para>

```

```

171     /// Initializes a new <see cref="SplitMemoryLinksBase"/> instance.
172     /// </para>
173     /// </summary>
174     /// <param name="dataMemory">
175     /// <para>A data memory.</para>
176     /// </param>
177     /// <param name="indexMemory">
178     /// <para>A index memory.</para>
179     /// </param>
180     /// <param name="memoryReservationStep">
181     /// <para>A memory reservation step.</para>
182     /// </param>
183     /// <param name="constants">
184     /// <para>A constants.</para>
185     /// </param>
186     /// <param name="useLinkedList">
187     /// <para>A use linked list.</para>
188     /// </param>
189     [MethodImpl(MethodImplOptions.AggressiveInlining)]
190     protected SplitMemoryLinksBase(IResizableDirectMemory dataMemory, IResizableDirectMemory
191     ↪ indexMemory, long memoryReservationStep, LinksConstants<TLinkAddress> constants,
192     ↪ bool useLinkedList)
193     {
194         _dataMemory = dataMemory;
195         _indexMemory = indexMemory;
196         _dataMemoryReservationStepInBytes = memoryReservationStep * LinkDataPartSizeInBytes;
197         _indexMemoryReservationStepInBytes = memoryReservationStep *
198         ↪ LinkIndexPartSizeInBytes;
199         _useLinkedList = useLinkedList;
200         Constants = constants;
201     }
202
203     /// <summary>
204     /// <para>
205     /// Initializes a new <see cref="SplitMemoryLinksBase"/> instance.
206     /// </para>
207     /// </summary>
208     /// <param name="dataMemory">
209     /// <para>A data memory.</para>
210     /// </param>
211     /// <param name="indexMemory">
212     /// <para>A index memory.</para>
213     /// </param>
214     /// <param name="memoryReservationStep">
215     /// <para>A memory reservation step.</para>
216     /// </param>
217     [MethodImpl(MethodImplOptions.AggressiveInlining)]
218     protected SplitMemoryLinksBase(IResizableDirectMemory dataMemory, IResizableDirectMemory
219     ↪ indexMemory, long memoryReservationStep) : this(dataMemory, indexMemory,
220     ↪ memoryReservationStep, Default<LinksConstants<TLinkAddress>>.Instance,
221     ↪ useLinkedList: true) { }
222
223     /// <summary>
224     /// <para>
225     /// Inits the data memory.
226     /// </para>
227     /// </summary>
228     /// <param name="dataMemory">
229     /// <para>The data memory.</para>
230     /// </param>
231     /// <param name="indexMemory">
232     /// <para>The index memory.</para>
233     /// </param>
234     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

242 protected virtual void Init(IResizableDirectMemory dataMemory, IResizableDirectMemory
    ↪ indexMemory)
243 {
244     // Read allocated links from header
245     if (indexMemory.ReservedCapacity < LinkHeaderSizeInBytes)
246     {
247         indexMemory.ReservedCapacity = LinkHeaderSizeInBytes;
248     }
249     SetPointers(dataMemory, indexMemory);
250     ref var header = ref GetHeaderReference();
251     var allocatedLinks = ConvertToInt64(header.AllocatedLinks);
252     // Adjust reserved capacity
253     var minimumDataReservedCapacity = allocatedLinks * LinkDataPartSizeInBytes;
254     if (minimumDataReservedCapacity < dataMemory.UsedCapacity)
255     {
256         minimumDataReservedCapacity = dataMemory.UsedCapacity;
257     }
258     if (minimumDataReservedCapacity < _dataMemoryReservationStepInBytes)
259     {
260         minimumDataReservedCapacity = _dataMemoryReservationStepInBytes;
261     }
262     var minimumIndexReservedCapacity = allocatedLinks * LinkDataPartSizeInBytes;
263     if (minimumIndexReservedCapacity < indexMemory.UsedCapacity)
264     {
265         minimumIndexReservedCapacity = indexMemory.UsedCapacity;
266     }
267     if (minimumIndexReservedCapacity < _indexMemoryReservationStepInBytes)
268     {
269         minimumIndexReservedCapacity = _indexMemoryReservationStepInBytes;
270     }
271     // Check for alignment
272     if (minimumDataReservedCapacity % _dataMemoryReservationStepInBytes > 0)
273     {
274         minimumDataReservedCapacity = ((minimumDataReservedCapacity /
    ↪ _dataMemoryReservationStepInBytes) * _dataMemoryReservationStepInBytes) +
    ↪ _dataMemoryReservationStepInBytes;
275     }
276     if (minimumIndexReservedCapacity % _indexMemoryReservationStepInBytes > 0)
277     {
278         minimumIndexReservedCapacity = ((minimumIndexReservedCapacity /
    ↪ _indexMemoryReservationStepInBytes) * _indexMemoryReservationStepInBytes) +
    ↪ _indexMemoryReservationStepInBytes;
279     }
280     if (dataMemory.ReservedCapacity != minimumDataReservedCapacity)
281     {
282         dataMemory.ReservedCapacity = minimumDataReservedCapacity;
283     }
284     if (indexMemory.ReservedCapacity != minimumIndexReservedCapacity)
285     {
286         indexMemory.ReservedCapacity = minimumIndexReservedCapacity;
287     }
288     SetPointers(dataMemory, indexMemory);
289     header = ref GetHeaderReference();
290     // Ensure correctness _memory.UsedCapacity over _header->AllocatedLinks
291     // Гарантия корректности _memory.UsedCapacity относительно _header->AllocatedLinks
292     dataMemory.UsedCapacity = (ConvertToInt64(header.AllocatedLinks) *
    ↪ LinkDataPartSizeInBytes) + LinkDataPartSizeInBytes; // First link is read only
    ↪ zero link.
293     indexMemory.UsedCapacity = (ConvertToInt64(header.AllocatedLinks) *
    ↪ LinkIndexPartSizeInBytes) + LinkHeaderSizeInBytes;
294     // Ensure correctness _memory.ReservedLinks over _header->ReservedCapacity
295     // Гарантия корректности _header->ReservedLinks относительно _memory.ReservedCapacity
296     header.ReservedLinks = ConvertToAddress((dataMemory.ReservedCapacity -
    ↪ LinkDataPartSizeInBytes) / LinkDataPartSizeInBytes);
297 }
298
299 /// <summary>
300 /// <para>
301 /// Counts the substitution.
302 /// </para>
303 /// <para></para>
304 /// </summary>
305 /// <param name="restriction">
306 /// <para>The substitution.</para>
307 /// <para></para>
308 /// </param>
309 /// <exception cref="NotSupportedException">
310 /// <para>Другие размеры и способы ограничений не поддерживаются.</para>

```

```

311 /// <para></para>
312 /// </exception>
313 /// <returns>
314 /// <para>The link</para>
315 /// <para></para>
316 /// </returns>
317 [MethodImpl(MethodImplOptions.AggressiveInlining)]
318 public virtual TLinkAddress Count(ICollection<TLinkAddress>? restriction)
319 {
320     // Если нет ограничений, тогда возвращаем общее число связей находящихся в хранилище.
321     if (restriction.Count == 0)
322     {
323         return Total;
324     }
325     var constants = Constants;
326     var any = constants.Any;
327     var index = this.GetIndex(restriction);
328     if (restriction.Count == 1)
329     {
330         if (AreEqual(index, any))
331         {
332             return Total;
333         }
334         return Exists(index) ? GetOne() : GetZero();
335     }
336     if (restriction.Count == 2)
337     {
338         var value = restriction[1];
339         if (AreEqual(index, any))
340         {
341             if (AreEqual(value, any))
342             {
343                 return Total; // Any - как отсутствие ограничения
344             }
345             var externalReferencesRange = constants.ExternalReferencesRange;
346             if (externalReferencesRange.HasValue &&
347                 ↪ externalReferencesRange.Value.Contains(value))
348             {
349                 return Add(ExternalSourcesTreeMethods.CountUsages(value),
350                     ↪ ExternalTargetsTreeMethods.CountUsages(value));
351             }
352             else
353             {
354                 if (_useLinkedList)
355                 {
356                     return Add(InternalSourcesListMethods.CountUsages(value),
357                         ↪ InternalTargetsTreeMethods.CountUsages(value));
358                 }
359                 else
360                 {
361                     return Add(InternalSourcesTreeMethods.CountUsages(value),
362                         ↪ InternalTargetsTreeMethods.CountUsages(value));
363                 }
364             }
365         }
366         else
367         {
368             if (!Exists(index))
369             {
370                 return GetZero();
371             }
372             if (AreEqual(value, any))
373             {
374                 return GetOne();
375             }
376             ref var storedLinkValue = ref GetLinkDataPartReference(index);
377             if (AreEqual(storedLinkValue.Source, value) ||
378                 ↪ AreEqual(storedLinkValue.Target, value))
379             {
380                 return GetOne();
381             }
382             return GetZero();
383         }
384     }
385     if (restriction.Count == 3)
386     {
387         var externalReferencesRange = constants.ExternalReferencesRange;
388         var source = this.GetSource(restriction);

```

```

384 var target = this.GetTarget(restriction);
385 if (AreEqual(index, any))
386 {
387     if (AreEqual(source, any) && AreEqual(target, any))
388     {
389         return Total;
390     }
391     else if (AreEqual(source, any))
392     {
393         if (externalReferencesRange.HasValue &&
394             ↪ externalReferencesRange.Value.Contains(target))
395         {
396             return ExternalTargetsTreeMethods.CountUsages(target);
397         }
398         else
399         {
400             return InternalTargetsTreeMethods.CountUsages(target);
401         }
402     }
403     else if (AreEqual(target, any))
404     {
405         if (externalReferencesRange.HasValue &&
406             ↪ externalReferencesRange.Value.Contains(source))
407         {
408             return ExternalSourcesTreeMethods.CountUsages(source);
409         }
410         else
411         {
412             if (_useLinkedList)
413             {
414                 return InternalSourcesListMethods.CountUsages(source);
415             }
416             else
417             {
418                 return InternalSourcesTreeMethods.CountUsages(source);
419             }
420         }
421     }
422     else //if(source != Any && target != Any)
423     {
424         // ЭКВИВАЛЕНТ Exists(source, target) => Count(Any, source, target) > 0
425         TLinkAddress link;
426         if (externalReferencesRange.HasValue)
427         {
428             if (externalReferencesRange.Value.Contains(source) &&
429                 ↪ externalReferencesRange.Value.Contains(target))
430             {
431                 link = ExternalSourcesTreeMethods.Search(source, target);
432             }
433             else if (externalReferencesRange.Value.Contains(source))
434             {
435                 link = InternalTargetsTreeMethods.Search(source, target);
436             }
437             else if (externalReferencesRange.Value.Contains(target))
438             {
439                 if (_useLinkedList)
440                 {
441                     link = ExternalSourcesTreeMethods.Search(source, target);
442                 }
443                 else
444                 {
445                     link = InternalSourcesTreeMethods.Search(source, target);
446                 }
447             }
448             else
449             {
450                 if (_useLinkedList ||
451                     ↪ GreaterThan(InternalSourcesTreeMethods.CountUsages(source),
452                     ↪ InternalTargetsTreeMethods.CountUsages(target)))
453                 {
454                     link = InternalTargetsTreeMethods.Search(source, target);
455                 }
456                 else
457                 {
458                     link = InternalSourcesTreeMethods.Search(source, target);
459                 }
460             }
461         }
462     }
463 }

```



```

457         else
458         {
459             if (_useLinkedList ||
460                 ⇨ GreaterThan(InternalSourcesTreeMethods.CountUsages(source),
461                 ⇨ InternalTargetsTreeMethods.CountUsages(target)))
462             {
463                 link = InternalTargetsTreeMethods.Search(source, target);
464             }
465             else
466             {
467                 link = InternalSourcesTreeMethods.Search(source, target);
468             }
469             return AreEqual(link, constants.Null) ? GetZero() : GetOne();
470         }
471     }
472     else
473     {
474         if (!Exists(index))
475         {
476             return GetZero();
477         }
478         if (AreEqual(source, any) && AreEqual(target, any))
479         {
480             return GetOne();
481         }
482         ref var storedLinkValue = ref GetLinkDataPartReference(index);
483         if (!AreEqual(source, any) && !AreEqual(target, any))
484         {
485             if (AreEqual(storedLinkValue.Source, source) &&
486                 ⇨ AreEqual(storedLinkValue.Target, target))
487             {
488                 return GetOne();
489             }
490             return GetZero();
491         }
492         var value = default(TLinkAddress);
493         if (AreEqual(source, any))
494         {
495             value = target;
496         }
497         if (AreEqual(target, any))
498         {
499             value = source;
500         }
501         if (AreEqual(storedLinkValue.Source, value) ||
502             ⇨ AreEqual(storedLinkValue.Target, value))
503         {
504             return GetOne();
505         }
506         return GetZero();
507     }
508 }
509 throw new NotSupportedException("Другие размеры и способы ограничений не
510 ⇨ поддерживаются.");
511 }
512
513 /// <summary>
514 /// <para>
515 /// Eaches the handler.
516 /// </para>
517 /// <para></para>
518 /// </summary>
519 /// <param name="handler">
520 /// <para>The handler.</para>
521 /// <para></para>
522 /// </param>
523 /// <param name="restriction">
524 /// <para>The substitution.</para>
525 /// <para></para>
526 /// </param>
527 /// <exception cref="NotSupportedException">
528 /// <para>Другие размеры и способы ограничений не поддерживаются.</para>
529 /// <para></para>
530 /// </exception>
531 /// <returns>
532 /// <para>The link</para>
533 /// <para></para>

```

```

530 /// </returns>
531 [MethodImpl(MethodImplOptions.AggressiveInlining)]
532 public virtual TLinkAddress Each(ICollection<TLinkAddress>? restriction,
    ↳ ReadHandler<TLinkAddress>? handler)
533 {
534     var constants = Constants;
535     var @break = constants.Break;
536     if (restriction.Count == 0)
537     {
538         for (var link = GetOne(); LessOrEqualThan(link,
    ↳ GetHeaderReference().AllocatedLinks); link = Increment(link))
539         {
540             if (Exists(link) && AreEqual(handler(GetLinkStruct(link)), @break))
541             {
542                 return @break;
543             }
544         }
545         return @break;
546     }
547     var @continue = constants.Continue;
548     var any = constants.Any;
549     var index = this.GetIndex(restriction);
550     if (restriction.Count == 1)
551     {
552         if (AreEqual(index, any))
553         {
554             return Each(Array.Empty<TLinkAddress>(), handler);
555         }
556         if (!Exists(index))
557         {
558             return @continue;
559         }
560         return handler(GetLinkStruct(index));
561     }
562     if (restriction.Count == 2)
563     {
564         var value = restriction[1];
565         if (AreEqual(index, any))
566         {
567             if (AreEqual(value, any))
568             {
569                 return Each(Array.Empty<TLinkAddress>(), handler);
570             }
571             if (AreEqual(Each(new Link<TLinkAddress>(index, value, any), handler),
    ↳ @break))
572             {
573                 return @break;
574             }
575             return Each(new Link<TLinkAddress>(index, any, value), handler);
576         }
577         else
578         {
579             if (!Exists(index))
580             {
581                 return @continue;
582             }
583             if (AreEqual(value, any))
584             {
585                 return handler(GetLinkStruct(index));
586             }
587             ref var storedLinkValue = ref GetLinkDataPartReference(index);
588             if (AreEqual(storedLinkValue.Source, value) ||
    AreEqual(storedLinkValue.Target, value))
589             {
590                 return handler(GetLinkStruct(index));
591             }
592             return @continue;
593         }
594     }
595 }
596 if (restriction.Count == 3)
597 {
598     var externalReferencesRange = constants.ExternalReferencesRange;
599     var source = this.GetSource(restriction);
600     var target = this.GetTarget(restriction);
601     if (AreEqual(index, any))
602     {
603         if (AreEqual(source, any) && AreEqual(target, any))
604         {

```

```

605         return Each(Array.Empty<TLinkAddress>(), handler);
606     }
607     else if (AreEqual(source, any))
608     {
609         if (externalReferencesRange.HasValue &&
610             ↪ externalReferencesRange.Value.Contains(target))
611         {
612             return ExternalTargetsTreeMethods.EachUsage(target, handler);
613         }
614         else
615         {
616             return InternalTargetsTreeMethods.EachUsage(target, handler);
617         }
618     }
619     else if (AreEqual(target, any))
620     {
621         if (externalReferencesRange.HasValue &&
622             ↪ externalReferencesRange.Value.Contains(source))
623         {
624             return ExternalSourcesTreeMethods.EachUsage(source, handler);
625         }
626         else
627         {
628             if (_useLinkedList)
629             {
630                 return InternalSourcesListMethods.EachUsage(source, handler);
631             }
632             else
633             {
634                 return InternalSourcesTreeMethods.EachUsage(source, handler);
635             }
636         }
637     }
638     else //if(source != Any && target != Any)
639     {
640         TLinkAddress link;
641         if (externalReferencesRange.HasValue)
642         {
643             if (externalReferencesRange.Value.Contains(source) &&
644                 ↪ externalReferencesRange.Value.Contains(target))
645             {
646                 link = ExternalSourcesTreeMethods.Search(source, target);
647             }
648             else if (externalReferencesRange.Value.Contains(source))
649             {
650                 link = InternalTargetsTreeMethods.Search(source, target);
651             }
652             else if (externalReferencesRange.Value.Contains(target))
653             {
654                 if (_useLinkedList)
655                 {
656                     link = ExternalSourcesTreeMethods.Search(source, target);
657                 }
658                 else
659                 {
660                     link = InternalSourcesTreeMethods.Search(source, target);
661                 }
662             }
663             else
664             {
665                 if (_useLinkedList ||
666                     ↪ GreaterThan(InternalSourcesTreeMethods.CountUsages(source),
667                     ↪ InternalTargetsTreeMethods.CountUsages(target)))
668                 {
669                     link = InternalTargetsTreeMethods.Search(source, target);
670                 }
671                 else
672                 {
673                     link = InternalSourcesTreeMethods.Search(source, target);
674                 }
675             }
676         }
677         else
678         {
679             if (_useLinkedList ||
680                 ↪ GreaterThan(InternalSourcesTreeMethods.CountUsages(source),
681                 ↪ InternalTargetsTreeMethods.CountUsages(target)))
682             {
683                 link = InternalTargetsTreeMethods.Search(source, target);
684             }
685             else
686             {
687                 link = InternalSourcesTreeMethods.Search(source, target);
688             }
689         }
690     }
691     return link;
692 }

```

```

676         link = InternalTargetsTreeMethods.Search(source, target);
677     }
678     else
679     {
680         link = InternalSourcesTreeMethods.Search(source, target);
681     }
682 }
683 return AreEqual(link, constants.Null) ? @continue :
    ↪ handler(GetLinkStruct(link));
684 }
685 }
686 else
687 {
688     if (!Exists(index))
689     {
690         return @continue;
691     }
692     if (AreEqual(source, any) && AreEqual(target, any))
693     {
694         return handler(GetLinkStruct(index));
695     }
696     ref var storedLinkValue = ref GetLinkDataPartReference(index);
697     if (!AreEqual(source, any) && !AreEqual(target, any))
698     {
699         if (AreEqual(storedLinkValue.Source, source) &&
700             AreEqual(storedLinkValue.Target, target))
701         {
702             return handler(GetLinkStruct(index));
703         }
704         return @continue;
705     }
706     var value = default(TLinkAddress);
707     if (AreEqual(source, any))
708     {
709         value = target;
710     }
711     if (AreEqual(target, any))
712     {
713         value = source;
714     }
715     if (AreEqual(storedLinkValue.Source, value) ||
716         AreEqual(storedLinkValue.Target, value))
717     {
718         return handler(GetLinkStruct(index));
719     }
720     return @continue;
721 }
722 }
723 throw new NotSupportedException("Другие размеры и способы ограничений не
    ↪ поддерживаются.");
724 }
725
726 /// <remarks>
727 /// TODO: Возможно можно перемещать значения, если указан индекс, но значение существует
    ↪ в другом месте (но не в менеджере памяти, а в логике Links)
728 /// </remarks>
729 [MethodImpl(MethodImplOptions.AggressiveInlining)]
730 public virtual TLinkAddress Update(IList<TLinkAddress>? restriction,
    ↪ IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler)
731 {
732     var constants = Constants;
733     var @null = constants.Null;
734     var externalReferencesRange = constants.ExternalReferencesRange;
735     var linkIndex = this.GetIndex(restriction);
736     var before = GetLinkStruct(linkIndex);
737     ref var link = ref GetLinkDataPartReference(linkIndex);
738     var source = link.Source;
739     var target = link.Target;
740     ref var header = ref GetHeaderReference();
741     ref var rootAsSource = ref header.RootAsSource;
742     ref var rootAsTarget = ref header.RootAsTarget;
743     // Будет корректно работать только в том случае, если пространство выделенной связи
    ↪ предварительно заполнено нулями
744     if (!AreEqual(source, @null))
745     {
746         if (externalReferencesRange.HasValue &&
    ↪ externalReferencesRange.Value.Contains(source))
747         {

```

```

748         ExternalSourcesTreeMethods.Detach(ref rootAsSource, linkIndex);
749     }
750     else
751     {
752         if (_useLinkedList)
753         {
754             InternalSourcesListMethods.Detach(source, linkIndex);
755         }
756         else
757         {
758             InternalSourcesTreeMethods.Detach(ref
759                 ↪ GetLinkIndexPartReference(source).RootAsSource, linkIndex);
760         }
761     }
762     if (!AreEqual(target, @null))
763     {
764         if (externalReferencesRange.HasValue &&
765             ↪ externalReferencesRange.Value.Contains(target))
766         {
767             ExternalTargetsTreeMethods.Detach(ref rootAsTarget, linkIndex);
768         }
769         else
770         {
771             InternalTargetsTreeMethods.Detach(ref
772                 ↪ GetLinkIndexPartReference(target).RootAsTarget, linkIndex);
773         }
774     }
775     source = link.Source = this.GetSource(substitution);
776     target = link.Target = this.GetTarget(substitution);
777     if (!AreEqual(source, @null))
778     {
779         if (externalReferencesRange.HasValue &&
780             ↪ externalReferencesRange.Value.Contains(source))
781         {
782             ExternalSourcesTreeMethods.Attach(ref rootAsSource, linkIndex);
783         }
784         else
785         {
786             if (_useLinkedList)
787             {
788                 InternalSourcesListMethods.AttachAsLast(source, linkIndex);
789             }
790             else
791             {
792                 InternalSourcesTreeMethods.Attach(ref
793                     ↪ GetLinkIndexPartReference(source).RootAsSource, linkIndex);
794             }
795         }
796     }
797     if (!AreEqual(target, @null))
798     {
799         if (externalReferencesRange.HasValue &&
800             ↪ externalReferencesRange.Value.Contains(target))
801         {
802             ExternalTargetsTreeMethods.Attach(ref rootAsTarget, linkIndex);
803         }
804         else
805         {
806             InternalTargetsTreeMethods.Attach(ref
807                 ↪ GetLinkIndexPartReference(target).RootAsTarget, linkIndex);
808         }
809     }
810     return handler?.Invoke(before, new Link<TLinkAddress>(linkIndex, source, target)) ??
811         ↪ Constants.Continue;
812 }
813
814 /// <remarks>
815 /// TODO: Возможно нужно будет заполнение нулями, если внешнее API ими не заполняет
816 ↪ пространство
817 /// </remarks>
818 [MethodImpl(MethodImplOptions.AggressiveInlining)]
819 public virtual TLinkAddress Create(ICollection<TLinkAddress>? substitution,
820     ↪ WriteHandler<TLinkAddress>? handler)
821 {
822     ref var header = ref GetHeaderReference();
823     var freeLink = header.FirstFreeLink;
824     if (!AreEqual(freeLink, Constants.Null))

```

```

816 {
817     UnusedLinksListMethods.Detach(freeLink);
818 }
819 else
820 {
821     var maximumPossibleInnerReference = Constants.InternalReferencesRange.Maximum;
822     if (GreaterThan(header.AllocatedLinks, maximumPossibleInnerReference))
823     {
824         throw new
825             ↳ LinksLimitReachedException<TLinkAddress>(maximumPossibleInnerReference);
826     }
827     if (GreaterOrEqualThan(header.AllocatedLinks, Decrement(header.ReservedLinks)))
828     {
829         _dataMemory.ReservedCapacity += _dataMemory.ReservationStepInBytes;
830         _indexMemory.ReservedCapacity += _indexMemory.ReservationStepInBytes;
831         SetPointers(_dataMemory, _indexMemory);
832         header = ref GetHeaderReference();
833         header.ReservedLinks = ConvertToAddress(_dataMemory.ReservedCapacity /
834             ↳ LinkDataPartSizeInBytes);
835     }
836     freeLink = header.AllocatedLinks = Increment(header.AllocatedLinks);
837     _dataMemory.UsedCapacity += LinkDataPartSizeInBytes;
838     _indexMemory.UsedCapacity += LinkIndexPartSizeInBytes;
839 }
840 return handler?.Invoke(null, GetLinkStruct(freeLink)) ?? Constants.Continue;
841 }
842
843 /// <summary>
844 /// <para>
845 /// Deletes the substitution.
846 /// </para>
847 /// <para></para>
848 /// </summary>
849 /// <param name="restriction">
850 /// <para>The substitution.</para>
851 /// <para></para>
852 /// </param>
853 [MethodImpl(MethodImplOptions.AggressiveInlining)]
854 public virtual TLinkAddress Delete(ICollection<TLinkAddress>? restriction,
855     ↳ WriteHandler<TLinkAddress>? handler)
856 {
857     ref var header = ref GetHeaderReference();
858     var link = restriction[Constants.IndexPart];
859     var before = GetLinkStruct(link);
860     if (LessThan(link, header.AllocatedLinks))
861     {
862         UnusedLinksListMethods.AttachAsFirst(link);
863     }
864     else if (AreEqual(link, header.AllocatedLinks))
865     {
866         header.AllocatedLinks = Decrement(header.AllocatedLinks);
867         _dataMemory.UsedCapacity -= LinkDataPartSizeInBytes;
868         _indexMemory.UsedCapacity -= LinkIndexPartSizeInBytes;
869         // Убираем все связи, находящиеся в списке свободных в конце файла, до тех пор,
870         ↳ пока не дойдём до первой существующей связи
871         // Позволяет оптимизировать количество выделенных связей (AllocatedLinks)
872         while (GreaterThan(header.AllocatedLinks, GetZero()) &&
873             ↳ IsUnusedLink(header.AllocatedLinks))
874         {
875             UnusedLinksListMethods.Detach(header.AllocatedLinks);
876             header.AllocatedLinks = Decrement(header.AllocatedLinks);
877             _dataMemory.UsedCapacity -= LinkDataPartSizeInBytes;
878             _indexMemory.UsedCapacity -= LinkIndexPartSizeInBytes;
879         }
880     }
881     return handler?.Invoke(before, null) ?? Constants.Continue;
882 }
883
884 /// <summary>
885 /// <para>
886 /// Gets the link struct using the specified link index.
887 /// </para>
888 /// <para></para>
889 /// </summary>
890 /// <param name="linkIndex">
891 /// <para>The link index.</para>
892 /// <para></para>
893 /// </param>

```

```

889 /// <returns>
890 /// <para>A list of t link</para>
891 /// <para></para>
892 /// </returns>
893 [MethodImpl(MethodImplOptions.AggressiveInlining)]
894 public IList<TLinkAddress>? GetLinkStruct(TLinkAddress linkIndex)
895 {
896     ref var link = ref GetLinkDataPartReference(linkIndex);
897     return new Link<TLinkAddress>(linkIndex, link.Source, link.Target);
898 }
899
900 /// <remarks>
901 /// TODO: Возможно это должно быть событием, вызываемым из IMemory, в том случае, если
902   → адрес реально поменялся
903 ///
904 /// Указатель this.links может быть в том же месте,
905 /// так как 0-я связь не используется и имеет такой же размер как Header,
906 /// поэтому header размещается в том же месте, что и 0-я связь
907 /// </remarks>
908 [MethodImpl(MethodImplOptions.AggressiveInlining)]
909 protected abstract void SetPointers(IResizableDirectMemory dataMemory,
910   → IResizableDirectMemory indexMemory);
911
912 /// <summary>
913 /// <para>
914 /// Resets the pointers.
915 /// </para>
916 /// <para></para>
917 /// </summary>
918 [MethodImpl(MethodImplOptions.AggressiveInlining)]
919 protected virtual void ResetPointers()
920 {
921     InternalSourcesListMethods = null;
922     InternalSourcesTreeMethods = null;
923     ExternalSourcesTreeMethods = null;
924     InternalTargetsTreeMethods = null;
925     ExternalTargetsTreeMethods = null;
926     UnusedLinksListMethods = null;
927 }
928
929 /// <summary>
930 /// <para>
931 /// Gets the header reference.
932 /// </para>
933 /// <para></para>
934 /// </summary>
935 /// <returns>
936 /// <para>A ref links header of t link</para>
937 /// <para></para>
938 /// </returns>
939 [MethodImpl(MethodImplOptions.AggressiveInlining)]
940 protected abstract ref LinksHeader<TLinkAddress> GetHeaderReference();
941
942 /// <summary>
943 /// <para>
944 /// Gets the link data part reference using the specified link index.
945 /// </para>
946 /// <para></para>
947 /// </summary>
948 /// <param name="linkIndex">
949 /// <para>The link index.</para>
950 /// </param>
951 /// <returns>
952 /// <para>A ref raw link data part of t link</para>
953 /// <para></para>
954 /// </returns>
955 [MethodImpl(MethodImplOptions.AggressiveInlining)]
956 protected abstract ref RawLinkDataPart<TLinkAddress>
957   → GetLinkDataPartReference(TLinkAddress linkIndex);
958
959 /// <summary>
960 /// <para>
961 /// Gets the link index part reference using the specified link index.
962 /// </para>
963 /// <para></para>
964 /// </summary>
965 /// <param name="linkIndex">

```

```

964    /// <para>The link index.</para>
965    /// <para></para>
966    /// </param>
967    /// <returns>
968    /// <para>A ref raw link index part of t link</para>
969    /// <para></para>
970    /// </returns>
971    [MethodImpl(MethodImplOptions.AggressiveInlining)]
972    protected abstract ref RawLinkIndexPart<TLinkAddress>
    ↪ GetLinkIndexPartReference(TLinkAddress linkIndex);

973
974    /// <summary>
975    /// <para>
976    /// Determines whether this instance exists.
977    /// </para>
978    /// <para></para>
979    /// </summary>
980    /// <param name="link">
981    /// <para>The link.</para>
982    /// <para></para>
983    /// </param>
984    /// <returns>
985    /// <para>The bool</para>
986    /// <para></para>
987    /// </returns>
988    [MethodImpl(MethodImplOptions.AggressiveInlining)]
989    protected virtual bool Exists(TLinkAddress link)
990        => GreaterOrEqualThan(link, Constants.InternalReferencesRange.Minimum)
991            && LessOrEqualThan(link, GetHeaderReference().AllocatedLinks)
992            && !IsUnusedLink(link);
993
994    /// <summary>
995    /// <para>
996    /// Determines whether this instance is unused link.
997    /// </para>
998    /// <para></para>
999    /// </summary>
1000    /// <param name="linkIndex">
1001    /// <para>The link index.</para>
1002    /// <para></para>
1003    /// </param>
1004    /// <returns>
1005    /// <para>The bool</para>
1006    /// <para></para>
1007    /// </returns>
1008    [MethodImpl(MethodImplOptions.AggressiveInlining)]
1009    protected virtual bool IsUnusedLink(TLinkAddress linkIndex)
1010    {
1011        if (!AreEqual(GetHeaderReference().FirstFreeLink, linkIndex)) // May be this check
1012        ↪ is not needed
1013        {
1014            // TODO: Reduce access to memory in different location (should be enough to use
1015            ↪ just linkIndexPart)
1016            ref var linkDataPart = ref GetLinkDataPartReference(linkIndex);
1017            ref var linkIndexPart = ref GetLinkIndexPartReference(linkIndex);
1018            return AreEqual(linkIndexPart.SizeAsTarget, default) &&
1019                ↪ !AreEqual(linkDataPart.Source, default);
1020        }
1021        else
1022        {
1023            return true;
1024        }
1025    }
1026
1027    /// <summary>
1028    /// <para>
1029    /// Gets the one.
1030    /// </para>
1031    /// <para></para>
1032    /// </summary>
1033    /// <returns>
1034    /// <para>The link</para>
1035    /// <para></para>
1036    /// </returns>
1037    [MethodImpl(MethodImplOptions.AggressiveInlining)]
1038    protected virtual TLinkAddress GetOne() => _one;
1039
1040    /// <summary>

```



```

1038    /// <para>
1039    /// Gets the zero.
1040    /// </para>
1041    /// <para></para>
1042    /// </summary>
1043    /// <returns>
1044    /// <para>The link</para>
1045    /// <para></para>
1046    /// </returns>
1047    [MethodImpl(MethodImplOptions.AggressiveInlining)]
1048    protected virtual TLinkAddress GetZero() => default;
1049
1050    /// <summary>
1051    /// <para>
1052    /// Determines whether this instance are equal.
1053    /// </para>
1054    /// <para></para>
1055    /// </summary>
1056    /// <param name="first">
1057    /// <para>The first.</para>
1058    /// <para></para>
1059    /// </param>
1060    /// <param name="second">
1061    /// <para>The second.</para>
1062    /// <para></para>
1063    /// </param>
1064    /// <returns>
1065    /// <para>The bool</para>
1066    /// <para></para>
1067    /// </returns>
1068    [MethodImpl(MethodImplOptions.AggressiveInlining)]
1069    protected virtual bool AreEqual(TLinkAddress first, TLinkAddress second) =>
1070        ↪ _equalityComparer.Equals(first, second);
1071
1072    /// <summary>
1073    /// <para>
1074    /// Determines whether this instance less than.
1075    /// </para>
1076    /// <para></para>
1077    /// </summary>
1078    /// <param name="first">
1079    /// <para>The first.</para>
1080    /// <para></para>
1081    /// </param>
1082    /// <param name="second">
1083    /// <para>The second.</para>
1084    /// <para></para>
1085    /// </param>
1086    /// <returns>
1087    /// <para>The bool</para>
1088    /// <para></para>
1089    /// </returns>
1090    [MethodImpl(MethodImplOptions.AggressiveInlining)]
1091    protected virtual bool LessThan(TLinkAddress first, TLinkAddress second) =>
1092        ↪ _comparer.Compare(first, second) < 0;
1093
1094    /// <summary>
1095    /// <para>
1096    /// Determines whether this instance less or equal than.
1097    /// </para>
1098    /// <para></para>
1099    /// </summary>
1100    /// <param name="first">
1101    /// <para>The first.</para>
1102    /// <para></para>
1103    /// </param>
1104    /// <param name="second">
1105    /// <para>The second.</para>
1106    /// <para></para>
1107    /// </param>
1108    /// <returns>
1109    /// <para>The bool</para>
1110    /// <para></para>
1111    /// </returns>
1112    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    protected virtual bool LessOrEqualThan(TLinkAddress first, TLinkAddress second) =>
        ↪ _comparer.Compare(first, second) <= 0;

```

```

1113     /// <summary>
1114     /// <para>
1115     /// Determines whether this instance greater than.
1116     /// </para>
1117     /// <para></para>
1118     /// </summary>
1119     /// <param name="first">
1120     /// <para>The first.</para>
1121     /// <para></para>
1122     /// </param>
1123     /// <param name="second">
1124     /// <para>The second.</para>
1125     /// <para></para>
1126     /// </param>
1127     /// <returns>
1128     /// <para>The bool</para>
1129     /// <para></para>
1130     /// </returns>
1131     [MethodImpl(MethodImplOptions.AggressiveInlining)]
1132     protected virtual bool GreaterThan(TLinkAddress first, TLinkAddress second) =>
1133         ↪ _comparer.Compare(first, second) > 0;
1134
1135     /// <summary>
1136     /// <para>
1137     /// Determines whether this instance greater or equal than.
1138     /// </para>
1139     /// <para></para>
1140     /// </summary>
1141     /// <param name="first">
1142     /// <para>The first.</para>
1143     /// <para></para>
1144     /// </param>
1145     /// <param name="second">
1146     /// <para>The second.</para>
1147     /// <para></para>
1148     /// </param>
1149     /// <returns>
1150     /// <para>The bool</para>
1151     /// <para></para>
1152     /// </returns>
1153     [MethodImpl(MethodImplOptions.AggressiveInlining)]
1154     protected virtual bool GreaterOrEqualThan(TLinkAddress first, TLinkAddress second) =>
1155         ↪ _comparer.Compare(first, second) >= 0;
1156
1157     /// <summary>
1158     /// <para>
1159     /// Converts the to int 64 using the specified value.
1160     /// </para>
1161     /// <para></para>
1162     /// </summary>
1163     /// <param name="value">
1164     /// <para>The value.</para>
1165     /// <para></para>
1166     /// </param>
1167     /// <returns>
1168     /// <para>The long</para>
1169     /// <para></para>
1170     /// </returns>
1171     [MethodImpl(MethodImplOptions.AggressiveInlining)]
1172     protected virtual long ConvertToInt64(TLinkAddress value) =>
1173         ↪ _addressToInt64Converter.Convert(value);
1174
1175     /// <summary>
1176     /// <para>
1177     /// Converts the to address using the specified value.
1178     /// </para>
1179     /// <para></para>
1180     /// </summary>
1181     /// <param name="value">
1182     /// <para>The value.</para>
1183     /// <para></para>
1184     /// </param>
1185     /// <returns>
1186     /// <para>The link</para>
1187     /// <para></para>
1188     /// </returns>
1189     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

1187     protected virtual TLinkAddress ConvertToAddress(long value) =>
1188         ↪ _int64ToAddressConverter.Convert(value);
1189
1189     /// <summary>
1190     /// <para>
1191     /// Adds the first.
1192     /// </para>
1193     /// <para></para>
1194     /// </summary>
1195     /// <param name="first">
1196     /// <para>The first.</para>
1197     /// <para></para>
1198     /// </param>
1199     /// <param name="second">
1200     /// <para>The second.</para>
1201     /// <para></para>
1202     /// </param>
1203     /// <returns>
1204     /// <para>The link</para>
1205     /// <para></para>
1206     /// </returns>
1207     [MethodImpl(MethodImplOptions.AggressiveInlining)]
1208     protected virtual TLinkAddress Add(TLinkAddress first, TLinkAddress second) =>
1209         ↪ Arithmetic<TLinkAddress>.Add(first, second);
1210
1210     /// <summary>
1211     /// <para>
1212     /// Subtracts the first.
1213     /// </para>
1214     /// <para></para>
1215     /// </summary>
1216     /// <param name="first">
1217     /// <para>The first.</para>
1218     /// <para></para>
1219     /// </param>
1220     /// <param name="second">
1221     /// <para>The second.</para>
1222     /// <para></para>
1223     /// </param>
1224     /// <returns>
1225     /// <para>The link</para>
1226     /// <para></para>
1227     /// </returns>
1228     [MethodImpl(MethodImplOptions.AggressiveInlining)]
1229     protected virtual TLinkAddress Subtract(TLinkAddress first, TLinkAddress second) =>
1230         ↪ Arithmetic<TLinkAddress>.Subtract(first, second);
1231
1231     /// <summary>
1232     /// <para>
1233     /// Increments the link.
1234     /// </para>
1235     /// <para></para>
1236     /// </summary>
1237     /// <param name="link">
1238     /// <para>The link.</para>
1239     /// <para></para>
1240     /// </param>
1241     /// <returns>
1242     /// <para>The link</para>
1243     /// <para></para>
1244     /// </returns>
1245     [MethodImpl(MethodImplOptions.AggressiveInlining)]
1246     protected virtual TLinkAddress Increment(TLinkAddress link) =>
1247         ↪ Arithmetic<TLinkAddress>.Increment(link);
1248
1248     /// <summary>
1249     /// <para>
1250     /// Decrements the link.
1251     /// </para>
1252     /// <para></para>
1253     /// </summary>
1254     /// <param name="link">
1255     /// <para>The link.</para>
1256     /// <para></para>
1257     /// </param>
1258     /// <returns>
1259     /// <para>The link</para>
1260     /// <para></para>

```

```

1261     /// </returns>
1262     [MethodImpl(MethodImplOptions.AggressiveInlining)]
1263     protected virtual TLinkAddress Decrement(TLinkAddress link) =>
        ↪ Arithmetic<TLinkAddress>.Decrement(link);
1264
1265     #region Disposable
1266
1267     /// <summary>
1268     /// <para>
1269     /// Gets the allow multiple dispose calls value.
1270     /// </para>
1271     /// <para></para>
1272     /// </summary>
1273     protected override bool AllowMultipleDisposeCalls
1274     {
1275         [MethodImpl(MethodImplOptions.AggressiveInlining)]
1276         get => true;
1277     }
1278
1279     /// <summary>
1280     /// <para>
1281     /// Disposes the manual.
1282     /// </para>
1283     /// <para></para>
1284     /// </summary>
1285     /// <param name="manual">
1286     /// <para>The manual.</para>
1287     /// <para></para>
1288     /// </param>
1289     /// <param name="wasDisposed">
1290     /// <para>The was disposed.</para>
1291     /// <para></para>
1292     /// </param>
1293     [MethodImpl(MethodImplOptions.AggressiveInlining)]
1294     protected override void Dispose(bool manual, bool wasDisposed)
1295     {
1296         if (!wasDisposed)
1297         {
1298             ResetPointers();
1299             _dataMemory.DisposeIfPossible();
1300             _indexMemory.DisposeIfPossible();
1301         }
1302     }
1303
1304     #endregion
1305 }
1306 }

```

1.47 ./csharp/Platform.Data.Doublets/Memory/Split/Generic/UnusedLinksListMethods.cs

```

1  using System.Runtime.CompilerServices;
2  using Platform.Collections.Methods.Lists;
3  using Platform.Converters;
4  using static System.Runtime.CompilerServices.Unsafe;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Memory.Split.Generic
9  {
10     /// <summary>
11     /// <para>
12     /// Represents the unused links list methods.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     /// <seealso cref="AbsoluteCircularDoublyLinkedListMethods{TLinkAddress}">
17     /// <seealso cref="ILinksListMethods{TLinkAddress}">
18     public unsafe class UnusedLinksListMethods<TLinkAddress> :
        ↪ AbsoluteCircularDoublyLinkedListMethods<TLinkAddress>, ILinksListMethods<TLinkAddress>
19     {
20         private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
            ↪ = UncheckedConverter<TLinkAddress, long>.Default;
21         private readonly byte* _links;
22         private readonly byte* _header;
23
24         /// <summary>
25         /// <para>
26         /// Initializes a new <see cref="UnusedLinksListMethods"> instance.
27         /// </para>
28         /// <para></para>

```

```

29     /// </summary>
30     /// <param name="links">
31     /// <para>A links.</para>
32     /// <para></para>
33     /// </param>
34     /// <param name="header">
35     /// <para>A header.</para>
36     /// <para></para>
37     /// </param>
38     [MethodImpl(MethodImplOptions.AggressiveInlining)]
39     public UnusedLinksListMethods(byte* links, byte* header)
40     {
41         _links = links;
42         _header = header;
43     }
44
45     /// <summary>
46     /// <para>
47     /// Gets the header reference.
48     /// </para>
49     /// <para></para>
50     /// </summary>
51     /// <returns>
52     /// <para>A ref links header of t link</para>
53     /// <para></para>
54     /// </returns>
55     [MethodImpl(MethodImplOptions.AggressiveInlining)]
56     protected virtual ref LinksHeader<TLinkAddress> GetHeaderReference() => ref
57         ↳ AsRef<LinksHeader<TLinkAddress>>(_header);
58
59     /// <summary>
60     /// <para>
61     /// Gets the link data part reference using the specified link.
62     /// </para>
63     /// <para></para>
64     /// </summary>
65     /// <param name="link">
66     /// <para>The link.</para>
67     /// <para></para>
68     /// </param>
69     /// <returns>
70     /// <para>A ref raw link data part of t link</para>
71     /// <para></para>
72     /// </returns>
73     [MethodImpl(MethodImplOptions.AggressiveInlining)]
74     protected virtual ref RawLinkDataPart<TLinkAddress>
75         ↳ GetLinkDataPartReference(TLinkAddress link) => ref
76         ↳ AsRef<RawLinkDataPart<TLinkAddress>>(_links +
77         ↳ (RawLinkDataPart<TLinkAddress>.SizeInBytes *
78         ↳ _addressToInt64Converter.Convert(link)));
79
80     /// <summary>
81     /// <para>
82     /// Gets the first.
83     /// </para>
84     /// <para></para>
85     /// </summary>
86     /// <returns>
87     /// <para>The link</para>
88     /// <para></para>
89     /// </returns>
90     [MethodImpl(MethodImplOptions.AggressiveInlining)]
91     protected override TLinkAddress GetFirst() => GetHeaderReference().FirstFreeLink;
92
93     /// <summary>
94     /// <para>
95     /// Gets the last.
96     /// </para>
97     /// <para></para>
98     /// </summary>
99     /// <returns>
100    /// <para>The link</para>
101    /// <para></para>
102    /// </returns>
103    [MethodImpl(MethodImplOptions.AggressiveInlining)]
104    protected override TLinkAddress GetLast() => GetHeaderReference().LastFreeLink;
105
106    /// <summary>

```

```

102    /// <para>
103    /// Gets the previous using the specified element.
104    /// </para>
105    /// <para></para>
106    /// </summary>
107    /// <param name="element">
108    /// <para>The element.</para>
109    /// <para></para>
110    /// </param>
111    /// <returns>
112    /// <para>The link</para>
113    /// <para></para>
114    /// </returns>
115    [MethodImpl(MethodImplOptions.AggressiveInlining)]
116    protected override TLinkAddress GetPrevious(TLinkAddress element) =>
117        ↪ GetLinkDataPartReference(element).Source;
118
119    /// <summary>
120    /// <para>
121    /// Gets the next using the specified element.
122    /// </para>
123    /// <para></para>
124    /// </summary>
125    /// <param name="element">
126    /// <para>The element.</para>
127    /// <para></para>
128    /// </param>
129    /// <returns>
130    /// <para>The link</para>
131    /// <para></para>
132    /// </returns>
133    [MethodImpl(MethodImplOptions.AggressiveInlining)]
134    protected override TLinkAddress GetNext(TLinkAddress element) =>
135        ↪ GetLinkDataPartReference(element).Target;
136
137    /// <summary>
138    /// <para>
139    /// Gets the size.
140    /// </para>
141    /// <para></para>
142    /// </summary>
143    /// <returns>
144    /// <para>The link</para>
145    /// <para></para>
146    /// </returns>
147    [MethodImpl(MethodImplOptions.AggressiveInlining)]
148    protected override TLinkAddress GetSize() => GetHeaderReference().FreeLinks;
149
150    /// <summary>
151    /// <para>
152    /// Sets the first using the specified element.
153    /// </para>
154    /// <para></para>
155    /// </summary>
156    /// <param name="element">
157    /// <para>The element.</para>
158    /// <para></para>
159    /// </param>
160    [MethodImpl(MethodImplOptions.AggressiveInlining)]
161    protected override void SetFirst(TLinkAddress element) =>
162        ↪ GetHeaderReference().FirstFreeLink = element;
163
164    /// <summary>
165    /// <para>
166    /// Sets the last using the specified element.
167    /// </para>
168    /// <para></para>
169    /// </summary>
170    /// <param name="element">
171    /// <para>The element.</para>
172    /// <para></para>
173    /// </param>
174    [MethodImpl(MethodImplOptions.AggressiveInlining)]
175    protected override void SetLast(TLinkAddress element) =>
176        ↪ GetHeaderReference().LastFreeLink = element;

```

```

176     /// Sets the previous using the specified element.
177     /// </para>
178     /// <para></para>
179     /// </summary>
180     /// <param name="element">
181     /// <para>The element.</para>
182     /// <para></para>
183     /// </param>
184     /// <param name="previous">
185     /// <para>The previous.</para>
186     /// <para></para>
187     /// </param>
188     [MethodImpl(MethodImplOptions.AggressiveInlining)]
189     protected override void SetPrevious(TLinkAddress element, TLinkAddress previous) =>
190         ↪ GetLinkDataPartReference(element).Source = previous;
191
192     /// <summary>
193     /// <para>
194     /// Sets the next using the specified element.
195     /// </para>
196     /// <para></para>
197     /// </summary>
198     /// <param name="element">
199     /// <para>The element.</para>
200     /// <para></para>
201     /// </param>
202     /// <param name="next">
203     /// <para>The next.</para>
204     /// <para></para>
205     /// </param>
206     [MethodImpl(MethodImplOptions.AggressiveInlining)]
207     protected override void SetNext(TLinkAddress element, TLinkAddress next) =>
208         ↪ GetLinkDataPartReference(element).Target = next;
209
210     /// <summary>
211     /// <para>
212     /// Sets the size using the specified size.
213     /// </para>
214     /// <para></para>
215     /// </summary>
216     /// <param name="size">
217     /// <para>The size.</para>
218     /// <para></para>
219     /// </param>
220     [MethodImpl(MethodImplOptions.AggressiveInlining)]
221     protected override void SetSize(TLinkAddress size) => GetHeaderReference().FreeLinks =
222         ↪ size;
223 }

```

1.48 ./csharp/Platform.Data.Doublets/Memory/Split/RawLinkDataPart.cs

```

1  using Platform.Unsafe;
2  using System;
3  using System.Collections.Generic;
4  using System.Runtime.CompilerServices;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Memory.Split
9  {
10     /// <summary>
11     /// <para>
12     /// The raw link data part.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     public struct RawLinkDataPart<TLinkAddress> : IEquatable<RawLinkDataPart<TLinkAddress>>
17     {
18         private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
19             ↪ EqualityComparer<TLinkAddress>.Default;
20
21         /// <summary>
22         /// <para>
23         /// The size.
24         /// </para>
25         /// <para></para>
26         /// </summary>
27         public static readonly long SizeInBytes = Structure<RawLinkDataPart<TLinkAddress>>.Size;

```

```

28     /// <summary>
29     /// <para>
30     /// The source.
31     /// </para>
32     /// <para></para>
33     /// </summary>
34     public TLinkAddress Source;
35     /// <summary>
36     /// <para>
37     /// The target.
38     /// </para>
39     /// <para></para>
40     /// </summary>
41     public TLinkAddress Target;
42
43     /// <summary>
44     /// <para>
45     /// Determines whether this instance equals.
46     /// </para>
47     /// <para></para>
48     /// </summary>
49     /// <param name="obj">
50     /// <para>The obj.</para>
51     /// <para></para>
52     /// </param>
53     /// <returns>
54     /// <para>The bool</para>
55     /// <para></para>
56     /// </returns>
57     [MethodImpl(MethodImplOptions.AggressiveInlining)]
58     public override bool Equals(object obj) => obj is RawLinkDataPart<TLinkAddress> link ?
    ↪ Equals(link) : false;
59
60     /// <summary>
61     /// <para>
62     /// Determines whether this instance equals.
63     /// </para>
64     /// <para></para>
65     /// </summary>
66     /// <param name="other">
67     /// <para>The other.</para>
68     /// <para></para>
69     /// </param>
70     /// <returns>
71     /// <para>The bool</para>
72     /// <para></para>
73     /// </returns>
74     [MethodImpl(MethodImplOptions.AggressiveInlining)]
75     public bool Equals(RawLinkDataPart<TLinkAddress> other)
76     => _equalityComparer.Equals(Source, other.Source)
77     && _equalityComparer.Equals(Target, other.Target);
78
79     /// <summary>
80     /// <para>
81     /// Gets the hash code.
82     /// </para>
83     /// <para></para>
84     /// </summary>
85     /// <returns>
86     /// <para>The int</para>
87     /// <para></para>
88     /// </returns>
89     [MethodImpl(MethodImplOptions.AggressiveInlining)]
90     public override int GetHashCode() => (Source, Target).GetHashCode();
91
92     [MethodImpl(MethodImplOptions.AggressiveInlining)]
93     public static bool operator ==(RawLinkDataPart<TLinkAddress> left,
    ↪ RawLinkDataPart<TLinkAddress> right) => left.Equals(right);
94
95     [MethodImpl(MethodImplOptions.AggressiveInlining)]
96     public static bool operator !=(RawLinkDataPart<TLinkAddress> left,
    ↪ RawLinkDataPart<TLinkAddress> right) => !(left == right);
97 }
98 }

```

1.49 ./csharp/Platform.Data.Doublets/Memory/Split/RawLinkIndexPart.cs

```

1 using Platform.Unsafe;
2 using System;

```



```

3 using System.Collections.Generic;
4 using System.Runtime.CompilerServices;
5
6 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8 namespace Platform.Data.Doublets.Memory.Split
9 {
10     /// <summary>
11     /// <para>
12     /// The raw link index part.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     public struct RawLinkIndexPart<TLinkAddress> : IEquatable<RawLinkIndexPart<TLinkAddress>>
17     {
18         private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
19             ↪ EqualityComparer<TLinkAddress>.Default;
20
21         /// <summary>
22         /// <para>
23         /// The size.
24         /// </para>
25         /// <para></para>
26         /// </summary>
27         public static readonly long SizeInBytes = Structure<RawLinkIndexPart<TLinkAddress>>.Size;
28
29         /// <summary>
30         /// <para>
31         /// The root as source.
32         /// </para>
33         /// <para></para>
34         /// </summary>
35         public TLinkAddress RootAsSource;
36
37         /// <summary>
38         /// <para>
39         /// The left as source.
40         /// </para>
41         /// <para></para>
42         /// </summary>
43         public TLinkAddress LeftAsSource;
44
45         /// <summary>
46         /// <para>
47         /// The right as source.
48         /// </para>
49         /// <para></para>
50         /// </summary>
51         public TLinkAddress RightAsSource;
52
53         /// <summary>
54         /// <para>
55         /// The size as source.
56         /// </para>
57         /// <para></para>
58         /// </summary>
59         public TLinkAddress SizeAsSource;
60
61         /// <summary>
62         /// <para>
63         /// The root as target.
64         /// </para>
65         /// <para></para>
66         /// </summary>
67         public TLinkAddress RootAsTarget;
68
69         /// <summary>
70         /// <para>
71         /// The left as target.
72         /// </para>
73         /// <para></para>
74         /// </summary>
75         public TLinkAddress LeftAsTarget;
76
77         /// <summary>
78         /// <para>
79         /// The right as target.
80         /// </para>
81         /// <para></para>
82         /// </summary>
83         public TLinkAddress RightAsTarget;
84
85         /// <summary>
86         /// <para>
87         /// The size as target.
88         /// </para>
89         /// <para></para>
90         /// </summary>
91         public TLinkAddress SizeAsTarget;
92     }
93 }

```

```

81     /// <para></para>
82     /// </summary>
83     public TLinkAddress SizeAsTarget;
84
85     /// <summary>
86     /// <para>
87     /// Determines whether this instance equals.
88     /// </para>
89     /// <para></para>
90     /// </summary>
91     /// <param name="obj">
92     /// <para>The obj.</para>
93     /// <para></para>
94     /// </param>
95     /// <returns>
96     /// <para>The bool</para>
97     /// <para></para>
98     /// </returns>
99     [MethodImpl(MethodImplOptions.AggressiveInlining)]
100    public override bool Equals(object obj) => obj is RawLinkIndexPart<TLinkAddress> link ?
        ↳ Equals(link) : false;
101
102    /// <summary>
103    /// <para>
104    /// Determines whether this instance equals.
105    /// </para>
106    /// <para></para>
107    /// </summary>
108    /// <param name="other">
109    /// <para>The other.</para>
110    /// <para></para>
111    /// </param>
112    /// <returns>
113    /// <para>The bool</para>
114    /// <para></para>
115    /// </returns>
116    [MethodImpl(MethodImplOptions.AggressiveInlining)]
117    public bool Equals(RawLinkIndexPart<TLinkAddress> other)
118        => _equalityComparer.Equals(RootAsSource, other.RootAsSource)
119        && _equalityComparer.Equals(LeftAsSource, other.LeftAsSource)
120        && _equalityComparer.Equals(RightAsSource, other.RightAsSource)
121        && _equalityComparer.Equals(SizeAsSource, other.SizeAsSource)
122        && _equalityComparer.Equals(RootAsTarget, other.RootAsTarget)
123        && _equalityComparer.Equals(LeftAsTarget, other.LeftAsTarget)
124        && _equalityComparer.Equals(RightAsTarget, other.RightAsTarget)
125        && _equalityComparer.Equals(SizeAsTarget, other.SizeAsTarget);
126
127    /// <summary>
128    /// <para>
129    /// Gets the hash code.
130    /// </para>
131    /// <para></para>
132    /// </summary>
133    /// <returns>
134    /// <para>The int</para>
135    /// <para></para>
136    /// </returns>
137    [MethodImpl(MethodImplOptions.AggressiveInlining)]
138    public override int GetHashCode() => (RootAsSource, LeftAsSource, RightAsSource,
        ↳ SizeAsSource, RootAsTarget, LeftAsTarget, RightAsTarget, SizeAsTarget).GetHashCode();
139
140    [MethodImpl(MethodImplOptions.AggressiveInlining)]
141    public static bool operator ==(RawLinkIndexPart<TLinkAddress> left,
        ↳ RawLinkIndexPart<TLinkAddress> right) => left.Equals(right);
142
143    [MethodImpl(MethodImplOptions.AggressiveInlining)]
144    public static bool operator !=(RawLinkIndexPart<TLinkAddress> left,
        ↳ RawLinkIndexPart<TLinkAddress> right) => !(left == right);
145 }
146 }

```

1.50 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksRecursionlessSizeBalancedTree

```

1 using System.Runtime.CompilerServices;
2 using Platform.Data.Doublets.Memory.Split.Generic;
3 using TLinkAddress = System.UInt32;
4
5 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6

```

```

7 namespace Platform.Data.Doublets.Memory.Split.Specific
8 {
9     /// <summary>
10    /// <para>
11    /// Represents the int 32 external links recursionless size balanced tree methods base.
12    /// </para>
13    /// <para></para>
14    /// </summary>
15    /// <seealso cref="ExternalLinksRecursionlessSizeBalancedTreeMethodsBase{TLinkAddress}"/>
16    /// <seealso cref="ILinksTreeMethods{TLinkAddress}"/>
17    public unsafe abstract class UInt32ExternalLinksRecursionlessSizeBalancedTreeMethodsBase :
18    ↪ ExternalLinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress>,
19    ↪ ILinksTreeMethods<TLinkAddress>
20    {
21        /// <summary>
22        /// <para>
23        /// The links data parts.
24        /// </para>
25        /// <para></para>
26        /// </summary>
27        protected new readonly RawLinkDataPart<TLinkAddress>* LinksDataParts;
28        /// <summary>
29        /// <para>
30        /// The links index parts.
31        /// </para>
32        /// <para></para>
33        /// </summary>
34        protected new readonly RawLinkIndexPart<TLinkAddress>* LinksIndexParts;
35        /// <summary>
36        /// <para>
37        /// The header.
38        /// </para>
39        /// <para></para>
40        /// </summary>
41        protected new readonly LinksHeader<TLinkAddress>* Header;
42
43        /// <summary>
44        /// <para>
45        /// Initializes a new <see
46        ↪ cref="UInt32ExternalLinksRecursionlessSizeBalancedTreeMethodsBase"/> instance.
47        /// </para>
48        /// <para></para>
49        /// </summary>
50        /// <param name="constants">
51        /// <para>A constants.</para>
52        /// <para></para>
53        /// </param>
54        /// <param name="linksDataParts">
55        /// <para>A links data parts.</para>
56        /// <para></para>
57        /// </param>
58        /// <param name="linksIndexParts">
59        /// <para>A links index parts.</para>
60        /// <para></para>
61        /// </param>
62        /// <param name="header">
63        /// <para>A header.</para>
64        /// <para></para>
65        /// </param>
66        [MethodImpl(MethodImplOptions.AggressiveInlining)]
67        protected UInt32ExternalLinksRecursionlessSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
68        ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
69        : base(constants, (byte*)linksDataParts, (byte*)linksIndexParts, (byte*)header)
70        {
71            LinksDataParts = linksDataParts;
72            LinksIndexParts = linksIndexParts;
73            Header = header;
74        }
75
76        /// <summary>
77        /// <para>
78        /// Gets the zero.
79        /// </para>
80        /// <para></para>
81        /// </summary>
82        /// <returns>
83        /// <para>The link</para>

```

```

80     /// <para></para>
81     /// </returns>
82     [MethodImpl(MethodImplOptions.AggressiveInlining)]
83     protected override TLinkAddress GetZero() => 0U;
84
85     /// <summary>
86     /// <para>
87     /// Determines whether this instance equal to zero.
88     /// </para>
89     /// <para></para>
90     /// </summary>
91     /// <param name="value">
92     /// <para>The value.</para>
93     /// <para></para>
94     /// </param>
95     /// <returns>
96     /// <para>The bool</para>
97     /// <para></para>
98     /// </returns>
99     [MethodImpl(MethodImplOptions.AggressiveInlining)]
100    protected override bool EqualToZero(TLinkAddress value) => value == 0U;
101
102    /// <summary>
103    /// <para>
104    /// Determines whether this instance are equal.
105    /// </para>
106    /// <para></para>
107    /// </summary>
108    /// <param name="first">
109    /// <para>The first.</para>
110    /// <para></para>
111    /// </param>
112    /// <param name="second">
113    /// <para>The second.</para>
114    /// <para></para>
115    /// </param>
116    /// <returns>
117    /// <para>The bool</para>
118    /// <para></para>
119    /// </returns>
120    [MethodImpl(MethodImplOptions.AggressiveInlining)]
121    protected override bool AreEqual(TLinkAddress first, TLinkAddress second) => first ==
        ↪ second;
122
123    /// <summary>
124    /// <para>
125    /// Determines whether this instance greater than zero.
126    /// </para>
127    /// <para></para>
128    /// </summary>
129    /// <param name="value">
130    /// <para>The value.</para>
131    /// <para></para>
132    /// </param>
133    /// <returns>
134    /// <para>The bool</para>
135    /// <para></para>
136    /// </returns>
137    [MethodImpl(MethodImplOptions.AggressiveInlining)]
138    protected override bool GreaterThanZero(TLinkAddress value) => value > 0U;
139
140    /// <summary>
141    /// <para>
142    /// Determines whether this instance greater than.
143    /// </para>
144    /// <para></para>
145    /// </summary>
146    /// <param name="first">
147    /// <para>The first.</para>
148    /// <para></para>
149    /// </param>
150    /// <param name="second">
151    /// <para>The second.</para>
152    /// <para></para>
153    /// </param>
154    /// <returns>
155    /// <para>The bool</para>
156    /// <para></para>

```

```

157     /// </returns>
158     [MethodImpl(MethodImplOptions.AggressiveInlining)]
159     protected override bool GreaterThan(TLinkAddress first, TLinkAddress second) => first >
        ↪ second;

160
161     /// <summary>
162     /// <para>
163     /// Determines whether this instance greater or equal than.
164     /// </para>
165     /// <para></para>
166     /// </summary>
167     /// <param name="first">
168     /// <para>The first.</para>
169     /// <para></para>
170     /// </param>
171     /// <param name="second">
172     /// <para>The second.</para>
173     /// <para></para>
174     /// </param>
175     /// <returns>
176     /// <para>The bool</para>
177     /// <para></para>
178     /// </returns>
179     [MethodImpl(MethodImplOptions.AggressiveInlining)]
180     protected override bool GreaterOrEqualThan(TLinkAddress first, TLinkAddress second) =>
        ↪ first >= second;

181
182     /// <summary>
183     /// <para>
184     /// Determines whether this instance greater or equal than zero.
185     /// </para>
186     /// <para></para>
187     /// </summary>
188     /// <param name="value">
189     /// <para>The value.</para>
190     /// <para></para>
191     /// </param>
192     /// <returns>
193     /// <para>The bool</para>
194     /// <para></para>
195     /// </returns>
196     [MethodImpl(MethodImplOptions.AggressiveInlining)]
197     protected override bool GreaterOrEqualThanZero(TLinkAddress value) => true; // value >=
        ↪ 0 is always true for ulong

198
199     /// <summary>
200     /// <para>
201     /// Determines whether this instance less or equal than zero.
202     /// </para>
203     /// <para></para>
204     /// </summary>
205     /// <param name="value">
206     /// <para>The value.</para>
207     /// <para></para>
208     /// </param>
209     /// <returns>
210     /// <para>The bool</para>
211     /// <para></para>
212     /// </returns>
213     [MethodImpl(MethodImplOptions.AggressiveInlining)]
214     protected override bool LessOrEqualThanZero(TLinkAddress value) => value == OUL; //
        ↪ value is always >= 0 for ulong

215
216     /// <summary>
217     /// <para>
218     /// Determines whether this instance less or equal than.
219     /// </para>
220     /// <para></para>
221     /// </summary>
222     /// <param name="first">
223     /// <para>The first.</para>
224     /// <para></para>
225     /// </param>
226     /// <param name="second">
227     /// <para>The second.</para>
228     /// <para></para>
229     /// </param>
230     /// <returns>

```

```

231    /// <para>The bool</para>
232    /// <para></para>
233    /// </returns>
234    [MethodImpl(MethodImplOptions.AggressiveInlining)]
235    protected override bool LessOrEqualThan(TLinkAddress first, TLinkAddress second) =>
        ↪ first <= second;

236
237    /// <summary>
238    /// <para>
239    /// Determines whether this instance less than zero.
240    /// </para>
241    /// <para></para>
242    /// </summary>
243    /// <param name="value">
244    /// <para>The value.</para>
245    /// <para></para>
246    /// </param>
247    /// <returns>
248    /// <para>The bool</para>
249    /// <para></para>
250    /// </returns>
251    [MethodImpl(MethodImplOptions.AggressiveInlining)]
252    protected override bool LessThanZero(TLinkAddress value) => false; // value < 0 is
        ↪ always false for ulong

253
254    /// <summary>
255    /// <para>
256    /// Determines whether this instance less than.
257    /// </para>
258    /// <para></para>
259    /// </summary>
260    /// <param name="first">
261    /// <para>The first.</para>
262    /// <para></para>
263    /// </param>
264    /// <param name="second">
265    /// <para>The second.</para>
266    /// <para></para>
267    /// </param>
268    /// <returns>
269    /// <para>The bool</para>
270    /// <para></para>
271    /// </returns>
272    [MethodImpl(MethodImplOptions.AggressiveInlining)]
273    protected override bool LessThan(TLinkAddress first, TLinkAddress second) => first <
        ↪ second;

274
275    /// <summary>
276    /// <para>
277    /// Increments the value.
278    /// </para>
279    /// <para></para>
280    /// </summary>
281    /// <param name="value">
282    /// <para>The value.</para>
283    /// <para></para>
284    /// </param>
285    /// <returns>
286    /// <para>The link</para>
287    /// <para></para>
288    /// </returns>
289    [MethodImpl(MethodImplOptions.AggressiveInlining)]
290    protected override TLinkAddress Increment(TLinkAddress value) => ++value;

291
292    /// <summary>
293    /// <para>
294    /// Decrements the value.
295    /// </para>
296    /// <para></para>
297    /// </summary>
298    /// <param name="value">
299    /// <para>The value.</para>
300    /// <para></para>
301    /// </param>
302    /// <returns>
303    /// <para>The link</para>
304    /// <para></para>
305    /// </returns>

```

```

306 [MethodImpl(MethodImplOptions.AggressiveInlining)]
307 protected override TLinkAddress Decrement(TLinkAddress value) => --value;
308
309 /// <summary>
310 /// <para>
311 /// Adds the first.
312 /// </para>
313 /// <para></para>
314 /// </summary>
315 /// <param name="first">
316 /// <para>The first.</para>
317 /// <para></para>
318 /// </param>
319 /// <param name="second">
320 /// <para>The second.</para>
321 /// <para></para>
322 /// </param>
323 /// <returns>
324 /// <para>The link</para>
325 /// <para></para>
326 /// </returns>
327 [MethodImpl(MethodImplOptions.AggressiveInlining)]
328 protected override TLinkAddress Add(TLinkAddress first, TLinkAddress second) => first +
    ↪ second;
329
330 /// <summary>
331 /// <para>
332 /// Subtracts the first.
333 /// </para>
334 /// <para></para>
335 /// </summary>
336 /// <param name="first">
337 /// <para>The first.</para>
338 /// <para></para>
339 /// </param>
340 /// <param name="second">
341 /// <para>The second.</para>
342 /// <para></para>
343 /// </param>
344 /// <returns>
345 /// <para>The link</para>
346 /// <para></para>
347 /// </returns>
348 [MethodImpl(MethodImplOptions.AggressiveInlining)]
349 protected override TLinkAddress Subtract(TLinkAddress first, TLinkAddress second) =>
    ↪ first - second;
350
351 /// <summary>
352 /// <para>
353 /// Gets the header reference.
354 /// </para>
355 /// <para></para>
356 /// </summary>
357 /// <returns>
358 /// <para>A ref links header of t link</para>
359 /// <para></para>
360 /// </returns>
361 [MethodImpl(MethodImplOptions.AggressiveInlining)]
362 protected override ref LinksHeader<TLinkAddress> GetHeaderReference() => ref *Header;
363
364 /// <summary>
365 /// <para>
366 /// Gets the link data part reference using the specified link.
367 /// </para>
368 /// <para></para>
369 /// </summary>
370 /// <param name="link">
371 /// <para>The link.</para>
372 /// <para></para>
373 /// </param>
374 /// <returns>
375 /// <para>A ref raw link data part of t link</para>
376 /// <para></para>
377 /// </returns>
378 [MethodImpl(MethodImplOptions.AggressiveInlining)]
379 protected override ref RawLinkDataPart<TLinkAddress>
    ↪ GetLinkDataPartReference(TLinkAddress link) => ref LinksDataParts[link];
380

```

```

381     /// <summary>
382     /// <para>
383     /// Gets the link index part reference using the specified link.
384     /// </para>
385     /// <para></para>
386     /// </summary>
387     /// <param name="link">
388     /// <para>The link.</para>
389     /// <para></para>
390     /// </param>
391     /// <returns>
392     /// <para>A ref raw link index part of t link</para>
393     /// <para></para>
394     /// </returns>
395     [MethodImpl(MethodImplOptions.AggressiveInlining)]
396     protected override ref RawLinkIndexPart<TLinkAddress>
397     ↪ GetLinkIndexPartReference(TLinkAddress link) => ref LinksIndexParts[link];
398
399     /// <summary>
400     /// <para>
401     /// Determines whether this instance first is to the left of second.
402     /// </para>
403     /// <para></para>
404     /// </summary>
405     /// <param name="first">
406     /// <para>The first.</para>
407     /// <para></para>
408     /// </param>
409     /// <param name="second">
410     /// <para>The second.</para>
411     /// <para></para>
412     /// </param>
413     /// <returns>
414     /// <para>The bool</para>
415     /// <para></para>
416     /// </returns>
417     [MethodImpl(MethodImplOptions.AggressiveInlining)]
418     protected override bool FirstIsToLeftOfSecond(TLinkAddress first, TLinkAddress second)
419     {
420         ref var firstLink = ref LinksDataParts[first];
421         ref var secondLink = ref LinksDataParts[second];
422         return FirstIsToLeftOfSecond(firstLink.Source, firstLink.Target,
423             ↪ secondLink.Source, secondLink.Target);
424     }
425
426     /// <summary>
427     /// <para>
428     /// Determines whether this instance first is to the right of second.
429     /// </para>
430     /// <para></para>
431     /// </summary>
432     /// <param name="first">
433     /// <para>The first.</para>
434     /// <para></para>
435     /// </param>
436     /// <param name="second">
437     /// <para>The second.</para>
438     /// <para></para>
439     /// </param>
440     /// <returns>
441     /// <para>The bool</para>
442     /// <para></para>
443     /// </returns>
444     [MethodImpl(MethodImplOptions.AggressiveInlining)]
445     protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
446     ↪ second)
447     {
448         ref var firstLink = ref LinksDataParts[first];
449         ref var secondLink = ref LinksDataParts[second];
450         return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
451             ↪ secondLink.Source, secondLink.Target);
452     }
453 }

```

1.51 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksSizeBalancedTreeMethodsBase

```

1 using System.Runtime.CompilerServices;
2 using Platform.Data.Doublets.Memory.Split.Generic;

```



```

3 using TLinkAddress = System.UInt32;
4
5 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7 namespace Platform.Data.Doublets.Memory.Split.Specific
8 {
9     /// <summary>
10    /// <para>
11    /// Represents the int 32 external links size balanced tree methods base.
12    /// </para>
13    /// <para></para>
14    /// </summary>
15    /// <seealso cref="ExternalLinksSizeBalancedTreeMethodsBase{TLinkAddress}"/>
16    /// <seealso cref="ILinksTreeMethods{TLinkAddress}"/>
17    public unsafe abstract class UInt32ExternalLinksSizeBalancedTreeMethodsBase :
18    ↪ ExternalLinksSizeBalancedTreeMethodsBase<TLinkAddress>, ILinksTreeMethods<TLinkAddress>
19    {
20        /// <summary>
21        /// <para>
22        /// The links data parts.
23        /// </para>
24        /// <para></para>
25        /// </summary>
26        protected new readonly RawLinkDataPart<TLinkAddress>* LinksDataParts;
27        /// <summary>
28        /// <para>
29        /// The links index parts.
30        /// </para>
31        /// <para></para>
32        /// </summary>
33        protected new readonly RawLinkIndexPart<TLinkAddress>* LinksIndexParts;
34        /// <summary>
35        /// <para>
36        /// The header.
37        /// </para>
38        /// <para></para>
39        /// </summary>
40        protected new readonly LinksHeader<TLinkAddress>* Header;
41
42        /// <summary>
43        /// <para>
44        /// Initializes a new <see cref="UInt32ExternalLinksSizeBalancedTreeMethodsBase"/>
45        ↪ instance.
46        /// </para>
47        /// <para></para>
48        /// </summary>
49        /// <param name="constants">
50        /// <para>A constants.</para>
51        /// <para></para>
52        /// </param>
53        /// <param name="linksDataParts">
54        /// <para>A links data parts.</para>
55        /// <para></para>
56        /// </param>
57        /// <param name="linksIndexParts">
58        /// <para>A links index parts.</para>
59        /// <para></para>
60        /// </param>
61        /// <param name="header">
62        /// <para>A header.</para>
63        /// <para></para>
64        /// </param>
65        [MethodImpl(MethodImplOptions.AggressiveInlining)]
66        protected UInt32ExternalLinksSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress>
67        ↪ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
68        ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
69        : base(constants, (byte*)linksDataParts, (byte*)linksIndexParts, (byte*)header)
70        {
71            LinksDataParts = linksDataParts;
72            LinksIndexParts = linksIndexParts;
73            Header = header;
74        }
75
76        /// <summary>
77        /// <para>
78        /// Gets the zero.
79        /// </para>
80        /// <para></para>
81        /// </summary>

```

```

78     /// <returns>
79     /// <para>The link</para>
80     /// <para></para>
81     /// </returns>
82     [MethodImpl(MethodImplOptions.AggressiveInlining)]
83     protected override TLinkAddress GetZero() => 0U;
84
85     /// <summary>
86     /// <para>
87     /// Determines whether this instance equal to zero.
88     /// </para>
89     /// <para></para>
90     /// </summary>
91     /// <param name="value">
92     /// <para>The value.</para>
93     /// <para></para>
94     /// </param>
95     /// <returns>
96     /// <para>The bool</para>
97     /// <para></para>
98     /// </returns>
99     [MethodImpl(MethodImplOptions.AggressiveInlining)]
100    protected override bool EqualToZero(TLinkAddress value) => value == 0U;
101
102    /// <summary>
103    /// <para>
104    /// Determines whether this instance are equal.
105    /// </para>
106    /// <para></para>
107    /// </summary>
108    /// <param name="first">
109    /// <para>The first.</para>
110    /// <para></para>
111    /// </param>
112    /// <param name="second">
113    /// <para>The second.</para>
114    /// <para></para>
115    /// </param>
116    /// <returns>
117    /// <para>The bool</para>
118    /// <para></para>
119    /// </returns>
120    [MethodImpl(MethodImplOptions.AggressiveInlining)]
121    protected override bool AreEqual(TLinkAddress first, TLinkAddress second) => first ==
        ↪ second;
122
123    /// <summary>
124    /// <para>
125    /// Determines whether this instance greater than zero.
126    /// </para>
127    /// <para></para>
128    /// </summary>
129    /// <param name="value">
130    /// <para>The value.</para>
131    /// <para></para>
132    /// </param>
133    /// <returns>
134    /// <para>The bool</para>
135    /// <para></para>
136    /// </returns>
137    [MethodImpl(MethodImplOptions.AggressiveInlining)]
138    protected override bool GreaterThanZero(TLinkAddress value) => value > 0U;
139
140    /// <summary>
141    /// <para>
142    /// Determines whether this instance greater than.
143    /// </para>
144    /// <para></para>
145    /// </summary>
146    /// <param name="first">
147    /// <para>The first.</para>
148    /// <para></para>
149    /// </param>
150    /// <param name="second">
151    /// <para>The second.</para>
152    /// <para></para>
153    /// </param>
154    /// <returns>

```

```

155     /// <para>The bool</para>
156     /// <para></para>
157     /// </returns>
158     [MethodImpl(MethodImplOptions.AggressiveInlining)]
159     protected override bool GreaterThan(TLinkAddress first, TLinkAddress second) => first >
        ↪ second;

160
161     /// <summary>
162     /// <para>
163     /// Determines whether this instance greater or equal than.
164     /// </para>
165     /// <para></para>
166     /// </summary>
167     /// <param name="first">
168     /// <para>The first.</para>
169     /// <para></para>
170     /// </param>
171     /// <param name="second">
172     /// <para>The second.</para>
173     /// <para></para>
174     /// </param>
175     /// <returns>
176     /// <para>The bool</para>
177     /// <para></para>
178     /// </returns>
179     [MethodImpl(MethodImplOptions.AggressiveInlining)]
180     protected override bool GreaterOrEqualThan(TLinkAddress first, TLinkAddress second) =>
        ↪ first >= second;

181
182     /// <summary>
183     /// <para>
184     /// Determines whether this instance greater or equal than zero.
185     /// </para>
186     /// <para></para>
187     /// </summary>
188     /// <param name="value">
189     /// <para>The value.</para>
190     /// <para></para>
191     /// </param>
192     /// <returns>
193     /// <para>The bool</para>
194     /// <para></para>
195     /// </returns>
196     [MethodImpl(MethodImplOptions.AggressiveInlining)]
197     protected override bool GreaterOrEqualThanZero(TLinkAddress value) => true; // value >=
        ↪ 0 is always true for ulong

198
199     /// <summary>
200     /// <para>
201     /// Determines whether this instance less or equal than zero.
202     /// </para>
203     /// <para></para>
204     /// </summary>
205     /// <param name="value">
206     /// <para>The value.</para>
207     /// <para></para>
208     /// </param>
209     /// <returns>
210     /// <para>The bool</para>
211     /// <para></para>
212     /// </returns>
213     [MethodImpl(MethodImplOptions.AggressiveInlining)]
214     protected override bool LessOrEqualThanZero(TLinkAddress value) => value == 0UL; //
        ↪ value is always >= 0 for ulong

215
216     /// <summary>
217     /// <para>
218     /// Determines whether this instance less or equal than.
219     /// </para>
220     /// <para></para>
221     /// </summary>
222     /// <param name="first">
223     /// <para>The first.</para>
224     /// <para></para>
225     /// </param>
226     /// <param name="second">
227     /// <para>The second.</para>
228     /// <para></para>

```

```

229     /// </param>
230     /// <returns>
231     /// <para>The bool</para>
232     /// <para></para>
233     /// </returns>
234     [MethodImpl(MethodImplOptions.AggressiveInlining)]
235     protected override bool LessOrEqualThan(TLinkAddress first, TLinkAddress second) =>
236         ↪ first <= second;
237
238     /// <summary>
239     /// <para>
240     /// Determines whether this instance less than zero.
241     /// </para>
242     /// <para></para>
243     /// </summary>
244     /// <param name="value">
245     /// <para>The value.</para>
246     /// <para></para>
247     /// </param>
248     /// <returns>
249     /// <para>The bool</para>
250     /// <para></para>
251     /// </returns>
252     [MethodImpl(MethodImplOptions.AggressiveInlining)]
253     protected override bool LessThanZero(TLinkAddress value) => false; // value < 0 is
254     ↪ always false for ulong
255
256     /// <summary>
257     /// <para>
258     /// Determines whether this instance less than.
259     /// </para>
260     /// <para></para>
261     /// </summary>
262     /// <param name="first">
263     /// <para>The first.</para>
264     /// <para></para>
265     /// </param>
266     /// <param name="second">
267     /// <para>The second.</para>
268     /// <para></para>
269     /// </param>
270     /// <returns>
271     /// <para>The bool</para>
272     /// <para></para>
273     /// </returns>
274     [MethodImpl(MethodImplOptions.AggressiveInlining)]
275     protected override bool LessThan(TLinkAddress first, TLinkAddress second) => first <
276     ↪ second;
277
278     /// <summary>
279     /// <para>
280     /// Increments the value.
281     /// </para>
282     /// <para></para>
283     /// </summary>
284     /// <param name="value">
285     /// <para>The value.</para>
286     /// <para></para>
287     /// </param>
288     /// <returns>
289     /// <para>The link</para>
290     /// <para></para>
291     /// </returns>
292     [MethodImpl(MethodImplOptions.AggressiveInlining)]
293     protected override TLinkAddress Increment(TLinkAddress value) => ++value;
294
295     /// <summary>
296     /// <para>
297     /// Decrements the value.
298     /// </para>
299     /// <para></para>
300     /// </summary>
301     /// <param name="value">
302     /// <para>The value.</para>
303     /// <para></para>
304     /// </param>
305     /// <returns>
306     /// <para>The link</para>

```

```

304     /// <para></para>
305     /// </returns>
306     [MethodImpl(MethodImplOptions.AggressiveInlining)]
307     protected override TLinkAddress Decrement(TLinkAddress value) => --value;
308
309     /// <summary>
310     /// <para>
311     /// Adds the first.
312     /// </para>
313     /// <para></para>
314     /// </summary>
315     /// <param name="first">
316     /// <para>The first.</para>
317     /// <para></para>
318     /// </param>
319     /// <param name="second">
320     /// <para>The second.</para>
321     /// <para></para>
322     /// </param>
323     /// <returns>
324     /// <para>The link</para>
325     /// <para></para>
326     /// </returns>
327     [MethodImpl(MethodImplOptions.AggressiveInlining)]
328     protected override TLinkAddress Add(TLinkAddress first, TLinkAddress second) => first +
        ↪ second;
329
330     /// <summary>
331     /// <para>
332     /// Subtracts the first.
333     /// </para>
334     /// <para></para>
335     /// </summary>
336     /// <param name="first">
337     /// <para>The first.</para>
338     /// <para></para>
339     /// </param>
340     /// <param name="second">
341     /// <para>The second.</para>
342     /// <para></para>
343     /// </param>
344     /// <returns>
345     /// <para>The link</para>
346     /// <para></para>
347     /// </returns>
348     [MethodImpl(MethodImplOptions.AggressiveInlining)]
349     protected override TLinkAddress Subtract(TLinkAddress first, TLinkAddress second) =>
        ↪ first - second;
350
351     /// <summary>
352     /// <para>
353     /// Gets the header reference.
354     /// </para>
355     /// <para></para>
356     /// </summary>
357     /// <returns>
358     /// <para>A ref links header of t link</para>
359     /// <para></para>
360     /// </returns>
361     [MethodImpl(MethodImplOptions.AggressiveInlining)]
362     protected override ref LinksHeader<TLinkAddress> GetHeaderReference() => ref *Header;
363
364     /// <summary>
365     /// <para>
366     /// Gets the link data part reference using the specified link.
367     /// </para>
368     /// <para></para>
369     /// </summary>
370     /// <param name="link">
371     /// <para>The link.</para>
372     /// <para></para>
373     /// </param>
374     /// <returns>
375     /// <para>A ref raw link data part of t link</para>
376     /// <para></para>
377     /// </returns>
378     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

379 protected override ref RawLinkDataPart<TLinkAddress>
    ↳ GetLinkDataPartReference(TLinkAddress link) => ref LinksDataParts[link];
380
381 /// <summary>
382 /// <para>
383 /// Gets the link index part reference using the specified link.
384 /// </para>
385 /// <para></para>
386 /// </summary>
387 /// <param name="link">
388 /// <para>The link.</para>
389 /// <para></para>
390 /// </param>
391 /// <returns>
392 /// <para>A ref raw link index part of t link</para>
393 /// <para></para>
394 /// </returns>
395 [MethodImpl(MethodImplOptions.AggressiveInlining)]
396 protected override ref RawLinkIndexPart<TLinkAddress>
    ↳ GetLinkIndexPartReference(TLinkAddress link) => ref LinksIndexParts[link];
397
398 /// <summary>
399 /// <para>
400 /// Determines whether this instance first is to the left of second.
401 /// </para>
402 /// <para></para>
403 /// </summary>
404 /// <param name="first">
405 /// <para>The first.</para>
406 /// <para></para>
407 /// </param>
408 /// <param name="second">
409 /// <para>The second.</para>
410 /// <para></para>
411 /// </param>
412 /// <returns>
413 /// <para>The bool</para>
414 /// <para></para>
415 /// </returns>
416 [MethodImpl(MethodImplOptions.AggressiveInlining)]
417 protected override bool FirstIsToTheLeftOfSecond(TLinkAddress first, TLinkAddress second)
418 {
419     ref var firstLink = ref LinksDataParts[first];
420     ref var secondLink = ref LinksDataParts[second];
421     return FirstIsToTheLeftOfSecond(firstLink.Source, firstLink.Target,
    ↳ secondLink.Source, secondLink.Target);
422 }
423
424 /// <summary>
425 /// <para>
426 /// Determines whether this instance first is to the right of second.
427 /// </para>
428 /// <para></para>
429 /// </summary>
430 /// <param name="first">
431 /// <para>The first.</para>
432 /// <para></para>
433 /// </param>
434 /// <param name="second">
435 /// <para>The second.</para>
436 /// <para></para>
437 /// </param>
438 /// <returns>
439 /// <para>The bool</para>
440 /// <para></para>
441 /// </returns>
442 [MethodImpl(MethodImplOptions.AggressiveInlining)]
443 protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
    ↳ second)
444 {
445     ref var firstLink = ref LinksDataParts[first];
446     ref var secondLink = ref LinksDataParts[second];
447     return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
    ↳ secondLink.Source, secondLink.Target);
448 }
449 }
450 }

```

1.52 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksSourcesRecursionlessSizeBalancedTreeMethodsBase

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt32;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 32 external links sources recursionless size balanced tree methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="UInt32ExternalLinksRecursionlessSizeBalancedTreeMethodsBase"/>
15     public unsafe class UInt32ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods :
16         ↳ UInt32ExternalLinksRecursionlessSizeBalancedTreeMethodsBase
17     {
18         /// <summary>
19         /// <para>
20         /// Initializes a new <see
21         ↳ cref="UInt32ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods"/> instance.
22         /// </para>
23         /// <para></para>
24         /// </summary>
25         /// <param name="constants">
26         /// <para>A constants.</para>
27         /// </param>
28         /// <param name="linksDataParts">
29         /// <para>A links data parts.</para>
30         /// </param>
31         /// <param name="linksIndexParts">
32         /// <para>A links index parts.</para>
33         /// </param>
34         /// <param name="header">
35         /// <para>A header.</para>
36         /// </param>
37         [MethodImpl(MethodImplOptions.AggressiveInlining)]
38         public UInt32ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
39         ↳ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
40         ↳ : base(constants, linksDataParts, linksIndexParts, header) { }
41
42         /// <summary>
43         /// <para>
44         /// Gets the left reference using the specified node.
45         /// </para>
46         /// <para></para>
47         /// </summary>
48         /// <param name="node">
49         /// <para>The node.</para>
50         /// </param>
51         /// <returns>
52         /// <para>The ref link</para>
53         /// </returns>
54         [MethodImpl(MethodImplOptions.AggressiveInlining)]
55         protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
56         ↳ LinksIndexParts[node].LeftAsSource;
57
58         /// <summary>
59         /// <para>
60         /// Gets the right reference using the specified node.
61         /// </para>
62         /// <para></para>
63         /// </summary>
64         /// <param name="node">
65         /// <para>The node.</para>
66         /// </param>
67         /// <returns>
68         /// <para>The ref link</para>
69         /// </returns>
70         /// <para></para>
71

```

```

72     /// </returns>
73     [MethodImpl(MethodImplOptions.AggressiveInlining)]
74     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
75     ↪ LinksIndexParts[node].RightAsSource;
76
77     /// <summary>
78     /// <para>
79     /// Gets the left using the specified node.
80     /// </para>
81     /// <para></para>
82     /// </summary>
83     /// <param name="node">
84     /// <para>The node.</para>
85     /// <para></para>
86     /// </param>
87     /// <returns>
88     /// <para>The link</para>
89     /// <para></para>
90     /// </returns>
91     [MethodImpl(MethodImplOptions.AggressiveInlining)]
92     protected override TLinkAddress GetLeft(TLinkAddress node) =>
93     ↪ LinksIndexParts[node].LeftAsSource;
94
95     /// <summary>
96     /// <para>
97     /// Gets the right using the specified node.
98     /// </para>
99     /// <para></para>
100    /// </summary>
101    /// <param name="node">
102    /// <para>The node.</para>
103    /// <para></para>
104    /// </param>
105    /// <returns>
106    /// <para>The link</para>
107    /// <para></para>
108    /// </returns>
109    [MethodImpl(MethodImplOptions.AggressiveInlining)]
110    protected override TLinkAddress GetRight(TLinkAddress node) =>
111    ↪ LinksIndexParts[node].RightAsSource;
112
113    /// <summary>
114    /// <para>
115    /// Sets the left using the specified node.
116    /// </para>
117    /// <para></para>
118    /// </summary>
119    /// <param name="node">
120    /// <para>The node.</para>
121    /// <para></para>
122    /// </param>
123    /// <param name="left">
124    /// <para>The left.</para>
125    /// <para></para>
126    /// </param>
127    [MethodImpl(MethodImplOptions.AggressiveInlining)]
128    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
129    ↪ LinksIndexParts[node].LeftAsSource = left;
130
131    /// <summary>
132    /// <para>
133    /// Sets the right using the specified node.
134    /// </para>
135    /// <para></para>
136    /// </summary>
137    /// <param name="node">
138    /// <para>The node.</para>
139    /// <para></para>
140    /// </param>
141    /// <param name="right">
142    /// <para>The right.</para>
143    /// <para></para>
144    /// </param>
145    [MethodImpl(MethodImplOptions.AggressiveInlining)]
146    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
147    ↪ LinksIndexParts[node].RightAsSource = right;

```



```

144    /// <summary>
145    /// <para>
146    /// Gets the size using the specified node.
147    /// </para>
148    /// <para></para>
149    /// </summary>
150    /// <param name="node">
151    /// <para>The node.</para>
152    /// <para></para>
153    /// </param>
154    /// <returns>
155    /// <para>The link</para>
156    /// <para></para>
157    /// </returns>
158    [MethodImpl(MethodImplOptions.AggressiveInlining)]
159    protected override TLinkAddress GetSize(TLinkAddress node) =>
160        ↪ LinksIndexParts[node].SizeAsSource;
161
162    /// <summary>
163    /// <para>
164    /// Sets the size using the specified node.
165    /// </para>
166    /// <para></para>
167    /// </summary>
168    /// <param name="node">
169    /// <para>The node.</para>
170    /// <para></para>
171    /// </param>
172    /// <param name="size">
173    /// <para>The size.</para>
174    /// <para></para>
175    /// </param>
176    [MethodImpl(MethodImplOptions.AggressiveInlining)]
177    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
178        ↪ LinksIndexParts[node].SizeAsSource = size;
179
180    /// <summary>
181    /// <para>
182    /// Gets the tree root.
183    /// </para>
184    /// <para></para>
185    /// </summary>
186    /// <returns>
187    /// <para>The link</para>
188    /// <para></para>
189    /// </returns>
190    [MethodImpl(MethodImplOptions.AggressiveInlining)]
191    protected override TLinkAddress GetTreeRoot() => Header->RootAsSource;
192
193    /// <summary>
194    /// <para>
195    /// Gets the base part value using the specified node.
196    /// </para>
197    /// <para></para>
198    /// </summary>
199    /// <param name="node">
200    /// <para>The node.</para>
201    /// <para></para>
202    /// </param>
203    /// <returns>
204    /// <para>The link</para>
205    /// <para></para>
206    /// </returns>
207    [MethodImpl(MethodImplOptions.AggressiveInlining)]
208    protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
209        ↪ LinksDataParts[node].Source;
210
211    /// <summary>
212    /// <para>
213    /// Determines whether this instance first is to the left of second.
214    /// </para>
215    /// <para></para>
216    /// </summary>
217    /// <param name="firstSource">
218    /// <para>The first source.</para>
219    /// <para></para>
220    /// </param>
221    /// <param name="firstTarget">

```

```

219     /// <para>The first target.</para>
220     /// <para></para>
221     /// </param>
222     /// <param name="secondSource">
223     /// <para>The second source.</para>
224     /// <para></para>
225     /// </param>
226     /// <param name="secondTarget">
227     /// <para>The second target.</para>
228     /// <para></para>
229     /// </param>
230     /// <returns>
231     /// <para>The bool</para>
232     /// <para></para>
233     /// </returns>
234     [MethodImpl(MethodImplOptions.AggressiveInlining)]
235     protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
236     => firstSource < secondSource || firstSource == secondSource && firstTarget <
    ↪ secondTarget;

237     /// <summary>
238     /// <para>
239     /// Determines whether this instance first is to the right of second.
240     /// </para>
241     /// <para></para>
242     /// </summary>
243     /// <param name="firstSource">
244     /// <para>The first source.</para>
245     /// <para></para>
246     /// </param>
247     /// <param name="firstTarget">
248     /// <para>The first target.</para>
249     /// <para></para>
250     /// </param>
251     /// <param name="secondSource">
252     /// <para>The second source.</para>
253     /// <para></para>
254     /// </param>
255     /// <param name="secondTarget">
256     /// <para>The second target.</para>
257     /// <para></para>
258     /// </param>
259     /// <returns>
260     /// <para>The bool</para>
261     /// <para></para>
262     /// </returns>
263     [MethodImpl(MethodImplOptions.AggressiveInlining)]
264     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
265     => firstSource > secondSource || firstSource == secondSource && firstTarget >
    ↪ secondTarget;

267     /// <summary>
268     /// <para>
269     /// Clears the node using the specified node.
270     /// </para>
271     /// <para></para>
272     /// </summary>
273     /// <param name="node">
274     /// <para>The node.</para>
275     /// <para></para>
276     /// </param>
277     [MethodImpl(MethodImplOptions.AggressiveInlining)]
278     protected override void ClearNode(TLinkAddress node)
279     {
280         {
281             ref var link = ref LinksIndexParts[node];
282             link.LeftAsSource = Zero;
283             link.RightAsSource = Zero;
284             link.SizeAsSource = Zero;
285         }
286     }
287 }

```

1.53 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksSourcesSizeBalancedTreeMeth

```

1 using System.Runtime.CompilerServices;
2 using TLinkAddress = System.UInt32;
3

```

```

4 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6 namespace Platform.Data.Doublets.Memory.Split.Specific
7 {
8     /// <summary>
9     /// <para>
10    /// Represents the int 32 external links sources size balanced tree methods.
11    /// </para>
12    /// <para></para>
13    /// </summary>
14    /// <seealso cref="UInt32ExternalLinksSizeBalancedTreeMethodsBase"/>
15    public unsafe class UInt32ExternalLinksSourcesSizeBalancedTreeMethods :
16    ↪ UInt32ExternalLinksSizeBalancedTreeMethodsBase
17    {
18        /// <summary>
19        /// <para>
20        /// Initializes a new <see cref="UInt32ExternalLinksSourcesSizeBalancedTreeMethods"/>
21        ↪ instance.
22        /// </para>
23        /// <para></para>
24        /// </summary>
25        /// <param name="constants">
26        /// <para>A constants.</para>
27        /// <para></para>
28        /// </param>
29        /// <param name="linksDataParts">
30        /// <para>A links data parts.</para>
31        /// <para></para>
32        /// </param>
33        /// <param name="linksIndexParts">
34        /// <para>A links index parts.</para>
35        /// <para></para>
36        /// </param>
37        /// <param name="header">
38        /// <para>A header.</para>
39        /// <para></para>
40        /// </param>
41        [MethodImpl(MethodImplOptions.AggressiveInlining)]
42        public UInt32ExternalLinksSourcesSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
43        ↪ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
44        ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
45        ↪ : base(constants, linksDataParts, linksIndexParts, header) { }
46
47        /// <summary>
48        /// <para>
49        /// Gets the left reference using the specified node.
50        /// </para>
51        /// <para></para>
52        /// </summary>
53        /// <param name="node">
54        /// <para>The node.</para>
55        /// <para></para>
56        /// </param>
57        /// <returns>
58        /// <para>The ref link</para>
59        /// <para></para>
60        /// </returns>
61        [MethodImpl(MethodImplOptions.AggressiveInlining)]
62        protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
63        ↪ LinksIndexParts[node].LeftAsSource;
64
65        /// <summary>
66        /// <para>
67        /// Gets the right reference using the specified node.
68        /// </para>
69        /// <para></para>
70        /// </summary>
71        /// <param name="node">
72        /// <para>The node.</para>
73        /// <para></para>
74        /// </param>
75        /// <returns>
76        /// <para>The ref link</para>
77        /// <para></para>
78        /// </returns>
79        [MethodImpl(MethodImplOptions.AggressiveInlining)]
80        protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
81        ↪ LinksIndexParts[node].RightAsSource;
82    }
83 }

```

```

75
76    /// <summary>
77    /// <para>
78    /// Gets the left using the specified node.
79    /// </para>
80    /// <para></para>
81    /// </summary>
82    /// <param name="node">
83    /// <para>The node.</para>
84    /// <para></para>
85    /// </param>
86    /// <returns>
87    /// <para>The link</para>
88    /// <para></para>
89    /// </returns>
90    [MethodImpl(MethodImplOptions.AggressiveInlining)]
91    protected override TLinkAddress GetLeft(TLinkAddress node) =>
92        ↪ LinksIndexParts[node].LeftAsSource;
93
94    /// <summary>
95    /// <para>
96    /// Gets the right using the specified node.
97    /// </para>
98    /// <para></para>
99    /// </summary>
100    /// <param name="node">
101    /// <para>The node.</para>
102    /// <para></para>
103    /// </param>
104    /// <returns>
105    /// <para>The link</para>
106    /// <para></para>
107    /// </returns>
108    [MethodImpl(MethodImplOptions.AggressiveInlining)]
109    protected override TLinkAddress GetRight(TLinkAddress node) =>
110        ↪ LinksIndexParts[node].RightAsSource;
111
112    /// <summary>
113    /// <para>
114    /// Sets the left using the specified node.
115    /// </para>
116    /// <para></para>
117    /// </summary>
118    /// <param name="node">
119    /// <para>The node.</para>
120    /// <para></para>
121    /// </param>
122    /// <param name="left">
123    /// <para>The left.</para>
124    /// <para></para>
125    /// </param>
126    [MethodImpl(MethodImplOptions.AggressiveInlining)]
127    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
128        ↪ LinksIndexParts[node].LeftAsSource = left;
129
130    /// <summary>
131    /// <para>
132    /// Sets the right using the specified node.
133    /// </para>
134    /// <para></para>
135    /// </summary>
136    /// <param name="node">
137    /// <para>The node.</para>
138    /// <para></para>
139    /// </param>
140    /// <param name="right">
141    /// <para>The right.</para>
142    /// <para></para>
143    /// </param>
144    [MethodImpl(MethodImplOptions.AggressiveInlining)]
145    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
146        ↪ LinksIndexParts[node].RightAsSource = right;
147
148    /// <summary>
149    /// <para>
150    /// Gets the size using the specified node.
151    /// </para>
152    /// <para></para>

```

```

149     /// </summary>
150     /// <param name="node">
151     /// <para>The node.</para>
152     /// <para></para>
153     /// </param>
154     /// <returns>
155     /// <para>The link</para>
156     /// <para></para>
157     /// </returns>
158     [MethodImpl(MethodImplOptions.AggressiveInlining)]
159     protected override TLinkAddress GetSize(TLinkAddress node) =>
160         ↪ LinksIndexParts[node].SizeAsSource;
161
162     /// <summary>
163     /// <para>
164     /// Sets the size using the specified node.
165     /// </para>
166     /// <para></para>
167     /// </summary>
168     /// <param name="node">
169     /// <para>The node.</para>
170     /// <para></para>
171     /// </param>
172     /// <param name="size">
173     /// <para>The size.</para>
174     /// <para></para>
175     /// </param>
176     [MethodImpl(MethodImplOptions.AggressiveInlining)]
177     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
178         ↪ LinksIndexParts[node].SizeAsSource = size;
179
180     /// <summary>
181     /// <para>
182     /// Gets the tree root.
183     /// </para>
184     /// <para></para>
185     /// </summary>
186     /// <returns>
187     /// <para>The link</para>
188     /// <para></para>
189     /// </returns>
190     [MethodImpl(MethodImplOptions.AggressiveInlining)]
191     protected override TLinkAddress GetTreeRoot() => Header->RootAsSource;
192
193     /// <summary>
194     /// <para>
195     /// Gets the base part value using the specified node.
196     /// </para>
197     /// <para></para>
198     /// </summary>
199     /// <param name="node">
200     /// <para>The node.</para>
201     /// <para></para>
202     /// </param>
203     /// <returns>
204     /// <para>The link</para>
205     /// <para></para>
206     /// </returns>
207     [MethodImpl(MethodImplOptions.AggressiveInlining)]
208     protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
209         ↪ LinksDataParts[node].Source;
210
211     /// <summary>
212     /// <para>
213     /// Determines whether this instance first is to the left of second.
214     /// </para>
215     /// <para></para>
216     /// </summary>
217     /// <param name="firstSource">
218     /// <para>The first source.</para>
219     /// <para></para>
220     /// </param>
221     /// <param name="firstTarget">
222     /// <para>The first target.</para>
223     /// <para></para>
224     /// </param>
225     /// <param name="secondSource">
226     /// <para>The second source.</para>
227     /// <para></para>
228     /// </param>

```

```

224     /// <para></para>
225     /// </param>
226     /// <param name="secondTarget">
227     /// <para>The second target.</para>
228     /// <para></para>
229     /// </param>
230     /// <returns>
231     /// <para>The bool</para>
232     /// <para></para>
233     /// </returns>
234     [MethodImpl(MethodImplOptions.AggressiveInlining)]
235     protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
236     => firstSource < secondSource || firstSource == secondSource && firstTarget <
    ↪ secondTarget;

237
238     /// <summary>
239     /// <para>
240     /// Determines whether this instance first is to the right of second.
241     /// </para>
242     /// <para></para>
243     /// </summary>
244     /// <param name="firstSource">
245     /// <para>The first source.</para>
246     /// <para></para>
247     /// </param>
248     /// <param name="firstTarget">
249     /// <para>The first target.</para>
250     /// <para></para>
251     /// </param>
252     /// <param name="secondSource">
253     /// <para>The second source.</para>
254     /// <para></para>
255     /// </param>
256     /// <param name="secondTarget">
257     /// <para>The second target.</para>
258     /// <para></para>
259     /// </param>
260     /// <returns>
261     /// <para>The bool</para>
262     /// <para></para>
263     /// </returns>
264     [MethodImpl(MethodImplOptions.AggressiveInlining)]
265     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
266     => firstSource > secondSource || firstSource == secondSource && firstTarget >
    ↪ secondTarget;

267
268     /// <summary>
269     /// <para>
270     /// Clears the node using the specified node.
271     /// </para>
272     /// <para></para>
273     /// </summary>
274     /// <param name="node">
275     /// <para>The node.</para>
276     /// <para></para>
277     /// </param>
278     [MethodImpl(MethodImplOptions.AggressiveInlining)]
279     protected override void ClearNode(TLinkAddress node)
280     {
281         ref var link = ref LinksIndexParts[node];
282         link.LeftAsSource = Zero;
283         link.RightAsSource = Zero;
284         link.SizeAsSource = Zero;
285     }
286 }
287 }

```

1.54 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksTargetsRecursionlessSizeBalance

```

1 using System.Runtime.CompilerServices;
2 using TLinkAddress = System.UInt32;
3
4 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6 namespace Platform.Data.Doublets.Memory.Split.Specific
7 {
8     /// <summary>

```

```

9  /// <para>
10  /// Represents the int 32 external links targets recursionless size balanced tree methods.
11  /// </para>
12  /// <para></para>
13  /// </summary>
14  /// <seealso cref="UInt32ExternalLinksRecursionlessSizeBalancedTreeMethodsBase"/>
15  public unsafe class UInt32ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods :
16  {
17      /// <summary>
18      /// <para>
19      /// Initializes a new <see
20      ↪ cref="UInt32ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods"/> instance.
21      /// </para>
22      /// <para></para>
23      /// </summary>
24      /// <param name="constants">
25      /// <para>A constants.</para>
26      /// <para></para>
27      /// </param>
28      /// <param name="linksDataParts">
29      /// <para>A links data parts.</para>
30      /// <para></para>
31      /// </param>
32      /// <param name="linksIndexParts">
33      /// <para>A links index parts.</para>
34      /// <para></para>
35      /// </param>
36      /// <param name="header">
37      /// <para>A header.</para>
38      /// <para></para>
39      /// </param>
40      [MethodImpl(MethodImplOptions.AggressiveInlining)]
41      public UInt32ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods(LinksConstants<TLi
42      ↪ nkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
43      ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
44      ↪ : base(constants, linksDataParts, linksIndexParts, header) { }
45
46      /// <summary>
47      /// <para>
48      /// Gets the left reference using the specified node.
49      /// </para>
50      /// <para></para>
51      /// </summary>
52      /// <param name="node">
53      /// <para>The node.</para>
54      /// <para></para>
55      /// </param>
56      /// <returns>
57      /// <para>The ref link</para>
58      /// <para></para>
59      /// </returns>
60      [MethodImpl(MethodImplOptions.AggressiveInlining)]
61      protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
62      ↪ LinksIndexParts[node].LeftAsTarget;
63
64      /// <summary>
65      /// <para>
66      /// Gets the right reference using the specified node.
67      /// </para>
68      /// <para></para>
69      /// </summary>
70      /// <param name="node">
71      /// <para>The node.</para>
72      /// <para></para>
73      /// </param>
74      /// <returns>
75      /// <para>The ref link</para>
76      /// <para></para>
77      /// </returns>
78      [MethodImpl(MethodImplOptions.AggressiveInlining)]
79      protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
80      ↪ LinksIndexParts[node].RightAsTarget;
81
82      /// <summary>
83      /// <para>
84      /// Gets the left using the specified node.
85      /// </para>

```

```

80     /// <para></para>
81     /// </summary>
82     /// <param name="node">
83     /// <para>The node.</para>
84     /// <para></para>
85     /// </param>
86     /// <returns>
87     /// <para>The link</para>
88     /// <para></para>
89     /// </returns>
90     [MethodImpl(MethodImplOptions.AggressiveInlining)]
91     protected override TLinkAddress GetLeft(TLinkAddress node) =>
92         ↪ LinksIndexParts[node].LeftAsTarget;
93
94     /// <summary>
95     /// <para>
96     /// Gets the right using the specified node.
97     /// </para>
98     /// <para></para>
99     /// </summary>
100    /// <param name="node">
101    /// <para>The node.</para>
102    /// <para></para>
103    /// </param>
104    /// <returns>
105    /// <para>The link</para>
106    /// <para></para>
107    /// </returns>
108    [MethodImpl(MethodImplOptions.AggressiveInlining)]
109    protected override TLinkAddress GetRight(TLinkAddress node) =>
110        ↪ LinksIndexParts[node].RightAsTarget;
111
112    /// <summary>
113    /// <para>
114    /// Sets the left using the specified node.
115    /// </para>
116    /// <para></para>
117    /// </summary>
118    /// <param name="node">
119    /// <para>The node.</para>
120    /// <para></para>
121    /// </param>
122    /// <param name="left">
123    /// <para>The left.</para>
124    /// <para></para>
125    /// </param>
126    [MethodImpl(MethodImplOptions.AggressiveInlining)]
127    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
128        ↪ LinksIndexParts[node].LeftAsTarget = left;
129
130    /// <summary>
131    /// <para>
132    /// Sets the right using the specified node.
133    /// </para>
134    /// <para></para>
135    /// </summary>
136    /// <param name="node">
137    /// <para>The node.</para>
138    /// <para></para>
139    /// </param>
140    /// <param name="right">
141    /// <para>The right.</para>
142    /// <para></para>
143    /// </param>
144    [MethodImpl(MethodImplOptions.AggressiveInlining)]
145    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
146        ↪ LinksIndexParts[node].RightAsTarget = right;
147
148    /// <summary>
149    /// <para>
150    /// Gets the size using the specified node.
151    /// </para>
152    /// <para></para>
153    /// </summary>
154    /// <param name="node">
155    /// <para>The node.</para>
156    /// <para></para>
157    /// </param>

```



```

154    /// <returns>
155    /// <para>The link</para>
156    /// <para></para>
157    /// </returns>
158    [MethodImpl(MethodImplOptions.AggressiveInlining)]
159    protected override TLinkAddress GetSize(TLinkAddress node) =>
160        ↳ LinksIndexParts[node].SizeAsTarget;
161
162    /// <summary>
163    /// <para>
164    /// Sets the size using the specified node.
165    /// </para>
166    /// <para></para>
167    /// </summary>
168    /// <param name="node">
169    /// <para>The node.</para>
170    /// <para></para>
171    /// </param>
172    /// <param name="size">
173    /// <para>The size.</para>
174    /// <para></para>
175    /// </param>
176    [MethodImpl(MethodImplOptions.AggressiveInlining)]
177    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
178        ↳ LinksIndexParts[node].SizeAsTarget = size;
179
180    /// <summary>
181    /// <para>
182    /// Gets the tree root.
183    /// </para>
184    /// <para></para>
185    /// </summary>
186    /// <returns>
187    /// <para>The link</para>
188    /// <para></para>
189    /// </returns>
190    [MethodImpl(MethodImplOptions.AggressiveInlining)]
191    protected override TLinkAddress GetTreeRoot() => Header->RootAsTarget;
192
193    /// <summary>
194    /// <para>
195    /// Gets the base part value using the specified node.
196    /// </para>
197    /// <para></para>
198    /// </summary>
199    /// <param name="node">
200    /// <para>The node.</para>
201    /// <para></para>
202    /// </param>
203    /// <returns>
204    /// <para>The link</para>
205    /// <para></para>
206    /// </returns>
207    [MethodImpl(MethodImplOptions.AggressiveInlining)]
208    protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
209        ↳ LinksDataParts[node].Target;
210
211    /// <summary>
212    /// <para>
213    /// Determines whether this instance first is to the left of second.
214    /// </para>
215    /// <para></para>
216    /// </summary>
217    /// <param name="firstSource">
218    /// <para>The first source.</para>
219    /// <para></para>
220    /// </param>
221    /// <param name="firstTarget">
222    /// <para>The first target.</para>
223    /// <para></para>
224    /// </param>
225    /// <param name="secondSource">
226    /// <para>The second source.</para>
227    /// <para></para>
228    /// </param>
229    /// <param name="secondTarget">
230    /// <para>The second target.</para>
231    /// <para></para>
232    /// </param>

```

```

229     /// </param>
230     /// <returns>
231     /// <para>The bool</para>
232     /// <para></para>
233     /// </returns>
234     [MethodImpl(MethodImplOptions.AggressiveInlining)]
235     protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
236     => firstTarget < secondTarget || firstTarget == secondTarget && firstSource <
    ↪ secondSource;

237
238     /// <summary>
239     /// <para>
240     /// Determines whether this instance first is to the right of second.
241     /// </para>
242     /// <para></para>
243     /// </summary>
244     /// <param name="firstSource">
245     /// <para>The first source.</para>
246     /// <para></para>
247     /// </param>
248     /// <param name="firstTarget">
249     /// <para>The first target.</para>
250     /// <para></para>
251     /// </param>
252     /// <param name="secondSource">
253     /// <para>The second source.</para>
254     /// <para></para>
255     /// </param>
256     /// <param name="secondTarget">
257     /// <para>The second target.</para>
258     /// <para></para>
259     /// </param>
260     /// <returns>
261     /// <para>The bool</para>
262     /// <para></para>
263     /// </returns>
264     [MethodImpl(MethodImplOptions.AggressiveInlining)]
265     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
266     => firstTarget > secondTarget || firstTarget == secondTarget && firstSource >
    ↪ secondSource;

267
268     /// <summary>
269     /// <para>
270     /// Clears the node using the specified node.
271     /// </para>
272     /// <para></para>
273     /// </summary>
274     /// <param name="node">
275     /// <para>The node.</para>
276     /// <para></para>
277     /// </param>
278     [MethodImpl(MethodImplOptions.AggressiveInlining)]
279     protected override void ClearNode(TLinkAddress node)
280     {
281         ref var link = ref LinksIndexParts[node];
282         link.LeftAsTarget = Zero;
283         link.RightAsTarget = Zero;
284         link.SizeAsTarget = Zero;
285     }
286 }
287 }

```

1.55 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksTargetsSizeBalancedTreeMethods

```

1 using System.Runtime.CompilerServices;
2 using TLinkAddress = System.UInt32;
3
4 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6 namespace Platform.Data.Doublets.Memory.Split.Specific
7 {
8     /// <summary>
9     /// <para>
10     /// Represents the int 32 external links targets size balanced tree methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>

```

```

14  /// <seealso cref="UInt32ExternalLinksSizeBalancedTreeMethodsBase"/>
15  public unsafe class UInt32ExternalLinksTargetsSizeBalancedTreeMethods :
    ↳ UInt32ExternalLinksSizeBalancedTreeMethodsBase
16  {
17      /// <summary>
18      /// <para>
19      /// Initializes a new <see cref="UInt32ExternalLinksTargetsSizeBalancedTreeMethods"/>
    ↳ instance.
20      /// </para>
21      /// <para></para>
22      /// </summary>
23      /// <param name="constants">
24      /// <para>A constants.</para>
25      /// <para></para>
26      /// </param>
27      /// <param name="linksDataParts">
28      /// <para>A links data parts.</para>
29      /// <para></para>
30      /// </param>
31      /// <param name="linksIndexParts">
32      /// <para>A links index parts.</para>
33      /// <para></para>
34      /// </param>
35      /// <param name="header">
36      /// <para>A header.</para>
37      /// <para></para>
38      /// </param>
39      [MethodImpl(MethodImplOptions.AggressiveInlining)]
40      public UInt32ExternalLinksTargetsSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
    ↳ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
    ↳ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
    ↳ : base(constants, linksDataParts, linksIndexParts, header) { }
41
42      /// <summary>
43      /// <para>
44      /// Gets the left reference using the specified node.
45      /// </para>
46      /// <para></para>
47      /// </summary>
48      /// <param name="node">
49      /// <para>The node.</para>
50      /// <para></para>
51      /// </param>
52      /// <returns>
53      /// <para>The ref link</para>
54      /// <para></para>
55      /// </returns>
56      [MethodImpl(MethodImplOptions.AggressiveInlining)]
57      protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↳ LinksIndexParts[node].LeftAsTarget;
58
59      /// <summary>
60      /// <para>
61      /// Gets the right reference using the specified node.
62      /// </para>
63      /// <para></para>
64      /// </summary>
65      /// <param name="node">
66      /// <para>The node.</para>
67      /// <para></para>
68      /// </param>
69      /// <returns>
70      /// <para>The ref link</para>
71      /// <para></para>
72      /// </returns>
73      [MethodImpl(MethodImplOptions.AggressiveInlining)]
74      protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↳ LinksIndexParts[node].RightAsTarget;
75
76      /// <summary>
77      /// <para>
78      /// Gets the left using the specified node.
79      /// </para>
80      /// <para></para>
81      /// </summary>
82      /// <param name="node">
83      /// <para>The node.</para>
84      /// <para></para>

```

```

85     /// </param>
86     /// <returns>
87     /// <para>The link</para>
88     /// <para></para>
89     /// </returns>
90     [MethodImpl(MethodImplOptions.AggressiveInlining)]
91     protected override TLinkAddress GetLeft(TLinkAddress node) =>
92         ↪ LinksIndexParts[node].LeftAsTarget;
93
94     /// <summary>
95     /// <para>
96     /// Gets the right using the specified node.
97     /// </para>
98     /// <para></para>
99     /// </summary>
100    /// <param name="node">
101    /// <para>The node.</para>
102    /// <para></para>
103    /// </param>
104    /// <returns>
105    /// <para>The link</para>
106    /// <para></para>
107    /// </returns>
108    [MethodImpl(MethodImplOptions.AggressiveInlining)]
109    protected override TLinkAddress GetRight(TLinkAddress node) =>
110        ↪ LinksIndexParts[node].RightAsTarget;
111
112    /// <summary>
113    /// <para>
114    /// Sets the left using the specified node.
115    /// </para>
116    /// <para></para>
117    /// </summary>
118    /// <param name="node">
119    /// <para>The node.</para>
120    /// <para></para>
121    /// </param>
122    /// <param name="left">
123    /// <para>The left.</para>
124    /// <para></para>
125    /// </param>
126    [MethodImpl(MethodImplOptions.AggressiveInlining)]
127    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
128        ↪ LinksIndexParts[node].LeftAsTarget = left;
129
130    /// <summary>
131    /// <para>
132    /// Sets the right using the specified node.
133    /// </para>
134    /// <para></para>
135    /// </summary>
136    /// <param name="node">
137    /// <para>The node.</para>
138    /// <para></para>
139    /// </param>
140    /// <param name="right">
141    /// <para>The right.</para>
142    /// <para></para>
143    /// </param>
144    [MethodImpl(MethodImplOptions.AggressiveInlining)]
145    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
146        ↪ LinksIndexParts[node].RightAsTarget = right;
147
148    /// <summary>
149    /// <para>
150    /// Gets the size using the specified node.
151    /// </para>
152    /// <para></para>
153    /// </summary>
154    /// <param name="node">
155    /// <para>The node.</para>
156    /// <para></para>
157    /// </param>
158    /// <returns>
159    /// <para>The link</para>
160    /// <para></para>
161    /// </returns>
162    [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

159     protected override TLinkAddress GetSize(TLinkAddress node) =>
160         ↪ LinksIndexParts[node].SizeAsTarget;
161
162     /// <summary>
163     /// <para>
164     /// Sets the size using the specified node.
165     /// </para>
166     /// </summary>
167     /// <param name="node">
168     /// <para>The node.</para>
169     /// </param>
170     /// <param name="size">
171     /// <para>The size.</para>
172     /// </param>
173     [MethodImpl(MethodImplOptions.AggressiveInlining)]
174     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
175         ↪ LinksIndexParts[node].SizeAsTarget = size;
176
177     /// <summary>
178     /// <para>
179     /// Gets the tree root.
180     /// </para>
181     /// </summary>
182     /// <returns>
183     /// <para>The link</para>
184     /// </returns>
185     [MethodImpl(MethodImplOptions.AggressiveInlining)]
186     protected override TLinkAddress GetTreeRoot() => Header->RootAsTarget;
187
188     /// <summary>
189     /// <para>
190     /// Gets the base part value using the specified node.
191     /// </para>
192     /// </summary>
193     /// <param name="node">
194     /// <para>The node.</para>
195     /// </param>
196     /// <returns>
197     /// <para>The link</para>
198     /// </returns>
199     [MethodImpl(MethodImplOptions.AggressiveInlining)]
200     protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
201         ↪ LinksDataParts[node].Target;
202
203     /// <summary>
204     /// <para>
205     /// Determines whether this instance first is to the left of second.
206     /// </para>
207     /// </summary>
208     /// <param name="firstSource">
209     /// <para>The first source.</para>
210     /// </param>
211     /// <param name="firstTarget">
212     /// <para>The first target.</para>
213     /// </param>
214     /// <param name="secondSource">
215     /// <para>The second source.</para>
216     /// </param>
217     /// <param name="secondTarget">
218     /// <para>The second target.</para>
219     /// </param>
220     /// <returns>
221     /// <para>The bool</para>
222     /// </returns>
223

```

```

234 [MethodImpl(MethodImplOptions.AggressiveInlining)]
235 protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
236 => firstTarget < secondTarget || firstTarget == secondTarget && firstSource <
    ↪ secondSource;

237
238 /// <summary>
239 /// <para>
240 /// Determines whether this instance first is to the right of second.
241 /// </para>
242 /// <para></para>
243 /// </summary>
244 /// <param name="firstSource">
245 /// <para>The first source.</para>
246 /// <para></para>
247 /// </param>
248 /// <param name="firstTarget">
249 /// <para>The first target.</para>
250 /// <para></para>
251 /// </param>
252 /// <param name="secondSource">
253 /// <para>The second source.</para>
254 /// <para></para>
255 /// </param>
256 /// <param name="secondTarget">
257 /// <para>The second target.</para>
258 /// <para></para>
259 /// </param>
260 /// <returns>
261 /// <para>The bool</para>
262 /// <para></para>
263 /// </returns>
264 [MethodImpl(MethodImplOptions.AggressiveInlining)]
265 protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
266 => firstTarget > secondTarget || firstTarget == secondTarget && firstSource >
    ↪ secondSource;

267
268 /// <summary>
269 /// <para>
270 /// Clears the node using the specified node.
271 /// </para>
272 /// <para></para>
273 /// </summary>
274 /// <param name="node">
275 /// <para>The node.</para>
276 /// <para></para>
277 /// </param>
278 [MethodImpl(MethodImplOptions.AggressiveInlining)]
279 protected override void ClearNode(TLinkAddress node)
280 {
281     ref var link = ref LinksIndexParts[node];
282     link.LeftAsTarget = Zero;
283     link.RightAsTarget = Zero;
284     link.SizeAsTarget = Zero;
285 }
286 }
287 }

```

1.56 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksRecursionlessSizeBalancedTreeM

```

1 using System.Runtime.CompilerServices;
2 using Platform.Data.Doublets.Memory.Split.Generic;
3 using TLinkAddress = System.UInt32;
4
5 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7 namespace Platform.Data.Doublets.Memory.Split.Specific
8 {
9     /// <summary>
10    /// <para>
11    /// Represents the int 32 internal links recursionless size balanced tree methods base.
12    /// </para>
13    /// <para></para>
14    /// </summary>
15    /// <seealso cref="InternalLinksRecursionlessSizeBalancedTreeMethodsBase{TLinkAddress}"/>
16    public unsafe abstract class UInt32InternalLinksRecursionlessSizeBalancedTreeMethodsBase :
    ↪ InternalLinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress>
17    {

```

```

18     /// <summary>
19     /// <para>
20     /// The links data parts.
21     /// </para>
22     /// <para></para>
23     /// </summary>
24     protected new readonly RawLinkDataPart<TLinkAddress>* LinksDataParts;
25     /// <summary>
26     /// <para>
27     /// The links index parts.
28     /// </para>
29     /// <para></para>
30     /// </summary>
31     protected new readonly RawLinkIndexPart<TLinkAddress>* LinksIndexParts;
32     /// <summary>
33     /// <para>
34     /// The header.
35     /// </para>
36     /// <para></para>
37     /// </summary>
38     protected new readonly LinksHeader<TLinkAddress>* Header;
39
40     /// <summary>
41     /// <para>
42     /// Initializes a new <see
43     ↪ cref="UInt32InternalLinksRecursionlessSizeBalancedTreeMethodsBase"/> instance.
44     /// </para>
45     /// <para></para>
46     /// </summary>
47     /// <param name="constants">
48     /// <para>A constants.</para>
49     /// </param>
50     /// <param name="linksDataParts">
51     /// <para>A links data parts.</para>
52     /// </param>
53     /// <param name="linksIndexParts">
54     /// <para>A links index parts.</para>
55     /// </param>
56     /// <param name="header">
57     /// <para>A header.</para>
58     /// </param>
59     [MethodImpl(MethodImplOptions.AggressiveInlining)]
60     protected UInt32InternalLinksRecursionlessSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
61     ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
62     : base(constants, (byte*)linksDataParts, (byte*)linksIndexParts, (byte*)header)
63     {
64         LinksDataParts = linksDataParts;
65         LinksIndexParts = linksIndexParts;
66         Header = header;
67     }
68
69     /// <summary>
70     /// <para>
71     /// Gets the zero.
72     /// </para>
73     /// <para></para>
74     /// </summary>
75     /// <returns>
76     /// <para>The link</para>
77     /// <para></para>
78     /// </returns>
79     [MethodImpl(MethodImplOptions.AggressiveInlining)]
80     protected override TLinkAddress GetZero() => 0U;
81
82     /// <summary>
83     /// <para>
84     /// Determines whether this instance equal to zero.
85     /// </para>
86     /// <para></para>
87     /// </summary>
88     /// <param name="value">
89     /// <para>The value.</para>
90     /// </param>
91     /// <para></para>
92     /// </summary>

```

```

93     /// </param>
94     /// <returns>
95     /// <para>The bool</para>
96     /// <para></para>
97     /// </returns>
98     [MethodImpl(MethodImplOptions.AggressiveInlining)]
99     protected override bool EqualToZero(TLinkAddress value) => value == 0U;
100
101     /// <summary>
102     /// <para>
103     /// Determines whether this instance are equal.
104     /// </para>
105     /// <para></para>
106     /// </summary>
107     /// <param name="first">
108     /// <para>The first.</para>
109     /// <para></para>
110     /// </param>
111     /// <param name="second">
112     /// <para>The second.</para>
113     /// <para></para>
114     /// </param>
115     /// <returns>
116     /// <para>The bool</para>
117     /// <para></para>
118     /// </returns>
119     [MethodImpl(MethodImplOptions.AggressiveInlining)]
120     protected override bool AreEqual(TLinkAddress first, TLinkAddress second) => first ==
        ↳ second;
121
122     /// <summary>
123     /// <para>
124     /// Determines whether this instance greater than zero.
125     /// </para>
126     /// <para></para>
127     /// </summary>
128     /// <param name="value">
129     /// <para>The value.</para>
130     /// <para></para>
131     /// </param>
132     /// <returns>
133     /// <para>The bool</para>
134     /// <para></para>
135     /// </returns>
136     [MethodImpl(MethodImplOptions.AggressiveInlining)]
137     protected override bool GreaterThanZero(TLinkAddress value) => value > 0U;
138
139     /// <summary>
140     /// <para>
141     /// Determines whether this instance greater than.
142     /// </para>
143     /// <para></para>
144     /// </summary>
145     /// <param name="first">
146     /// <para>The first.</para>
147     /// <para></para>
148     /// </param>
149     /// <param name="second">
150     /// <para>The second.</para>
151     /// <para></para>
152     /// </param>
153     /// <returns>
154     /// <para>The bool</para>
155     /// <para></para>
156     /// </returns>
157     [MethodImpl(MethodImplOptions.AggressiveInlining)]
158     protected override bool GreaterThan(TLinkAddress first, TLinkAddress second) => first >
        ↳ second;
159
160     /// <summary>
161     /// <para>
162     /// Determines whether this instance greater or equal than.
163     /// </para>
164     /// <para></para>
165     /// </summary>
166     /// <param name="first">
167     /// <para>The first.</para>
168     /// <para></para>

```



```

169     /// </param>
170     /// <param name="second">
171     /// <para>The second.</para>
172     /// <para></para>
173     /// </param>
174     /// <returns>
175     /// <para>The bool</para>
176     /// <para></para>
177     /// </returns>
178     [MethodImpl(MethodImplOptions.AggressiveInlining)]
179     protected override bool GreaterOrEqualThan(TLinkAddress first, TLinkAddress second) =>
180         ↪ first >= second;
181
182     /// <summary>
183     /// <para>
184     /// Determines whether this instance greater or equal than zero.
185     /// </para>
186     /// <para></para>
187     /// </summary>
188     /// <param name="value">
189     /// <para>The value.</para>
190     /// <para></para>
191     /// </param>
192     /// <returns>
193     /// <para>The bool</para>
194     /// <para></para>
195     /// </returns>
196     [MethodImpl(MethodImplOptions.AggressiveInlining)]
197     protected override bool GreaterOrEqualThanZero(TLinkAddress value) => true; // value >=
198         ↪ 0 is always true for ulong
199
200     /// <summary>
201     /// <para>
202     /// Determines whether this instance less or equal than zero.
203     /// </para>
204     /// <para></para>
205     /// </summary>
206     /// <param name="value">
207     /// <para>The value.</para>
208     /// <para></para>
209     /// </param>
210     /// <returns>
211     /// <para>The bool</para>
212     /// <para></para>
213     /// </returns>
214     [MethodImpl(MethodImplOptions.AggressiveInlining)]
215     protected override bool LessOrEqualThanZero(TLinkAddress value) => value == OUL; //
216         ↪ value is always >= 0 for ulong
217
218     /// <summary>
219     /// <para>
220     /// Determines whether this instance less or equal than.
221     /// </para>
222     /// <para></para>
223     /// </summary>
224     /// <param name="first">
225     /// <para>The first.</para>
226     /// <para></para>
227     /// </param>
228     /// <param name="second">
229     /// <para>The second.</para>
230     /// <para></para>
231     /// </param>
232     /// <returns>
233     /// <para>The bool</para>
234     /// <para></para>
235     /// </returns>
236     [MethodImpl(MethodImplOptions.AggressiveInlining)]
237     protected override bool LessOrEqualThan(TLinkAddress first, TLinkAddress second) =>
238         ↪ first <= second;
239
240     /// <summary>
241     /// <para>
242     /// Determines whether this instance less than zero.
243     /// </para>
244     /// <para></para>
245     /// </summary>
246     /// <param name="value">

```

```

243     /// <para>The value.</para>
244     /// <para></para>
245     /// </param>
246     /// <returns>
247     /// <para>The bool</para>
248     /// <para></para>
249     /// </returns>
250     [MethodImpl(MethodImplOptions.AggressiveInlining)]
251     protected override bool LessThanZero(TLinkAddress value) => false; // value < 0 is
    ↪ always false for ulong
252
253     /// <summary>
254     /// <para>
255     /// Determines whether this instance less than.
256     /// </para>
257     /// <para></para>
258     /// </summary>
259     /// <param name="first">
260     /// <para>The first.</para>
261     /// <para></para>
262     /// </param>
263     /// <param name="second">
264     /// <para>The second.</para>
265     /// <para></para>
266     /// </param>
267     /// <returns>
268     /// <para>The bool</para>
269     /// <para></para>
270     /// </returns>
271     [MethodImpl(MethodImplOptions.AggressiveInlining)]
272     protected override bool LessThan(TLinkAddress first, TLinkAddress second) => first <
    ↪ second;
273
274     /// <summary>
275     /// <para>
276     /// Increments the value.
277     /// </para>
278     /// <para></para>
279     /// </summary>
280     /// <param name="value">
281     /// <para>The value.</para>
282     /// <para></para>
283     /// </param>
284     /// <returns>
285     /// <para>The link</para>
286     /// <para></para>
287     /// </returns>
288     [MethodImpl(MethodImplOptions.AggressiveInlining)]
289     protected override TLinkAddress Increment(TLinkAddress value) => ++value;
290
291     /// <summary>
292     /// <para>
293     /// Decrements the value.
294     /// </para>
295     /// <para></para>
296     /// </summary>
297     /// <param name="value">
298     /// <para>The value.</para>
299     /// <para></para>
300     /// </param>
301     /// <returns>
302     /// <para>The link</para>
303     /// <para></para>
304     /// </returns>
305     [MethodImpl(MethodImplOptions.AggressiveInlining)]
306     protected override TLinkAddress Decrement(TLinkAddress value) => --value;
307
308     /// <summary>
309     /// <para>
310     /// Adds the first.
311     /// </para>
312     /// <para></para>
313     /// </summary>
314     /// <param name="first">
315     /// <para>The first.</para>
316     /// <para></para>
317     /// </param>
318     /// <param name="second">

```

```

319    /// <para>The second.</para>
320    /// <para></para>
321    /// </param>
322    /// <returns>
323    /// <para>The link</para>
324    /// <para></para>
325    /// </returns>
326    [MethodImpl(MethodImplOptions.AggressiveInlining)]
327    protected override TLinkAddress Add(TLinkAddress first, TLinkAddress second) => first +
    ↪ second;
328
329    /// <summary>
330    /// <para>
331    /// Subtracts the first.
332    /// </para>
333    /// <para></para>
334    /// </summary>
335    /// <param name="first">
336    /// <para>The first.</para>
337    /// <para></para>
338    /// </param>
339    /// <param name="second">
340    /// <para>The second.</para>
341    /// <para></para>
342    /// </param>
343    /// <returns>
344    /// <para>The link</para>
345    /// <para></para>
346    /// </returns>
347    [MethodImpl(MethodImplOptions.AggressiveInlining)]
348    protected override TLinkAddress Subtract(TLinkAddress first, TLinkAddress second) =>
    ↪ first - second;
349
350    /// <summary>
351    /// <para>
352    /// Gets the link data part reference using the specified link.
353    /// </para>
354    /// <para></para>
355    /// </summary>
356    /// <param name="link">
357    /// <para>The link.</para>
358    /// <para></para>
359    /// </param>
360    /// <returns>
361    /// <para>A ref raw link data part of t link</para>
362    /// <para></para>
363    /// </returns>
364    [MethodImpl(MethodImplOptions.AggressiveInlining)]
365    protected override ref RawLinkDataPart<TLinkAddress>
    ↪ GetLinkDataPartReference(TLinkAddress link) => ref LinksDataParts[link];
366
367    /// <summary>
368    /// <para>
369    /// Gets the link index part reference using the specified link.
370    /// </para>
371    /// <para></para>
372    /// </summary>
373    /// <param name="link">
374    /// <para>The link.</para>
375    /// <para></para>
376    /// </param>
377    /// <returns>
378    /// <para>A ref raw link index part of t link</para>
379    /// <para></para>
380    /// </returns>
381    [MethodImpl(MethodImplOptions.AggressiveInlining)]
382    protected override ref RawLinkIndexPart<TLinkAddress>
    ↪ GetLinkIndexPartReference(TLinkAddress link) => ref LinksIndexParts[link];
383
384    /// <summary>
385    /// <para>
386    /// Determines whether this instance first is to the left of second.
387    /// </para>
388    /// <para></para>
389    /// </summary>
390    /// <param name="first">
391    /// <para>The first.</para>
392    /// <para></para>

```

```

393     /// </param>
394     /// <param name="second">
395     /// <para>The second.</para>
396     /// <para></para>
397     /// </param>
398     /// <returns>
399     /// <para>The bool</para>
400     /// <para></para>
401     /// </returns>
402     [MethodImpl(MethodImplOptions.AggressiveInlining)]
403     protected override bool FirstIsToTheLeftOfSecond(TLinkAddress first, TLinkAddress
    ↪ second) => GetKeyPartValue(first) < GetKeyPartValue(second);
404
405     /// <summary>
406     /// <para>
407     /// Determines whether this instance first is to the right of second.
408     /// </para>
409     /// <para></para>
410     /// </summary>
411     /// <param name="first">
412     /// <para>The first.</para>
413     /// <para></para>
414     /// </param>
415     /// <param name="second">
416     /// <para>The second.</para>
417     /// <para></para>
418     /// </param>
419     /// <returns>
420     /// <para>The bool</para>
421     /// <para></para>
422     /// </returns>
423     [MethodImpl(MethodImplOptions.AggressiveInlining)]
424     protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
    ↪ second) => GetKeyPartValue(first) > GetKeyPartValue(second);
425 }
426 }

```

1.57 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksSizeBalancedTreeMethodsBase.

```

1 using System.Runtime.CompilerServices;
2 using Platform.Data.Doublets.Memory.Split.Generic;
3 using TLinkAddress = System.UInt32;
4
5 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7 namespace Platform.Data.Doublets.Memory.Split.Specific
8 {
9     /// <summary>
10    /// <para>
11    /// Represents the int 32 internal links size balanced tree methods base.
12    /// </para>
13    /// <para></para>
14    /// </summary>
15    /// <seealso cref="InternalLinksSizeBalancedTreeMethodsBase{TLinkAddress}"/>
16    public unsafe abstract class UInt32InternalLinksSizeBalancedTreeMethodsBase :
    ↪ InternalLinksSizeBalancedTreeMethodsBase<TLinkAddress>
17    {
18        /// <summary>
19        /// <para>
20        /// The links data parts.
21        /// </para>
22        /// <para></para>
23        /// </summary>
24        protected new readonly RawLinkDataPart<TLinkAddress>* LinksDataParts;
25        /// <summary>
26        /// <para>
27        /// The links index parts.
28        /// </para>
29        /// <para></para>
30        /// </summary>
31        protected new readonly RawLinkIndexPart<TLinkAddress>* LinksIndexParts;
32        /// <summary>
33        /// <para>
34        /// The header.
35        /// </para>
36        /// <para></para>
37        /// </summary>
38        protected new readonly LinksHeader<TLinkAddress>* Header;
39

```

```

40    /// <summary>
41    /// <para>
42    /// Initializes a new <see cref="UInt32InternalLinksSizeBalancedTreeMethodsBase"/>
    ↪ instance.
43    /// </para>
44    /// <para></para>
45    /// </summary>
46    /// <param name="constants">
47    /// <para>A constants.</para>
48    /// <para></para>
49    /// </param>
50    /// <param name="linksDataParts">
51    /// <para>A links data parts.</para>
52    /// <para></para>
53    /// </param>
54    /// <param name="linksIndexParts">
55    /// <para>A links index parts.</para>
56    /// <para></para>
57    /// </param>
58    /// <param name="header">
59    /// <para>A header.</para>
60    /// <para></para>
61    /// </param>
62    [MethodImpl(MethodImplOptions.AggressiveInlining)]
63    protected UInt32InternalLinksSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress>
    ↪ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
    ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
    : base(constants, (byte*)linksDataParts, (byte*)linksIndexParts, (byte*)header)
64    {
65        LinksDataParts = linksDataParts;
66        LinksIndexParts = linksIndexParts;
67        Header = header;
68    }
69
70
71    /// <summary>
72    /// <para>
73    /// Gets the zero.
74    /// </para>
75    /// <para></para>
76    /// </summary>
77    /// <returns>
78    /// <para>The link</para>
79    /// <para></para>
80    /// </returns>
81    [MethodImpl(MethodImplOptions.AggressiveInlining)]
82    protected override TLinkAddress GetZero() => 0U;
83
84    /// <summary>
85    /// <para>
86    /// Determines whether this instance equal to zero.
87    /// </para>
88    /// <para></para>
89    /// </summary>
90    /// <param name="value">
91    /// <para>The value.</para>
92    /// <para></para>
93    /// </param>
94    /// <returns>
95    /// <para>The bool</para>
96    /// <para></para>
97    /// </returns>
98    [MethodImpl(MethodImplOptions.AggressiveInlining)]
99    protected override bool EqualToZero(TLinkAddress value) => value == 0U;
100
101    /// <summary>
102    /// <para>
103    /// Determines whether this instance are equal.
104    /// </para>
105    /// <para></para>
106    /// </summary>
107    /// <param name="first">
108    /// <para>The first.</para>
109    /// <para></para>
110    /// </param>
111    /// <param name="second">
112    /// <para>The second.</para>
113    /// <para></para>
114    /// </param>

```

```

115     /// <returns>
116     /// <para>The bool</para>
117     /// <para></para>
118     /// </returns>
119     [MethodImpl(MethodImplOptions.AggressiveInlining)]
120     protected override bool AreEqual(TLinkAddress first, TLinkAddress second) => first ==
        ↳ second;

121
122     /// <summary>
123     /// <para>
124     /// Determines whether this instance greater than zero.
125     /// </para>
126     /// <para></para>
127     /// </summary>
128     /// <param name="value">
129     /// <para>The value.</para>
130     /// <para></para>
131     /// </param>
132     /// <returns>
133     /// <para>The bool</para>
134     /// <para></para>
135     /// </returns>
136     [MethodImpl(MethodImplOptions.AggressiveInlining)]
137     protected override bool GreaterThanZero(TLinkAddress value) => value > 0U;

138
139     /// <summary>
140     /// <para>
141     /// Determines whether this instance greater than.
142     /// </para>
143     /// <para></para>
144     /// </summary>
145     /// <param name="first">
146     /// <para>The first.</para>
147     /// <para></para>
148     /// </param>
149     /// <param name="second">
150     /// <para>The second.</para>
151     /// <para></para>
152     /// </param>
153     /// <returns>
154     /// <para>The bool</para>
155     /// <para></para>
156     /// </returns>
157     [MethodImpl(MethodImplOptions.AggressiveInlining)]
158     protected override bool GreaterThan(TLinkAddress first, TLinkAddress second) => first >
        ↳ second;

159
160     /// <summary>
161     /// <para>
162     /// Determines whether this instance greater or equal than.
163     /// </para>
164     /// <para></para>
165     /// </summary>
166     /// <param name="first">
167     /// <para>The first.</para>
168     /// <para></para>
169     /// </param>
170     /// <param name="second">
171     /// <para>The second.</para>
172     /// <para></para>
173     /// </param>
174     /// <returns>
175     /// <para>The bool</para>
176     /// <para></para>
177     /// </returns>
178     [MethodImpl(MethodImplOptions.AggressiveInlining)]
179     protected override bool GreaterOrEqualThan(TLinkAddress first, TLinkAddress second) =>
        ↳ first >= second;

180
181     /// <summary>
182     /// <para>
183     /// Determines whether this instance greater or equal than zero.
184     /// </para>
185     /// <para></para>
186     /// </summary>
187     /// <param name="value">
188     /// <para>The value.</para>
189     /// <para></para>

```

```

190    /// </param>
191    /// <returns>
192    /// <para>The bool</para>
193    /// <para></para>
194    /// </returns>
195    [MethodImpl(MethodImplOptions.AggressiveInlining)]
196    protected override bool GreaterOrEqualThanZero(TLinkAddress value) => true; // value >=
    ↪ 0 is always true for ulong
197
198    /// <summary>
199    /// <para>
200    /// Determines whether this instance less or equal than zero.
201    /// </para>
202    /// <para></para>
203    /// </summary>
204    /// <param name="value">
205    /// <para>The value.</para>
206    /// <para></para>
207    /// </param>
208    /// <returns>
209    /// <para>The bool</para>
210    /// <para></para>
211    /// </returns>
212    [MethodImpl(MethodImplOptions.AggressiveInlining)]
213    protected override bool LessOrEqualThanZero(TLinkAddress value) => value == 0UL; //
    ↪ value is always >= 0 for ulong
214
215    /// <summary>
216    /// <para>
217    /// Determines whether this instance less or equal than.
218    /// </para>
219    /// <para></para>
220    /// </summary>
221    /// <param name="first">
222    /// <para>The first.</para>
223    /// <para></para>
224    /// </param>
225    /// <param name="second">
226    /// <para>The second.</para>
227    /// <para></para>
228    /// </param>
229    /// <returns>
230    /// <para>The bool</para>
231    /// <para></para>
232    /// </returns>
233    [MethodImpl(MethodImplOptions.AggressiveInlining)]
234    protected override bool LessOrEqualThan(TLinkAddress first, TLinkAddress second) =>
    ↪ first <= second;
235
236    /// <summary>
237    /// <para>
238    /// Determines whether this instance less than zero.
239    /// </para>
240    /// <para></para>
241    /// </summary>
242    /// <param name="value">
243    /// <para>The value.</para>
244    /// <para></para>
245    /// </param>
246    /// <returns>
247    /// <para>The bool</para>
248    /// <para></para>
249    /// </returns>
250    [MethodImpl(MethodImplOptions.AggressiveInlining)]
251    protected override bool LessThanZero(TLinkAddress value) => false; // value < 0 is
    ↪ always false for ulong
252
253    /// <summary>
254    /// <para>
255    /// Determines whether this instance less than.
256    /// </para>
257    /// <para></para>
258    /// </summary>
259    /// <param name="first">
260    /// <para>The first.</para>
261    /// <para></para>
262    /// </param>
263    /// <param name="second">

```

```

264     /// <para>The second.</para>
265     /// <para></para>
266     /// </param>
267     /// <returns>
268     /// <para>The bool</para>
269     /// <para></para>
270     /// </returns>
271     [MethodImpl(MethodImplOptions.AggressiveInlining)]
272     protected override bool LessThan(TLinkAddress first, TLinkAddress second) => first <
        ↪ second;
273
274     /// <summary>
275     /// <para>
276     /// Increments the value.
277     /// </para>
278     /// <para></para>
279     /// </summary>
280     /// <param name="value">
281     /// <para>The value.</para>
282     /// <para></para>
283     /// </param>
284     /// <returns>
285     /// <para>The link</para>
286     /// <para></para>
287     /// </returns>
288     [MethodImpl(MethodImplOptions.AggressiveInlining)]
289     protected override TLinkAddress Increment(TLinkAddress value) => ++value;
290
291     /// <summary>
292     /// <para>
293     /// Decrements the value.
294     /// </para>
295     /// <para></para>
296     /// </summary>
297     /// <param name="value">
298     /// <para>The value.</para>
299     /// <para></para>
300     /// </param>
301     /// <returns>
302     /// <para>The link</para>
303     /// <para></para>
304     /// </returns>
305     [MethodImpl(MethodImplOptions.AggressiveInlining)]
306     protected override TLinkAddress Decrement(TLinkAddress value) => --value;
307
308     /// <summary>
309     /// <para>
310     /// Adds the first.
311     /// </para>
312     /// <para></para>
313     /// </summary>
314     /// <param name="first">
315     /// <para>The first.</para>
316     /// <para></para>
317     /// </param>
318     /// <param name="second">
319     /// <para>The second.</para>
320     /// <para></para>
321     /// </param>
322     /// <returns>
323     /// <para>The link</para>
324     /// <para></para>
325     /// </returns>
326     [MethodImpl(MethodImplOptions.AggressiveInlining)]
327     protected override TLinkAddress Add(TLinkAddress first, TLinkAddress second) => first +
        ↪ second;
328
329     /// <summary>
330     /// <para>
331     /// Subtracts the first.
332     /// </para>
333     /// <para></para>
334     /// </summary>
335     /// <param name="first">
336     /// <para>The first.</para>
337     /// <para></para>
338     /// </param>
339     /// <param name="second">

```



```

340    /// <para>The second.</para>
341    /// <para></para>
342    /// </param>
343    /// <returns>
344    /// <para>The link</para>
345    /// <para></para>
346    /// </returns>
347    [MethodImpl(MethodImplOptions.AggressiveInlining)]
348    protected override TLinkAddress Subtract(TLinkAddress first, TLinkAddress second) =>
349        ↪ first - second;
350
351    /// <summary>
352    /// <para>
353    /// Gets the link data part reference using the specified link.
354    /// </para>
355    /// <para></para>
356    /// </summary>
357    /// <param name="link">
358    /// <para>The link.</para>
359    /// <para></para>
360    /// </param>
361    /// <returns>
362    /// <para>A ref raw link data part of t link</para>
363    /// <para></para>
364    /// </returns>
365    [MethodImpl(MethodImplOptions.AggressiveInlining)]
366    protected override ref RawLinkDataPart<TLinkAddress>
367        ↪ GetLinkDataPartReference(TLinkAddress link) => ref LinksDataParts[link];
368
369    /// <summary>
370    /// <para>
371    /// Gets the link index part reference using the specified link.
372    /// </para>
373    /// <para></para>
374    /// </summary>
375    /// <param name="link">
376    /// <para>The link.</para>
377    /// <para></para>
378    /// </param>
379    /// <returns>
380    /// <para>A ref raw link index part of t link</para>
381    /// <para></para>
382    /// </returns>
383    [MethodImpl(MethodImplOptions.AggressiveInlining)]
384    protected override ref RawLinkIndexPart<TLinkAddress>
385        ↪ GetLinkIndexPartReference(TLinkAddress link) => ref LinksIndexParts[link];
386
387    /// <summary>
388    /// <para>
389    /// Determines whether this instance first is to the left of second.
390    /// </para>
391    /// <para></para>
392    /// </summary>
393    /// <param name="first">
394    /// <para>The first.</para>
395    /// <para></para>
396    /// </param>
397    /// <param name="second">
398    /// <para>The second.</para>
399    /// <para></para>
400    /// </param>
401    /// <returns>
402    /// <para>The bool</para>
403    /// <para></para>
404    /// </returns>
405    [MethodImpl(MethodImplOptions.AggressiveInlining)]
406    protected override bool FirstIsToLeftOfSecond(TLinkAddress first, TLinkAddress
407        ↪ second) => GetKeyPartValue(first) < GetKeyPartValue(second);
408
409    /// <summary>
410    /// <para>
411    /// Determines whether this instance first is to the right of second.
412    /// </para>
413    /// <para></para>
414    /// </summary>
415    /// <param name="first">
416    /// <para>The first.</para>
417    /// <para></para>
418    /// </param>
419    /// <param name="second">
420    /// <para>The second.</para>
421    /// <para></para>
422    /// </param>
423    /// <returns>
424    /// <para>The bool</para>
425    /// <para></para>
426    /// </returns>
427    [MethodImpl(MethodImplOptions.AggressiveInlining)]
428    protected override bool FirstIsToRightOfSecond(TLinkAddress first, TLinkAddress
429        ↪ second) => GetKeyPartValue(first) > GetKeyPartValue(second);

```

```

414     /// </param>
415     /// <param name="second">
416     /// <para>The second.</para>
417     /// <para></para>
418     /// </param>
419     /// <returns>
420     /// <para>The bool</para>
421     /// <para></para>
422     /// </returns>
423     [MethodImpl(MethodImplOptions.AggressiveInlining)]
424     protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
        ↪ second) => GetKeyPartValue(first) > GetKeyPartValue(second);
425 }
426 }

```

1.58 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksSourcesLinkedListMethods.cs

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt32;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Generic
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 32 internal links sources linked list methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="InternalLinksSourcesLinkedListMethods{TLinkAddress}"/>
15     public unsafe class UInt32InternalLinksSourcesLinkedListMethods :
        ↪ InternalLinksSourcesLinkedListMethods<TLinkAddress>
16     {
17         private readonly RawLinkDataPart<TLinkAddress>* _linksDataParts;
18         private readonly RawLinkIndexPart<TLinkAddress>* _linksIndexParts;
19
20         /// <summary>
21         /// <para>
22         /// Initializes a new <see cref="UInt32InternalLinksSourcesLinkedListMethods"/> instance.
23         /// </para>
24         /// <para></para>
25         /// </summary>
26         /// <param name="constants">
27         /// <para>A constants.</para>
28         /// <para></para>
29         /// </param>
30         /// <param name="linksDataParts">
31         /// <para>A links data parts.</para>
32         /// <para></para>
33         /// </param>
34         /// <param name="linksIndexParts">
35         /// <para>A links index parts.</para>
36         /// <para></para>
37         /// </param>
38         [MethodImpl(MethodImplOptions.AggressiveInlining)]
39         public UInt32InternalLinksSourcesLinkedListMethods(LinksConstants<TLinkAddress>
            ↪ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
            ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts)
            : base(constants, (byte*)linksDataParts, (byte*)linksIndexParts)
40         {
41             _linksDataParts = linksDataParts;
42             _linksIndexParts = linksIndexParts;
43         }
44
45         /// <summary>
46         /// <para>
47         /// Gets the link data part reference using the specified link.
48         /// </para>
49         /// <para></para>
50         /// <para></para>
51         /// </summary>
52         /// <param name="link">
53         /// <para>The link.</para>
54         /// <para></para>
55         /// </param>
56         /// <returns>
57         /// <para>A ref raw link data part of t link</para>
58         /// <para></para>
59         /// </returns>
60         [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

61     protected override ref RawLinkDataPart<TLinkAddress>
        ↪ GetLinkDataPartReference(TLinkAddress link) => ref _linksDataParts[link];
62
63     /// <summary>
64     /// <para>
65     /// Gets the link index part reference using the specified link.
66     /// </para>
67     /// <para></para>
68     /// </summary>
69     /// <param name="link">
70     /// <para>The link.</para>
71     /// <para></para>
72     /// </param>
73     /// <returns>
74     /// <para>A ref raw link index part of t link</para>
75     /// <para></para>
76     /// </returns>
77     [MethodImpl(MethodImplOptions.AggressiveInlining)]
78     protected override ref RawLinkIndexPart<TLinkAddress>
        ↪ GetLinkIndexPartReference(TLinkAddress link) => ref _linksIndexParts[link];
79 }
80 }

```

1.59 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksSourcesRecursionlessSizeBalancedTreeMethodsBase

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt32;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 32 internal links sources recursionless size balanced tree methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="UInt32InternalLinksRecursionlessSizeBalancedTreeMethodsBase"/>
15     public unsafe class UInt32InternalLinksSourcesRecursionlessSizeBalancedTreeMethods :
        ↪ UInt32InternalLinksRecursionlessSizeBalancedTreeMethodsBase
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see
20         ↪ cref="UInt32InternalLinksSourcesRecursionlessSizeBalancedTreeMethods"/> instance.
21         /// </para>
22         /// <para></para>
23         /// </summary>
24         /// <param name="constants">
25         /// <para>A constants.</para>
26         /// <para></para>
27         /// </param>
28         /// <param name="linksDataParts">
29         /// <para>A links data parts.</para>
30         /// <para></para>
31         /// </param>
32         /// <param name="linksIndexParts">
33         /// <para>A links index parts.</para>
34         /// <para></para>
35         /// </param>
36         /// <param name="header">
37         /// <para>A header.</para>
38         /// <para></para>
39         /// </param>
40         [MethodImpl(MethodImplOptions.AggressiveInlining)]
41         public UInt32InternalLinksSourcesRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
        ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
        ↪ : base(constants, linksDataParts, linksIndexParts, header) { }
42
43         /// <summary>
44         /// <para>
45         /// Gets the left reference using the specified node.
46         /// </para>
47         /// <para></para>
48         /// </summary>
49         /// <param name="node">
50         /// <para>The node.</para>

```

```

50    /// <para></para>
51    /// </param>
52    /// <returns>
53    /// <para>The ref link</para>
54    /// <para></para>
55    /// </returns>
56    [MethodImpl(MethodImplOptions.AggressiveInlining)]
57    protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].LeftAsSource;
58
59    /// <summary>
60    /// <para>
61    /// Gets the right reference using the specified node.
62    /// </para>
63    /// <para></para>
64    /// </summary>
65    /// <param name="node">
66    /// <para>The node.</para>
67    /// <para></para>
68    /// </param>
69    /// <returns>
70    /// <para>The ref link</para>
71    /// <para></para>
72    /// </returns>
73    [MethodImpl(MethodImplOptions.AggressiveInlining)]
74    protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].RightAsSource;
75
76    /// <summary>
77    /// <para>
78    /// Gets the left using the specified node.
79    /// </para>
80    /// <para></para>
81    /// </summary>
82    /// <param name="node">
83    /// <para>The node.</para>
84    /// <para></para>
85    /// </param>
86    /// <returns>
87    /// <para>The link</para>
88    /// <para></para>
89    /// </returns>
90    [MethodImpl(MethodImplOptions.AggressiveInlining)]
91    protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ LinksIndexParts[node].LeftAsSource;
92
93    /// <summary>
94    /// <para>
95    /// Gets the right using the specified node.
96    /// </para>
97    /// <para></para>
98    /// </summary>
99    /// <param name="node">
100    /// <para>The node.</para>
101    /// <para></para>
102    /// </param>
103    /// <returns>
104    /// <para>The link</para>
105    /// <para></para>
106    /// </returns>
107    [MethodImpl(MethodImplOptions.AggressiveInlining)]
108    protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↪ LinksIndexParts[node].RightAsSource;
109
110    /// <summary>
111    /// <para>
112    /// Sets the left using the specified node.
113    /// </para>
114    /// <para></para>
115    /// </summary>
116    /// <param name="node">
117    /// <para>The node.</para>
118    /// <para></para>
119    /// </param>
120    /// <param name="left">
121    /// <para>The left.</para>
122    /// <para></para>
123    /// </param>

```

```

124 [MethodImpl(MethodImplOptions.AggressiveInlining)]
125 protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
    ↳ LinksIndexParts[node].LeftAsSource = left;

126
127 /// <summary>
128 /// <para>
129 /// Sets the right using the specified node.
130 /// </para>
131 /// <para></para>
132 /// </summary>
133 /// <param name="node">
134 /// <para>The node.</para>
135 /// <para></para>
136 /// </param>
137 /// <param name="right">
138 /// <para>The right.</para>
139 /// <para></para>
140 /// </param>
141 [MethodImpl(MethodImplOptions.AggressiveInlining)]
142 protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
    ↳ LinksIndexParts[node].RightAsSource = right;

143
144 /// <summary>
145 /// <para>
146 /// Gets the size using the specified node.
147 /// </para>
148 /// <para></para>
149 /// </summary>
150 /// <param name="node">
151 /// <para>The node.</para>
152 /// <para></para>
153 /// </param>
154 /// <returns>
155 /// <para>The link</para>
156 /// <para></para>
157 /// </returns>
158 [MethodImpl(MethodImplOptions.AggressiveInlining)]
159 protected override TLinkAddress GetSize(TLinkAddress node) =>
    ↳ LinksIndexParts[node].SizeAsSource;

160
161 /// <summary>
162 /// <para>
163 /// Sets the size using the specified node.
164 /// </para>
165 /// <para></para>
166 /// </summary>
167 /// <param name="node">
168 /// <para>The node.</para>
169 /// <para></para>
170 /// </param>
171 /// <param name="size">
172 /// <para>The size.</para>
173 /// <para></para>
174 /// </param>
175 [MethodImpl(MethodImplOptions.AggressiveInlining)]
176 protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
    ↳ LinksIndexParts[node].SizeAsSource = size;

177
178 /// <summary>
179 /// <para>
180 /// Gets the tree root using the specified node.
181 /// </para>
182 /// <para></para>
183 /// </summary>
184 /// <param name="node">
185 /// <para>The node.</para>
186 /// <para></para>
187 /// </param>
188 /// <returns>
189 /// <para>The link</para>
190 /// <para></para>
191 /// </returns>
192 [MethodImpl(MethodImplOptions.AggressiveInlining)]
193 protected override TLinkAddress GetTreeRoot(TLinkAddress node) =>
    ↳ LinksIndexParts[node].RootAsSource;

194
195 /// <summary>

```

```

196     /// <para>
197     /// Gets the base part value using the specified node.
198     /// </para>
199     /// <para></para>
200     /// </summary>
201     /// <param name="node">
202     /// <para>The node.</para>
203     /// <para></para>
204     /// </param>
205     /// <returns>
206     /// <para>The link</para>
207     /// <para></para>
208     /// </returns>
209     [MethodImpl(MethodImplOptions.AggressiveInlining)]
210     protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
211         ↪ LinksDataParts[node].Source;
212
213     /// <summary>
214     /// <para>
215     /// Gets the key part value using the specified node.
216     /// </para>
217     /// <para></para>
218     /// </summary>
219     /// <param name="node">
220     /// <para>The node.</para>
221     /// <para></para>
222     /// </param>
223     /// <returns>
224     /// <para>The link</para>
225     /// <para></para>
226     /// </returns>
227     [MethodImpl(MethodImplOptions.AggressiveInlining)]
228     protected override TLinkAddress GetKeyPartValue(TLinkAddress node) =>
229         ↪ LinksDataParts[node].Target;
230
231     /// <summary>
232     /// <para>
233     /// Clears the node using the specified node.
234     /// </para>
235     /// <para></para>
236     /// </summary>
237     /// <param name="node">
238     /// <para>The node.</para>
239     /// <para></para>
240     /// </param>
241     [MethodImpl(MethodImplOptions.AggressiveInlining)]
242     protected override void ClearNode(TLinkAddress node)
243     {
244         ref var link = ref LinksIndexParts[node];
245         link.LeftAsSource = Zero;
246         link.RightAsSource = Zero;
247         link.SizeAsSource = Zero;
248     }
249
250     /// <summary>
251     /// <para>
252     /// Searches the source.
253     /// </para>
254     /// <para></para>
255     /// </summary>
256     /// <param name="source">
257     /// <para>The source.</para>
258     /// <para></para>
259     /// </param>
260     /// <param name="target">
261     /// <para>The target.</para>
262     /// <para></para>
263     /// </param>
264     /// <returns>
265     /// <para>The link</para>
266     /// <para></para>
267     /// </returns>
268     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
269         ↪ SearchCore(GetTreeRoot(source), target);
270 }

```

1.60 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksSourcesSizeBalancedTreeMethod

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt32;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 32 internal links sources size balanced tree methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="UInt32InternalLinksSizeBalancedTreeMethodsBase"/>
15     public unsafe class UInt32InternalLinksSourcesSizeBalancedTreeMethods :
16         ↳ UInt32InternalLinksSizeBalancedTreeMethodsBase
17     {
18         /// <summary>
19         /// <para>
20         /// Initializes a new <see cref="UInt32InternalLinksSourcesSizeBalancedTreeMethods"/>
21         ↳ instance.
22         /// </para>
23         /// <para></para>
24         /// </summary>
25         /// <param name="constants">
26         /// <para>A constants.</para>
27         /// <para></para>
28         /// </param>
29         /// <param name="linksDataParts">
30         /// <para>A links data parts.</para>
31         /// <para></para>
32         /// </param>
33         /// <param name="linksIndexParts">
34         /// <para>A links index parts.</para>
35         /// <para></para>
36         /// </param>
37         /// <param name="header">
38         /// <para>A header.</para>
39         /// <para></para>
40         /// </param>
41         [MethodImpl(MethodImplOptions.AggressiveInlining)]
42         public UInt32InternalLinksSourcesSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
43             ↳ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
44             ↳ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
45             ↳ : base(constants, linksDataParts, linksIndexParts, header) { }
46
47         /// <summary>
48         /// <para>
49         /// Gets the left reference using the specified node.
50         /// </para>
51         /// <para></para>
52         /// </summary>
53         /// <param name="node">
54         /// <para>The node.</para>
55         /// <para></para>
56         /// </param>
57         /// <returns>
58         /// <para>The ref link</para>
59         /// <para></para>
60         /// </returns>
61         [MethodImpl(MethodImplOptions.AggressiveInlining)]
62         protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
63             ↳ LinksIndexParts[node].LeftAsSource;
64
65         /// <summary>
66         /// <para>
67         /// Gets the right reference using the specified node.
68         /// </para>
69         /// <para></para>
70         /// </summary>
71         /// <param name="node">
72         /// <para>The node.</para>
73         /// <para></para>
74         /// </param>
75         /// <returns>
76         /// <para>The ref link</para>
77         /// <para></para>
78         /// </returns>

```

```

72     /// </returns>
73     [MethodImpl(MethodImplOptions.AggressiveInlining)]
74     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
75     ↪ LinksIndexParts[node].RightAsSource;
76
77     /// <summary>
78     /// <para>
79     /// Gets the left using the specified node.
80     /// </para>
81     /// <para></para>
82     /// </summary>
83     /// <param name="node">
84     /// <para>The node.</para>
85     /// <para></para>
86     /// </param>
87     /// <returns>
88     /// <para>The link</para>
89     /// <para></para>
90     /// </returns>
91     [MethodImpl(MethodImplOptions.AggressiveInlining)]
92     protected override TLinkAddress GetLeft(TLinkAddress node) =>
93     ↪ LinksIndexParts[node].LeftAsSource;
94
95     /// <summary>
96     /// <para>
97     /// Gets the right using the specified node.
98     /// </para>
99     /// <para></para>
100    /// </summary>
101    /// <param name="node">
102    /// <para>The node.</para>
103    /// <para></para>
104    /// </param>
105    /// <returns>
106    /// <para>The link</para>
107    /// <para></para>
108    /// </returns>
109    [MethodImpl(MethodImplOptions.AggressiveInlining)]
110    protected override TLinkAddress GetRight(TLinkAddress node) =>
111    ↪ LinksIndexParts[node].RightAsSource;
112
113    /// <summary>
114    /// <para>
115    /// Sets the left using the specified node.
116    /// </para>
117    /// <para></para>
118    /// </summary>
119    /// <param name="node">
120    /// <para>The node.</para>
121    /// <para></para>
122    /// </param>
123    /// <param name="left">
124    /// <para>The left.</para>
125    /// <para></para>
126    /// </param>
127    [MethodImpl(MethodImplOptions.AggressiveInlining)]
128    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
129    ↪ LinksIndexParts[node].LeftAsSource = left;
130
131    /// <summary>
132    /// <para>
133    /// Sets the right using the specified node.
134    /// </para>
135    /// <para></para>
136    /// </summary>
137    /// <param name="node">
138    /// <para>The node.</para>
139    /// <para></para>
140    /// </param>
141    /// <param name="right">
142    /// <para>The right.</para>
143    /// <para></para>
144    /// </param>
145    [MethodImpl(MethodImplOptions.AggressiveInlining)]
146    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
147    ↪ LinksIndexParts[node].RightAsSource = right;

```



```

144    /// <summary>
145    /// <para>
146    /// Gets the size using the specified node.
147    /// </para>
148    /// <para></para>
149    /// </summary>
150    /// <param name="node">
151    /// <para>The node.</para>
152    /// <para></para>
153    /// </param>
154    /// <returns>
155    /// <para>The link</para>
156    /// <para></para>
157    /// </returns>
158    [MethodImpl(MethodImplOptions.AggressiveInlining)]
159    protected override TLinkAddress GetSize(TLinkAddress node) =>
160        ↪ LinksIndexParts[node].SizeAsSource;
161
162    /// <summary>
163    /// <para>
164    /// Sets the size using the specified node.
165    /// </para>
166    /// <para></para>
167    /// </summary>
168    /// <param name="node">
169    /// <para>The node.</para>
170    /// <para></para>
171    /// </param>
172    /// <param name="size">
173    /// <para>The size.</para>
174    /// <para></para>
175    /// </param>
176    [MethodImpl(MethodImplOptions.AggressiveInlining)]
177    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
178        ↪ LinksIndexParts[node].SizeAsSource = size;
179
180    /// <summary>
181    /// <para>
182    /// Gets the tree root using the specified node.
183    /// </para>
184    /// <para></para>
185    /// </summary>
186    /// <param name="node">
187    /// <para>The node.</para>
188    /// <para></para>
189    /// </param>
190    /// <returns>
191    /// <para>The link</para>
192    /// <para></para>
193    /// </returns>
194    [MethodImpl(MethodImplOptions.AggressiveInlining)]
195    protected override TLinkAddress GetTreeRoot(TLinkAddress node) =>
196        ↪ LinksIndexParts[node].RootAsSource;
197
198    /// <summary>
199    /// <para>
200    /// Gets the base part value using the specified node.
201    /// </para>
202    /// <para></para>
203    /// </summary>
204    /// <param name="node">
205    /// <para>The node.</para>
206    /// <para></para>
207    /// </param>
208    /// <returns>
209    /// <para>The link</para>
210    /// <para></para>
211    /// </returns>
212    [MethodImpl(MethodImplOptions.AggressiveInlining)]
213    protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
214        ↪ LinksDataParts[node].Source;
215
216    /// <summary>
217    /// <para>
218    /// Gets the key part value using the specified node.
219    /// </para>
220    /// <para></para>
221    /// </summary>

```

```

218     /// <param name="node">
219     /// <para>The node.</para>
220     /// <para></para>
221     /// </param>
222     /// <returns>
223     /// <para>The link</para>
224     /// <para></para>
225     /// </returns>
226     [MethodImpl(MethodImplOptions.AggressiveInlining)]
227     protected override TLinkAddress GetKeyPartValue(TLinkAddress node) =>
228         ↪ LinksDataParts[node].Target;
229
230     /// <summary>
231     /// <para>
232     /// Clears the node using the specified node.
233     /// </para>
234     /// <para></para>
235     /// </summary>
236     /// <param name="node">
237     /// <para>The node.</para>
238     /// <para></para>
239     /// </param>
240     [MethodImpl(MethodImplOptions.AggressiveInlining)]
241     protected override void ClearNode(TLinkAddress node)
242     {
243         ref var link = ref LinksIndexParts[node];
244         link.LeftAsSource = Zero;
245         link.RightAsSource = Zero;
246         link.SizeAsSource = Zero;
247     }
248
249     /// <summary>
250     /// <para>
251     /// Searches the source.
252     /// </para>
253     /// <para></para>
254     /// </summary>
255     /// <param name="source">
256     /// <para>The source.</para>
257     /// <para></para>
258     /// </param>
259     /// <param name="target">
260     /// <para>The target.</para>
261     /// <para></para>
262     /// </param>
263     /// <returns>
264     /// <para>The link</para>
265     /// <para></para>
266     /// </returns>
267     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
268         ↪ SearchCore(GetTreeRoot(source), target);

```

1.61 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksTargetsRecursionlessSizeBalancedTreeMethodsBase

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt32;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 32 internal links targets recursionless size balanced tree methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="UInt32InternalLinksRecursionlessSizeBalancedTreeMethodsBase"/>
15     public unsafe class UInt32InternalLinksTargetsRecursionlessSizeBalancedTreeMethods :
16         ↪ UInt32InternalLinksRecursionlessSizeBalancedTreeMethodsBase
17     {
18         /// <summary>
19         /// <para>
20         /// Initializes a new <see
21         ↪ cref="UInt32InternalLinksTargetsRecursionlessSizeBalancedTreeMethods"/> instance.
22         /// </para>
23         /// <para></para>

```

```

22     /// </summary>
23     /// <param name="constants">
24     /// <para>A constants.</para>
25     /// <para></para>
26     /// </param>
27     /// <param name="linksDataParts">
28     /// <para>A links data parts.</para>
29     /// <para></para>
30     /// </param>
31     /// <param name="linksIndexParts">
32     /// <para>A links index parts.</para>
33     /// <para></para>
34     /// </param>
35     /// <param name="header">
36     /// <para>A header.</para>
37     /// <para></para>
38     /// </param>
39     [MethodImpl(MethodImplOptions.AggressiveInlining)]
40     public UInt32InternalLinksTargetsRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
    ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
    ↪ : base(constants, linksDataParts, linksIndexParts, header) { }
41
42     /// <summary>
43     /// <para>
44     /// Gets the left reference using the specified node.
45     /// </para>
46     /// <para></para>
47     /// </summary>
48     /// <param name="node">
49     /// <para>The node.</para>
50     /// <para></para>
51     /// </param>
52     /// <returns>
53     /// <para>The ref link</para>
54     /// <para></para>
55     /// </returns>
56     [MethodImpl(MethodImplOptions.AggressiveInlining)]
57     protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].LeftAsTarget;
58
59     /// <summary>
60     /// <para>
61     /// Gets the right reference using the specified node.
62     /// </para>
63     /// <para></para>
64     /// </summary>
65     /// <param name="node">
66     /// <para>The node.</para>
67     /// <para></para>
68     /// </param>
69     /// <returns>
70     /// <para>The ref link</para>
71     /// <para></para>
72     /// </returns>
73     [MethodImpl(MethodImplOptions.AggressiveInlining)]
74     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].RightAsTarget;
75
76     /// <summary>
77     /// <para>
78     /// Gets the left using the specified node.
79     /// </para>
80     /// <para></para>
81     /// </summary>
82     /// <param name="node">
83     /// <para>The node.</para>
84     /// <para></para>
85     /// </param>
86     /// <returns>
87     /// <para>The link</para>
88     /// <para></para>
89     /// </returns>
90     [MethodImpl(MethodImplOptions.AggressiveInlining)]
91     protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ LinksIndexParts[node].LeftAsTarget;
92
93     /// <summary>

```

```

94    /// <para>
95    /// Gets the right using the specified node.
96    /// </para>
97    /// <para></para>
98    /// </summary>
99    /// <param name="node">
100    /// <para>The node.</para>
101    /// <para></para>
102    /// </param>
103    /// <returns>
104    /// <para>The link</para>
105    /// <para></para>
106    /// </returns>
107    [MethodImpl(MethodImplOptions.AggressiveInlining)]
108    protected override TLinkAddress GetRight(TLinkAddress node) =>
109        ↪ LinksIndexParts[node].RightAsTarget;
110
111    /// <summary>
112    /// <para>
113    /// Sets the left using the specified node.
114    /// </para>
115    /// <para></para>
116    /// </summary>
117    /// <param name="node">
118    /// <para>The node.</para>
119    /// <para></para>
120    /// </param>
121    /// <param name="left">
122    /// <para>The left.</para>
123    /// <para></para>
124    /// </param>
125    [MethodImpl(MethodImplOptions.AggressiveInlining)]
126    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
127        ↪ LinksIndexParts[node].LeftAsTarget = left;
128
129    /// <summary>
130    /// <para>
131    /// Sets the right using the specified node.
132    /// </para>
133    /// <para></para>
134    /// </summary>
135    /// <param name="node">
136    /// <para>The node.</para>
137    /// <para></para>
138    /// </param>
139    /// <param name="right">
140    /// <para>The right.</para>
141    /// <para></para>
142    /// </param>
143    [MethodImpl(MethodImplOptions.AggressiveInlining)]
144    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
145        ↪ LinksIndexParts[node].RightAsTarget = right;
146
147    /// <summary>
148    /// <para>
149    /// Gets the size using the specified node.
150    /// </para>
151    /// <para></para>
152    /// </summary>
153    /// <param name="node">
154    /// <para>The node.</para>
155    /// <para></para>
156    /// </param>
157    /// <returns>
158    /// <para>The link</para>
159    /// <para></para>
160    /// </returns>
161    [MethodImpl(MethodImplOptions.AggressiveInlining)]
162    protected override TLinkAddress GetSize(TLinkAddress node) =>
163        ↪ LinksIndexParts[node].SizeAsTarget;
164
165    /// <summary>
166    /// <para>
167    /// Sets the size using the specified node.
168    /// </para>
169    /// <para></para>
170    /// </summary>
171    /// <param name="node">

```

```

168    /// <para>The node.</para>
169    /// <para></para>
170    /// </param>
171    /// <param name="size">
172    /// <para>The size.</para>
173    /// <para></para>
174    /// </param>
175    [MethodImpl(MethodImplOptions.AggressiveInlining)]
176    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
177        ↪ LinksIndexParts[node].SizeAsTarget = size;
178
179    /// <summary>
180    /// <para>
181    /// Gets the tree root using the specified node.
182    /// </para>
183    /// <para></para>
184    /// </summary>
185    /// <param name="node">
186    /// <para>The node.</para>
187    /// <para></para>
188    /// </param>
189    /// <returns>
190    /// <para>The link</para>
191    /// <para></para>
192    /// </returns>
193    [MethodImpl(MethodImplOptions.AggressiveInlining)]
194    protected override TLinkAddress GetTreeRoot(TLinkAddress node) =>
195        ↪ LinksIndexParts[node].RootAsTarget;
196
197    /// <summary>
198    /// <para>
199    /// Gets the base part value using the specified node.
200    /// </para>
201    /// <para></para>
202    /// </summary>
203    /// <param name="node">
204    /// <para>The node.</para>
205    /// <para></para>
206    /// </param>
207    /// <returns>
208    /// <para>The link</para>
209    /// <para></para>
210    /// </returns>
211    [MethodImpl(MethodImplOptions.AggressiveInlining)]
212    protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
213        ↪ LinksDataParts[node].Target;
214
215    /// <summary>
216    /// <para>
217    /// Gets the key part value using the specified node.
218    /// </para>
219    /// <para></para>
220    /// </summary>
221    /// <param name="node">
222    /// <para>The node.</para>
223    /// <para></para>
224    /// </param>
225    /// <returns>
226    /// <para>The link</para>
227    /// <para></para>
228    /// </returns>
229    [MethodImpl(MethodImplOptions.AggressiveInlining)]
230    protected override TLinkAddress GetKeyPartValue(TLinkAddress node) =>
231        ↪ LinksDataParts[node].Source;
232
233    /// <summary>
234    /// <para>
235    /// Clears the node using the specified node.
236    /// </para>
237    /// <para></para>
238    /// </summary>
239    /// <param name="node">
240    /// <para>The node.</para>
241    /// <para></para>
242    /// </param>
243    [MethodImpl(MethodImplOptions.AggressiveInlining)]
244    protected override void ClearNode(TLinkAddress node)
245    {

```

```

242         ref var link = ref LinksIndexParts[node];
243         link.LeftAsTarget = Zero;
244         link.RightAsTarget = Zero;
245         link.SizeAsTarget = Zero;
246     }
247
248     /// <summary>
249     /// <para>
250     /// Searches the source.
251     /// </para>
252     /// <para></para>
253     /// </summary>
254     /// <param name="source">
255     /// <para>The source.</para>
256     /// <para></para>
257     /// </param>
258     /// <param name="target">
259     /// <para>The target.</para>
260     /// <para></para>
261     /// </param>
262     /// <returns>
263     /// <para>The link</para>
264     /// <para></para>
265     /// </returns>
266     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
        ↪ SearchCore(GetTreeRoot(target), source);
267 }
268 }

```

1.62 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksTargetsSizeBalancedTreeMetho

```

1 using System.Runtime.CompilerServices;
2 using TLinkAddress = System.UInt32;
3
4 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6 namespace Platform.Data.Doublets.Memory.Split.Specific
7 {
8     /// <summary>
9     /// <para>
10    /// Represents the int 32 internal links targets size balanced tree methods.
11    /// </para>
12    /// <para></para>
13    /// </summary>
14    /// <seealso cref="UInt32InternalLinksSizeBalancedTreeMethodsBase"/>
15    public unsafe class UInt32InternalLinksTargetsSizeBalancedTreeMethods :
        ↪ UInt32InternalLinksSizeBalancedTreeMethodsBase
16    {
17        /// <summary>
18        /// <para>
19        /// Initializes a new <see cref="UInt32InternalLinksTargetsSizeBalancedTreeMethods"/>
20        ↪ instance.
21        /// </para>
22        /// <para></para>
23        /// </summary>
24        /// <param name="constants">
25        /// <para>A constants.</para>
26        /// <para></para>
27        /// </param>
28        /// <param name="linksDataParts">
29        /// <para>A links data parts.</para>
30        /// <para></para>
31        /// </param>
32        /// <param name="linksIndexParts">
33        /// <para>A links index parts.</para>
34        /// <para></para>
35        /// </param>
36        /// <param name="header">
37        /// <para>A header.</para>
38        /// <para></para>
39        /// </param>
40        [MethodImpl(MethodImplOptions.AggressiveInlining)]
41        public UInt32InternalLinksTargetsSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
        ↪ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
        ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
        ↪ : base(constants, linksDataParts, linksIndexParts, header) { }
41
42        /// <summary>
43        /// <para>
44        /// Gets the left reference using the specified node.

```

```

45     /// </para>
46     /// <para></para>
47     /// </summary>
48     /// <param name="node">
49     /// <para>The node.</para>
50     /// <para></para>
51     /// </param>
52     /// <returns>
53     /// <para>The ref link</para>
54     /// <para></para>
55     /// </returns>
56     [MethodImpl(MethodImplOptions.AggressiveInlining)]
57     protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
58     ↪ LinksIndexParts[node].LeftAsTarget;
59
60     /// <summary>
61     /// <para>
62     /// Gets the right reference using the specified node.
63     /// </para>
64     /// <para></para>
65     /// </summary>
66     /// <param name="node">
67     /// <para>The node.</para>
68     /// <para></para>
69     /// </param>
70     /// <returns>
71     /// <para>The ref link</para>
72     /// <para></para>
73     /// </returns>
74     [MethodImpl(MethodImplOptions.AggressiveInlining)]
75     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
76     ↪ LinksIndexParts[node].RightAsTarget;
77
78     /// <summary>
79     /// <para>
80     /// Gets the left using the specified node.
81     /// </para>
82     /// <para></para>
83     /// </summary>
84     /// <param name="node">
85     /// <para>The node.</para>
86     /// <para></para>
87     /// </param>
88     /// <returns>
89     /// <para>The link</para>
90     /// <para></para>
91     /// </returns>
92     [MethodImpl(MethodImplOptions.AggressiveInlining)]
93     protected override TLinkAddress GetLeft(TLinkAddress node) =>
94     ↪ LinksIndexParts[node].LeftAsTarget;
95
96     /// <summary>
97     /// <para>
98     /// Gets the right using the specified node.
99     /// </para>
100    /// <para></para>
101    /// </summary>
102    /// <param name="node">
103    /// <para>The node.</para>
104    /// <para></para>
105    /// </param>
106    /// <returns>
107    /// <para>The link</para>
108    /// <para></para>
109    /// </returns>
110    [MethodImpl(MethodImplOptions.AggressiveInlining)]
111    protected override TLinkAddress GetRight(TLinkAddress node) =>
112    ↪ LinksIndexParts[node].RightAsTarget;
113
114    /// <summary>
115    /// <para>
116    /// Sets the left using the specified node.
117    /// </para>
118    /// <para></para>
119    /// </summary>
120    /// <param name="node">
121    /// <para>The node.</para>
122    /// <para></para>
123    /// </param>
124    /// </summary>

```

```

119     /// </param>
120     /// <param name="left">
121     /// <para>The left.</para>
122     /// <para></para>
123     /// </param>
124     [MethodImpl(MethodImplOptions.AggressiveInlining)]
125     protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
126         ↪ LinksIndexParts[node].LeftAsTarget = left;
127
128     /// <summary>
129     /// <para>
130     /// Sets the right using the specified node.
131     /// </para>
132     /// <para></para>
133     /// </summary>
134     /// <param name="node">
135     /// <para>The node.</para>
136     /// <para></para>
137     /// </param>
138     /// <param name="right">
139     /// <para>The right.</para>
140     /// <para></para>
141     /// </param>
142     [MethodImpl(MethodImplOptions.AggressiveInlining)]
143     protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
144         ↪ LinksIndexParts[node].RightAsTarget = right;
145
146     /// <summary>
147     /// <para>
148     /// Gets the size using the specified node.
149     /// </para>
150     /// <para></para>
151     /// </summary>
152     /// <param name="node">
153     /// <para>The node.</para>
154     /// <para></para>
155     /// </param>
156     /// <returns>
157     /// <para>The link</para>
158     /// <para></para>
159     /// </returns>
160     [MethodImpl(MethodImplOptions.AggressiveInlining)]
161     protected override TLinkAddress GetSize(TLinkAddress node) =>
162         ↪ LinksIndexParts[node].SizeAsTarget;
163
164     /// <summary>
165     /// <para>
166     /// Sets the size using the specified node.
167     /// </para>
168     /// <para></para>
169     /// </summary>
170     /// <param name="node">
171     /// <para>The node.</para>
172     /// <para></para>
173     /// </param>
174     /// <param name="size">
175     /// <para>The size.</para>
176     /// <para></para>
177     /// </param>
178     [MethodImpl(MethodImplOptions.AggressiveInlining)]
179     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
180         ↪ LinksIndexParts[node].SizeAsTarget = size;
181
182     /// <summary>
183     /// <para>
184     /// Gets the tree root using the specified node.
185     /// </para>
186     /// <para></para>
187     /// </summary>
188     /// <param name="node">
189     /// <para>The node.</para>
190     /// <para></para>
191     /// </param>
192     /// <returns>
193     /// <para>The link</para>
194     /// <para></para>
195     /// </returns>
196     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```



```

193     protected override TLinkAddress GetTreeRoot(TLinkAddress node) =>
194         ↳ LinksIndexParts[node].RootAsTarget;
195
196     /// <summary>
197     /// <para>
198     /// Gets the base part value using the specified node.
199     /// </para>
200     /// <para></para>
201     /// </summary>
202     /// <param name="node">
203     /// <para>The node.</para>
204     /// <para></para>
205     /// </param>
206     /// <returns>
207     /// <para>The link</para>
208     /// <para></para>
209     /// </returns>
210     [MethodImpl(MethodImplOptions.AggressiveInlining)]
211     protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
212         ↳ LinksDataParts[node].Target;
213
214     /// <summary>
215     /// <para>
216     /// Gets the key part value using the specified node.
217     /// </para>
218     /// <para></para>
219     /// </summary>
220     /// <param name="node">
221     /// <para>The node.</para>
222     /// <para></para>
223     /// </param>
224     /// <returns>
225     /// <para>The link</para>
226     /// <para></para>
227     /// </returns>
228     [MethodImpl(MethodImplOptions.AggressiveInlining)]
229     protected override TLinkAddress GetKeyPartValue(TLinkAddress node) =>
230         ↳ LinksDataParts[node].Source;
231
232     /// <summary>
233     /// <para>
234     /// Clears the node using the specified node.
235     /// </para>
236     /// <para></para>
237     /// </summary>
238     /// <param name="node">
239     /// <para>The node.</para>
240     /// <para></para>
241     /// </param>
242     [MethodImpl(MethodImplOptions.AggressiveInlining)]
243     protected override void ClearNode(TLinkAddress node)
244     {
245         ref var link = ref LinksIndexParts[node];
246         link.LeftAsTarget = Zero;
247         link.RightAsTarget = Zero;
248         link.SizeAsTarget = Zero;
249     }
250
251     /// <summary>
252     /// <para>
253     /// Searches the source.
254     /// </para>
255     /// <para></para>
256     /// </summary>
257     /// <param name="source">
258     /// <para>The source.</para>
259     /// <para></para>
260     /// </param>
261     /// <param name="target">
262     /// <para>The target.</para>
263     /// <para></para>
264     /// </param>
265     /// <returns>
266     /// <para>The link</para>
267     /// <para></para>
268     /// </returns>
269     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
270         ↳ SearchCore(GetTreeRoot(target), source);

```

```
267 }
268 }
```

1.63 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32SplitMemoryLinks.cs

```
1 using System;
2 using System.Runtime.CompilerServices;
3 using Platform.Singletons;
4 using Platform.Memory;
5 using Platform.Data.Doublets.Memory.Split.Generic;
6 using TLinkAddress = System.UInt32;
7
8 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
9
10 namespace Platform.Data.Doublets.Memory.Split.Specific
11 {
12     /// <summary>
13     /// <para>
14     /// Represents the int 32 split memory links.
15     /// </para>
16     /// <para></para>
17     /// </summary>
18     /// <seealso cref="SplitMemoryLinksBase{TLinkAddress}"/>
19     public unsafe class UInt32SplitMemoryLinks : SplitMemoryLinksBase<TLinkAddress>
20     {
21         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createInternalSourceTreeMethods;
22         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createExternalSourceTreeMethods;
23         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createInternalTargetTreeMethods;
24         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createExternalTargetTreeMethods;
25         private LinksHeader<TLinkAddress>* _header;
26         private RawLinkDataPart<TLinkAddress>* _linksDataParts;
27         private RawLinkIndexPart<TLinkAddress>* _linksIndexParts;
28
29         /// <summary>
30         /// <para>
31         /// Initializes a new <see cref="UInt32SplitMemoryLinks"/> instance.
32         /// </para>
33         /// <para></para>
34         /// </summary>
35         /// <param name="dataMemory">
36         /// <para>A data memory.</para>
37         /// <para></para>
38         /// </param>
39         /// <param name="indexMemory">
40         /// <para>A index memory.</para>
41         /// <para></para>
42         /// </param>
43         [MethodImpl(MethodImplOptions.AggressiveInlining)]
44         public UInt32SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
45             ↪ indexMemory) : this(dataMemory, indexMemory, DefaultLinksSizeStep) { }
46
47         /// <summary>
48         /// <para>
49         /// Initializes a new <see cref="UInt32SplitMemoryLinks"/> instance.
50         /// </para>
51         /// <para></para>
52         /// </summary>
53         /// <param name="dataMemory">
54         /// <para>A data memory.</para>
55         /// <para></para>
56         /// </param>
57         /// <param name="indexMemory">
58         /// <para>A index memory.</para>
59         /// <para></para>
60         /// </param>
61         /// <param name="memoryReservationStep">
62         /// <para>A memory reservation step.</para>
63         /// <para></para>
64         /// </param>
65         [MethodImpl(MethodImplOptions.AggressiveInlining)]
66         public UInt32SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
67             ↪ indexMemory, long memoryReservationStep) : this(dataMemory, indexMemory,
68             ↪ memoryReservationStep, Default<LinksConstants<TLinkAddress>>.Instance,
69             ↪ IndexTreeType.Default, useLinkedList: true) { }
70
71         /// <summary>
72         /// <para>
73         /// Initializes a new <see cref="UInt32SplitMemoryLinks"/> instance.
74         /// </para>
75         /// <para></para>
```

```

72     /// </summary>
73     /// <param name="dataMemory">
74     /// <para>A data memory.</para>
75     /// <para></para>
76     /// </param>
77     /// <param name="indexMemory">
78     /// <para>A index memory.</para>
79     /// <para></para>
80     /// </param>
81     /// <param name="memoryReservationStep">
82     /// <para>A memory reservation step.</para>
83     /// <para></para>
84     /// </param>
85     /// <param name="constants">
86     /// <para>A constants.</para>
87     /// <para></para>
88     /// </param>
89     [MethodImpl(MethodImplOptions.AggressiveInlining)]
90     public UInt32SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
        ↳ indexMemory, long memoryReservationStep, LinksConstants<TLinkAddress> constants) :
        ↳ this(dataMemory, indexMemory, memoryReservationStep, constants,
        ↳ IndexTreeType.Default, useLinkedList: true) { }

91
92     /// <summary>
93     /// <para>
94     /// Initializes a new <see cref="UInt32SplitMemoryLinks"/> instance.
95     /// </para>
96     /// <para></para>
97     /// </summary>
98     /// <param name="dataMemory">
99     /// <para>A data memory.</para>
100    /// <para></para>
101    /// </param>
102    /// <param name="indexMemory">
103    /// <para>A index memory.</para>
104    /// <para></para>
105    /// </param>
106    /// <param name="memoryReservationStep">
107    /// <para>A memory reservation step.</para>
108    /// <para></para>
109    /// </param>
110    /// <param name="constants">
111    /// <para>A constants.</para>
112    /// <para></para>
113    /// </param>
114    /// <param name="indexTreeType">
115    /// <para>A index tree type.</para>
116    /// <para></para>
117    /// </param>
118    /// <param name="useLinkedList">
119    /// <para>A use linked list.</para>
120    /// <para></para>
121    /// </param>
122    [MethodImpl(MethodImplOptions.AggressiveInlining)]
123    public UInt32SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
        ↳ indexMemory, long memoryReservationStep, LinksConstants<TLinkAddress> constants,
        ↳ IndexTreeType indexTreeType, bool useLinkedList) : base(dataMemory, indexMemory,
        ↳ memoryReservationStep, constants, useLinkedList)
124    {
125        if (indexTreeType == IndexTreeType.SizeBalancedTree)
126        {
127            _createInternalSourceTreeMethods = () => new
                ↳ UInt32InternalLinksSourcesSizeBalancedTreeMethods(Constants,
                ↳ _linksDataParts, _linksIndexParts, _header);
128            _createExternalSourceTreeMethods = () => new
                ↳ UInt32ExternalLinksSourcesSizeBalancedTreeMethods(Constants,
                ↳ _linksDataParts, _linksIndexParts, _header);
129            _createInternalTargetTreeMethods = () => new
                ↳ UInt32InternalLinksTargetsSizeBalancedTreeMethods(Constants,
                ↳ _linksDataParts, _linksIndexParts, _header);
130            _createExternalTargetTreeMethods = () => new
                ↳ UInt32ExternalLinksTargetsSizeBalancedTreeMethods(Constants,
                ↳ _linksDataParts, _linksIndexParts, _header);
131        }
132        else
133        {

```

```

134         _createInternalSourceTreeMethods = () => new
135         ↪ UInt32InternalLinksSourcesRecursionlessSizeBalancedTreeMethods(Constants,
136         ↪ _linksDataParts, _linksIndexParts, _header);
137         _createExternalSourceTreeMethods = () => new
138         ↪ UInt32ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods(Constants,
139         ↪ _linksDataParts, _linksIndexParts, _header);
140         _createInternalTargetTreeMethods = () => new
141         ↪ UInt32InternalLinksTargetsRecursionlessSizeBalancedTreeMethods(Constants,
142         ↪ _linksDataParts, _linksIndexParts, _header);
143         _createExternalTargetTreeMethods = () => new
144         ↪ UInt32ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods(Constants,
145         ↪ _linksDataParts, _linksIndexParts, _header);
146     }
147     Init(dataMemory, indexMemory);
148 }
149
150 /// <summary>
151 /// <para>
152 /// Sets the pointers using the specified data memory.
153 /// </para>
154 /// <para></para>
155 /// </summary>
156 /// <param name="dataMemory">
157 /// <para>The data memory.</para>
158 /// <para></para>
159 /// </param>
160 /// <param name="indexMemory">
161 /// <para>The index memory.</para>
162 /// <para></para>
163 /// </param>
164 [MethodImpl(MethodImplOptions.AggressiveInlining)]
165 protected override void SetPointers(IResizableDirectMemory dataMemory,
166 ↪ IResizableDirectMemory indexMemory)
167 {
168     _linksDataParts = (RawLinkDataPart<TLinkAddress>*)dataMemory.Pointer;
169     _linksIndexParts = (RawLinkIndexPart<TLinkAddress>*)indexMemory.Pointer;
170     _header = (LinksHeader<TLinkAddress>*)indexMemory.Pointer;
171     if (_useLinkedList)
172     {
173         InternalSourcesListMethods = new
174         ↪ UInt32InternalLinksSourcesLinkedListMethods(Constants, _linksDataParts,
175         ↪ _linksIndexParts);
176     }
177     else
178     {
179         InternalSourcesTreeMethods = _createInternalSourceTreeMethods();
180     }
181     ExternalSourcesTreeMethods = _createExternalSourceTreeMethods();
182     InternalTargetsTreeMethods = _createInternalTargetTreeMethods();
183     ExternalTargetsTreeMethods = _createExternalTargetTreeMethods();
184     UnusedLinksListMethods = new UInt32UnusedLinksListMethods(_linksDataParts, _header);
185 }
186
187 /// <summary>
188 /// <para>
189 /// Resets the pointers.
190 /// </para>
191 /// <para></para>
192 /// </summary>
193 [MethodImpl(MethodImplOptions.AggressiveInlining)]
194 protected override void ResetPointers()
195 {
196     base.ResetPointers();
197     _linksDataParts = null;
198     _linksIndexParts = null;
199     _header = null;
200 }
201
202 /// <summary>
203 /// <para>
204 /// Gets the header reference.
205 /// </para>
206 /// <para></para>
207 /// </summary>
208 /// <returns>
209 /// <para>A ref links header of t link</para>
210 /// <para></para>
211 /// </returns>

```

```

201 [MethodImpl(MethodImplOptions.AggressiveInlining)]
202 protected override ref LinksHeader<TLinkAddress> GetHeaderReference() => ref *_header;
203
204 /// <summary>
205 /// <para>
206 /// Gets the link data part reference using the specified link index.
207 /// </para>
208 /// <para></para>
209 /// </summary>
210 /// <param name="linkIndex">
211 /// <para>The link index.</para>
212 /// <para></para>
213 /// </param>
214 /// <returns>
215 /// <para>A ref raw link data part of t link</para>
216 /// <para></para>
217 /// </returns>
218 [MethodImpl(MethodImplOptions.AggressiveInlining)]
219 protected override ref RawLinkDataPart<TLinkAddress>
220     ↪ GetLinkDataPartReference(TLinkAddress linkIndex) => ref _linksDataParts[linkIndex];
221
222 /// <summary>
223 /// <para>
224 /// Gets the link index part reference using the specified link index.
225 /// </para>
226 /// <para></para>
227 /// </summary>
228 /// <param name="linkIndex">
229 /// <para>The link index.</para>
230 /// <para></para>
231 /// </param>
232 /// <returns>
233 /// <para>A ref raw link index part of t link</para>
234 /// <para></para>
235 /// </returns>
236 [MethodImpl(MethodImplOptions.AggressiveInlining)]
237 protected override ref RawLinkIndexPart<TLinkAddress>
238     ↪ GetLinkIndexPartReference(TLinkAddress linkIndex) => ref _linksIndexParts[linkIndex];
239
240 /// <summary>
241 /// <para>
242 /// Determines whether this instance are equal.
243 /// </para>
244 /// <para></para>
245 /// </summary>
246 /// <param name="first">
247 /// <para>The first.</para>
248 /// <para></para>
249 /// </param>
250 /// <param name="second">
251 /// <para>The second.</para>
252 /// <para></para>
253 /// </param>
254 /// <returns>
255 /// <para>The bool</para>
256 /// <para></para>
257 /// </returns>
258 [MethodImpl(MethodImplOptions.AggressiveInlining)]
259 protected override bool AreEqual(TLinkAddress first, TLinkAddress second) => first ==
260     ↪ second;
261
262 /// <summary>
263 /// <para>
264 /// Determines whether this instance less than.
265 /// </para>
266 /// <para></para>
267 /// </summary>
268 /// <param name="first">
269 /// <para>The first.</para>
270 /// <para></para>
271 /// </param>
272 /// <param name="second">
273 /// <para>The second.</para>
274 /// <para></para>
275 /// </param>
276 /// <returns>
277 /// <para>The bool</para>
278 /// <para></para>
279 /// </returns>

```

```

276 /// </returns>
277 [MethodImpl(MethodImplOptions.AggressiveInlining)]
278 protected override bool LessThan(TLinkAddress first, TLinkAddress second) => first <
    ↪ second;
279
280 /// <summary>
281 /// <para>
282 /// Determines whether this instance less or equal than.
283 /// </para>
284 /// <para></para>
285 /// </summary>
286 /// <param name="first">
287 /// <para>The first.</para>
288 /// <para></para>
289 /// </param>
290 /// <param name="second">
291 /// <para>The second.</para>
292 /// <para></para>
293 /// </param>
294 /// <returns>
295 /// <para>The bool</para>
296 /// <para></para>
297 /// </returns>
298 [MethodImpl(MethodImplOptions.AggressiveInlining)]
299 protected override bool LessOrEqualThan(TLinkAddress first, TLinkAddress second) =>
    ↪ first <= second;
300
301 /// <summary>
302 /// <para>
303 /// Determines whether this instance greater than.
304 /// </para>
305 /// <para></para>
306 /// </summary>
307 /// <param name="first">
308 /// <para>The first.</para>
309 /// <para></para>
310 /// </param>
311 /// <param name="second">
312 /// <para>The second.</para>
313 /// <para></para>
314 /// </param>
315 /// <returns>
316 /// <para>The bool</para>
317 /// <para></para>
318 /// </returns>
319 [MethodImpl(MethodImplOptions.AggressiveInlining)]
320 protected override bool GreaterThan(TLinkAddress first, TLinkAddress second) => first >
    ↪ second;
321
322 /// <summary>
323 /// <para>
324 /// Determines whether this instance greater or equal than.
325 /// </para>
326 /// <para></para>
327 /// </summary>
328 /// <param name="first">
329 /// <para>The first.</para>
330 /// <para></para>
331 /// </param>
332 /// <param name="second">
333 /// <para>The second.</para>
334 /// <para></para>
335 /// </param>
336 /// <returns>
337 /// <para>The bool</para>
338 /// <para></para>
339 /// </returns>
340 [MethodImpl(MethodImplOptions.AggressiveInlining)]
341 protected override bool GreaterOrEqualThan(TLinkAddress first, TLinkAddress second) =>
    ↪ first >= second;
342
343 /// <summary>
344 /// <para>
345 /// Gets the zero.
346 /// </para>
347 /// <para></para>
348 /// </summary>
349 /// <returns>

```

```

350    /// <para>The link</para>
351    /// <para></para>
352    /// </returns>
353    [MethodImpl(MethodImplOptions.AggressiveInlining)]
354    protected override TLinkAddress GetZero() => 0U;
355
356    /// <summary>
357    /// <para>
358    /// Gets the one.
359    /// </para>
360    /// <para></para>
361    /// </summary>
362    /// <returns>
363    /// <para>The link</para>
364    /// <para></para>
365    /// </returns>
366    [MethodImpl(MethodImplOptions.AggressiveInlining)]
367    protected override TLinkAddress GetOne() => 1U;
368
369    /// <summary>
370    /// <para>
371    /// Converts the to int 64 using the specified value.
372    /// </para>
373    /// <para></para>
374    /// </summary>
375    /// <param name="value">
376    /// <para>The value.</para>
377    /// <para></para>
378    /// </param>
379    /// <returns>
380    /// <para>The long</para>
381    /// <para></para>
382    /// </returns>
383    [MethodImpl(MethodImplOptions.AggressiveInlining)]
384    protected override long ConvertToInt64(TLinkAddress value) => value;
385
386    /// <summary>
387    /// <para>
388    /// Converts the to address using the specified value.
389    /// </para>
390    /// <para></para>
391    /// </summary>
392    /// <param name="value">
393    /// <para>The value.</para>
394    /// <para></para>
395    /// </param>
396    /// <returns>
397    /// <para>The link</para>
398    /// <para></para>
399    /// </returns>
400    [MethodImpl(MethodImplOptions.AggressiveInlining)]
401    protected override TLinkAddress ConvertToAddress(long value) => (TLinkAddress)value;
402
403    /// <summary>
404    /// <para>
405    /// Adds the first.
406    /// </para>
407    /// <para></para>
408    /// </summary>
409    /// <param name="first">
410    /// <para>The first.</para>
411    /// <para></para>
412    /// </param>
413    /// <param name="second">
414    /// <para>The second.</para>
415    /// <para></para>
416    /// </param>
417    /// <returns>
418    /// <para>The link</para>
419    /// <para></para>
420    /// </returns>
421    [MethodImpl(MethodImplOptions.AggressiveInlining)]
422    protected override TLinkAddress Add(TLinkAddress first, TLinkAddress second) => first +
    ↪ second;
423
424    /// <summary>
425    /// <para>
426    /// Subtracts the first.

```

```

427     /// </para>
428     /// <para></para>
429     /// </summary>
430     /// <param name="first">
431     /// <para>The first.</para>
432     /// <para></para>
433     /// </param>
434     /// <param name="second">
435     /// <para>The second.</para>
436     /// <para></para>
437     /// </param>
438     /// <returns>
439     /// <para>The link</para>
440     /// <para></para>
441     /// </returns>
442     [MethodImpl(MethodImplOptions.AggressiveInlining)]
443     protected override TLinkAddress Subtract(TLinkAddress first, TLinkAddress second) =>
444         ↪ first - second;
445
446     /// <summary>
447     /// <para>
448     /// Increments the link.
449     /// </para>
450     /// <para></para>
451     /// </summary>
452     /// <param name="link">
453     /// <para>The link.</para>
454     /// <para></para>
455     /// </param>
456     /// <returns>
457     /// <para>The link</para>
458     /// <para></para>
459     /// </returns>
460     [MethodImpl(MethodImplOptions.AggressiveInlining)]
461     protected override TLinkAddress Increment(TLinkAddress link) => ++link;
462
463     /// <summary>
464     /// <para>
465     /// Decrements the link.
466     /// </para>
467     /// <para></para>
468     /// </summary>
469     /// <param name="link">
470     /// <para>The link.</para>
471     /// <para></para>
472     /// </param>
473     /// <returns>
474     /// <para>The link</para>
475     /// <para></para>
476     /// </returns>
477     [MethodImpl(MethodImplOptions.AggressiveInlining)]
478     protected override TLinkAddress Decrement(TLinkAddress link) => --link;
479 }

```

1.64 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32UnusedLinksListMethods.cs

```

1  using System.Runtime.CompilerServices;
2  using Platform.Data.Doublets.Memory.Split.Generic;
3  using TLinkAddress = System.UInt32;
4
5  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7  namespace Platform.Data.Doublets.Memory.Split.Specific
8  {
9      /// <summary>
10     /// <para>
11     /// Represents the int 32 unused links list methods.
12     /// </para>
13     /// <para></para>
14     /// </summary>
15     /// <seealso cref="UnusedLinksListMethods{TLinkAddress}"/>
16     public unsafe class UInt32UnusedLinksListMethods : UnusedLinksListMethods<TLinkAddress>
17     {
18         private readonly RawLinkDataPart<TLinkAddress>* _links;
19         private readonly LinksHeader<TLinkAddress>* _header;
20
21         /// <summary>
22         /// <para>
23         /// Initializes a new <see cref="UInt32UnusedLinksListMethods"/> instance.

```



```

24     /// </para>
25     /// <para></para>
26     /// </summary>
27     /// <param name="links">
28     /// <para>A links.</para>
29     /// <para></para>
30     /// </param>
31     /// <param name="header">
32     /// <para>A header.</para>
33     /// <para></para>
34     /// </param>
35     [MethodImpl(MethodImplOptions.AggressiveInlining)]
36     public UInt32UnusedLinksListMethods(RawLinkDataPart<TLinkAddress>* links,
    → LinksHeader<TLinkAddress>* header)
    : base((byte*)links, (byte*)header)
37     {
38     {
39         _links = links;
40         _header = header;
41     }
42
43     /// <summary>
44     /// <para>
45     /// Gets the link data part reference using the specified link.
46     /// </para>
47     /// <para></para>
48     /// </summary>
49     /// <param name="link">
50     /// <para>The link.</para>
51     /// <para></para>
52     /// </param>
53     /// <returns>
54     /// <para>A ref raw link data part of t link</para>
55     /// <para></para>
56     /// </returns>
57     [MethodImpl(MethodImplOptions.AggressiveInlining)]
58     protected override ref RawLinkDataPart<TLinkAddress>
    → GetLinkDataPartReference(TLinkAddress link) => ref _links[link];
59
60     /// <summary>
61     /// <para>
62     /// Gets the header reference.
63     /// </para>
64     /// <para></para>
65     /// </summary>
66     /// <returns>
67     /// <para>A ref links header of t link</para>
68     /// <para></para>
69     /// </returns>
70     [MethodImpl(MethodImplOptions.AggressiveInlining)]
71     protected override ref LinksHeader<TLinkAddress> GetHeaderReference() => ref *_header;
72 }
73 }

```

1.65 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksRecursionlessSizeBalancedTree

```

1 using System.Runtime.CompilerServices;
2 using Platform.Data.Doublets.Memory.Split.Generic;
3 using TLinkAddress = System.UInt64;
4
5 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7 namespace Platform.Data.Doublets.Memory.Split.Specific
8 {
9     /// <summary>
10    /// <para>
11    /// Represents the int 64 external links recursionless size balanced tree methods base.
12    /// </para>
13    /// <para></para>
14    /// </summary>
15    /// <seealso cref="ExternalLinksRecursionlessSizeBalancedTreeMethodsBase{TLinkAddress}"/>
16    /// <seealso cref="ILinksTreeMethods{TLinkAddress}"/>
17    public unsafe abstract class UInt64ExternalLinksRecursionlessSizeBalancedTreeMethodsBase :
    → ExternalLinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress>,
    → ILinksTreeMethods<TLinkAddress>
18    {
19        /// <summary>
20        /// <para>
21        /// The links data parts.
22        /// </para>
23        /// <para></para>

```

```

24     /// </summary>
25     protected new readonly RawLinkDataPart<TLinkAddress>* LinksDataParts;
26     /// <summary>
27     /// <para>
28     /// The links index parts.
29     /// </para>
30     /// <para></para>
31     /// </summary>
32     protected new readonly RawLinkIndexPart<TLinkAddress>* LinksIndexParts;
33     /// <summary>
34     /// <para>
35     /// The header.
36     /// </para>
37     /// <para></para>
38     /// </summary>
39     protected new readonly LinksHeader<TLinkAddress>* Header;
40
41     /// <summary>
42     /// <para>
43     /// Initializes a new <see
44     ↪ cref="UInt64ExternalLinksRecursionlessSizeBalancedTreeMethodsBase"/> instance.
45     /// <para></para>
46     /// </summary>
47     /// <param name="constants">
48     /// <para>A constants.</para>
49     /// <para></para>
50     /// </param>
51     /// <param name="linksDataParts">
52     /// <para>A links data parts.</para>
53     /// <para></para>
54     /// </param>
55     /// <param name="linksIndexParts">
56     /// <para>A links index parts.</para>
57     /// <para></para>
58     /// </param>
59     /// <param name="header">
60     /// <para>A header.</para>
61     /// <para></para>
62     /// </param>
63     [MethodImpl(MethodImplOptions.AggressiveInlining)]
64     protected UInt64ExternalLinksRecursionlessSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
65     ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
66     : base(constants, (byte*)linksDataParts, (byte*)linksIndexParts, (byte*)header)
67     {
68         LinksDataParts = linksDataParts;
69         LinksIndexParts = linksIndexParts;
70         Header = header;
71     }
72
73     /// <summary>
74     /// <para>
75     /// Gets the zero.
76     /// </para>
77     /// <para></para>
78     /// </summary>
79     /// <returns>
80     /// <para>The ulong</para>
81     /// <para></para>
82     /// </returns>
83     [MethodImpl(MethodImplOptions.AggressiveInlining)]
84     protected override ulong GetZero() => 0UL;
85
86     /// <summary>
87     /// <para>
88     /// Determines whether this instance equal to zero.
89     /// </para>
90     /// <para></para>
91     /// </summary>
92     /// <param name="value">
93     /// <para>The value.</para>
94     /// <para></para>
95     /// </param>
96     /// <returns>
97     /// <para>The bool</para>
98     /// <para></para>
99     /// </returns>

```

```

99 [MethodImpl(MethodImplOptions.AggressiveInlining)]
100 protected override bool EqualToZero(ulong value) => value == 0UL;
101
102 /// <summary>
103 /// <para>
104 /// Determines whether this instance are equal.
105 /// </para>
106 /// <para></para>
107 /// </summary>
108 /// <param name="first">
109 /// <para>The first.</para>
110 /// <para></para>
111 /// </param>
112 /// <param name="second">
113 /// <para>The second.</para>
114 /// <para></para>
115 /// </param>
116 /// <returns>
117 /// <para>The bool</para>
118 /// <para></para>
119 /// </returns>
120 [MethodImpl(MethodImplOptions.AggressiveInlining)]
121 protected override bool AreEqual(ulong first, ulong second) => first == second;
122
123 /// <summary>
124 /// <para>
125 /// Determines whether this instance greater than zero.
126 /// </para>
127 /// <para></para>
128 /// </summary>
129 /// <param name="value">
130 /// <para>The value.</para>
131 /// <para></para>
132 /// </param>
133 /// <returns>
134 /// <para>The bool</para>
135 /// <para></para>
136 /// </returns>
137 [MethodImpl(MethodImplOptions.AggressiveInlining)]
138 protected override bool GreaterThanZero(ulong value) => value > 0UL;
139
140 /// <summary>
141 /// <para>
142 /// Determines whether this instance greater than.
143 /// </para>
144 /// <para></para>
145 /// </summary>
146 /// <param name="first">
147 /// <para>The first.</para>
148 /// <para></para>
149 /// </param>
150 /// <param name="second">
151 /// <para>The second.</para>
152 /// <para></para>
153 /// </param>
154 /// <returns>
155 /// <para>The bool</para>
156 /// <para></para>
157 /// </returns>
158 [MethodImpl(MethodImplOptions.AggressiveInlining)]
159 protected override bool GreaterThan(ulong first, ulong second) => first > second;
160
161 /// <summary>
162 /// <para>
163 /// Determines whether this instance greater or equal than.
164 /// </para>
165 /// <para></para>
166 /// </summary>
167 /// <param name="first">
168 /// <para>The first.</para>
169 /// <para></para>
170 /// </param>
171 /// <param name="second">
172 /// <para>The second.</para>
173 /// <para></para>
174 /// </param>
175 /// <returns>
176 /// <para>The bool</para>

```

```

177     /// <para></para>
178     /// </returns>
179     [MethodImpl(MethodImplOptions.AggressiveInlining)]
180     protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;
181
182     /// <summary>
183     /// <para>
184     /// Determines whether this instance greater or equal than zero.
185     /// </para>
186     /// <para></para>
187     /// </summary>
188     /// <param name="value">
189     /// <para>The value.</para>
190     /// <para></para>
191     /// </param>
192     /// <returns>
193     /// <para>The bool</para>
194     /// <para></para>
195     /// </returns>
196     [MethodImpl(MethodImplOptions.AggressiveInlining)]
197     protected override bool GreaterOrEqualThanZero(ulong value) => true; // value >= 0 is
198     ↪ always true for ulong
199
200     /// <summary>
201     /// <para>
202     /// Determines whether this instance less or equal than zero.
203     /// </para>
204     /// <para></para>
205     /// </summary>
206     /// <param name="value">
207     /// <para>The value.</para>
208     /// <para></para>
209     /// </param>
210     /// <returns>
211     /// <para>The bool</para>
212     /// <para></para>
213     /// </returns>
214     [MethodImpl(MethodImplOptions.AggressiveInlining)]
215     protected override bool LessOrEqualThanZero(ulong value) => value == 0UL; // value is
216     ↪ always >= 0 for ulong
217
218     /// <summary>
219     /// <para>
220     /// Determines whether this instance less or equal than.
221     /// </para>
222     /// <para></para>
223     /// </summary>
224     /// <param name="first">
225     /// <para>The first.</para>
226     /// <para></para>
227     /// </param>
228     /// <param name="second">
229     /// <para>The second.</para>
230     /// <para></para>
231     /// </param>
232     /// <returns>
233     /// <para>The bool</para>
234     /// <para></para>
235     /// </returns>
236     [MethodImpl(MethodImplOptions.AggressiveInlining)]
237     protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;
238
239     /// <summary>
240     /// <para>
241     /// Determines whether this instance less than zero.
242     /// </para>
243     /// <para></para>
244     /// </summary>
245     /// <param name="value">
246     /// <para>The value.</para>
247     /// <para></para>
248     /// </param>
249     /// <returns>
250     /// <para>The bool</para>
251     /// <para></para>
252     /// </returns>
253     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

252     protected override bool LessThanZero(ulong value) => false; // value < 0 is always false
253     ↪ for ulong
254
255     /// <summary>
256     /// <para>
257     /// Determines whether this instance less than.
258     /// </para>
259     /// <para></para>
260     /// </summary>
261     /// <param name="first">
262     /// <para>The first.</para>
263     /// <para></para>
264     /// </param>
265     /// <param name="second">
266     /// <para>The second.</para>
267     /// <para></para>
268     /// </param>
269     /// <returns>
270     /// <para>The bool</para>
271     /// <para></para>
272     /// </returns>
273     [MethodImpl(MethodImplOptions.AggressiveInlining)]
274     protected override bool LessThan(ulong first, ulong second) => first < second;
275
276     /// <summary>
277     /// <para>
278     /// Increments the value.
279     /// </para>
280     /// <para></para>
281     /// </summary>
282     /// <param name="value">
283     /// <para>The value.</para>
284     /// <para></para>
285     /// </param>
286     /// <returns>
287     /// <para>The ulong</para>
288     /// <para></para>
289     /// </returns>
290     [MethodImpl(MethodImplOptions.AggressiveInlining)]
291     protected override ulong Increment(ulong value) => ++value;
292
293     /// <summary>
294     /// <para>
295     /// Decrements the value.
296     /// </para>
297     /// <para></para>
298     /// </summary>
299     /// <param name="value">
300     /// <para>The value.</para>
301     /// <para></para>
302     /// </param>
303     /// <returns>
304     /// <para>The ulong</para>
305     /// <para></para>
306     /// </returns>
307     [MethodImpl(MethodImplOptions.AggressiveInlining)]
308     protected override ulong Decrement(ulong value) => --value;
309
310     /// <summary>
311     /// <para>
312     /// Adds the first.
313     /// </para>
314     /// <para></para>
315     /// </summary>
316     /// <param name="first">
317     /// <para>The first.</para>
318     /// <para></para>
319     /// </param>
320     /// <param name="second">
321     /// <para>The second.</para>
322     /// <para></para>
323     /// </param>
324     /// <returns>
325     /// <para>The ulong</para>
326     /// <para></para>
327     /// </returns>
328     [MethodImpl(MethodImplOptions.AggressiveInlining)]
329     protected override ulong Add(ulong first, ulong second) => first + second;

```

```

329
330    /// <summary>
331    /// <para>
332    /// Subtracts the first.
333    /// </para>
334    /// <para></para>
335    /// </summary>
336    /// <param name="first">
337    /// <para>The first.</para>
338    /// <para></para>
339    /// </param>
340    /// <param name="second">
341    /// <para>The second.</para>
342    /// <para></para>
343    /// </param>
344    /// <returns>
345    /// <para>The ulong</para>
346    /// <para></para>
347    /// </returns>
348    [MethodImpl(MethodImplOptions.AggressiveInlining)]
349    protected override ulong Subtract(ulong first, ulong second) => first - second;
350
351    /// <summary>
352    /// <para>
353    /// Gets the header reference.
354    /// </para>
355    /// <para></para>
356    /// </summary>
357    /// <returns>
358    /// <para>A ref links header of t link</para>
359    /// <para></para>
360    /// </returns>
361    [MethodImpl(MethodImplOptions.AggressiveInlining)]
362    protected override ref LinksHeader<TLinkAddress> GetHeaderReference() => ref *Header;
363
364    /// <summary>
365    /// <para>
366    /// Gets the link data part reference using the specified link.
367    /// </para>
368    /// <para></para>
369    /// </summary>
370    /// <param name="link">
371    /// <para>The link.</para>
372    /// <para></para>
373    /// </param>
374    /// <returns>
375    /// <para>A ref raw link data part of t link</para>
376    /// <para></para>
377    /// </returns>
378    [MethodImpl(MethodImplOptions.AggressiveInlining)]
379    protected override ref RawLinkDataPart<TLinkAddress>
380    ↪ GetLinkDataPartReference(TLinkAddress link) => ref LinksDataParts[link];
381
382    /// <summary>
383    /// <para>
384    /// Gets the link index part reference using the specified link.
385    /// </para>
386    /// <para></para>
387    /// </summary>
388    /// <param name="link">
389    /// <para>The link.</para>
390    /// <para></para>
391    /// </param>
392    /// <returns>
393    /// <para>A ref raw link index part of t link</para>
394    /// <para></para>
395    /// </returns>
396    [MethodImpl(MethodImplOptions.AggressiveInlining)]
397    protected override ref RawLinkIndexPart<TLinkAddress>
398    ↪ GetLinkIndexPartReference(TLinkAddress link) => ref LinksIndexParts[link];
399
400    /// <summary>
401    /// <para>
402    /// Determines whether this instance first is to the left of second.
403    /// </para>
404    /// <para></para>
405    /// </summary>
406    /// <param name="first">

```

```

405     /// <para>The first.</para>
406     /// <para></para>
407     /// </param>
408     /// <param name="second">
409     /// <para>The second.</para>
410     /// <para></para>
411     /// </param>
412     /// <returns>
413     /// <para>The bool</para>
414     /// <para></para>
415     /// </returns>
416     [MethodImpl(MethodImplOptions.AggressiveInlining)]
417     protected override bool FirstIsToTheLeftOfSecond(TLinkAddress first, TLinkAddress second)
418     {
419         ref var firstLink = ref LinksDataParts[first];
420         ref var secondLink = ref LinksDataParts[second];
421         return FirstIsToTheLeftOfSecond(firstLink.Source, firstLink.Target,
422             ↪ secondLink.Source, secondLink.Target);
423     }
424     /// <summary>
425     /// <para>
426     /// Determines whether this instance first is to the right of second.
427     /// </para>
428     /// <para></para>
429     /// </summary>
430     /// <param name="first">
431     /// <para>The first.</para>
432     /// <para></para>
433     /// </param>
434     /// <param name="second">
435     /// <para>The second.</para>
436     /// <para></para>
437     /// </param>
438     /// <returns>
439     /// <para>The bool</para>
440     /// <para></para>
441     /// </returns>
442     [MethodImpl(MethodImplOptions.AggressiveInlining)]
443     protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
444         ↪ second)
445     {
446         ref var firstLink = ref LinksDataParts[first];
447         ref var secondLink = ref LinksDataParts[second];
448         return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
449             ↪ secondLink.Source, secondLink.Target);
450     }
451 }

```

1.66 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksSizeBalancedTreeMethodsBase

```

1  using System.Runtime.CompilerServices;
2  using Platform.Data.Doublets.Memory.Split.Generic;
3  using TLinkAddress = System.UInt64;
4
5  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7  namespace Platform.Data.Doublets.Memory.Split.Specific
8  {
9      /// <summary>
10     /// <para>
11     /// Represents the int 64 external links size balanced tree methods base.
12     /// </para>
13     /// <para></para>
14     /// </summary>
15     /// <seealso cref="ExternalLinksSizeBalancedTreeMethodsBase{TLinkAddress}"/>
16     /// <seealso cref="ILinksTreeMethods{TLinkAddress}"/>
17     public unsafe abstract class UInt64ExternalLinksSizeBalancedTreeMethodsBase :
18         ↪ ExternalLinksSizeBalancedTreeMethodsBase<TLinkAddress>, ILinksTreeMethods<TLinkAddress>
19     {
20         /// <summary>
21         /// <para>
22         /// The links data parts.
23         /// </para>
24         /// <para></para>
25         /// </summary>
26         protected new readonly RawLinkDataPart<TLinkAddress>* LinksDataParts;
27     }

```

```

27     /// <para>
28     /// The links index parts.
29     /// </para>
30     /// <para></para>
31     /// </summary>
32     protected new readonly RawLinkIndexPart<TLinkAddress>* LinksIndexParts;
33     /// <summary>
34     /// <para>
35     /// The header.
36     /// </para>
37     /// <para></para>
38     /// </summary>
39     protected new readonly LinksHeader<TLinkAddress>* Header;
40
41     /// <summary>
42     /// <para>
43     /// Initializes a new <see cref="UInt64ExternalLinksSizeBalancedTreeMethodsBase"/>
44     ↪ instance.
45     /// </para>
46     /// <para></para>
47     /// </summary>
48     /// <param name="constants">
49     /// <para>A constants.</para>
50     /// <para></para>
51     /// </param>
52     /// <param name="linksDataParts">
53     /// <para>A links data parts.</para>
54     /// <para></para>
55     /// </param>
56     /// <param name="linksIndexParts">
57     /// <para>A links index parts.</para>
58     /// <para></para>
59     /// </param>
60     /// <param name="header">
61     /// <para>A header.</para>
62     /// <para></para>
63     /// </param>
64     [MethodImpl(MethodImplOptions.AggressiveInlining)]
65     protected UInt64ExternalLinksSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress>
66     ↪ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
67     ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
68     : base(constants, (byte*)linksDataParts, (byte*)linksIndexParts, (byte*)header)
69     {
70         LinksDataParts = linksDataParts;
71         LinksIndexParts = linksIndexParts;
72         Header = header;
73     }
74
75     /// <summary>
76     /// <para>
77     /// Gets the zero.
78     /// </para>
79     /// <para></para>
80     /// </summary>
81     /// <returns>
82     /// <para>The ulong</para>
83     /// <para></para>
84     /// </returns>
85     [MethodImpl(MethodImplOptions.AggressiveInlining)]
86     protected override ulong GetZero() => 0UL;
87
88     /// <summary>
89     /// <para>
90     /// Determines whether this instance equal to zero.
91     /// </para>
92     /// <para></para>
93     /// </summary>
94     /// <param name="value">
95     /// <para>The value.</para>
96     /// <para></para>
97     /// </param>
98     /// <returns>
99     /// <para>The bool</para>
100     /// <para></para>
101     /// </returns>
102     [MethodImpl(MethodImplOptions.AggressiveInlining)]
103     protected override bool EqualToZero(ulong value) => value == 0UL;

```



```

102     /// <summary>
103     /// <para>
104     /// Determines whether this instance are equal.
105     /// </para>
106     /// <para></para>
107     /// </summary>
108     /// <param name="first">
109     /// <para>The first.</para>
110     /// <para></para>
111     /// </param>
112     /// <param name="second">
113     /// <para>The second.</para>
114     /// <para></para>
115     /// </param>
116     /// <returns>
117     /// <para>The bool</para>
118     /// <para></para>
119     /// </returns>
120     [MethodImpl(MethodImplOptions.AggressiveInlining)]
121     protected override bool AreEqual(ulong first, ulong second) => first == second;
122
123     /// <summary>
124     /// <para>
125     /// Determines whether this instance greater than zero.
126     /// </para>
127     /// <para></para>
128     /// </summary>
129     /// <param name="value">
130     /// <para>The value.</para>
131     /// <para></para>
132     /// </param>
133     /// <returns>
134     /// <para>The bool</para>
135     /// <para></para>
136     /// </returns>
137     [MethodImpl(MethodImplOptions.AggressiveInlining)]
138     protected override bool GreaterThanZero(ulong value) => value > 0UL;
139
140     /// <summary>
141     /// <para>
142     /// Determines whether this instance greater than.
143     /// </para>
144     /// <para></para>
145     /// </summary>
146     /// <param name="first">
147     /// <para>The first.</para>
148     /// <para></para>
149     /// </param>
150     /// <param name="second">
151     /// <para>The second.</para>
152     /// <para></para>
153     /// </param>
154     /// <returns>
155     /// <para>The bool</para>
156     /// <para></para>
157     /// </returns>
158     [MethodImpl(MethodImplOptions.AggressiveInlining)]
159     protected override bool GreaterThan(ulong first, ulong second) => first > second;
160
161     /// <summary>
162     /// <para>
163     /// Determines whether this instance greater or equal than.
164     /// </para>
165     /// <para></para>
166     /// </summary>
167     /// <param name="first">
168     /// <para>The first.</para>
169     /// <para></para>
170     /// </param>
171     /// <param name="second">
172     /// <para>The second.</para>
173     /// <para></para>
174     /// </param>
175     /// <returns>
176     /// <para>The bool</para>
177     /// <para></para>
178     /// </returns>
179     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

180     protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;
181
182     /// <summary>
183     /// <para>
184     /// Determines whether this instance greater or equal than zero.
185     /// </para>
186     /// <para></para>
187     /// </summary>
188     /// <param name="value">
189     /// <para>The value.</para>
190     /// <para></para>
191     /// </param>
192     /// <returns>
193     /// <para>The bool</para>
194     /// <para></para>
195     /// </returns>
196     [MethodImpl(MethodImplOptions.AggressiveInlining)]
197     protected override bool GreaterOrEqualThanZero(ulong value) => true; // value >= 0 is
    ↪ always true for ulong
198
199     /// <summary>
200     /// <para>
201     /// Determines whether this instance less or equal than zero.
202     /// </para>
203     /// <para></para>
204     /// </summary>
205     /// <param name="value">
206     /// <para>The value.</para>
207     /// <para></para>
208     /// </param>
209     /// <returns>
210     /// <para>The bool</para>
211     /// <para></para>
212     /// </returns>
213     [MethodImpl(MethodImplOptions.AggressiveInlining)]
214     protected override bool LessOrEqualThanZero(ulong value) => value == 0UL; // value is
    ↪ always >= 0 for ulong
215
216     /// <summary>
217     /// <para>
218     /// Determines whether this instance less or equal than.
219     /// </para>
220     /// <para></para>
221     /// </summary>
222     /// <param name="first">
223     /// <para>The first.</para>
224     /// <para></para>
225     /// </param>
226     /// <param name="second">
227     /// <para>The second.</para>
228     /// <para></para>
229     /// </param>
230     /// <returns>
231     /// <para>The bool</para>
232     /// <para></para>
233     /// </returns>
234     [MethodImpl(MethodImplOptions.AggressiveInlining)]
235     protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;
236
237     /// <summary>
238     /// <para>
239     /// Determines whether this instance less than zero.
240     /// </para>
241     /// <para></para>
242     /// </summary>
243     /// <param name="value">
244     /// <para>The value.</para>
245     /// <para></para>
246     /// </param>
247     /// <returns>
248     /// <para>The bool</para>
249     /// <para></para>
250     /// </returns>
251     [MethodImpl(MethodImplOptions.AggressiveInlining)]
252     protected override bool LessThanZero(ulong value) => false; // value < 0 is always false
    ↪ for ulong
253
254     /// <summary>

```

```

255     /// <para>
256     /// Determines whether this instance less than.
257     /// </para>
258     /// <para></para>
259     /// </summary>
260     /// <param name="first">
261     /// <para>The first.</para>
262     /// <para></para>
263     /// </param>
264     /// <param name="second">
265     /// <para>The second.</para>
266     /// <para></para>
267     /// </param>
268     /// <returns>
269     /// <para>The bool</para>
270     /// <para></para>
271     /// </returns>
272     [MethodImpl(MethodImplOptions.AggressiveInlining)]
273     protected override bool LessThan(ulong first, ulong second) => first < second;
274
275     /// <summary>
276     /// <para>
277     /// Increments the value.
278     /// </para>
279     /// <para></para>
280     /// </summary>
281     /// <param name="value">
282     /// <para>The value.</para>
283     /// <para></para>
284     /// </param>
285     /// <returns>
286     /// <para>The ulong</para>
287     /// <para></para>
288     /// </returns>
289     [MethodImpl(MethodImplOptions.AggressiveInlining)]
290     protected override ulong Increment(ulong value) => ++value;
291
292     /// <summary>
293     /// <para>
294     /// Decrements the value.
295     /// </para>
296     /// <para></para>
297     /// </summary>
298     /// <param name="value">
299     /// <para>The value.</para>
300     /// <para></para>
301     /// </param>
302     /// <returns>
303     /// <para>The ulong</para>
304     /// <para></para>
305     /// </returns>
306     [MethodImpl(MethodImplOptions.AggressiveInlining)]
307     protected override ulong Decrement(ulong value) => --value;
308
309     /// <summary>
310     /// <para>
311     /// Adds the first.
312     /// </para>
313     /// <para></para>
314     /// </summary>
315     /// <param name="first">
316     /// <para>The first.</para>
317     /// <para></para>
318     /// </param>
319     /// <param name="second">
320     /// <para>The second.</para>
321     /// <para></para>
322     /// </param>
323     /// <returns>
324     /// <para>The ulong</para>
325     /// <para></para>
326     /// </returns>
327     [MethodImpl(MethodImplOptions.AggressiveInlining)]
328     protected override ulong Add(ulong first, ulong second) => first + second;
329
330     /// <summary>
331     /// <para>
332     /// Subtracts the first.

```

```

333     /// </para>
334     /// <para></para>
335     /// </summary>
336     /// <param name="first">
337     /// <para>The first.</para>
338     /// <para></para>
339     /// </param>
340     /// <param name="second">
341     /// <para>The second.</para>
342     /// <para></para>
343     /// </param>
344     /// <returns>
345     /// <para>The ulong</para>
346     /// <para></para>
347     /// </returns>
348     [MethodImpl(MethodImplOptions.AggressiveInlining)]
349     protected override ulong Subtract(ulong first, ulong second) => first - second;
350
351     /// <summary>
352     /// <para>
353     /// Gets the header reference.
354     /// </para>
355     /// <para></para>
356     /// </summary>
357     /// <returns>
358     /// <para>A ref links header of t link</para>
359     /// <para></para>
360     /// </returns>
361     [MethodImpl(MethodImplOptions.AggressiveInlining)]
362     protected override ref LinksHeader<TLinkAddress> GetHeaderReference() => ref *Header;
363
364     /// <summary>
365     /// <para>
366     /// Gets the link data part reference using the specified link.
367     /// </para>
368     /// <para></para>
369     /// </summary>
370     /// <param name="link">
371     /// <para>The link.</para>
372     /// <para></para>
373     /// </param>
374     /// <returns>
375     /// <para>A ref raw link data part of t link</para>
376     /// <para></para>
377     /// </returns>
378     [MethodImpl(MethodImplOptions.AggressiveInlining)]
379     protected override ref RawLinkDataPart<TLinkAddress>
380     ↪ GetLinkDataPartReference(TLinkAddress link) => ref LinksDataParts[link];
381
382     /// <summary>
383     /// <para>
384     /// Gets the link index part reference using the specified link.
385     /// </para>
386     /// <para></para>
387     /// </summary>
388     /// <param name="link">
389     /// <para>The link.</para>
390     /// <para></para>
391     /// </param>
392     /// <returns>
393     /// <para>A ref raw link index part of t link</para>
394     /// <para></para>
395     /// </returns>
396     [MethodImpl(MethodImplOptions.AggressiveInlining)]
397     protected override ref RawLinkIndexPart<TLinkAddress>
398     ↪ GetLinkIndexPartReference(TLinkAddress link) => ref LinksIndexParts[link];
399
400     /// <summary>
401     /// <para>
402     /// Determines whether this instance first is to the left of second.
403     /// </para>
404     /// <para></para>
405     /// </summary>
406     /// <param name="first">
407     /// <para>The first.</para>
408     /// <para></para>
409     /// </param>
410     /// <param name="second">

```

```

409     /// <para>The second.</para>
410     /// <para></para>
411     /// </param>
412     /// <returns>
413     /// <para>The bool</para>
414     /// <para></para>
415     /// </returns>
416     [MethodImpl(MethodImplOptions.AggressiveInlining)]
417     protected override bool FirstIsToTheLeftOfSecond(TLinkAddress first, TLinkAddress second)
418     {
419         ref var firstLink = ref LinksDataParts[first];
420         ref var secondLink = ref LinksDataParts[second];
421         return FirstIsToTheLeftOfSecond(firstLink.Source, firstLink.Target,
422             ↪ secondLink.Source, secondLink.Target);
423     }
424     /// <summary>
425     /// <para>
426     /// Determines whether this instance first is to the right of second.
427     /// </para>
428     /// <para></para>
429     /// </summary>
430     /// <param name="first">
431     /// <para>The first.</para>
432     /// <para></para>
433     /// </param>
434     /// <param name="second">
435     /// <para>The second.</para>
436     /// <para></para>
437     /// </param>
438     /// <returns>
439     /// <para>The bool</para>
440     /// <para></para>
441     /// </returns>
442     [MethodImpl(MethodImplOptions.AggressiveInlining)]
443     protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
444         ↪ second)
445     {
446         ref var firstLink = ref LinksDataParts[first];
447         ref var secondLink = ref LinksDataParts[second];
448         return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
449             ↪ secondLink.Source, secondLink.Target);
450     }
451 }

```

1.67 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksSourcesRecursionlessSizeBalancedTreeMethodsBase

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt64;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 64 external links sources recursionless size balanced tree methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="UInt64ExternalLinksRecursionlessSizeBalancedTreeMethodsBase"/>
15     public unsafe class UInt64ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods :
16         ↪ UInt64ExternalLinksRecursionlessSizeBalancedTreeMethodsBase
17     {
18         /// <summary>
19         /// <para>
20         /// Initializes a new <see
21         ↪ cref="UInt64ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods"/> instance.
22         /// </para>
23         /// <para></para>
24         /// </summary>
25         /// <param name="constants">
26         /// <para>A constants.</para>
27         /// <para></para>
28         /// </param>
29         /// <param name="linksDataParts">
30         /// <para>A links data parts.</para>
31         /// <para></para>
32         /// </param>

```

```

30    /// </param>
31    /// <param name="linksIndexParts">
32    /// <para>A links index parts.</para>
33    /// </para></param>
34    /// </param>
35    /// <param name="header">
36    /// <para>A header.</para>
37    /// </para></param>
38    /// </param>
39    [MethodImpl(MethodImplOptions.AggressiveInlining)]
40    public UInt64 ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
    ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
    ↪ : base(constants, linksDataParts, linksIndexParts, header) { }

41
42    /// <summary>
43    /// <para>
44    /// Gets the left reference using the specified node.
45    /// </para>
46    /// </para></summary>
47    /// </summary>
48    /// <param name="node">
49    /// <para>The node.</para>
50    /// </para></param>
51    /// </param>
52    /// <returns>
53    /// <para>The ref link</para>
54    /// </para></returns>
55    /// </returns>
56    [MethodImpl(MethodImplOptions.AggressiveInlining)]
57    protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].LeftAsSource;

58
59    /// <summary>
60    /// <para>
61    /// Gets the right reference using the specified node.
62    /// </para>
63    /// </para></summary>
64    /// </summary>
65    /// <param name="node">
66    /// <para>The node.</para>
67    /// </para></param>
68    /// </param>
69    /// <returns>
70    /// <para>The ref link</para>
71    /// </para></returns>
72    /// </returns>
73    [MethodImpl(MethodImplOptions.AggressiveInlining)]
74    protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].RightAsSource;

75
76    /// <summary>
77    /// <para>
78    /// Gets the left using the specified node.
79    /// </para>
80    /// </para></summary>
81    /// </summary>
82    /// <param name="node">
83    /// <para>The node.</para>
84    /// </para></param>
85    /// </param>
86    /// <returns>
87    /// <para>The link</para>
88    /// </para></returns>
89    /// </returns>
90    [MethodImpl(MethodImplOptions.AggressiveInlining)]
91    protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ LinksIndexParts[node].LeftAsSource;

92
93    /// <summary>
94    /// <para>
95    /// Gets the right using the specified node.
96    /// </para>
97    /// </para></summary>
98    /// </summary>
99    /// <param name="node">
100    /// <para>The node.</para>
101    /// </para></param>

```

```

102     /// </param>
103     /// <returns>
104     /// <para>The link</para>
105     /// <para></para>
106     /// </returns>
107     [MethodImpl(MethodImplOptions.AggressiveInlining)]
108     protected override TLinkAddress GetRight(TLinkAddress node) =>
109         ↪ LinksIndexParts[node].RightAsSource;
110
111     /// <summary>
112     /// <para>
113     /// Sets the left using the specified node.
114     /// </para>
115     /// <para></para>
116     /// </summary>
117     /// <param name="node">
118     /// <para>The node.</para>
119     /// <para></para>
120     /// </param>
121     /// <param name="left">
122     /// <para>The left.</para>
123     /// <para></para>
124     /// </param>
125     [MethodImpl(MethodImplOptions.AggressiveInlining)]
126     protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
127         ↪ LinksIndexParts[node].LeftAsSource = left;
128
129     /// <summary>
130     /// <para>
131     /// Sets the right using the specified node.
132     /// </para>
133     /// <para></para>
134     /// </summary>
135     /// <param name="node">
136     /// <para>The node.</para>
137     /// <para></para>
138     /// </param>
139     /// <param name="right">
140     /// <para>The right.</para>
141     /// <para></para>
142     /// </param>
143     [MethodImpl(MethodImplOptions.AggressiveInlining)]
144     protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
145         ↪ LinksIndexParts[node].RightAsSource = right;
146
147     /// <summary>
148     /// <para>
149     /// Gets the size using the specified node.
150     /// </para>
151     /// <para></para>
152     /// </summary>
153     /// <param name="node">
154     /// <para>The node.</para>
155     /// <para></para>
156     /// </param>
157     /// <returns>
158     /// <para>The link</para>
159     /// <para></para>
160     /// </returns>
161     [MethodImpl(MethodImplOptions.AggressiveInlining)]
162     protected override TLinkAddress GetSize(TLinkAddress node) =>
163         ↪ LinksIndexParts[node].SizeAsSource;
164
165     /// <summary>
166     /// <para>
167     /// Sets the size using the specified node.
168     /// </para>
169     /// <para></para>
170     /// </summary>
171     /// <param name="node">
172     /// <para>The node.</para>
173     /// <para></para>
174     /// </param>
175     /// <param name="size">
176     /// <para>The size.</para>
177     /// <para></para>
178     /// </param>
179     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

176 protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
177     ↳ LinksIndexParts[node].SizeAsSource = size;
178
179 /// <summary>
180 /// <para>
181 /// Gets the tree root.
182 /// </para>
183 /// <para></para>
184 /// </summary>
185 /// <returns>
186 /// <para>The link</para>
187 /// <para></para>
188 /// </returns>
189 [MethodImpl(MethodImplOptions.AggressiveInlining)]
190 protected override TLinkAddress GetTreeRoot() => Header->RootAsSource;
191
192 /// <summary>
193 /// <para>
194 /// Gets the base part value using the specified node.
195 /// </para>
196 /// <para></para>
197 /// </summary>
198 /// <param name="node">
199 /// <para>The node.</para>
200 /// <para></para>
201 /// </param>
202 /// <returns>
203 /// <para>The link</para>
204 /// <para></para>
205 /// </returns>
206 [MethodImpl(MethodImplOptions.AggressiveInlining)]
207 protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
208     ↳ LinksDataParts[node].Source;
209
210 /// <summary>
211 /// <para>
212 /// Determines whether this instance first is to the left of second.
213 /// </para>
214 /// <para></para>
215 /// </summary>
216 /// <param name="firstSource">
217 /// <para>The first source.</para>
218 /// <para></para>
219 /// </param>
220 /// <param name="firstTarget">
221 /// <para>The first target.</para>
222 /// <para></para>
223 /// </param>
224 /// <param name="secondSource">
225 /// <para>The second source.</para>
226 /// <para></para>
227 /// </param>
228 /// <param name="secondTarget">
229 /// <para>The second target.</para>
230 /// <para></para>
231 /// </param>
232 /// <returns>
233 /// <para>The bool</para>
234 /// <para></para>
235 /// </returns>
236 [MethodImpl(MethodImplOptions.AggressiveInlining)]
237 protected override bool FirstIsToTheLeftOfSecond(TLinkAddress firstSource, TLinkAddress
238     ↳ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
239     => firstSource < secondSource || firstSource == secondSource && firstTarget <
240     ↳ secondTarget;
241
242 /// <summary>
243 /// <para>
244 /// Determines whether this instance first is to the right of second.
245 /// </para>
246 /// <para></para>
247 /// </summary>
248 /// <param name="firstSource">
249 /// <para>The first source.</para>
250 /// <para></para>
251 /// </param>
252 /// <param name="firstTarget">
253 /// <para>The first target.</para>
254 /// <para></para>
255 /// </param>
256 /// <param name="secondSource">
257 /// <para>The second source.</para>
258 /// <para></para>
259 /// </param>
260 /// <param name="secondTarget">
261 /// <para>The second target.</para>
262 /// <para></para>
263 /// </param>
264 /// <returns>
265 /// <para>The bool</para>
266 /// <para></para>
267 /// </returns>
268 [MethodImpl(MethodImplOptions.AggressiveInlining)]
269 protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
270     ↳ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
271     => firstSource > secondSource || firstSource == secondSource && firstTarget >
272     ↳ secondTarget;

```



```

250     /// <para></para>
251     /// </param>
252     /// <param name="secondSource">
253     /// <para>The second source.</para>
254     /// <para></para>
255     /// </param>
256     /// <param name="secondTarget">
257     /// <para>The second target.</para>
258     /// <para></para>
259     /// </param>
260     /// <returns>
261     /// <para>The bool</para>
262     /// <para></para>
263     /// </returns>
264     [MethodImpl(MethodImplOptions.AggressiveInlining)]
265     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
        ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
266         => firstSource > secondSource || firstSource == secondSource && firstTarget >
        ↪ secondTarget;
267
268     /// <summary>
269     /// <para>
270     /// Clears the node using the specified node.
271     /// </para>
272     /// <para></para>
273     /// </summary>
274     /// <param name="node">
275     /// <para>The node.</para>
276     /// <para></para>
277     /// </param>
278     [MethodImpl(MethodImplOptions.AggressiveInlining)]
279     protected override void ClearNode(TLinkAddress node)
280     {
281         ref var link = ref LinksIndexParts[node];
282         link.LeftAsSource = Zero;
283         link.RightAsSource = Zero;
284         link.SizeAsSource = Zero;
285     }
286 }
287 }

```

1.68 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksSourcesSizeBalancedTreeMethods

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt64;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 64 external links sources size balanced tree methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="UInt64ExternalLinksSizeBalancedTreeMethodsBase"/>
15     public unsafe class UInt64ExternalLinksSourcesSizeBalancedTreeMethods :
        ↪ UInt64ExternalLinksSizeBalancedTreeMethodsBase
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see cref="UInt64ExternalLinksSourcesSizeBalancedTreeMethods"/>
        ↪ instance.
20         /// </para>
21         /// <para></para>
22         /// </summary>
23         /// <param name="constants">
24         /// <para>A constants.</para>
25         /// <para></para>
26         /// </param>
27         /// <param name="linksDataParts">
28         /// <para>A links data parts.</para>
29         /// <para></para>
30         /// </param>
31         /// <param name="linksIndexParts">
32         /// <para>A links index parts.</para>
33         /// <para></para>
34         /// </param>

```

```

35    /// <param name="header">
36    /// <para>A header.</para>
37    /// <para></para>
38    /// </param>
39    [MethodImpl(MethodImplOptions.AggressiveInlining)]
40    public UInt64ExternalLinksSourcesSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
    ↪ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
    ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
    ↪ : base(constants, linksDataParts, linksIndexParts, header) { }

41
42    /// <summary>
43    /// <para>
44    /// Gets the left reference using the specified node.
45    /// </para>
46    /// <para></para>
47    /// </summary>
48    /// <param name="node">
49    /// <para>The node.</para>
50    /// <para></para>
51    /// </param>
52    /// <returns>
53    /// <para>The ref link</para>
54    /// <para></para>
55    /// </returns>
56    [MethodImpl(MethodImplOptions.AggressiveInlining)]
57    protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].LeftAsSource;

58
59    /// <summary>
60    /// <para>
61    /// Gets the right reference using the specified node.
62    /// </para>
63    /// <para></para>
64    /// </summary>
65    /// <param name="node">
66    /// <para>The node.</para>
67    /// <para></para>
68    /// </param>
69    /// <returns>
70    /// <para>The ref link</para>
71    /// <para></para>
72    /// </returns>
73    [MethodImpl(MethodImplOptions.AggressiveInlining)]
74    protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].RightAsSource;

75
76    /// <summary>
77    /// <para>
78    /// Gets the left using the specified node.
79    /// </para>
80    /// <para></para>
81    /// </summary>
82    /// <param name="node">
83    /// <para>The node.</para>
84    /// <para></para>
85    /// </param>
86    /// <returns>
87    /// <para>The link</para>
88    /// <para></para>
89    /// </returns>
90    [MethodImpl(MethodImplOptions.AggressiveInlining)]
91    protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ LinksIndexParts[node].LeftAsSource;

92
93    /// <summary>
94    /// <para>
95    /// Gets the right using the specified node.
96    /// </para>
97    /// <para></para>
98    /// </summary>
99    /// <param name="node">
100    /// <para>The node.</para>
101    /// <para></para>
102    /// </param>
103    /// <returns>
104    /// <para>The link</para>
105    /// <para></para>
106    /// </returns>

```

```

107 [MethodImpl(MethodImplOptions.AggressiveInlining)]
108 protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↳ LinksIndexParts[node].RightAsSource;

109
110 /// <summary>
111 /// <para>
112 /// Sets the left using the specified node.
113 /// </para>
114 /// <para></para>
115 /// </summary>
116 /// <param name="node">
117 /// <para>The node.</para>
118 /// <para></para>
119 /// </param>
120 /// <param name="left">
121 /// <para>The left.</para>
122 /// <para></para>
123 /// </param>
124 [MethodImpl(MethodImplOptions.AggressiveInlining)]
125 protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
    ↳ LinksIndexParts[node].LeftAsSource = left;

126
127 /// <summary>
128 /// <para>
129 /// Sets the right using the specified node.
130 /// </para>
131 /// <para></para>
132 /// </summary>
133 /// <param name="node">
134 /// <para>The node.</para>
135 /// <para></para>
136 /// </param>
137 /// <param name="right">
138 /// <para>The right.</para>
139 /// <para></para>
140 /// </param>
141 [MethodImpl(MethodImplOptions.AggressiveInlining)]
142 protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
    ↳ LinksIndexParts[node].RightAsSource = right;

143
144 /// <summary>
145 /// <para>
146 /// Gets the size using the specified node.
147 /// </para>
148 /// <para></para>
149 /// </summary>
150 /// <param name="node">
151 /// <para>The node.</para>
152 /// <para></para>
153 /// </param>
154 /// <returns>
155 /// <para>The link</para>
156 /// <para></para>
157 /// </returns>
158 [MethodImpl(MethodImplOptions.AggressiveInlining)]
159 protected override TLinkAddress GetSize(TLinkAddress node) =>
    ↳ LinksIndexParts[node].SizeAsSource;

160
161 /// <summary>
162 /// <para>
163 /// Sets the size using the specified node.
164 /// </para>
165 /// <para></para>
166 /// </summary>
167 /// <param name="node">
168 /// <para>The node.</para>
169 /// <para></para>
170 /// </param>
171 /// <param name="size">
172 /// <para>The size.</para>
173 /// <para></para>
174 /// </param>
175 [MethodImpl(MethodImplOptions.AggressiveInlining)]
176 protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
    ↳ LinksIndexParts[node].SizeAsSource = size;

177
178 /// <summary>

```

```

179    /// <para>
180    /// Gets the tree root.
181    /// </para>
182    /// <para></para>
183    /// </summary>
184    /// <returns>
185    /// <para>The link</para>
186    /// <para></para>
187    /// </returns>
188    [MethodImpl(MethodImplOptions.AggressiveInlining)]
189    protected override TLinkAddress GetTreeRoot() => Header->RootAsSource;
190
191    /// <summary>
192    /// <para>
193    /// Gets the base part value using the specified node.
194    /// </para>
195    /// <para></para>
196    /// </summary>
197    /// <param name="node">
198    /// <para>The node.</para>
199    /// <para></para>
200    /// </param>
201    /// <returns>
202    /// <para>The link</para>
203    /// <para></para>
204    /// </returns>
205    [MethodImpl(MethodImplOptions.AggressiveInlining)]
206    protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
207        ↳ LinksDataParts[node].Source;
208
209    /// <summary>
210    /// <para>
211    /// Determines whether this instance first is to the left of second.
212    /// </para>
213    /// <para></para>
214    /// </summary>
215    /// <param name="firstSource">
216    /// <para>The first source.</para>
217    /// <para></para>
218    /// </param>
219    /// <param name="firstTarget">
220    /// <para>The first target.</para>
221    /// <para></para>
222    /// </param>
223    /// <param name="secondSource">
224    /// <para>The second source.</para>
225    /// <para></para>
226    /// </param>
227    /// <param name="secondTarget">
228    /// <para>The second target.</para>
229    /// <para></para>
230    /// </param>
231    /// <returns>
232    /// <para>The bool</para>
233    /// <para></para>
234    /// </returns>
235    [MethodImpl(MethodImplOptions.AggressiveInlining)]
236    protected override bool FirstIsToTheLeftOfSecond(TLinkAddress firstSource, TLinkAddress
237        ↳ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
238        => firstSource < secondSource || firstSource == secondSource && firstTarget <
239        ↳ secondTarget;
240
241    /// <summary>
242    /// <para>
243    /// Determines whether this instance first is to the right of second.
244    /// </para>
245    /// <para></para>
246    /// </summary>
247    /// <param name="firstSource">
248    /// <para>The first source.</para>
249    /// <para></para>
250    /// </param>
251    /// <param name="firstTarget">
252    /// <para>The first target.</para>
253    /// <para></para>
254    /// </param>
255    /// <param name="secondSource">
256    /// <para>The second source.</para>
257    /// <para></para>
258    /// </param>
259    /// <returns>
260    /// <para>The bool</para>
261    /// <para></para>
262    /// </returns>
263    [MethodImpl(MethodImplOptions.AggressiveInlining)]
264    protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
265        ↳ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
266        => firstSource > secondSource || firstSource == secondSource && firstTarget >
267        ↳ secondTarget;

```

```

254     /// <para></para>
255     /// </param>
256     /// <param name="secondTarget">
257     /// <para>The second target.</para>
258     /// <para></para>
259     /// </param>
260     /// <returns>
261     /// <para>The bool</para>
262     /// <para></para>
263     /// </returns>
264     [MethodImpl(MethodImplOptions.AggressiveInlining)]
265     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
        ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
266         => firstSource > secondSource || firstSource == secondSource && firstTarget >
        ↪ secondTarget;
267
268     /// <summary>
269     /// <para>
270     /// Clears the node using the specified node.
271     /// </para>
272     /// <para></para>
273     /// </summary>
274     /// <param name="node">
275     /// <para>The node.</para>
276     /// <para></para>
277     /// </param>
278     [MethodImpl(MethodImplOptions.AggressiveInlining)]
279     protected override void ClearNode(TLinkAddress node)
280     {
281         ref var link = ref LinksIndexParts[node];
282         link.LeftAsSource = Zero;
283         link.RightAsSource = Zero;
284         link.SizeAsSource = Zero;
285     }
286 }
287 }

```

1.69 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksTargetsRecursionlessSizeBalancedTreeMethodsBase

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt64;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 64 external links targets recursionless size balanced tree methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="UInt64ExternalLinksRecursionlessSizeBalancedTreeMethodsBase"/>
15     public unsafe class UInt64ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods :
        ↪ UInt64ExternalLinksRecursionlessSizeBalancedTreeMethodsBase
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see
        ↪ cref="UInt64ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods"/> instance.
20         /// </para>
21         /// <para></para>
22         /// </summary>
23         /// <param name="constants">
24         /// <para>A constants.</para>
25         /// <para></para>
26         /// </param>
27         /// <param name="linksDataParts">
28         /// <para>A links data parts.</para>
29         /// <para></para>
30         /// </param>
31         /// <param name="linksIndexParts">
32         /// <para>A links index parts.</para>
33         /// <para></para>
34         /// </param>
35         /// <param name="header">
36         /// <para>A header.</para>
37         /// <para></para>
38         /// </param>

```

```

39 [MethodImpl(MethodImplOptions.AggressiveInlining)]
40 public UInt64ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods(LinksConstants<TLi
    ↳ nkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
    ↳ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
    ↳ : base(constants, linksDataParts, linksIndexParts, header) { }

41
42 /// <summary>
43 /// <para>
44 /// Gets the left reference using the specified node.
45 /// </para>
46 /// <para></para>
47 /// </summary>
48 /// <param name="node">
49 /// <para>The node.</para>
50 /// <para></para>
51 /// </param>
52 /// <returns>
53 /// <para>The ref link</para>
54 /// <para></para>
55 /// </returns>
56 [MethodImpl(MethodImplOptions.AggressiveInlining)]
57 protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↳ LinksIndexParts[node].LeftAsTarget;

58
59 /// <summary>
60 /// <para>
61 /// Gets the right reference using the specified node.
62 /// </para>
63 /// <para></para>
64 /// </summary>
65 /// <param name="node">
66 /// <para>The node.</para>
67 /// <para></para>
68 /// </param>
69 /// <returns>
70 /// <para>The ref link</para>
71 /// <para></para>
72 /// </returns>
73 [MethodImpl(MethodImplOptions.AggressiveInlining)]
74 protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↳ LinksIndexParts[node].RightAsTarget;

75
76 /// <summary>
77 /// <para>
78 /// Gets the left using the specified node.
79 /// </para>
80 /// <para></para>
81 /// </summary>
82 /// <param name="node">
83 /// <para>The node.</para>
84 /// <para></para>
85 /// </param>
86 /// <returns>
87 /// <para>The link</para>
88 /// <para></para>
89 /// </returns>
90 [MethodImpl(MethodImplOptions.AggressiveInlining)]
91 protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↳ LinksIndexParts[node].LeftAsTarget;

92
93 /// <summary>
94 /// <para>
95 /// Gets the right using the specified node.
96 /// </para>
97 /// <para></para>
98 /// </summary>
99 /// <param name="node">
100 /// <para>The node.</para>
101 /// <para></para>
102 /// </param>
103 /// <returns>
104 /// <para>The link</para>
105 /// <para></para>
106 /// </returns>
107 [MethodImpl(MethodImplOptions.AggressiveInlining)]
108 protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↳ LinksIndexParts[node].RightAsTarget;

```

```

110    /// <summary>
111    /// <para>
112    /// Sets the left using the specified node.
113    /// </para>
114    /// <para></para>
115    /// </summary>
116    /// <param name="node">
117    /// <para>The node.</para>
118    /// <para></para>
119    /// </param>
120    /// <param name="left">
121    /// <para>The left.</para>
122    /// <para></para>
123    /// </param>
124    [MethodImpl(MethodImplOptions.AggressiveInlining)]
125    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
126        ↪ LinksIndexParts[node].LeftAsTarget = left;
127
128    /// <summary>
129    /// <para>
130    /// Sets the right using the specified node.
131    /// </para>
132    /// <para></para>
133    /// </summary>
134    /// <param name="node">
135    /// <para>The node.</para>
136    /// <para></para>
137    /// </param>
138    /// <param name="right">
139    /// <para>The right.</para>
140    /// <para></para>
141    /// </param>
142    [MethodImpl(MethodImplOptions.AggressiveInlining)]
143    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
144        ↪ LinksIndexParts[node].RightAsTarget = right;
145
146    /// <summary>
147    /// <para>
148    /// Gets the size using the specified node.
149    /// </para>
150    /// <para></para>
151    /// </summary>
152    /// <param name="node">
153    /// <para>The node.</para>
154    /// <para></para>
155    /// </param>
156    /// <returns>
157    /// <para>The link</para>
158    /// <para></para>
159    /// </returns>
160    [MethodImpl(MethodImplOptions.AggressiveInlining)]
161    protected override TLinkAddress GetSize(TLinkAddress node) =>
162        ↪ LinksIndexParts[node].SizeAsTarget;
163
164    /// <summary>
165    /// <para>
166    /// Sets the size using the specified node.
167    /// </para>
168    /// <para></para>
169    /// </summary>
170    /// <param name="node">
171    /// <para>The node.</para>
172    /// <para></para>
173    /// </param>
174    /// <param name="size">
175    /// <para>The size.</para>
176    /// <para></para>
177    /// </param>
178    [MethodImpl(MethodImplOptions.AggressiveInlining)]
179    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
180        ↪ LinksIndexParts[node].SizeAsTarget = size;
181
182    /// <summary>
183    /// <para>
184    /// Gets the tree root.
185    /// </para>
186    /// <para></para>
187    /// </summary>

```

```

184    /// <returns>
185    /// <para>The link</para>
186    /// <para></para>
187    /// </returns>
188    [MethodImpl(MethodImplOptions.AggressiveInlining)]
189    protected override TLinkAddress GetTreeRoot() => Header->RootAsTarget;
190
191    /// <summary>
192    /// <para>
193    /// Gets the base part value using the specified node.
194    /// </para>
195    /// <para></para>
196    /// </summary>
197    /// <param name="node">
198    /// <para>The node.</para>
199    /// <para></para>
200    /// </param>
201    /// <returns>
202    /// <para>The link</para>
203    /// <para></para>
204    /// </returns>
205    [MethodImpl(MethodImplOptions.AggressiveInlining)]
206    protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
207        ↳ LinksDataParts[node].Target;
208
209    /// <summary>
210    /// <para>
211    /// Determines whether this instance first is to the left of second.
212    /// </para>
213    /// <para></para>
214    /// </summary>
215    /// <param name="firstSource">
216    /// <para>The first source.</para>
217    /// <para></para>
218    /// </param>
219    /// <param name="firstTarget">
220    /// <para>The first target.</para>
221    /// <para></para>
222    /// </param>
223    /// <param name="secondSource">
224    /// <para>The second source.</para>
225    /// <para></para>
226    /// </param>
227    /// <param name="secondTarget">
228    /// <para>The second target.</para>
229    /// <para></para>
230    /// </param>
231    /// <returns>
232    /// <para>The bool</para>
233    /// <para></para>
234    /// </returns>
235    [MethodImpl(MethodImplOptions.AggressiveInlining)]
236    protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
237        ↳ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
238        => firstTarget < secondTarget || firstTarget == secondTarget && firstSource <
239        ↳ secondSource;
240
241    /// <summary>
242    /// <para>
243    /// Determines whether this instance first is to the right of second.
244    /// </para>
245    /// <para></para>
246    /// </summary>
247    /// <param name="firstSource">
248    /// <para>The first source.</para>
249    /// <para></para>
250    /// </param>
251    /// <param name="firstTarget">
252    /// <para>The first target.</para>
253    /// <para></para>
254    /// </param>
255    /// <param name="secondSource">
256    /// <para>The second source.</para>
257    /// <para></para>
258    /// </param>
259    /// <param name="secondTarget">
260    /// <para>The second target.</para>
261    /// <para></para>
262    /// </param>
263    /// <returns>
264    /// <para>The bool</para>
265    /// <para></para>
266    /// </returns>
267    [MethodImpl(MethodImplOptions.AggressiveInlining)]
268    protected override bool FirstIsToRightOfSecond(TLinkAddress firstSource, TLinkAddress
269        ↳ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
270        => firstTarget > secondTarget || firstTarget == secondTarget && firstSource >
271        ↳ secondSource;

```



```

259     /// </param>
260     /// <returns>
261     /// <para>The bool</para>
262     /// <para></para>
263     /// </returns>
264     [MethodImpl(MethodImplOptions.AggressiveInlining)]
265     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
    ↪ => firstTarget > secondTarget || firstTarget == secondTarget && firstSource >
    ↪ secondSource;
267
268     /// <summary>
269     /// <para>
270     /// Clears the node using the specified node.
271     /// </para>
272     /// <para></para>
273     /// </summary>
274     /// <param name="node">
275     /// <para>The node.</para>
276     /// <para></para>
277     /// </param>
278     [MethodImpl(MethodImplOptions.AggressiveInlining)]
279     protected override void ClearNode(TLinkAddress node)
280     {
281         ref var link = ref LinksIndexParts[node];
282         link.LeftAsTarget = Zero;
283         link.RightAsTarget = Zero;
284         link.SizeAsTarget = Zero;
285     }
286 }
287 }

```

1.70 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksTargetsSizeBalancedTreeMethods

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt64;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 64 external links targets size balanced tree methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="UInt64ExternalLinksSizeBalancedTreeMethodsBase"/>
15     public unsafe class UInt64ExternalLinksTargetsSizeBalancedTreeMethods :
    ↪ UInt64ExternalLinksSizeBalancedTreeMethodsBase
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see cref="UInt64ExternalLinksTargetsSizeBalancedTreeMethods"/>
    ↪ instance.
20         /// </para>
21         /// <para></para>
22         /// </summary>
23         /// <param name="constants">
24         /// <para>A constants.</para>
25         /// <para></para>
26         /// </param>
27         /// <param name="linksDataParts">
28         /// <para>A links data parts.</para>
29         /// <para></para>
30         /// </param>
31         /// <param name="linksIndexParts">
32         /// <para>A links index parts.</para>
33         /// <para></para>
34         /// </param>
35         /// <param name="header">
36         /// <para>A header.</para>
37         /// <para></para>
38         /// </param>
39         [MethodImpl(MethodImplOptions.AggressiveInlining)]
40         public UInt64ExternalLinksTargetsSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
    ↪ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
    ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
    ↪ : base(constants, linksDataParts, linksIndexParts, header) { }
41

```

```

42    /// <summary>
43    /// <para>
44    /// Gets the left reference using the specified node.
45    /// </para>
46    /// <para></para>
47    /// </summary>
48    /// <param name="node">
49    /// <para>The node.</para>
50    /// <para></para>
51    /// </param>
52    /// <returns>
53    /// <para>The ref link</para>
54    /// <para></para>
55    /// </returns>
56    [MethodImpl(MethodImplOptions.AggressiveInlining)]
57    protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].LeftAsTarget;
58
59    /// <summary>
60    /// <para>
61    /// Gets the right reference using the specified node.
62    /// </para>
63    /// <para></para>
64    /// </summary>
65    /// <param name="node">
66    /// <para>The node.</para>
67    /// <para></para>
68    /// </param>
69    /// <returns>
70    /// <para>The ref link</para>
71    /// <para></para>
72    /// </returns>
73    [MethodImpl(MethodImplOptions.AggressiveInlining)]
74    protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].RightAsTarget;
75
76    /// <summary>
77    /// <para>
78    /// Gets the left using the specified node.
79    /// </para>
80    /// <para></para>
81    /// </summary>
82    /// <param name="node">
83    /// <para>The node.</para>
84    /// <para></para>
85    /// </param>
86    /// <returns>
87    /// <para>The link</para>
88    /// <para></para>
89    /// </returns>
90    [MethodImpl(MethodImplOptions.AggressiveInlining)]
91    protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ LinksIndexParts[node].LeftAsTarget;
92
93    /// <summary>
94    /// <para>
95    /// Gets the right using the specified node.
96    /// </para>
97    /// <para></para>
98    /// </summary>
99    /// <param name="node">
100    /// <para>The node.</para>
101    /// <para></para>
102    /// </param>
103    /// <returns>
104    /// <para>The link</para>
105    /// <para></para>
106    /// </returns>
107    [MethodImpl(MethodImplOptions.AggressiveInlining)]
108    protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↪ LinksIndexParts[node].RightAsTarget;
109
110    /// <summary>
111    /// <para>
112    /// Sets the left using the specified node.
113    /// </para>
114    /// <para></para>
115    /// </summary>

```

```

116    /// <param name="node">
117    /// <para>The node.</para>
118    /// <para></para>
119    /// </param>
120    /// <param name="left">
121    /// <para>The left.</para>
122    /// <para></para>
123    /// </param>
124    [MethodImpl(MethodImplOptions.AggressiveInlining)]
125    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
126        ↪ LinksIndexParts[node].LeftAsTarget = left;
127
128    /// <summary>
129    /// <para>
130    /// Sets the right using the specified node.
131    /// </para>
132    /// <para></para>
133    /// </summary>
134    /// <param name="node">
135    /// <para>The node.</para>
136    /// <para></para>
137    /// </param>
138    /// <param name="right">
139    /// <para>The right.</para>
140    /// <para></para>
141    /// </param>
142    [MethodImpl(MethodImplOptions.AggressiveInlining)]
143    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
144        ↪ LinksIndexParts[node].RightAsTarget = right;
145
146    /// <summary>
147    /// <para>
148    /// Gets the size using the specified node.
149    /// </para>
150    /// <para></para>
151    /// </summary>
152    /// <param name="node">
153    /// <para>The node.</para>
154    /// <para></para>
155    /// </param>
156    /// <returns>
157    /// <para>The link</para>
158    /// <para></para>
159    /// </returns>
160    [MethodImpl(MethodImplOptions.AggressiveInlining)]
161    protected override TLinkAddress GetSize(TLinkAddress node) =>
162        ↪ LinksIndexParts[node].SizeAsTarget;
163
164    /// <summary>
165    /// <para>
166    /// Sets the size using the specified node.
167    /// </para>
168    /// <para></para>
169    /// </summary>
170    /// <param name="node">
171    /// <para>The node.</para>
172    /// <para></para>
173    /// </param>
174    /// <param name="size">
175    /// <para>The size.</para>
176    /// <para></para>
177    /// </param>
178    [MethodImpl(MethodImplOptions.AggressiveInlining)]
179    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
180        ↪ LinksIndexParts[node].SizeAsTarget = size;
181
182    /// <summary>
183    /// <para>
184    /// Gets the tree root.
185    /// </para>
186    /// <para></para>
187    /// </summary>
188    /// <returns>
189    /// <para>The link</para>
190    /// <para></para>
191    /// </returns>
192    [MethodImpl(MethodImplOptions.AggressiveInlining)]
193    protected override TLinkAddress GetTreeRoot() => Header->RootAsTarget;

```

```

190
191    /// <summary>
192    /// <para>
193    /// Gets the base part value using the specified node.
194    /// </para>
195    /// <para></para>
196    /// </summary>
197    /// <param name="node">
198    /// <para>The node.</para>
199    /// <para></para>
200    /// </param>
201    /// <returns>
202    /// <para>The link</para>
203    /// <para></para>
204    /// </returns>
205    [MethodImpl(MethodImplOptions.AggressiveInlining)]
206    protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
207        ↪ LinksDataParts[node].Target;
208
209    /// <summary>
210    /// <para>
211    /// Determines whether this instance first is to the left of second.
212    /// </para>
213    /// <para></para>
214    /// </summary>
215    /// <param name="firstSource">
216    /// <para>The first source.</para>
217    /// <para></para>
218    /// </param>
219    /// <param name="firstTarget">
220    /// <para>The first target.</para>
221    /// <para></para>
222    /// </param>
223    /// <param name="secondSource">
224    /// <para>The second source.</para>
225    /// <para></para>
226    /// </param>
227    /// <param name="secondTarget">
228    /// <para>The second target.</para>
229    /// <para></para>
230    /// </param>
231    /// <returns>
232    /// <para>The bool</para>
233    /// <para></para>
234    /// </returns>
235    [MethodImpl(MethodImplOptions.AggressiveInlining)]
236    protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
237        ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
238        => firstTarget < secondTarget || firstTarget == secondTarget && firstSource <
239        ↪ secondSource;
240
241    /// <summary>
242    /// <para>
243    /// Determines whether this instance first is to the right of second.
244    /// </para>
245    /// <para></para>
246    /// </summary>
247    /// <param name="firstSource">
248    /// <para>The first source.</para>
249    /// <para></para>
250    /// </param>
251    /// <param name="firstTarget">
252    /// <para>The first target.</para>
253    /// <para></para>
254    /// </param>
255    /// <param name="secondSource">
256    /// <para>The second source.</para>
257    /// <para></para>
258    /// </param>
259    /// <param name="secondTarget">
260    /// <para>The second target.</para>
261    /// <para></para>
262    /// </param>
263    /// <returns>
264    /// <para>The bool</para>
265    /// <para></para>
266    /// </returns>
267    [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

265         protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
        ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget)
266         => firstTarget > secondTarget || firstTarget == secondTarget && firstSource >
        ↪ secondSource;
267
268         /// <summary>
269         /// <para>
270         /// Clears the node using the specified node.
271         /// </para>
272         /// <para></para>
273         /// </summary>
274         /// <param name="node">
275         /// <para>The node.</para>
276         /// <para></para>
277         /// </param>
278         [MethodImpl(MethodImplOptions.AggressiveInlining)]
279         protected override void ClearNode(TLinkAddress node)
280         {
281             ref var link = ref LinksIndexParts[node];
282             link.LeftAsTarget = Zero;
283             link.RightAsTarget = Zero;
284             link.SizeAsTarget = Zero;
285         }
286     }
287 }

```

1.71 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksRecursionlessSizeBalancedTreeMethodsBase.cs

```

1 using System.Runtime.CompilerServices;
2 using Platform.Data.Doublets.Memory.Split.Generic;
3 using TLinkAddress = System.UInt64;
4
5 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7 namespace Platform.Data.Doublets.Memory.Split.Specific
8 {
9     /// <summary>
10    /// <para>
11    /// Represents the int 64 internal links recursionless size balanced tree methods base.
12    /// </para>
13    /// <para></para>
14    /// </summary>
15    /// <seealso cref="InternalLinksRecursionlessSizeBalancedTreeMethodsBase{TLinkAddress}"/>
16    public unsafe abstract class UInt64InternalLinksRecursionlessSizeBalancedTreeMethodsBase :
    ↪ InternalLinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress>
17    {
18        /// <summary>
19        /// <para>
20        /// The links data parts.
21        /// </para>
22        /// <para></para>
23        /// </summary>
24        protected new readonly RawLinkDataPart<TLinkAddress>* LinksDataParts;
25        /// <summary>
26        /// <para>
27        /// The links index parts.
28        /// </para>
29        /// <para></para>
30        /// </summary>
31        protected new readonly RawLinkIndexPart<TLinkAddress>* LinksIndexParts;
32        /// <summary>
33        /// <para>
34        /// The header.
35        /// </para>
36        /// <para></para>
37        /// </summary>
38        protected new readonly LinksHeader<TLinkAddress>* Header;
39
40        /// <summary>
41        /// <para>
42        /// Initializes a new <see
        ↪ cref="UInt64InternalLinksRecursionlessSizeBalancedTreeMethodsBase"/> instance.
43        /// </para>
44        /// <para></para>
45        /// </summary>
46        /// <param name="constants">
47        /// <para>A constants.</para>
48        /// <para></para>
49        /// </param>
50        /// <param name="linksDataParts">

```

```

51     /// <para>A links data parts.</para>
52     /// <para></para>
53     /// </param>
54     /// <param name="linksIndexParts">
55     /// <para>A links index parts.</para>
56     /// <para></para>
57     /// </param>
58     /// <param name="header">
59     /// <para>A header.</para>
60     /// <para></para>
61     /// </param>
62     [MethodImpl(MethodImplOptions.AggressiveInlining)]
63     protected UInt64InternalLinksRecursionlessSizeBalancedTreeMethodsBase(LinksConstants<TLi
    ↪ nkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
    ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
64         : base(constants, (byte*)linksDataParts, (byte*)linksIndexParts, (byte*)header)
65     {
66         LinksDataParts = linksDataParts;
67         LinksIndexParts = linksIndexParts;
68         Header = header;
69     }
70
71     /// <summary>
72     /// <para>
73     /// Gets the zero.
74     /// </para>
75     /// <para></para>
76     /// </summary>
77     /// <returns>
78     /// <para>The ulong</para>
79     /// <para></para>
80     /// </returns>
81     [MethodImpl(MethodImplOptions.AggressiveInlining)]
82     protected override ulong GetZero() => 0UL;
83
84     /// <summary>
85     /// <para>
86     /// Determines whether this instance equal to zero.
87     /// </para>
88     /// <para></para>
89     /// </summary>
90     /// <param name="value">
91     /// <para>The value.</para>
92     /// <para></para>
93     /// </param>
94     /// <returns>
95     /// <para>The bool</para>
96     /// <para></para>
97     /// </returns>
98     [MethodImpl(MethodImplOptions.AggressiveInlining)]
99     protected override bool EqualToZero(ulong value) => value == 0UL;
100
101     /// <summary>
102     /// <para>
103     /// Determines whether this instance are equal.
104     /// </para>
105     /// <para></para>
106     /// </summary>
107     /// <param name="first">
108     /// <para>The first.</para>
109     /// <para></para>
110     /// </param>
111     /// <param name="second">
112     /// <para>The second.</para>
113     /// <para></para>
114     /// </param>
115     /// <returns>
116     /// <para>The bool</para>
117     /// <para></para>
118     /// </returns>
119     [MethodImpl(MethodImplOptions.AggressiveInlining)]
120     protected override bool AreEqual(ulong first, ulong second) => first == second;
121
122     /// <summary>
123     /// <para>
124     /// Determines whether this instance greater than zero.
125     /// </para>
126     /// <para></para>

```

```

127     /// </summary>
128     /// <param name="value">
129     /// <para>The value.</para>
130     /// <para></para>
131     /// </param>
132     /// <returns>
133     /// <para>The bool</para>
134     /// <para></para>
135     /// </returns>
136     [MethodImpl(MethodImplOptions.AggressiveInlining)]
137     protected override bool GreaterThanZero(ulong value) => value > 0UL;
138
139     /// <summary>
140     /// <para>
141     /// Determines whether this instance greater than.
142     /// </para>
143     /// <para></para>
144     /// </summary>
145     /// <param name="first">
146     /// <para>The first.</para>
147     /// <para></para>
148     /// </param>
149     /// <param name="second">
150     /// <para>The second.</para>
151     /// <para></para>
152     /// </param>
153     /// <returns>
154     /// <para>The bool</para>
155     /// <para></para>
156     /// </returns>
157     [MethodImpl(MethodImplOptions.AggressiveInlining)]
158     protected override bool GreaterThan(ulong first, ulong second) => first > second;
159
160     /// <summary>
161     /// <para>
162     /// Determines whether this instance greater or equal than.
163     /// </para>
164     /// <para></para>
165     /// </summary>
166     /// <param name="first">
167     /// <para>The first.</para>
168     /// <para></para>
169     /// </param>
170     /// <param name="second">
171     /// <para>The second.</para>
172     /// <para></para>
173     /// </param>
174     /// <returns>
175     /// <para>The bool</para>
176     /// <para></para>
177     /// </returns>
178     [MethodImpl(MethodImplOptions.AggressiveInlining)]
179     protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;
180
181     /// <summary>
182     /// <para>
183     /// Determines whether this instance greater or equal than zero.
184     /// </para>
185     /// <para></para>
186     /// </summary>
187     /// <param name="value">
188     /// <para>The value.</para>
189     /// <para></para>
190     /// </param>
191     /// <returns>
192     /// <para>The bool</para>
193     /// <para></para>
194     /// </returns>
195     [MethodImpl(MethodImplOptions.AggressiveInlining)]
196     protected override bool GreaterOrEqualThanZero(ulong value) => true; // value >= 0 is
    ↪ always true for ulong
197
198     /// <summary>
199     /// <para>
200     /// Determines whether this instance less or equal than zero.
201     /// </para>
202     /// <para></para>
203     /// </summary>

```

```

204     /// <param name="value">
205     /// <para>The value.</para>
206     /// <para></para>
207     /// </param>
208     /// <returns>
209     /// <para>The bool</para>
210     /// <para></para>
211     /// </returns>
212     [MethodImpl(MethodImplOptions.AggressiveInlining)]
213     protected override bool LessOrEqualThanZero(ulong value) => value == 0UL; // value is
    ↪ always >= 0 for ulong
214
215     /// <summary>
216     /// <para>
217     /// Determines whether this instance less or equal than.
218     /// </para>
219     /// <para></para>
220     /// </summary>
221     /// <param name="first">
222     /// <para>The first.</para>
223     /// <para></para>
224     /// </param>
225     /// <param name="second">
226     /// <para>The second.</para>
227     /// <para></para>
228     /// </param>
229     /// <returns>
230     /// <para>The bool</para>
231     /// <para></para>
232     /// </returns>
233     [MethodImpl(MethodImplOptions.AggressiveInlining)]
234     protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;
235
236     /// <summary>
237     /// <para>
238     /// Determines whether this instance less than zero.
239     /// </para>
240     /// <para></para>
241     /// </summary>
242     /// <param name="value">
243     /// <para>The value.</para>
244     /// <para></para>
245     /// </param>
246     /// <returns>
247     /// <para>The bool</para>
248     /// <para></para>
249     /// </returns>
250     [MethodImpl(MethodImplOptions.AggressiveInlining)]
251     protected override bool LessThanZero(ulong value) => false; // value < 0 is always false
    ↪ for ulong
252
253     /// <summary>
254     /// <para>
255     /// Determines whether this instance less than.
256     /// </para>
257     /// <para></para>
258     /// </summary>
259     /// <param name="first">
260     /// <para>The first.</para>
261     /// <para></para>
262     /// </param>
263     /// <param name="second">
264     /// <para>The second.</para>
265     /// <para></para>
266     /// </param>
267     /// <returns>
268     /// <para>The bool</para>
269     /// <para></para>
270     /// </returns>
271     [MethodImpl(MethodImplOptions.AggressiveInlining)]
272     protected override bool LessThan(ulong first, ulong second) => first < second;
273
274     /// <summary>
275     /// <para>
276     /// Increments the value.
277     /// </para>
278     /// <para></para>
279     /// </summary>

```



```

280     /// <param name="value">
281     /// <para>The value.</para>
282     /// <para></para>
283     /// </param>
284     /// <returns>
285     /// <para>The ulong</para>
286     /// <para></para>
287     /// </returns>
288     [MethodImpl(MethodImplOptions.AggressiveInlining)]
289     protected override ulong Increment(ulong value) => ++value;
290
291     /// <summary>
292     /// <para>
293     /// Decrements the value.
294     /// </para>
295     /// <para></para>
296     /// </summary>
297     /// <param name="value">
298     /// <para>The value.</para>
299     /// <para></para>
300     /// </param>
301     /// <returns>
302     /// <para>The ulong</para>
303     /// <para></para>
304     /// </returns>
305     [MethodImpl(MethodImplOptions.AggressiveInlining)]
306     protected override ulong Decrement(ulong value) => --value;
307
308     /// <summary>
309     /// <para>
310     /// Adds the first.
311     /// </para>
312     /// <para></para>
313     /// </summary>
314     /// <param name="first">
315     /// <para>The first.</para>
316     /// <para></para>
317     /// </param>
318     /// <param name="second">
319     /// <para>The second.</para>
320     /// <para></para>
321     /// </param>
322     /// <returns>
323     /// <para>The ulong</para>
324     /// <para></para>
325     /// </returns>
326     [MethodImpl(MethodImplOptions.AggressiveInlining)]
327     protected override ulong Add(ulong first, ulong second) => first + second;
328
329     /// <summary>
330     /// <para>
331     /// Subtracts the first.
332     /// </para>
333     /// <para></para>
334     /// </summary>
335     /// <param name="first">
336     /// <para>The first.</para>
337     /// <para></para>
338     /// </param>
339     /// <param name="second">
340     /// <para>The second.</para>
341     /// <para></para>
342     /// </param>
343     /// <returns>
344     /// <para>The ulong</para>
345     /// <para></para>
346     /// </returns>
347     [MethodImpl(MethodImplOptions.AggressiveInlining)]
348     protected override ulong Subtract(ulong first, ulong second) => first - second;
349
350     /// <summary>
351     /// <para>
352     /// Gets the link data part reference using the specified link.
353     /// </para>
354     /// <para></para>
355     /// </summary>
356     /// <param name="link">
357     /// <para>The link.</para>

```

```

358     /// <para></para>
359     /// </param>
360     /// <returns>
361     /// <para>A ref raw link data part of t link</para>
362     /// <para></para>
363     /// </returns>
364     [MethodImpl(MethodImplOptions.AggressiveInlining)]
365     protected override ref RawLinkDataPart<TLinkAddress>
366     ↪ GetLinkDataPartReference(TLinkAddress link) => ref LinksDataParts[link];
367
368     /// <summary>
369     /// <para>
370     /// Gets the link index part reference using the specified link.
371     /// </para>
372     /// <para></para>
373     /// </summary>
374     /// <param name="link">
375     /// <para>The link.</para>
376     /// <para></para>
377     /// </param>
378     /// <returns>
379     /// <para>A ref raw link index part of t link</para>
380     /// <para></para>
381     /// </returns>
382     [MethodImpl(MethodImplOptions.AggressiveInlining)]
383     protected override ref RawLinkIndexPart<TLinkAddress>
384     ↪ GetLinkIndexPartReference(TLinkAddress link) => ref LinksIndexParts[link];
385
386     /// <summary>
387     /// <para>
388     /// Determines whether this instance first is to the left of second.
389     /// </para>
390     /// <para></para>
391     /// </summary>
392     /// <param name="first">
393     /// <para>The first.</para>
394     /// <para></para>
395     /// </param>
396     /// <param name="second">
397     /// <para>The second.</para>
398     /// <para></para>
399     /// </param>
400     /// <returns>
401     /// <para>The bool</para>
402     /// <para></para>
403     /// </returns>
404     [MethodImpl(MethodImplOptions.AggressiveInlining)]
405     protected override bool FirstIsToLeftOfSecond(TLinkAddress first, TLinkAddress
406     ↪ second) => GetKeyPartValue(first) < GetKeyPartValue(second);
407
408     /// <summary>
409     /// <para>
410     /// Determines whether this instance first is to the right of second.
411     /// </para>
412     /// <para></para>
413     /// </summary>
414     /// <param name="first">
415     /// <para>The first.</para>
416     /// <para></para>
417     /// </param>
418     /// <param name="second">
419     /// <para>The second.</para>
420     /// <para></para>
421     /// </param>
422     /// <returns>
423     /// <para>The bool</para>
424     /// <para></para>
425     /// </returns>
426     [MethodImpl(MethodImplOptions.AggressiveInlining)]
427     protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
428     ↪ second) => GetKeyPartValue(first) > GetKeyPartValue(second);
429 }

```

1.72 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksSizeBalancedTreeMethodsBase.

```

1 using System.Runtime.CompilerServices;
2 using Platform.Data.Doublets.Memory.Split.Generic;
3 using TLinkAddress = System.UInt64;

```

```

4
5 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7 namespace Platform.Data.Doublets.Memory.Split.Specific
8 {
9     /// <summary>
10    /// <para>
11    /// Represents the int 64 internal links size balanced tree methods base.
12    /// </para>
13    /// <para></para>
14    /// </summary>
15    /// <seealso cref="InternalLinksSizeBalancedTreeMethodsBase{TLinkAddress}"/>
16    public unsafe abstract class UInt64InternalLinksSizeBalancedTreeMethodsBase :
17        ↳ InternalLinksSizeBalancedTreeMethodsBase<TLinkAddress>
18    {
19        /// <summary>
20        /// <para>
21        /// The links data parts.
22        /// </para>
23        /// <para></para>
24        /// </summary>
25        protected new readonly RawLinkDataPart<TLinkAddress>* LinksDataParts;
26        /// <summary>
27        /// <para>
28        /// The links index parts.
29        /// </para>
30        /// <para></para>
31        /// </summary>
32        protected new readonly RawLinkIndexPart<TLinkAddress>* LinksIndexParts;
33        /// <summary>
34        /// <para>
35        /// The header.
36        /// </para>
37        /// <para></para>
38        /// </summary>
39        protected new readonly LinksHeader<TLinkAddress>* Header;
40
41        /// <summary>
42        /// <para>
43        /// Initializes a new <see cref="UInt64InternalLinksSizeBalancedTreeMethodsBase"/>
44        /// ↳ instance.
45        /// </para>
46        /// <para></para>
47        /// </summary>
48        /// <param name="constants">
49        /// <para>A constants.</para>
50        /// <para></para>
51        /// </param>
52        /// <param name="linksDataParts">
53        /// <para>A links data parts.</para>
54        /// <para></para>
55        /// </param>
56        /// <param name="linksIndexParts">
57        /// <para>A links index parts.</para>
58        /// <para></para>
59        /// </param>
60        /// <param name="header">
61        /// <para>A header.</para>
62        /// <para></para>
63        /// </param>
64        [MethodImpl(MethodImplOptions.AggressiveInlining)]
65        protected UInt64InternalLinksSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress>
66            ↳ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
67            ↳ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
68            : base(constants, (byte*)linksDataParts, (byte*)linksIndexParts, (byte*)header)
69        {
70            LinksDataParts = linksDataParts;
71            LinksIndexParts = linksIndexParts;
72            Header = header;
73        }
74
75        /// <summary>
76        /// <para>
77        /// Gets the zero.
78        /// </para>
79        /// <para></para>
80        /// </summary>
81        /// <returns>
82        /// <para>The ulong</para>

```

```

79     /// <para></para>
80     /// </returns>
81     [MethodImpl(MethodImplOptions.AggressiveInlining)]
82     protected override ulong GetZero() => OUL;
83
84     /// <summary>
85     /// <para>
86     /// Determines whether this instance equal to zero.
87     /// </para>
88     /// <para></para>
89     /// </summary>
90     /// <param name="value">
91     /// <para>The value.</para>
92     /// <para></para>
93     /// </param>
94     /// <returns>
95     /// <para>The bool</para>
96     /// <para></para>
97     /// </returns>
98     [MethodImpl(MethodImplOptions.AggressiveInlining)]
99     protected override bool EqualToZero(ulong value) => value == OUL;
100
101     /// <summary>
102     /// <para>
103     /// Determines whether this instance are equal.
104     /// </para>
105     /// <para></para>
106     /// </summary>
107     /// <param name="first">
108     /// <para>The first.</para>
109     /// <para></para>
110     /// </param>
111     /// <param name="second">
112     /// <para>The second.</para>
113     /// <para></para>
114     /// </param>
115     /// <returns>
116     /// <para>The bool</para>
117     /// <para></para>
118     /// </returns>
119     [MethodImpl(MethodImplOptions.AggressiveInlining)]
120     protected override bool AreEqual(ulong first, ulong second) => first == second;
121
122     /// <summary>
123     /// <para>
124     /// Determines whether this instance greater than zero.
125     /// </para>
126     /// <para></para>
127     /// </summary>
128     /// <param name="value">
129     /// <para>The value.</para>
130     /// <para></para>
131     /// </param>
132     /// <returns>
133     /// <para>The bool</para>
134     /// <para></para>
135     /// </returns>
136     [MethodImpl(MethodImplOptions.AggressiveInlining)]
137     protected override bool GreaterThanZero(ulong value) => value > OUL;
138
139     /// <summary>
140     /// <para>
141     /// Determines whether this instance greater than.
142     /// </para>
143     /// <para></para>
144     /// </summary>
145     /// <param name="first">
146     /// <para>The first.</para>
147     /// <para></para>
148     /// </param>
149     /// <param name="second">
150     /// <para>The second.</para>
151     /// <para></para>
152     /// </param>
153     /// <returns>
154     /// <para>The bool</para>
155     /// <para></para>
156     /// </returns>

```

```

157 [MethodImpl(MethodImplOptions.AggressiveInlining)]
158 protected override bool GreaterThan(ulong first, ulong second) => first > second;
159
160 /// <summary>
161 /// <para>
162 /// Determines whether this instance greater or equal than.
163 /// </para>
164 /// <para></para>
165 /// </summary>
166 /// <param name="first">
167 /// <para>The first.</para>
168 /// <para></para>
169 /// </param>
170 /// <param name="second">
171 /// <para>The second.</para>
172 /// <para></para>
173 /// </param>
174 /// <returns>
175 /// <para>The bool</para>
176 /// <para></para>
177 /// </returns>
178 [MethodImpl(MethodImplOptions.AggressiveInlining)]
179 protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;
180
181 /// <summary>
182 /// <para>
183 /// Determines whether this instance greater or equal than zero.
184 /// </para>
185 /// <para></para>
186 /// </summary>
187 /// <param name="value">
188 /// <para>The value.</para>
189 /// <para></para>
190 /// </param>
191 /// <returns>
192 /// <para>The bool</para>
193 /// <para></para>
194 /// </returns>
195 [MethodImpl(MethodImplOptions.AggressiveInlining)]
196 protected override bool GreaterOrEqualThanZero(ulong value) => true; // value >= 0 is
    ↳ always true for ulong
197
198 /// <summary>
199 /// <para>
200 /// Determines whether this instance less or equal than zero.
201 /// </para>
202 /// <para></para>
203 /// </summary>
204 /// <param name="value">
205 /// <para>The value.</para>
206 /// <para></para>
207 /// </param>
208 /// <returns>
209 /// <para>The bool</para>
210 /// <para></para>
211 /// </returns>
212 [MethodImpl(MethodImplOptions.AggressiveInlining)]
213 protected override bool LessOrEqualThanZero(ulong value) => value == 0UL; // value is
    ↳ always >= 0 for ulong
214
215 /// <summary>
216 /// <para>
217 /// Determines whether this instance less or equal than.
218 /// </para>
219 /// <para></para>
220 /// </summary>
221 /// <param name="first">
222 /// <para>The first.</para>
223 /// <para></para>
224 /// </param>
225 /// <param name="second">
226 /// <para>The second.</para>
227 /// <para></para>
228 /// </param>
229 /// <returns>
230 /// <para>The bool</para>
231 /// <para></para>
232 /// </returns>

```

```

233 [MethodImpl(MethodImplOptions.AggressiveInlining)]
234 protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;
235
236 /// <summary>
237 /// <para>
238 /// Determines whether this instance less than zero.
239 /// </para>
240 /// <para></para>
241 /// </summary>
242 /// <param name="value">
243 /// <para>The value.</para>
244 /// <para></para>
245 /// </param>
246 /// <returns>
247 /// <para>The bool</para>
248 /// <para></para>
249 /// </returns>
250 [MethodImpl(MethodImplOptions.AggressiveInlining)]
251 protected override bool LessThanZero(ulong value) => false; // value < 0 is always false
    ↳ for ulong
252
253 /// <summary>
254 /// <para>
255 /// Determines whether this instance less than.
256 /// </para>
257 /// <para></para>
258 /// </summary>
259 /// <param name="first">
260 /// <para>The first.</para>
261 /// <para></para>
262 /// </param>
263 /// <param name="second">
264 /// <para>The second.</para>
265 /// <para></para>
266 /// </param>
267 /// <returns>
268 /// <para>The bool</para>
269 /// <para></para>
270 /// </returns>
271 [MethodImpl(MethodImplOptions.AggressiveInlining)]
272 protected override bool LessThan(ulong first, ulong second) => first < second;
273
274 /// <summary>
275 /// <para>
276 /// Increments the value.
277 /// </para>
278 /// <para></para>
279 /// </summary>
280 /// <param name="value">
281 /// <para>The value.</para>
282 /// <para></para>
283 /// </param>
284 /// <returns>
285 /// <para>The ulong</para>
286 /// <para></para>
287 /// </returns>
288 [MethodImpl(MethodImplOptions.AggressiveInlining)]
289 protected override ulong Increment(ulong value) => ++value;
290
291 /// <summary>
292 /// <para>
293 /// Decrements the value.
294 /// </para>
295 /// <para></para>
296 /// </summary>
297 /// <param name="value">
298 /// <para>The value.</para>
299 /// <para></para>
300 /// </param>
301 /// <returns>
302 /// <para>The ulong</para>
303 /// <para></para>
304 /// </returns>
305 [MethodImpl(MethodImplOptions.AggressiveInlining)]
306 protected override ulong Decrement(ulong value) => --value;
307
308 /// <summary>
309 /// <para>

```

```

310    /// Adds the first.
311    /// </para>
312    /// <para></para>
313    /// </summary>
314    /// <param name="first">
315    /// <para>The first.</para>
316    /// <para></para>
317    /// </param>
318    /// <param name="second">
319    /// <para>The second.</para>
320    /// <para></para>
321    /// </param>
322    /// <returns>
323    /// <para>The ulong</para>
324    /// <para></para>
325    /// </returns>
326    [MethodImpl(MethodImplOptions.AggressiveInlining)]
327    protected override ulong Add(ulong first, ulong second) => first + second;
328
329    /// <summary>
330    /// <para>
331    /// Subtracts the first.
332    /// </para>
333    /// <para></para>
334    /// </summary>
335    /// <param name="first">
336    /// <para>The first.</para>
337    /// <para></para>
338    /// </param>
339    /// <param name="second">
340    /// <para>The second.</para>
341    /// <para></para>
342    /// </param>
343    /// <returns>
344    /// <para>The ulong</para>
345    /// <para></para>
346    /// </returns>
347    [MethodImpl(MethodImplOptions.AggressiveInlining)]
348    protected override ulong Subtract(ulong first, ulong second) => first - second;
349
350    /// <summary>
351    /// <para>
352    /// Gets the link data part reference using the specified link.
353    /// </para>
354    /// <para></para>
355    /// </summary>
356    /// <param name="link">
357    /// <para>The link.</para>
358    /// <para></para>
359    /// </param>
360    /// <returns>
361    /// <para>A ref raw link data part of t link</para>
362    /// <para></para>
363    /// </returns>
364    [MethodImpl(MethodImplOptions.AggressiveInlining)]
365    protected override ref RawLinkDataPart<TLinkAddress>
366    ↪ GetLinkDataPartReference(TLinkAddress link) => ref LinksDataParts[link];
367
368    /// <summary>
369    /// <para>
370    /// Gets the link index part reference using the specified link.
371    /// </para>
372    /// <para></para>
373    /// </summary>
374    /// <param name="link">
375    /// <para>The link.</para>
376    /// <para></para>
377    /// </param>
378    /// <returns>
379    /// <para>A ref raw link index part of t link</para>
380    /// <para></para>
381    /// </returns>
382    [MethodImpl(MethodImplOptions.AggressiveInlining)]
383    protected override ref RawLinkIndexPart<TLinkAddress>
384    ↪ GetLinkIndexPartReference(TLinkAddress link) => ref LinksIndexParts[link];
385
386    /// <summary>
387    /// <para>

```

```

386     /// Determines whether this instance first is to the left of second.
387     /// </para>
388     /// <para></para>
389     /// </summary>
390     /// <param name="first">
391     /// <para>The first.</para>
392     /// <para></para>
393     /// </param>
394     /// <param name="second">
395     /// <para>The second.</para>
396     /// <para></para>
397     /// </param>
398     /// <returns>
399     /// <para>The bool</para>
400     /// <para></para>
401     /// </returns>
402     [MethodImpl(MethodImplOptions.AggressiveInlining)]
403     protected override bool FirstIsToTheLeftOfSecond(TLinkAddress first, TLinkAddress
        ↪ second) => GetKeyPartValue(first) < GetKeyPartValue(second);
404
405     /// <summary>
406     /// <para>
407     /// Determines whether this instance first is to the right of second.
408     /// </para>
409     /// <para></para>
410     /// </summary>
411     /// <param name="first">
412     /// <para>The first.</para>
413     /// <para></para>
414     /// </param>
415     /// <param name="second">
416     /// <para>The second.</para>
417     /// <para></para>
418     /// </param>
419     /// <returns>
420     /// <para>The bool</para>
421     /// <para></para>
422     /// </returns>
423     [MethodImpl(MethodImplOptions.AggressiveInlining)]
424     protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
        ↪ second) => GetKeyPartValue(first) > GetKeyPartValue(second);
425 }
426 }

```

1.73 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksSourcesLinkedListMethods.cs

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt64;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Generic
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 64 internal links sources linked list methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="InternalLinksSourcesLinkedListMethods{TLinkAddress}"/>
15     public unsafe class UInt64InternalLinksSourcesLinkedListMethods :
        ↪ InternalLinksSourcesLinkedListMethods<TLinkAddress>
16     {
17         private readonly RawLinkDataPart<TLinkAddress>* _linksDataParts;
18         private readonly RawLinkIndexPart<TLinkAddress>* _linksIndexParts;
19
20         /// <summary>
21         /// <para>
22         /// Initializes a new <see cref="UInt64InternalLinksSourcesLinkedListMethods"/> instance.
23         /// </para>
24         /// <para></para>
25         /// </summary>
26         /// <param name="constants">
27         /// <para>A constants.</para>
28         /// <para></para>
29         /// </param>
30         /// <param name="linksDataParts">
31         /// <para>A links data parts.</para>
32         /// <para></para>

```



```

33     /// </param>
34     /// <param name="linksIndexParts">
35     /// <para>A links index parts.</para>
36     /// <para></para>
37     /// </param>
38     [MethodImpl(MethodImplOptions.AggressiveInlining)]
39     public UInt64InternalLinksSourcesLinkedListMethods(LinksConstants<TLinkAddress>
        ↳ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
        ↳ RawLinkIndexPart<TLinkAddress>* linksIndexParts)
40         : base(constants, (byte*)linksDataParts, (byte*)linksIndexParts)
41     {
42         _linksDataParts = linksDataParts;
43         _linksIndexParts = linksIndexParts;
44     }
45
46     /// <summary>
47     /// <para>
48     /// Gets the link data part reference using the specified link.
49     /// </para>
50     /// <para></para>
51     /// </summary>
52     /// <param name="link">
53     /// <para>The link.</para>
54     /// <para></para>
55     /// </param>
56     /// <returns>
57     /// <para>A ref raw link data part of t link</para>
58     /// <para></para>
59     /// </returns>
60     [MethodImpl(MethodImplOptions.AggressiveInlining)]
61     protected override ref RawLinkDataPart<TLinkAddress>
        ↳ GetLinkDataPartReference(TLinkAddress link) => ref _linksDataParts[link];
62
63     /// <summary>
64     /// <para>
65     /// Gets the link index part reference using the specified link.
66     /// </para>
67     /// <para></para>
68     /// </summary>
69     /// <param name="link">
70     /// <para>The link.</para>
71     /// <para></para>
72     /// </param>
73     /// <returns>
74     /// <para>A ref raw link index part of t link</para>
75     /// <para></para>
76     /// </returns>
77     [MethodImpl(MethodImplOptions.AggressiveInlining)]
78     protected override ref RawLinkIndexPart<TLinkAddress>
        ↳ GetLinkIndexPartReference(TLinkAddress link) => ref _linksIndexParts[link];
79 }
80 }

```

1.74 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksSourcesRecursionlessSizeBalancedTreeMethods

```

1 using System.Runtime.CompilerServices;
2 using TLinkAddress = System.UInt64;
3
4 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6 namespace Platform.Data.Doublets.Memory.Split.Specific
7 {
8     /// <summary>
9     /// <para>
10    /// Represents the int 64 internal links sources recursionless size balanced tree methods.
11    /// </para>
12    /// <para></para>
13    /// </summary>
14    /// <seealso cref="UInt64InternalLinksRecursionlessSizeBalancedTreeMethodsBase"/>
15    public unsafe class UInt64InternalLinksSourcesRecursionlessSizeBalancedTreeMethods :
        ↳ UInt64InternalLinksRecursionlessSizeBalancedTreeMethodsBase
16    {
17        /// <summary>
18        /// <para>
19        /// Initializes a new <see
        ↳ cref="UInt64InternalLinksSourcesRecursionlessSizeBalancedTreeMethods"/> instance.
20        /// </para>
21        /// <para></para>
22        /// </summary>

```

```

23     /// <param name="constants">
24     /// <para>A constants.</para>
25     /// <para></para>
26     /// </param>
27     /// <param name="linksDataParts">
28     /// <para>A links data parts.</para>
29     /// <para></para>
30     /// </param>
31     /// <param name="linksIndexParts">
32     /// <para>A links index parts.</para>
33     /// <para></para>
34     /// </param>
35     /// <param name="header">
36     /// <para>A header.</para>
37     /// <para></para>
38     /// </param>
39     [MethodImpl(MethodImplOptions.AggressiveInlining)]
40     public UInt64InternalLinksSourcesRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
    ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
    ↪ : base(constants, linksDataParts, linksIndexParts, header) { }
41
42     /// <summary>
43     /// <para>
44     /// Gets the left reference using the specified node.
45     /// </para>
46     /// <para></para>
47     /// </summary>
48     /// <param name="node">
49     /// <para>The node.</para>
50     /// <para></para>
51     /// </param>
52     /// <returns>
53     /// <para>The ref link</para>
54     /// <para></para>
55     /// </returns>
56     [MethodImpl(MethodImplOptions.AggressiveInlining)]
57     protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].LeftAsSource;
58
59     /// <summary>
60     /// <para>
61     /// Gets the right reference using the specified node.
62     /// </para>
63     /// <para></para>
64     /// </summary>
65     /// <param name="node">
66     /// <para>The node.</para>
67     /// <para></para>
68     /// </param>
69     /// <returns>
70     /// <para>The ref link</para>
71     /// <para></para>
72     /// </returns>
73     [MethodImpl(MethodImplOptions.AggressiveInlining)]
74     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].RightAsSource;
75
76     /// <summary>
77     /// <para>
78     /// Gets the left using the specified node.
79     /// </para>
80     /// <para></para>
81     /// </summary>
82     /// <param name="node">
83     /// <para>The node.</para>
84     /// <para></para>
85     /// </param>
86     /// <returns>
87     /// <para>The link</para>
88     /// <para></para>
89     /// </returns>
90     [MethodImpl(MethodImplOptions.AggressiveInlining)]
91     protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ LinksIndexParts[node].LeftAsSource;
92
93     /// <summary>
94     /// <para>

```

```

95     /// Gets the right using the specified node.
96     /// </para>
97     /// <para></para>
98     /// </summary>
99     /// <param name="node">
100    /// <para>The node.</para>
101    /// <para></para>
102    /// </param>
103    /// <returns>
104    /// <para>The link</para>
105    /// <para></para>
106    /// </returns>
107    [MethodImpl(MethodImplOptions.AggressiveInlining)]
108    protected override TLinkAddress GetRight(TLinkAddress node) =>
109        ↪ LinksIndexParts[node].RightAsSource;
110
111    /// <summary>
112    /// <para>
113    /// Sets the left using the specified node.
114    /// </para>
115    /// <para></para>
116    /// </summary>
117    /// <param name="node">
118    /// <para>The node.</para>
119    /// <para></para>
120    /// </param>
121    /// <param name="left">
122    /// <para>The left.</para>
123    /// <para></para>
124    /// </param>
125    [MethodImpl(MethodImplOptions.AggressiveInlining)]
126    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
127        ↪ LinksIndexParts[node].LeftAsSource = left;
128
129    /// <summary>
130    /// <para>
131    /// Sets the right using the specified node.
132    /// </para>
133    /// <para></para>
134    /// </summary>
135    /// <param name="node">
136    /// <para>The node.</para>
137    /// <para></para>
138    /// </param>
139    /// <param name="right">
140    /// <para>The right.</para>
141    /// <para></para>
142    /// </param>
143    [MethodImpl(MethodImplOptions.AggressiveInlining)]
144    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
145        ↪ LinksIndexParts[node].RightAsSource = right;
146
147    /// <summary>
148    /// <para>
149    /// Gets the size using the specified node.
150    /// </para>
151    /// <para></para>
152    /// </summary>
153    /// <param name="node">
154    /// <para>The node.</para>
155    /// <para></para>
156    /// </param>
157    /// <returns>
158    /// <para>The link</para>
159    /// <para></para>
160    /// </returns>
161    [MethodImpl(MethodImplOptions.AggressiveInlining)]
162    protected override TLinkAddress GetSize(TLinkAddress node) =>
163        ↪ LinksIndexParts[node].SizeAsSource;
164
165    /// <summary>
166    /// <para>
167    /// Sets the size using the specified node.
168    /// </para>
169    /// <para></para>
170    /// </summary>
171    /// <param name="node">
172    /// <para>The node.</para>

```

```

169    /// <para></para>
170    /// </param>
171    /// <param name="size">
172    /// <para>The size.</para>
173    /// <para></para>
174    /// </param>
175    [MethodImpl(MethodImplOptions.AggressiveInlining)]
176    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
177        ↪ LinksIndexParts[node].SizeAsSource = size;
178
179    /// <summary>
180    /// <para>
181    /// Gets the tree root using the specified node.
182    /// </para>
183    /// </summary>
184    /// <param name="node">
185    /// <para>The node.</para>
186    /// <para></para>
187    /// </param>
188    /// <returns>
189    /// <para>The link</para>
190    /// <para></para>
191    /// </returns>
192    [MethodImpl(MethodImplOptions.AggressiveInlining)]
193    protected override TLinkAddress GetTreeRoot(TLinkAddress node) =>
194        ↪ LinksIndexParts[node].RootAsSource;
195
196    /// <summary>
197    /// <para>
198    /// Gets the base part value using the specified node.
199    /// </para>
200    /// <para></para>
201    /// </summary>
202    /// <param name="node">
203    /// <para>The node.</para>
204    /// <para></para>
205    /// </param>
206    /// <returns>
207    /// <para>The link</para>
208    /// <para></para>
209    /// </returns>
210    [MethodImpl(MethodImplOptions.AggressiveInlining)]
211    protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
212        ↪ LinksDataParts[node].Source;
213
214    /// <summary>
215    /// <para>
216    /// Gets the key part value using the specified node.
217    /// </para>
218    /// <para></para>
219    /// </summary>
220    /// <param name="node">
221    /// <para>The node.</para>
222    /// <para></para>
223    /// </param>
224    /// <returns>
225    /// <para>The link</para>
226    /// <para></para>
227    /// </returns>
228    [MethodImpl(MethodImplOptions.AggressiveInlining)]
229    protected override TLinkAddress GetKeyPartValue(TLinkAddress node) =>
230        ↪ LinksDataParts[node].Target;
231
232    /// <summary>
233    /// <para>
234    /// Clears the node using the specified node.
235    /// </para>
236    /// <para></para>
237    /// </summary>
238    /// <param name="node">
239    /// <para>The node.</para>
240    /// <para></para>
241    /// </param>
242    [MethodImpl(MethodImplOptions.AggressiveInlining)]
243    protected override void ClearNode(TLinkAddress node)
244    {
245        ref var link = ref LinksIndexParts[node];

```

```

243         link.LeftAsSource = Zero;
244         link.RightAsSource = Zero;
245         link.SizeAsSource = Zero;
246     }
247
248     /// <summary>
249     /// <para>
250     /// Searches the source.
251     /// </para>
252     /// <para></para>
253     /// </summary>
254     /// <param name="source">
255     /// <para>The source.</para>
256     /// <para></para>
257     /// </param>
258     /// <param name="target">
259     /// <para>The target.</para>
260     /// <para></para>
261     /// </param>
262     /// <returns>
263     /// <para>The link</para>
264     /// <para></para>
265     /// </returns>
266     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
        ↪ SearchCore(GetTreeRoot(source), target);
267 }
268 }

```

1.75 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksSourcesSizeBalancedTreeMethod

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt64;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 64 internal links sources size balanced tree methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="UInt64InternalLinksSizeBalancedTreeMethodsBase"/>
15     public unsafe class UInt64InternalLinksSourcesSizeBalancedTreeMethods :
        ↪ UInt64InternalLinksSizeBalancedTreeMethodsBase
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see cref="UInt64InternalLinksSourcesSizeBalancedTreeMethods"/>
20         ↪ instance.
21         /// </para>
22         /// <para></para>
23         /// </summary>
24         /// <param name="constants">
25         /// <para>A constants.</para>
26         /// <para></para>
27         /// </param>
28         /// <param name="linksDataParts">
29         /// <para>A links data parts.</para>
30         /// <para></para>
31         /// </param>
32         /// <param name="linksIndexParts">
33         /// <para>A links index parts.</para>
34         /// <para></para>
35         /// </param>
36         /// <param name="header">
37         /// <para>A header.</para>
38         /// <para></para>
39         /// </param>
40         [MethodImpl(MethodImplOptions.AggressiveInlining)]
41         public UInt64InternalLinksSourcesSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
        ↪ constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
        ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
        ↪ : base(constants, linksDataParts, linksIndexParts, header) { }
41
42         /// <summary>
43         /// <para>
44         /// Gets the left reference using the specified node.
45         /// </para>

```

```

46     /// <para></para>
47     /// </summary>
48     /// <param name="node">
49     /// <para>The node.</para>
50     /// <para></para>
51     /// </param>
52     /// <returns>
53     /// <para>The ref link</para>
54     /// <para></para>
55     /// </returns>
56     [MethodImpl(MethodImplOptions.AggressiveInlining)]
57     protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].LeftAsSource;

58
59     /// <summary>
60     /// <para>
61     /// Gets the right reference using the specified node.
62     /// </para>
63     /// <para></para>
64     /// </summary>
65     /// <param name="node">
66     /// <para>The node.</para>
67     /// <para></para>
68     /// </param>
69     /// <returns>
70     /// <para>The ref link</para>
71     /// <para></para>
72     /// </returns>
73     [MethodImpl(MethodImplOptions.AggressiveInlining)]
74     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ LinksIndexParts[node].RightAsSource;

75
76     /// <summary>
77     /// <para>
78     /// Gets the left using the specified node.
79     /// </para>
80     /// <para></para>
81     /// </summary>
82     /// <param name="node">
83     /// <para>The node.</para>
84     /// <para></para>
85     /// </param>
86     /// <returns>
87     /// <para>The link</para>
88     /// <para></para>
89     /// </returns>
90     [MethodImpl(MethodImplOptions.AggressiveInlining)]
91     protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ LinksIndexParts[node].LeftAsSource;

92
93     /// <summary>
94     /// <para>
95     /// Gets the right using the specified node.
96     /// </para>
97     /// <para></para>
98     /// </summary>
99     /// <param name="node">
100    /// <para>The node.</para>
101    /// <para></para>
102    /// </param>
103    /// <returns>
104    /// <para>The link</para>
105    /// <para></para>
106    /// </returns>
107    [MethodImpl(MethodImplOptions.AggressiveInlining)]
108    protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↪ LinksIndexParts[node].RightAsSource;

109
110    /// <summary>
111    /// <para>
112    /// Sets the left using the specified node.
113    /// </para>
114    /// <para></para>
115    /// </summary>
116    /// <param name="node">
117    /// <para>The node.</para>
118    /// <para></para>
119    /// </param>

```

```

120    /// <param name="left">
121    /// <para>The left.</para>
122    /// <para></para>
123    /// </param>
124    [MethodImpl(MethodImplOptions.AggressiveInlining)]
125    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
126        ↳ LinksIndexParts[node].LeftAsSource = left;
127
128    /// <summary>
129    /// <para>
130    /// Sets the right using the specified node.
131    /// </para>
132    /// <para></para>
133    /// </summary>
134    /// <param name="node">
135    /// <para>The node.</para>
136    /// <para></para>
137    /// </param>
138    /// <param name="right">
139    /// <para>The right.</para>
140    /// <para></para>
141    /// </param>
142    [MethodImpl(MethodImplOptions.AggressiveInlining)]
143    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
144        ↳ LinksIndexParts[node].RightAsSource = right;
145
146    /// <summary>
147    /// <para>
148    /// Gets the size using the specified node.
149    /// </para>
150    /// <para></para>
151    /// </summary>
152    /// <param name="node">
153    /// <para>The node.</para>
154    /// <para></para>
155    /// </param>
156    /// <returns>
157    /// <para>The link</para>
158    /// <para></para>
159    /// </returns>
160    [MethodImpl(MethodImplOptions.AggressiveInlining)]
161    protected override TLinkAddress GetSize(TLinkAddress node) =>
162        ↳ LinksIndexParts[node].SizeAsSource;
163
164    /// <summary>
165    /// <para>
166    /// Sets the size using the specified node.
167    /// </para>
168    /// <para></para>
169    /// </summary>
170    /// <param name="node">
171    /// <para>The node.</para>
172    /// <para></para>
173    /// </param>
174    /// <param name="size">
175    /// <para>The size.</para>
176    /// <para></para>
177    /// </param>
178    [MethodImpl(MethodImplOptions.AggressiveInlining)]
179    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
180        ↳ LinksIndexParts[node].SizeAsSource = size;
181
182    /// <summary>
183    /// <para>
184    /// Gets the tree root using the specified node.
185    /// </para>
186    /// <para></para>
187    /// </summary>
188    /// <param name="node">
189    /// <para>The node.</para>
190    /// <para></para>
191    /// </param>
192    /// <returns>
193    /// <para>The link</para>
194    /// <para></para>
195    /// </returns>
196    [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

193     protected override TLinkAddress GetTreeRoot(TLinkAddress node) =>
194         ↳ LinksIndexParts[node].RootAsSource;
195
196     /// <summary>
197     /// <para>
198     /// Gets the base part value using the specified node.
199     /// </para>
200     /// <para></para>
201     /// </summary>
202     /// <param name="node">
203     /// <para>The node.</para>
204     /// <para></para>
205     /// </param>
206     /// <returns>
207     /// <para>The link</para>
208     /// <para></para>
209     /// </returns>
210     [MethodImpl(MethodImplOptions.AggressiveInlining)]
211     protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
212         ↳ LinksDataParts[node].Source;
213
214     /// <summary>
215     /// <para>
216     /// Gets the key part value using the specified node.
217     /// </para>
218     /// <para></para>
219     /// </summary>
220     /// <param name="node">
221     /// <para>The node.</para>
222     /// <para></para>
223     /// </param>
224     /// <returns>
225     /// <para>The link</para>
226     /// <para></para>
227     /// </returns>
228     [MethodImpl(MethodImplOptions.AggressiveInlining)]
229     protected override TLinkAddress GetKeyPartValue(TLinkAddress node) =>
230         ↳ LinksDataParts[node].Target;
231
232     /// <summary>
233     /// <para>
234     /// Clears the node using the specified node.
235     /// </para>
236     /// <para></para>
237     /// </summary>
238     /// <param name="node">
239     /// <para>The node.</para>
240     /// <para></para>
241     /// </param>
242     [MethodImpl(MethodImplOptions.AggressiveInlining)]
243     protected override void ClearNode(TLinkAddress node)
244     {
245         ref var link = ref LinksIndexParts[node];
246         link.LeftAsSource = Zero;
247         link.RightAsSource = Zero;
248         link.SizeAsSource = Zero;
249     }
250
251     /// <summary>
252     /// <para>
253     /// Searches the source.
254     /// </para>
255     /// <para></para>
256     /// </summary>
257     /// <param name="source">
258     /// <para>The source.</para>
259     /// <para></para>
260     /// </param>
261     /// <param name="target">
262     /// <para>The target.</para>
263     /// <para></para>
264     /// </param>
265     /// <returns>
266     /// <para>The link</para>
267     /// <para></para>
268     /// </returns>
269     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
270         ↳ SearchCore(GetTreeRoot(source), target);

```



```
267 }
268 }
```

1.76 ./csharp/Platform.Data.Doublets.Memory.Split.Specific/UInt64InternalLinksTargetsRecursionlessSizeBalanced

```
1 using System.Runtime.CompilerServices;
2 using TLinkAddress = System.UInt64;
3
4 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6 namespace Platform.Data.Doublets.Memory.Split.Specific
7 {
8     /// <summary>
9     /// <para>
10    /// Represents the int 64 internal links targets recursionless size balanced tree methods.
11    /// </para>
12    /// <para></para>
13    /// </summary>
14    /// <seealso cref="UInt64InternalLinksRecursionlessSizeBalancedTreeMethodsBase"/>
15    public unsafe class UInt64InternalLinksTargetsRecursionlessSizeBalancedTreeMethods :
16    ↪ UInt64InternalLinksRecursionlessSizeBalancedTreeMethodsBase
17    {
18        /// <summary>
19        /// <para>
20        /// Initializes a new <see
21        ↪ cref="UInt64InternalLinksTargetsRecursionlessSizeBalancedTreeMethods"/> instance.
22        /// </para>
23        /// <para></para>
24        /// </summary>
25        /// <param name="constants">
26        /// <para>A constants.</para>
27        /// <para></para>
28        /// </param>
29        /// <param name="linksDataParts">
30        /// <para>A links data parts.</para>
31        /// <para></para>
32        /// </param>
33        /// <param name="linksIndexParts">
34        /// <para>A links index parts.</para>
35        /// <para></para>
36        /// </param>
37        /// <param name="header">
38        /// <para>A header.</para>
39        /// <para></para>
40        /// </param>
41        [MethodImpl(MethodImplOptions.AggressiveInlining)]
42        public UInt64InternalLinksTargetsRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddress> constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
43        ↪ RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
44        ↪ : base(constants, linksDataParts, linksIndexParts, header) { }
45
46        /// <summary>
47        /// <para>
48        /// Gets the left reference using the specified node.
49        /// </para>
50        /// <para></para>
51        /// </summary>
52        /// <param name="node">
53        /// <para>The node.</para>
54        /// <para></para>
55        /// </param>
56        /// <returns>
57        /// <para>The ref ulong</para>
58        /// <para></para>
59        /// </returns>
60        [MethodImpl(MethodImplOptions.AggressiveInlining)]
61        protected override ref ulong GetLeftReference(ulong node) => ref
62        ↪ LinksIndexParts[node].LeftAsTarget;
63
64        /// <summary>
65        /// <para>
66        /// Gets the right reference using the specified node.
67        /// </para>
68        /// <para></para>
69        /// </summary>
70        /// <param name="node">
71        /// <para>The node.</para>
72        /// <para></para>
73        /// </param>
```

```

69     /// <returns>
70     /// <para>The ref ulong</para>
71     /// <para></para>
72     /// </returns>
73     [MethodImpl(MethodImplOptions.AggressiveInlining)]
74     protected override ref ulong GetRightReference(ulong node) => ref
75     ↪ LinksIndexParts[node].RightAsTarget;
76
77     /// <summary>
78     /// <para>
79     /// Gets the left using the specified node.
80     /// </para>
81     /// <para></para>
82     /// </summary>
83     /// <param name="node">
84     /// <para>The node.</para>
85     /// <para></para>
86     /// </param>
87     /// <returns>
88     /// <para>The link</para>
89     /// <para></para>
90     /// </returns>
91     [MethodImpl(MethodImplOptions.AggressiveInlining)]
92     protected override TLinkAddress GetLeft(TLinkAddress node) =>
93     ↪ LinksIndexParts[node].LeftAsTarget;
94
95     /// <summary>
96     /// <para>
97     /// Gets the right using the specified node.
98     /// </para>
99     /// <para></para>
100    /// </summary>
101    /// <param name="node">
102    /// <para>The node.</para>
103    /// <para></para>
104    /// </param>
105    /// <returns>
106    /// <para>The link</para>
107    /// <para></para>
108    /// </returns>
109    [MethodImpl(MethodImplOptions.AggressiveInlining)]
110    protected override TLinkAddress GetRight(TLinkAddress node) =>
111    ↪ LinksIndexParts[node].RightAsTarget;
112
113    /// <summary>
114    /// <para>
115    /// Sets the left using the specified node.
116    /// </para>
117    /// <para></para>
118    /// </summary>
119    /// <param name="node">
120    /// <para>The node.</para>
121    /// <para></para>
122    /// </param>
123    /// <param name="left">
124    /// <para>The left.</para>
125    /// <para></para>
126    /// </param>
127    [MethodImpl(MethodImplOptions.AggressiveInlining)]
128    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
129    ↪ LinksIndexParts[node].LeftAsTarget = left;
130
131    /// <summary>
132    /// <para>
133    /// Sets the right using the specified node.
134    /// </para>
135    /// <para></para>
136    /// </summary>
137    /// <param name="node">
138    /// <para>The node.</para>
139    /// <para></para>
140    /// </param>
141    /// <param name="right">
142    /// <para>The right.</para>
143    /// <para></para>
144    /// </param>
145    [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

142     protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
143         ↳ LinksIndexParts[node].RightAsTarget = right;
144
145     /// <summary>
146     /// <para>
147     /// Gets the size using the specified node.
148     /// </para>
149     /// <para></para>
150     /// </summary>
151     /// <param name="node">
152     /// <para>The node.</para>
153     /// <para></para>
154     /// </param>
155     /// <returns>
156     /// <para>The link</para>
157     /// <para></para>
158     /// </returns>
159     [MethodImpl(MethodImplOptions.AggressiveInlining)]
160     protected override TLinkAddress GetSize(TLinkAddress node) =>
161         ↳ LinksIndexParts[node].SizeAsTarget;
162
163     /// <summary>
164     /// <para>
165     /// Sets the size using the specified node.
166     /// </para>
167     /// <para></para>
168     /// </summary>
169     /// <param name="node">
170     /// <para>The node.</para>
171     /// <para></para>
172     /// </param>
173     /// <param name="size">
174     /// <para>The size.</para>
175     /// <para></para>
176     /// </param>
177     [MethodImpl(MethodImplOptions.AggressiveInlining)]
178     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
179         ↳ LinksIndexParts[node].SizeAsTarget = size;
180
181     /// <summary>
182     /// <para>
183     /// Gets the tree root using the specified node.
184     /// </para>
185     /// <para></para>
186     /// </summary>
187     /// <param name="node">
188     /// <para>The node.</para>
189     /// <para></para>
190     /// </param>
191     /// <returns>
192     /// <para>The link</para>
193     /// <para></para>
194     /// </returns>
195     [MethodImpl(MethodImplOptions.AggressiveInlining)]
196     protected override TLinkAddress GetTreeRoot(TLinkAddress node) =>
197         ↳ LinksIndexParts[node].RootAsTarget;
198
199     /// <summary>
200     /// <para>
201     /// Gets the base part value using the specified node.
202     /// </para>
203     /// <para></para>
204     /// </summary>
205     /// <param name="node">
206     /// <para>The node.</para>
207     /// <para></para>
208     /// </param>
209     /// <returns>
210     /// <para>The link</para>
211     /// <para></para>
212     /// </returns>
213     [MethodImpl(MethodImplOptions.AggressiveInlining)]
214     protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
215         ↳ LinksDataParts[node].Target;
216
217     /// <summary>
218     /// <para>

```

```

214     /// Gets the key part value using the specified node.
215     /// </para>
216     /// <para></para>
217     /// </summary>
218     /// <param name="node">
219     /// <para>The node.</para>
220     /// <para></para>
221     /// </param>
222     /// <returns>
223     /// <para>The link</para>
224     /// <para></para>
225     /// </returns>
226     [MethodImpl(MethodImplOptions.AggressiveInlining)]
227     protected override TLinkAddress GetKeyPartValue(TLinkAddress node) =>
228         ↪ LinksDataParts[node].Source;
229
230     /// <summary>
231     /// <para>
232     /// Clears the node using the specified node.
233     /// </para>
234     /// <para></para>
235     /// </summary>
236     /// <param name="node">
237     /// <para>The node.</para>
238     /// <para></para>
239     /// </param>
240     [MethodImpl(MethodImplOptions.AggressiveInlining)]
241     protected override void ClearNode(TLinkAddress node)
242     {
243         ref var link = ref LinksIndexParts[node];
244         link.LeftAsTarget = Zero;
245         link.RightAsTarget = Zero;
246         link.SizeAsTarget = Zero;
247     }
248
249     /// <summary>
250     /// <para>
251     /// Searches the source.
252     /// </para>
253     /// <para></para>
254     /// </summary>
255     /// <param name="source">
256     /// <para>The source.</para>
257     /// <para></para>
258     /// </param>
259     /// <param name="target">
260     /// <para>The target.</para>
261     /// <para></para>
262     /// </param>
263     /// <returns>
264     /// <para>The link</para>
265     /// <para></para>
266     /// </returns>
267     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
268         ↪ SearchCore(GetTreeRoot(target), source);
269 }
270 }

```

1.77 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksTargetsSizeBalancedTreeMethod

```

1  using System.Runtime.CompilerServices;
2  using TLinkAddress = System.UInt64;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.Split.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 64 internal links targets size balanced tree methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="UInt64InternalLinksSizeBalancedTreeMethodsBase"/>
15     public unsafe class UInt64InternalLinksTargetsSizeBalancedTreeMethods :
16         ↪ UInt64InternalLinksSizeBalancedTreeMethodsBase
17     {
18         /// <summary>
19         /// <para>

```

```

19     /// Initializes a new <see cref="UInt64InternalLinksTargetsSizeBalancedTreeMethods"/>
    → instance.
20     /// </para>
21     /// <para></para>
22     /// </summary>
23     /// <param name="constants">
24     /// <para>A constants.</para>
25     /// <para></para>
26     /// </param>
27     /// <param name="linksDataParts">
28     /// <para>A links data parts.</para>
29     /// <para></para>
30     /// </param>
31     /// <param name="linksIndexParts">
32     /// <para>A links index parts.</para>
33     /// <para></para>
34     /// </param>
35     /// <param name="header">
36     /// <para>A header.</para>
37     /// <para></para>
38     /// </param>
39     [MethodImpl(MethodImplOptions.AggressiveInlining)]
40     public UInt64InternalLinksTargetsSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
    → constants, RawLinkDataPart<TLinkAddress>* linksDataParts,
    → RawLinkIndexPart<TLinkAddress>* linksIndexParts, LinksHeader<TLinkAddress>* header)
    → : base(constants, linksDataParts, linksIndexParts, header) { }

41     /// <summary>
42     /// <para>
43     /// Gets the left reference using the specified node.
44     /// </para>
45     /// <para></para>
46     /// </summary>
47     /// <param name="node">
48     /// <para>The node.</para>
49     /// <para></para>
50     /// </param>
51     /// <returns>
52     /// <para>The ref ulong</para>
53     /// <para></para>
54     /// </returns>
55     [MethodImpl(MethodImplOptions.AggressiveInlining)]
56     protected override ref ulong GetLeftReference(ulong node) => ref
    → LinksIndexParts[node].LeftAsTarget;

58     /// <summary>
59     /// <para>
60     /// Gets the right reference using the specified node.
61     /// </para>
62     /// <para></para>
63     /// </summary>
64     /// <param name="node">
65     /// <para>The node.</para>
66     /// <para></para>
67     /// </param>
68     /// <returns>
69     /// <para>The ref ulong</para>
70     /// <para></para>
71     /// </returns>
72     [MethodImpl(MethodImplOptions.AggressiveInlining)]
73     protected override ref ulong GetRightReference(ulong node) => ref
    → LinksIndexParts[node].RightAsTarget;

75     /// <summary>
76     /// <para>
77     /// Gets the left using the specified node.
78     /// </para>
79     /// <para></para>
80     /// </summary>
81     /// <param name="node">
82     /// <para>The node.</para>
83     /// <para></para>
84     /// </param>
85     /// <returns>
86     /// <para>The link</para>
87     /// <para></para>
88     /// </returns>
89     [MethodImpl(MethodImplOptions.AggressiveInlining)]
90

```

```

91     protected override TLinkAddress GetLeft(TLinkAddress node) =>
92         ↪ LinksIndexParts[node].LeftAsTarget;
93
94     /// <summary>
95     /// <para>
96     /// Gets the right using the specified node.
97     /// </para>
98     /// <para></para>
99     /// </summary>
100    /// <param name="node">
101    /// <para>The node.</para>
102    /// <para></para>
103    /// </param>
104    /// <returns>
105    /// <para>The link</para>
106    /// <para></para>
107    /// </returns>
108    [MethodImpl(MethodImplOptions.AggressiveInlining)]
109    protected override TLinkAddress GetRight(TLinkAddress node) =>
110        ↪ LinksIndexParts[node].RightAsTarget;
111
112    /// <summary>
113    /// <para>
114    /// Sets the left using the specified node.
115    /// </para>
116    /// <para></para>
117    /// </summary>
118    /// <param name="node">
119    /// <para>The node.</para>
120    /// <para></para>
121    /// </param>
122    /// <param name="left">
123    /// <para>The left.</para>
124    /// <para></para>
125    /// </param>
126    [MethodImpl(MethodImplOptions.AggressiveInlining)]
127    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
128        ↪ LinksIndexParts[node].LeftAsTarget = left;
129
130    /// <summary>
131    /// <para>
132    /// Sets the right using the specified node.
133    /// </para>
134    /// <para></para>
135    /// </summary>
136    /// <param name="node">
137    /// <para>The node.</para>
138    /// <para></para>
139    /// </param>
140    /// <param name="right">
141    /// <para>The right.</para>
142    /// <para></para>
143    /// </param>
144    [MethodImpl(MethodImplOptions.AggressiveInlining)]
145    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
146        ↪ LinksIndexParts[node].RightAsTarget = right;
147
148    /// <summary>
149    /// <para>
150    /// Gets the size using the specified node.
151    /// </para>
152    /// <para></para>
153    /// </summary>
154    /// <param name="node">
155    /// <para>The node.</para>
156    /// <para></para>
157    /// </param>
158    /// <returns>
159    /// <para>The link</para>
160    /// <para></para>
161    /// </returns>
162    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    protected override TLinkAddress GetSize(TLinkAddress node) =>
        ↪ LinksIndexParts[node].SizeAsTarget;

```

```

163     /// Sets the size using the specified node.
164     /// </para>
165     /// <para></para>
166     /// </summary>
167     /// <param name="node">
168     /// <para>The node.</para>
169     /// <para></para>
170     /// </param>
171     /// <param name="size">
172     /// <para>The size.</para>
173     /// <para></para>
174     /// </param>
175     [MethodImpl(MethodImplOptions.AggressiveInlining)]
176     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
177         ↪ LinksIndexParts[node].SizeAsTarget = size;
178
179     /// <summary>
180     /// <para>
181     /// Gets the tree root using the specified node.
182     /// </para>
183     /// <para></para>
184     /// </summary>
185     /// <param name="node">
186     /// <para>The node.</para>
187     /// <para></para>
188     /// </param>
189     /// <returns>
190     /// <para>The link</para>
191     /// <para></para>
192     /// </returns>
193     [MethodImpl(MethodImplOptions.AggressiveInlining)]
194     protected override TLinkAddress GetTreeRoot(TLinkAddress node) =>
195         ↪ LinksIndexParts[node].RootAsTarget;
196
197     /// <summary>
198     /// <para>
199     /// Gets the base part value using the specified node.
200     /// </para>
201     /// <para></para>
202     /// </summary>
203     /// <param name="node">
204     /// <para>The node.</para>
205     /// <para></para>
206     /// </param>
207     /// <returns>
208     /// <para>The link</para>
209     /// <para></para>
210     /// </returns>
211     [MethodImpl(MethodImplOptions.AggressiveInlining)]
212     protected override TLinkAddress GetBasePartValue(TLinkAddress node) =>
213         ↪ LinksDataParts[node].Target;
214
215     /// <summary>
216     /// <para>
217     /// Gets the key part value using the specified node.
218     /// </para>
219     /// <para></para>
220     /// </summary>
221     /// <param name="node">
222     /// <para>The node.</para>
223     /// <para></para>
224     /// </param>
225     /// <returns>
226     /// <para>The link</para>
227     /// <para></para>
228     /// </returns>
229     [MethodImpl(MethodImplOptions.AggressiveInlining)]
230     protected override TLinkAddress GetKeyPartValue(TLinkAddress node) =>
231         ↪ LinksDataParts[node].Source;
232
233     /// <summary>
234     /// <para>
235     /// Clears the node using the specified node.
236     /// </para>
237     /// <para></para>
238     /// </summary>
239     /// <param name="node">
240     /// <para>The node.</para>
241     /// <para></para>
242     /// </param>

```

```

237     /// <para></para>
238     /// </param>
239     [MethodImpl(MethodImplOptions.AggressiveInlining)]
240     protected override void ClearNode(TLinkAddress node)
241     {
242         ref var link = ref LinksIndexParts[node];
243         link.LeftAsTarget = Zero;
244         link.RightAsTarget = Zero;
245         link.SizeAsTarget = Zero;
246     }
247
248     /// <summary>
249     /// <para>
250     /// Searches the source.
251     /// </para>
252     /// <para></para>
253     /// </summary>
254     /// <param name="source">
255     /// <para>The source.</para>
256     /// <para></para>
257     /// </param>
258     /// <param name="target">
259     /// <para>The target.</para>
260     /// <para></para>
261     /// </param>
262     /// <returns>
263     /// <para>The link</para>
264     /// <para></para>
265     /// </returns>
266     public override TLinkAddress Search(TLinkAddress source, TLinkAddress target) =>
        ↪ SearchCore(GetTreeRoot(target), source);
267 }
268 }

```

1.78 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64SplitMemoryLinks.cs

```

1  using System;
2  using System.Runtime.CompilerServices;
3  using Platform.Singletons;
4  using Platform.Memory;
5  using Platform.Data.Doublets.Memory.Split.Generic;
6  using TLinkAddress = System.UInt64;
7
8  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
9
10 namespace Platform.Data.Doublets.Memory.Split.Specific
11 {
12     /// <summary>
13     /// <para>
14     /// Represents the int 64 split memory links.
15     /// </para>
16     /// <para></para>
17     /// </summary>
18     /// <seealso cref="SplitMemoryLinksBase{TLinkAddress}"/>
19     public unsafe class UInt64SplitMemoryLinks : SplitMemoryLinksBase<TLinkAddress>
20     {
21         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createInternalSourceTreeMethods;
22         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createExternalSourceTreeMethods;
23         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createInternalTargetTreeMethods;
24         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createExternalTargetTreeMethods;
25         private LinksHeader<ulong>* _header;
26         private RawLinkDataPart<ulong>* _linksDataParts;
27         private RawLinkIndexPart<ulong>* _linksIndexParts;
28
29         /// <summary>
30         /// <para>
31         /// Initializes a new <see cref="UInt64SplitMemoryLinks"/> instance.
32         /// </para>
33         /// <para></para>
34         /// </summary>
35         /// <param name="dataMemory">
36         /// <para>A data memory.</para>
37         /// <para></para>
38         /// </param>
39         /// <param name="indexMemory">
40         /// <para>A index memory.</para>
41         /// <para></para>
42         /// </param>
43         [MethodImpl(MethodImplOptions.AggressiveInlining)]
44         public UInt64SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
            ↪ indexMemory) : this(dataMemory, indexMemory, DefaultLinksSizeStep) { }

```



```

45
46    /// <summary>
47    /// <para>
48    /// Initializes a new <see cref="UInt64SplitMemoryLinks"/> instance.
49    /// </para>
50    /// <para></para>
51    /// </summary>
52    /// <param name="dataMemory">
53    /// <para>A data memory.</para>
54    /// <para></para>
55    /// </param>
56    /// <param name="indexMemory">
57    /// <para>A index memory.</para>
58    /// <para></para>
59    /// </param>
60    /// <param name="memoryReservationStep">
61    /// <para>A memory reservation step.</para>
62    /// <para></para>
63    /// </param>
64    [MethodImpl(MethodImplOptions.AggressiveInlining)]
65    public UInt64SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
        ↳ indexMemory, long memoryReservationStep) : this(dataMemory, indexMemory,
        ↳ memoryReservationStep, Default<LinksConstants<TLinkAddress>>.Instance,
        ↳ IndexTreeType.Default, useLinkedList: true) { }
66
67    /// <summary>
68    /// <para>
69    /// Initializes a new <see cref="UInt64SplitMemoryLinks"/> instance.
70    /// </para>
71    /// <para></para>
72    /// </summary>
73    /// <param name="dataMemory">
74    /// <para>A data memory.</para>
75    /// <para></para>
76    /// </param>
77    /// <param name="indexMemory">
78    /// <para>A index memory.</para>
79    /// <para></para>
80    /// </param>
81    /// <param name="memoryReservationStep">
82    /// <para>A memory reservation step.</para>
83    /// <para></para>
84    /// </param>
85    /// <param name="constants">
86    /// <para>A constants.</para>
87    /// <para></para>
88    /// </param>
89    [MethodImpl(MethodImplOptions.AggressiveInlining)]
90    public UInt64SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
        ↳ indexMemory, long memoryReservationStep, LinksConstants<TLinkAddress> constants) :
        ↳ this(dataMemory, indexMemory, memoryReservationStep, constants,
        ↳ IndexTreeType.Default, useLinkedList: true) { }
91
92    /// <summary>
93    /// <para>
94    /// Initializes a new <see cref="UInt64SplitMemoryLinks"/> instance.
95    /// </para>
96    /// <para></para>
97    /// </summary>
98    /// <param name="dataMemory">
99    /// <para>A data memory.</para>
100    /// <para></para>
101    /// </param>
102    /// <param name="indexMemory">
103    /// <para>A index memory.</para>
104    /// <para></para>
105    /// </param>
106    /// <param name="memoryReservationStep">
107    /// <para>A memory reservation step.</para>
108    /// <para></para>
109    /// </param>
110    /// <param name="constants">
111    /// <para>A constants.</para>
112    /// <para></para>
113    /// </param>
114    /// <param name="indexTreeType">
115    /// <para>A index tree type.</para>

```

```

116 /// <para></para>
117 /// </param>
118 /// <param name="useLinkedList">
119 /// <para>A use linked list.</para>
120 /// <para></para>
121 /// </param>
122 [MethodImpl(MethodImplOptions.AggressiveInlining)]
123 public UInt64SplitMemoryLinks(IResizableDirectMemory dataMemory, IResizableDirectMemory
    ↪ indexMemory, long memoryReservationStep, LinksConstants<TLinkAddress> constants,
    ↪ IndexTreeType indexTreeType, bool useLinkedList) : base(dataMemory, indexMemory,
    ↪ memoryReservationStep, constants, useLinkedList)
124 {
125     if (indexTreeType == IndexTreeType.SizeBalancedTree)
126     {
127         _createInternalSourceTreeMethods = () => new
            ↪ UInt64InternalLinksSourcesSizeBalancedTreeMethods(Constants,
            ↪ _linksDataParts, _linksIndexParts, _header);
128         _createExternalSourceTreeMethods = () => new
            ↪ UInt64ExternalLinksSourcesSizeBalancedTreeMethods(Constants,
            ↪ _linksDataParts, _linksIndexParts, _header);
129         _createInternalTargetTreeMethods = () => new
            ↪ UInt64InternalLinksTargetsSizeBalancedTreeMethods(Constants,
            ↪ _linksDataParts, _linksIndexParts, _header);
130         _createExternalTargetTreeMethods = () => new
            ↪ UInt64ExternalLinksTargetsSizeBalancedTreeMethods(Constants,
            ↪ _linksDataParts, _linksIndexParts, _header);
131     }
132     else
133     {
134         _createInternalSourceTreeMethods = () => new
            ↪ UInt64InternalLinksSourcesRecursionlessSizeBalancedTreeMethods(Constants,
            ↪ _linksDataParts, _linksIndexParts, _header);
135         _createExternalSourceTreeMethods = () => new
            ↪ UInt64ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods(Constants,
            ↪ _linksDataParts, _linksIndexParts, _header);
136         _createInternalTargetTreeMethods = () => new
            ↪ UInt64InternalLinksTargetsRecursionlessSizeBalancedTreeMethods(Constants,
            ↪ _linksDataParts, _linksIndexParts, _header);
137         _createExternalTargetTreeMethods = () => new
            ↪ UInt64ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods(Constants,
            ↪ _linksDataParts, _linksIndexParts, _header);
138     }
139     Init(dataMemory, indexMemory);
140 }
141
142 /// <summary>
143 /// <para>
144 /// Sets the pointers using the specified data memory.
145 /// </para>
146 /// <para></para>
147 /// </summary>
148 /// <param name="dataMemory">
149 /// <para>The data memory.</para>
150 /// <para></para>
151 /// </param>
152 /// <param name="indexMemory">
153 /// <para>The index memory.</para>
154 /// <para></para>
155 /// </param>
156 [MethodImpl(MethodImplOptions.AggressiveInlining)]
157 protected override void SetPointers(IResizableDirectMemory dataMemory,
    ↪ IResizableDirectMemory indexMemory)
158 {
159     _linksDataParts = (RawLinkDataPart<TLinkAddress>*)dataMemory.Pointer;
160     _linksIndexParts = (RawLinkIndexPart<TLinkAddress>*)indexMemory.Pointer;
161     _header = (LinksHeader<TLinkAddress>*)indexMemory.Pointer;
162     if (_useLinkedList)
163     {
164         InternalSourcesListMethods = new
            ↪ UInt64InternalLinksSourcesLinkedListMethods(Constants, _linksDataParts,
            ↪ _linksIndexParts);
165     }
166     else
167     {
168         InternalSourcesTreeMethods = _createInternalSourceTreeMethods();
169     }
170     ExternalSourcesTreeMethods = _createExternalSourceTreeMethods();

```

```

171     InternalTargetsTreeMethods = _createInternalTargetTreeMethods();
172     ExternalTargetsTreeMethods = _createExternalTargetTreeMethods();
173     UnusedLinksListMethods = new UInt64UnusedLinksListMethods(_linksDataParts, _header);
174 }
175
176 /// <summary>
177 /// <para>
178 /// Resets the pointers.
179 /// </para>
180 /// <para></para>
181 /// </summary>
182 [MethodImpl(MethodImplOptions.AggressiveInlining)]
183 protected override void ResetPointers()
184 {
185     base.ResetPointers();
186     _linksDataParts = null;
187     _linksIndexParts = null;
188     _header = null;
189 }
190
191 /// <summary>
192 /// <para>
193 /// Gets the header reference.
194 /// </para>
195 /// <para></para>
196 /// </summary>
197 /// <returns>
198 /// <para>A ref links header of t link</para>
199 /// <para></para>
200 /// </returns>
201 [MethodImpl(MethodImplOptions.AggressiveInlining)]
202 protected override ref LinksHeader<TLinkAddress> GetHeaderReference() => ref *_header;
203
204 /// <summary>
205 /// <para>
206 /// Gets the link data part reference using the specified link index.
207 /// </para>
208 /// <para></para>
209 /// </summary>
210 /// <param name="linkIndex">
211 /// <para>The link index.</para>
212 /// <para></para>
213 /// </param>
214 /// <returns>
215 /// <para>A ref raw link data part of t link</para>
216 /// <para></para>
217 /// </returns>
218 [MethodImpl(MethodImplOptions.AggressiveInlining)]
219 protected override ref RawLinkDataPart<TLinkAddress>
220     ↪ GetLinkDataPartReference(TLinkAddress linkIndex) => ref _linksDataParts[linkIndex];
221
222 /// <summary>
223 /// <para>
224 /// Gets the link index part reference using the specified link index.
225 /// </para>
226 /// <para></para>
227 /// </summary>
228 /// <param name="linkIndex">
229 /// <para>The link index.</para>
230 /// <para></para>
231 /// </param>
232 /// <returns>
233 /// <para>A ref raw link index part of t link</para>
234 /// <para></para>
235 /// </returns>
236 [MethodImpl(MethodImplOptions.AggressiveInlining)]
237 protected override ref RawLinkIndexPart<TLinkAddress>
238     ↪ GetLinkIndexPartReference(TLinkAddress linkIndex) => ref _linksIndexParts[linkIndex];
239
240 /// <summary>
241 /// <para>
242 /// Determines whether this instance are equal.
243 /// </para>
244 /// <para></para>
245 /// </summary>
246 /// <param name="first">
247 /// <para>The first.</para>
248 /// <para></para>
249 /// </param>

```

```

247     /// </param>
248     /// <param name="second">
249     /// <para>The second.</para>
250     /// <para></para>
251     /// </param>
252     /// <returns>
253     /// <para>The bool</para>
254     /// <para></para>
255     /// </returns>
256     [MethodImpl(MethodImplOptions.AggressiveInlining)]
257     protected override bool AreEqual(ulong first, ulong second) => first == second;
258
259     /// <summary>
260     /// <para>
261     /// Determines whether this instance less than.
262     /// </para>
263     /// <para></para>
264     /// </summary>
265     /// <param name="first">
266     /// <para>The first.</para>
267     /// <para></para>
268     /// </param>
269     /// <param name="second">
270     /// <para>The second.</para>
271     /// <para></para>
272     /// </param>
273     /// <returns>
274     /// <para>The bool</para>
275     /// <para></para>
276     /// </returns>
277     [MethodImpl(MethodImplOptions.AggressiveInlining)]
278     protected override bool LessThan(ulong first, ulong second) => first < second;
279
280     /// <summary>
281     /// <para>
282     /// Determines whether this instance less or equal than.
283     /// </para>
284     /// <para></para>
285     /// </summary>
286     /// <param name="first">
287     /// <para>The first.</para>
288     /// <para></para>
289     /// </param>
290     /// <param name="second">
291     /// <para>The second.</para>
292     /// <para></para>
293     /// </param>
294     /// <returns>
295     /// <para>The bool</para>
296     /// <para></para>
297     /// </returns>
298     [MethodImpl(MethodImplOptions.AggressiveInlining)]
299     protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;
300
301     /// <summary>
302     /// <para>
303     /// Determines whether this instance greater than.
304     /// </para>
305     /// <para></para>
306     /// </summary>
307     /// <param name="first">
308     /// <para>The first.</para>
309     /// <para></para>
310     /// </param>
311     /// <param name="second">
312     /// <para>The second.</para>
313     /// <para></para>
314     /// </param>
315     /// <returns>
316     /// <para>The bool</para>
317     /// <para></para>
318     /// </returns>
319     [MethodImpl(MethodImplOptions.AggressiveInlining)]
320     protected override bool GreaterThan(ulong first, ulong second) => first > second;
321
322     /// <summary>
323     /// <para>
324     /// Determines whether this instance greater or equal than.

```

```

325     /// </para>
326     /// <para></para>
327     /// </summary>
328     /// <param name="first">
329     /// <para>The first.</para>
330     /// <para></para>
331     /// </param>
332     /// <param name="second">
333     /// <para>The second.</para>
334     /// <para></para>
335     /// </param>
336     /// <returns>
337     /// <para>The bool</para>
338     /// <para></para>
339     /// </returns>
340     [MethodImpl(MethodImplOptions.AggressiveInlining)]
341     protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;
342
343     /// <summary>
344     /// <para>
345     /// Gets the zero.
346     /// </para>
347     /// <para></para>
348     /// </summary>
349     /// <returns>
350     /// <para>The ulong</para>
351     /// <para></para>
352     /// </returns>
353     [MethodImpl(MethodImplOptions.AggressiveInlining)]
354     protected override ulong GetZero() => 0UL;
355
356     /// <summary>
357     /// <para>
358     /// Gets the one.
359     /// </para>
360     /// <para></para>
361     /// </summary>
362     /// <returns>
363     /// <para>The ulong</para>
364     /// <para></para>
365     /// </returns>
366     [MethodImpl(MethodImplOptions.AggressiveInlining)]
367     protected override ulong GetOne() => 1UL;
368
369     /// <summary>
370     /// <para>
371     /// Converts the to int 64 using the specified value.
372     /// </para>
373     /// <para></para>
374     /// </summary>
375     /// <param name="value">
376     /// <para>The value.</para>
377     /// <para></para>
378     /// </param>
379     /// <returns>
380     /// <para>The long</para>
381     /// <para></para>
382     /// </returns>
383     [MethodImpl(MethodImplOptions.AggressiveInlining)]
384     protected override long ConvertToInt64(ulong value) => (long)value;
385
386     /// <summary>
387     /// <para>
388     /// Converts the to address using the specified value.
389     /// </para>
390     /// <para></para>
391     /// </summary>
392     /// <param name="value">
393     /// <para>The value.</para>
394     /// <para></para>
395     /// </param>
396     /// <returns>
397     /// <para>The ulong</para>
398     /// <para></para>
399     /// </returns>
400     [MethodImpl(MethodImplOptions.AggressiveInlining)]
401     protected override ulong ConvertToAddress(long value) => (ulong)value;
402

```

```

403     /// <summary>
404     /// <para>
405     /// Adds the first.
406     /// </para>
407     /// <para></para>
408     /// </summary>
409     /// <param name="first">
410     /// <para>The first.</para>
411     /// <para></para>
412     /// </param>
413     /// <param name="second">
414     /// <para>The second.</para>
415     /// <para></para>
416     /// </param>
417     /// <returns>
418     /// <para>The ulong</para>
419     /// <para></para>
420     /// </returns>
421     [MethodImpl(MethodImplOptions.AggressiveInlining)]
422     protected override ulong Add(ulong first, ulong second) => first + second;
423
424     /// <summary>
425     /// <para>
426     /// Subtracts the first.
427     /// </para>
428     /// <para></para>
429     /// </summary>
430     /// <param name="first">
431     /// <para>The first.</para>
432     /// <para></para>
433     /// </param>
434     /// <param name="second">
435     /// <para>The second.</para>
436     /// <para></para>
437     /// </param>
438     /// <returns>
439     /// <para>The ulong</para>
440     /// <para></para>
441     /// </returns>
442     [MethodImpl(MethodImplOptions.AggressiveInlining)]
443     protected override ulong Subtract(ulong first, ulong second) => first - second;
444
445     /// <summary>
446     /// <para>
447     /// Increments the link.
448     /// </para>
449     /// <para></para>
450     /// </summary>
451     /// <param name="link">
452     /// <para>The link.</para>
453     /// <para></para>
454     /// </param>
455     /// <returns>
456     /// <para>The ulong</para>
457     /// <para></para>
458     /// </returns>
459     [MethodImpl(MethodImplOptions.AggressiveInlining)]
460     protected override ulong Increment(ulong link) => ++link;
461
462     /// <summary>
463     /// <para>
464     /// Decrements the link.
465     /// </para>
466     /// <para></para>
467     /// </summary>
468     /// <param name="link">
469     /// <para>The link.</para>
470     /// <para></para>
471     /// </param>
472     /// <returns>
473     /// <para>The ulong</para>
474     /// <para></para>
475     /// </returns>
476     [MethodImpl(MethodImplOptions.AggressiveInlining)]
477     protected override ulong Decrement(ulong link) => --link;
478 }
479 }

```

1.79 ./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64UnusedLinksListMethods.cs

```

1  using System.Runtime.CompilerServices;
2  using Platform.Data.Doublets.Memory.Split.Generic;
3  using TLinkAddress = System.UInt64;
4
5  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7  namespace Platform.Data.Doublets.Memory.Split.Specific
8  {
9      /// <summary>
10     /// <para>
11     /// Represents the int 64 unused links list methods.
12     /// </para>
13     /// <para></para>
14     /// </summary>
15     /// <seealso cref="UnusedLinksListMethods{TLinkAddress}"/>
16     public unsafe class UInt64UnusedLinksListMethods : UnusedLinksListMethods<TLinkAddress>
17     {
18         private readonly RawLinkDataPart<ulong>* _links;
19         private readonly LinksHeader<ulong>* _header;
20
21         /// <summary>
22         /// <para>
23         /// Initializes a new <see cref="UInt64UnusedLinksListMethods"/> instance.
24         /// </para>
25         /// <para></para>
26         /// </summary>
27         /// <param name="links">
28         /// <para>A links.</para>
29         /// <para></para>
30         /// </param>
31         /// <param name="header">
32         /// <para>A header.</para>
33         /// <para></para>
34         /// </param>
35         [MethodImpl(MethodImplOptions.AggressiveInlining)]
36         public UInt64UnusedLinksListMethods(RawLinkDataPart<ulong>* links, LinksHeader<ulong>*
37         ↪ header)
38             : base((byte*)links, (byte*)header)
39         {
40             _links = links;
41             _header = header;
42         }
43
44         /// <summary>
45         /// <para>
46         /// Gets the link data part reference using the specified link.
47         /// </para>
48         /// <para></para>
49         /// </summary>
50         /// <param name="link">
51         /// <para>The link.</para>
52         /// <para></para>
53         /// </param>
54         /// <returns>
55         /// <para>A ref raw link data part of t link</para>
56         /// <para></para>
57         /// </returns>
58         [MethodImpl(MethodImplOptions.AggressiveInlining)]
59         protected override ref RawLinkDataPart<TLinkAddress>
60         ↪ GetLinkDataPartReference(TLinkAddress link) => ref _links[link];
61
62         /// <summary>
63         /// <para>
64         /// Gets the header reference.
65         /// </para>
66         /// <para></para>
67         /// </summary>
68         /// <returns>
69         /// <para>A ref links header of t link</para>
70         /// <para></para>
71         /// </returns>
72         [MethodImpl(MethodImplOptions.AggressiveInlining)]
73         protected override ref LinksHeader<TLinkAddress> GetHeaderReference() => ref *_header;
74     }
75 }

```

1.80 ./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksAvlBalancedTreeMethodsBase.cs

```

1  using System;
2  using System.Text;
3  using System.Collections.Generic;
4  using System.Runtime.CompilerServices;
5  using Platform.Collections.Methods.Trees;
6  using Platform.Converters;
7  using Platform.Delegates;
8  using Platform.Numbers;
9  using static System.Runtime.CompilerServices.Unsafe;
10
11 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
12
13 namespace Platform.Data.Doublets.Memory.United.Generic
14 {
15     /// <summary>
16     /// <para>
17     /// Represents the links avl balanced tree methods base.
18     /// </para>
19     /// <para></para>
20     /// </summary>
21     /// <seealso cref="SizedAndThreadedAVLBalancedTreeMethods{TLinkAddress}"/>
22     /// <seealso cref="ILinksTreeMethods{TLinkAddress}"/>
23     public unsafe abstract class LinksAvlBalancedTreeMethodsBase<TLinkAddress> :
24         ↳ SizedAndThreadedAVLBalancedTreeMethods<TLinkAddress>, ILinksTreeMethods<TLinkAddress>
25     {
26         private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
27             ↳ = UncheckedConverter<TLinkAddress, long>.Default;
28         private static readonly UncheckedConverter<TLinkAddress, int> _addressToInt32Converter =
29             ↳ UncheckedConverter<TLinkAddress, int>.Default;
30         private static readonly UncheckedConverter<bool, TLinkAddress> _boolToAddressConverter =
31             ↳ UncheckedConverter<bool, TLinkAddress>.Default;
32         private static readonly UncheckedConverter<TLinkAddress, bool> _addressToBoolConverter =
33             ↳ UncheckedConverter<TLinkAddress, bool>.Default;
34         private static readonly UncheckedConverter<int, TLinkAddress> _int32ToAddressConverter =
35             ↳ UncheckedConverter<int, TLinkAddress>.Default;
36
37         /// <summary>
38         /// <para>
39         /// The break.
40         /// </para>
41         /// <para></para>
42         /// </summary>
43         protected readonly TLinkAddress Break;
44
45         /// <summary>
46         /// <para>
47         /// The continue.
48         /// </para>
49         /// <para></para>
50         /// </summary>
51         protected readonly TLinkAddress Continue;
52
53         /// <summary>
54         /// <para>
55         /// The links.
56         /// </para>
57         /// <para></para>
58         /// </summary>
59         protected readonly byte* Links;
60
61         /// <summary>
62         /// <para>
63         /// The header.
64         /// </para>
65         /// <para></para>
66         /// </summary>
67         protected readonly byte* Header;
68
69         /// <summary>
70         /// <para>
71         /// Initializes a new <see cref="LinksAvlBalancedTreeMethodsBase"/> instance.
72         /// </para>
73         /// <para></para>
74         /// </summary>
75         /// <param name="constants">
76         /// <para>A constants.</para>
77         /// <para></para>
78         /// </param>
79         /// <param name="links">
80         /// <para>A links.</para>
81         /// <para></para>
82         /// </param>

```



```

73     /// </param>
74     /// <param name="header">
75     /// <para>A header.</para>
76     /// <para></para>
77     /// </param>
78     [MethodImpl(MethodImplOptions.AggressiveInlining)]
79     protected LinksAvlBalancedTreeMethodsBase(LinksConstants<TLinkAddress> constants, byte*
80     ↪ links, byte* header)
81     {
82         Links = links;
83         Header = header;
84         Break = constants.Break;
85         Continue = constants.Continue;
86     }
87     /// <summary>
88     /// <para>
89     /// Gets the tree root.
90     /// </para>
91     /// <para></para>
92     /// </summary>
93     /// <returns>
94     /// <para>The link</para>
95     /// <para></para>
96     /// </returns>
97     [MethodImpl(MethodImplOptions.AggressiveInlining)]
98     protected abstract TLinkAddress GetTreeRoot();
99
100    /// <summary>
101    /// <para>
102    /// Gets the base part value using the specified link.
103    /// </para>
104    /// <para></para>
105    /// </summary>
106    /// <param name="link">
107    /// <para>The link.</para>
108    /// <para></para>
109    /// </param>
110    /// <returns>
111    /// <para>The link</para>
112    /// <para></para>
113    /// </returns>
114    [MethodImpl(MethodImplOptions.AggressiveInlining)]
115    protected abstract TLinkAddress GetBasePartValue(TLinkAddress link);
116
117    /// <summary>
118    /// <para>
119    /// Determines whether this instance first is to the right of second.
120    /// </para>
121    /// <para></para>
122    /// </summary>
123    /// <param name="source">
124    /// <para>The source.</para>
125    /// <para></para>
126    /// </param>
127    /// <param name="target">
128    /// <para>The target.</para>
129    /// <para></para>
130    /// </param>
131    /// <param name="rootSource">
132    /// <para>The root source.</para>
133    /// <para></para>
134    /// </param>
135    /// <param name="rootTarget">
136    /// <para>The root target.</para>
137    /// <para></para>
138    /// </param>
139    /// <returns>
140    /// <para>The bool</para>
141    /// <para></para>
142    /// </returns>
143    [MethodImpl(MethodImplOptions.AggressiveInlining)]
144    protected abstract bool FirstIsToTheRightOfSecond(TLinkAddress source, TLinkAddress
145    ↪ target, TLinkAddress rootSource, TLinkAddress rootTarget);
146
147    /// <summary>
148    /// <para>
149    /// Determines whether this instance first is to the left of second.

```

```

149    /// </para>
150    /// <para></para>
151    /// </summary>
152    /// <param name="source">
153    /// <para>The source.</para>
154    /// <para></para>
155    /// </param>
156    /// <param name="target">
157    /// <para>The target.</para>
158    /// <para></para>
159    /// </param>
160    /// <param name="rootSource">
161    /// <para>The root source.</para>
162    /// <para></para>
163    /// </param>
164    /// <param name="rootTarget">
165    /// <para>The root target.</para>
166    /// <para></para>
167    /// </param>
168    /// <returns>
169    /// <para>The bool</para>
170    /// <para></para>
171    /// </returns>
172    [MethodImpl(MethodImplOptions.AggressiveInlining)]
173    protected abstract bool FirstIsToTheLeftOfSecond(TLinkAddress source, TLinkAddress
    ↪ target, TLinkAddress rootSource, TLinkAddress rootTarget);
174
175    /// <summary>
176    /// <para>
177    /// Gets the header reference.
178    /// </para>
179    /// <para></para>
180    /// </summary>
181    /// <returns>
182    /// <para>A ref links header of t link</para>
183    /// <para></para>
184    /// </returns>
185    [MethodImpl(MethodImplOptions.AggressiveInlining)]
186    protected virtual ref LinksHeader<TLinkAddress> GetHeaderReference() => ref
    ↪ AsRef<LinksHeader<TLinkAddress>>(Header);
187
188    /// <summary>
189    /// <para>
190    /// Gets the link reference using the specified link.
191    /// </para>
192    /// <para></para>
193    /// </summary>
194    /// <param name="link">
195    /// <para>The link.</para>
196    /// <para></para>
197    /// </param>
198    /// <returns>
199    /// <para>A ref raw link of t link</para>
200    /// <para></para>
201    /// </returns>
202    [MethodImpl(MethodImplOptions.AggressiveInlining)]
203    protected virtual ref RawLink<TLinkAddress> GetLinkReference(TLinkAddress link) => ref
    ↪ AsRef<RawLink<TLinkAddress>>(Links + (RawLink<TLinkAddress>.SizeInBytes *
    ↪ _addressToInt64Converter.Convert(link)));
204
205    /// <summary>
206    /// <para>
207    /// Gets the link values using the specified link index.
208    /// </para>
209    /// <para></para>
210    /// </summary>
211    /// <param name="linkIndex">
212    /// <para>The link index.</para>
213    /// <para></para>
214    /// </param>
215    /// <returns>
216    /// <para>A list of t link</para>
217    /// <para></para>
218    /// </returns>
219    [MethodImpl(MethodImplOptions.AggressiveInlining)]
220    protected virtual IList<TLinkAddress>? GetLinkValues(TLinkAddress linkIndex)
221    {

```

```

222     ref var link = ref GetLinkReference(linkIndex);
223     return new Link<TLinkAddress>(linkIndex, link.Source, link.Target);
224 }
225
226 /// <summary>
227 /// <para>
228 /// Determines whether this instance first is to the left of second.
229 /// </para>
230 /// <para></para>
231 /// </summary>
232 /// <param name="first">
233 /// <para>The first.</para>
234 /// <para></para>
235 /// </param>
236 /// <param name="second">
237 /// <para>The second.</para>
238 /// <para></para>
239 /// </param>
240 /// <returns>
241 /// <para>The bool</para>
242 /// <para></para>
243 /// </returns>
244 [MethodImpl(MethodImplOptions.AggressiveInlining)]
245 protected override bool FirstIsToLeftOfSecond(TLinkAddress first, TLinkAddress second)
246 {
247     ref var firstLink = ref GetLinkReference(first);
248     ref var secondLink = ref GetLinkReference(second);
249     return FirstIsToLeftOfSecond(firstLink.Source, firstLink.Target,
250         ↪ secondLink.Source, secondLink.Target);
251 }
252
253 /// <summary>
254 /// <para>
255 /// Determines whether this instance first is to the right of second.
256 /// </para>
257 /// <para></para>
258 /// </summary>
259 /// <param name="first">
260 /// <para>The first.</para>
261 /// <para></para>
262 /// </param>
263 /// <param name="second">
264 /// <para>The second.</para>
265 /// <para></para>
266 /// </param>
267 /// <returns>
268 /// <para>The bool</para>
269 /// <para></para>
270 /// </returns>
271 [MethodImpl(MethodImplOptions.AggressiveInlining)]
272 protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
273     ↪ second)
274 {
275     ref var firstLink = ref GetLinkReference(first);
276     ref var secondLink = ref GetLinkReference(second);
277     return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
278         ↪ secondLink.Source, secondLink.Target);
279 }
280
281 /// <summary>
282 /// <para>
283 /// Gets the size value using the specified value.
284 /// </para>
285 /// <para></para>
286 /// </summary>
287 /// <param name="value">
288 /// <para>The value.</para>
289 /// <para></para>
290 /// </param>
291 /// <returns>
292 /// <para>The link</para>
293 /// <para></para>
294 /// </returns>
295 [MethodImpl(MethodImplOptions.AggressiveInlining)]
296 protected virtual TLinkAddress GetSizeValue(TLinkAddress value) =>
297     ↪ Bit<TLinkAddress>.PartialRead(value, 5, -5);
298
299 /// <summary>

```

```

296    /// <para>
297    /// Sets the size value using the specified stored value.
298    /// </para>
299    /// <para></para>
300    /// </summary>
301    /// <param name="storedValue">
302    /// <para>The stored value.</para>
303    /// <para></para>
304    /// </param>
305    /// <param name="size">
306    /// <para>The size.</para>
307    /// <para></para>
308    /// </param>
309    [MethodImpl(MethodImplOptions.AggressiveInlining)]
310    protected virtual void SetSizeValue(ref TLinkAddress storedValue, TLinkAddress size) =>
311    ↪ storedValue = Bit<TLinkAddress>.PartialWrite(storedValue, size, 5, -5);
312
313    /// <summary>
314    /// <para>
315    /// Determines whether this instance get left is child value.
316    /// </para>
317    /// <para></para>
318    /// </summary>
319    /// <param name="value">
320    /// <para>The value.</para>
321    /// <para></para>
322    /// </param>
323    /// <returns>
324    /// <para>The bool</para>
325    /// <para></para>
326    /// </returns>
327    [MethodImpl(MethodImplOptions.AggressiveInlining)]
328    protected virtual bool GetLeftIsChildValue(TLinkAddress value)
329    {
330        unchecked
331        {
332            return _addressToBoolConverter.Convert(Bit<TLinkAddress>.PartialRead(value, 4,
333            ↪ 1));
334            //return !EqualityComparer.Equals(Bit<TLinkAddress>.PartialRead(value, 4, 1),
335            ↪ default);
336        }
337    }
338
339    /// <summary>
340    /// <para>
341    /// Sets the left is child value using the specified stored value.
342    /// </para>
343    /// <para></para>
344    /// </summary>
345    /// <param name="storedValue">
346    /// <para>The stored value.</para>
347    /// <para></para>
348    /// </param>
349    /// <param name="value">
350    /// <para>The value.</para>
351    /// <para></para>
352    /// </param>
353    [MethodImpl(MethodImplOptions.AggressiveInlining)]
354    protected virtual void SetLeftIsChildValue(ref TLinkAddress storedValue, bool value)
355    {
356        unchecked
357        {
358            var previousValue = storedValue;
359            var modified = Bit<TLinkAddress>.PartialWrite(previousValue,
360            ↪ _boolToAddressConverter.Convert(value), 4, 1);
361            storedValue = modified;
362        }
363    }
364
365    /// <summary>
366    /// <para>
367    /// Determines whether this instance get right is child value.
368    /// </para>
369    /// <para></para>
370    /// </summary>
371    /// <param name="value">
372    /// <para>The value.</para>
373    /// <para></para>
374    /// </param>

```

```

370 /// </param>
371 /// <returns>
372 /// <para>The bool</para>
373 /// <para></para>
374 /// </returns>
375 [MethodImpl(MethodImplOptions.AggressiveInlining)]
376 protected virtual bool GetRightIsChildValue(TLinkAddress value)
377 {
378     unchecked
379     {
380         return _addressToBoolConverter.Convert(Bit<TLinkAddress>.PartialRead(value, 3,
381             ↪ 1));
382         //return !EqualityComparer.Equals(Bit<TLinkAddress>.PartialRead(value, 3, 1),
383             ↪ default);
384     }
385 }
386
387 /// <summary>
388 /// <para>
389 /// Sets the right is child value using the specified stored value.
390 /// </para>
391 /// <para></para>
392 /// </summary>
393 /// <param name="storedValue">
394 /// <para>The stored value.</para>
395 /// <para></para>
396 /// </param>
397 /// <param name="value">
398 /// <para>The value.</para>
399 /// <para></para>
400 /// </param>
401 [MethodImpl(MethodImplOptions.AggressiveInlining)]
402 protected virtual void SetRightIsChildValue(ref TLinkAddress storedValue, bool value)
403 {
404     unchecked
405     {
406         var previousValue = storedValue;
407         var modified = Bit<TLinkAddress>.PartialWrite(previousValue,
408             ↪ _boolToAddressConverter.Convert(value), 3, 1);
409         storedValue = modified;
410     }
411 }
412
413 /// <summary>
414 /// <para>
415 /// Determines whether this instance is child.
416 /// </para>
417 /// <para></para>
418 /// </summary>
419 /// <param name="parent">
420 /// <para>The parent.</para>
421 /// <para></para>
422 /// </param>
423 /// <param name="possibleChild">
424 /// <para>The possible child.</para>
425 /// <para></para>
426 /// </param>
427 /// <returns>
428 /// <para>The bool</para>
429 /// <para></para>
430 /// </returns>
431 [MethodImpl(MethodImplOptions.AggressiveInlining)]
432 protected bool IsChild(TLinkAddress parent, TLinkAddress possibleChild)
433 {
434     var parentSize = GetSize(parent);
435     var childSize = GetSizeOrZero(possibleChild);
436     return GreaterThanZero(childSize) && LessOrEqualThan(childSize, parentSize);
437 }
438
439 /// <summary>
440 /// <para>
441 /// Gets the balance value using the specified stored value.
442 /// </para>
443 /// <para></para>
444 /// </summary>
445 /// <param name="storedValue">
446 /// <para>The stored value.</para>
447 /// <para></para>

```

```

445 /// </param>
446 /// <returns>
447 /// <para>The sbyte</para>
448 /// <para></para>
449 /// </returns>
450 [MethodImpl(MethodImplOptions.AggressiveInlining)]
451 protected virtual sbyte GetBalanceValue(TLinkAddress storedValue)
452 {
453     unchecked
454     {
455         var value =
456             ↪ _addressToInt32Converter.Convert(Bit<TLinkAddress>.PartialRead(storedValue,
457             ↪ 0, 3));
458         value |= 0xF8 * ((value & 4) >> 2); // if negative, then continue ones to the
459             ↪ end of sbyte
460         return (sbyte)value;
461     }
462 }
463
464 /// <summary>
465 /// <para>
466 /// Sets the balance value using the specified stored value.
467 /// </para>
468 /// <para></para>
469 /// </summary>
470 /// <param name="storedValue">
471 /// <para>The stored value.</para>
472 /// <para></para>
473 /// </param>
474 /// <param name="value">
475 /// <para>The value.</para>
476 /// <para></para>
477 /// </param>
478 [MethodImpl(MethodImplOptions.AggressiveInlining)]
479 protected virtual void SetBalanceValue(ref TLinkAddress storedValue, sbyte value)
480 {
481     unchecked
482     {
483         var packagedValue = _int32ToAddressConverter.Convert((byte)value >> 5 & 4 |
484             ↪ value & 3);
485         var modified = Bit<TLinkAddress>.PartialWrite(storedValue, packagedValue, 0, 3);
486         storedValue = modified;
487     }
488 }
489
490 /// <summary>
491 /// <para>
492 /// The zero.
493 /// </para>
494 /// <para></para>
495 /// </summary>
496 public TLinkAddress this[TLinkAddress index]
497 {
498     [MethodImpl(MethodImplOptions.AggressiveInlining)]
499     get
500     {
501         var root = GetTreeRoot();
502         if (GreaterOrEqualThan(index, GetSize(root)))
503         {
504             return Zero;
505         }
506         while (!EqualToZero(root))
507         {
508             var left = GetLeftOrDefault(root);
509             var leftSize = GetSizeOrZero(left);
510             if (LessThan(index, leftSize))
511             {
512                 root = left;
513                 continue;
514             }
515             if (AreEqual(index, leftSize))
516             {
517                 return root;
518             }
519             root = GetRightOrDefault(root);
520             index = Subtract(index, Increment(leftSize));
521         }
522         return Zero; // TODO: Impossible situation exception (only if tree structure
523             ↪ broken)
524     }
525 }

```

```

519     }
520 }
521
522 /// <summary>
523 /// Выполняет поиск и возвращает индекс связи с указанными Source (началом) и Target
524   ↳ (концом).
525 /// </summary>
526 /// <param name="source">Индекс связи, которая является началом на искомой связи.</param>
527 /// <param name="target">Индекс связи, которая является концом на искомой связи.</param>
528 /// <returns>Индекс искомой связи.</returns>
529 [MethodImpl(MethodImplOptions.AggressiveInlining)]
530 public TLinkAddress Search(TLinkAddress source, TLinkAddress target)
531 {
532     var root = GetTreeRoot();
533     while (!EqualToZero(root))
534     {
535         ref var rootLink = ref GetLinkReference(root);
536         var rootSource = rootLink.Source;
537         var rootTarget = rootLink.Target;
538         if (FirstIsToTheLeftOfSecond(source, target, rootSource, rootTarget)) //
539             ↳ node.Key < root.Key
540         {
541             root = GetLeftOrDefault(root);
542         }
543         else if (FirstIsToTheRightOfSecond(source, target, rootSource, rootTarget)) //
544             ↳ node.Key > root.Key
545         {
546             root = GetRightOrDefault(root);
547         }
548         else // node.Key == root.Key
549         {
550             return root;
551         }
552     }
553     return Zero;
554 }
555
556 // TODO: Return indices range instead of references count
557 /// <summary>
558 /// <para>
559 /// Counts the usages using the specified link.
560 /// </para>
561 /// <para></para>
562 /// </summary>
563 /// <param name="link">
564 /// <para>The link.</para>
565 /// <para></para>
566 /// </param>
567 /// <returns>
568 /// <para>The link</para>
569 /// <para></para>
570 /// </returns>
571 [MethodImpl(MethodImplOptions.AggressiveInlining)]
572 public TLinkAddress CountUsages(TLinkAddress link)
573 {
574     var root = GetTreeRoot();
575     var total = GetSize(root);
576     var totalRightIgnore = Zero;
577     while (!EqualToZero(root))
578     {
579         var @base = GetBasePartValue(root);
580         if (LessOrEqualThan(@base, link))
581         {
582             root = GetRightOrDefault(root);
583         }
584         else
585         {
586             totalRightIgnore = Add(totalRightIgnore, Increment(GetRightSize(root)));
587             root = GetLeftOrDefault(root);
588         }
589     }
590     root = GetTreeRoot();
591     var totalLeftIgnore = Zero;
592     while (!EqualToZero(root))
593     {
594         var @base = GetBasePartValue(root);
595         if (GreaterOrEqualThan(@base, link))
596         {

```

```

594         root = GetLeftOrDefault(root);
595     }
596     else
597     {
598         totalLeftIgnore = Add(totalLeftIgnore, Increment(GetLeftSize(root)));
599
600         root = GetRightOrDefault(root);
601     }
602 }
603 return Subtract(Subtract(total, totalRightIgnore), totalLeftIgnore);
604 }
605
606 /// <summary>
607 /// <para>
608 /// Eaches the usage using the specified link.
609 /// </para>
610 /// <para></para>
611 /// </summary>
612 /// <param name="link">
613 /// <para>The link.</para>
614 /// <para></para>
615 /// </param>
616 /// <param name="handler">
617 /// <para>The handler.</para>
618 /// <para></para>
619 /// </param>
620 /// <returns>
621 /// <para>The continue.</para>
622 /// <para></para>
623 /// </returns>
624 [MethodImpl(MethodImplOptions.AggressiveInlining)]
625 public TLinkAddress EachUsage(TLinkAddress link, ReadHandler<TLinkAddress>? handler)
626 {
627     var root = GetTreeRoot();
628     if (EqualToZero(root))
629     {
630         return Continue;
631     }
632     TLinkAddress first = Zero, current = root;
633     while (!EqualToZero(current))
634     {
635         var @base = GetBasePartValue(current);
636         if (GreaterOrEqualThan(@base, link))
637         {
638             if (AreEqual(@base, link))
639             {
640                 first = current;
641             }
642             current = GetLeftOrDefault(current);
643         }
644         else
645         {
646             current = GetRightOrDefault(current);
647         }
648     }
649     if (!EqualToZero(first))
650     {
651         current = first;
652         while (true)
653         {
654             if (AreEqual(handler(GetLinkValues(current)), Break))
655             {
656                 return Break;
657             }
658             current = GetNext(current);
659             if (EqualToZero(current) || !AreEqual(GetBasePartValue(current), link))
660             {
661                 break;
662             }
663         }
664     }
665     return Continue;
666 }
667
668 /// <summary>
669 /// <para>
670 /// Prints the node value using the specified node.
671 /// </para>
672 /// <para></para>

```



```

673     /// </summary>
674     /// <param name="node">
675     /// <para>The node.</para>
676     /// <para></para>
677     /// </param>
678     /// <param name="sb">
679     /// <para>The sb.</para>
680     /// <para></para>
681     /// </param>
682     [MethodImpl(MethodImplOptions.AggressiveInlining)]
683     protected override void PrintNodeValue(TLinkAddress node, StringBuilder sb)
684     {
685         ref var link = ref GetLinkReference(node);
686         sb.Append(' ');
687         sb.Append(link.Source);
688         sb.Append('-');
689         sb.Append('>');
690         sb.Append(link.Target);
691     }
692 }
693 }

```

1.81 ./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksRecursionlessSizeBalancedTreeMethodsBase

```

1  using System;
2  using System.Text;
3  using System.Collections.Generic;
4  using System.Runtime.CompilerServices;
5  using Platform.Collections.Methods.Trees;
6  using Platform.Converters;
7  using Platform.Delegates;
8  using static System.Runtime.CompilerServices.Unsafe;
9
10 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
11
12 namespace Platform.Data.Doublets.Memory.United.Generic
13 {
14     /// <summary>
15     /// <para>
16     /// Represents the links recursionless size balanced tree methods base.
17     /// </para>
18     /// <para></para>
19     /// </summary>
20     /// <seealso cref="RecursionlessSizeBalancedTreeMethods{TLinkAddress}"/>
21     /// <seealso cref="ILinksTreeMethods{TLinkAddress}"/>
22     public unsafe abstract class LinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress> :
23     ↪ RecursionlessSizeBalancedTreeMethods<TLinkAddress>, ILinksTreeMethods<TLinkAddress>
24     {
25         private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
26         ↪ = UncheckedConverter<TLinkAddress, long>.Default;
27
28         /// <summary>
29         /// <para>
30         /// The break.
31         /// </para>
32         /// <para></para>
33         /// </summary>
34         protected readonly TLinkAddress Break;
35
36         /// <summary>
37         /// <para>
38         /// The continue.
39         /// </para>
40         /// <para></para>
41         /// </summary>
42         protected readonly TLinkAddress Continue;
43
44         /// <summary>
45         /// <para>
46         /// The links.
47         /// </para>
48         /// <para></para>
49         /// </summary>
50         protected readonly byte* Links;
51
52         /// <summary>
53         /// <para>
54         /// The header.
55         /// </para>
56         /// <para></para>
57         /// </summary>
58         protected readonly byte* Header;
59     }
60 }

```

```

55     /// <summary>
56     /// <para>
57     /// Initializes a new <see cref="LinksRecursionlessSizeBalancedTreeMethodsBase"/>
    ↪ instance.
58     /// </para>
59     /// <para></para>
60     /// </summary>
61     /// <param name="constants">
62     /// <para>A constants.</para>
63     /// <para></para>
64     /// </param>
65     /// <param name="links">
66     /// <para>A links.</para>
67     /// <para></para>
68     /// </param>
69     /// <param name="header">
70     /// <para>A header.</para>
71     /// <para></para>
72     /// </param>
73     [MethodImpl(MethodImplOptions.AggressiveInlining)]
74     protected LinksRecursionlessSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress>
    ↪ constants, byte* links, byte* header)
75     {
76         Links = links;
77         Header = header;
78         Break = constants.Break;
79         Continue = constants.Continue;
80     }
81
82     /// <summary>
83     /// <para>
84     /// Gets the tree root.
85     /// </para>
86     /// <para></para>
87     /// </summary>
88     /// <returns>
89     /// <para>The link</para>
90     /// <para></para>
91     /// </returns>
92     [MethodImpl(MethodImplOptions.AggressiveInlining)]
93     protected abstract TLinkAddress GetTreeRoot();
94
95     /// <summary>
96     /// <para>
97     /// Gets the base part value using the specified link.
98     /// </para>
99     /// <para></para>
100    /// </summary>
101    /// <param name="link">
102    /// <para>The link.</para>
103    /// <para></para>
104    /// </param>
105    /// <returns>
106    /// <para>The link</para>
107    /// <para></para>
108    /// </returns>
109    [MethodImpl(MethodImplOptions.AggressiveInlining)]
110    protected abstract TLinkAddress GetBasePartValue(TLinkAddress link);
111
112    /// <summary>
113    /// <para>
114    /// Determines whether this instance first is to the right of second.
115    /// </para>
116    /// <para></para>
117    /// </summary>
118    /// <param name="source">
119    /// <para>The source.</para>
120    /// <para></para>
121    /// </param>
122    /// <param name="target">
123    /// <para>The target.</para>
124    /// <para></para>
125    /// </param>
126    /// <param name="rootSource">
127    /// <para>The root source.</para>
128    /// <para></para>
129    /// </param>
130    /// <param name="rootTarget">

```

```

131    /// <para>The root target.</para>
132    /// <para></para>
133    /// </param>
134    /// <returns>
135    /// <para>The bool</para>
136    /// <para></para>
137    /// </returns>
138    [MethodImpl(MethodImplOptions.AggressiveInlining)]
139    protected abstract bool FirstIsToTheRightOfSecond(TLinkAddress source, TLinkAddress
    ↪ target, TLinkAddress rootSource, TLinkAddress rootTarget);

140
141    /// <summary>
142    /// <para>
143    /// Determines whether this instance first is to the left of second.
144    /// </para>
145    /// <para></para>
146    /// </summary>
147    /// <param name="source">
148    /// <para>The source.</para>
149    /// <para></para>
150    /// </param>
151    /// <param name="target">
152    /// <para>The target.</para>
153    /// <para></para>
154    /// </param>
155    /// <param name="rootSource">
156    /// <para>The root source.</para>
157    /// <para></para>
158    /// </param>
159    /// <param name="rootTarget">
160    /// <para>The root target.</para>
161    /// <para></para>
162    /// </param>
163    /// <returns>
164    /// <para>The bool</para>
165    /// <para></para>
166    /// </returns>
167    [MethodImpl(MethodImplOptions.AggressiveInlining)]
168    protected abstract bool FirstIsToTheLeftOfSecond(TLinkAddress source, TLinkAddress
    ↪ target, TLinkAddress rootSource, TLinkAddress rootTarget);

169
170    /// <summary>
171    /// <para>
172    /// Gets the header reference.
173    /// </para>
174    /// <para></para>
175    /// </summary>
176    /// <returns>
177    /// <para>A ref links header of t link</para>
178    /// <para></para>
179    /// </returns>
180    [MethodImpl(MethodImplOptions.AggressiveInlining)]
181    protected virtual ref LinksHeader<TLinkAddress> GetHeaderReference() => ref
    ↪ AsRef<LinksHeader<TLinkAddress>>(Header);

182
183    /// <summary>
184    /// <para>
185    /// Gets the link reference using the specified link.
186    /// </para>
187    /// <para></para>
188    /// </summary>
189    /// <param name="link">
190    /// <para>The link.</para>
191    /// <para></para>
192    /// </param>
193    /// <returns>
194    /// <para>A ref raw link of t link</para>
195    /// <para></para>
196    /// </returns>
197    [MethodImpl(MethodImplOptions.AggressiveInlining)]
198    protected virtual ref RawLink<TLinkAddress> GetLinkReference(TLinkAddress link) => ref
    ↪ AsRef<RawLink<TLinkAddress>>(Links + (RawLink<TLinkAddress>.SizeInBytes *
    ↪ _addressToInt64Converter.Convert(link)));

199
200    /// <summary>
201    /// <para>
202    /// Gets the link values using the specified link index.

```

```

203 /// </para>
204 /// <para></para>
205 /// </summary>
206 /// <param name="linkIndex">
207 /// <para>The link index.</para>
208 /// <para></para>
209 /// </param>
210 /// <returns>
211 /// <para>A list of t link</para>
212 /// <para></para>
213 /// </returns>
214 [MethodImpl(MethodImplOptions.AggressiveInlining)]
215 protected virtual IList<TLinkAddress>? GetLinkValues(TLinkAddress linkIndex)
216 {
217     ref var link = ref GetLinkReference(linkIndex);
218     return new Link<TLinkAddress>(linkIndex, link.Source, link.Target);
219 }
220
221 /// <summary>
222 /// <para>
223 /// Determines whether this instance first is to the left of second.
224 /// </para>
225 /// <para></para>
226 /// </summary>
227 /// <param name="first">
228 /// <para>The first.</para>
229 /// <para></para>
230 /// </param>
231 /// <param name="second">
232 /// <para>The second.</para>
233 /// <para></para>
234 /// </param>
235 /// <returns>
236 /// <para>The bool</para>
237 /// <para></para>
238 /// </returns>
239 [MethodImpl(MethodImplOptions.AggressiveInlining)]
240 protected override bool FirstIsToLeftOfSecond(TLinkAddress first, TLinkAddress second)
241 {
242     ref var firstLink = ref GetLinkReference(first);
243     ref var secondLink = ref GetLinkReference(second);
244     return FirstIsToLeftOfSecond(firstLink.Source, firstLink.Target,
245         ↪ secondLink.Source, secondLink.Target);
246 }
247
248 /// <summary>
249 /// <para>
250 /// Determines whether this instance first is to the right of second.
251 /// </para>
252 /// <para></para>
253 /// </summary>
254 /// <param name="first">
255 /// <para>The first.</para>
256 /// <para></para>
257 /// </param>
258 /// <param name="second">
259 /// <para>The second.</para>
260 /// <para></para>
261 /// </param>
262 /// <returns>
263 /// <para>The bool</para>
264 /// <para></para>
265 /// </returns>
266 [MethodImpl(MethodImplOptions.AggressiveInlining)]
267 protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
268     ↪ second)
269 {
270     ref var firstLink = ref GetLinkReference(first);
271     ref var secondLink = ref GetLinkReference(second);
272     return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
273         ↪ secondLink.Source, secondLink.Target);
274 }
275
276 /// <summary>
277 /// <para>
278 /// The zero.
279 /// </para>
280 /// <para></para>

```

```

278 /// </summary>
279 public TLinkAddress this[TLinkAddress index]
280 {
281     [MethodImpl(MethodImplOptions.AggressiveInlining)]
282     get
283     {
284         var root = GetTreeRoot();
285         if (GreaterOrEqualThan(index, GetSize(root)))
286         {
287             return Zero;
288         }
289         while (!EqualToZero(root))
290         {
291             var left = GetLeftOrDefault(root);
292             var leftSize = GetSizeOrZero(left);
293             if (LessThan(index, leftSize))
294             {
295                 root = left;
296                 continue;
297             }
298             if (AreEqual(index, leftSize))
299             {
300                 return root;
301             }
302             root = GetRightOrDefault(root);
303             index = Subtract(index, Increment(leftSize));
304         }
305         return Zero; // TODO: Impossible situation exception (only if tree structure
306                     ↪ broken)
307     }
308 }
309
310 /// <summary>
311 /// Выполняет поиск и возвращает индекс связи с указанными Source (началом) и Target
312 /// ↪ (концом).
313 /// </summary>
314 /// <param name="source">Индекс связи, которая является началом на искомой связи.</param>
315 /// <param name="target">Индекс связи, которая является концом на искомой связи.</param>
316 /// <returns>Индекс искомой связи.</returns>
317 [MethodImpl(MethodImplOptions.AggressiveInlining)]
318 public TLinkAddress Search(TLinkAddress source, TLinkAddress target)
319 {
320     var root = GetTreeRoot();
321     while (!EqualToZero(root))
322     {
323         ref var rootLink = ref GetLinkReference(root);
324         var rootSource = rootLink.Source;
325         var rootTarget = rootLink.Target;
326         if (FirstIsToTheLeftOfSecond(source, target, rootSource, rootTarget)) //
327             ↪ node.Key < root.Key
328         {
329             root = GetLeftOrDefault(root);
330         }
331         else if (FirstIsToTheRightOfSecond(source, target, rootSource, rootTarget)) //
332             ↪ node.Key > root.Key
333         {
334             root = GetRightOrDefault(root);
335         }
336         else // node.Key == root.Key
337         {
338             return root;
339         }
340     }
341     return Zero;
342 }
343
344 // TODO: Return indices range instead of references count
345 /// <summary>
346 /// <para>
347 /// Counts the usages using the specified link.
348 /// </para>
349 /// <para></para>
350 /// </summary>
351 /// <param name="link">
352 /// <para>The link.</para>
353 /// <para></para>
354 /// </param>
355 /// <returns>

```

```

352 /// <para>The link</para>
353 /// <para></para>
354 /// </returns>
355 [MethodImpl(MethodImplOptions.AggressiveInlining)]
356 public TLinkAddress CountUsages(TLinkAddress link)
357 {
358     var root = GetTreeRoot();
359     var total = GetSize(root);
360     var totalRightIgnore = Zero;
361     while (!EqualToZero(root))
362     {
363         var @base = GetBasePartValue(root);
364         if (LessOrEqualThan(@base, link))
365         {
366             root = GetRightOrDefault(root);
367         }
368         else
369         {
370             totalRightIgnore = Add(totalRightIgnore, Increment(GetRightSize(root)));
371             root = GetLeftOrDefault(root);
372         }
373     }
374     root = GetTreeRoot();
375     var totalLeftIgnore = Zero;
376     while (!EqualToZero(root))
377     {
378         var @base = GetBasePartValue(root);
379         if (GreaterOrEqualThan(@base, link))
380         {
381             root = GetLeftOrDefault(root);
382         }
383         else
384         {
385             totalLeftIgnore = Add(totalLeftIgnore, Increment(GetLeftSize(root)));
386             root = GetRightOrDefault(root);
387         }
388     }
389     return Subtract(Subtract(total, totalRightIgnore), totalLeftIgnore);
390 }
391
392 /// <summary>
393 /// <para>
394 /// Eaches the usage using the specified base.
395 /// </para>
396 /// <para></para>
397 /// </summary>
398 /// <param name="@base">
399 /// <para>The base.</para>
400 /// <para></para>
401 /// </param>
402 /// <param name="handler">
403 /// <para>The handler.</para>
404 /// <para></para>
405 /// </param>
406 /// <returns>
407 /// <para>The link</para>
408 /// <para></para>
409 /// </returns>
410 [MethodImpl(MethodImplOptions.AggressiveInlining)]
411 public TLinkAddress EachUsage(TLinkAddress @base, ReadHandler<TLinkAddress>? handler) =>
412     ↳ EachUsageCore(@base, GetTreeRoot(), handler);
413
414 // TODO: 1. Move target, handler to separate object. 2. Use stack or walker 3. Use
415 ↳ low-level MSIL stack.
416 [MethodImpl(MethodImplOptions.AggressiveInlining)]
417 private TLinkAddress EachUsageCore(TLinkAddress @base, TLinkAddress link,
418     ↳ ReadHandler<TLinkAddress>? handler)
419 {
420     var @continue = Continue;
421     if (EqualToZero(link))
422     {
423         return @continue;
424     }
425     var linkBasePart = GetBasePartValue(link);
426     var @break = Break;
427     if (GreaterThan(linkBasePart, @base))
428     {
429         if (AreEqual(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))

```

```

427         {
428             return @break;
429         }
430     }
431     else if (LessThan(linkBasePart, @base))
432     {
433         if (AreEqual(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
434         {
435             return @break;
436         }
437     }
438     else //if (linkBasePart == @base)
439     {
440         if (AreEqual(handler(GetLinkValues(link)), @break))
441         {
442             return @break;
443         }
444         if (AreEqual(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))
445         {
446             return @break;
447         }
448         if (AreEqual(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
449         {
450             return @break;
451         }
452     }
453     return @continue;
454 }
455
456 /// <summary>
457 /// <para>
458 /// Prints the node value using the specified node.
459 /// </para>
460 /// <para></para>
461 /// </summary>
462 /// <param name="node">
463 /// <para>The node.</para>
464 /// <para></para>
465 /// </param>
466 /// <param name="sb">
467 /// <para>The sb.</para>
468 /// <para></para>
469 /// </param>
470 [MethodImpl(MethodImplOptions.AggressiveInlining)]
471 protected override void PrintNodeValue(TLinkAddress node, StringBuilder sb)
472 {
473     ref var link = ref GetLinkReference(node);
474     sb.Append(' ');
475     sb.Append(link.Source);
476     sb.Append('-');
477     sb.Append('>');
478     sb.Append(link.Target);
479 }
480 }
481 }

```

1.82 ./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksSizeBalancedTreeMethodsBase.cs

```

1  using System;
2  using System.Text;
3  using System.Collections.Generic;
4  using System.Runtime.CompilerServices;
5  using Platform.Collections.Methods.Trees;
6  using Platform.Converters;
7  using Platform.Delegates;
8  using static System.Runtime.CompilerServices.Unsafe;
9
10 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
11
12 namespace Platform.Data.Doublets.Memory.United.Generic
13 {
14     /// <summary>
15     /// <para>
16     /// Represents the links size balanced tree methods base.
17     /// </para>
18     /// <para></para>
19     /// </summary>
20     /// <seealso cref="SizeBalancedTreeMethods{TLinkAddress}"/>
21     /// <seealso cref="ILinksTreeMethods{TLinkAddress}"/>
22     public unsafe abstract class LinksSizeBalancedTreeMethodsBase<TLinkAddress> :
23         ↳ SizeBalancedTreeMethods<TLinkAddress>, ILinksTreeMethods<TLinkAddress>

```

```

23 {
24     private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
25         ↪ = UncheckedConverter<TLinkAddress, long>.Default;
26
27     /// <summary>
28     /// <para>
29     /// The break.
30     /// </para>
31     /// <para></para>
32     /// </summary>
33     protected readonly TLinkAddress Break;
34     /// <summary>
35     /// <para>
36     /// The continue.
37     /// </para>
38     /// <para></para>
39     /// </summary>
40     protected readonly TLinkAddress Continue;
41     /// <summary>
42     /// <para>
43     /// The links.
44     /// </para>
45     /// <para></para>
46     /// </summary>
47     protected readonly byte* Links;
48     /// <summary>
49     /// <para>
50     /// The header.
51     /// </para>
52     /// <para></para>
53     /// </summary>
54     protected readonly byte* Header;
55
56     /// <summary>
57     /// <para>
58     /// Initializes a new <see cref="LinksSizeBalancedTreeMethodsBase"/> instance.
59     /// </para>
60     /// <para></para>
61     /// </summary>
62     /// <param name="constants">
63     /// <para>A constants.</para>
64     /// <para></para>
65     /// </param>
66     /// <param name="links">
67     /// <para>A links.</para>
68     /// <para></para>
69     /// </param>
70     /// <param name="header">
71     /// <para>A header.</para>
72     /// <para></para>
73     /// </param>
74     [MethodImpl(MethodImplOptions.AggressiveInlining)]
75     protected LinksSizeBalancedTreeMethodsBase(LinksConstants<TLinkAddress> constants, byte*
76         ↪ links, byte* header)
77     {
78         Links = links;
79         Header = header;
80         Break = constants.Break;
81         Continue = constants.Continue;
82     }
83
84     /// <summary>
85     /// <para>
86     /// Gets the tree root.
87     /// </para>
88     /// <para></para>
89     /// </summary>
90     /// <returns>
91     /// <para>The link</para>
92     /// <para></para>
93     /// </returns>
94     [MethodImpl(MethodImplOptions.AggressiveInlining)]
95     protected abstract TLinkAddress GetTreeRoot();
96
97     /// <summary>
98     /// <para>
99     /// Gets the base part value using the specified link.
100    /// </para>
101    /// <para></para>

```



```

100     /// </summary>
101     /// <param name="link">
102     /// <para>The link.</para>
103     /// <para></para>
104     /// </param>
105     /// <returns>
106     /// <para>The link</para>
107     /// <para></para>
108     /// </returns>
109     [MethodImpl(MethodImplOptions.AggressiveInlining)]
110     protected abstract TLinkAddress GetBasePartValue(TLinkAddress link);
111
112     /// <summary>
113     /// <para>
114     /// <para>Determines whether this instance first is to the right of second.
115     /// </para>
116     /// <para></para>
117     /// </summary>
118     /// <param name="source">
119     /// <para>The source.</para>
120     /// <para></para>
121     /// </param>
122     /// <param name="target">
123     /// <para>The target.</para>
124     /// <para></para>
125     /// </param>
126     /// <param name="rootSource">
127     /// <para>The root source.</para>
128     /// <para></para>
129     /// </param>
130     /// <param name="rootTarget">
131     /// <para>The root target.</para>
132     /// <para></para>
133     /// </param>
134     /// <returns>
135     /// <para>The bool</para>
136     /// <para></para>
137     /// </returns>
138     [MethodImpl(MethodImplOptions.AggressiveInlining)]
139     protected abstract bool FirstIsToTheRightOfSecond(TLinkAddress source, TLinkAddress
140     ↪ target, TLinkAddress rootSource, TLinkAddress rootTarget);
141
142     /// <summary>
143     /// <para>
144     /// <para>Determines whether this instance first is to the left of second.
145     /// </para>
146     /// <para></para>
147     /// </summary>
148     /// <param name="source">
149     /// <para>The source.</para>
150     /// <para></para>
151     /// </param>
152     /// <param name="target">
153     /// <para>The target.</para>
154     /// <para></para>
155     /// </param>
156     /// <param name="rootSource">
157     /// <para>The root source.</para>
158     /// <para></para>
159     /// </param>
160     /// <param name="rootTarget">
161     /// <para>The root target.</para>
162     /// <para></para>
163     /// </param>
164     /// <returns>
165     /// <para>The bool</para>
166     /// <para></para>
167     /// </returns>
168     [MethodImpl(MethodImplOptions.AggressiveInlining)]
169     protected abstract bool FirstIsToTheLeftOfSecond(TLinkAddress source, TLinkAddress
170     ↪ target, TLinkAddress rootSource, TLinkAddress rootTarget);
171
172     /// <summary>
173     /// <para>
174     /// <para>Gets the header reference.
175     /// </para>
176     /// <para></para>
177     /// </summary>

```

```

176    /// <returns>
177    /// <para>A ref links header of t link</para>
178    /// <para></para>
179    /// </returns>
180    [MethodImpl(MethodImplOptions.AggressiveInlining)]
181    protected virtual ref LinksHeader<TLinkAddress> GetHeaderReference() => ref
        ↳ AsRef<LinksHeader<TLinkAddress>>(Header);

182
183    /// <summary>
184    /// <para>
185    /// Gets the link reference using the specified link.
186    /// </para>
187    /// <para></para>
188    /// </summary>
189    /// <param name="link">
190    /// <para>The link.</para>
191    /// <para></para>
192    /// </param>
193    /// <returns>
194    /// <para>A ref raw link of t link</para>
195    /// <para></para>
196    /// </returns>
197    [MethodImpl(MethodImplOptions.AggressiveInlining)]
198    protected virtual ref RawLink<TLinkAddress> GetLinkReference(TLinkAddress link) => ref
        ↳ AsRef<RawLink<TLinkAddress>>(Links + (RawLink<TLinkAddress>.SizeInBytes *
        ↳ _addressToInt64Converter.Convert(link)));

199
200    /// <summary>
201    /// <para>
202    /// Gets the link values using the specified link index.
203    /// </para>
204    /// <para></para>
205    /// </summary>
206    /// <param name="linkIndex">
207    /// <para>The link index.</para>
208    /// <para></para>
209    /// </param>
210    /// <returns>
211    /// <para>A list of t link</para>
212    /// <para></para>
213    /// </returns>
214    [MethodImpl(MethodImplOptions.AggressiveInlining)]
215    protected virtual IList<TLinkAddress>? GetLinkValues(TLinkAddress linkIndex)
216    {
217        ref var link = ref GetLinkReference(linkIndex);
218        return new Link<TLinkAddress>(linkIndex, link.Source, link.Target);
219    }

220
221    /// <summary>
222    /// <para>
223    /// Determines whether this instance first is to the left of second.
224    /// </para>
225    /// <para></para>
226    /// </summary>
227    /// <param name="first">
228    /// <para>The first.</para>
229    /// <para></para>
230    /// </param>
231    /// <param name="second">
232    /// <para>The second.</para>
233    /// <para></para>
234    /// </param>
235    /// <returns>
236    /// <para>The bool</para>
237    /// <para></para>
238    /// </returns>
239    [MethodImpl(MethodImplOptions.AggressiveInlining)]
240    protected override bool FirstIsToLeftOfSecond(TLinkAddress first, TLinkAddress second)
241    {
242        ref var firstLink = ref GetLinkReference(first);
243        ref var secondLink = ref GetLinkReference(second);
244        return FirstIsToLeftOfSecond(firstLink.Source, firstLink.Target,
        ↳ secondLink.Source, secondLink.Target);
245    }

246
247    /// <summary>
248    /// <para>
249    /// Determines whether this instance first is to the right of second.

```

```

250     /// </para>
251     /// <para></para>
252     /// </summary>
253     /// <param name="first">
254     /// <para>The first.</para>
255     /// <para></para>
256     /// </param>
257     /// <param name="second">
258     /// <para>The second.</para>
259     /// <para></para>
260     /// </param>
261     /// <returns>
262     /// <para>The bool</para>
263     /// <para></para>
264     /// </returns>
265     [MethodImpl(MethodImplOptions.AggressiveInlining)]
266     protected override bool FirstIsToTheRightOfSecond(TLinkAddress first, TLinkAddress
    ↪ second)
267     {
268         ref var firstLink = ref GetLinkReference(first);
269         ref var secondLink = ref GetLinkReference(second);
270         return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
    ↪ secondLink.Source, secondLink.Target);
271     }
272
273     /// <summary>
274     /// <para>
275     /// The zero.
276     /// </para>
277     /// <para></para>
278     /// </summary>
279     public TLinkAddress this[TLinkAddress index]
280     {
281         [MethodImpl(MethodImplOptions.AggressiveInlining)]
282         get
283         {
284             var root = GetTreeRoot();
285             if (GreaterOrEqualThan(index, GetSize(root)))
286             {
287                 return Zero;
288             }
289             while (!EqualToZero(root))
290             {
291                 var left = GetLeftOrDefault(root);
292                 var leftSize = GetSizeOrZero(left);
293                 if (LessThan(index, leftSize))
294                 {
295                     root = left;
296                     continue;
297                 }
298                 if (AreEqual(index, leftSize))
299                 {
300                     return root;
301                 }
302                 root = GetRightOrDefault(root);
303                 index = Subtract(index, Increment(leftSize));
304             }
305             return Zero; // TODO: Impossible situation exception (only if tree structure
    ↪ broken)
306         }
307     }
308
309     /// <summary>
310     /// Выполняет поиск и возвращает индекс связи с указанными Source (началом) и Target
    ↪ (концом).
311     /// </summary>
312     /// <param name="source">Индекс связи, которая является началом на искомой связи.</param>
313     /// <param name="target">Индекс связи, которая является концом на искомой связи.</param>
314     /// <returns>Индекс искомой связи.</returns>
315     [MethodImpl(MethodImplOptions.AggressiveInlining)]
316     public TLinkAddress Search(TLinkAddress source, TLinkAddress target)
317     {
318         var root = GetTreeRoot();
319         while (!EqualToZero(root))
320         {
321             ref var rootLink = ref GetLinkReference(root);
322             var rootSource = rootLink.Source;
323             var rootTarget = rootLink.Target;

```

```

324         if (FirstIsToTheLeftOfSecond(source, target, rootSource, rootTarget)) //
325             ↪ node.Key < root.Key
326         {
327             root = GetLeftOrDefault(root);
328         }
329         else if (FirstIsToTheRightOfSecond(source, target, rootSource, rootTarget)) //
330             ↪ node.Key > root.Key
331         {
332             root = GetRightOrDefault(root);
333         }
334         else // node.Key == root.Key
335         {
336             return root;
337         }
338     }
339     return Zero;
340 }
341
342 // TODO: Return indices range instead of references count
343 /// <summary>
344 /// <para>
345 /// Counts the usages using the specified link.
346 /// </para>
347 /// <para></para>
348 /// </summary>
349 /// <param name="link">
350 /// <para>The link.</para>
351 /// </param>
352 /// <returns>
353 /// <para>The link</para>
354 /// </returns>
355 [MethodImpl(MethodImplOptions.AggressiveInlining)]
356 public TLinkAddress CountUsages(TLinkAddress link)
357 {
358     var root = GetTreeRoot();
359     var total = GetSize(root);
360     var totalRightIgnore = Zero;
361     while (!EqualToZero(root))
362     {
363         var @base = GetBasePartValue(root);
364         if (LessOrEqualThan(@base, link))
365         {
366             root = GetRightOrDefault(root);
367         }
368         else
369         {
370             totalRightIgnore = Add(totalRightIgnore, Increment(GetRightSize(root)));
371             root = GetLeftOrDefault(root);
372         }
373     }
374     root = GetTreeRoot();
375     var totalLeftIgnore = Zero;
376     while (!EqualToZero(root))
377     {
378         var @base = GetBasePartValue(root);
379         if (GreaterOrEqualThan(@base, link))
380         {
381             root = GetLeftOrDefault(root);
382         }
383         else
384         {
385             totalLeftIgnore = Add(totalLeftIgnore, Increment(GetLeftSize(root)));
386             root = GetRightOrDefault(root);
387         }
388     }
389     return Subtract(Subtract(total, totalRightIgnore), totalLeftIgnore);
390 }
391
392 /// <summary>
393 /// <para>
394 /// Eaches the usage using the specified base.
395 /// </para>
396 /// <para></para>
397 /// </summary>
398 /// <param name="@base">
399 /// <para>The base.</para>

```

```

400    /// <para></para>
401    /// </param>
402    /// <param name="handler">
403    /// <para>The handler.</para>
404    /// <para></para>
405    /// </param>
406    /// <returns>
407    /// <para>The link</para>
408    /// <para></para>
409    /// </returns>
410    [MethodImpl(MethodImplOptions.AggressiveInlining)]
411    public TLinkAddress EachUsage(TLinkAddress @base, ReadHandler<TLinkAddress>? handler) =>
        ↳ EachUsageCore(@base, GetTreeRoot(), handler);

412
413    // TODO: 1. Move target, handler to separate object. 2. Use stack or walker 3. Use
        ↳ low-level MSIL stack.
414    [MethodImpl(MethodImplOptions.AggressiveInlining)]
415    private TLinkAddress EachUsageCore(TLinkAddress @base, TLinkAddress link,
        ↳ ReadHandler<TLinkAddress>? handler)
416    {
417        var @continue = Continue;
418        if (EqualToZero(link))
419        {
420            return @continue;
421        }
422        var linkBasePart = GetBasePartValue(link);
423        var @break = Break;
424        if (GreaterThan(linkBasePart, @base))
425        {
426            if (AreEqual(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))
427            {
428                return @break;
429            }
430        }
431        else if (LessThan(linkBasePart, @base))
432        {
433            if (AreEqual(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
434            {
435                return @break;
436            }
437        }
438        else //if (linkBasePart == @base)
439        {
440            if (AreEqual(handler(GetLinkValues(link)), @break))
441            {
442                return @break;
443            }
444            if (AreEqual(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))
445            {
446                return @break;
447            }
448            if (AreEqual(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
449            {
450                return @break;
451            }
452        }
453        return @continue;
454    }

455
456    /// <summary>
457    /// <para>
458    /// Prints the node value using the specified node.
459    /// </para>
460    /// <para></para>
461    /// </summary>
462    /// <param name="node">
463    /// <para>The node.</para>
464    /// <para></para>
465    /// </param>
466    /// <param name="sb">
467    /// <para>The sb.</para>
468    /// <para></para>
469    /// </param>
470    [MethodImpl(MethodImplOptions.AggressiveInlining)]
471    protected override void PrintNodeValue(TLinkAddress node, StringBuilder sb)
472    {
473        ref var link = ref GetLinkReference(node);
474        sb.Append(' ');

```

```

475         sb.Append(link.Source);
476         sb.Append('-');
477         sb.Append('>');
478         sb.Append(link.Target);
479     }
480 }
481 }

```

1.83 ./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksSourcesAvlBalancedTreeMethods.cs

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.United.Generic
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the links sources avl balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="LinksAvlBalancedTreeMethodsBase{TLinkAddress}"/>
14     public unsafe class LinksSourcesAvlBalancedTreeMethods<TLinkAddress> :
15         ↳ LinksAvlBalancedTreeMethodsBase<TLinkAddress>
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see cref="LinksSourcesAvlBalancedTreeMethods"/> instance.
20         /// </para>
21         /// <para></para>
22         /// </summary>
23         /// <param name="constants">
24         /// <para>A constants.</para>
25         /// <para></para>
26         /// </param>
27         /// <param name="links">
28         /// <para>A links.</para>
29         /// <para></para>
30         /// </param>
31         /// <param name="header">
32         /// <para>A header.</para>
33         /// <para></para>
34         /// </param>
35         [MethodImpl(MethodImplOptions.AggressiveInlining)]
36         public LinksSourcesAvlBalancedTreeMethods(LinksConstants<TLinkAddress> constants, byte*
37             ↳ links, byte* header) : base(constants, links, header) { }
38
39         /// <summary>
40         /// <para>
41         /// Gets the left reference using the specified node.
42         /// </para>
43         /// <para></para>
44         /// </summary>
45         /// <param name="node">
46         /// <para>The node.</para>
47         /// <para></para>
48         /// </param>
49         /// <returns>
50         /// <para>The ref link</para>
51         /// <para></para>
52         /// </returns>
53         [MethodImpl(MethodImplOptions.AggressiveInlining)]
54         protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
55             ↳ GetLinkReference(node).LeftAsSource;
56
57         /// <summary>
58         /// <para>
59         /// Gets the right reference using the specified node.
60         /// </para>
61         /// <para></para>
62         /// </summary>
63         /// <param name="node">
64         /// <para>The node.</para>
65         /// <para></para>
66         /// </param>
67         /// <returns>
68         /// <para>The ref link</para>
69         /// <para></para>
70         /// </returns>

```

```

67     /// </returns>
68     [MethodImpl(MethodImplOptions.AggressiveInlining)]
69     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ GetLinkReference(node).RightAsSource;

70
71     /// <summary>
72     /// <para>
73     /// Gets the left using the specified node.
74     /// </para>
75     /// <para></para>
76     /// </summary>
77     /// <param name="node">
78     /// <para>The node.</para>
79     /// <para></para>
80     /// </param>
81     /// <returns>
82     /// <para>The link</para>
83     /// <para></para>
84     /// </returns>
85     [MethodImpl(MethodImplOptions.AggressiveInlining)]
86     protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ GetLinkReference(node).LeftAsSource;

87
88     /// <summary>
89     /// <para>
90     /// Gets the right using the specified node.
91     /// </para>
92     /// <para></para>
93     /// </summary>
94     /// <param name="node">
95     /// <para>The node.</para>
96     /// <para></para>
97     /// </param>
98     /// <returns>
99     /// <para>The link</para>
100    /// <para></para>
101    /// </returns>
102    [MethodImpl(MethodImplOptions.AggressiveInlining)]
103    protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↪ GetLinkReference(node).RightAsSource;

104
105    /// <summary>
106    /// <para>
107    /// Sets the left using the specified node.
108    /// </para>
109    /// <para></para>
110    /// </summary>
111    /// <param name="node">
112    /// <para>The node.</para>
113    /// <para></para>
114    /// </param>
115    /// <param name="left">
116    /// <para>The left.</para>
117    /// <para></para>
118    /// </param>
119    [MethodImpl(MethodImplOptions.AggressiveInlining)]
120    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
    ↪ GetLinkReference(node).LeftAsSource = left;

121
122    /// <summary>
123    /// <para>
124    /// Sets the right using the specified node.
125    /// </para>
126    /// <para></para>
127    /// </summary>
128    /// <param name="node">
129    /// <para>The node.</para>
130    /// <para></para>
131    /// </param>
132    /// <param name="right">
133    /// <para>The right.</para>
134    /// <para></para>
135    /// </param>
136    [MethodImpl(MethodImplOptions.AggressiveInlining)]
137    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
    ↪ GetLinkReference(node).RightAsSource = right;

```

```

139    /// <summary>
140    /// <para>
141    /// Gets the size using the specified node.
142    /// </para>
143    /// <para></para>
144    /// </summary>
145    /// <param name="node">
146    /// <para>The node.</para>
147    /// <para></para>
148    /// </param>
149    /// <returns>
150    /// <para>The link</para>
151    /// <para></para>
152    /// </returns>
153    [MethodImpl(MethodImplOptions.AggressiveInlining)]
154    protected override TLinkAddress GetSize(TLinkAddress node) =>
155        ↪ GetSizeValue(GetLinkReference(node).SizeAsSource);
156
157    /// <summary>
158    /// <para>
159    /// Sets the size using the specified node.
160    /// </para>
161    /// <para></para>
162    /// </summary>
163    /// <param name="node">
164    /// <para>The node.</para>
165    /// <para></para>
166    /// </param>
167    /// <param name="size">
168    /// <para>The size.</para>
169    /// <para></para>
170    /// </param>
171    [MethodImpl(MethodImplOptions.AggressiveInlining)]
172    protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
173        ↪ SetSizeValue(ref GetLinkReference(node).SizeAsSource, size);
174
175    /// <summary>
176    /// <para>
177    /// Determines whether this instance get left is child.
178    /// </para>
179    /// <para></para>
180    /// </summary>
181    /// <param name="node">
182    /// <para>The node.</para>
183    /// <para></para>
184    /// </param>
185    /// <returns>
186    /// <para>The bool</para>
187    /// <para></para>
188    /// </returns>
189    [MethodImpl(MethodImplOptions.AggressiveInlining)]
190    protected override bool GetLeftIsChild(TLinkAddress node) =>
191        ↪ GetLeftIsChildValue(GetLinkReference(node).SizeAsSource);
192
193    /// <summary>
194    /// <para>
195    /// Sets the left is child using the specified node.
196    /// </para>
197    /// <para></para>
198    /// </summary>
199    /// <param name="node">
200    /// <para>The node.</para>
201    /// <para></para>
202    /// </param>
203    /// <param name="value">
204    /// <para>The value.</para>
205    /// <para></para>
206    /// </param>
207    [MethodImpl(MethodImplOptions.AggressiveInlining)]
208    protected override void SetLeftIsChild(TLinkAddress node, bool value) =>
209        ↪ SetLeftIsChildValue(ref GetLinkReference(node).SizeAsSource, value);
210
211    /// <summary>
212    /// <para>
213    /// Determines whether this instance get right is child.
214    /// </para>
215    /// <para></para>
216    /// </summary>

```



```

213     /// <param name="node">
214     /// <para>The node.</para>
215     /// <para></para>
216     /// </param>
217     /// <returns>
218     /// <para>The bool</para>
219     /// <para></para>
220     /// </returns>
221     [MethodImpl(MethodImplOptions.AggressiveInlining)]
222     protected override bool GetRightIsChild(TLinkAddress node) =>
223         ↪ GetRightIsChildValue(GetLinkReference(node).SizeAsSource);
224
225     /// <summary>
226     /// <para>
227     /// Sets the right is child using the specified node.
228     /// </para>
229     /// <para></para>
230     /// </summary>
231     /// <param name="node">
232     /// <para>The node.</para>
233     /// <para></para>
234     /// </param>
235     /// <param name="value">
236     /// <para>The value.</para>
237     /// <para></para>
238     /// </param>
239     [MethodImpl(MethodImplOptions.AggressiveInlining)]
240     protected override void SetRightIsChild(TLinkAddress node, bool value) =>
241         ↪ SetRightIsChildValue(ref GetLinkReference(node).SizeAsSource, value);
242
243     /// <summary>
244     /// <para>
245     /// Gets the balance using the specified node.
246     /// </para>
247     /// <para></para>
248     /// </summary>
249     /// <param name="node">
250     /// <para>The node.</para>
251     /// <para></para>
252     /// </param>
253     /// <returns>
254     /// <para>The sbyte</para>
255     /// <para></para>
256     /// </returns>
257     [MethodImpl(MethodImplOptions.AggressiveInlining)]
258     protected override sbyte GetBalance(TLinkAddress node) =>
259         ↪ GetBalanceValue(GetLinkReference(node).SizeAsSource);
260
261     /// <summary>
262     /// <para>
263     /// Sets the balance using the specified node.
264     /// </para>
265     /// <para></para>
266     /// </summary>
267     /// <param name="node">
268     /// <para>The node.</para>
269     /// <para></para>
270     /// </param>
271     /// <param name="value">
272     /// <para>The value.</para>
273     /// <para></para>
274     /// </param>
275     [MethodImpl(MethodImplOptions.AggressiveInlining)]
276     protected override void SetBalance(TLinkAddress node, sbyte value) =>
277         ↪ SetBalanceValue(ref GetLinkReference(node).SizeAsSource, value);
278
279     /// <summary>
280     /// <para>
281     /// Gets the tree root.
282     /// </para>
283     /// <para></para>
284     /// </summary>
285     /// <returns>
286     /// <para>The link</para>
287     /// <para></para>
288     /// </returns>
289     [MethodImpl(MethodImplOptions.AggressiveInlining)]
290     protected override TLinkAddress GetTreeRoot() => GetHeaderReference().RootAsSource;

```

```

287
288     /// <summary>
289     /// <para>
290     /// Gets the base part value using the specified link.
291     /// </para>
292     /// <para></para>
293     /// </summary>
294     /// <param name="link">
295     /// <para>The link.</para>
296     /// <para></para>
297     /// </param>
298     /// <returns>
299     /// <para>The link</para>
300     /// <para></para>
301     /// </returns>
302     [MethodImpl(MethodImplOptions.AggressiveInlining)]
303     protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
304         ↪ GetLinkReference(link).Source;
305
306     /// <summary>
307     /// <para>
308     /// Determines whether this instance first is to the left of second.
309     /// </para>
310     /// <para></para>
311     /// </summary>
312     /// <param name="firstSource">
313     /// <para>The first source.</para>
314     /// <para></para>
315     /// </param>
316     /// <param name="firstTarget">
317     /// <para>The first target.</para>
318     /// <para></para>
319     /// </param>
320     /// <param name="secondSource">
321     /// <para>The second source.</para>
322     /// <para></para>
323     /// </param>
324     /// <param name="secondTarget">
325     /// <para>The second target.</para>
326     /// <para></para>
327     /// </param>
328     /// <returns>
329     /// <para>The bool</para>
330     /// <para></para>
331     /// </returns>
332     [MethodImpl(MethodImplOptions.AggressiveInlining)]
333     protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
334         ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
335         ↪ LessThan(firstSource, secondSource) || (AreEqual(firstSource, secondSource) &&
336         ↪ LessThan(firstTarget, secondTarget));
337
338     /// <summary>
339     /// <para>
340     /// Determines whether this instance first is to the right of second.
341     /// </para>
342     /// <para></para>
343     /// </summary>
344     /// <param name="firstSource">
345     /// <para>The first source.</para>
346     /// <para></para>
347     /// </param>
348     /// <param name="firstTarget">
349     /// <para>The first target.</para>
350     /// <para></para>
351     /// </param>
352     /// <param name="secondSource">
353     /// <para>The second source.</para>
354     /// <para></para>
355     /// </param>
356     /// <param name="secondTarget">
357     /// <para>The second target.</para>
358     /// <para></para>
359     /// </param>
360     /// <returns>
361     /// <para>The bool</para>
362     /// <para></para>
363     /// </returns>

```

```

360 [MethodImpl(MethodImplOptions.AggressiveInlining)]
361 protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
    ↪ GreaterThan(firstSource, secondSource) || (AreEqual(firstSource, secondSource) &&
    ↪ GreaterThan(firstTarget, secondTarget));
362
363 /// <summary>
364 /// <para>
365 /// Clears the node using the specified node.
366 /// </para>
367 /// <para></para>
368 /// </summary>
369 /// <param name="node">
370 /// <para>The node.</para>
371 /// <para></para>
372 /// </param>
373 [MethodImpl(MethodImplOptions.AggressiveInlining)]
374 protected override void ClearNode(TLinkAddress node)
375 {
376     ref var link = ref GetLinkReference(node);
377     link.LeftAsSource = Zero;
378     link.RightAsSource = Zero;
379     link.SizeAsSource = Zero;
380 }
381 }
382 }

```

1.84 ./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksSourcesRecursionlessSizeBalancedTreeMethods

```

1 using System.Runtime.CompilerServices;
2
3 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5 namespace Platform.Data.Doublets.Memory.United.Generic
6 {
7     /// <summary>
8     /// <para>
9     /// Represents the links sources recursionless size balanced tree methods.
10    /// </para>
11    /// <para></para>
12    /// </summary>
13    /// <seealso cref="LinksRecursionlessSizeBalancedTreeMethodsBase{TLinkAddress}"/>
14    public unsafe class LinksSourcesRecursionlessSizeBalancedTreeMethods<TLinkAddress> :
    ↪ LinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress>
15    {
16        /// <summary>
17        /// <para>
18        /// Initializes a new <see cref="LinksSourcesRecursionlessSizeBalancedTreeMethods"/>
    ↪ instance.
19        /// </para>
20        /// <para></para>
21        /// </summary>
22        /// <param name="constants">
23        /// <para>A constants.</para>
24        /// <para></para>
25        /// </param>
26        /// <param name="links">
27        /// <para>A links.</para>
28        /// <para></para>
29        /// </param>
30        /// <param name="header">
31        /// <para>A header.</para>
32        /// <para></para>
33        /// </param>
34        [MethodImpl(MethodImplOptions.AggressiveInlining)]
35        public LinksSourcesRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
    ↪ constants, byte* links, byte* header) : base(constants, links, header) { }
36
37        /// <summary>
38        /// <para>
39        /// Gets the left reference using the specified node.
40        /// </para>
41        /// <para></para>
42        /// </summary>
43        /// <param name="node">
44        /// <para>The node.</para>
45        /// <para></para>
46        /// </param>
47        /// <returns>

```

```

48     /// <para>The ref link</para>
49     /// <para></para>
50     /// </returns>
51     [MethodImpl(MethodImplOptions.AggressiveInlining)]
52     protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
    ↪ GetLinkReference(node).LeftAsSource;
53
54     /// <summary>
55     /// <para>
56     /// Gets the right reference using the specified node.
57     /// </para>
58     /// <para></para>
59     /// </summary>
60     /// <param name="node">
61     /// <para>The node.</para>
62     /// <para></para>
63     /// </param>
64     /// <returns>
65     /// <para>The ref link</para>
66     /// <para></para>
67     /// </returns>
68     [MethodImpl(MethodImplOptions.AggressiveInlining)]
69     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ GetLinkReference(node).RightAsSource;
70
71     /// <summary>
72     /// <para>
73     /// Gets the left using the specified node.
74     /// </para>
75     /// <para></para>
76     /// </summary>
77     /// <param name="node">
78     /// <para>The node.</para>
79     /// <para></para>
80     /// </param>
81     /// <returns>
82     /// <para>The link</para>
83     /// <para></para>
84     /// </returns>
85     [MethodImpl(MethodImplOptions.AggressiveInlining)]
86     protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ GetLinkReference(node).LeftAsSource;
87
88     /// <summary>
89     /// <para>
90     /// Gets the right using the specified node.
91     /// </para>
92     /// <para></para>
93     /// </summary>
94     /// <param name="node">
95     /// <para>The node.</para>
96     /// <para></para>
97     /// </param>
98     /// <returns>
99     /// <para>The link</para>
100    /// <para></para>
101    /// </returns>
102    [MethodImpl(MethodImplOptions.AggressiveInlining)]
103    protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↪ GetLinkReference(node).RightAsSource;
104
105    /// <summary>
106    /// <para>
107    /// Sets the left using the specified node.
108    /// </para>
109    /// <para></para>
110    /// </summary>
111    /// <param name="node">
112    /// <para>The node.</para>
113    /// <para></para>
114    /// </param>
115    /// <param name="left">
116    /// <para>The left.</para>
117    /// <para></para>
118    /// </param>
119    [MethodImpl(MethodImplOptions.AggressiveInlining)]
120    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
    ↪ GetLinkReference(node).LeftAsSource = left;

```

```

121     /// <summary>
122     /// <para>
123     /// Sets the right using the specified node.
124     /// </para>
125     /// <para></para>
126     /// </summary>
127     /// <param name="node">
128     /// <para>The node.</para>
129     /// <para></para>
130     /// </param>
131     /// <param name="right">
132     /// <para>The right.</para>
133     /// <para></para>
134     /// </param>
135     [MethodImpl(MethodImplOptions.AggressiveInlining)]
136     protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
137     ↪ GetLinkReference(node).RightAsSource = right;
138
139     /// <summary>
140     /// <para>
141     /// Gets the size using the specified node.
142     /// </para>
143     /// <para></para>
144     /// </summary>
145     /// <param name="node">
146     /// <para>The node.</para>
147     /// <para></para>
148     /// </param>
149     /// <returns>
150     /// <para>The link</para>
151     /// <para></para>
152     /// </returns>
153     [MethodImpl(MethodImplOptions.AggressiveInlining)]
154     protected override TLinkAddress GetSize(TLinkAddress node) =>
155     ↪ GetLinkReference(node).SizeAsSource;
156
157     /// <summary>
158     /// <para>
159     /// Sets the size using the specified node.
160     /// </para>
161     /// <para></para>
162     /// </summary>
163     /// <param name="node">
164     /// <para>The node.</para>
165     /// <para></para>
166     /// </param>
167     /// <param name="size">
168     /// <para>The size.</para>
169     /// <para></para>
170     /// </param>
171     [MethodImpl(MethodImplOptions.AggressiveInlining)]
172     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
173     ↪ GetLinkReference(node).SizeAsSource = size;
174
175     /// <summary>
176     /// <para>
177     /// Gets the tree root.
178     /// </para>
179     /// <para></para>
180     /// </summary>
181     /// <returns>
182     /// <para>The link</para>
183     /// <para></para>
184     /// </returns>
185     [MethodImpl(MethodImplOptions.AggressiveInlining)]
186     protected override TLinkAddress GetTreeRoot() => GetHeaderReference().RootAsSource;
187
188     /// <summary>
189     /// <para>
190     /// Gets the base part value using the specified link.
191     /// </para>
192     /// <para></para>
193     /// </summary>
194     /// <param name="link">
195     /// <para>The link.</para>
196     /// <para></para>
197     /// </param>

```

```

196     /// <returns>
197     /// <para>The link</para>
198     /// <para></para>
199     /// </returns>
200     [MethodImpl(MethodImplOptions.AggressiveInlining)]
201     protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
202         ↪ GetLinkReference(link).Source;
203
204     /// <summary>
205     /// <para>
206     /// Determines whether this instance first is to the left of second.
207     /// </para>
208     /// <para></para>
209     /// </summary>
210     /// <param name="firstSource">
211     /// <para>The first source.</para>
212     /// <para></para>
213     /// </param>
214     /// <param name="firstTarget">
215     /// <para>The first target.</para>
216     /// <para></para>
217     /// </param>
218     /// <param name="secondSource">
219     /// <para>The second source.</para>
220     /// <para></para>
221     /// </param>
222     /// <param name="secondTarget">
223     /// <para>The second target.</para>
224     /// <para></para>
225     /// </param>
226     /// <returns>
227     /// <para>The bool</para>
228     /// <para></para>
229     /// </returns>
230     [MethodImpl(MethodImplOptions.AggressiveInlining)]
231     protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
232         ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
233         ↪ LessThan(firstSource, secondSource) || (AreEqual(firstSource, secondSource) &&
234         ↪ LessThan(firstTarget, secondTarget));
235
236     /// <summary>
237     /// <para>
238     /// Determines whether this instance first is to the right of second.
239     /// </para>
240     /// <para></para>
241     /// </summary>
242     /// <param name="firstSource">
243     /// <para>The first source.</para>
244     /// <para></para>
245     /// </param>
246     /// <param name="firstTarget">
247     /// <para>The first target.</para>
248     /// <para></para>
249     /// </param>
250     /// <param name="secondSource">
251     /// <para>The second source.</para>
252     /// <para></para>
253     /// </param>
254     /// <param name="secondTarget">
255     /// <para>The second target.</para>
256     /// <para></para>
257     /// </param>
258     /// <returns>
259     /// <para>The bool</para>
260     /// <para></para>
261     /// </returns>
262     [MethodImpl(MethodImplOptions.AggressiveInlining)]
263     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
264         ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
265         ↪ GreaterThan(firstSource, secondSource) || (AreEqual(firstSource, secondSource) &&
266         ↪ GreaterThan(firstTarget, secondTarget));
267
268     /// <summary>
269     /// <para>
270     /// Clears the node using the specified node.
271     /// </para>
272     /// <para></para>
273     /// </summary>

```

```

266     /// </summary>
267     /// <param name="node">
268     /// <para>The node.</para>
269     /// <para></para>
270     /// </param>
271     [MethodImpl(MethodImplOptions.AggressiveInlining)]
272     protected override void ClearNode(TLinkAddress node)
273     {
274         ref var link = ref GetLinkReference(node);
275         link.LeftAsSource = Zero;
276         link.RightAsSource = Zero;
277         link.SizeAsSource = Zero;
278     }
279 }
280 }

```

1.85 ./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksSourcesSizeBalancedTreeMethods.cs

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.United.Generic
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the links sources size balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="LinksSizeBalancedTreeMethodsBase{TLinkAddress}"/>
14     public unsafe class LinksSourcesSizeBalancedTreeMethods<TLinkAddress> :
15         ↳ LinksSizeBalancedTreeMethodsBase<TLinkAddress>
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see cref="LinksSourcesSizeBalancedTreeMethods"/> instance.
20         /// <para></para>
21         /// </summary>
22         /// <param name="constants">
23         /// <para>A constants.</para>
24         /// <para></para>
25         /// </param>
26         /// <param name="links">
27         /// <para>A links.</para>
28         /// <para></para>
29         /// </param>
30         /// <param name="header">
31         /// <para>A header.</para>
32         /// <para></para>
33         /// </param>
34         [MethodImpl(MethodImplOptions.AggressiveInlining)]
35         public LinksSourcesSizeBalancedTreeMethods(LinksConstants<TLinkAddress> constants, byte*
36             ↳ links, byte* header) : base(constants, links, header) { }
37
38         /// <summary>
39         /// <para>
40         /// Gets the left reference using the specified node.
41         /// <para></para>
42         /// </summary>
43         /// <param name="node">
44         /// <para>The node.</para>
45         /// <para></para>
46         /// </param>
47         /// <returns>
48         /// <para>The ref link</para>
49         /// <para></para>
50         /// </returns>
51         [MethodImpl(MethodImplOptions.AggressiveInlining)]
52         protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
53             ↳ GetLinkReference(node).LeftAsSource;
54
55         /// <summary>
56         /// <para>
57         /// Gets the right reference using the specified node.
58         /// <para></para>
59         /// </summary>
60         /// <param name="node">
61         /// <para>The node.</para>
62         /// <para></para>
63         /// </param>
64         /// <returns>
65         /// <para>The ref link</para>
66         /// <para></para>
67         /// </returns>
68         [MethodImpl(MethodImplOptions.AggressiveInlining)]
69         protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
70             ↳ GetLinkReference(node).RightAsSource;
71     }
72 }

```

```

59     /// </summary>
60     /// <param name="node">
61     /// <para>The node.</para>
62     /// <para></para>
63     /// </param>
64     /// <returns>
65     /// <para>The ref link</para>
66     /// <para></para>
67     /// </returns>
68     [MethodImpl(MethodImplOptions.AggressiveInlining)]
69     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ GetLinkReference(node).RightAsSource;

70
71     /// <summary>
72     /// <para>
73     /// Gets the left using the specified node.
74     /// </para>
75     /// <para></para>
76     /// </summary>
77     /// <param name="node">
78     /// <para>The node.</para>
79     /// <para></para>
80     /// </param>
81     /// <returns>
82     /// <para>The link</para>
83     /// <para></para>
84     /// </returns>
85     [MethodImpl(MethodImplOptions.AggressiveInlining)]
86     protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ GetLinkReference(node).LeftAsSource;

87
88     /// <summary>
89     /// <para>
90     /// Gets the right using the specified node.
91     /// </para>
92     /// <para></para>
93     /// </summary>
94     /// <param name="node">
95     /// <para>The node.</para>
96     /// <para></para>
97     /// </param>
98     /// <returns>
99     /// <para>The link</para>
100    /// <para></para>
101    /// </returns>
102    [MethodImpl(MethodImplOptions.AggressiveInlining)]
103    protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↪ GetLinkReference(node).RightAsSource;

104
105    /// <summary>
106    /// <para>
107    /// Sets the left using the specified node.
108    /// </para>
109    /// <para></para>
110    /// </summary>
111    /// <param name="node">
112    /// <para>The node.</para>
113    /// <para></para>
114    /// </param>
115    /// <param name="left">
116    /// <para>The left.</para>
117    /// <para></para>
118    /// </param>
119    [MethodImpl(MethodImplOptions.AggressiveInlining)]
120    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
    ↪ GetLinkReference(node).LeftAsSource = left;

121
122    /// <summary>
123    /// <para>
124    /// Sets the right using the specified node.
125    /// </para>
126    /// <para></para>
127    /// </summary>
128    /// <param name="node">
129    /// <para>The node.</para>
130    /// <para></para>
131    /// </param>
132    /// <param name="right">

```



```

133     /// <para>The right.</para>
134     /// <para></para>
135     /// </param>
136     [MethodImpl(MethodImplOptions.AggressiveInlining)]
137     protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
138         ↪ GetLinkReference(node).RightAsSource = right;
139
140     /// <summary>
141     /// <para>
142     /// Gets the size using the specified node.
143     /// </para>
144     /// </summary>
145     /// <param name="node">
146     /// <para>The node.</para>
147     /// </param>
148     /// <returns>
149     /// <para>The link</para>
150     /// </returns>
151     [MethodImpl(MethodImplOptions.AggressiveInlining)]
152     protected override TLinkAddress GetSize(TLinkAddress node) =>
153         ↪ GetLinkReference(node).SizeAsSource;
154
155     /// <summary>
156     /// <para>
157     /// Sets the size using the specified node.
158     /// </para>
159     /// </summary>
160     /// <param name="node">
161     /// <para>The node.</para>
162     /// </param>
163     /// <param name="size">
164     /// <para>The size.</para>
165     /// </param>
166     [MethodImpl(MethodImplOptions.AggressiveInlining)]
167     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
168         ↪ GetLinkReference(node).SizeAsSource = size;
169
170     /// <summary>
171     /// <para>
172     /// Gets the tree root.
173     /// </para>
174     /// </summary>
175     /// <returns>
176     /// <para>The link</para>
177     /// </returns>
178     [MethodImpl(MethodImplOptions.AggressiveInlining)]
179     protected override TLinkAddress GetTreeRoot() => GetHeaderReference().RootAsSource;
180
181     /// <summary>
182     /// <para>
183     /// Gets the base part value using the specified link.
184     /// </para>
185     /// </summary>
186     /// <param name="link">
187     /// <para>The link.</para>
188     /// </param>
189     /// <returns>
190     /// <para>The link</para>
191     /// </returns>
192     [MethodImpl(MethodImplOptions.AggressiveInlining)]
193     protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
194         ↪ GetLinkReference(link).Source;
195
196     /// <summary>
197     /// <para>
198     /// Determines whether this instance first is to the left of second.
199     /// </para>

```

```

207     /// <para></para>
208     /// </summary>
209     /// <param name="firstSource">
210     /// <para>The first source.</para>
211     /// <para></para>
212     /// </param>
213     /// <param name="firstTarget">
214     /// <para>The first target.</para>
215     /// <para></para>
216     /// </param>
217     /// <param name="secondSource">
218     /// <para>The second source.</para>
219     /// <para></para>
220     /// </param>
221     /// <param name="secondTarget">
222     /// <para>The second target.</para>
223     /// <para></para>
224     /// </param>
225     /// <returns>
226     /// <para>The bool</para>
227     /// <para></para>
228     /// </returns>
229     [MethodImpl(MethodImplOptions.AggressiveInlining)]
230     protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
    ↪ LessThan(firstSource, secondSource) || (AreEqual(firstSource, secondSource) &&
    ↪ LessThan(firstTarget, secondTarget));
231
232     /// <summary>
233     /// <para>
234     /// Determines whether this instance first is to the right of second.
235     /// </para>
236     /// <para></para>
237     /// </summary>
238     /// <param name="firstSource">
239     /// <para>The first source.</para>
240     /// <para></para>
241     /// </param>
242     /// <param name="firstTarget">
243     /// <para>The first target.</para>
244     /// <para></para>
245     /// </param>
246     /// <param name="secondSource">
247     /// <para>The second source.</para>
248     /// <para></para>
249     /// </param>
250     /// <param name="secondTarget">
251     /// <para>The second target.</para>
252     /// <para></para>
253     /// </param>
254     /// <returns>
255     /// <para>The bool</para>
256     /// <para></para>
257     /// </returns>
258     [MethodImpl(MethodImplOptions.AggressiveInlining)]
259     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
    ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
    ↪ GreaterThan(firstSource, secondSource) || (AreEqual(firstSource, secondSource) &&
    ↪ GreaterThan(firstTarget, secondTarget));
260
261     /// <summary>
262     /// <para>
263     /// Clears the node using the specified node.
264     /// </para>
265     /// <para></para>
266     /// </summary>
267     /// <param name="node">
268     /// <para>The node.</para>
269     /// <para></para>
270     /// </param>
271     [MethodImpl(MethodImplOptions.AggressiveInlining)]
272     protected override void ClearNode(TLinkAddress node)
273     {
274         ref var link = ref GetLinkReference(node);
275         link.LeftAsSource = Zero;
276         link.RightAsSource = Zero;
277         link.SizeAsSource = Zero;
278     }

```

```
279 }
280 }
```

1.86 ./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksTargetsAvlBalancedTreeMethods.cs

```
1 using System.Runtime.CompilerServices;
2
3 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5 namespace Platform.Data.Doublets.Memory.United.Generic
6 {
7     /// <summary>
8     /// <para>
9     /// Represents the links targets avl balanced tree methods.
10    /// </para>
11    /// <para></para>
12    /// </summary>
13    /// <seealso cref="LinksAvlBalancedTreeMethodsBase{TLinkAddress}"/>
14    public unsafe class LinksTargetsAvlBalancedTreeMethods<TLinkAddress> :
15        ↳ LinksAvlBalancedTreeMethodsBase<TLinkAddress>
16    {
17        /// <summary>
18        /// <para>
19        /// Initializes a new <see cref="LinksTargetsAvlBalancedTreeMethods"/> instance.
20        /// </para>
21        /// <para></para>
22        /// </summary>
23        /// <param name="constants">
24        /// <para>A constants.</para>
25        /// </param>
26        /// <param name="links">
27        /// <para>A links.</para>
28        /// </param>
29        /// <param name="header">
30        /// <para>A header.</para>
31        /// </param>
32        [MethodImpl(MethodImplOptions.AggressiveInlining)]
33        public LinksTargetsAvlBalancedTreeMethods(LinksConstants<TLinkAddress> constants, byte*
34            ↳ links, byte* header) : base(constants, links, header) { }
35
36        /// <summary>
37        /// <para>
38        /// Gets the left reference using the specified node.
39        /// </para>
40        /// <para></para>
41        /// </summary>
42        /// <param name="node">
43        /// <para>The node.</para>
44        /// </param>
45        /// <returns>
46        /// <para>The ref link</para>
47        /// </returns>
48        [MethodImpl(MethodImplOptions.AggressiveInlining)]
49        protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
50            ↳ GetLinkReference(node).LeftAsTarget;
51
52        /// <summary>
53        /// <para>
54        /// Gets the right reference using the specified node.
55        /// </para>
56        /// <para></para>
57        /// </summary>
58        /// <param name="node">
59        /// <para>The node.</para>
60        /// </param>
61        /// <returns>
62        /// <para>The ref link</para>
63        /// </returns>
64        [MethodImpl(MethodImplOptions.AggressiveInlining)]
65        protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
66            ↳ GetLinkReference(node).RightAsTarget;
67
68    }
69
70 }
```

```

71     /// <summary>
72     /// <para>
73     /// Gets the left using the specified node.
74     /// </para>
75     /// <para></para>
76     /// </summary>
77     /// <param name="node">
78     /// <para>The node.</para>
79     /// <para></para>
80     /// </param>
81     /// <returns>
82     /// <para>The link</para>
83     /// <para></para>
84     /// </returns>
85     [MethodImpl(MethodImplOptions.AggressiveInlining)]
86     protected override TLinkAddress GetLeft(TLinkAddress node) =>
87         ↪ GetLinkReference(node).LeftAsTarget;
88
89     /// <summary>
90     /// <para>
91     /// Gets the right using the specified node.
92     /// </para>
93     /// <para></para>
94     /// </summary>
95     /// <param name="node">
96     /// <para>The node.</para>
97     /// <para></para>
98     /// </param>
99     /// <returns>
100    /// <para>The link</para>
101    /// <para></para>
102    /// </returns>
103    [MethodImpl(MethodImplOptions.AggressiveInlining)]
104    protected override TLinkAddress GetRight(TLinkAddress node) =>
105        ↪ GetLinkReference(node).RightAsTarget;
106
107    /// <summary>
108    /// <para>
109    /// Sets the left using the specified node.
110    /// </para>
111    /// <para></para>
112    /// </summary>
113    /// <param name="node">
114    /// <para>The node.</para>
115    /// <para></para>
116    /// </param>
117    /// <param name="left">
118    /// <para>The left.</para>
119    /// <para></para>
120    /// </param>
121    [MethodImpl(MethodImplOptions.AggressiveInlining)]
122    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
123        ↪ GetLinkReference(node).LeftAsTarget = left;
124
125    /// <summary>
126    /// <para>
127    /// Sets the right using the specified node.
128    /// </para>
129    /// <para></para>
130    /// </summary>
131    /// <param name="node">
132    /// <para>The node.</para>
133    /// <para></para>
134    /// </param>
135    /// <param name="right">
136    /// <para>The right.</para>
137    /// <para></para>
138    /// </param>
139    [MethodImpl(MethodImplOptions.AggressiveInlining)]
140    protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
141        ↪ GetLinkReference(node).RightAsTarget = right;
142
143    /// <summary>
144    /// <para>
145    /// Gets the size using the specified node.
146    /// </para>
147    /// <para></para>
148    /// </summary>

```

```

145     /// <param name="node">
146     /// <para>The node.</para>
147     /// <para></para>
148     /// </param>
149     /// <returns>
150     /// <para>The link</para>
151     /// <para></para>
152     /// </returns>
153     [MethodImpl(MethodImplOptions.AggressiveInlining)]
154     protected override TLinkAddress GetSize(TLinkAddress node) =>
155         ↪ GetSizeValue(GetLinkReference(node).SizeAsTarget);
156
157     /// <summary>
158     /// <para>
159     /// Sets the size using the specified node.
160     /// </para>
161     /// <para></para>
162     /// </summary>
163     /// <param name="node">
164     /// <para>The node.</para>
165     /// <para></para>
166     /// </param>
167     /// <param name="size">
168     /// <para>The size.</para>
169     /// <para></para>
170     /// </param>
171     [MethodImpl(MethodImplOptions.AggressiveInlining)]
172     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
173         ↪ SetSizeValue(ref GetLinkReference(node).SizeAsTarget, size);
174
175     /// <summary>
176     /// <para>
177     /// Determines whether this instance get left is child.
178     /// </para>
179     /// <para></para>
180     /// </summary>
181     /// <param name="node">
182     /// <para>The node.</para>
183     /// <para></para>
184     /// </param>
185     /// <returns>
186     /// <para>The bool</para>
187     /// <para></para>
188     /// </returns>
189     [MethodImpl(MethodImplOptions.AggressiveInlining)]
190     protected override bool GetLeftIsChild(TLinkAddress node) =>
191         ↪ GetLeftIsChildValue(GetLinkReference(node).SizeAsTarget);
192
193     /// <summary>
194     /// <para>
195     /// Sets the left is child using the specified node.
196     /// </para>
197     /// <para></para>
198     /// </summary>
199     /// <param name="node">
200     /// <para>The node.</para>
201     /// <para></para>
202     /// </param>
203     /// <param name="value">
204     /// <para>The value.</para>
205     /// <para></para>
206     /// </param>
207     [MethodImpl(MethodImplOptions.AggressiveInlining)]
208     protected override void SetLeftIsChild(TLinkAddress node, bool value) =>
209         ↪ SetLeftIsChildValue(ref GetLinkReference(node).SizeAsTarget, value);
210
211     /// <summary>
212     /// <para>
213     /// Determines whether this instance get right is child.
214     /// </para>
215     /// <para></para>
216     /// </summary>
217     /// <param name="node">
218     /// <para>The node.</para>
219     /// <para></para>
220     /// </param>
221     /// <returns>
222     /// <para>The bool</para>

```

```

219 /// <para></para>
220 /// </returns>
221 [MethodImpl(MethodImplOptions.AggressiveInlining)]
222 protected override bool GetRightIsChild(TLinkAddress node) =>
223     ↪ GetRightIsChildValue(GetLinkReference(node).SizeAsTarget);
224
225 /// <summary>
226 /// <para>
227 /// Sets the right is child using the specified node.
228 /// </para>
229 /// </summary>
230 /// <param name="node">
231 /// <para>The node.</para>
232 /// </para>
233 /// </param>
234 /// <param name="value">
235 /// <para>The value.</para>
236 /// </para>
237 /// </param>
238 [MethodImpl(MethodImplOptions.AggressiveInlining)]
239 protected override void SetRightIsChild(TLinkAddress node, bool value) =>
240     ↪ SetRightIsChildValue(ref GetLinkReference(node).SizeAsTarget, value);
241
242 /// <summary>
243 /// <para>
244 /// Gets the balance using the specified node.
245 /// </para>
246 /// </summary>
247 /// <param name="node">
248 /// <para>The node.</para>
249 /// </para>
250 /// </param>
251 /// <returns>
252 /// <para>The sbyte</para>
253 /// </para>
254 /// </returns>
255 [MethodImpl(MethodImplOptions.AggressiveInlining)]
256 protected override sbyte GetBalance(TLinkAddress node) =>
257     ↪ GetBalanceValue(GetLinkReference(node).SizeAsTarget);
258
259 /// <summary>
260 /// <para>
261 /// Sets the balance using the specified node.
262 /// </para>
263 /// </summary>
264 /// <param name="node">
265 /// <para>The node.</para>
266 /// </para>
267 /// </param>
268 /// <param name="value">
269 /// <para>The value.</para>
270 /// </para>
271 /// </param>
272 [MethodImpl(MethodImplOptions.AggressiveInlining)]
273 protected override void SetBalance(TLinkAddress node, sbyte value) =>
274     ↪ SetBalanceValue(ref GetLinkReference(node).SizeAsTarget, value);
275
276 /// <summary>
277 /// <para>
278 /// Gets the tree root.
279 /// </para>
280 /// </summary>
281 /// <returns>
282 /// <para>The link</para>
283 /// </para>
284 /// </returns>
285 [MethodImpl(MethodImplOptions.AggressiveInlining)]
286 protected override TLinkAddress GetTreeRoot() => GetHeaderReference().RootAsTarget;
287
288 /// <summary>
289 /// <para>
290 /// Gets the base part value using the specified link.
291 /// </para>
292 /// </summary>

```

```

293     /// </summary>
294     /// <param name="link">
295     /// <para>The link.</para>
296     /// <para></para>
297     /// </param>
298     /// <returns>
299     /// <para>The link</para>
300     /// <para></para>
301     /// </returns>
302     [MethodImpl(MethodImplOptions.AggressiveInlining)]
303     protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
304         ↪ GetLinkReference(link).Target;
305
306     /// <summary>
307     /// <para>
308     /// Determines whether this instance first is to the left of second.
309     /// </para>
310     /// <para></para>
311     /// </summary>
312     /// <param name="firstSource">
313     /// <para>The first source.</para>
314     /// <para></para>
315     /// </param>
316     /// <param name="firstTarget">
317     /// <para>The first target.</para>
318     /// <para></para>
319     /// </param>
320     /// <param name="secondSource">
321     /// <para>The second source.</para>
322     /// <para></para>
323     /// </param>
324     /// <param name="secondTarget">
325     /// <para>The second target.</para>
326     /// <para></para>
327     /// </param>
328     /// <returns>
329     /// <para>The bool</para>
330     /// <para></para>
331     /// </returns>
332     [MethodImpl(MethodImplOptions.AggressiveInlining)]
333     protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
334         ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
335         ↪ LessThan(firstTarget, secondTarget) || (AreEqual(firstTarget, secondTarget) &&
336         ↪ LessThan(firstSource, secondSource));
337
338     /// <summary>
339     /// <para>
340     /// Determines whether this instance first is to the right of second.
341     /// </para>
342     /// <para></para>
343     /// </summary>
344     /// <param name="firstSource">
345     /// <para>The first source.</para>
346     /// <para></para>
347     /// </param>
348     /// <param name="firstTarget">
349     /// <para>The first target.</para>
350     /// <para></para>
351     /// </param>
352     /// <param name="secondSource">
353     /// <para>The second source.</para>
354     /// <para></para>
355     /// </param>
356     /// <param name="secondTarget">
357     /// <para>The second target.</para>
358     /// <para></para>
359     /// </param>
360     /// <returns>
361     /// <para>The bool</para>
362     /// <para></para>
363     /// </returns>
364     [MethodImpl(MethodImplOptions.AggressiveInlining)]
365     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
366         ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
367         ↪ GreaterThan(firstTarget, secondTarget) || (AreEqual(firstTarget, secondTarget) &&
368         ↪ GreaterThan(firstSource, secondSource));

```

```

363     /// <summary>
364     /// <para>
365     /// Clears the node using the specified node.
366     /// </para>
367     /// <para></para>
368     /// </summary>
369     /// <param name="node">
370     /// <para>The node.</para>
371     /// <para></para>
372     /// </param>
373     [MethodImpl(MethodImplOptions.AggressiveInlining)]
374     protected override void ClearNode(TLinkAddress node)
375     {
376         ref var link = ref GetLinkReference(node);
377         link.LeftAsTarget = Zero;
378         link.RightAsTarget = Zero;
379         link.SizeAsTarget = Zero;
380     }
381 }
382 }

```

1.87 ./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksTargetsRecursionlessSizeBalancedTreeMethods

```

using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Memory.United.Generic
{
    /// <summary>
    /// <para>
    /// Represents the links targets recursionless size balanced tree methods.
    /// </para>
    /// <para></para>
    /// </summary>
    /// <seealso cref="LinksRecursionlessSizeBalancedTreeMethodsBase{TLinkAddress}"/>
    public unsafe class LinksTargetsRecursionlessSizeBalancedTreeMethods<TLinkAddress> :
        LinksRecursionlessSizeBalancedTreeMethodsBase<TLinkAddress>
    {
        /// <summary>
        /// <para>
        /// Initializes a new <see cref="LinksTargetsRecursionlessSizeBalancedTreeMethods"/>
        /// instance.
        /// </para>
        /// <para></para>
        /// </summary>
        /// <param name="constants">
        /// <para>A constants.</para>
        /// <para></para>
        /// </param>
        /// <param name="links">
        /// <para>A links.</para>
        /// <para></para>
        /// </param>
        /// <param name="header">
        /// <para>A header.</para>
        /// <para></para>
        /// </param>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinksTargetsRecursionlessSizeBalancedTreeMethods(LinksConstants<TLinkAddress>
            constants, byte* links, byte* header) : base(constants, links, header) { }

        /// <summary>
        /// <para>
        /// Gets the left reference using the specified node.
        /// </para>
        /// <para></para>
        /// </summary>
        /// <param name="node">
        /// <para>The node.</para>
        /// <para></para>
        /// </param>
        /// <returns>
        /// <para>The ref link</para>
        /// <para></para>
        /// </returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
            GetLinkReference(node).LeftAsTarget;
    }
}

```



```

53
54     /// <summary>
55     /// <para>
56     /// Gets the right reference using the specified node.
57     /// </para>
58     /// <para></para>
59     /// </summary>
60     /// <param name="node">
61     /// <para>The node.</para>
62     /// <para></para>
63     /// </param>
64     /// <returns>
65     /// <para>The ref link</para>
66     /// <para></para>
67     /// </returns>
68     [MethodImpl(MethodImplOptions.AggressiveInlining)]
69     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ GetLinkReference(node).RightAsTarget;
70
71     /// <summary>
72     /// <para>
73     /// Gets the left using the specified node.
74     /// </para>
75     /// <para></para>
76     /// </summary>
77     /// <param name="node">
78     /// <para>The node.</para>
79     /// <para></para>
80     /// </param>
81     /// <returns>
82     /// <para>The link</para>
83     /// <para></para>
84     /// </returns>
85     [MethodImpl(MethodImplOptions.AggressiveInlining)]
86     protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ GetLinkReference(node).LeftAsTarget;
87
88     /// <summary>
89     /// <para>
90     /// Gets the right using the specified node.
91     /// </para>
92     /// <para></para>
93     /// </summary>
94     /// <param name="node">
95     /// <para>The node.</para>
96     /// <para></para>
97     /// </param>
98     /// <returns>
99     /// <para>The link</para>
100    /// <para></para>
101    /// </returns>
102    [MethodImpl(MethodImplOptions.AggressiveInlining)]
103    protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↪ GetLinkReference(node).RightAsTarget;
104
105    /// <summary>
106    /// <para>
107    /// Sets the left using the specified node.
108    /// </para>
109    /// <para></para>
110    /// </summary>
111    /// <param name="node">
112    /// <para>The node.</para>
113    /// <para></para>
114    /// </param>
115    /// <param name="left">
116    /// <para>The left.</para>
117    /// <para></para>
118    /// </param>
119    [MethodImpl(MethodImplOptions.AggressiveInlining)]
120    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
    ↪ GetLinkReference(node).LeftAsTarget = left;
121
122    /// <summary>
123    /// <para>
124    /// Sets the right using the specified node.
125    /// </para>
126    /// <para></para>

```

```

127     /// </summary>
128     /// <param name="node">
129     /// <para>The node.</para>
130     /// <para></para>
131     /// </param>
132     /// <param name="right">
133     /// <para>The right.</para>
134     /// <para></para>
135     /// </param>
136     [MethodImpl(MethodImplOptions.AggressiveInlining)]
137     protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
138         ↪ GetLinkReference(node).RightAsTarget = right;
139
140     /// <summary>
141     /// <para>
142     /// Gets the size using the specified node.
143     /// </para>
144     /// <para></para>
145     /// </summary>
146     /// <param name="node">
147     /// <para>The node.</para>
148     /// <para></para>
149     /// </param>
150     /// <returns>
151     /// <para>The link</para>
152     /// <para></para>
153     /// </returns>
154     [MethodImpl(MethodImplOptions.AggressiveInlining)]
155     protected override TLinkAddress GetSize(TLinkAddress node) =>
156         ↪ GetLinkReference(node).SizeAsTarget;
157
158     /// <summary>
159     /// <para>
160     /// Sets the size using the specified node.
161     /// </para>
162     /// <para></para>
163     /// </summary>
164     /// <param name="node">
165     /// <para>The node.</para>
166     /// <para></para>
167     /// </param>
168     /// <param name="size">
169     /// <para>The size.</para>
170     /// <para></para>
171     /// </param>
172     [MethodImpl(MethodImplOptions.AggressiveInlining)]
173     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
174         ↪ GetLinkReference(node).SizeAsTarget = size;
175
176     /// <summary>
177     /// <para>
178     /// Gets the tree root.
179     /// </para>
180     /// <para></para>
181     /// </summary>
182     /// <returns>
183     /// <para>The link</para>
184     /// <para></para>
185     /// </returns>
186     [MethodImpl(MethodImplOptions.AggressiveInlining)]
187     protected override TLinkAddress GetTreeRoot() => GetHeaderReference().RootAsTarget;
188
189     /// <summary>
190     /// <para>
191     /// Gets the base part value using the specified link.
192     /// </para>
193     /// <para></para>
194     /// </summary>
195     /// <param name="link">
196     /// <para>The link.</para>
197     /// <para></para>
198     /// </param>
199     /// <returns>
200     /// <para>The link</para>
201     /// <para></para>
202     /// </returns>
203     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

201     protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
202         ↪ GetLinkReference(link).Target;
203
204     /// <summary>
205     /// <para>
206     /// Determines whether this instance first is to the left of second.
207     /// </para>
208     /// </summary>
209     /// <param name="firstSource">
210     /// <para>The first source.</para>
211     /// <para></para>
212     /// </param>
213     /// <param name="firstTarget">
214     /// <para>The first target.</para>
215     /// <para></para>
216     /// </param>
217     /// <param name="secondSource">
218     /// <para>The second source.</para>
219     /// <para></para>
220     /// </param>
221     /// <param name="secondTarget">
222     /// <para>The second target.</para>
223     /// <para></para>
224     /// </param>
225     /// <returns>
226     /// <para>The bool</para>
227     /// <para></para>
228     /// </returns>
229     [MethodImpl(MethodImplOptions.AggressiveInlining)]
230     protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
231         ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
232         ↪ LessThan(firstTarget, secondTarget) || (AreEqual(firstTarget, secondTarget) &&
233         ↪ LessThan(firstSource, secondSource));
234
235     /// <summary>
236     /// <para>
237     /// Determines whether this instance first is to the right of second.
238     /// </para>
239     /// </summary>
240     /// <param name="firstSource">
241     /// <para>The first source.</para>
242     /// <para></para>
243     /// </param>
244     /// <param name="firstTarget">
245     /// <para>The first target.</para>
246     /// <para></para>
247     /// </param>
248     /// <param name="secondSource">
249     /// <para>The second source.</para>
250     /// <para></para>
251     /// </param>
252     /// <param name="secondTarget">
253     /// <para>The second target.</para>
254     /// <para></para>
255     /// </param>
256     /// <returns>
257     /// <para>The bool</para>
258     /// <para></para>
259     /// </returns>
260     [MethodImpl(MethodImplOptions.AggressiveInlining)]
261     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
262         ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
263         ↪ GreaterThan(firstTarget, secondTarget) || (AreEqual(firstTarget, secondTarget) &&
264         ↪ GreaterThan(firstSource, secondSource));
265
266     /// <summary>
267     /// <para>
268     /// Clears the node using the specified node.
269     /// </para>
270     /// </summary>
271     /// <param name="node">
272     /// <para>The node.</para>
273     /// <para></para>
274     /// </param>

```

```

271 [MethodImpl(MethodImplOptions.AggressiveInlining)]
272 protected override void ClearNode(TLinkAddress node)
273 {
274     ref var link = ref GetLinkReference(node);
275     link.LeftAsTarget = Zero;
276     link.RightAsTarget = Zero;
277     link.SizeAsTarget = Zero;
278 }
279 }
280 }

```

1.88 ./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksTargetsSizeBalancedTreeMethods.cs

```

1 using System.Runtime.CompilerServices;
2
3 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5 namespace Platform.Data.Doublets.Memory.United.Generic
6 {
7     /// <summary>
8     /// <para>
9     /// Represents the links targets size balanced tree methods.
10    /// </para>
11    /// <para></para>
12    /// </summary>
13    /// <seealso cref="LinksSizeBalancedTreeMethodsBase{TLinkAddress}"/>
14    public unsafe class LinksTargetsSizeBalancedTreeMethods<TLinkAddress> :
15        ↪ LinksSizeBalancedTreeMethodsBase<TLinkAddress>
16    {
17        /// <summary>
18        /// <para>
19        /// Initializes a new <see cref="LinksTargetsSizeBalancedTreeMethods"/> instance.
20        /// </para>
21        /// <para></para>
22        /// </summary>
23        /// <param name="constants">
24        /// <para>A constants.</para>
25        /// <para></para>
26        /// </param>
27        /// <param name="links">
28        /// <para>A links.</para>
29        /// <para></para>
30        /// </param>
31        /// <param name="header">
32        /// <para>A header.</para>
33        /// <para></para>
34        /// </param>
35        [MethodImpl(MethodImplOptions.AggressiveInlining)]
36        public LinksTargetsSizeBalancedTreeMethods(LinksConstants<TLinkAddress> constants, byte*
37            ↪ links, byte* header) : base(constants, links, header) { }
38
39        /// <summary>
40        /// <para>
41        /// Gets the left reference using the specified node.
42        /// </para>
43        /// <para></para>
44        /// </summary>
45        /// <param name="node">
46        /// <para>The node.</para>
47        /// <para></para>
48        /// </param>
49        /// <returns>
50        /// <para>The ref link</para>
51        /// <para></para>
52        /// </returns>
53        [MethodImpl(MethodImplOptions.AggressiveInlining)]
54        protected override ref TLinkAddress GetLeftReference(TLinkAddress node) => ref
55            ↪ GetLinkReference(node).LeftAsTarget;
56
57        /// <summary>
58        /// <para>
59        /// Gets the right reference using the specified node.
60        /// </para>
61        /// <para></para>
62        /// </summary>
63        /// <param name="node">
64        /// <para>The node.</para>
65        /// <para></para>
66        /// </param>

```

```

64     /// <returns>
65     /// <para>The ref link</para>
66     /// <para></para>
67     /// </returns>
68     [MethodImpl(MethodImplOptions.AggressiveInlining)]
69     protected override ref TLinkAddress GetRightReference(TLinkAddress node) => ref
    ↪ GetLinkReference(node).RightAsTarget;

70
71     /// <summary>
72     /// <para>
73     /// Gets the left using the specified node.
74     /// </para>
75     /// <para></para>
76     /// </summary>
77     /// <param name="node">
78     /// <para>The node.</para>
79     /// <para></para>
80     /// </param>
81     /// <returns>
82     /// <para>The link</para>
83     /// <para></para>
84     /// </returns>
85     [MethodImpl(MethodImplOptions.AggressiveInlining)]
86     protected override TLinkAddress GetLeft(TLinkAddress node) =>
    ↪ GetLinkReference(node).LeftAsTarget;

87
88     /// <summary>
89     /// <para>
90     /// Gets the right using the specified node.
91     /// </para>
92     /// <para></para>
93     /// </summary>
94     /// <param name="node">
95     /// <para>The node.</para>
96     /// <para></para>
97     /// </param>
98     /// <returns>
99     /// <para>The link</para>
100    /// <para></para>
101    /// </returns>
102    [MethodImpl(MethodImplOptions.AggressiveInlining)]
103    protected override TLinkAddress GetRight(TLinkAddress node) =>
    ↪ GetLinkReference(node).RightAsTarget;

104
105    /// <summary>
106    /// <para>
107    /// Sets the left using the specified node.
108    /// </para>
109    /// <para></para>
110    /// </summary>
111    /// <param name="node">
112    /// <para>The node.</para>
113    /// <para></para>
114    /// </param>
115    /// <param name="left">
116    /// <para>The left.</para>
117    /// <para></para>
118    /// </param>
119    [MethodImpl(MethodImplOptions.AggressiveInlining)]
120    protected override void SetLeft(TLinkAddress node, TLinkAddress left) =>
    ↪ GetLinkReference(node).LeftAsTarget = left;

121
122    /// <summary>
123    /// <para>
124    /// Sets the right using the specified node.
125    /// </para>
126    /// <para></para>
127    /// </summary>
128    /// <param name="node">
129    /// <para>The node.</para>
130    /// <para></para>
131    /// </param>
132    /// <param name="right">
133    /// <para>The right.</para>
134    /// <para></para>
135    /// </param>
136    [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

137     protected override void SetRight(TLinkAddress node, TLinkAddress right) =>
138         ↪ GetLinkReference(node).RightAsTarget = right;
139
140     /// <summary>
141     /// <para>
142     /// Gets the size using the specified node.
143     /// </para>
144     /// </summary>
145     /// <param name="node">
146     /// <para>The node.</para>
147     /// </param>
148     /// </returns>
149     /// <para>The link</para>
150     /// </returns>
151     [MethodImpl(MethodImplOptions.AggressiveInlining)]
152     protected override TLinkAddress GetSize(TLinkAddress node) =>
153         ↪ GetLinkReference(node).SizeAsTarget;
154
155     /// <summary>
156     /// <para>
157     /// Sets the size using the specified node.
158     /// </para>
159     /// </summary>
160     /// <param name="node">
161     /// <para>The node.</para>
162     /// </param>
163     /// <param name="size">
164     /// <para>The size.</para>
165     /// </param>
166     /// </returns>
167     [MethodImpl(MethodImplOptions.AggressiveInlining)]
168     protected override void SetSize(TLinkAddress node, TLinkAddress size) =>
169         ↪ GetLinkReference(node).SizeAsTarget = size;
170
171     /// <summary>
172     /// <para>
173     /// Gets the tree root.
174     /// </para>
175     /// </summary>
176     /// <returns>
177     /// <para>The link</para>
178     /// </returns>
179     [MethodImpl(MethodImplOptions.AggressiveInlining)]
180     protected override TLinkAddress GetTreeRoot() => GetHeaderReference().RootAsTarget;
181
182     /// <summary>
183     /// <para>
184     /// Gets the base part value using the specified link.
185     /// </para>
186     /// </summary>
187     /// <param name="link">
188     /// <para>The link.</para>
189     /// </param>
190     /// </returns>
191     /// <para>The link</para>
192     /// </returns>
193     [MethodImpl(MethodImplOptions.AggressiveInlining)]
194     protected override TLinkAddress GetBasePartValue(TLinkAddress link) =>
195         ↪ GetLinkReference(link).Target;
196
197     /// <summary>
198     /// <para>
199     /// Determines whether this instance first is to the left of second.
200     /// </para>
201     /// </summary>
202     /// <param name="firstSource">
203     /// <para>The first source.</para>
204     /// </param>

```

```

211     /// <para></para>
212     /// </param>
213     /// <param name="firstTarget">
214     /// <para>The first target.</para>
215     /// <para></para>
216     /// </param>
217     /// <param name="secondSource">
218     /// <para>The second source.</para>
219     /// <para></para>
220     /// </param>
221     /// <param name="secondTarget">
222     /// <para>The second target.</para>
223     /// <para></para>
224     /// </param>
225     /// <returns>
226     /// <para>The bool</para>
227     /// <para></para>
228     /// </returns>
229     [MethodImpl(MethodImplOptions.AggressiveInlining)]
230     protected override bool FirstIsToLeftOfSecond(TLinkAddress firstSource, TLinkAddress
        ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
        ↪ LessThan(firstTarget, secondTarget) || (AreEqual(firstTarget, secondTarget) &&
        ↪ LessThan(firstSource, secondSource));

231
232     /// <summary>
233     /// <para>
234     /// Determines whether this instance first is to the right of second.
235     /// </para>
236     /// <para></para>
237     /// </summary>
238     /// <param name="firstSource">
239     /// <para>The first source.</para>
240     /// <para></para>
241     /// </param>
242     /// <param name="firstTarget">
243     /// <para>The first target.</para>
244     /// <para></para>
245     /// </param>
246     /// <param name="secondSource">
247     /// <para>The second source.</para>
248     /// <para></para>
249     /// </param>
250     /// <param name="secondTarget">
251     /// <para>The second target.</para>
252     /// <para></para>
253     /// </param>
254     /// <returns>
255     /// <para>The bool</para>
256     /// <para></para>
257     /// </returns>
258     [MethodImpl(MethodImplOptions.AggressiveInlining)]
259     protected override bool FirstIsToTheRightOfSecond(TLinkAddress firstSource, TLinkAddress
        ↪ firstTarget, TLinkAddress secondSource, TLinkAddress secondTarget) =>
        ↪ GreaterThan(firstTarget, secondTarget) || (AreEqual(firstTarget, secondTarget) &&
        ↪ GreaterThan(firstSource, secondSource));

260
261     /// <summary>
262     /// <para>
263     /// Clears the node using the specified node.
264     /// </para>
265     /// <para></para>
266     /// </summary>
267     /// <param name="node">
268     /// <para>The node.</para>
269     /// <para></para>
270     /// </param>
271     [MethodImpl(MethodImplOptions.AggressiveInlining)]
272     protected override void ClearNode(TLinkAddress node)
273     {
274         ref var link = ref GetLinkReference(node);
275         link.LeftAsTarget = Zero;
276         link.RightAsTarget = Zero;
277         link.SizeAsTarget = Zero;
278     }
279 }
280 }

```

1.89 ./csharp/Platform.Data.Doublets/Memory/United/Generic/UnitedMemoryLinks.cs

```

1  using System;
2  using System.Runtime.CompilerServices;
3  using Platform.Singletons;
4  using Platform.Memory;
5  using static System.Runtime.CompilerServices.Unsafe;
6
7  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
8
9  namespace Platform.Data.Doublets.Memory.United.Generic
10 {
11     /// <summary>
12     /// <para>
13     /// Represents the united memory links.
14     /// </para>
15     /// <para></para>
16     /// </summary>
17     /// <seealso cref="UnitedMemoryLinksBase{TLinkAddress}"/>
18     public unsafe class UnitedMemoryLinks<TLinkAddress> : UnitedMemoryLinksBase<TLinkAddress>
19     {
20         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createSourceTreeMethods;
21         private readonly Func<ILinksTreeMethods<TLinkAddress>> _createTargetTreeMethods;
22         private byte* _header;
23         private byte* _links;
24
25         /// <summary>
26         /// <para>
27         /// Initializes a new <see cref="UnitedMemoryLinks"/> instance.
28         /// </para>
29         /// <para></para>
30         /// </summary>
31         /// <param name="address">
32         /// <para>A address.</para>
33         /// <para></para>
34         /// </param>
35         [MethodImpl(MethodImplOptions.AggressiveInlining)]
36         public UnitedMemoryLinks(string address) : this(address, DefaultLinksSizeStep) { }
37
38         /// <summary>
39         /// Создаёт экземпляр базы данных Links в файле по указанному адресу, с указанным
40         /// → минимальным шагом расширения базы данных.
41         /// </summary>
42         /// <param name="address">Полный путь к файлу базы данных.</param>
43         /// <param name="memoryReservationStep">Минимальный шаг расширения базы данных в
44         /// → байтах.</param>
45         [MethodImpl(MethodImplOptions.AggressiveInlining)]
46         public UnitedMemoryLinks(string address, long memoryReservationStep) : this(new
47         {
48             FileMappedResizableDirectMemory(address, memoryReservationStep),
49             memoryReservationStep
50         }) { }
51
52         /// <summary>
53         /// <para>
54         /// Initializes a new <see cref="UnitedMemoryLinks"/> instance.
55         /// </para>
56         /// <para></para>
57         /// </summary>
58         /// <param name="memory">
59         /// <para>A memory.</para>
60         /// <para></para>
61         /// </param>
62         [MethodImpl(MethodImplOptions.AggressiveInlining)]
63         public UnitedMemoryLinks(IResizableDirectMemory memory) : this(memory,
64         {
65             DefaultLinksSizeStep
66         }) { }
67
68         /// <summary>
69         /// <para>
70         /// Initializes a new <see cref="UnitedMemoryLinks"/> instance.
71         /// </para>
72         /// <para></para>
73         /// </summary>
74         /// <param name="memory">
75         /// <para>A memory.</para>
76         /// <para></para>
77         /// </param>
78         /// <param name="memoryReservationStep">
79         /// <para>A memory reservation step.</para>
80         /// <para></para>
81         /// </param>
82     }
83 }

```



```

73 [MethodImpl(MethodImplOptions.AggressiveInlining)]
74 public UnitedMemoryLinks(IResizableDirectMemory memory, long memoryReservationStep) :
    ↳ this(memory, memoryReservationStep, Default<LinksConstants<TLinkAddress>>.Instance,
    ↳ IndexTreeType.Default) { }
75
76 /// <summary>
77 /// <para>
78 /// Initializes a new <see cref="UnitedMemoryLinks"/> instance.
79 /// </para>
80 /// <para></para>
81 /// </summary>
82 /// <param name="memory">
83 /// <para>A memory.</para>
84 /// <para></para>
85 /// </param>
86 /// <param name="memoryReservationStep">
87 /// <para>A memory reservation step.</para>
88 /// <para></para>
89 /// </param>
90 /// <param name="constants">
91 /// <para>A constants.</para>
92 /// <para></para>
93 /// </param>
94 /// <param name="indexTreeType">
95 /// <para>A index tree type.</para>
96 /// <para></para>
97 /// </param>
98 [MethodImpl(MethodImplOptions.AggressiveInlining)]
99 public UnitedMemoryLinks(IResizableDirectMemory memory, long memoryReservationStep,
    ↳ LinksConstants<TLinkAddress> constants, IndexTreeType indexTreeType) : base(memory,
    ↳ memoryReservationStep, constants)
100 {
101     if (indexTreeType == IndexTreeType.SizedAndThreadedAVLBalancedTree)
102     {
103         _createSourceTreeMethods = () => new
            ↳ LinksSourcesAvlBalancedTreeMethods<TLinkAddress>(Constants, _links, _header);
104         _createTargetTreeMethods = () => new
            ↳ LinksTargetsAvlBalancedTreeMethods<TLinkAddress>(Constants, _links, _header);
105     }
106     else
107     {
108         _createSourceTreeMethods = () => new
            ↳ LinksSourcesSizeBalancedTreeMethods<TLinkAddress>(Constants, _links,
            ↳ _header);
109         _createTargetTreeMethods = () => new
            ↳ LinksTargetsSizeBalancedTreeMethods<TLinkAddress>(Constants, _links,
            ↳ _header);
110     }
111     Init(memory, memoryReservationStep);
112 }
113
114 /// <summary>
115 /// <para>
116 /// Sets the pointers using the specified memory.
117 /// </para>
118 /// <para></para>
119 /// </summary>
120 /// <param name="memory">
121 /// <para>The memory.</para>
122 /// <para></para>
123 /// </param>
124 [MethodImpl(MethodImplOptions.AggressiveInlining)]
125 protected override void SetPointers(IResizableDirectMemory memory)
126 {
127     _links = (byte*)memory.Pointer;
128     _header = _links;
129     SourcesTreeMethods = _createSourceTreeMethods();
130     TargetsTreeMethods = _createTargetTreeMethods();
131     UnusedLinksListMethods = new UnusedLinksListMethods<TLinkAddress>(_links, _header);
132 }
133
134 /// <summary>
135 /// <para>
136 /// Resets the pointers.
137 /// </para>
138 /// <para></para>
139 /// </summary>

```

```

140 [MethodImpl(MethodImplOptions.AggressiveInlining)]
141 protected override void ResetPointers()
142 {
143     base.ResetPointers();
144     _links = null;
145     _header = null;
146 }
147
148 /// <summary>
149 /// <para>
150 /// Gets the header reference.
151 /// </para>
152 /// <para></para>
153 /// </summary>
154 /// <returns>
155 /// <para>A ref links header of t link</para>
156 /// <para></para>
157 /// </returns>
158 [MethodImpl(MethodImplOptions.AggressiveInlining)]
159 protected override ref LinksHeader<TLinkAddress> GetHeaderReference() => ref
    ↳ AsRef<LinksHeader<TLinkAddress>>(_header);
160
161 /// <summary>
162 /// <para>
163 /// Gets the link reference using the specified link index.
164 /// </para>
165 /// <para></para>
166 /// </summary>
167 /// <param name="linkIndex">
168 /// <para>The link index.</para>
169 /// <para></para>
170 /// </param>
171 /// <returns>
172 /// <para>A ref raw link of t link</para>
173 /// <para></para>
174 /// </returns>
175 [MethodImpl(MethodImplOptions.AggressiveInlining)]
176 protected override ref RawLink<TLinkAddress> GetLinkReference(TLinkAddress linkIndex) =>
    ↳ ref AsRef<RawLink<TLinkAddress>>(_links + (LinkSizeInBytes *
    ↳ ConvertToInt64(linkIndex)));
177 }
178 }

```

1.90 ./csharp/Platform.Data.Doublets/Memory/United/Generic/UnitedMemoryLinksBase.cs

```

1 using System;
2 using System.Collections.Generic;
3 using System.Runtime.CompilerServices;
4 using Platform.Disposables;
5 using Platform.Singletons;
6 using Platform.Converters;
7 using Platform.Numbers;
8 using Platform.Memory;
9 using Platform.Data.Exceptions;
10 using Platform.Delegates;
11
12 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
13
14 namespace Platform.Data.Doublets.Memory.United.Generic
15 {
16     /// <summary>
17     /// <para>
18     /// Represents the united memory links base.
19     /// </para>
20     /// <para></para>
21     /// </summary>
22     /// <seealso cref="DisposableBase"/>
23     /// <seealso cref="ILinks{TLinkAddress}"/>
24     public abstract class UnitedMemoryLinksBase<TLinkAddress> : DisposableBase,
        ↳ ILinks<TLinkAddress> where TLinkAddress : struct
25     {
26         private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
            ↳ EqualityComparer<TLinkAddress>.Default;
27         private static readonly Comparer<TLinkAddress> _comparer =
            ↳ Comparer<TLinkAddress>.Default;
28         private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
            ↳ = UncheckedConverter<TLinkAddress, long>.Default;
29         private static readonly UncheckedConverter<long, TLinkAddress> _int64ToAddressConverter
            ↳ = UncheckedConverter<long, TLinkAddress>.Default;
30         private static readonly TLinkAddress _zero = default;

```

```

31 private static readonly TLinkAddress _one = Arithmetic.Increment(_zero);
32
33 /// <summary>Возвращает размер одной связи в байтах.</summary>
34 /// <remarks>
35 /// Используется только во вне класса, не рекомендуется использовать внутри.
36 /// Так как во вне не обязательно будет доступен unsafe C#.
37 /// </remarks>
38 public static readonly long LinkSizeInBytes = RawLink<TLinkAddress>.SizeInBytes;
39
40 /// <summary>
41 /// <para>
42 /// The size in bytes.
43 /// </para>
44 /// <para></para>
45 /// </summary>
46 public static readonly long LinkHeaderSizeInBytes =
47     ↳ LinksHeader<TLinkAddress>.SizeInBytes;
48
49 /// <summary>
50 /// <para>
51 /// The link size in bytes.
52 /// </para>
53 /// <para></para>
54 /// </summary>
55 public static readonly long DefaultLinksSizeStep = LinkSizeInBytes * 1024 * 1024;
56
57 /// <summary>
58 /// <para>
59 /// The memory.
60 /// </para>
61 /// <para></para>
62 /// </summary>
63 protected readonly IResizableDirectMemory _memory;
64
65 /// <summary>
66 /// <para>
67 /// The memory reservation step.
68 /// </para>
69 /// <para></para>
70 /// </summary>
71 protected readonly long _memoryReservationStep;
72
73 /// <summary>
74 /// <para>
75 /// The targets tree methods.
76 /// </para>
77 /// <para></para>
78 /// </summary>
79 protected ILinksTreeMethods<TLinkAddress> TargetsTreeMethods;
80
81 /// <summary>
82 /// <para>
83 /// The sources tree methods.
84 /// </para>
85 /// <para></para>
86 /// </summary>
87 protected ILinksTreeMethods<TLinkAddress> SourcesTreeMethods;
88
89 // TODO: Возможно чтобы гарантированно проверять на то, является ли связь удалённой,
90 // ↳ нужно использовать не список а дерево, так как так можно быстрее проверить на
91 // ↳ наличие связи внутри
92 /// <summary>
93 /// <para>
94 /// The unused links list methods.
95 /// </para>
96 /// <para></para>
97 /// </summary>
98 protected ILinksListMethods<TLinkAddress> UnusedLinksListMethods;
99
100 /// <summary>
101 /// Возвращает общее число связей находящихся в хранилище.
102 /// </summary>
103 protected virtual TLinkAddress Total
104 {
105     [MethodImpl(MethodImplOptions.AggressiveInlining)]
106     get
107     {
108         ref var header = ref GetHeaderReference();
109         return Subtract(header.AllocatedLinks, header.FreeLinks);
110     }
111 }

```

```

107     /// <summary>
108     /// <para>
109     /// Gets the constants value.
110     /// </para>
111     /// <para></para>
112     /// </summary>
113     public virtual LinksConstants<TLinkAddress> Constants
114     {
115         [MethodImpl(MethodImplOptions.AggressiveInlining)]
116         get;
117     }
118
119     /// <summary>
120     /// <para>
121     /// Initializes a new <see cref="UnitedMemoryLinksBase"/> instance.
122     /// </para>
123     /// <para></para>
124     /// </summary>
125     /// <param name="memory">
126     /// <para>A memory.</para>
127     /// <para></para>
128     /// </param>
129     /// <param name="memoryReservationStep">
130     /// <para>A memory reservation step.</para>
131     /// <para></para>
132     /// </param>
133     /// <param name="constants">
134     /// <para>A constants.</para>
135     /// <para></para>
136     /// </param>
137     [MethodImpl(MethodImplOptions.AggressiveInlining)]
138     protected UnitedMemoryLinksBase(IResizableDirectMemory memory, long
139     ↪ memoryReservationStep, LinksConstants<TLinkAddress> constants)
140     {
141         _memory = memory;
142         _memoryReservationStep = memoryReservationStep;
143         Constants = constants;
144     }
145
146     /// <summary>
147     /// <para>
148     /// Initializes a new <see cref="UnitedMemoryLinksBase"/> instance.
149     /// </para>
150     /// <para></para>
151     /// </summary>
152     /// <param name="memory">
153     /// <para>A memory.</para>
154     /// <para></para>
155     /// </param>
156     /// <param name="memoryReservationStep">
157     /// <para>A memory reservation step.</para>
158     /// <para></para>
159     /// </param>
160     [MethodImpl(MethodImplOptions.AggressiveInlining)]
161     protected UnitedMemoryLinksBase(IResizableDirectMemory memory, long
162     ↪ memoryReservationStep) : this(memory, memoryReservationStep,
163     ↪ Default<LinksConstants<TLinkAddress>>.Instance) { }
164
165     /// <summary>
166     /// <para>
167     /// Inits the memory.
168     /// </para>
169     /// <para></para>
170     /// </summary>
171     /// <param name="memory">
172     /// <para>The memory.</para>
173     /// <para></para>
174     /// </param>
175     /// <param name="memoryReservationStep">
176     /// <para>The memory reservation step.</para>
177     /// <para></para>
178     /// </param>
179     [MethodImpl(MethodImplOptions.AggressiveInlining)]
180     protected virtual void Init(IResizableDirectMemory memory, long memoryReservationStep)
181     {
182         if (memory.ReservedCapacity < memoryReservationStep)
183         {
184             memory.ReservedCapacity = memoryReservationStep;
185         }
186     }

```

```

182     }
183     SetPointers(memory);
184     ref var header = ref GetHeaderReference();
185     // Гарантия корректности _memory.UsedCapacity относительно _header->AllocatedLinks
186     memory.UsedCapacity = (ConvertToInt64(header.AllocatedLinks) * LinkSizeInBytes) +
        ↪ LinkHeaderSizeInBytes;
187     // Гарантия корректности _header->ReservedLinks относительно _memory.ReservedCapacity
188     header.ReservedLinks = ConvertToAddress((memory.ReservedCapacity -
        ↪ LinkHeaderSizeInBytes) / LinkSizeInBytes);
189 }
190
191 /// <summary>
192 /// <para>
193 /// Counts the substitution.
194 /// </para>
195 /// <para></para>
196 /// </summary>
197 /// <param name="restriction">
198 /// <para>The substitution.</para>
199 /// <para></para>
200 /// </param>
201 /// <exception cref="NotSupportedException">
202 /// <para>Другие размеры и способы ограничений не поддерживаются.</para>
203 /// <para></para>
204 /// </exception>
205 /// <returns>
206 /// <para>The link</para>
207 /// <para></para>
208 /// </returns>
209 [MethodImpl(MethodImplOptions.AggressiveInlining)]
210 public virtual TLinkAddress Count(ICollection<TLinkAddress>? restriction)
211 {
212     // Если нет ограничений, тогда возвращаем общее число связей находящихся в хранилище.
213     if (restriction.Count == 0)
214     {
215         return Total;
216     }
217     var constants = Constants;
218     var any = constants.Any;
219     var index = this.GetIndex(restriction);
220     if (restriction.Count == 1)
221     {
222         if (AreEqual(index, any))
223         {
224             return Total;
225         }
226         return Exists(index) ? GetOne() : GetZero();
227     }
228     if (restriction.Count == 2)
229     {
230         var value = restriction[1];
231         if (AreEqual(index, any))
232         {
233             if (AreEqual(value, any))
234             {
235                 return Total; // Any - как отсутствие ограничения
236             }
237             return Add(SourcesTreeMethods.CountUsages(value),
                ↪ TargetsTreeMethods.CountUsages(value));
238         }
239         else
240         {
241             if (!Exists(index))
242             {
243                 return GetZero();
244             }
245             if (AreEqual(value, any))
246             {
247                 return GetOne();
248             }
249             ref var storedLinkValue = ref GetLinkReference(index);
250             if (AreEqual(storedLinkValue.Source, value) ||
                ↪ AreEqual(storedLinkValue.Target, value))
251             {
252                 return GetOne();
253             }
254             return GetZero();
255         }
256     }
257 }

```

```

256     }
257     if (restriction.Count == 3)
258     {
259         var source = this.GetSource(restriction);
260         var target = this.GetTarget(restriction);
261         if (AreEqual(index, any))
262         {
263             if (AreEqual(source, any) && AreEqual(target, any))
264             {
265                 return Total;
266             }
267             else if (AreEqual(source, any))
268             {
269                 return TargetsTreeMethods.CountUsages(target);
270             }
271             else if (AreEqual(target, any))
272             {
273                 return SourcesTreeMethods.CountUsages(source);
274             }
275             else //if(source != Any && target != Any)
276             {
277                 // Эквивалент Exists(source, target) => Count(Any, source, target) > 0
278                 var link = SourcesTreeMethods.Search(source, target);
279                 return AreEqual(link, constants.Null) ? GetZero() : GetOne();
280             }
281         }
282         else
283         {
284             if (!Exists(index))
285             {
286                 return GetZero();
287             }
288             if (AreEqual(source, any) && AreEqual(target, any))
289             {
290                 return GetOne();
291             }
292             ref var storedLinkValue = ref GetLinkReference(index);
293             if (!AreEqual(source, any) && !AreEqual(target, any))
294             {
295                 if (AreEqual(storedLinkValue.Source, source) &&
296                     ⇨ AreEqual(storedLinkValue.Target, target))
297                 {
298                     return GetOne();
299                 }
300                 return GetZero();
301             }
302             var value = default(TLinkAddress);
303             if (AreEqual(source, any))
304             {
305                 value = target;
306             }
307             if (AreEqual(target, any))
308             {
309                 value = source;
310             }
311             if (AreEqual(storedLinkValue.Source, value) ||
312                 ⇨ AreEqual(storedLinkValue.Target, value))
313             {
314                 return GetOne();
315             }
316             return GetZero();
317         }
318     }
319     throw new NotSupportedException("Другие размеры и способы ограничений не
320     ⇨ поддерживаются.");
321 }
322
323 /// <summary>
324 /// <para>
325 /// Eaches the handler.
326 /// </para>
327 /// <para></para>
328 /// </summary>
329 /// <param name="handler">
330 /// <para>The handler.</para>
331 /// <para></para>
332 /// </param>
333 /// <param name="restriction">

```

```

331 /// <para>The substitution.</para>
332 /// <para></para>
333 /// </param>
334 /// <exception cref="NotSupportedException">
335 /// <para>Другие размеры и способы ограничений не поддерживаются.</para>
336 /// <para></para>
337 /// </exception>
338 /// <returns>
339 /// <para>The link</para>
340 /// <para></para>
341 /// </returns>
342 [MethodImpl(MethodImplOptions.AggressiveInlining)]
343 public virtual TLinkAddress Each(IList<TLinkAddress>? restriction,
    ↳ ReadHandler<TLinkAddress>? handler)
344 {
345     var constants = Constants;
346     var @break = constants.Break;
347     if (restriction.Count == 0)
348     {
349         for (var link = GetOne(); LessOrEqualThan(link,
    ↳ GetHeaderReference().AllocatedLinks); link = Increment(link))
350         {
351             if (Exists(link) && AreEqual(handler(GetLinkStruct(link)), @break))
352             {
353                 return @break;
354             }
355         }
356         return @break;
357     }
358     var @continue = constants.Continue;
359     var any = constants.Any;
360     var index = this.GetIndex(restriction);
361     if (restriction.Count == 1)
362     {
363         if (AreEqual(index, any))
364         {
365             return Each(Array.Empty<TLinkAddress>(), handler);
366         }
367         if (!Exists(index))
368         {
369             return @continue;
370         }
371         return handler(GetLinkStruct(index));
372     }
373     if (restriction.Count == 2)
374     {
375         var value = restriction[1];
376         if (AreEqual(index, any))
377         {
378             if (AreEqual(value, any))
379             {
380                 return Each(Array.Empty<TLinkAddress>(), handler);
381             }
382             if (AreEqual(Each(new Link<TLinkAddress>(index, value, any), handler),
    ↳ @break))
383             {
384                 return @break;
385             }
386             return Each(new Link<TLinkAddress>(index, any, value), handler);
387         }
388         else
389         {
390             if (!Exists(index))
391             {
392                 return @continue;
393             }
394             if (AreEqual(value, any))
395             {
396                 return handler(GetLinkStruct(index));
397             }
398             ref var storedLinkValue = ref GetLinkReference(index);
399             if (AreEqual(storedLinkValue.Source, value) ||
400                 AreEqual(storedLinkValue.Target, value))
401             {
402                 return handler(GetLinkStruct(index));
403             }
404             return @continue;
405         }
406     }

```

```

406     }
407     if (restriction.Count == 3)
408     {
409         var source = this.GetSource(restriction);
410         var target = this.GetTarget(restriction);
411         if (AreEqual(index, any))
412         {
413             if (AreEqual(source, any) && AreEqual(target, any))
414             {
415                 return Each(Array.Empty<TLinkAddress>(), handler);
416             }
417             else if (AreEqual(source, any))
418             {
419                 return TargetsTreeMethods.EachUsage(target, handler);
420             }
421             else if (AreEqual(target, any))
422             {
423                 return SourcesTreeMethods.EachUsage(source, handler);
424             }
425             else //if(source != Any && target != Any)
426             {
427                 var link = SourcesTreeMethods.Search(source, target);
428                 return AreEqual(link, constants.Null) ? @continue :
429                     ↪ handler(GetLinkStruct(link));
430             }
431         }
432         else
433         {
434             if (!Exists(index))
435             {
436                 return @continue;
437             }
438             if (AreEqual(source, any) && AreEqual(target, any))
439             {
440                 return handler(GetLinkStruct(index));
441             }
442             ref var storedLinkValue = ref GetLinkReference(index);
443             if (!AreEqual(source, any) && !AreEqual(target, any))
444             {
445                 if (AreEqual(storedLinkValue.Source, source) &&
446                     AreEqual(storedLinkValue.Target, target))
447                 {
448                     return handler(GetLinkStruct(index));
449                 }
450                 return @continue;
451             }
452             var value = default(TLinkAddress);
453             if (AreEqual(source, any))
454             {
455                 value = target;
456             }
457             if (AreEqual(target, any))
458             {
459                 value = source;
460             }
461             if (AreEqual(storedLinkValue.Source, value) ||
462                 AreEqual(storedLinkValue.Target, value))
463             {
464                 return handler(GetLinkStruct(index));
465             }
466             return @continue;
467         }
468     }
469     throw new NotSupportedException("Другие размеры и способы ограничений не
470     ↪ поддерживаются.");
471 }
472
473 /// <remarks>
474 /// TODO: Возможно можно перемещать значения, если указан индекс, но значение существует
475 ↪ в другом месте (но не в менеджере памяти, а в логике Links)
476 /// </remarks>
477 [MethodImpl(MethodImplOptions.AggressiveInlining)]
478 public virtual TLinkAddress Update(IList<TLinkAddress>? restriction,
479     ↪ IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler)
480 {
481     var constants = Constants;
482     var @null = constants.Null;
483     var linkIndex = this.GetIndex(restriction);

```



```

480     var before = GetLinkStruct(linkIndex);
481     ref var link = ref GetLinkReference(linkIndex);
482     ref var header = ref GetHeaderReference();
483     ref var firstAsSource = ref header.RootAsSource;
484     ref var firstAsTarget = ref header.RootAsTarget;
485     // Будет корректно работать только в том случае, если пространство выделенной связи
486     //   ↳ предварительно заполнено нулями
487     if (!AreEqual(link.Source, @null))
488     {
489         SourcesTreeMethods.Detach(ref firstAsSource, linkIndex);
490     }
491     if (!AreEqual(link.Target, @null))
492     {
493         TargetsTreeMethods.Detach(ref firstAsTarget, linkIndex);
494     }
495     link.Source = this.GetSource(substitution);
496     link.Target = this.GetTarget(substitution);
497     if (!AreEqual(link.Source, @null))
498     {
499         SourcesTreeMethods.Attach(ref firstAsSource, linkIndex);
500     }
501     if (!AreEqual(link.Target, @null))
502     {
503         TargetsTreeMethods.Attach(ref firstAsTarget, linkIndex);
504     }
505     return handler?.Invoke(before, GetLinkStruct(linkIndex)) ?? Constants.Continue;
506 }
507
508 /// <remarks>
509 /// TODO: Возможно нужно будет заполнение нулями, если внешнее API ими не заполняет
510 ///   ↳ пространство
511 /// </remarks>
512 [MethodImpl(MethodImplOptions.AggressiveInlining)]
513 public virtual TLinkAddress Create(ICollection<TLinkAddress>? substitution,
514     //   ↳ WriteHandler<TLinkAddress>? handler)
515 {
516     ref var header = ref GetHeaderReference();
517     var freeLink = header.FirstFreeLink;
518     if (!AreEqual(freeLink, Constants.Null))
519     {
520         UnusedLinksListMethods.Detach(freeLink);
521     }
522     else
523     {
524         {
525             var maximumPossibleInnerReference = Constants.InternalReferencesRange.Maximum;
526             if (GreaterThan(header.AllocatedLinks, maximumPossibleInnerReference))
527             {
528                 throw new
529                     //   ↳ LinksLimitReachedException<TLinkAddress>(maximumPossibleInnerReference);
530             }
531             if (GreaterOrEqualThan(header.AllocatedLinks, Decrement(header.ReservedLinks)))
532             {
533                 _memory.ReservedCapacity += _memory.ReservationStep;
534                 SetPointers(_memory);
535                 header = ref GetHeaderReference();
536                 header.ReservedLinks = ConvertToAddress(_memory.ReservedCapacity /
537                     //   ↳ LinkSizeInBytes);
538             }
539             freeLink = header.AllocatedLinks = Increment(header.AllocatedLinks);
540             _memory.UsedCapacity += LinkSizeInBytes;
541         }
542     }
543     return handler?.Invoke(null, new Link<TLinkAddress>(freeLink, Constants.Null,
544         //   ↳ Constants.Null)) ?? Constants.Continue;
545 }
546
547 /// <summary>
548 /// <para>
549 /// Deletes the substitution.
550 /// </para>
551 /// <para></para>
552 /// </summary>
553 /// <param name="restriction">
554 /// <para>The substitution.</para>
555 /// <para></para>
556 /// </param>
557 [MethodImpl(MethodImplOptions.AggressiveInlining)]
558 public virtual TLinkAddress Delete(ICollection<TLinkAddress>? restriction,
559     //   ↳ WriteHandler<TLinkAddress>? handler)

```

```

551 {
552     ref var header = ref GetHeaderReference();
553     var link = restriction[Constants.IndexPart];
554     var before = GetLinkStruct(link);
555     if (LessThan(link, header.AllocatedLinks))
556     {
557         UnusedLinksListMethods.AttachAsFirst(link);
558         return handler?.Invoke(before, null) ?? Constants.Continue;
559     }
560     else if (AreEqual(link, header.AllocatedLinks))
561     {
562         header.AllocatedLinks = Decrement(header.AllocatedLinks);
563         _memory.UsedCapacity -= LinkSizeInBytes;
564         // Убираем все связи, находящиеся в списке свободных в конце файла, до тех пор,
565         // → пока не дойдём до первой существующей связи
566         // Позволяет оптимизировать количество выделенных связей (AllocatedLinks)
567         while (GreaterThan(header.AllocatedLinks, GetZero()) &&
568             → IsUnusedLink(header.AllocatedLinks))
569         {
570             UnusedLinksListMethods.Detach(header.AllocatedLinks);
571             header.AllocatedLinks = Decrement(header.AllocatedLinks);
572             _memory.UsedCapacity -= LinkSizeInBytes;
573         }
574         return handler?.Invoke(before, null) ?? Constants.Continue;
575     }
576     return Constants.Continue;
577 }
578
579 /// <summary>
580 /// <para>
581 /// Gets the link struct using the specified link index.
582 /// </para>
583 /// <para></para>
584 /// </summary>
585 /// <param name="linkIndex">
586 /// <para>The link index.</para>
587 /// <para></para>
588 /// </param>
589 /// <returns>
590 /// <para>A list of t link</para>
591 /// <para></para>
592 /// </returns>
593 [MethodImpl(MethodImplOptions.AggressiveInlining)]
594 public IList<TLinkAddress>? GetLinkStruct(TLinkAddress linkIndex)
595 {
596     ref var link = ref GetLinkReference(linkIndex);
597     return new Link<TLinkAddress>(linkIndex, link.Source, link.Target);
598 }
599
600 /// <remarks>
601 /// TODO: Возможно это должно быть событием, вызываемым из IMemory, в том случае, если
602 /// → адрес реально поменялся
603 ///
604 /// Указатель this.links может быть в том же месте,
605 /// так как 0-я связь не используется и имеет такой же размер как Header,
606 /// поэтому header размещается в том же месте, что и 0-я связь
607 /// </remarks>
608 [MethodImpl(MethodImplOptions.AggressiveInlining)]
609 protected abstract void SetPointers(IResizableDirectMemory memory);
610
611 /// <summary>
612 /// <para>
613 /// Resets the pointers.
614 /// </para>
615 /// <para></para>
616 /// </summary>
617 [MethodImpl(MethodImplOptions.AggressiveInlining)]
618 protected virtual void ResetPointers()
619 {
620     SourcesTreeMethods = null;
621     TargetsTreeMethods = null;
622     UnusedLinksListMethods = null;
623 }
624
625 /// <summary>
626 /// <para>
627 /// Gets the header reference.
628 /// </para>

```

```

626    /// <para></para>
627    /// </summary>
628    /// <returns>
629    /// <para>A ref links header of t link</para>
630    /// <para></para>
631    /// </returns>
632    [MethodImpl(MethodImplOptions.AggressiveInlining)]
633    protected abstract ref LinksHeader<TLinkAddress> GetHeaderReference();
634
635    /// <summary>
636    /// <para>
637    /// Gets the link reference using the specified link index.
638    /// </para>
639    /// <para></para>
640    /// </summary>
641    /// <param name="linkIndex">
642    /// <para>The link index.</para>
643    /// <para></para>
644    /// </param>
645    /// <returns>
646    /// <para>A ref raw link of t link</para>
647    /// <para></para>
648    /// </returns>
649    [MethodImpl(MethodImplOptions.AggressiveInlining)]
650    protected abstract ref RawLink<TLinkAddress> GetLinkReference(TLinkAddress linkIndex);
651
652    /// <summary>
653    /// <para>
654    /// Determines whether this instance exists.
655    /// </para>
656    /// <para></para>
657    /// </summary>
658    /// <param name="link">
659    /// <para>The link.</para>
660    /// <para></para>
661    /// </param>
662    /// <returns>
663    /// <para>The bool</para>
664    /// <para></para>
665    /// </returns>
666    [MethodImpl(MethodImplOptions.AggressiveInlining)]
667    protected virtual bool Exists(TLinkAddress link)
668        => GreaterOrEqualThan(link, Constants.InternalReferencesRange.Minimum)
669        && LessOrEqualThan(link, GetHeaderReference().AllocatedLinks)
670        && !IsUnusedLink(link);
671
672    /// <summary>
673    /// <para>
674    /// Determines whether this instance is unused link.
675    /// </para>
676    /// <para></para>
677    /// </summary>
678    /// <param name="linkIndex">
679    /// <para>The link index.</para>
680    /// <para></para>
681    /// </param>
682    /// <returns>
683    /// <para>The bool</para>
684    /// <para></para>
685    /// </returns>
686    [MethodImpl(MethodImplOptions.AggressiveInlining)]
687    protected virtual bool IsUnusedLink(TLinkAddress linkIndex)
688    {
689        if (!AreEqual(GetHeaderReference().FirstFreeLink, linkIndex)) // May be this check
690            ↪ is not needed
691        {
692            ref var link = ref GetLinkReference(linkIndex);
693            return AreEqual(link.SizeAsSource, default) && !AreEqual(link.Source, default);
694        }
695        else
696        {
697            return true;
698        }
699    }
700
701    /// <summary>
702    /// <para>
703    /// Gets the one.

```

```

703     /// </para>
704     /// <para></para>
705     /// </summary>
706     /// <returns>
707     /// <para>The link</para>
708     /// <para></para>
709     /// </returns>
710     [MethodImpl(MethodImplOptions.AggressiveInlining)]
711     protected virtual TLinkAddress GetOne() => _one;
712
713     /// <summary>
714     /// <para>
715     /// Gets the zero.
716     /// </para>
717     /// <para></para>
718     /// </summary>
719     /// <returns>
720     /// <para>The link</para>
721     /// <para></para>
722     /// </returns>
723     [MethodImpl(MethodImplOptions.AggressiveInlining)]
724     protected virtual TLinkAddress GetZero() => default;
725
726     /// <summary>
727     /// <para>
728     /// Determines whether this instance are equal.
729     /// </para>
730     /// <para></para>
731     /// </summary>
732     /// <param name="first">
733     /// <para>The first.</para>
734     /// <para></para>
735     /// </param>
736     /// <param name="second">
737     /// <para>The second.</para>
738     /// <para></para>
739     /// </param>
740     /// <returns>
741     /// <para>The bool</para>
742     /// <para></para>
743     /// </returns>
744     [MethodImpl(MethodImplOptions.AggressiveInlining)]
745     protected virtual bool AreEqual(TLinkAddress first, TLinkAddress second) =>
746         ↪ _equalityComparer.Equals(first, second);
747
748     /// <summary>
749     /// <para>
750     /// Determines whether this instance less than.
751     /// </para>
752     /// <para></para>
753     /// </summary>
754     /// <param name="first">
755     /// <para>The first.</para>
756     /// <para></para>
757     /// </param>
758     /// <param name="second">
759     /// <para>The second.</para>
760     /// <para></para>
761     /// </param>
762     /// <returns>
763     /// <para>The bool</para>
764     /// <para></para>
765     /// </returns>
766     [MethodImpl(MethodImplOptions.AggressiveInlining)]
767     protected virtual bool LessThan(TLinkAddress first, TLinkAddress second) =>
768         ↪ _comparer.Compare(first, second) < 0;
769
770     /// <summary>
771     /// <para>
772     /// Determines whether this instance less or equal than.
773     /// </para>
774     /// <para></para>
775     /// </summary>
776     /// <param name="first">
777     /// <para>The first.</para>
778     /// <para></para>
779     /// </param>
780     /// <param name="second">

```

```

779    /// <para>The second.</para>
780    /// <para></para>
781    /// </param>
782    /// <returns>
783    /// <para>The bool</para>
784    /// <para></para>
785    /// </returns>
786    [MethodImpl(MethodImplOptions.AggressiveInlining)]
787    protected virtual bool LessOrEqualThan(TLinkAddress first, TLinkAddress second) =>
788        ↪ _comparer.Compare(first, second) <= 0;
789
790    /// <summary>
791    /// <para>
792    /// Determines whether this instance greater than.
793    /// </para>
794    /// <para></para>
795    /// </summary>
796    /// <param name="first">
797    /// <para>The first.</para>
798    /// <para></para>
799    /// </param>
800    /// <param name="second">
801    /// <para>The second.</para>
802    /// <para></para>
803    /// </param>
804    /// <returns>
805    /// <para>The bool</para>
806    /// <para></para>
807    /// </returns>
808    [MethodImpl(MethodImplOptions.AggressiveInlining)]
809    protected virtual bool GreaterThan(TLinkAddress first, TLinkAddress second) =>
810        ↪ _comparer.Compare(first, second) > 0;
811
812    /// <summary>
813    /// <para>
814    /// Determines whether this instance greater or equal than.
815    /// </para>
816    /// <para></para>
817    /// </summary>
818    /// <param name="first">
819    /// <para>The first.</para>
820    /// <para></para>
821    /// </param>
822    /// <param name="second">
823    /// <para>The second.</para>
824    /// <para></para>
825    /// </param>
826    /// <returns>
827    /// <para>The bool</para>
828    /// <para></para>
829    /// </returns>
830    [MethodImpl(MethodImplOptions.AggressiveInlining)]
831    protected virtual bool GreaterOrEqualThan(TLinkAddress first, TLinkAddress second) =>
832        ↪ _comparer.Compare(first, second) >= 0;
833
834    /// <summary>
835    /// <para>
836    /// Converts the to int 64 using the specified value.
837    /// </para>
838    /// <para></para>
839    /// </summary>
840    /// <param name="value">
841    /// <para>The value.</para>
842    /// <para></para>
843    /// </param>
844    /// <returns>
845    /// <para>The long</para>
846    /// <para></para>
847    /// </returns>
848    [MethodImpl(MethodImplOptions.AggressiveInlining)]
849    protected virtual long ConvertToInt64(TLinkAddress value) =>
850        ↪ _addressToInt64Converter.Convert(value);
851
852    /// <summary>
853    /// <para>
854    /// Converts the to address using the specified value.
855    /// </para>
856    /// <para></para>

```

```

853     /// </summary>
854     /// <param name="value">
855     /// <para>The value.</para>
856     /// <para></para>
857     /// </param>
858     /// <returns>
859     /// <para>The link</para>
860     /// <para></para>
861     /// </returns>
862     [MethodImpl(MethodImplOptions.AggressiveInlining)]
863     protected virtual TLinkAddress ConvertToAddress(long value) =>
864         ↪ _int64ToAddressConverter.Convert(value);
865
866     /// <summary>
867     /// <para>
868     /// Adds the first.
869     /// </para>
870     /// <para></para>
871     /// </summary>
872     /// <param name="first">
873     /// <para>The first.</para>
874     /// <para></para>
875     /// </param>
876     /// <param name="second">
877     /// <para>The second.</para>
878     /// <para></para>
879     /// </param>
880     /// <returns>
881     /// <para>The link</para>
882     /// <para></para>
883     /// </returns>
884     [MethodImpl(MethodImplOptions.AggressiveInlining)]
885     protected virtual TLinkAddress Add(TLinkAddress first, TLinkAddress second) =>
886         ↪ Arithmetic<TLinkAddress>.Add(first, second);
887
888     /// <summary>
889     /// <para>
890     /// Subtracts the first.
891     /// </para>
892     /// <para></para>
893     /// </summary>
894     /// <param name="first">
895     /// <para>The first.</para>
896     /// <para></para>
897     /// </param>
898     /// <param name="second">
899     /// <para>The second.</para>
900     /// <para></para>
901     /// </param>
902     /// <returns>
903     /// <para>The link</para>
904     /// <para></para>
905     /// </returns>
906     [MethodImpl(MethodImplOptions.AggressiveInlining)]
907     protected virtual TLinkAddress Subtract(TLinkAddress first, TLinkAddress second) =>
908         ↪ Arithmetic<TLinkAddress>.Subtract(first, second);
909
910     /// <summary>
911     /// <para>
912     /// Increments the link.
913     /// </para>
914     /// <para></para>
915     /// </summary>
916     /// <param name="link">
917     /// <para>The link.</para>
918     /// <para></para>
919     /// </param>
920     /// <returns>
921     /// <para>The link</para>
922     /// <para></para>
923     /// </returns>
924     [MethodImpl(MethodImplOptions.AggressiveInlining)]
925     protected virtual TLinkAddress Increment(TLinkAddress link) =>
926         ↪ Arithmetic<TLinkAddress>.Increment(link);
927
928     /// <summary>
929     /// <para>
930     /// Decrements the link.

```

```

927     /// </para>
928     /// <para></para>
929     /// </summary>
930     /// <param name="link">
931     /// <para>The link.</para>
932     /// <para></para>
933     /// </param>
934     /// <returns>
935     /// <para>The link</para>
936     /// <para></para>
937     /// </returns>
938     [MethodImpl(MethodImplOptions.AggressiveInlining)]
939     protected virtual TLinkAddress Decrement(TLinkAddress link) =>
        ↪ Arithmetic<TLinkAddress>.Decrement(link);

940
941     #region Disposable
942
943     /// <summary>
944     /// <para>
945     /// Gets the allow multiple dispose calls value.
946     /// </para>
947     /// <para></para>
948     /// </summary>
949     protected override bool AllowMultipleDisposeCalls
950     {
951         [MethodImpl(MethodImplOptions.AggressiveInlining)]
952         get => true;
953     }
954
955     /// <summary>
956     /// <para>
957     /// Disposes the manual.
958     /// </para>
959     /// <para></para>
960     /// </summary>
961     /// <param name="manual">
962     /// <para>The manual.</para>
963     /// <para></para>
964     /// </param>
965     /// <param name="wasDisposed">
966     /// <para>The was disposed.</para>
967     /// <para></para>
968     /// </param>
969     [MethodImpl(MethodImplOptions.AggressiveInlining)]
970     protected override void Dispose(bool manual, bool wasDisposed)
971     {
972         if (!wasDisposed)
973         {
974             ResetPointers();
975             _memory.DisposeIfPossible();
976         }
977     }
978
979     #endregion
980 }
981 }

```

1.91 ./csharp/Platform.Data.Doublets/Memory/United/Generic/UnusedLinksListMethods.cs

```

1  using System.Runtime.CompilerServices;
2  using Platform.Collections.Methods.Lists;
3  using Platform.Converters;
4  using static System.Runtime.CompilerServices.Unsafe;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Memory.United.Generic
9  {
10     /// <summary>
11     /// <para>
12     /// Represents the unused links list methods.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     /// <seealso cref="AbsoluteCircularDoublyLinkedListMethods{TLinkAddress}"/>
17     /// <seealso cref="ILinksListMethods{TLinkAddress}"/>
18     public unsafe class UnusedLinksListMethods<TLinkAddress> :
        ↪ AbsoluteCircularDoublyLinkedListMethods<TLinkAddress>, ILinksListMethods<TLinkAddress>
19     {

```

```

20 private static readonly UncheckedConverter<TLinkAddress, long> _addressToInt64Converter
    ↪ = UncheckedConverter<TLinkAddress, long>.Default;
21 private readonly byte* _links;
22 private readonly byte* _header;
23
24 /// <summary>
25 /// <para>
26 /// Initializes a new <see cref="UnusedLinksListMethods"/> instance.
27 /// </para>
28 /// <para></para>
29 /// </summary>
30 /// <param name="links">
31 /// <para>A links.</para>
32 /// <para></para>
33 /// </param>
34 /// <param name="header">
35 /// <para>A header.</para>
36 /// <para></para>
37 /// </param>
38 [MethodImpl(MethodImplOptions.AggressiveInlining)]
39 public UnusedLinksListMethods(byte* links, byte* header)
40 {
41     _links = links;
42     _header = header;
43 }
44
45 /// <summary>
46 /// <para>
47 /// Gets the header reference.
48 /// </para>
49 /// <para></para>
50 /// </summary>
51 /// <returns>
52 /// <para>A ref links header of t link</para>
53 /// <para></para>
54 /// </returns>
55 [MethodImpl(MethodImplOptions.AggressiveInlining)]
56 protected virtual ref LinksHeader<TLinkAddress> GetHeaderReference() => ref
    ↪ AsRef<LinksHeader<TLinkAddress>>(_header);
57
58 /// <summary>
59 /// <para>
60 /// Gets the link reference using the specified link.
61 /// </para>
62 /// <para></para>
63 /// </summary>
64 /// <param name="link">
65 /// <para>The link.</para>
66 /// <para></para>
67 /// </param>
68 /// <returns>
69 /// <para>A ref raw link of t link</para>
70 /// <para></para>
71 /// </returns>
72 [MethodImpl(MethodImplOptions.AggressiveInlining)]
73 protected virtual ref RawLink<TLinkAddress> GetLinkReference(TLinkAddress link) => ref
    ↪ AsRef<RawLink<TLinkAddress>>(_links + (RawLink<TLinkAddress>.SizeInBytes *
    ↪ _addressToInt64Converter.Convert(link)));
74
75 /// <summary>
76 /// <para>
77 /// Gets the first.
78 /// </para>
79 /// <para></para>
80 /// </summary>
81 /// <returns>
82 /// <para>The link</para>
83 /// <para></para>
84 /// </returns>
85 [MethodImpl(MethodImplOptions.AggressiveInlining)]
86 protected override TLinkAddress GetFirst() => GetHeaderReference().FirstFreeLink;
87
88 /// <summary>
89 /// <para>
90 /// Gets the last.
91 /// </para>
92 /// <para></para>
93 /// </summary>

```



```

94     /// <returns>
95     /// <para>The link</para>
96     /// <para></para>
97     /// </returns>
98     [MethodImpl(MethodImplOptions.AggressiveInlining)]
99     protected override TLinkAddress GetLast() => GetHeaderReference().LastFreeLink;
100
101     /// <summary>
102     /// <para>
103     /// Gets the previous using the specified element.
104     /// </para>
105     /// <para></para>
106     /// </summary>
107     /// <param name="element">
108     /// <para>The element.</para>
109     /// <para></para>
110     /// </param>
111     /// <returns>
112     /// <para>The link</para>
113     /// <para></para>
114     /// </returns>
115     [MethodImpl(MethodImplOptions.AggressiveInlining)]
116     protected override TLinkAddress GetPrevious(TLinkAddress element) =>
117         ↪ GetLinkReference(element).Source;
118
119     /// <summary>
120     /// <para>
121     /// Gets the next using the specified element.
122     /// </para>
123     /// <para></para>
124     /// </summary>
125     /// <param name="element">
126     /// <para>The element.</para>
127     /// <para></para>
128     /// </param>
129     /// <returns>
130     /// <para>The link</para>
131     /// <para></para>
132     /// </returns>
133     [MethodImpl(MethodImplOptions.AggressiveInlining)]
134     protected override TLinkAddress GetNext(TLinkAddress element) =>
135         ↪ GetLinkReference(element).Target;
136
137     /// <summary>
138     /// <para>
139     /// Gets the size.
140     /// </para>
141     /// <para></para>
142     /// </summary>
143     /// <returns>
144     /// <para>The link</para>
145     /// <para></para>
146     /// </returns>
147     [MethodImpl(MethodImplOptions.AggressiveInlining)]
148     protected override TLinkAddress GetSize() => GetHeaderReference().FreeLinks;
149
150     /// <summary>
151     /// <para>
152     /// Sets the first using the specified element.
153     /// </para>
154     /// <para></para>
155     /// </summary>
156     /// <param name="element">
157     /// <para>The element.</para>
158     /// <para></para>
159     /// </param>
160     [MethodImpl(MethodImplOptions.AggressiveInlining)]
161     protected override void SetFirst(TLinkAddress element) =>
162         ↪ GetHeaderReference().FirstFreeLink = element;
163
164     /// <summary>
165     /// <para>
166     /// Sets the last using the specified element.
167     /// </para>
168     /// <para></para>
169     /// </summary>
170     /// <param name="element">
171     /// <para>The element.</para>
172     /// <para></para>
173     /// </param>

```

```

169     /// <para></para>
170     /// </param>
171     [MethodImpl(MethodImplOptions.AggressiveInlining)]
172     protected override void SetLast(TLinkAddress element) =>
173         ↪ GetHeaderReference().LastFreeLink = element;
174
175     /// <summary>
176     /// <para>
177     /// Sets the previous using the specified element.
178     /// </para>
179     /// </summary>
180     /// <param name="element">
181     /// <para>The element.</para>
182     /// </para>
183     /// </param>
184     /// <param name="previous">
185     /// <para>The previous.</para>
186     /// </para>
187     /// </param>
188     [MethodImpl(MethodImplOptions.AggressiveInlining)]
189     protected override void SetPrevious(TLinkAddress element, TLinkAddress previous) =>
190         ↪ GetLinkReference(element).Source = previous;
191
192     /// <summary>
193     /// <para>
194     /// Sets the next using the specified element.
195     /// </para>
196     /// </summary>
197     /// <param name="element">
198     /// <para>The element.</para>
199     /// </para>
200     /// </param>
201     /// <param name="next">
202     /// <para>The next.</para>
203     /// </para>
204     /// </param>
205     [MethodImpl(MethodImplOptions.AggressiveInlining)]
206     protected override void SetNext(TLinkAddress element, TLinkAddress next) =>
207         ↪ GetLinkReference(element).Target = next;
208
209     /// <summary>
210     /// <para>
211     /// Sets the size using the specified size.
212     /// </para>
213     /// </summary>
214     /// <param name="size">
215     /// <para>The size.</para>
216     /// </para>
217     /// </param>
218     [MethodImpl(MethodImplOptions.AggressiveInlining)]
219     protected override void SetSize(TLinkAddress size) => GetHeaderReference().FreeLinks =
220         ↪ size;
221     }

```

1.92 ./csharp/Platform.Data.Doublets/Memory/United/RawLink.cs

```

1  using Platform.Unsafe;
2  using System;
3  using System.Collections.Generic;
4  using System.Runtime.CompilerServices;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Memory.United
9  {
10     /// <summary>
11     /// <para>
12     /// The raw link.
13     /// </para>
14     /// </summary>
15     public struct RawLink<TLinkAddress> : IEquatable<RawLink<TLinkAddress>>
16     {
17         private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
18             ↪ EqualityComparer<TLinkAddress>.Default;
19

```

```

20     /// <summary>
21     /// <para>
22     /// The size.
23     /// </para>
24     /// <para></para>
25     /// </summary>
26     public static readonly long SizeInBytes = Structure<RawLink<TLinkAddress>>.Size;
27
28     /// <summary>
29     /// <para>
30     /// The source.
31     /// </para>
32     /// <para></para>
33     /// </summary>
34     public TLinkAddress Source;
35     /// <summary>
36     /// <para>
37     /// The target.
38     /// </para>
39     /// <para></para>
40     /// </summary>
41     public TLinkAddress Target;
42     /// <summary>
43     /// <para>
44     /// The left as source.
45     /// </para>
46     /// <para></para>
47     /// </summary>
48     public TLinkAddress LeftAsSource;
49     /// <summary>
50     /// <para>
51     /// The right as source.
52     /// </para>
53     /// <para></para>
54     /// </summary>
55     public TLinkAddress RightAsSource;
56     /// <summary>
57     /// <para>
58     /// The size as source.
59     /// </para>
60     /// <para></para>
61     /// </summary>
62     public TLinkAddress SizeAsSource;
63     /// <summary>
64     /// <para>
65     /// The left as target.
66     /// </para>
67     /// <para></para>
68     /// </summary>
69     public TLinkAddress LeftAsTarget;
70     /// <summary>
71     /// <para>
72     /// The right as target.
73     /// </para>
74     /// <para></para>
75     /// </summary>
76     public TLinkAddress RightAsTarget;
77     /// <summary>
78     /// <para>
79     /// The size as target.
80     /// </para>
81     /// <para></para>
82     /// </summary>
83     public TLinkAddress SizeAsTarget;
84
85     /// <summary>
86     /// <para>
87     /// Determines whether this instance equals.
88     /// </para>
89     /// <para></para>
90     /// </summary>
91     /// <param name="obj">
92     /// <para>The obj.</para>
93     /// <para></para>
94     /// </param>
95     /// <returns>
96     /// <para>The bool</para>
97     /// <para></para>

```

```

98     /// </returns>
99     [MethodImpl(MethodImplOptions.AggressiveInlining)]
100    public override bool Equals(object obj) => obj is RawLink<TLinkAddress> link ?
        ↳ Equals(link) : false;

101
102    /// <summary>
103    /// <para>
104    /// Determines whether this instance equals.
105    /// </para>
106    /// <para></para>
107    /// </summary>
108    /// <param name="other">
109    /// <para>The other.</para>
110    /// <para></para>
111    /// </param>
112    /// <returns>
113    /// <para>The bool</para>
114    /// <para></para>
115    /// </returns>
116    [MethodImpl(MethodImplOptions.AggressiveInlining)]
117    public bool Equals(RawLink<TLinkAddress> other)
118        => _equalityComparer.Equals(Source, other.Source)
119        && _equalityComparer.Equals(Target, other.Target)
120        && _equalityComparer.Equals(LeftAsSource, other.LeftAsSource)
121        && _equalityComparer.Equals(RightAsSource, other.RightAsSource)
122        && _equalityComparer.Equals(SizeAsSource, other.SizeAsSource)
123        && _equalityComparer.Equals(LeftAsTarget, other.LeftAsTarget)
124        && _equalityComparer.Equals(RightAsTarget, other.RightAsTarget)
125        && _equalityComparer.Equals(SizeAsTarget, other.SizeAsTarget);

126
127    /// <summary>
128    /// <para>
129    /// Gets the hash code.
130    /// </para>
131    /// <para></para>
132    /// </summary>
133    /// <returns>
134    /// <para>The int</para>
135    /// <para></para>
136    /// </returns>
137    [MethodImpl(MethodImplOptions.AggressiveInlining)]
138    public override int GetHashCode() => (Source, Target, LeftAsSource, RightAsSource,
        ↳ SizeAsSource, LeftAsTarget, RightAsTarget, SizeAsTarget).GetHashCode();

139
140    [MethodImpl(MethodImplOptions.AggressiveInlining)]
141    public static bool operator ==(RawLink<TLinkAddress> left, RawLink<TLinkAddress> right)
142        ↳ => left.Equals(right);

143
144    [MethodImpl(MethodImplOptions.AggressiveInlining)]
145    public static bool operator !=(RawLink<TLinkAddress> left, RawLink<TLinkAddress> right)
146        ↳ => !(left == right);
}
}

```

1.93 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksRecursionlessSizeBalancedTreeMethods

```

1  using System.Runtime.CompilerServices;
2  using Platform.Data.Doublets.Memory.United.Generic;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.United.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 32 links recursionless size balanced tree methods base.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="LinksRecursionlessSizeBalancedTreeMethodsBase{uint}"/>
15     public unsafe abstract class UInt32LinksRecursionlessSizeBalancedTreeMethodsBase :
        ↳ LinksRecursionlessSizeBalancedTreeMethodsBase<uint>
16     {
17         /// <summary>
18         /// <para>
19         /// The links.
20         /// </para>
21         /// <para></para>
22         /// </summary>

```

```

23     protected new readonly RawLink<uint>* Links;
24     /// <summary>
25     /// <para>
26     /// The header.
27     /// </para>
28     /// <para></para>
29     /// </summary>
30     protected new readonly LinksHeader<uint>* Header;
31
32     /// <summary>
33     /// <para>
34     /// Initializes a new <see cref="UInt32LinksRecursionlessSizeBalancedTreeMethodsBase"/>
35     ↪ instance.
36     /// </para>
37     /// <para></para>
38     /// </summary>
39     /// <param name="constants">
40     /// <para>A constants.</para>
41     /// <para></para>
42     /// </param>
43     /// <param name="links">
44     /// <para>A links.</para>
45     /// <para></para>
46     /// </param>
47     /// <param name="header">
48     /// <para>A header.</para>
49     /// <para></para>
50     /// </param>
51     protected UInt32LinksRecursionlessSizeBalancedTreeMethodsBase(LinksConstants<uint>
52     ↪ constants, RawLink<uint>* links, LinksHeader<uint>* header)
53     : base(constants, (byte*)links, (byte*)header)
54     {
55         Links = links;
56         Header = header;
57     }
58
59     /// <summary>
60     /// <para>
61     /// Gets the zero.
62     /// </para>
63     /// <para></para>
64     /// </summary>
65     /// <returns>
66     /// <para>The uint</para>
67     /// <para></para>
68     /// </returns>
69     [MethodImpl(MethodImplOptions.AggressiveInlining)]
70     protected override uint GetZero() => 0U;
71
72     /// <summary>
73     /// <para>
74     /// Determines whether this instance equal to zero.
75     /// </para>
76     /// <para></para>
77     /// </summary>
78     /// <param name="value">
79     /// <para>The value.</para>
80     /// <para></para>
81     /// </param>
82     /// <returns>
83     /// <para>The bool</para>
84     /// <para></para>
85     /// </returns>
86     [MethodImpl(MethodImplOptions.AggressiveInlining)]
87     protected override bool EqualToZero(uint value) => value == 0U;
88
89     /// <summary>
90     /// <para>
91     /// Determines whether this instance are equal.
92     /// </para>
93     /// <para></para>
94     /// </summary>
95     /// <param name="first">
96     /// <para>The first.</para>
97     /// <para></para>
98     /// </param>
99     /// <param name="second">
100    /// <para>The second.</para>

```

```

99     /// <para></para>
100    /// </param>
101    /// <returns>
102    /// <para>The bool</para>
103    /// <para></para>
104    /// </returns>
105    [MethodImpl(MethodImplOptions.AggressiveInlining)]
106    protected override bool AreEqual(uint first, uint second) => first == second;
107
108    /// <summary>
109    /// <para>
110    /// Determines whether this instance greater than zero.
111    /// </para>
112    /// <para></para>
113    /// </summary>
114    /// <param name="value">
115    /// <para>The value.</para>
116    /// <para></para>
117    /// </param>
118    /// <returns>
119    /// <para>The bool</para>
120    /// <para></para>
121    /// </returns>
122    [MethodImpl(MethodImplOptions.AggressiveInlining)]
123    protected override bool GreaterThanZero(uint value) => value > 0U;
124
125    /// <summary>
126    /// <para>
127    /// Determines whether this instance greater than.
128    /// </para>
129    /// <para></para>
130    /// </summary>
131    /// <param name="first">
132    /// <para>The first.</para>
133    /// <para></para>
134    /// </param>
135    /// <param name="second">
136    /// <para>The second.</para>
137    /// <para></para>
138    /// </param>
139    /// <returns>
140    /// <para>The bool</para>
141    /// <para></para>
142    /// </returns>
143    [MethodImpl(MethodImplOptions.AggressiveInlining)]
144    protected override bool GreaterThan(uint first, uint second) => first > second;
145
146    /// <summary>
147    /// <para>
148    /// Determines whether this instance greater or equal than.
149    /// </para>
150    /// <para></para>
151    /// </summary>
152    /// <param name="first">
153    /// <para>The first.</para>
154    /// <para></para>
155    /// </param>
156    /// <param name="second">
157    /// <para>The second.</para>
158    /// <para></para>
159    /// </param>
160    /// <returns>
161    /// <para>The bool</para>
162    /// <para></para>
163    /// </returns>
164    [MethodImpl(MethodImplOptions.AggressiveInlining)]
165    protected override bool GreaterOrEqualThan(uint first, uint second) => first >= second;
166
167    /// <summary>
168    /// <para>
169    /// Determines whether this instance greater or equal than zero.
170    /// </para>
171    /// <para></para>
172    /// </summary>
173    /// <param name="value">
174    /// <para>The value.</para>
175    /// <para></para>
176    /// </param>

```

```

177     /// <returns>
178     /// <para>The bool</para>
179     /// <para></para>
180     /// </returns>
181     [MethodImpl(MethodImplOptions.AggressiveInlining)]
182     protected override bool GreaterOrEqualThanZero(uint value) => true; // value >= 0 is
    ↪ always true for uint

183
184     /// <summary>
185     /// <para>
186     /// Determines whether this instance less or equal than zero.
187     /// </para>
188     /// <para></para>
189     /// </summary>
190     /// <param name="value">
191     /// <para>The value.</para>
192     /// <para></para>
193     /// </param>
194     /// <returns>
195     /// <para>The bool</para>
196     /// <para></para>
197     /// </returns>
198     [MethodImpl(MethodImplOptions.AggressiveInlining)]
199     protected override bool LessOrEqualThanZero(uint value) => value == 0U; // value is
    ↪ always >= 0 for uint

200
201     /// <summary>
202     /// <para>
203     /// Determines whether this instance less or equal than.
204     /// </para>
205     /// <para></para>
206     /// </summary>
207     /// <param name="first">
208     /// <para>The first.</para>
209     /// <para></para>
210     /// </param>
211     /// <param name="second">
212     /// <para>The second.</para>
213     /// <para></para>
214     /// </param>
215     /// <returns>
216     /// <para>The bool</para>
217     /// <para></para>
218     /// </returns>
219     [MethodImpl(MethodImplOptions.AggressiveInlining)]
220     protected override bool LessOrEqualThan(uint first, uint second) => first <= second;

221
222     /// <summary>
223     /// <para>
224     /// Determines whether this instance less than zero.
225     /// </para>
226     /// <para></para>
227     /// </summary>
228     /// <param name="value">
229     /// <para>The value.</para>
230     /// <para></para>
231     /// </param>
232     /// <returns>
233     /// <para>The bool</para>
234     /// <para></para>
235     /// </returns>
236     [MethodImpl(MethodImplOptions.AggressiveInlining)]
237     protected override bool LessThanZero(uint value) => false; // value < 0 is always false
    ↪ for uint

238
239     /// <summary>
240     /// <para>
241     /// Determines whether this instance less than.
242     /// </para>
243     /// <para></para>
244     /// </summary>
245     /// <param name="first">
246     /// <para>The first.</para>
247     /// <para></para>
248     /// </param>
249     /// <param name="second">
250     /// <para>The second.</para>
251     /// <para></para>

```

```

252     /// </param>
253     /// <returns>
254     /// <para>The bool</para>
255     /// <para></para>
256     /// </returns>
257     [MethodImpl(MethodImplOptions.AggressiveInlining)]
258     protected override bool LessThan(uint first, uint second) => first < second;
259
260     /// <summary>
261     /// <para>
262     /// Increments the value.
263     /// </para>
264     /// <para></para>
265     /// </summary>
266     /// <param name="value">
267     /// <para>The value.</para>
268     /// <para></para>
269     /// </param>
270     /// <returns>
271     /// <para>The uint</para>
272     /// <para></para>
273     /// </returns>
274     [MethodImpl(MethodImplOptions.AggressiveInlining)]
275     protected override uint Increment(uint value) => ++value;
276
277     /// <summary>
278     /// <para>
279     /// Decrements the value.
280     /// </para>
281     /// <para></para>
282     /// </summary>
283     /// <param name="value">
284     /// <para>The value.</para>
285     /// <para></para>
286     /// </param>
287     /// <returns>
288     /// <para>The uint</para>
289     /// <para></para>
290     /// </returns>
291     [MethodImpl(MethodImplOptions.AggressiveInlining)]
292     protected override uint Decrement(uint value) => --value;
293
294     /// <summary>
295     /// <para>
296     /// Adds the first.
297     /// </para>
298     /// <para></para>
299     /// </summary>
300     /// <param name="first">
301     /// <para>The first.</para>
302     /// <para></para>
303     /// </param>
304     /// <param name="second">
305     /// <para>The second.</para>
306     /// <para></para>
307     /// </param>
308     /// <returns>
309     /// <para>The uint</para>
310     /// <para></para>
311     /// </returns>
312     [MethodImpl(MethodImplOptions.AggressiveInlining)]
313     protected override uint Add(uint first, uint second) => first + second;
314
315     /// <summary>
316     /// <para>
317     /// Subtracts the first.
318     /// </para>
319     /// <para></para>
320     /// </summary>
321     /// <param name="first">
322     /// <para>The first.</para>
323     /// <para></para>
324     /// </param>
325     /// <param name="second">
326     /// <para>The second.</para>
327     /// <para></para>
328     /// </param>
329     /// <returns>

```



```

330 /// <para>The uint</para>
331 /// <para></para>
332 /// </returns>
333 [MethodImpl(MethodImplOptions.AggressiveInlining)]
334 protected override uint Subtract(uint first, uint second) => first - second;
335
336 /// <summary>
337 /// <para>
338 /// Determines whether this instance first is to the left of second.
339 /// </para>
340 /// <para></para>
341 /// </summary>
342 /// <param name="first">
343 /// <para>The first.</para>
344 /// <para></para>
345 /// </param>
346 /// <param name="second">
347 /// <para>The second.</para>
348 /// <para></para>
349 /// </param>
350 /// <returns>
351 /// <para>The bool</para>
352 /// <para></para>
353 /// </returns>
354 [MethodImpl(MethodImplOptions.AggressiveInlining)]
355 protected override bool FirstIsToLeftOfSecond(uint first, uint second)
356 {
357     ref var firstLink = ref Links[first];
358     ref var secondLink = ref Links[second];
359     return FirstIsToLeftOfSecond(firstLink.Source, firstLink.Target,
        ↪ secondLink.Source, secondLink.Target);
360 }
361
362 /// <summary>
363 /// <para>
364 /// Determines whether this instance first is to the right of second.
365 /// </para>
366 /// <para></para>
367 /// </summary>
368 /// <param name="first">
369 /// <para>The first.</para>
370 /// <para></para>
371 /// </param>
372 /// <param name="second">
373 /// <para>The second.</para>
374 /// <para></para>
375 /// </param>
376 /// <returns>
377 /// <para>The bool</para>
378 /// <para></para>
379 /// </returns>
380 [MethodImpl(MethodImplOptions.AggressiveInlining)]
381 protected override bool FirstIsToTheRightOfSecond(uint first, uint second)
382 {
383     ref var firstLink = ref Links[first];
384     ref var secondLink = ref Links[second];
385     return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
        ↪ secondLink.Source, secondLink.Target);
386 }
387
388 /// <summary>
389 /// <para>
390 /// Gets the header reference.
391 /// </para>
392 /// <para></para>
393 /// </summary>
394 /// <returns>
395 /// <para>A ref links header of uint</para>
396 /// <para></para>
397 /// </returns>
398 [MethodImpl(MethodImplOptions.AggressiveInlining)]
399 protected override ref LinksHeader<uint> GetHeaderReference() => ref *Header;
400
401 /// <summary>
402 /// <para>
403 /// Gets the link reference using the specified link.
404 /// </para>
405 /// <para></para>

```

```

406     /// </summary>
407     /// <param name="link">
408     /// <para>The link.</para>
409     /// <para></para>
410     /// </param>
411     /// <returns>
412     /// <para>A ref raw link of uint</para>
413     /// <para></para>
414     /// </returns>
415     [MethodImpl(MethodImplOptions.AggressiveInlining)]
416     protected override ref RawLink<uint> GetLinkReference(uint link) => ref Links[link];
417 }
418 }

```

1.94 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksSizeBalancedTreeMethodsBase.cs

```

1  using System.Runtime.CompilerServices;
2  using Platform.Data.Doublets.Memory.United.Generic;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.United.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 32 links size balanced tree methods base.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="LinksSizeBalancedTreeMethodsBase{uint}"/>
15     public unsafe abstract class UInt32LinksSizeBalancedTreeMethodsBase :
16     ↪ LinksSizeBalancedTreeMethodsBase<uint>
17     {
18         /// <summary>
19         /// <para>
20         /// The links.
21         /// </para>
22         /// <para></para>
23         /// </summary>
24         protected new readonly RawLink<uint>* Links;
25
26         /// <summary>
27         /// <para>
28         /// The header.
29         /// </para>
30         /// <para></para>
31         /// </summary>
32         protected new readonly LinksHeader<uint>* Header;
33
34         /// <summary>
35         /// <para>
36         /// Initializes a new <see cref="UInt32LinksSizeBalancedTreeMethodsBase"/> instance.
37         /// </para>
38         /// <para></para>
39         /// </summary>
40         /// <param name="constants">
41         /// <para>A constants.</para>
42         /// <para></para>
43         /// </param>
44         /// <param name="links">
45         /// <para>A links.</para>
46         /// <para></para>
47         /// </param>
48         /// <param name="header">
49         /// <para>A header.</para>
50         /// <para></para>
51         /// </param>
52         protected UInt32LinksSizeBalancedTreeMethodsBase(LinksConstants<uint> constants,
53     ↪ RawLink<uint>* links, LinksHeader<uint>* header)
54         : base(constants, (byte*)links, (byte*)header)
55         {
56             Links = links;
57             Header = header;
58         }
59
60         /// <summary>
61         /// <para>
62         /// Gets the zero.
63         /// </para>
64         /// <para></para>
65         /// </summary>

```

```

63     /// <returns>
64     /// <para>The uint</para>
65     /// <para></para>
66     /// </returns>
67     [MethodImpl(MethodImplOptions.AggressiveInlining)]
68     protected override uint GetZero() => 0U;
69
70     /// <summary>
71     /// <para>
72     /// Determines whether this instance equal to zero.
73     /// </para>
74     /// <para></para>
75     /// </summary>
76     /// <param name="value">
77     /// <para>The value.</para>
78     /// <para></para>
79     /// </param>
80     /// <returns>
81     /// <para>The bool</para>
82     /// <para></para>
83     /// </returns>
84     [MethodImpl(MethodImplOptions.AggressiveInlining)]
85     protected override bool EqualToZero(uint value) => value == 0U;
86
87     /// <summary>
88     /// <para>
89     /// Determines whether this instance are equal.
90     /// </para>
91     /// <para></para>
92     /// </summary>
93     /// <param name="first">
94     /// <para>The first.</para>
95     /// <para></para>
96     /// </param>
97     /// <param name="second">
98     /// <para>The second.</para>
99     /// <para></para>
100    /// </param>
101    /// <returns>
102    /// <para>The bool</para>
103    /// <para></para>
104    /// </returns>
105    [MethodImpl(MethodImplOptions.AggressiveInlining)]
106    protected override bool AreEqual(uint first, uint second) => first == second;
107
108    /// <summary>
109    /// <para>
110    /// Determines whether this instance greater than zero.
111    /// </para>
112    /// <para></para>
113    /// </summary>
114    /// <param name="value">
115    /// <para>The value.</para>
116    /// <para></para>
117    /// </param>
118    /// <returns>
119    /// <para>The bool</para>
120    /// <para></para>
121    /// </returns>
122    [MethodImpl(MethodImplOptions.AggressiveInlining)]
123    protected override bool GreaterThanZero(uint value) => value > 0U;
124
125    /// <summary>
126    /// <para>
127    /// Determines whether this instance greater than.
128    /// </para>
129    /// <para></para>
130    /// </summary>
131    /// <param name="first">
132    /// <para>The first.</para>
133    /// <para></para>
134    /// </param>
135    /// <param name="second">
136    /// <para>The second.</para>
137    /// <para></para>
138    /// </param>
139    /// <returns>
140    /// <para>The bool</para>

```

```

141     /// <para></para>
142     /// </returns>
143     [MethodImpl(MethodImplOptions.AggressiveInlining)]
144     protected override bool GreaterThan(uint first, uint second) => first > second;
145
146     /// <summary>
147     /// <para>
148     /// Determines whether this instance greater or equal than.
149     /// </para>
150     /// <para></para>
151     /// </summary>
152     /// <param name="first">
153     /// <para>The first.</para>
154     /// <para></para>
155     /// </param>
156     /// <param name="second">
157     /// <para>The second.</para>
158     /// <para></para>
159     /// </param>
160     /// <returns>
161     /// <para>The bool</para>
162     /// <para></para>
163     /// </returns>
164     [MethodImpl(MethodImplOptions.AggressiveInlining)]
165     protected override bool GreaterOrEqualThan(uint first, uint second) => first >= second;
166
167     /// <summary>
168     /// <para>
169     /// Determines whether this instance greater or equal than zero.
170     /// </para>
171     /// <para></para>
172     /// </summary>
173     /// <param name="value">
174     /// <para>The value.</para>
175     /// <para></para>
176     /// </param>
177     /// <returns>
178     /// <para>The bool</para>
179     /// <para></para>
180     /// </returns>
181     [MethodImpl(MethodImplOptions.AggressiveInlining)]
182     protected override bool GreaterOrEqualThanZero(uint value) => true; // value >= 0 is
    ↪ always true for uint
183
184     /// <summary>
185     /// <para>
186     /// Determines whether this instance less or equal than zero.
187     /// </para>
188     /// <para></para>
189     /// </summary>
190     /// <param name="value">
191     /// <para>The value.</para>
192     /// <para></para>
193     /// </param>
194     /// <returns>
195     /// <para>The bool</para>
196     /// <para></para>
197     /// </returns>
198     [MethodImpl(MethodImplOptions.AggressiveInlining)]
199     protected override bool LessOrEqualThanZero(uint value) => value == 0U; // value is
    ↪ always >= 0 for uint
200
201     /// <summary>
202     /// <para>
203     /// Determines whether this instance less or equal than.
204     /// </para>
205     /// <para></para>
206     /// </summary>
207     /// <param name="first">
208     /// <para>The first.</para>
209     /// <para></para>
210     /// </param>
211     /// <param name="second">
212     /// <para>The second.</para>
213     /// <para></para>
214     /// </param>
215     /// <returns>
216     /// <para>The bool</para>

```

```

217     /// <para></para>
218     /// </returns>
219     [MethodImpl(MethodImplOptions.AggressiveInlining)]
220     protected override bool LessOrEqualThan(uint first, uint second) => first <= second;
221
222     /// <summary>
223     /// <para>
224     /// Determines whether this instance less than zero.
225     /// </para>
226     /// <para></para>
227     /// </summary>
228     /// <param name="value">
229     /// <para>The value.</para>
230     /// <para></para>
231     /// </param>
232     /// <returns>
233     /// <para>The bool</para>
234     /// <para></para>
235     /// </returns>
236     [MethodImpl(MethodImplOptions.AggressiveInlining)]
237     protected override bool LessThanZero(uint value) => false; // value < 0 is always false
238     ↪ for uint
239
240     /// <summary>
241     /// <para>
242     /// Determines whether this instance less than.
243     /// </para>
244     /// <para></para>
245     /// </summary>
246     /// <param name="first">
247     /// <para>The first.</para>
248     /// <para></para>
249     /// </param>
250     /// <param name="second">
251     /// <para>The second.</para>
252     /// <para></para>
253     /// </param>
254     /// <returns>
255     /// <para>The bool</para>
256     /// <para></para>
257     /// </returns>
258     [MethodImpl(MethodImplOptions.AggressiveInlining)]
259     protected override bool LessThan(uint first, uint second) => first < second;
260
261     /// <summary>
262     /// <para>
263     /// Increments the value.
264     /// </para>
265     /// <para></para>
266     /// </summary>
267     /// <param name="value">
268     /// <para>The value.</para>
269     /// <para></para>
270     /// </param>
271     /// <returns>
272     /// <para>The uint</para>
273     /// <para></para>
274     /// </returns>
275     [MethodImpl(MethodImplOptions.AggressiveInlining)]
276     protected override uint Increment(uint value) => ++value;
277
278     /// <summary>
279     /// <para>
280     /// Decrements the value.
281     /// </para>
282     /// <para></para>
283     /// </summary>
284     /// <param name="value">
285     /// <para>The value.</para>
286     /// <para></para>
287     /// </param>
288     /// <returns>
289     /// <para>The uint</para>
290     /// <para></para>
291     /// </returns>
292     [MethodImpl(MethodImplOptions.AggressiveInlining)]
293     protected override uint Decrement(uint value) => --value;

```

```

294    /// <summary>
295    /// <para>
296    /// Adds the first.
297    /// </para>
298    /// <para></para>
299    /// </summary>
300    /// <param name="first">
301    /// <para>The first.</para>
302    /// <para></para>
303    /// </param>
304    /// <param name="second">
305    /// <para>The second.</para>
306    /// <para></para>
307    /// </param>
308    /// <returns>
309    /// <para>The uint</para>
310    /// <para></para>
311    /// </returns>
312    [MethodImpl(MethodImplOptions.AggressiveInlining)]
313    protected override uint Add(uint first, uint second) => first + second;
314
315    /// <summary>
316    /// <para>
317    /// Subtracts the first.
318    /// </para>
319    /// <para></para>
320    /// </summary>
321    /// <param name="first">
322    /// <para>The first.</para>
323    /// <para></para>
324    /// </param>
325    /// <param name="second">
326    /// <para>The second.</para>
327    /// <para></para>
328    /// </param>
329    /// <returns>
330    /// <para>The uint</para>
331    /// <para></para>
332    /// </returns>
333    [MethodImpl(MethodImplOptions.AggressiveInlining)]
334    protected override uint Subtract(uint first, uint second) => first - second;
335
336    /// <summary>
337    /// <para>
338    /// Determines whether this instance first is to the left of second.
339    /// </para>
340    /// <para></para>
341    /// </summary>
342    /// <param name="first">
343    /// <para>The first.</para>
344    /// <para></para>
345    /// </param>
346    /// <param name="second">
347    /// <para>The second.</para>
348    /// <para></para>
349    /// </param>
350    /// <returns>
351    /// <para>The bool</para>
352    /// <para></para>
353    /// </returns>
354    [MethodImpl(MethodImplOptions.AggressiveInlining)]
355    protected override bool FirstIsToLeftOfSecond(uint first, uint second)
356    {
357        ref var firstLink = ref Links[first];
358        ref var secondLink = ref Links[second];
359        return FirstIsToLeftOfSecond(firstLink.Source, firstLink.Target,
360            ↪ secondLink.Source, secondLink.Target);
361    }
362
363    /// <summary>
364    /// <para>
365    /// Determines whether this instance first is to the right of second.
366    /// </para>
367    /// <para></para>
368    /// </summary>
369    /// <param name="first">
370    /// <para>The first.</para>
371    /// <para></para>

```

```

371     /// </param>
372     /// <param name="second">
373     /// <para>The second.</para>
374     /// <para></para>
375     /// </param>
376     /// <returns>
377     /// <para>The bool</para>
378     /// <para></para>
379     /// </returns>
380     [MethodImpl(MethodImplOptions.AggressiveInlining)]
381     protected override bool FirstIsToTheRightOfSecond(uint first, uint second)
382     {
383         ref var firstLink = ref Links[first];
384         ref var secondLink = ref Links[second];
385         return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
386             ↪ secondLink.Source, secondLink.Target);
387     }
388     /// <summary>
389     /// <para>
390     /// Gets the header reference.
391     /// </para>
392     /// <para></para>
393     /// </summary>
394     /// <returns>
395     /// <para>A ref links header of uint</para>
396     /// <para></para>
397     /// </returns>
398     [MethodImpl(MethodImplOptions.AggressiveInlining)]
399     protected override ref LinksHeader<uint> GetHeaderReference() => ref *Header;
400
401     /// <summary>
402     /// <para>
403     /// Gets the link reference using the specified link.
404     /// </para>
405     /// <para></para>
406     /// </summary>
407     /// <param name="link">
408     /// <para>The link.</para>
409     /// <para></para>
410     /// </param>
411     /// <returns>
412     /// <para>A ref raw link of uint</para>
413     /// <para></para>
414     /// </returns>
415     [MethodImpl(MethodImplOptions.AggressiveInlining)]
416     protected override ref RawLink<uint> GetLinkReference(uint link) => ref Links[link];
417 }
418 }

```

1.95 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksSourcesRecursionlessSizeBalancedTree

```

1 using System.Runtime.CompilerServices;
2
3 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5 namespace Platform.Data.Doublets.Memory.United.Specific
6 {
7     /// <summary>
8     /// <para>
9     /// Represents the int 32 links sources recursionless size balanced tree methods.
10    /// </para>
11    /// <para></para>
12    /// </summary>
13    /// <seealso cref="UInt32LinksRecursionlessSizeBalancedTreeMethodsBase"/>
14    public unsafe class UInt32LinksSourcesRecursionlessSizeBalancedTreeMethods :
15        ↪ UInt32LinksRecursionlessSizeBalancedTreeMethodsBase
16    {
17        /// <summary>
18        /// <para>
19        /// Initializes a new <see
20        ↪ cref="UInt32LinksSourcesRecursionlessSizeBalancedTreeMethods"/> instance.
21        /// </para>
22        /// <para></para>
23        /// </summary>
24        /// <param name="constants">
25        /// <para>A constants.</para>
26        /// <para></para>
27        /// </param>

```

```

26    /// <param name="links">
27    /// <para>A links.</para>
28    /// <para></para>
29    /// </param>
30    /// <param name="header">
31    /// <para>A header.</para>
32    /// <para></para>
33    /// </param>
34    public UInt32LinksSourcesRecursionlessSizeBalancedTreeMethods(LinksConstants<uint>
    ↪ constants, RawLink<uint>* links, LinksHeader<uint>* header) : base(constants, links,
    ↪ header) { }

35
36    /// <summary>
37    /// <para>
38    /// Gets the left reference using the specified node.
39    /// </para>
40    /// <para></para>
41    /// </summary>
42    /// <param name="node">
43    /// <para>The node.</para>
44    /// <para></para>
45    /// </param>
46    /// <returns>
47    /// <para>The ref uint</para>
48    /// <para></para>
49    /// </returns>
50    [MethodImpl(MethodImplOptions.AggressiveInlining)]
51    protected override ref uint GetLeftReference(uint node) => ref Links[node].LeftAsSource;
52
53    /// <summary>
54    /// <para>
55    /// Gets the right reference using the specified node.
56    /// </para>
57    /// <para></para>
58    /// </summary>
59    /// <param name="node">
60    /// <para>The node.</para>
61    /// <para></para>
62    /// </param>
63    /// <returns>
64    /// <para>The ref uint</para>
65    /// <para></para>
66    /// </returns>
67    [MethodImpl(MethodImplOptions.AggressiveInlining)]
68    protected override ref uint GetRightReference(uint node) => ref
    ↪ Links[node].RightAsSource;
69
70    /// <summary>
71    /// <para>
72    /// Gets the left using the specified node.
73    /// </para>
74    /// <para></para>
75    /// </summary>
76    /// <param name="node">
77    /// <para>The node.</para>
78    /// <para></para>
79    /// </param>
80    /// <returns>
81    /// <para>The uint</para>
82    /// <para></para>
83    /// </returns>
84    [MethodImpl(MethodImplOptions.AggressiveInlining)]
85    protected override uint GetLeft(uint node) => Links[node].LeftAsSource;
86
87    /// <summary>
88    /// <para>
89    /// Gets the right using the specified node.
90    /// </para>
91    /// <para></para>
92    /// </summary>
93    /// <param name="node">
94    /// <para>The node.</para>
95    /// <para></para>
96    /// </param>
97    /// <returns>
98    /// <para>The uint</para>
99    /// <para></para>
100   /// </returns>

```



```

101 [MethodImpl(MethodImplOptions.AggressiveInlining)]
102 protected override uint GetRight(uint node) => Links[node].RightAsSource;
103
104 /// <summary>
105 /// <para>
106 /// Sets the left using the specified node.
107 /// </para>
108 /// <para></para>
109 /// </summary>
110 /// <param name="node">
111 /// <para>The node.</para>
112 /// <para></para>
113 /// </param>
114 /// <param name="left">
115 /// <para>The left.</para>
116 /// <para></para>
117 /// </param>
118 [MethodImpl(MethodImplOptions.AggressiveInlining)]
119 protected override void SetLeft(uint node, uint left) => Links[node].LeftAsSource = left;
120
121 /// <summary>
122 /// <para>
123 /// Sets the right using the specified node.
124 /// </para>
125 /// <para></para>
126 /// </summary>
127 /// <param name="node">
128 /// <para>The node.</para>
129 /// <para></para>
130 /// </param>
131 /// <param name="right">
132 /// <para>The right.</para>
133 /// <para></para>
134 /// </param>
135 [MethodImpl(MethodImplOptions.AggressiveInlining)]
136 protected override void SetRight(uint node, uint right) => Links[node].RightAsSource =
    → right;
137
138 /// <summary>
139 /// <para>
140 /// Gets the size using the specified node.
141 /// </para>
142 /// <para></para>
143 /// </summary>
144 /// <param name="node">
145 /// <para>The node.</para>
146 /// <para></para>
147 /// </param>
148 /// <returns>
149 /// <para>The uint</para>
150 /// <para></para>
151 /// </returns>
152 [MethodImpl(MethodImplOptions.AggressiveInlining)]
153 protected override uint GetSize(uint node) => Links[node].SizeAsSource;
154
155 /// <summary>
156 /// <para>
157 /// Sets the size using the specified node.
158 /// </para>
159 /// <para></para>
160 /// </summary>
161 /// <param name="node">
162 /// <para>The node.</para>
163 /// <para></para>
164 /// </param>
165 /// <param name="size">
166 /// <para>The size.</para>
167 /// <para></para>
168 /// </param>
169 [MethodImpl(MethodImplOptions.AggressiveInlining)]
170 protected override void SetSize(uint node, uint size) => Links[node].SizeAsSource = size;
171
172 /// <summary>
173 /// <para>
174 /// Gets the tree root.
175 /// </para>
176 /// <para></para>
177 /// </summary>

```

```

178     /// <returns>
179     /// <para>The uint</para>
180     /// <para></para>
181     /// </returns>
182     [MethodImpl(MethodImplOptions.AggressiveInlining)]
183     protected override uint GetTreeRoot() => Header->RootAsSource;
184
185     /// <summary>
186     /// <para>
187     /// Gets the base part value using the specified link.
188     /// </para>
189     /// <para></para>
190     /// </summary>
191     /// <param name="link">
192     /// <para>The link.</para>
193     /// <para></para>
194     /// </param>
195     /// <returns>
196     /// <para>The uint</para>
197     /// <para></para>
198     /// </returns>
199     [MethodImpl(MethodImplOptions.AggressiveInlining)]
200     protected override uint GetBasePartValue(uint link) => Links[link].Source;
201
202     /// <summary>
203     /// <para>
204     /// Determines whether this instance first is to the left of second.
205     /// </para>
206     /// <para></para>
207     /// </summary>
208     /// <param name="firstSource">
209     /// <para>The first source.</para>
210     /// <para></para>
211     /// </param>
212     /// <param name="firstTarget">
213     /// <para>The first target.</para>
214     /// <para></para>
215     /// </param>
216     /// <param name="secondSource">
217     /// <para>The second source.</para>
218     /// <para></para>
219     /// </param>
220     /// <param name="secondTarget">
221     /// <para>The second target.</para>
222     /// <para></para>
223     /// </param>
224     /// <returns>
225     /// <para>The bool</para>
226     /// <para></para>
227     /// </returns>
228     [MethodImpl(MethodImplOptions.AggressiveInlining)]
229     protected override bool FirstIsToLeftOfSecond(uint firstSource, uint firstTarget,
230     ↪ uint secondSource, uint secondTarget)
231     => firstSource < secondSource || (firstSource == secondSource && firstTarget <
232     ↪ secondTarget);
233
234     /// <summary>
235     /// <para>
236     /// Determines whether this instance first is to the right of second.
237     /// </para>
238     /// <para></para>
239     /// </summary>
240     /// <param name="firstSource">
241     /// <para>The first source.</para>
242     /// <para></para>
243     /// </param>
244     /// <param name="firstTarget">
245     /// <para>The first target.</para>
246     /// <para></para>
247     /// </param>
248     /// <param name="secondSource">
249     /// <para>The second source.</para>
250     /// <para></para>
251     /// </param>
252     /// <param name="secondTarget">
253     /// <para>The second target.</para>
254     /// <para></para>
255     /// </param>

```

```

254     /// <returns>
255     /// <para>The bool</para>
256     /// <para></para>
257     /// </returns>
258     [MethodImpl(MethodImplOptions.AggressiveInlining)]
259     protected override bool FirstIsToTheRightOfSecond(uint firstSource, uint firstTarget,
260     ↪ uint secondSource, uint secondTarget)
261     => firstSource > secondSource || (firstSource == secondSource && firstTarget >
262     ↪ secondTarget);
263
264     /// <summary>
265     /// <para>
266     /// Clears the node using the specified node.
267     /// </para>
268     /// <para></para>
269     /// </summary>
270     /// <param name="node">
271     /// <para>The node.</para>
272     /// <para></para>
273     /// </param>
274     [MethodImpl(MethodImplOptions.AggressiveInlining)]
275     protected override void ClearNode(uint node)
276     {
277         ref var link = ref Links[node];
278         link.LeftAsSource = 0U;
279         link.RightAsSource = 0U;
280         link.SizeAsSource = 0U;
281     }
282 }

```

1.96 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksSourcesSizeBalancedTreeMethods.cs

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.United.Specific
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the int 32 links sources size balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="UInt32LinksSizeBalancedTreeMethodsBase"/>
14     public unsafe class UInt32LinksSourcesSizeBalancedTreeMethods :
15     ↪ UInt32LinksSizeBalancedTreeMethodsBase
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see cref="UInt32LinksSourcesSizeBalancedTreeMethods"/> instance.
20         /// </para>
21         /// <para></para>
22         /// </summary>
23         /// <param name="constants">
24         /// <para>A constants.</para>
25         /// <para></para>
26         /// </param>
27         /// <param name="links">
28         /// <para>A links.</para>
29         /// <para></para>
30         /// </param>
31         /// <param name="header">
32         /// <para>A header.</para>
33         /// <para></para>
34         /// </param>
35         public UInt32LinksSourcesSizeBalancedTreeMethods(LinksConstants<uint> constants,
36         ↪ RawLink<uint>* links, LinksHeader<uint>* header) : base(constants, links, header) { }
37
38         /// <summary>
39         /// <para>
40         /// Gets the left reference using the specified node.
41         /// </para>
42         /// <para></para>
43         /// </summary>
44         /// <param name="node">
45         /// <para>The node.</para>
46         /// <para></para>

```

```

45     /// </param>
46     /// <returns>
47     /// <para>The ref uint</para>
48     /// <para></para>
49     /// </returns>
50     [MethodImpl(MethodImplOptions.AggressiveInlining)]
51     protected override ref uint GetLeftReference(uint node) => ref Links[node].LeftAsSource;
52
53     /// <summary>
54     /// <para>
55     /// Gets the right reference using the specified node.
56     /// </para>
57     /// <para></para>
58     /// </summary>
59     /// <param name="node">
60     /// <para>The node.</para>
61     /// <para></para>
62     /// </param>
63     /// <returns>
64     /// <para>The ref uint</para>
65     /// <para></para>
66     /// </returns>
67     [MethodImpl(MethodImplOptions.AggressiveInlining)]
68     protected override ref uint GetRightReference(uint node) => ref
        ↪ Links[node].RightAsSource;
69
70     /// <summary>
71     /// <para>
72     /// Gets the left using the specified node.
73     /// </para>
74     /// <para></para>
75     /// </summary>
76     /// <param name="node">
77     /// <para>The node.</para>
78     /// <para></para>
79     /// </param>
80     /// <returns>
81     /// <para>The uint</para>
82     /// <para></para>
83     /// </returns>
84     [MethodImpl(MethodImplOptions.AggressiveInlining)]
85     protected override uint GetLeft(uint node) => Links[node].LeftAsSource;
86
87     /// <summary>
88     /// <para>
89     /// Gets the right using the specified node.
90     /// </para>
91     /// <para></para>
92     /// </summary>
93     /// <param name="node">
94     /// <para>The node.</para>
95     /// <para></para>
96     /// </param>
97     /// <returns>
98     /// <para>The uint</para>
99     /// <para></para>
100    /// </returns>
101    [MethodImpl(MethodImplOptions.AggressiveInlining)]
102    protected override uint GetRight(uint node) => Links[node].RightAsSource;
103
104    /// <summary>
105    /// <para>
106    /// Sets the left using the specified node.
107    /// </para>
108    /// <para></para>
109    /// </summary>
110    /// <param name="node">
111    /// <para>The node.</para>
112    /// <para></para>
113    /// </param>
114    /// <param name="left">
115    /// <para>The left.</para>
116    /// <para></para>
117    /// </param>
118    [MethodImpl(MethodImplOptions.AggressiveInlining)]
119    protected override void SetLeft(uint node, uint left) => Links[node].LeftAsSource = left;
120
121    /// <summary>

```

```

122    /// <para>
123    /// Sets the right using the specified node.
124    /// </para>
125    /// <para></para>
126    /// </summary>
127    /// <param name="node">
128    /// <para>The node.</para>
129    /// <para></para>
130    /// </param>
131    /// <param name="right">
132    /// <para>The right.</para>
133    /// <para></para>
134    /// </param>
135    [MethodImpl(MethodImplOptions.AggressiveInlining)]
136    protected override void SetRight(uint node, uint right) => Links[node].RightAsSource =
        ↪ right;
137
138    /// <summary>
139    /// <para>
140    /// Gets the size using the specified node.
141    /// </para>
142    /// <para></para>
143    /// </summary>
144    /// <param name="node">
145    /// <para>The node.</para>
146    /// <para></para>
147    /// </param>
148    /// <returns>
149    /// <para>The uint</para>
150    /// <para></para>
151    /// </returns>
152    [MethodImpl(MethodImplOptions.AggressiveInlining)]
153    protected override uint GetSize(uint node) => Links[node].SizeAsSource;
154
155    /// <summary>
156    /// <para>
157    /// Sets the size using the specified node.
158    /// </para>
159    /// <para></para>
160    /// </summary>
161    /// <param name="node">
162    /// <para>The node.</para>
163    /// <para></para>
164    /// </param>
165    /// <param name="size">
166    /// <para>The size.</para>
167    /// <para></para>
168    /// </param>
169    [MethodImpl(MethodImplOptions.AggressiveInlining)]
170    protected override void SetSize(uint node, uint size) => Links[node].SizeAsSource = size;
171
172    /// <summary>
173    /// <para>
174    /// Gets the tree root.
175    /// </para>
176    /// <para></para>
177    /// </summary>
178    /// <returns>
179    /// <para>The uint</para>
180    /// <para></para>
181    /// </returns>
182    [MethodImpl(MethodImplOptions.AggressiveInlining)]
183    protected override uint GetTreeRoot() => Header->RootAsSource;
184
185    /// <summary>
186    /// <para>
187    /// Gets the base part value using the specified link.
188    /// </para>
189    /// <para></para>
190    /// </summary>
191    /// <param name="link">
192    /// <para>The link.</para>
193    /// <para></para>
194    /// </param>
195    /// <returns>
196    /// <para>The uint</para>
197    /// <para></para>
198    /// </returns>

```

```

199 [MethodImpl(MethodImplOptions.AggressiveInlining)]
200 protected override uint GetBasePartValue(uint link) => Links[link].Source;
201
202 /// <summary>
203 /// <para>
204 /// Determines whether this instance first is to the left of second.
205 /// </para>
206 /// <para></para>
207 /// </summary>
208 /// <param name="firstSource">
209 /// <para>The first source.</para>
210 /// <para></para>
211 /// </param>
212 /// <param name="firstTarget">
213 /// <para>The first target.</para>
214 /// <para></para>
215 /// </param>
216 /// <param name="secondSource">
217 /// <para>The second source.</para>
218 /// <para></para>
219 /// </param>
220 /// <param name="secondTarget">
221 /// <para>The second target.</para>
222 /// <para></para>
223 /// </param>
224 /// <returns>
225 /// <para>The bool</para>
226 /// <para></para>
227 /// </returns>
228 [MethodImpl(MethodImplOptions.AggressiveInlining)]
229 protected override bool FirstIsToLeftOfSecond(uint firstSource, uint firstTarget,
230 ↪ uint secondSource, uint secondTarget)
231     => firstSource < secondSource || (firstSource == secondSource && firstTarget <
232     ↪ secondTarget);
233
234 /// <summary>
235 /// <para>
236 /// Determines whether this instance first is to the right of second.
237 /// </para>
238 /// <para></para>
239 /// </summary>
240 /// <param name="firstSource">
241 /// <para>The first source.</para>
242 /// <para></para>
243 /// </param>
244 /// <param name="firstTarget">
245 /// <para>The first target.</para>
246 /// <para></para>
247 /// </param>
248 /// <param name="secondSource">
249 /// <para>The second source.</para>
250 /// <para></para>
251 /// </param>
252 /// <param name="secondTarget">
253 /// <para>The second target.</para>
254 /// <para></para>
255 /// </param>
256 /// <returns>
257 /// <para>The bool</para>
258 /// <para></para>
259 /// </returns>
260 [MethodImpl(MethodImplOptions.AggressiveInlining)]
261 protected override bool FirstIsToTheRightOfSecond(uint firstSource, uint firstTarget,
262 ↪ uint secondSource, uint secondTarget)
263     => firstSource > secondSource || (firstSource == secondSource && firstTarget >
264     ↪ secondTarget);
265
266 /// <summary>
267 /// <para>
268 /// Clears the node using the specified node.
269 /// </para>
270 /// <para></para>
271 /// </summary>
272 /// <param name="node">
273 /// <para>The node.</para>
274 /// <para></para>
275 /// </param>

```

```

272     [MethodImpl(MethodImplOptions.AggressiveInlining)]
273     protected override void ClearNode(uint node)
274     {
275         ref var link = ref Links[node];
276         link.LeftAsSource = 0U;
277         link.RightAsSource = 0U;
278         link.SizeAsSource = 0U;
279     }
280 }
281 }

```

1.97 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksTargetsRecursionlessSizeBalancedTree

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.United.Specific
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the int 32 links targets recursionless size balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="UInt32LinksRecursionlessSizeBalancedTreeMethodsBase"/>
14     public unsafe class UInt32LinksTargetsRecursionlessSizeBalancedTreeMethods :
15         ↪ UInt32LinksRecursionlessSizeBalancedTreeMethodsBase
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see
20         ↪ cref="UInt32LinksTargetsRecursionlessSizeBalancedTreeMethods"/> instance.
21         /// </para>
22         /// <para></para>
23         /// </summary>
24         /// <param name="constants">
25         /// <para>A constants.</para>
26         /// <para></para>
27         /// </param>
28         /// <param name="links">
29         /// <para>A links.</para>
30         /// <para></para>
31         /// </param>
32         /// <param name="header">
33         /// <para>A header.</para>
34         /// <para></para>
35         /// </param>
36         public UInt32LinksTargetsRecursionlessSizeBalancedTreeMethods(LinksConstants<uint>
37             ↪ constants, RawLink<uint>* links, LinksHeader<uint>* header) : base(constants, links,
38             ↪ header) { }
39
40         /// <summary>
41         /// <para>
42         /// Gets the left reference using the specified node.
43         /// </para>
44         /// <para></para>
45         /// </summary>
46         /// <param name="node">
47         /// <para>The node.</para>
48         /// <para></para>
49         /// </param>
50         /// <returns>
51         /// <para>The ref uint</para>
52         /// <para></para>
53         /// </returns>
54         [MethodImpl(MethodImplOptions.AggressiveInlining)]
55         protected override ref uint GetLeftReference(uint node) => ref Links[node].LeftAsTarget;
56
57         /// <summary>
58         /// <para>
59         /// Gets the right reference using the specified node.
60         /// </para>
61         /// <para></para>
62         /// </summary>
63         /// <param name="node">
64         /// <para>The node.</para>
65         /// <para></para>
66         /// </param>

```

```

63     /// <returns>
64     /// <para>The ref uint</para>
65     /// <para></para>
66     /// </returns>
67     [MethodImpl(MethodImplOptions.AggressiveInlining)]
68     protected override ref uint GetRightReference(uint node) => ref
        ↳ Links[node].RightAsTarget;
69
70     /// <summary>
71     /// <para>
72     /// Gets the left using the specified node.
73     /// </para>
74     /// <para></para>
75     /// </summary>
76     /// <param name="node">
77     /// <para>The node.</para>
78     /// <para></para>
79     /// </param>
80     /// <returns>
81     /// <para>The uint</para>
82     /// <para></para>
83     /// </returns>
84     [MethodImpl(MethodImplOptions.AggressiveInlining)]
85     protected override uint GetLeft(uint node) => Links[node].LeftAsTarget;
86
87     /// <summary>
88     /// <para>
89     /// Gets the right using the specified node.
90     /// </para>
91     /// <para></para>
92     /// </summary>
93     /// <param name="node">
94     /// <para>The node.</para>
95     /// <para></para>
96     /// </param>
97     /// <returns>
98     /// <para>The uint</para>
99     /// <para></para>
100    /// </returns>
101    [MethodImpl(MethodImplOptions.AggressiveInlining)]
102    protected override uint GetRight(uint node) => Links[node].RightAsTarget;
103
104    /// <summary>
105    /// <para>
106    /// Sets the left using the specified node.
107    /// </para>
108    /// <para></para>
109    /// </summary>
110    /// <param name="node">
111    /// <para>The node.</para>
112    /// <para></para>
113    /// </param>
114    /// <param name="left">
115    /// <para>The left.</para>
116    /// <para></para>
117    /// </param>
118    [MethodImpl(MethodImplOptions.AggressiveInlining)]
119    protected override void SetLeft(uint node, uint left) => Links[node].LeftAsTarget = left;
120
121    /// <summary>
122    /// <para>
123    /// Sets the right using the specified node.
124    /// </para>
125    /// <para></para>
126    /// </summary>
127    /// <param name="node">
128    /// <para>The node.</para>
129    /// <para></para>
130    /// </param>
131    /// <param name="right">
132    /// <para>The right.</para>
133    /// <para></para>
134    /// </param>
135    [MethodImpl(MethodImplOptions.AggressiveInlining)]
136    protected override void SetRight(uint node, uint right) => Links[node].RightAsTarget =
        ↳ right;
137
138    /// <summary>

```



```

139    /// <para>
140    /// Gets the size using the specified node.
141    /// </para>
142    /// <para></para>
143    /// </summary>
144    /// <param name="node">
145    /// <para>The node.</para>
146    /// <para></para>
147    /// </param>
148    /// <returns>
149    /// <para>The uint</para>
150    /// <para></para>
151    /// </returns>
152    [MethodImpl(MethodImplOptions.AggressiveInlining)]
153    protected override uint GetSize(uint node) => Links[node].SizeAsTarget;
154
155    /// <summary>
156    /// <para>
157    /// Sets the size using the specified node.
158    /// </para>
159    /// <para></para>
160    /// </summary>
161    /// <param name="node">
162    /// <para>The node.</para>
163    /// <para></para>
164    /// </param>
165    /// <param name="size">
166    /// <para>The size.</para>
167    /// <para></para>
168    /// </param>
169    [MethodImpl(MethodImplOptions.AggressiveInlining)]
170    protected override void SetSize(uint node, uint size) => Links[node].SizeAsTarget = size;
171
172    /// <summary>
173    /// <para>
174    /// Gets the tree root.
175    /// </para>
176    /// <para></para>
177    /// </summary>
178    /// <returns>
179    /// <para>The uint</para>
180    /// <para></para>
181    /// </returns>
182    [MethodImpl(MethodImplOptions.AggressiveInlining)]
183    protected override uint GetTreeRoot() => Header->RootAsTarget;
184
185    /// <summary>
186    /// <para>
187    /// Gets the base part value using the specified link.
188    /// </para>
189    /// <para></para>
190    /// </summary>
191    /// <param name="link">
192    /// <para>The link.</para>
193    /// <para></para>
194    /// </param>
195    /// <returns>
196    /// <para>The uint</para>
197    /// <para></para>
198    /// </returns>
199    [MethodImpl(MethodImplOptions.AggressiveInlining)]
200    protected override uint GetBasePartValue(uint link) => Links[link].Target;
201
202    /// <summary>
203    /// <para>
204    /// Determines whether this instance first is to the left of second.
205    /// </para>
206    /// <para></para>
207    /// </summary>
208    /// <param name="firstSource">
209    /// <para>The first source.</para>
210    /// <para></para>
211    /// </param>
212    /// <param name="firstTarget">
213    /// <para>The first target.</para>
214    /// <para></para>
215    /// </param>
216    /// <param name="secondSource">

```

```

217     /// <para>The second source.</para>
218     /// <para></para>
219     /// </param>
220     /// <param name="secondTarget">
221     /// <para>The second target.</para>
222     /// <para></para>
223     /// </param>
224     /// <returns>
225     /// <para>The bool</para>
226     /// <para></para>
227     /// </returns>
228     [MethodImpl(MethodImplOptions.AggressiveInlining)]
229     protected override bool FirstIsToTheLeftOfSecond(uint firstSource, uint firstTarget,
230     ↪ uint secondSource, uint secondTarget)
231     => firstTarget < secondTarget || (firstTarget == secondTarget && firstSource <
232     ↪ secondSource);
233
234     /// <summary>
235     /// <para>
236     /// Determines whether this instance first is to the right of second.
237     /// </para>
238     /// <para></para>
239     /// </summary>
240     /// <param name="firstSource">
241     /// <para>The first source.</para>
242     /// <para></para>
243     /// </param>
244     /// <param name="firstTarget">
245     /// <para>The first target.</para>
246     /// <para></para>
247     /// </param>
248     /// <param name="secondSource">
249     /// <para>The second source.</para>
250     /// <para></para>
251     /// </param>
252     /// <param name="secondTarget">
253     /// <para>The second target.</para>
254     /// <para></para>
255     /// </param>
256     /// <returns>
257     /// <para>The bool</para>
258     /// <para></para>
259     /// </returns>
260     [MethodImpl(MethodImplOptions.AggressiveInlining)]
261     protected override bool FirstIsToTheRightOfSecond(uint firstSource, uint firstTarget,
262     ↪ uint secondSource, uint secondTarget)
263     => firstTarget > secondTarget || (firstTarget == secondTarget && firstSource >
264     ↪ secondSource);
265
266     /// <summary>
267     /// <para>
268     /// Clears the node using the specified node.
269     /// </para>
270     /// <para></para>
271     /// </summary>
272     /// <param name="node">
273     /// <para>The node.</para>
274     /// <para></para>
275     /// </param>
276     [MethodImpl(MethodImplOptions.AggressiveInlining)]
277     protected override void ClearNode(uint node)
278     {
279         ref var link = ref Links[node];
280         link.LeftAsTarget = 0U;
281         link.RightAsTarget = 0U;
282         link.SizeAsTarget = 0U;
283     }
284 }

```

1.98 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksTargetsSizeBalancedTreeMethods.cs

```

1 using System.Runtime.CompilerServices;
2
3 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5 namespace Platform.Data.Doublets.Memory.United.Specific
6 {
7     /// <summary>

```

```

8  /// <para>
9  /// Represents the int 32 links targets size balanced tree methods.
10 /// </para>
11 /// <para></para>
12 /// </summary>
13 /// <seealso cref="UInt32LinksSizeBalancedTreeMethodsBase"/>
14 public unsafe class UInt32LinksTargetsSizeBalancedTreeMethods :
15     ↳ UInt32LinksSizeBalancedTreeMethodsBase
16 {
17     /// <summary>
18     /// <para>
19     /// Initializes a new <see cref="UInt32LinksTargetsSizeBalancedTreeMethods"/> instance.
20     /// </para>
21     /// </summary>
22     /// <param name="constants">
23     /// <para>A constants.</para>
24     /// </param>
25     /// <param name="links">
26     /// <para>A links.</para>
27     /// </param>
28     /// <param name="header">
29     /// <para>A header.</para>
30     /// </param>
31     public UInt32LinksTargetsSizeBalancedTreeMethods(LinksConstants<uint> constants,
32     ↳ RawLink<uint>* links, LinksHeader<uint>* header) : base(constants, links, header) { }
33
34     /// <summary>
35     /// <para>
36     /// Gets the left reference using the specified node.
37     /// </para>
38     /// </summary>
39     /// <param name="node">
40     /// <para>The node.</para>
41     /// </param>
42     /// <returns>
43     /// <para>The ref uint</para>
44     /// </returns>
45     [MethodImpl(MethodImplOptions.AggressiveInlining)]
46     protected override ref uint GetLeftReference(uint node) => ref Links[node].LeftAsTarget;
47
48     /// <summary>
49     /// <para>
50     /// Gets the right reference using the specified node.
51     /// </para>
52     /// </summary>
53     /// <param name="node">
54     /// <para>The node.</para>
55     /// </param>
56     /// <returns>
57     /// <para>The ref uint</para>
58     /// </returns>
59     [MethodImpl(MethodImplOptions.AggressiveInlining)]
60     protected override ref uint GetRightReference(uint node) => ref
61     ↳ Links[node].RightAsTarget;
62
63     /// <summary>
64     /// <para>
65     /// Gets the left using the specified node.
66     /// </para>
67     /// </summary>
68     /// <param name="node">
69     /// <para>The node.</para>
70     /// </param>
71     /// <returns>
72     /// <para>The uint</para>
73     /// </returns>
74     [MethodImpl(MethodImplOptions.AggressiveInlining)]
75     protected override uint GetLeftReference(uint node) => Links[node].LeftAsTarget;
76
77     /// <summary>
78     /// <para>
79     /// Gets the right using the specified node.
80     /// </para>
81     /// </summary>
82     /// <param name="node">
83     /// <para>The node.</para>
84     /// </param>
85     /// <returns>
86     /// <para>The uint</para>
87     /// </returns>
88     [MethodImpl(MethodImplOptions.AggressiveInlining)]
89     protected override uint GetRightReference(uint node) => Links[node].RightAsTarget;

```

```

83     /// </returns>
84     [MethodImpl(MethodImplOptions.AggressiveInlining)]
85     protected override uint GetLeft(uint node) => Links[node].LeftAsTarget;
86
87     /// <summary>
88     /// <para>
89     /// Gets the right using the specified node.
90     /// </para>
91     /// <para></para>
92     /// </summary>
93     /// <param name="node">
94     /// <para>The node.</para>
95     /// <para></para>
96     /// </param>
97     /// <returns>
98     /// <para>The uint</para>
99     /// <para></para>
100    /// </returns>
101    [MethodImpl(MethodImplOptions.AggressiveInlining)]
102    protected override uint GetRight(uint node) => Links[node].RightAsTarget;
103
104    /// <summary>
105    /// <para>
106    /// Sets the left using the specified node.
107    /// </para>
108    /// <para></para>
109    /// </summary>
110    /// <param name="node">
111    /// <para>The node.</para>
112    /// <para></para>
113    /// </param>
114    /// <param name="left">
115    /// <para>The left.</para>
116    /// <para></para>
117    /// </param>
118    [MethodImpl(MethodImplOptions.AggressiveInlining)]
119    protected override void SetLeft(uint node, uint left) => Links[node].LeftAsTarget = left;
120
121    /// <summary>
122    /// <para>
123    /// Sets the right using the specified node.
124    /// </para>
125    /// <para></para>
126    /// </summary>
127    /// <param name="node">
128    /// <para>The node.</para>
129    /// <para></para>
130    /// </param>
131    /// <param name="right">
132    /// <para>The right.</para>
133    /// <para></para>
134    /// </param>
135    [MethodImpl(MethodImplOptions.AggressiveInlining)]
136    protected override void SetRight(uint node, uint right) => Links[node].RightAsTarget =
        ↪ right;
137
138    /// <summary>
139    /// <para>
140    /// Gets the size using the specified node.
141    /// </para>
142    /// <para></para>
143    /// </summary>
144    /// <param name="node">
145    /// <para>The node.</para>
146    /// <para></para>
147    /// </param>
148    /// <returns>
149    /// <para>The uint</para>
150    /// <para></para>
151    /// </returns>
152    [MethodImpl(MethodImplOptions.AggressiveInlining)]
153    protected override uint GetSize(uint node) => Links[node].SizeAsTarget;
154
155    /// <summary>
156    /// <para>
157    /// Sets the size using the specified node.
158    /// </para>
159    /// <para></para>

```

```

160     /// </summary>
161     /// <param name="node">
162     /// <para>The node.</para>
163     /// <para></para>
164     /// </param>
165     /// <param name="size">
166     /// <para>The size.</para>
167     /// <para></para>
168     /// </param>
169     [MethodImpl(MethodImplOptions.AggressiveInlining)]
170     protected override void SetSize(uint node, uint size) => Links[node].SizeAsTarget = size;
171
172     /// <summary>
173     /// <para>
174     /// Gets the tree root.
175     /// </para>
176     /// <para></para>
177     /// </summary>
178     /// <returns>
179     /// <para>The uint</para>
180     /// <para></para>
181     /// </returns>
182     [MethodImpl(MethodImplOptions.AggressiveInlining)]
183     protected override uint GetTreeRoot() => Header->RootAsTarget;
184
185     /// <summary>
186     /// <para>
187     /// Gets the base part value using the specified link.
188     /// </para>
189     /// <para></para>
190     /// </summary>
191     /// <param name="link">
192     /// <para>The link.</para>
193     /// <para></para>
194     /// </param>
195     /// <returns>
196     /// <para>The uint</para>
197     /// <para></para>
198     /// </returns>
199     [MethodImpl(MethodImplOptions.AggressiveInlining)]
200     protected override uint GetBasePartValue(uint link) => Links[link].Target;
201
202     /// <summary>
203     /// <para>
204     /// Determines whether this instance first is to the left of second.
205     /// </para>
206     /// <para></para>
207     /// </summary>
208     /// <param name="firstSource">
209     /// <para>The first source.</para>
210     /// <para></para>
211     /// </param>
212     /// <param name="firstTarget">
213     /// <para>The first target.</para>
214     /// <para></para>
215     /// </param>
216     /// <param name="secondSource">
217     /// <para>The second source.</para>
218     /// <para></para>
219     /// </param>
220     /// <param name="secondTarget">
221     /// <para>The second target.</para>
222     /// <para></para>
223     /// </param>
224     /// <returns>
225     /// <para>The bool</para>
226     /// <para></para>
227     /// </returns>
228     [MethodImpl(MethodImplOptions.AggressiveInlining)]
229     protected override bool FirstIsToTheLeftOfSecond(uint firstSource, uint firstTarget,
230     ↪ uint secondSource, uint secondTarget)
231     => firstTarget < secondTarget || (firstTarget == secondTarget && firstSource <
232     ↪ secondSource);
233
234     /// <summary>
235     /// <para>
236     /// Determines whether this instance first is to the right of second.
237     /// </para>

```

```

236     /// <para></para>
237     /// </summary>
238     /// <param name="firstSource">
239     /// <para>The first source.</para>
240     /// <para></para>
241     /// </param>
242     /// <param name="firstTarget">
243     /// <para>The first target.</para>
244     /// <para></para>
245     /// </param>
246     /// <param name="secondSource">
247     /// <para>The second source.</para>
248     /// <para></para>
249     /// </param>
250     /// <param name="secondTarget">
251     /// <para>The second target.</para>
252     /// <para></para>
253     /// </param>
254     /// <returns>
255     /// <para>The bool</para>
256     /// <para></para>
257     /// </returns>
258     [MethodImpl(MethodImplOptions.AggressiveInlining)]
259     protected override bool FirstIsToTheRightOfSecond(uint firstSource, uint firstTarget,
    ↪ uint secondSource, uint secondTarget)
260     => firstTarget > secondTarget || (firstTarget == secondTarget && firstSource >
    ↪ secondSource);
261
262     /// <summary>
263     /// <para>
264     /// Clears the node using the specified node.
265     /// </para>
266     /// <para></para>
267     /// </summary>
268     /// <param name="node">
269     /// <para>The node.</para>
270     /// <para></para>
271     /// </param>
272     [MethodImpl(MethodImplOptions.AggressiveInlining)]
273     protected override void ClearNode(uint node)
274     {
275         ref var link = ref Links[node];
276         link.LeftAsTarget = 0U;
277         link.RightAsTarget = 0U;
278         link.SizeAsTarget = 0U;
279     }
280 }
281 }

```

1.99 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32UnitedMemoryLinks.cs

```

1  using System;
2  using System.Runtime.CompilerServices;
3  using Platform.Memory;
4  using Platform.Singletons;
5  using Platform.Data.Doublets.Memory.United.Generic;
6
7  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
8
9  namespace Platform.Data.Doublets.Memory.United.Specific
10 {
11     /// <summary>
12     /// <para>Represents a low-level implementation of direct access to resizable memory, for
    ↪ organizing the storage of links with addresses represented as <see cref="uint" />.</para>
13     /// <para>Представляет низкоуровневую реализация прямого доступа к памяти с переменным
    ↪ размером, для организации хранения связей с адресами представленными в виде <see
    ↪ cref="uint"/>.</para>
14     /// </summary>
15     public unsafe class UInt32UnitedMemoryLinks : UnitedMemoryLinksBase<uint>
16     {
17         private readonly Func<ILinksTreeMethods<uint>> _createSourceTreeMethods;
18         private readonly Func<ILinksTreeMethods<uint>> _createTargetTreeMethods;
19         private LinksHeader<uint>* _header;
20         private RawLink<uint>* _links;
21
22         /// <summary>
23         /// <para>
24         /// Initializes a new <see cref="UInt32UnitedMemoryLinks"/> instance.
25         /// </para>
26         /// <para></para>

```

```

27     /// </summary>
28     /// <param name="address">
29     /// <para>A address.</para>
30     /// <para></para>
31     /// </param>
32     [MethodImpl(MethodImplOptions.AggressiveInlining)]
33     public UInt32UnitedMemoryLinks(string address) : this(address, DefaultLinksSizeStep) { }
34
35     /// <summary>
36     /// Создаёт экземпляр базы данных Links в файле по указанному адресу, с указанным
37     ↪ минимальным шагом расширения базы данных.
38     /// </summary>
39     /// <param name="address">Полный путь к файлу базы данных.</param>
40     /// <param name="memoryReservationStep">Минимальный шаг расширения базы данных в
41     ↪ байтах.</param>
42     [MethodImpl(MethodImplOptions.AggressiveInlining)]
43     public UInt32UnitedMemoryLinks(string address, long memoryReservationStep) : this(new
44     ↪ FileMappedResizableDirectMemory(address, memoryReservationStep),
45     ↪ memoryReservationStep) { }
46
47     /// <summary>
48     /// <para>
49     /// Initializes a new <see cref="UInt32UnitedMemoryLinks"/> instance.
50     /// </para>
51     /// <para></para>
52     /// </summary>
53     /// <param name="memory">
54     /// <para>A memory.</para>
55     /// <para></para>
56     /// </param>
57     [MethodImpl(MethodImplOptions.AggressiveInlining)]
58     public UInt32UnitedMemoryLinks(IResizableDirectMemory memory) : this(memory,
59     ↪ DefaultLinksSizeStep) { }
60
61     /// <summary>
62     /// <para>
63     /// Initializes a new <see cref="UInt32UnitedMemoryLinks"/> instance.
64     /// </para>
65     /// <para></para>
66     /// </summary>
67     /// <param name="memory">
68     /// <para>A memory.</para>
69     /// <para></para>
70     /// </param>
71     /// <param name="memoryReservationStep">
72     /// <para>A memory reservation step.</para>
73     /// <para></para>
74     /// </param>
75     [MethodImpl(MethodImplOptions.AggressiveInlining)]
76     public UInt32UnitedMemoryLinks(IResizableDirectMemory memory, long
77     ↪ memoryReservationStep) : this(memory, memoryReservationStep,
78     ↪ Default<LinksConstants<uint>>.Instance, IndexTreeType.Default) { }
79
80     /// <summary>
81     /// <para>
82     /// Initializes a new <see cref="UInt32UnitedMemoryLinks"/> instance.
83     /// </para>
84     /// <para></para>
85     /// </summary>
86     /// <param name="memory">
87     /// <para>A memory.</para>
88     /// <para></para>
89     /// </param>
90     /// <param name="memoryReservationStep">
91     /// <para>A memory reservation step.</para>
92     /// <para></para>
93     /// </param>
94     /// <param name="constants">
95     /// <para>A constants.</para>
96     /// <para></para>
97     /// </param>
98     /// <param name="indexTreeType">
99     /// <para>A index tree type.</para>
100    /// <para></para>
101    /// </param>
102    [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

96 public UInt32UnitedMemoryLinks(IResizableDirectMemory memory, long
    ↳ memoryReservationStep, LinksConstants<uint> constants, IndexTreeType indexTreeType)
    ↳ : base(memory, memoryReservationStep, constants)
97 {
98     if (indexTreeType == IndexTreeType.SizeBalancedTree)
99     {
100         _createSourceTreeMethods = () => new
            ↳ UInt32LinksSourcesSizeBalancedTreeMethods(Constants, _links, _header);
101         _createTargetTreeMethods = () => new
            ↳ UInt32LinksTargetsSizeBalancedTreeMethods(Constants, _links, _header);
102     }
103     else
104     {
105         _createSourceTreeMethods = () => new
            ↳ UInt32LinksSourcesRecursionlessSizeBalancedTreeMethods(Constants, _links,
            ↳ _header);
106         _createTargetTreeMethods = () => new
            ↳ UInt32LinksTargetsRecursionlessSizeBalancedTreeMethods(Constants, _links,
            ↳ _header);
107     }
108     Init(memory, memoryReservationStep);
109 }
110
111 /// <summary>
112 /// <para>
113 /// Sets the pointers using the specified memory.
114 /// </para>
115 /// <para></para>
116 /// </summary>
117 /// <param name="memory">
118 /// <para>The memory.</para>
119 /// <para></para>
120 /// </param>
121 [MethodImpl(MethodImplOptions.AggressiveInlining)]
122 protected override void SetPointers(IResizableDirectMemory memory)
123 {
124     _header = (LinksHeader<uint>*)memory.Pointer;
125     _links = (RawLink<uint>*)memory.Pointer;
126     SourcesTreeMethods = _createSourceTreeMethods();
127     TargetsTreeMethods = _createTargetTreeMethods();
128     UnusedLinksListMethods = new UInt32UnusedLinksListMethods(_links, _header);
129 }
130
131 /// <summary>
132 /// <para>
133 /// Resets the pointers.
134 /// </para>
135 /// <para></para>
136 /// </summary>
137 [MethodImpl(MethodImplOptions.AggressiveInlining)]
138 protected override void ResetPointers()
139 {
140     base.ResetPointers();
141     _links = null;
142     _header = null;
143 }
144
145 /// <summary>
146 /// <para>
147 /// Gets the header reference.
148 /// </para>
149 /// <para></para>
150 /// </summary>
151 /// <returns>
152 /// <para>A ref links header of uint</para>
153 /// <para></para>
154 /// </returns>
155 [MethodImpl(MethodImplOptions.AggressiveInlining)]
156 protected override ref LinksHeader<uint> GetHeaderReference() => ref *_header;
157
158 /// <summary>
159 /// <para>
160 /// Gets the link reference using the specified link index.
161 /// </para>
162 /// <para></para>
163 /// </summary>
164 /// <param name="linkIndex">
165 /// <para>The link index.</para>

```



```

166     /// <para></para>
167     /// </param>
168     /// <returns>
169     /// <para>A ref raw link of uint</para>
170     /// <para></para>
171     /// </returns>
172     [MethodImpl(MethodImplOptions.AggressiveInlining)]
173     protected override ref RawLink<uint> GetLinkReference(uint linkIndex) => ref
174         ↪ _links[linkIndex];
175
176     /// <summary>
177     /// <para>
178     /// Determines whether this instance are equal.
179     /// </para>
180     /// <para></para>
181     /// </summary>
182     /// <param name="first">
183     /// <para>The first.</para>
184     /// <para></para>
185     /// </param>
186     /// <param name="second">
187     /// <para>The second.</para>
188     /// <para></para>
189     /// </param>
190     /// <returns>
191     /// <para>The bool</para>
192     /// <para></para>
193     /// </returns>
194     [MethodImpl(MethodImplOptions.AggressiveInlining)]
195     protected override bool AreEqual(uint first, uint second) => first == second;
196
197     /// <summary>
198     /// <para>
199     /// Determines whether this instance less than.
200     /// </para>
201     /// <para></para>
202     /// </summary>
203     /// <param name="first">
204     /// <para>The first.</para>
205     /// <para></para>
206     /// </param>
207     /// <param name="second">
208     /// <para>The second.</para>
209     /// <para></para>
210     /// </param>
211     /// <returns>
212     /// <para>The bool</para>
213     /// <para></para>
214     /// </returns>
215     [MethodImpl(MethodImplOptions.AggressiveInlining)]
216     protected override bool LessThan(uint first, uint second) => first < second;
217
218     /// <summary>
219     /// <para>
220     /// Determines whether this instance less or equal than.
221     /// </para>
222     /// <para></para>
223     /// </summary>
224     /// <param name="first">
225     /// <para>The first.</para>
226     /// <para></para>
227     /// </param>
228     /// <param name="second">
229     /// <para>The second.</para>
230     /// <para></para>
231     /// </param>
232     /// <returns>
233     /// <para>The bool</para>
234     /// <para></para>
235     /// </returns>
236     [MethodImpl(MethodImplOptions.AggressiveInlining)]
237     protected override bool LessOrEqualThan(uint first, uint second) => first <= second;
238
239     /// <summary>
240     /// <para>
241     /// Determines whether this instance greater than.
242     /// </para>
243     /// <para></para>

```

```

243     /// </summary>
244     /// <param name="first">
245     /// <para>The first.</para>
246     /// <para></para>
247     /// </param>
248     /// <param name="second">
249     /// <para>The second.</para>
250     /// <para></para>
251     /// </param>
252     /// <returns>
253     /// <para>The bool</para>
254     /// <para></para>
255     /// </returns>
256     [MethodImpl(MethodImplOptions.AggressiveInlining)]
257     protected override bool GreaterThan(uint first, uint second) => first > second;
258
259     /// <summary>
260     /// <para>
261     /// Determines whether this instance greater or equal than.
262     /// </para>
263     /// <para></para>
264     /// </summary>
265     /// <param name="first">
266     /// <para>The first.</para>
267     /// <para></para>
268     /// </param>
269     /// <param name="second">
270     /// <para>The second.</para>
271     /// <para></para>
272     /// </param>
273     /// <returns>
274     /// <para>The bool</para>
275     /// <para></para>
276     /// </returns>
277     [MethodImpl(MethodImplOptions.AggressiveInlining)]
278     protected override bool GreaterOrEqualThan(uint first, uint second) => first >= second;
279
280     /// <summary>
281     /// <para>
282     /// Gets the zero.
283     /// </para>
284     /// <para></para>
285     /// </summary>
286     /// <returns>
287     /// <para>The uint</para>
288     /// <para></para>
289     /// </returns>
290     [MethodImpl(MethodImplOptions.AggressiveInlining)]
291     protected override uint GetZero() => 0U;
292
293     /// <summary>
294     /// <para>
295     /// Gets the one.
296     /// </para>
297     /// <para></para>
298     /// </summary>
299     /// <returns>
300     /// <para>The uint</para>
301     /// <para></para>
302     /// </returns>
303     [MethodImpl(MethodImplOptions.AggressiveInlining)]
304     protected override uint GetOne() => 1U;
305
306     /// <summary>
307     /// <para>
308     /// Converts the to int 64 using the specified value.
309     /// </para>
310     /// <para></para>
311     /// </summary>
312     /// <param name="value">
313     /// <para>The value.</para>
314     /// <para></para>
315     /// </param>
316     /// <returns>
317     /// <para>The long</para>
318     /// <para></para>
319     /// </returns>
320     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

321     protected override long ConvertToInt64(uint value) => (long)value;
322
323     /// <summary>
324     /// <para>
325     /// Converts the to address using the specified value.
326     /// </para>
327     /// <para></para>
328     /// </summary>
329     /// <param name="value">
330     /// <para>The value.</para>
331     /// <para></para>
332     /// </param>
333     /// <returns>
334     /// <para>The uint</para>
335     /// <para></para>
336     /// </returns>
337     [MethodImpl(MethodImplOptions.AggressiveInlining)]
338     protected override uint ConvertToAddress(long value) => (uint)value;
339
340     /// <summary>
341     /// <para>
342     /// Adds the first.
343     /// </para>
344     /// <para></para>
345     /// </summary>
346     /// <param name="first">
347     /// <para>The first.</para>
348     /// <para></para>
349     /// </param>
350     /// <param name="second">
351     /// <para>The second.</para>
352     /// <para></para>
353     /// </param>
354     /// <returns>
355     /// <para>The uint</para>
356     /// <para></para>
357     /// </returns>
358     [MethodImpl(MethodImplOptions.AggressiveInlining)]
359     protected override uint Add(uint first, uint second) => first + second;
360
361     /// <summary>
362     /// <para>
363     /// Subtracts the first.
364     /// </para>
365     /// <para></para>
366     /// </summary>
367     /// <param name="first">
368     /// <para>The first.</para>
369     /// <para></para>
370     /// </param>
371     /// <param name="second">
372     /// <para>The second.</para>
373     /// <para></para>
374     /// </param>
375     /// <returns>
376     /// <para>The uint</para>
377     /// <para></para>
378     /// </returns>
379     [MethodImpl(MethodImplOptions.AggressiveInlining)]
380     protected override uint Subtract(uint first, uint second) => first - second;
381
382     /// <summary>
383     /// <para>
384     /// Increments the link.
385     /// </para>
386     /// <para></para>
387     /// </summary>
388     /// <param name="link">
389     /// <para>The link.</para>
390     /// <para></para>
391     /// </param>
392     /// <returns>
393     /// <para>The uint</para>
394     /// <para></para>
395     /// </returns>
396     [MethodImpl(MethodImplOptions.AggressiveInlining)]
397     protected override uint Increment(uint link) => ++link;
398

```

```

399     /// <summary>
400     /// <para>
401     /// Decrements the link.
402     /// </para>
403     /// <para></para>
404     /// </summary>
405     /// <param name="link">
406     /// <para>The link.</para>
407     /// <para></para>
408     /// </param>
409     /// <returns>
410     /// <para>The uint</para>
411     /// <para></para>
412     /// </returns>
413     [MethodImpl(MethodImplOptions.AggressiveInlining)]
414     protected override uint Decrement(uint link) => --link;
415 }
416 }

```

1.100 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32UnusedLinksListMethods.cs

```

1  using System.Runtime.CompilerServices;
2  using Platform.Data.Doublets.Memory.United.Generic;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.United.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 32 unused links list methods.
11     /// </para>
12     /// <para></para>
13     /// </summary>
14     /// <seealso cref="UnusedLinksListMethods{uint}"/>
15     public unsafe class UInt32UnusedLinksListMethods : UnusedLinksListMethods<uint>
16     {
17         private readonly RawLink<uint>* _links;
18         private readonly LinksHeader<uint>* _header;
19
20         /// <summary>
21         /// <para>
22         /// Initializes a new <see cref="UInt32UnusedLinksListMethods"/> instance.
23         /// </para>
24         /// <para></para>
25         /// </summary>
26         /// <param name="links">
27         /// <para>A links.</para>
28         /// <para></para>
29         /// </param>
30         /// <param name="header">
31         /// <para>A header.</para>
32         /// <para></para>
33         /// </param>
34         [MethodImpl(MethodImplOptions.AggressiveInlining)]
35         public UInt32UnusedLinksListMethods(RawLink<uint>* links, LinksHeader<uint>* header)
36             : base((byte*)links, (byte*)header)
37         {
38             _links = links;
39             _header = header;
40         }
41
42         /// <summary>
43         /// <para>
44         /// Gets the link reference using the specified link.
45         /// </para>
46         /// <para></para>
47         /// </summary>
48         /// <param name="link">
49         /// <para>The link.</para>
50         /// <para></para>
51         /// </param>
52         /// <returns>
53         /// <para>A ref raw link of uint</para>
54         /// <para></para>
55         /// </returns>
56         [MethodImpl(MethodImplOptions.AggressiveInlining)]
57         protected override ref RawLink<uint> GetLinkReference(uint link) => ref _links[link];
58
59         /// <summary>

```

```

60     /// <para>
61     /// Gets the header reference.
62     /// </para>
63     /// <para></para>
64     /// </summary>
65     /// <returns>
66     /// <para>A ref links header of uint</para>
67     /// <para></para>
68     /// </returns>
69     [MethodImpl(MethodImplOptions.AggressiveInlining)]
70     protected override ref LinksHeader<uint> GetHeaderReference() => ref *_header;
71 }
72 }
```

1.101 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksAvlBalancedTreeMethodsBase.cs

```

1 using System.Runtime.CompilerServices;
2 using Platform.Data.Doublets.Memory.United.Generic;
3 using static System.Runtime.CompilerServices.Unsafe;
4
5 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7 namespace Platform.Data.Doublets.Memory.United.Specific
8 {
9     /// <summary>
10     /// <para>
11     /// Represents the int 64 links avl balanced tree methods base.
12     /// </para>
13     /// <para></para>
14     /// </summary>
15     /// <seealso cref="LinksAvlBalancedTreeMethodsBase{ulong}" />
16     public unsafe abstract class UInt64LinksAvlBalancedTreeMethodsBase :
17         ↳ LinksAvlBalancedTreeMethodsBase<ulong>
18     {
19         /// <summary>
20         /// <para>
21         /// The links.
22         /// </para>
23         /// <para></para>
24         /// </summary>
25         protected new readonly RawLink<ulong>* Links;
26         /// <summary>
27         /// <para>
28         /// The header.
29         /// </para>
30         /// <para></para>
31         /// </summary>
32         protected new readonly LinksHeader<ulong>* Header;
33
34         /// <summary>
35         /// <para>
36         /// Initializes a new <see cref="UInt64LinksAvlBalancedTreeMethodsBase" /> instance.
37         /// </para>
38         /// <para></para>
39         /// </summary>
40         /// <param name="constants">
41         /// <para>A constants.</para>
42         /// </param>
43         /// <param name="links">
44         /// <para>A links.</para>
45         /// <para></para>
46         /// </param>
47         /// <param name="header">
48         /// <para>A header.</para>
49         /// <para></para>
50         /// </param>
51         protected UInt64LinksAvlBalancedTreeMethodsBase(LinksConstants<ulong> constants,
52             ↳ RawLink<ulong>* links, LinksHeader<ulong>* header)
53             : base(constants, (byte*)links, (byte*)header)
54         {
55             Links = links;
56             Header = header;
57         }
58
59         /// <summary>
60         /// <para>
61         /// Gets the zero.
62         /// </para>
63         /// <para></para>
64         /// </summary>

```

```

63     /// </summary>
64     /// <returns>
65     /// <para>The ulong</para>
66     /// <para></para>
67     /// </returns>
68     [MethodImpl(MethodImplOptions.AggressiveInlining)]
69     protected override ulong GetZero() => OUL;
70
71     /// <summary>
72     /// <para>
73     /// Determines whether this instance equal to zero.
74     /// </para>
75     /// <para></para>
76     /// </summary>
77     /// <param name="value">
78     /// <para>The value.</para>
79     /// <para></para>
80     /// </param>
81     /// <returns>
82     /// <para>The bool</para>
83     /// <para></para>
84     /// </returns>
85     [MethodImpl(MethodImplOptions.AggressiveInlining)]
86     protected override bool EqualToZero(ulong value) => value == OUL;
87
88     /// <summary>
89     /// <para>
90     /// Determines whether this instance are equal.
91     /// </para>
92     /// <para></para>
93     /// </summary>
94     /// <param name="first">
95     /// <para>The first.</para>
96     /// <para></para>
97     /// </param>
98     /// <param name="second">
99     /// <para>The second.</para>
100    /// <para></para>
101    /// </param>
102    /// <returns>
103    /// <para>The bool</para>
104    /// <para></para>
105    /// </returns>
106    [MethodImpl(MethodImplOptions.AggressiveInlining)]
107    protected override bool AreEqual(ulong first, ulong second) => first == second;
108
109    /// <summary>
110    /// <para>
111    /// Determines whether this instance greater than zero.
112    /// </para>
113    /// <para></para>
114    /// </summary>
115    /// <param name="value">
116    /// <para>The value.</para>
117    /// <para></para>
118    /// </param>
119    /// <returns>
120    /// <para>The bool</para>
121    /// <para></para>
122    /// </returns>
123    [MethodImpl(MethodImplOptions.AggressiveInlining)]
124    protected override bool GreaterThanZero(ulong value) => value > OUL;
125
126    /// <summary>
127    /// <para>
128    /// Determines whether this instance greater than.
129    /// </para>
130    /// <para></para>
131    /// </summary>
132    /// <param name="first">
133    /// <para>The first.</para>
134    /// <para></para>
135    /// </param>
136    /// <param name="second">
137    /// <para>The second.</para>
138    /// <para></para>
139    /// </param>
140    /// <returns>

```

```

141 /// <para>The bool</para>
142 /// <para></para>
143 /// </returns>
144 [MethodImpl(MethodImplOptions.AggressiveInlining)]
145 protected override bool GreaterThan(ulong first, ulong second) => first > second;
146
147 /// <summary>
148 /// <para>
149 /// Determines whether this instance greater or equal than.
150 /// </para>
151 /// <para></para>
152 /// </summary>
153 /// <param name="first">
154 /// <para>The first.</para>
155 /// <para></para>
156 /// </param>
157 /// <param name="second">
158 /// <para>The second.</para>
159 /// <para></para>
160 /// </param>
161 /// <returns>
162 /// <para>The bool</para>
163 /// <para></para>
164 /// </returns>
165 [MethodImpl(MethodImplOptions.AggressiveInlining)]
166 protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;
167
168 /// <summary>
169 /// <para>
170 /// Determines whether this instance greater or equal than zero.
171 /// </para>
172 /// <para></para>
173 /// </summary>
174 /// <param name="value">
175 /// <para>The value.</para>
176 /// <para></para>
177 /// </param>
178 /// <returns>
179 /// <para>The bool</para>
180 /// <para></para>
181 /// </returns>
182 [MethodImpl(MethodImplOptions.AggressiveInlining)]
183 protected override bool GreaterOrEqualThanZero(ulong value) => true; // value >= 0 is
    ↳ always true for ulong
184
185 /// <summary>
186 /// <para>
187 /// Determines whether this instance less or equal than zero.
188 /// </para>
189 /// <para></para>
190 /// </summary>
191 /// <param name="value">
192 /// <para>The value.</para>
193 /// <para></para>
194 /// </param>
195 /// <returns>
196 /// <para>The bool</para>
197 /// <para></para>
198 /// </returns>
199 [MethodImpl(MethodImplOptions.AggressiveInlining)]
200 protected override bool LessOrEqualThanZero(ulong value) => value == 0UL; // value is
    ↳ always >= 0 for ulong
201
202 /// <summary>
203 /// <para>
204 /// Determines whether this instance less or equal than.
205 /// </para>
206 /// <para></para>
207 /// </summary>
208 /// <param name="first">
209 /// <para>The first.</para>
210 /// <para></para>
211 /// </param>
212 /// <param name="second">
213 /// <para>The second.</para>
214 /// <para></para>
215 /// </param>
216 /// <returns>

```

```

217     /// <para>The bool</para>
218     /// <para></para>
219     /// </returns>
220     [MethodImpl(MethodImplOptions.AggressiveInlining)]
221     protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;
222
223     /// <summary>
224     /// <para>
225     /// Determines whether this instance less than zero.
226     /// </para>
227     /// <para></para>
228     /// </summary>
229     /// <param name="value">
230     /// <para>The value.</para>
231     /// <para></para>
232     /// </param>
233     /// <returns>
234     /// <para>The bool</para>
235     /// <para></para>
236     /// </returns>
237     [MethodImpl(MethodImplOptions.AggressiveInlining)]
238     protected override bool LessThanZero(ulong value) => false; // value < 0 is always false
239     ↪ for ulong
240
241     /// <summary>
242     /// <para>
243     /// Determines whether this instance less than.
244     /// </para>
245     /// <para></para>
246     /// </summary>
247     /// <param name="first">
248     /// <para>The first.</para>
249     /// <para></para>
250     /// </param>
251     /// <param name="second">
252     /// <para>The second.</para>
253     /// <para></para>
254     /// </param>
255     /// <returns>
256     /// <para>The bool</para>
257     /// <para></para>
258     /// </returns>
259     [MethodImpl(MethodImplOptions.AggressiveInlining)]
260     protected override bool LessThan(ulong first, ulong second) => first < second;
261
262     /// <summary>
263     /// <para>
264     /// Increments the value.
265     /// </para>
266     /// <para></para>
267     /// </summary>
268     /// <param name="value">
269     /// <para>The value.</para>
270     /// <para></para>
271     /// </param>
272     /// <returns>
273     /// <para>The ulong</para>
274     /// <para></para>
275     /// </returns>
276     [MethodImpl(MethodImplOptions.AggressiveInlining)]
277     protected override ulong Increment(ulong value) => ++value;
278
279     /// <summary>
280     /// <para>
281     /// Decrements the value.
282     /// </para>
283     /// <para></para>
284     /// </summary>
285     /// <param name="value">
286     /// <para>The value.</para>
287     /// <para></para>
288     /// </param>
289     /// <returns>
290     /// <para>The ulong</para>
291     /// <para></para>
292     /// </returns>
293     [MethodImpl(MethodImplOptions.AggressiveInlining)]
294     protected override ulong Decrement(ulong value) => --value;

```



```

294     /// <summary>
295     /// <para>
296     /// Adds the first.
297     /// </para>
298     /// <para></para>
299     /// </summary>
300     /// <param name="first">
301     /// <para>The first.</para>
302     /// <para></para>
303     /// </param>
304     /// <param name="second">
305     /// <para>The second.</para>
306     /// <para></para>
307     /// </param>
308     /// <returns>
309     /// <para>The ulong</para>
310     /// <para></para>
311     /// </returns>
312     [MethodImpl(MethodImplOptions.AggressiveInlining)]
313     protected override ulong Add(ulong first, ulong second) => first + second;
314
315     /// <summary>
316     /// <para>
317     /// Subtracts the first.
318     /// </para>
319     /// <para></para>
320     /// </summary>
321     /// <param name="first">
322     /// <para>The first.</para>
323     /// <para></para>
324     /// </param>
325     /// <param name="second">
326     /// <para>The second.</para>
327     /// <para></para>
328     /// </param>
329     /// <returns>
330     /// <para>The ulong</para>
331     /// <para></para>
332     /// </returns>
333     [MethodImpl(MethodImplOptions.AggressiveInlining)]
334     protected override ulong Subtract(ulong first, ulong second) => first - second;
335
336     /// <summary>
337     /// <para>
338     /// Determines whether this instance first is to the left of second.
339     /// </para>
340     /// <para></para>
341     /// </summary>
342     /// <param name="first">
343     /// <para>The first.</para>
344     /// <para></para>
345     /// </param>
346     /// <param name="second">
347     /// <para>The second.</para>
348     /// <para></para>
349     /// </param>
350     /// <returns>
351     /// <para>The bool</para>
352     /// <para></para>
353     /// </returns>
354     [MethodImpl(MethodImplOptions.AggressiveInlining)]
355     protected override bool FirstIsToLeftOfSecond(ulong first, ulong second)
356     {
357         ref var firstLink = ref Links[first];
358         ref var secondLink = ref Links[second];
359         return FirstIsToLeftOfSecond(firstLink.Source, firstLink.Target,
360             ↪ secondLink.Source, secondLink.Target);
361     }
362
363     /// <summary>
364     /// <para>
365     /// Determines whether this instance first is to the right of second.
366     /// </para>
367     /// <para></para>
368     /// </summary>
369     /// <param name="first">
370     /// <para>The first.</para>

```

```

371    /// <para></para>
372    /// </param>
373    /// <param name="second">
374    /// <para>The second.</para>
375    /// <para></para>
376    /// </param>
377    /// <returns>
378    /// <para>The bool</para>
379    /// <para></para>
380    /// </returns>
381    [MethodImpl(MethodImplOptions.AggressiveInlining)]
382    protected override bool FirstIsToTheRightOfSecond(ulong first, ulong second)
383    {
384        ref var firstLink = ref Links[first];
385        ref var secondLink = ref Links[second];
386        return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
387            ↪ secondLink.Source, secondLink.Target);
388    }
389    /// <summary>
390    /// <para>
391    /// Gets the size value using the specified value.
392    /// </para>
393    /// <para></para>
394    /// </summary>
395    /// <param name="value">
396    /// <para>The value.</para>
397    /// <para></para>
398    /// </param>
399    /// <returns>
400    /// <para>The ulong</para>
401    /// <para></para>
402    /// </returns>
403    [MethodImpl(MethodImplOptions.AggressiveInlining)]
404    protected override ulong GetSizeValue(ulong value) => (value & 4294967264UL) >> 5;
405
406    /// <summary>
407    /// <para>
408    /// Sets the size value using the specified stored value.
409    /// </para>
410    /// <para></para>
411    /// </summary>
412    /// <param name="storedValue">
413    /// <para>The stored value.</para>
414    /// <para></para>
415    /// </param>
416    /// <param name="size">
417    /// <para>The size.</para>
418    /// <para></para>
419    /// </param>
420    [MethodImpl(MethodImplOptions.AggressiveInlining)]
421    protected override void SetSizeValue(ref ulong storedValue, ulong size) => storedValue =
422        ↪ storedValue & 31UL | (size & 134217727UL) << 5;
423
424    /// <summary>
425    /// <para>
426    /// Determines whether this instance get left is child value.
427    /// </para>
428    /// <para></para>
429    /// </summary>
430    /// <param name="value">
431    /// <para>The value.</para>
432    /// <para></para>
433    /// </param>
434    /// <returns>
435    /// <para>The bool</para>
436    /// <para></para>
437    /// </returns>
438    [MethodImpl(MethodImplOptions.AggressiveInlining)]
439    protected override bool GetLeftIsChildValue(ulong value) => (value & 16UL) >> 4 == 1UL;
440
441    /// <summary>
442    /// <para>
443    /// Sets the left is child value using the specified stored value.
444    /// </para>
445    /// <para></para>
446    /// </summary>
447    /// <param name="storedValue">

```

```

447 /// <para>The stored value.</para>
448 /// <para></para>
449 /// </param>
450 /// <param name="value">
451 /// <para>The value.</para>
452 /// <para></para>
453 /// </param>
454 [MethodImpl(MethodImplOptions.AggressiveInlining)]
455 protected override void SetLeftIsChildValue(ref ulong storedValue, bool value) =>
456     ↳ storedValue = storedValue & 4294967279UL | (As<bool, byte>(ref value) & 1UL) << 4;
457
458 /// <summary>
459 /// <para>
460 /// Determines whether this instance get right is child value.
461 /// </para>
462 /// <para></para>
463 /// </summary>
464 /// <param name="value">
465 /// <para>The value.</para>
466 /// <para></para>
467 /// </param>
468 /// <returns>
469 /// <para>The bool</para>
470 /// <para></para>
471 /// </returns>
472 [MethodImpl(MethodImplOptions.AggressiveInlining)]
473 protected override bool GetRightIsChildValue(ulong value) => (value & 8UL) >> 3 == 1UL;
474
475 /// <summary>
476 /// <para>
477 /// Sets the right is child value using the specified stored value.
478 /// </para>
479 /// <para></para>
480 /// </summary>
481 /// <param name="storedValue">
482 /// <para>The stored value.</para>
483 /// <para></para>
484 /// </param>
485 /// <param name="value">
486 /// <para>The value.</para>
487 /// <para></para>
488 /// </param>
489 [MethodImpl(MethodImplOptions.AggressiveInlining)]
490 protected override void SetRightIsChildValue(ref ulong storedValue, bool value) =>
491     ↳ storedValue = storedValue & 4294967287UL | (As<bool, byte>(ref value) & 1UL) << 3;
492
493 /// <summary>
494 /// <para>
495 /// Gets the balance value using the specified value.
496 /// </para>
497 /// <para></para>
498 /// </summary>
499 /// <param name="value">
500 /// <para>The value.</para>
501 /// <para></para>
502 /// </param>
503 /// <returns>
504 /// <para>The sbyte</para>
505 /// <para></para>
506 /// </returns>
507 [MethodImpl(MethodImplOptions.AggressiveInlining)]
508 protected override sbyte GetBalanceValue(ulong value) => unchecked((sbyte)(value & 7UL |
509     ↳ 0xF8UL * ((value & 4UL) >> 2))); // if negative, then continue ones to the end of
510     ↳ sbyte
511
512 /// <summary>
513 /// <para>
514 /// Sets the balance value using the specified stored value.
515 /// </para>
516 /// <para></para>
517 /// </summary>
518 /// <param name="storedValue">
519 /// <para>The stored value.</para>
520 /// <para></para>
521 /// </param>
522 /// <param name="value">
523 /// <para>The value.</para>
524 /// <para></para>
525 /// </param>

```

```

521     /// </param>
522     [MethodImpl(MethodImplOptions.AggressiveInlining)]
523     protected override void SetBalanceValue(ref ulong storedValue, sbyte value) =>
524     ↪ storedValue = unchecked(storedValue & 4294967288UL | (ulong)((byte)value >> 5 & 4 |
525     ↪ value & 3) & 7UL);
526
527     /// <summary>
528     /// <para>
529     /// Gets the header reference.
530     /// </para>
531     /// </summary>
532     /// <returns>
533     /// <para>A ref links header of ulong</para>
534     /// </returns>
535     [MethodImpl(MethodImplOptions.AggressiveInlining)]
536     protected override ref LinksHeader<ulong> GetHeaderReference() => ref *Header;
537
538     /// <summary>
539     /// <para>
540     /// Gets the link reference using the specified link.
541     /// </para>
542     /// </summary>
543     /// <param name="link">
544     /// <para>The link.</para>
545     /// </param>
546     /// <returns>
547     /// <para>A ref raw link of ulong</para>
548     /// </returns>
549     [MethodImpl(MethodImplOptions.AggressiveInlining)]
550     protected override ref RawLink<ulong> GetLinkReference(ulong link) => ref Links[link];
551 }
552 }
553 }
554 }
555 }

```

1.102 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksRecursionlessSizeBalancedTreeMeth

```

1  using System.Runtime.CompilerServices;
2  using Platform.Data.Doublets.Memory.United.Generic;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.Memory.United.Specific
7  {
8      /// <summary>
9      /// <para>
10     /// Represents the int 64 links recursionless size balanced tree methods base.
11     /// </para>
12     /// </summary>
13     /// <seealso cref="LinksRecursionlessSizeBalancedTreeMethodsBase{ulong}"/>
14     public unsafe abstract class UInt64LinksRecursionlessSizeBalancedTreeMethodsBase :
15     ↪ LinksRecursionlessSizeBalancedTreeMethodsBase<ulong>
16     {
17         /// <summary>
18         /// <para>
19         /// The links.
20         /// </para>
21         /// </summary>
22         protected new readonly RawLink<ulong>* Links;
23
24         /// <summary>
25         /// <para>
26         /// The header.
27         /// </para>
28         /// </summary>
29         protected new readonly LinksHeader<ulong>* Header;
30
31         /// <summary>
32         /// <para>
33         /// Initializes a new <see cref="UInt64LinksRecursionlessSizeBalancedTreeMethodsBase"/>
34         ↪ instance.
35         /// </para>
36         /// </summary>
37

```

```

38     /// <param name="constants">
39     /// <para>A constants.</para>
40     /// <para></para>
41     /// </param>
42     /// <param name="links">
43     /// <para>A links.</para>
44     /// <para></para>
45     /// </param>
46     /// <param name="header">
47     /// <para>A header.</para>
48     /// <para></para>
49     /// </param>
50     protected UInt64LinksRecursionlessSizeBalancedTreeMethodsBase(LinksConstants<ulong>
    → constants, RawLink<ulong>* links, LinksHeader<ulong>* header)
    : base(constants, (byte*)links, (byte*)header)
51     {
52     }
53     Links = links;
54     Header = header;
55 }
56
57     /// <summary>
58     /// <para>
59     /// Gets the zero.
60     /// </para>
61     /// <para></para>
62     /// </summary>
63     /// <returns>
64     /// <para>The ulong</para>
65     /// <para></para>
66     /// </returns>
67     [MethodImpl(MethodImplOptions.AggressiveInlining)]
68     protected override ulong GetZero() => OUL;
69
70     /// <summary>
71     /// <para>
72     /// Determines whether this instance equal to zero.
73     /// </para>
74     /// <para></para>
75     /// </summary>
76     /// <param name="value">
77     /// <para>The value.</para>
78     /// <para></para>
79     /// </param>
80     /// <returns>
81     /// <para>The bool</para>
82     /// <para></para>
83     /// </returns>
84     [MethodImpl(MethodImplOptions.AggressiveInlining)]
85     protected override bool EqualToZero(ulong value) => value == OUL;
86
87     /// <summary>
88     /// <para>
89     /// Determines whether this instance are equal.
90     /// </para>
91     /// <para></para>
92     /// </summary>
93     /// <param name="first">
94     /// <para>The first.</para>
95     /// <para></para>
96     /// </param>
97     /// <param name="second">
98     /// <para>The second.</para>
99     /// <para></para>
100    /// </param>
101    /// <returns>
102    /// <para>The bool</para>
103    /// <para></para>
104    /// </returns>
105    [MethodImpl(MethodImplOptions.AggressiveInlining)]
106    protected override bool AreEqual(ulong first, ulong second) => first == second;
107
108    /// <summary>
109    /// <para>
110    /// Determines whether this instance greater than zero.
111    /// </para>
112    /// <para></para>
113    /// </summary>
114    /// <param name="value">

```

```

115     /// <para>The value.</para>
116     /// <para></para>
117     /// </param>
118     /// <returns>
119     /// <para>The bool</para>
120     /// <para></para>
121     /// </returns>
122     [MethodImpl(MethodImplOptions.AggressiveInlining)]
123     protected override bool GreaterThanZero(ulong value) => value > 0UL;
124
125     /// <summary>
126     /// <para>
127     /// Determines whether this instance greater than.
128     /// </para>
129     /// <para></para>
130     /// </summary>
131     /// <param name="first">
132     /// <para>The first.</para>
133     /// <para></para>
134     /// </param>
135     /// <param name="second">
136     /// <para>The second.</para>
137     /// <para></para>
138     /// </param>
139     /// <returns>
140     /// <para>The bool</para>
141     /// <para></para>
142     /// </returns>
143     [MethodImpl(MethodImplOptions.AggressiveInlining)]
144     protected override bool GreaterThan(ulong first, ulong second) => first > second;
145
146     /// <summary>
147     /// <para>
148     /// Determines whether this instance greater or equal than.
149     /// </para>
150     /// <para></para>
151     /// </summary>
152     /// <param name="first">
153     /// <para>The first.</para>
154     /// <para></para>
155     /// </param>
156     /// <param name="second">
157     /// <para>The second.</para>
158     /// <para></para>
159     /// </param>
160     /// <returns>
161     /// <para>The bool</para>
162     /// <para></para>
163     /// </returns>
164     [MethodImpl(MethodImplOptions.AggressiveInlining)]
165     protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;
166
167     /// <summary>
168     /// <para>
169     /// Determines whether this instance greater or equal than zero.
170     /// </para>
171     /// <para></para>
172     /// </summary>
173     /// <param name="value">
174     /// <para>The value.</para>
175     /// <para></para>
176     /// </param>
177     /// <returns>
178     /// <para>The bool</para>
179     /// <para></para>
180     /// </returns>
181     [MethodImpl(MethodImplOptions.AggressiveInlining)]
182     protected override bool GreaterOrEqualThanZero(ulong value) => true; // value >= 0 is
    ↪ always true for ulong
183
184     /// <summary>
185     /// <para>
186     /// Determines whether this instance less or equal than zero.
187     /// </para>
188     /// <para></para>
189     /// </summary>
190     /// <param name="value">
191     /// <para>The value.</para>

```

```

192    /// <para></para>
193    /// </param>
194    /// <returns>
195    /// <para>The bool</para>
196    /// <para></para>
197    /// </returns>
198    [MethodImpl(MethodImplOptions.AggressiveInlining)]
199    protected override bool LessOrEqualThanZero(ulong value) => value == 0UL; // value is
    ↪ always >= 0 for ulong
200
201    /// <summary>
202    /// <para>
203    /// Determines whether this instance less or equal than.
204    /// </para>
205    /// <para></para>
206    /// </summary>
207    /// <param name="first">
208    /// <para>The first.</para>
209    /// <para></para>
210    /// </param>
211    /// <param name="second">
212    /// <para>The second.</para>
213    /// <para></para>
214    /// </param>
215    /// <returns>
216    /// <para>The bool</para>
217    /// <para></para>
218    /// </returns>
219    [MethodImpl(MethodImplOptions.AggressiveInlining)]
220    protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;
221
222    /// <summary>
223    /// <para>
224    /// Determines whether this instance less than zero.
225    /// </para>
226    /// <para></para>
227    /// </summary>
228    /// <param name="value">
229    /// <para>The value.</para>
230    /// <para></para>
231    /// </param>
232    /// <returns>
233    /// <para>The bool</para>
234    /// <para></para>
235    /// </returns>
236    [MethodImpl(MethodImplOptions.AggressiveInlining)]
237    protected override bool LessThanZero(ulong value) => false; // value < 0 is always false
    ↪ for ulong
238
239    /// <summary>
240    /// <para>
241    /// Determines whether this instance less than.
242    /// </para>
243    /// <para></para>
244    /// </summary>
245    /// <param name="first">
246    /// <para>The first.</para>
247    /// <para></para>
248    /// </param>
249    /// <param name="second">
250    /// <para>The second.</para>
251    /// <para></para>
252    /// </param>
253    /// <returns>
254    /// <para>The bool</para>
255    /// <para></para>
256    /// </returns>
257    [MethodImpl(MethodImplOptions.AggressiveInlining)]
258    protected override bool LessThan(ulong first, ulong second) => first < second;
259
260    /// <summary>
261    /// <para>
262    /// Increments the value.
263    /// </para>
264    /// <para></para>
265    /// </summary>
266    /// <param name="value">
267    /// <para>The value.</para>

```

```

268     /// <para></para>
269     /// </param>
270     /// <returns>
271     /// <para>The ulong</para>
272     /// <para></para>
273     /// </returns>
274     [MethodImpl(MethodImplOptions.AggressiveInlining)]
275     protected override ulong Increment(ulong value) => ++value;
276
277     /// <summary>
278     /// <para>
279     /// Decrements the value.
280     /// </para>
281     /// <para></para>
282     /// </summary>
283     /// <param name="value">
284     /// <para>The value.</para>
285     /// <para></para>
286     /// </param>
287     /// <returns>
288     /// <para>The ulong</para>
289     /// <para></para>
290     /// </returns>
291     [MethodImpl(MethodImplOptions.AggressiveInlining)]
292     protected override ulong Decrement(ulong value) => --value;
293
294     /// <summary>
295     /// <para>
296     /// Adds the first.
297     /// </para>
298     /// <para></para>
299     /// </summary>
300     /// <param name="first">
301     /// <para>The first.</para>
302     /// <para></para>
303     /// </param>
304     /// <param name="second">
305     /// <para>The second.</para>
306     /// <para></para>
307     /// </param>
308     /// <returns>
309     /// <para>The ulong</para>
310     /// <para></para>
311     /// </returns>
312     [MethodImpl(MethodImplOptions.AggressiveInlining)]
313     protected override ulong Add(ulong first, ulong second) => first + second;
314
315     /// <summary>
316     /// <para>
317     /// Subtracts the first.
318     /// </para>
319     /// <para></para>
320     /// </summary>
321     /// <param name="first">
322     /// <para>The first.</para>
323     /// <para></para>
324     /// </param>
325     /// <param name="second">
326     /// <para>The second.</para>
327     /// <para></para>
328     /// </param>
329     /// <returns>
330     /// <para>The ulong</para>
331     /// <para></para>
332     /// </returns>
333     [MethodImpl(MethodImplOptions.AggressiveInlining)]
334     protected override ulong Subtract(ulong first, ulong second) => first - second;
335
336     /// <summary>
337     /// <para>
338     /// Determines whether this instance first is to the left of second.
339     /// </para>
340     /// <para></para>
341     /// </summary>
342     /// <param name="first">
343     /// <para>The first.</para>
344     /// <para></para>
345     /// </param>

```



```

346    /// <param name="second">
347    /// <para>The second.</para>
348    /// <para></para>
349    /// </param>
350    /// <returns>
351    /// <para>The bool</para>
352    /// <para></para>
353    /// </returns>
354    [MethodImpl(MethodImplOptions.AggressiveInlining)]
355    protected override bool FirstIsToTheLeftOfSecond(ulong first, ulong second)
356    {
357        ref var firstLink = ref Links[first];
358        ref var secondLink = ref Links[second];
359        return FirstIsToTheLeftOfSecond(firstLink.Source, firstLink.Target,
360            ↪ secondLink.Source, secondLink.Target);
361    }
362    /// <summary>
363    /// <para>
364    /// Determines whether this instance first is to the right of second.
365    /// </para>
366    /// <para></para>
367    /// </summary>
368    /// <param name="first">
369    /// <para>The first.</para>
370    /// <para></para>
371    /// </param>
372    /// <param name="second">
373    /// <para>The second.</para>
374    /// <para></para>
375    /// </param>
376    /// <returns>
377    /// <para>The bool</para>
378    /// <para></para>
379    /// </returns>
380    [MethodImpl(MethodImplOptions.AggressiveInlining)]
381    protected override bool FirstIsToTheRightOfSecond(ulong first, ulong second)
382    {
383        ref var firstLink = ref Links[first];
384        ref var secondLink = ref Links[second];
385        return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
386            ↪ secondLink.Source, secondLink.Target);
387    }
388    /// <summary>
389    /// <para>
390    /// Gets the header reference.
391    /// </para>
392    /// <para></para>
393    /// </summary>
394    /// <returns>
395    /// <para>A ref links header of ulong</para>
396    /// <para></para>
397    /// </returns>
398    [MethodImpl(MethodImplOptions.AggressiveInlining)]
399    protected override ref LinksHeader<ulong> GetHeaderReference() => ref *Header;
400
401    /// <summary>
402    /// <para>
403    /// Gets the link reference using the specified link.
404    /// </para>
405    /// <para></para>
406    /// </summary>
407    /// <param name="link">
408    /// <para>The link.</para>
409    /// <para></para>
410    /// </param>
411    /// <returns>
412    /// <para>A ref raw link of ulong</para>
413    /// <para></para>
414    /// </returns>
415    [MethodImpl(MethodImplOptions.AggressiveInlining)]
416    protected override ref RawLink<ulong> GetLinkReference(ulong link) => ref Links[link];
417 }
418 }

```

1.103 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksSizeBalancedTreeMethodsBase.cs

```
1 using System.Runtime.CompilerServices;
2 using Platform.Data.Doublets.Memory.United.Generic;
3
4 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6 namespace Platform.Data.Doublets.Memory.United.Specific
7 {
8     /// <summary>
9     /// <para>
10    /// Represents the int 64 links size balanced tree methods base.
11    /// </para>
12    /// <para></para>
13    /// </summary>
14    /// <seealso cref="LinksSizeBalancedTreeMethodsBase{ulong}"/>
15    public unsafe abstract class UInt64LinksSizeBalancedTreeMethodsBase :
16    ↪ LinksSizeBalancedTreeMethodsBase<ulong>
17    {
18        /// <summary>
19        /// <para>
20        /// The links.
21        /// </para>
22        /// <para></para>
23        /// </summary>
24        protected new readonly RawLink<ulong>* Links;
25        /// <summary>
26        /// <para>
27        /// The header.
28        /// </para>
29        /// <para></para>
30        /// </summary>
31        protected new readonly LinksHeader<ulong>* Header;
32
33        /// <summary>
34        /// <para>
35        /// Initializes a new <see cref="UInt64LinksSizeBalancedTreeMethodsBase"/> instance.
36        /// </para>
37        /// <para></para>
38        /// </summary>
39        /// <param name="constants">
40        /// <para>A constants.</para>
41        /// <para></para>
42        /// </param>
43        /// <param name="links">
44        /// <para>A links.</para>
45        /// <para></para>
46        /// </param>
47        /// <param name="header">
48        /// <para>A header.</para>
49        /// <para></para>
50        /// </param>
51        protected UInt64LinksSizeBalancedTreeMethodsBase(LinksConstants<ulong> constants,
52    ↪ RawLink<ulong>* links, LinksHeader<ulong>* header)
53        : base(constants, (byte*)links, (byte*)header)
54        {
55            Links = links;
56            Header = header;
57        }
58
59        /// <summary>
60        /// <para>
61        /// Gets the zero.
62        /// </para>
63        /// <para></para>
64        /// </summary>
65        /// <returns>
66        /// <para>The ulong</para>
67        /// <para></para>
68        /// </returns>
69        [MethodImpl(MethodImplOptions.AggressiveInlining)]
70        protected override ulong GetZero() => 0UL;
71
72        /// <summary>
73        /// <para>
74        /// Determines whether this instance equal to zero.
75        /// </para>
76        /// <para></para>
77        /// </summary>
```

```

76     /// <param name="value">
77     /// <para>The value.</para>
78     /// <para></para>
79     /// </param>
80     /// <returns>
81     /// <para>The bool</para>
82     /// <para></para>
83     /// </returns>
84     [MethodImpl(MethodImplOptions.AggressiveInlining)]
85     protected override bool EqualToZero(ulong value) => value == 0UL;
86
87     /// <summary>
88     /// <para>
89     /// Determines whether this instance are equal.
90     /// </para>
91     /// <para></para>
92     /// </summary>
93     /// <param name="first">
94     /// <para>The first.</para>
95     /// <para></para>
96     /// </param>
97     /// <param name="second">
98     /// <para>The second.</para>
99     /// <para></para>
100    /// </param>
101    /// <returns>
102    /// <para>The bool</para>
103    /// <para></para>
104    /// </returns>
105    [MethodImpl(MethodImplOptions.AggressiveInlining)]
106    protected override bool AreEqual(ulong first, ulong second) => first == second;
107
108    /// <summary>
109    /// <para>
110    /// Determines whether this instance greater than zero.
111    /// </para>
112    /// <para></para>
113    /// </summary>
114    /// <param name="value">
115    /// <para>The value.</para>
116    /// <para></para>
117    /// </param>
118    /// <returns>
119    /// <para>The bool</para>
120    /// <para></para>
121    /// </returns>
122    [MethodImpl(MethodImplOptions.AggressiveInlining)]
123    protected override bool GreaterThanZero(ulong value) => value > 0UL;
124
125    /// <summary>
126    /// <para>
127    /// Determines whether this instance greater than.
128    /// </para>
129    /// <para></para>
130    /// </summary>
131    /// <param name="first">
132    /// <para>The first.</para>
133    /// <para></para>
134    /// </param>
135    /// <param name="second">
136    /// <para>The second.</para>
137    /// <para></para>
138    /// </param>
139    /// <returns>
140    /// <para>The bool</para>
141    /// <para></para>
142    /// </returns>
143    [MethodImpl(MethodImplOptions.AggressiveInlining)]
144    protected override bool GreaterThan(ulong first, ulong second) => first > second;
145
146    /// <summary>
147    /// <para>
148    /// Determines whether this instance greater or equal than.
149    /// </para>
150    /// <para></para>
151    /// </summary>
152    /// <param name="first">
153    /// <para>The first.</para>

```

```

154    /// <para></para>
155    /// </param>
156    /// <param name="second">
157    /// <para>The second.</para>
158    /// <para></para>
159    /// </param>
160    /// <returns>
161    /// <para>The bool</para>
162    /// <para></para>
163    /// </returns>
164    [MethodImpl(MethodImplOptions.AggressiveInlining)]
165    protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;
166
167    /// <summary>
168    /// <para>
169    /// Determines whether this instance greater or equal than zero.
170    /// </para>
171    /// <para></para>
172    /// </summary>
173    /// <param name="value">
174    /// <para>The value.</para>
175    /// <para></para>
176    /// </param>
177    /// <returns>
178    /// <para>The bool</para>
179    /// <para></para>
180    /// </returns>
181    [MethodImpl(MethodImplOptions.AggressiveInlining)]
182    protected override bool GreaterOrEqualThanZero(ulong value) => true; // value >= 0 is
    ↪ always true for ulong
183
184    /// <summary>
185    /// <para>
186    /// Determines whether this instance less or equal than zero.
187    /// </para>
188    /// <para></para>
189    /// </summary>
190    /// <param name="value">
191    /// <para>The value.</para>
192    /// <para></para>
193    /// </param>
194    /// <returns>
195    /// <para>The bool</para>
196    /// <para></para>
197    /// </returns>
198    [MethodImpl(MethodImplOptions.AggressiveInlining)]
199    protected override bool LessOrEqualThanZero(ulong value) => value == 0UL; // value is
    ↪ always >= 0 for ulong
200
201    /// <summary>
202    /// <para>
203    /// Determines whether this instance less or equal than.
204    /// </para>
205    /// <para></para>
206    /// </summary>
207    /// <param name="first">
208    /// <para>The first.</para>
209    /// <para></para>
210    /// </param>
211    /// <param name="second">
212    /// <para>The second.</para>
213    /// <para></para>
214    /// </param>
215    /// <returns>
216    /// <para>The bool</para>
217    /// <para></para>
218    /// </returns>
219    [MethodImpl(MethodImplOptions.AggressiveInlining)]
220    protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;
221
222    /// <summary>
223    /// <para>
224    /// Determines whether this instance less than zero.
225    /// </para>
226    /// <para></para>
227    /// </summary>
228    /// <param name="value">
229    /// <para>The value.</para>

```

```

230    /// <para></para>
231    /// </param>
232    /// <returns>
233    /// <para>The bool</para>
234    /// <para></para>
235    /// </returns>
236    [MethodImpl(MethodImplOptions.AggressiveInlining)]
237    protected override bool LessThanZero(ulong value) => false; // value < 0 is always false
    ↪    for ulong
238
239    /// <summary>
240    /// <para>
241    /// Determines whether this instance less than.
242    /// </para>
243    /// <para></para>
244    /// </summary>
245    /// <param name="first">
246    /// <para>The first.</para>
247    /// <para></para>
248    /// </param>
249    /// <param name="second">
250    /// <para>The second.</para>
251    /// <para></para>
252    /// </param>
253    /// <returns>
254    /// <para>The bool</para>
255    /// <para></para>
256    /// </returns>
257    [MethodImpl(MethodImplOptions.AggressiveInlining)]
258    protected override bool LessThan(ulong first, ulong second) => first < second;
259
260    /// <summary>
261    /// <para>
262    /// Increments the value.
263    /// </para>
264    /// <para></para>
265    /// </summary>
266    /// <param name="value">
267    /// <para>The value.</para>
268    /// <para></para>
269    /// </param>
270    /// <returns>
271    /// <para>The ulong</para>
272    /// <para></para>
273    /// </returns>
274    [MethodImpl(MethodImplOptions.AggressiveInlining)]
275    protected override ulong Increment(ulong value) => ++value;
276
277    /// <summary>
278    /// <para>
279    /// Decrements the value.
280    /// </para>
281    /// <para></para>
282    /// </summary>
283    /// <param name="value">
284    /// <para>The value.</para>
285    /// <para></para>
286    /// </param>
287    /// <returns>
288    /// <para>The ulong</para>
289    /// <para></para>
290    /// </returns>
291    [MethodImpl(MethodImplOptions.AggressiveInlining)]
292    protected override ulong Decrement(ulong value) => --value;
293
294    /// <summary>
295    /// <para>
296    /// Adds the first.
297    /// </para>
298    /// <para></para>
299    /// </summary>
300    /// <param name="first">
301    /// <para>The first.</para>
302    /// <para></para>
303    /// </param>
304    /// <param name="second">
305    /// <para>The second.</para>
306    /// <para></para>

```

```

307     /// </param>
308     /// <returns>
309     /// <para>The ulong</para>
310     /// <para></para>
311     /// </returns>
312     [MethodImpl(MethodImplOptions.AggressiveInlining)]
313     protected override ulong Add(ulong first, ulong second) => first + second;
314
315     /// <summary>
316     /// <para>
317     /// Subtracts the first.
318     /// </para>
319     /// <para></para>
320     /// </summary>
321     /// <param name="first">
322     /// <para>The first.</para>
323     /// <para></para>
324     /// </param>
325     /// <param name="second">
326     /// <para>The second.</para>
327     /// <para></para>
328     /// </param>
329     /// <returns>
330     /// <para>The ulong</para>
331     /// <para></para>
332     /// </returns>
333     [MethodImpl(MethodImplOptions.AggressiveInlining)]
334     protected override ulong Subtract(ulong first, ulong second) => first - second;
335
336     /// <summary>
337     /// <para>
338     /// Determines whether this instance first is to the left of second.
339     /// </para>
340     /// <para></para>
341     /// </summary>
342     /// <param name="first">
343     /// <para>The first.</para>
344     /// <para></para>
345     /// </param>
346     /// <param name="second">
347     /// <para>The second.</para>
348     /// <para></para>
349     /// </param>
350     /// <returns>
351     /// <para>The bool</para>
352     /// <para></para>
353     /// </returns>
354     [MethodImpl(MethodImplOptions.AggressiveInlining)]
355     protected override bool FirstIsToLeftOfSecond(ulong first, ulong second)
356     {
357         ref var firstLink = ref Links[first];
358         ref var secondLink = ref Links[second];
359         return FirstIsToLeftOfSecond(firstLink.Source, firstLink.Target,
360             ↪ secondLink.Source, secondLink.Target);
361     }
362
363     /// <summary>
364     /// <para>
365     /// Determines whether this instance first is to the right of second.
366     /// </para>
367     /// <para></para>
368     /// </summary>
369     /// <param name="first">
370     /// <para>The first.</para>
371     /// <para></para>
372     /// </param>
373     /// <param name="second">
374     /// <para>The second.</para>
375     /// <para></para>
376     /// </param>
377     /// <returns>
378     /// <para>The bool</para>
379     /// <para></para>
380     /// </returns>
381     [MethodImpl(MethodImplOptions.AggressiveInlining)]
382     protected override bool FirstIsToTheRightOfSecond(ulong first, ulong second)
383     {
384         ref var firstLink = ref Links[first];

```

```

384         ref var secondLink = ref Links[second];
385         return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
        ↪ secondLink.Source, secondLink.Target);
386     }
387
388     /// <summary>
389     /// <para>
390     /// Gets the header reference.
391     /// </para>
392     /// <para></para>
393     /// </summary>
394     /// <returns>
395     /// <para>A ref links header of ulong</para>
396     /// <para></para>
397     /// </returns>
398     [MethodImpl(MethodImplOptions.AggressiveInlining)]
399     protected override ref LinksHeader<ulong> GetHeaderReference() => ref *Header;
400
401     /// <summary>
402     /// <para>
403     /// Gets the link reference using the specified link.
404     /// </para>
405     /// <para></para>
406     /// </summary>
407     /// <param name="link">
408     /// <para>The link.</para>
409     /// <para></para>
410     /// </param>
411     /// <returns>
412     /// <para>A ref raw link of ulong</para>
413     /// <para></para>
414     /// </returns>
415     [MethodImpl(MethodImplOptions.AggressiveInlining)]
416     protected override ref RawLink<ulong> GetLinkReference(ulong link) => ref Links[link];
417 }
418 }

```

1.104 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksSourcesAvlBalancedTreeMethods.cs

```

1 using System.Runtime.CompilerServices;
2
3 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5 namespace Platform.Data.Doublets.Memory.United.Specific
6 {
7     /// <summary>
8     /// <para>
9     /// Represents the int 64 links sources avl balanced tree methods.
10    /// </para>
11    /// <para></para>
12    /// </summary>
13    /// <seealso cref="UInt64LinksAvlBalancedTreeMethodsBase"/>
14    public unsafe class UInt64LinksSourcesAvlBalancedTreeMethods :
        ↪ UInt64LinksAvlBalancedTreeMethodsBase
15    {
16        /// <summary>
17        /// <para>
18        /// Initializes a new <see cref="UInt64LinksSourcesAvlBalancedTreeMethods"/> instance.
19        /// </para>
20        /// <para></para>
21        /// </summary>
22        /// <param name="constants">
23        /// <para>A constants.</para>
24        /// <para></para>
25        /// </param>
26        /// <param name="links">
27        /// <para>A links.</para>
28        /// <para></para>
29        /// </param>
30        /// <param name="header">
31        /// <para>A header.</para>
32        /// <para></para>
33        /// </param>
34        public UInt64LinksSourcesAvlBalancedTreeMethods(LinksConstants<ulong> constants,
        ↪ RawLink<ulong>* links, LinksHeader<ulong>* header) : base(constants, links, header)
        ↪ { }
35
36        /// <summary>
37        /// <para>

```

```

38     /// Gets the left reference using the specified node.
39     /// </para>
40     /// <para></para>
41     /// </summary>
42     /// <param name="node">
43     /// <para>The node.</para>
44     /// <para></para>
45     /// </param>
46     /// <returns>
47     /// <para>The ref ulong</para>
48     /// <para></para>
49     /// </returns>
50     [MethodImpl(MethodImplOptions.AggressiveInlining)]
51     protected override ref ulong GetLeftReference(ulong node) => ref
52     ↪ Links[node].LeftAsSource;
53
54     /// <summary>
55     /// <para>
56     /// Gets the right reference using the specified node.
57     /// </para>
58     /// <para></para>
59     /// </summary>
60     /// <param name="node">
61     /// <para>The node.</para>
62     /// <para></para>
63     /// </param>
64     /// <returns>
65     /// <para>The ref ulong</para>
66     /// <para></para>
67     /// </returns>
68     [MethodImpl(MethodImplOptions.AggressiveInlining)]
69     protected override ref ulong GetRightReference(ulong node) => ref
70     ↪ Links[node].RightAsSource;
71
72     /// <summary>
73     /// <para>
74     /// Gets the left using the specified node.
75     /// </para>
76     /// <para></para>
77     /// </summary>
78     /// <param name="node">
79     /// <para>The node.</para>
80     /// <para></para>
81     /// </param>
82     /// <returns>
83     /// <para>The ulong</para>
84     /// <para></para>
85     /// </returns>
86     [MethodImpl(MethodImplOptions.AggressiveInlining)]
87     protected override ulong GetLeft(ulong node) => Links[node].LeftAsSource;
88
89     /// <summary>
90     /// <para>
91     /// Gets the right using the specified node.
92     /// </para>
93     /// <para></para>
94     /// </summary>
95     /// <param name="node">
96     /// <para>The node.</para>
97     /// <para></para>
98     /// </param>
99     /// <returns>
100    /// <para>The ulong</para>
101    /// <para></para>
102    /// </returns>
103    [MethodImpl(MethodImplOptions.AggressiveInlining)]
104    protected override ulong GetRight(ulong node) => Links[node].RightAsSource;
105
106    /// <summary>
107    /// <para>
108    /// Sets the left using the specified node.
109    /// </para>
110    /// <para></para>
111    /// </summary>
112    /// <param name="node">
113    /// <para>The node.</para>

```



```

114     /// <param name="left">
115     /// <para>The left.</para>
116     /// <para></para>
117     /// </param>
118     [MethodImpl(MethodImplOptions.AggressiveInlining)]
119     protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsSource =
        ↳ left;

120
121     /// <summary>
122     /// <para>
123     /// Sets the right using the specified node.
124     /// </para>
125     /// <para></para>
126     /// </summary>
127     /// <param name="node">
128     /// <para>The node.</para>
129     /// <para></para>
130     /// </param>
131     /// <param name="right">
132     /// <para>The right.</para>
133     /// <para></para>
134     /// </param>
135     [MethodImpl(MethodImplOptions.AggressiveInlining)]
136     protected override void SetRight(ulong node, ulong right) => Links[node].RightAsSource =
        ↳ right;

137
138     /// <summary>
139     /// <para>
140     /// Gets the size using the specified node.
141     /// </para>
142     /// <para></para>
143     /// </summary>
144     /// <param name="node">
145     /// <para>The node.</para>
146     /// <para></para>
147     /// </param>
148     /// <returns>
149     /// <para>The ulong</para>
150     /// <para></para>
151     /// </returns>
152     [MethodImpl(MethodImplOptions.AggressiveInlining)]
153     protected override ulong GetSize(ulong node) => GetSizeValue(Links[node].SizeAsSource);

154
155     /// <summary>
156     /// <para>
157     /// Sets the size using the specified node.
158     /// </para>
159     /// <para></para>
160     /// </summary>
161     /// <param name="node">
162     /// <para>The node.</para>
163     /// <para></para>
164     /// </param>
165     /// <param name="size">
166     /// <para>The size.</para>
167     /// <para></para>
168     /// </param>
169     [MethodImpl(MethodImplOptions.AggressiveInlining)]
170     protected override void SetSize(ulong node, ulong size) => SetSizeValue(ref
        ↳ Links[node].SizeAsSource, size);

171
172     /// <summary>
173     /// <para>
174     /// Determines whether this instance get left is child.
175     /// </para>
176     /// <para></para>
177     /// </summary>
178     /// <param name="node">
179     /// <para>The node.</para>
180     /// <para></para>
181     /// </param>
182     /// <returns>
183     /// <para>The bool</para>
184     /// <para></para>
185     /// </returns>
186     [MethodImpl(MethodImplOptions.AggressiveInlining)]
187     protected override bool GetLeftIsChild(ulong node) =>
        ↳ GetLeftIsChildValue(Links[node].SizeAsSource);

```

```

188
189 // [MethodImpl(MethodImplOptions.AggressiveInlining)]
190 // protected override bool GetLeftIsChild(ulong node) => IsChild(node, GetLeft(node));
191
192 /// <summary>
193 /// <para>
194 /// Sets the left is child using the specified node.
195 /// </para>
196 /// <para></para>
197 /// </summary>
198 /// <param name="node">
199 /// <para>The node.</para>
200 /// <para></para>
201 /// </param>
202 /// <param name="value">
203 /// <para>The value.</para>
204 /// <para></para>
205 /// </param>
206 [MethodImpl(MethodImplOptions.AggressiveInlining)]
207 protected override void SetLeftIsChild(ulong node, bool value) =>
208     ↪ SetLeftIsChildValue(ref Links[node].SizeAsSource, value);
209
210 /// <summary>
211 /// <para>
212 /// Determines whether this instance get right is child.
213 /// </para>
214 /// <para></para>
215 /// </summary>
216 /// <param name="node">
217 /// <para>The node.</para>
218 /// <para></para>
219 /// </param>
220 /// <returns>
221 /// <para>The bool</para>
222 /// <para></para>
223 /// </returns>
224 [MethodImpl(MethodImplOptions.AggressiveInlining)]
225 protected override bool GetRightIsChild(ulong node) =>
226     ↪ GetRightIsChildValue(Links[node].SizeAsSource);
227
228 // [MethodImpl(MethodImplOptions.AggressiveInlining)]
229 // protected override bool GetRightIsChild(ulong node) => IsChild(node, GetRight(node));
230
231 /// <summary>
232 /// <para>
233 /// Sets the right is child using the specified node.
234 /// </para>
235 /// <para></para>
236 /// </summary>
237 /// <param name="node">
238 /// <para>The node.</para>
239 /// <para></para>
240 /// </param>
241 /// <param name="value">
242 /// <para>The value.</para>
243 /// <para></para>
244 /// </param>
245 [MethodImpl(MethodImplOptions.AggressiveInlining)]
246 protected override void SetRightIsChild(ulong node, bool value) =>
247     ↪ SetRightIsChildValue(ref Links[node].SizeAsSource, value);
248
249 /// <summary>
250 /// <para>
251 /// Gets the balance using the specified node.
252 /// </para>
253 /// <para></para>
254 /// </summary>
255 /// <param name="node">
256 /// <para>The node.</para>
257 /// <para></para>
258 /// </param>
259 /// <returns>
260 /// <para>The sbyte</para>
261 /// <para></para>
262 /// </returns>
263 [MethodImpl(MethodImplOptions.AggressiveInlining)]
264 protected override sbyte GetBalance(ulong node) =>
265     ↪ GetBalanceValue(Links[node].SizeAsSource);

```

```

262     /// <summary>
263     /// <para>
264     /// Sets the balance using the specified node.
265     /// </para>
266     /// <para></para>
267     /// </summary>
268     /// <param name="node">
269     /// <para>The node.</para>
270     /// <para></para>
271     /// </param>
272     /// <param name="value">
273     /// <para>The value.</para>
274     /// <para></para>
275     /// </param>
276     [MethodImpl(MethodImplOptions.AggressiveInlining)]
277     protected override void SetBalance(ulong node, sbyte value) => SetBalanceValue(ref
278     ↪ Links[node].SizeAsSource, value);
279
280     /// <summary>
281     /// <para>
282     /// Gets the tree root.
283     /// </para>
284     /// <para></para>
285     /// </summary>
286     /// <returns>
287     /// <para>The ulong</para>
288     /// <para></para>
289     /// </returns>
290     [MethodImpl(MethodImplOptions.AggressiveInlining)]
291     protected override ulong GetTreeRoot() => Header->RootAsSource;
292
293     /// <summary>
294     /// <para>
295     /// Gets the base part value using the specified link.
296     /// </para>
297     /// <para></para>
298     /// </summary>
299     /// <param name="link">
300     /// <para>The link.</para>
301     /// <para></para>
302     /// </param>
303     /// <returns>
304     /// <para>The ulong</para>
305     /// <para></para>
306     /// </returns>
307     [MethodImpl(MethodImplOptions.AggressiveInlining)]
308     protected override ulong GetBasePartValue(ulong link) => Links[link].Source;
309
310     /// <summary>
311     /// <para>
312     /// Determines whether this instance first is to the left of second.
313     /// </para>
314     /// <para></para>
315     /// </summary>
316     /// <param name="firstSource">
317     /// <para>The first source.</para>
318     /// <para></para>
319     /// </param>
320     /// <param name="firstTarget">
321     /// <para>The first target.</para>
322     /// <para></para>
323     /// </param>
324     /// <param name="secondSource">
325     /// <para>The second source.</para>
326     /// <para></para>
327     /// </param>
328     /// <param name="secondTarget">
329     /// <para>The second target.</para>
330     /// <para></para>
331     /// </param>
332     /// <returns>
333     /// <para>The bool</para>
334     /// <para></para>
335     /// </returns>
336     [MethodImpl(MethodImplOptions.AggressiveInlining)]
337     protected override bool FirstIsToTheLeftOfSecond(ulong firstSource, ulong firstTarget,
    ↪ ulong secondSource, ulong secondTarget)

```

```

338         => firstSource < secondSource || (firstSource == secondSource && firstTarget <
        ↪ secondTarget);
339
340     /// <summary>
341     /// <para>
342     /// Determines whether this instance first is to the right of second.
343     /// </para>
344     /// <para></para>
345     /// </summary>
346     /// <param name="firstSource">
347     /// <para>The first source.</para>
348     /// <para></para>
349     /// </param>
350     /// <param name="firstTarget">
351     /// <para>The first target.</para>
352     /// <para></para>
353     /// </param>
354     /// <param name="secondSource">
355     /// <para>The second source.</para>
356     /// <para></para>
357     /// </param>
358     /// <param name="secondTarget">
359     /// <para>The second target.</para>
360     /// <para></para>
361     /// </param>
362     /// <returns>
363     /// <para>The bool</para>
364     /// <para></para>
365     /// </returns>
366     [MethodImpl(MethodImplOptions.AggressiveInlining)]
367     protected override bool FirstIsToTheRightOfSecond(ulong firstSource, ulong firstTarget,
        ↪ ulong secondSource, ulong secondTarget)
368     => firstSource > secondSource || (firstSource == secondSource && firstTarget >
        ↪ secondTarget);
369
370     /// <summary>
371     /// <para>
372     /// Clears the node using the specified node.
373     /// </para>
374     /// <para></para>
375     /// </summary>
376     /// <param name="node">
377     /// <para>The node.</para>
378     /// <para></para>
379     /// </param>
380     [MethodImpl(MethodImplOptions.AggressiveInlining)]
381     protected override void ClearNode(ulong node)
382     {
383         ref var link = ref Links[node];
384         link.LeftAsSource = OUL;
385         link.RightAsSource = OUL;
386         link.SizeAsSource = OUL;
387     }
388 }
389 }

```

1.105 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksSourcesRecursionlessSizeBalancedTreeMethods

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.United.Specific
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the int 64 links sources recursionless size balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="UInt64LinksRecursionlessSizeBalancedTreeMethodsBase"/>
14     public unsafe class UInt64LinksSourcesRecursionlessSizeBalancedTreeMethods :
        ↪ UInt64LinksRecursionlessSizeBalancedTreeMethodsBase
15     {
16         /// <summary>
17         /// <para>
18         /// Initializes a new <see
19         ↪ cref="UInt64LinksSourcesRecursionlessSizeBalancedTreeMethods"/> instance.
20         /// </para>

```

```

20    /// <para></para>
21    /// </summary>
22    /// <param name="constants">
23    /// <para>A constants.</para>
24    /// <para></para>
25    /// </param>
26    /// <param name="links">
27    /// <para>A links.</para>
28    /// <para></para>
29    /// </param>
30    /// <param name="header">
31    /// <para>A header.</para>
32    /// <para></para>
33    /// </param>
34    public UInt64LinksSourcesRecursionlessSizeBalancedTreeMethods(LinksConstants<ulong>
    ↪ constants, RawLink<ulong>* links, LinksHeader<ulong>* header) : base(constants,
    ↪ links, header) { }
35
36    /// <summary>
37    /// <para>
38    /// Gets the left reference using the specified node.
39    /// </para>
40    /// <para></para>
41    /// </summary>
42    /// <param name="node">
43    /// <para>The node.</para>
44    /// <para></para>
45    /// </param>
46    /// <returns>
47    /// <para>The ref ulong</para>
48    /// <para></para>
49    /// </returns>
50    [MethodImpl(MethodImplOptions.AggressiveInlining)]
51    protected override ref ulong GetLeftReference(ulong node) => ref
    ↪ Links[node].LeftAsSource;
52
53    /// <summary>
54    /// <para>
55    /// Gets the right reference using the specified node.
56    /// </para>
57    /// <para></para>
58    /// </summary>
59    /// <param name="node">
60    /// <para>The node.</para>
61    /// <para></para>
62    /// </param>
63    /// <returns>
64    /// <para>The ref ulong</para>
65    /// <para></para>
66    /// </returns>
67    [MethodImpl(MethodImplOptions.AggressiveInlining)]
68    protected override ref ulong GetRightReference(ulong node) => ref
    ↪ Links[node].RightAsSource;
69
70    /// <summary>
71    /// <para>
72    /// Gets the left using the specified node.
73    /// </para>
74    /// <para></para>
75    /// </summary>
76    /// <param name="node">
77    /// <para>The node.</para>
78    /// <para></para>
79    /// </param>
80    /// <returns>
81    /// <para>The ulong</para>
82    /// <para></para>
83    /// </returns>
84    [MethodImpl(MethodImplOptions.AggressiveInlining)]
85    protected override ulong GetLeft(ulong node) => Links[node].LeftAsSource;
86
87    /// <summary>
88    /// <para>
89    /// Gets the right using the specified node.
90    /// </para>
91    /// <para></para>
92    /// </summary>
93    /// <param name="node">

```

```

94    /// <para>The node.</para>
95    /// <para></para>
96    /// </param>
97    /// <returns>
98    /// <para>The ulong</para>
99    /// <para></para>
100   /// </returns>
101   [MethodImpl(MethodImplOptions.AggressiveInlining)]
102   protected override ulong GetRight(ulong node) => Links[node].RightAsSource;
103
104   /// <summary>
105   /// <para>
106   /// Sets the left using the specified node.
107   /// </para>
108   /// <para></para>
109   /// </summary>
110   /// <param name="node">
111   /// <para>The node.</para>
112   /// <para></para>
113   /// </param>
114   /// <param name="left">
115   /// <para>The left.</para>
116   /// <para></para>
117   /// </param>
118   [MethodImpl(MethodImplOptions.AggressiveInlining)]
119   protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsSource =
    ↪ left;
120
121   /// <summary>
122   /// <para>
123   /// Sets the right using the specified node.
124   /// </para>
125   /// <para></para>
126   /// </summary>
127   /// <param name="node">
128   /// <para>The node.</para>
129   /// <para></para>
130   /// </param>
131   /// <param name="right">
132   /// <para>The right.</para>
133   /// <para></para>
134   /// </param>
135   [MethodImpl(MethodImplOptions.AggressiveInlining)]
136   protected override void SetRight(ulong node, ulong right) => Links[node].RightAsSource =
    ↪ right;
137
138   /// <summary>
139   /// <para>
140   /// Gets the size using the specified node.
141   /// </para>
142   /// <para></para>
143   /// </summary>
144   /// <param name="node">
145   /// <para>The node.</para>
146   /// <para></para>
147   /// </param>
148   /// <returns>
149   /// <para>The ulong</para>
150   /// <para></para>
151   /// </returns>
152   [MethodImpl(MethodImplOptions.AggressiveInlining)]
153   protected override ulong GetSize(ulong node) => Links[node].SizeAsSource;
154
155   /// <summary>
156   /// <para>
157   /// Sets the size using the specified node.
158   /// </para>
159   /// <para></para>
160   /// </summary>
161   /// <param name="node">
162   /// <para>The node.</para>
163   /// <para></para>
164   /// </param>
165   /// <param name="size">
166   /// <para>The size.</para>
167   /// <para></para>
168   /// </param>
169   [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

170     protected override void SetSize(ulong node, ulong size) => Links[node].SizeAsSource =
171         ↳ size;
172
173     /// <summary>
174     /// <para>
175     /// Gets the tree root.
176     /// </para>
177     /// <para></para>
178     /// </summary>
179     /// <returns>
180     /// <para>The ulong</para>
181     /// <para></para>
182     /// </returns>
183     [MethodImpl(MethodImplOptions.AggressiveInlining)]
184     protected override ulong GetTreeRoot() => Header->RootAsSource;
185
186     /// <summary>
187     /// <para>
188     /// Gets the base part value using the specified link.
189     /// </para>
190     /// <para></para>
191     /// </summary>
192     /// <param name="link">
193     /// <para>The link.</para>
194     /// <para></para>
195     /// </param>
196     /// <returns>
197     /// <para>The ulong</para>
198     /// <para></para>
199     /// </returns>
200     [MethodImpl(MethodImplOptions.AggressiveInlining)]
201     protected override ulong GetBasePartValue(ulong link) => Links[link].Source;
202
203     /// <summary>
204     /// <para>
205     /// Determines whether this instance first is to the left of second.
206     /// </para>
207     /// <para></para>
208     /// </summary>
209     /// <param name="firstSource">
210     /// <para>The first source.</para>
211     /// <para></para>
212     /// </param>
213     /// <param name="firstTarget">
214     /// <para>The first target.</para>
215     /// <para></para>
216     /// </param>
217     /// <param name="secondSource">
218     /// <para>The second source.</para>
219     /// <para></para>
220     /// </param>
221     /// <param name="secondTarget">
222     /// <para>The second target.</para>
223     /// <para></para>
224     /// </param>
225     /// <returns>
226     /// <para>The bool</para>
227     /// <para></para>
228     /// </returns>
229     [MethodImpl(MethodImplOptions.AggressiveInlining)]
230     protected override bool FirstIsToLeftOfSecond(ulong firstSource, ulong firstTarget,
231         ↳ ulong secondSource, ulong secondTarget)
232         => firstSource < secondSource || (firstSource == secondSource && firstTarget <
233             ↳ secondTarget);
234
235     /// <summary>
236     /// <para>
237     /// Determines whether this instance first is to the right of second.
238     /// </para>
239     /// <para></para>
240     /// </summary>
241     /// <param name="firstSource">
242     /// <para>The first source.</para>
243     /// <para></para>
244     /// </param>
245     /// <param name="firstTarget">
246     /// <para>The first target.</para>
247     /// <para></para>
248     /// </param>
249     /// <param name="secondSource">
250     /// <para>The second source.</para>
251     /// <para></para>
252     /// </param>
253     /// <param name="secondTarget">
254     /// <para>The second target.</para>
255     /// <para></para>
256     /// </param>
257     /// <returns>
258     /// <para>The bool</para>
259     /// <para></para>
260     /// </returns>
261     [MethodImpl(MethodImplOptions.AggressiveInlining)]
262     protected override bool FirstIsToRightOfSecond(ulong firstSource, ulong firstTarget,
263         ↳ ulong secondSource, ulong secondTarget)
264         => firstSource > secondSource || (firstSource == secondSource && firstTarget >
265             ↳ secondTarget);

```

```

/// </param>
/// <param name="secondSource">
/// <para>The second source.</para>
/// <para></para>
/// </param>
/// <param name="secondTarget">
/// <para>The second target.</para>
/// <para></para>
/// </param>
/// <returns>
/// <para>The bool</para>
/// <para></para>
/// </returns>
[MethodImpl(MethodImplOptions.AggressiveInlining)]
protected override bool FirstIsToTheRightOfSecond(ulong firstSource, ulong firstTarget,
    ↪   ulong secondSource, ulong secondTarget)
    ⇒ firstSource > secondSource || (firstSource == secondSource && firstTarget >
    ↪   secondTarget);

/// <summary>
/// <para>
/// Clears the node using the specified node.
/// </para>
/// <para></para>
/// </summary>
/// <param name="node">
/// <para>The node.</para>
/// <para></para>
/// </param>
[MethodImpl(MethodImplOptions.AggressiveInlining)]
protected override void ClearNode(ulong node)
{
    ref var link = ref Links[node];
    link.LeftAsSource = OUL;
    link.RightAsSource = OUL;
    link.SizeAsSource = OUL;
}

```

1.106 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksSourcesSizeBalancedTreeMethods.c

```

1 using System.Runtime.CompilerServices;
2
3 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5 namespace Platform.Data.Doublets.Memory.United.Specific
6 {
7     /// <summary>
8     /// <para>
9     /// Represents the int 64 links sources size balanced tree methods.
10    /// </para>
11    /// <para></para>
12    /// </summary>
13    /// <seealso cref="UInt64LinksSizeBalancedTreeMethodsBase"/>
14    public unsafe class UInt64LinksSourcesSizeBalancedTreeMethods :
15        ↳ UInt64LinksSizeBalancedTreeMethodsBase
16    {
17        /// <summary>
18        /// <para>
19        /// Initializes a new <see cref="UInt64LinksSourcesSizeBalancedTreeMethods"/> instance.
20        /// <para></para>
21        /// </summary>
22        /// <param name="constants">
23        /// <para>A constants.</para>
24        /// <para></para>
25        /// </param>
26        /// <param name="links">
27        /// <para>A links.</para>
28        /// <para></para>
29        /// </param>
30        /// <param name="header">
31        /// <para>A header.</para>
32        /// <para></para>
33        /// </param>
34        public UInt64LinksSourcesSizeBalancedTreeMethods(LinksConstants<ulong> constants,
35            ↳ RawLink<ulong>* links, LinksHeader<ulong>* header) : base(constants, links, header)
36        {
37        }
38    }
39 }

```



```

35
36    /// <summary>
37    /// <para>
38    /// Gets the left reference using the specified node.
39    /// </para>
40    /// <para></para>
41    /// </summary>
42    /// <param name="node">
43    /// <para>The node.</para>
44    /// <para></para>
45    /// </param>
46    /// <returns>
47    /// <para>The ref ulong</para>
48    /// <para></para>
49    /// </returns>
50    [MethodImpl(MethodImplOptions.AggressiveInlining)]
51    protected override ref ulong GetLeftReference(ulong node) => ref
    ↳ Links[node].LeftAsSource;
52
53    /// <summary>
54    /// <para>
55    /// Gets the right reference using the specified node.
56    /// </para>
57    /// <para></para>
58    /// </summary>
59    /// <param name="node">
60    /// <para>The node.</para>
61    /// <para></para>
62    /// </param>
63    /// <returns>
64    /// <para>The ref ulong</para>
65    /// <para></para>
66    /// </returns>
67    [MethodImpl(MethodImplOptions.AggressiveInlining)]
68    protected override ref ulong GetRightReference(ulong node) => ref
    ↳ Links[node].RightAsSource;
69
70    /// <summary>
71    /// <para>
72    /// Gets the left using the specified node.
73    /// </para>
74    /// <para></para>
75    /// </summary>
76    /// <param name="node">
77    /// <para>The node.</para>
78    /// <para></para>
79    /// </param>
80    /// <returns>
81    /// <para>The ulong</para>
82    /// <para></para>
83    /// </returns>
84    [MethodImpl(MethodImplOptions.AggressiveInlining)]
85    protected override ulong GetLeft(ulong node) => Links[node].LeftAsSource;
86
87    /// <summary>
88    /// <para>
89    /// Gets the right using the specified node.
90    /// </para>
91    /// <para></para>
92    /// </summary>
93    /// <param name="node">
94    /// <para>The node.</para>
95    /// <para></para>
96    /// </param>
97    /// <returns>
98    /// <para>The ulong</para>
99    /// <para></para>
100    /// </returns>
101    [MethodImpl(MethodImplOptions.AggressiveInlining)]
102    protected override ulong GetRight(ulong node) => Links[node].RightAsSource;
103
104    /// <summary>
105    /// <para>
106    /// Sets the left using the specified node.
107    /// </para>
108    /// <para></para>
109    /// </summary>
110    /// <param name="node">

```

```

111    /// <para>The node.</para>
112    /// <para></para>
113    /// </param>
114    /// <param name="left">
115    /// <para>The left.</para>
116    /// <para></para>
117    /// </param>
118    [MethodImpl(MethodImplOptions.AggressiveInlining)]
119    protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsSource =
    ↪ left;

120
121    /// <summary>
122    /// <para>
123    /// Sets the right using the specified node.
124    /// </para>
125    /// <para></para>
126    /// </summary>
127    /// <param name="node">
128    /// <para>The node.</para>
129    /// <para></para>
130    /// </param>
131    /// <param name="right">
132    /// <para>The right.</para>
133    /// <para></para>
134    /// </param>
135    [MethodImpl(MethodImplOptions.AggressiveInlining)]
136    protected override void SetRight(ulong node, ulong right) => Links[node].RightAsSource =
    ↪ right;

137
138    /// <summary>
139    /// <para>
140    /// Gets the size using the specified node.
141    /// </para>
142    /// <para></para>
143    /// </summary>
144    /// <param name="node">
145    /// <para>The node.</para>
146    /// <para></para>
147    /// </param>
148    /// <returns>
149    /// <para>The ulong</para>
150    /// <para></para>
151    /// </returns>
152    [MethodImpl(MethodImplOptions.AggressiveInlining)]
153    protected override ulong GetSize(ulong node) => Links[node].SizeAsSource;
154
155    /// <summary>
156    /// <para>
157    /// Sets the size using the specified node.
158    /// </para>
159    /// <para></para>
160    /// </summary>
161    /// <param name="node">
162    /// <para>The node.</para>
163    /// <para></para>
164    /// </param>
165    /// <param name="size">
166    /// <para>The size.</para>
167    /// <para></para>
168    /// </param>
169    [MethodImpl(MethodImplOptions.AggressiveInlining)]
170    protected override void SetSize(ulong node, ulong size) => Links[node].SizeAsSource =
    ↪ size;

171
172    /// <summary>
173    /// <para>
174    /// Gets the tree root.
175    /// </para>
176    /// <para></para>
177    /// </summary>
178    /// <returns>
179    /// <para>The ulong</para>
180    /// <para></para>
181    /// </returns>
182    [MethodImpl(MethodImplOptions.AggressiveInlining)]
183    protected override ulong GetTreeRoot() => Header->RootAsSource;
184
185    /// <summary>

```

```

/// <para>
/// Gets the base part value using the specified link.
/// </para>
/// <para></para>
/// </summary>
/// <param name="link">
/// <para>The link.</para>
/// <para></para>
/// </param>
/// <returns>
/// <para>The ulong</para>
/// <para></para>
/// </returns>
[MethodImpl(MethodImplOptions.AggressiveInlining)]
protected override ulong GetBasePartValue(ulong link) => Links[link].Source;

/// <summary>
/// <para>
/// Determines whether this instance first is to the left of second.
/// </para>
/// <para></para>
/// </summary>
/// <param name="firstSource">
/// <para>The first source.</para>
/// <para></para>
/// </param>
/// <param name="firstTarget">
/// <para>The first target.</para>
/// <para></para>
/// </param>
/// <param name="secondSource">
/// <para>The second source.</para>
/// <para></para>
/// </param>
/// <param name="secondTarget">
/// <para>The second target.</para>
/// <para></para>
/// </param>
/// <returns>
/// <para>The bool</para>
/// <para></para>
/// </returns>
[MethodImpl(MethodImplOptions.AggressiveInlining)]
protected override bool FirstIsToLeftOfSecond(ulong firstSource, ulong firstTarget,
↪   ulong secondSource, ulong secondTarget)
    => firstSource < secondSource || (firstSource == secondSource && firstTarget <
↪   secondTarget);

/// <summary>
/// <para>
/// Determines whether this instance first is to the right of second.
/// </para>
/// <para></para>
/// </summary>
/// <param name="firstSource">
/// <para>The first source.</para>
/// <para></para>
/// </param>
/// <param name="firstTarget">
/// <para>The first target.</para>
/// <para></para>
/// </param>
/// <param name="secondSource">
/// <para>The second source.</para>
/// <para></para>
/// </param>
/// <param name="secondTarget">
/// <para>The second target.</para>
/// <para></para>
/// </param>
/// <returns>
/// <para>The bool</para>
/// <para></para>
/// </returns>
[MethodImpl(MethodImplOptions.AggressiveInlining)]
protected override bool FirstIsToTheRightOfSecond(ulong firstSource, ulong firstTarget,
↪   ulong secondSource, ulong secondTarget)

```

```

260         => firstSource > secondSource || (firstSource == secondSource && firstTarget >
261             ↪ secondTarget);
262
263     /// <summary>
264     /// <para>
265     /// Clears the node using the specified node.
266     /// </para>
267     /// </summary>
268     /// <param name="node">
269     /// <para>The node.</para>
270     /// </param>
271     [MethodImpl(MethodImplOptions.AggressiveInlining)]
272     protected override void ClearNode(ulong node)
273     {
274         ref var link = ref Links[node];
275         link.LeftAsSource = OUL;
276         link.RightAsSource = OUL;
277         link.SizeAsSource = OUL;
278     }
279 }
280
281 }

```

1.107 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksTargetsAvlBalancedTreeMethods.cs

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.United.Specific
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the int 64 links targets avl balanced tree methods.
10     /// </para>
11     /// </summary>
12     /// <seealso cref="UInt64LinksAvlBalancedTreeMethodsBase"/>
13     public unsafe class UInt64LinksTargetsAvlBalancedTreeMethods :
14         ↪ UInt64LinksAvlBalancedTreeMethodsBase
15     {
16         /// <summary>
17         /// <para>
18         /// Initializes a new <see cref="UInt64LinksTargetsAvlBalancedTreeMethods"/> instance.
19         /// </para>
20         /// </summary>
21         /// <param name="constants">
22         /// <para>A constants.</para>
23         /// </param>
24         /// <param name="links">
25         /// <para>A links.</para>
26         /// </param>
27         /// <param name="header">
28         /// <para>A header.</para>
29         /// </param>
30         public UInt64LinksTargetsAvlBalancedTreeMethods(LinksConstants<ulong> constants,
31             ↪ RawLink<ulong>* links, LinksHeader<ulong>* header) : base(constants, links, header)
32         { }
33
34         /// <summary>
35         /// <para>
36         /// Gets the left reference using the specified node.
37         /// </para>
38         /// </summary>
39         /// <param name="node">
40         /// <para>The node.</para>
41         /// </param>
42         /// <returns>
43         /// <para>The ref ulong</para>
44         /// </returns>
45         [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

51     protected override ref ulong GetLeftReference(ulong node) => ref
    ↪     Links[node].LeftAsTarget;
52
53     /// <summary>
54     /// <para>
55     /// Gets the right reference using the specified node.
56     /// </para>
57     /// <para></para>
58     /// </summary>
59     /// <param name="node">
60     /// <para>The node.</para>
61     /// <para></para>
62     /// </param>
63     /// <returns>
64     /// <para>The ref ulong</para>
65     /// <para></para>
66     /// </returns>
67     [MethodImpl(MethodImplOptions.AggressiveInlining)]
68     protected override ref ulong GetRightReference(ulong node) => ref
    ↪     Links[node].RightAsTarget;
69
70     /// <summary>
71     /// <para>
72     /// Gets the left using the specified node.
73     /// </para>
74     /// <para></para>
75     /// </summary>
76     /// <param name="node">
77     /// <para>The node.</para>
78     /// <para></para>
79     /// </param>
80     /// <returns>
81     /// <para>The ulong</para>
82     /// <para></para>
83     /// </returns>
84     [MethodImpl(MethodImplOptions.AggressiveInlining)]
85     protected override ulong GetLeft(ulong node) => Links[node].LeftAsTarget;
86
87     /// <summary>
88     /// <para>
89     /// Gets the right using the specified node.
90     /// </para>
91     /// <para></para>
92     /// </summary>
93     /// <param name="node">
94     /// <para>The node.</para>
95     /// <para></para>
96     /// </param>
97     /// <returns>
98     /// <para>The ulong</para>
99     /// <para></para>
100    /// </returns>
101    [MethodImpl(MethodImplOptions.AggressiveInlining)]
102    protected override ulong GetRight(ulong node) => Links[node].RightAsTarget;
103
104    /// <summary>
105    /// <para>
106    /// Sets the left using the specified node.
107    /// </para>
108    /// <para></para>
109    /// </summary>
110    /// <param name="node">
111    /// <para>The node.</para>
112    /// <para></para>
113    /// </param>
114    /// <param name="left">
115    /// <para>The left.</para>
116    /// <para></para>
117    /// </param>
118    [MethodImpl(MethodImplOptions.AggressiveInlining)]
119    protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsTarget =
    ↪     left;
120
121    /// <summary>
122    /// <para>
123    /// Sets the right using the specified node.
124    /// </para>
125    /// <para></para>

```

```

126     /// </summary>
127     /// <param name="node">
128     /// <para>The node.</para>
129     /// <para></para>
130     /// </param>
131     /// <param name="right">
132     /// <para>The right.</para>
133     /// <para></para>
134     /// </param>
135     [MethodImpl(MethodImplOptions.AggressiveInlining)]
136     protected override void SetRight(ulong node, ulong right) => Links[node].RightAsTarget =
        ↳ right;

137     /// <summary>
138     /// <para>
139     /// Gets the size using the specified node.
140     /// </para>
141     /// <para></para>
142     /// </summary>
143     /// <param name="node">
144     /// <para>The node.</para>
145     /// <para></para>
146     /// </param>
147     /// <returns>
148     /// <para>The ulong</para>
149     /// <para></para>
150     /// </returns>
151     [MethodImpl(MethodImplOptions.AggressiveInlining)]
152     protected override ulong GetSize(ulong node) => GetSizeValue(Links[node].SizeAsTarget);

153     /// <summary>
154     /// <para>
155     /// Sets the size using the specified node.
156     /// </para>
157     /// <para></para>
158     /// </summary>
159     /// <param name="node">
160     /// <para>The node.</para>
161     /// <para></para>
162     /// </param>
163     /// <param name="size">
164     /// <para>The size.</para>
165     /// <para></para>
166     /// </param>
167     [MethodImpl(MethodImplOptions.AggressiveInlining)]
168     protected override void SetSize(ulong node, ulong size) => SetSizeValue(ref
        ↳ Links[node].SizeAsTarget, size);

171     /// <summary>
172     /// <para>
173     /// Determines whether this instance get left is child.
174     /// </para>
175     /// <para></para>
176     /// </summary>
177     /// <param name="node">
178     /// <para>The node.</para>
179     /// <para></para>
180     /// </param>
181     /// <returns>
182     /// <para>The bool</para>
183     /// <para></para>
184     /// </returns>
185     [MethodImpl(MethodImplOptions.AggressiveInlining)]
186     protected override bool GetLeftIsChild(ulong node) =>
        ↳ GetLeftIsChildValue(Links[node].SizeAsTarget);

188     /// <summary>
189     /// <para>
190     /// Sets the left is child using the specified node.
191     /// </para>
192     /// <para></para>
193     /// </summary>
194     /// <param name="node">
195     /// <para>The node.</para>
196     /// <para></para>
197     /// </param>
198     /// <param name="value">
199     /// <para>The value.</para>
200     /// <para></para>

```

```

201 /// <para></para>
202 /// </param>
203 [MethodImpl(MethodImplOptions.AggressiveInlining)]
204 protected override void SetLeftIsChild(ulong node, bool value) =>
205     ↪ SetLeftIsChildValue(ref Links[node].SizeAsTarget, value);
206
207 /// <summary>
208 /// <para>
209 /// Determines whether this instance get right is child.
210 /// </para>
211 /// </summary>
212 /// <param name="node">
213 /// <para>The node.</para>
214 /// </para>
215 /// </param>
216 /// <returns>
217 /// <para>The bool</para>
218 /// </returns>
219 [MethodImpl(MethodImplOptions.AggressiveInlining)]
220 protected override bool GetRightIsChild(ulong node) =>
221     ↪ GetRightIsChildValue(Links[node].SizeAsTarget);
222
223 /// <summary>
224 /// <para>
225 /// Sets the right is child using the specified node.
226 /// </para>
227 /// </summary>
228 /// <param name="node">
229 /// <para>The node.</para>
230 /// </para>
231 /// </param>
232 /// <param name="value">
233 /// <para>The value.</para>
234 /// </para>
235 /// </param>
236 [MethodImpl(MethodImplOptions.AggressiveInlining)]
237 protected override void SetRightIsChild(ulong node, bool value) =>
238     ↪ SetRightIsChildValue(ref Links[node].SizeAsTarget, value);
239
240 /// <summary>
241 /// <para>
242 /// Gets the balance using the specified node.
243 /// </para>
244 /// </summary>
245 /// <param name="node">
246 /// <para>The node.</para>
247 /// </para>
248 /// </param>
249 /// <returns>
250 /// <para>The sbyte</para>
251 /// </returns>
252 [MethodImpl(MethodImplOptions.AggressiveInlining)]
253 protected override sbyte GetBalance(ulong node) =>
254     ↪ GetBalanceValue(Links[node].SizeAsTarget);
255
256 /// <summary>
257 /// <para>
258 /// Sets the balance using the specified node.
259 /// </para>
260 /// </summary>
261 /// <param name="node">
262 /// <para>The node.</para>
263 /// </para>
264 /// </param>
265 /// <param name="value">
266 /// <para>The value.</para>
267 /// </para>
268 /// </param>
269 [MethodImpl(MethodImplOptions.AggressiveInlining)]
270 protected override void SetBalance(ulong node, sbyte value) => SetBalanceValue(ref
271     ↪ Links[node].SizeAsTarget, value);

```

```

273     /// <summary>
274     /// <para>
275     /// Gets the tree root.
276     /// </para>
277     /// <para></para>
278     /// </summary>
279     /// <returns>
280     /// <para>The ulong</para>
281     /// <para></para>
282     /// </returns>
283     [MethodImpl(MethodImplOptions.AggressiveInlining)]
284     protected override ulong GetTreeRoot() => Header->RootAsTarget;
285
286     /// <summary>
287     /// <para>
288     /// Gets the base part value using the specified link.
289     /// </para>
290     /// <para></para>
291     /// </summary>
292     /// <param name="link">
293     /// <para>The link.</para>
294     /// <para></para>
295     /// </param>
296     /// <returns>
297     /// <para>The ulong</para>
298     /// <para></para>
299     /// </returns>
300     [MethodImpl(MethodImplOptions.AggressiveInlining)]
301     protected override ulong GetBasePartValue(ulong link) => Links[link].Target;
302
303     /// <summary>
304     /// <para>
305     /// Determines whether this instance first is to the left of second.
306     /// </para>
307     /// <para></para>
308     /// </summary>
309     /// <param name="firstSource">
310     /// <para>The first source.</para>
311     /// <para></para>
312     /// </param>
313     /// <param name="firstTarget">
314     /// <para>The first target.</para>
315     /// <para></para>
316     /// </param>
317     /// <param name="secondSource">
318     /// <para>The second source.</para>
319     /// <para></para>
320     /// </param>
321     /// <param name="secondTarget">
322     /// <para>The second target.</para>
323     /// <para></para>
324     /// </param>
325     /// <returns>
326     /// <para>The bool</para>
327     /// <para></para>
328     /// </returns>
329     [MethodImpl(MethodImplOptions.AggressiveInlining)]
330     protected override bool FirstIsToTheLeftOfSecond(ulong firstSource, ulong firstTarget,
331     ↪     ulong secondSource, ulong secondTarget)
332     ↪     => firstTarget < secondTarget || (firstTarget == secondTarget && firstSource <
333     ↪     secondSource);
334
335     /// <summary>
336     /// <para>
337     /// Determines whether this instance first is to the right of second.
338     /// </para>
339     /// <para></para>
340     /// </summary>
341     /// <param name="firstSource">
342     /// <para>The first source.</para>
343     /// <para></para>
344     /// </param>
345     /// <param name="firstTarget">
346     /// <para>The first target.</para>
347     /// <para></para>
348     /// </param>
349     /// <param name="secondSource">

```



```

349     /// <para>The second source.</para>
350     /// <para></para>
351     /// </param>
352     /// <param name="secondTarget">
353     /// <para>The second target.</para>
354     /// <para></para>
355     /// </param>
356     /// <returns>
357     /// <para>The bool</para>
358     /// <para></para>
359     /// </returns>
360     [MethodImpl(MethodImplOptions.AggressiveInlining)]
361     protected override bool FirstIsToTheRightOfSecond(ulong firstSource, ulong firstTarget,
    ↪     ulong secondSource, ulong secondTarget)
362         => firstTarget > secondTarget || (firstTarget == secondTarget && firstSource >
    ↪     secondSource);
363
364     /// <summary>
365     /// <para>
366     /// Clears the node using the specified node.
367     /// </para>
368     /// <para></para>
369     /// </summary>
370     /// <param name="node">
371     /// <para>The node.</para>
372     /// <para></para>
373     /// </param>
374     [MethodImpl(MethodImplOptions.AggressiveInlining)]
375     protected override void ClearNode(ulong node)
376     {
377         ref var link = ref Links[node];
378         link.LeftAsTarget = OUL;
379         link.RightAsTarget = OUL;
380         link.SizeAsTarget = OUL;
381     }
382 }
383 }

```

1.108 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksTargetsRecursionlessSizeBalancedTreeMethodsBase

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.United.Specific
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the int 64 links targets recursionless size balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="UInt64LinksRecursionlessSizeBalancedTreeMethodsBase"/>
14     public unsafe class UInt64LinksTargetsRecursionlessSizeBalancedTreeMethods :
    ↪     UInt64LinksRecursionlessSizeBalancedTreeMethodsBase
15     {
16         /// <summary>
17         /// <para>
18         /// Initializes a new <see
    ↪     cref="UInt64LinksTargetsRecursionlessSizeBalancedTreeMethods"/> instance.
19         /// </para>
20         /// <para></para>
21         /// </summary>
22         /// <param name="constants">
23         /// <para>A constants.</para>
24         /// <para></para>
25         /// </param>
26         /// <param name="links">
27         /// <para>A links.</para>
28         /// <para></para>
29         /// </param>
30         /// <param name="header">
31         /// <para>A header.</para>
32         /// <para></para>
33         /// </param>
34         public UInt64LinksTargetsRecursionlessSizeBalancedTreeMethods(LinksConstants<ulong>
    ↪     constants, RawLink<ulong>* links, LinksHeader<ulong>* header) : base(constants,
    ↪     links, header) { }
35

```

```

36    /// <summary>
37    /// <para>
38    /// Gets the left reference using the specified node.
39    /// </para>
40    /// <para></para>
41    /// </summary>
42    /// <param name="node">
43    /// <para>The node.</para>
44    /// <para></para>
45    /// </param>
46    /// <returns>
47    /// <para>The ref ulong</para>
48    /// <para></para>
49    /// </returns>
50    [MethodImpl(MethodImplOptions.AggressiveInlining)]
51    protected override ref ulong GetLeftReference(ulong node) => ref
    ↪ Links[node].LeftAsTarget;
52
53    /// <summary>
54    /// <para>
55    /// Gets the right reference using the specified node.
56    /// </para>
57    /// <para></para>
58    /// </summary>
59    /// <param name="node">
60    /// <para>The node.</para>
61    /// <para></para>
62    /// </param>
63    /// <returns>
64    /// <para>The ref ulong</para>
65    /// <para></para>
66    /// </returns>
67    [MethodImpl(MethodImplOptions.AggressiveInlining)]
68    protected override ref ulong GetRightReference(ulong node) => ref
    ↪ Links[node].RightAsTarget;
69
70    /// <summary>
71    /// <para>
72    /// Gets the left using the specified node.
73    /// </para>
74    /// <para></para>
75    /// </summary>
76    /// <param name="node">
77    /// <para>The node.</para>
78    /// <para></para>
79    /// </param>
80    /// <returns>
81    /// <para>The ulong</para>
82    /// <para></para>
83    /// </returns>
84    [MethodImpl(MethodImplOptions.AggressiveInlining)]
85    protected override ulong GetLeft(ulong node) => Links[node].LeftAsTarget;
86
87    /// <summary>
88    /// <para>
89    /// Gets the right using the specified node.
90    /// </para>
91    /// <para></para>
92    /// </summary>
93    /// <param name="node">
94    /// <para>The node.</para>
95    /// <para></para>
96    /// </param>
97    /// <returns>
98    /// <para>The ulong</para>
99    /// <para></para>
100    /// </returns>
101    [MethodImpl(MethodImplOptions.AggressiveInlining)]
102    protected override ulong GetRight(ulong node) => Links[node].RightAsTarget;
103
104    /// <summary>
105    /// <para>
106    /// Sets the left using the specified node.
107    /// </para>
108    /// <para></para>
109    /// </summary>
110    /// <param name="node">
111    /// <para>The node.</para>

```

```

112     /// <para></para>
113     /// </param>
114     /// <param name="left">
115     /// <para>The left.</para>
116     /// <para></para>
117     /// </param>
118     [MethodImpl(MethodImplOptions.AggressiveInlining)]
119     protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsTarget =
        ↳ left;
120
121     /// <summary>
122     /// <para>
123     /// Sets the right using the specified node.
124     /// </para>
125     /// <para></para>
126     /// </summary>
127     /// <param name="node">
128     /// <para>The node.</para>
129     /// <para></para>
130     /// </param>
131     /// <param name="right">
132     /// <para>The right.</para>
133     /// <para></para>
134     /// </param>
135     [MethodImpl(MethodImplOptions.AggressiveInlining)]
136     protected override void SetRight(ulong node, ulong right) => Links[node].RightAsTarget =
        ↳ right;
137
138     /// <summary>
139     /// <para>
140     /// Gets the size using the specified node.
141     /// </para>
142     /// <para></para>
143     /// </summary>
144     /// <param name="node">
145     /// <para>The node.</para>
146     /// <para></para>
147     /// </param>
148     /// <returns>
149     /// <para>The ulong</para>
150     /// <para></para>
151     /// </returns>
152     [MethodImpl(MethodImplOptions.AggressiveInlining)]
153     protected override ulong GetSize(ulong node) => Links[node].SizeAsTarget;
154
155     /// <summary>
156     /// <para>
157     /// Sets the size using the specified node.
158     /// </para>
159     /// <para></para>
160     /// </summary>
161     /// <param name="node">
162     /// <para>The node.</para>
163     /// <para></para>
164     /// </param>
165     /// <param name="size">
166     /// <para>The size.</para>
167     /// <para></para>
168     /// </param>
169     [MethodImpl(MethodImplOptions.AggressiveInlining)]
170     protected override void SetSize(ulong node, ulong size) => Links[node].SizeAsTarget =
        ↳ size;
171
172     /// <summary>
173     /// <para>
174     /// Gets the tree root.
175     /// </para>
176     /// <para></para>
177     /// </summary>
178     /// <returns>
179     /// <para>The ulong</para>
180     /// <para></para>
181     /// </returns>
182     [MethodImpl(MethodImplOptions.AggressiveInlining)]
183     protected override ulong GetTreeRoot() => Header->RootAsTarget;
184
185     /// <summary>
186     /// <para>

```

```

187     /// Gets the base part value using the specified link.
188     /// </para>
189     /// <para></para>
190     /// </summary>
191     /// <param name="link">
192     /// <para>The link.</para>
193     /// <para></para>
194     /// </param>
195     /// <returns>
196     /// <para>The ulong</para>
197     /// <para></para>
198     /// </returns>
199     [MethodImpl(MethodImplOptions.AggressiveInlining)]
200     protected override ulong GetBasePartValue(ulong link) => Links[link].Target;
201
202     /// <summary>
203     /// <para>
204     /// Determines whether this instance first is to the left of second.
205     /// </para>
206     /// <para></para>
207     /// </summary>
208     /// <param name="firstSource">
209     /// <para>The first source.</para>
210     /// <para></para>
211     /// </param>
212     /// <param name="firstTarget">
213     /// <para>The first target.</para>
214     /// <para></para>
215     /// </param>
216     /// <param name="secondSource">
217     /// <para>The second source.</para>
218     /// <para></para>
219     /// </param>
220     /// <param name="secondTarget">
221     /// <para>The second target.</para>
222     /// <para></para>
223     /// </param>
224     /// <returns>
225     /// <para>The bool</para>
226     /// <para></para>
227     /// </returns>
228     [MethodImpl(MethodImplOptions.AggressiveInlining)]
229     protected override bool FirstIsToTheLeftOfSecond(ulong firstSource, ulong firstTarget,
230     ↪     ulong secondSource, ulong secondTarget)
231     => firstTarget < secondTarget || (firstTarget == secondTarget && firstSource <
232     ↪     secondSource);
233
234     /// <summary>
235     /// <para>
236     /// Determines whether this instance first is to the right of second.
237     /// </para>
238     /// <para></para>
239     /// </summary>
240     /// <param name="firstSource">
241     /// <para>The first source.</para>
242     /// <para></para>
243     /// </param>
244     /// <param name="firstTarget">
245     /// <para>The first target.</para>
246     /// <para></para>
247     /// </param>
248     /// <param name="secondSource">
249     /// <para>The second source.</para>
250     /// <para></para>
251     /// </param>
252     /// <param name="secondTarget">
253     /// <para>The second target.</para>
254     /// <para></para>
255     /// </param>
256     /// <returns>
257     /// <para>The bool</para>
258     /// <para></para>
259     /// </returns>
260     [MethodImpl(MethodImplOptions.AggressiveInlining)]
261     protected override bool FirstIsToTheRightOfSecond(ulong firstSource, ulong firstTarget,
262     ↪     ulong secondSource, ulong secondTarget)
263     => firstTarget > secondTarget || (firstTarget == secondTarget && firstSource >
264     ↪     secondSource);

```

```

261
262     /// <summary>
263     /// <para>
264     /// Clears the node using the specified node.
265     /// </para>
266     /// <para></para>
267     /// </summary>
268     /// <param name="node">
269     /// <para>The node.</para>
270     /// <para></para>
271     /// </param>
272     [MethodImpl(MethodImplOptions.AggressiveInlining)]
273     protected override void ClearNode(ulong node)
274     {
275         ref var link = ref Links[node];
276         link.LeftAsTarget = OUL;
277         link.RightAsTarget = OUL;
278         link.SizeAsTarget = OUL;
279     }
280 }
281 }

```

1.109 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksTargetsSizeBalancedTreeMethods.cs

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Memory.United.Specific
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the int 64 links targets size balanced tree methods.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     /// <seealso cref="UInt64LinksSizeBalancedTreeMethodsBase"/>
14     public unsafe class UInt64LinksTargetsSizeBalancedTreeMethods :
15         ↳ UInt64LinksSizeBalancedTreeMethodsBase
16     {
17         /// <summary>
18         /// <para>
19         /// Initializes a new <see cref="UInt64LinksTargetsSizeBalancedTreeMethods"/> instance.
20         /// </para>
21         /// <para></para>
22         /// </summary>
23         /// <param name="constants">
24         /// <para>A constants.</para>
25         /// <para></para>
26         /// </param>
27         /// <param name="links">
28         /// <para>A links.</para>
29         /// <para></para>
30         /// </param>
31         /// <param name="header">
32         /// <para>A header.</para>
33         /// <para></para>
34         /// </param>
35         public UInt64LinksTargetsSizeBalancedTreeMethods(LinksConstants<ulong> constants,
36             ↳ RawLink<ulong>* links, LinksHeader<ulong>* header) : base(constants, links, header)
37             ↳ { }
38
39         /// <summary>
40         /// <para>
41         /// Gets the left reference using the specified node.
42         /// </para>
43         /// <para></para>
44         /// </summary>
45         /// <param name="node">
46         /// <para>The node.</para>
47         /// <para></para>
48         /// </param>
49         /// <returns>
50         /// <para>The ref ulong</para>
51         /// <para></para>
52         /// </returns>
53         [MethodImpl(MethodImplOptions.AggressiveInlining)]
54         protected override ref ulong GetLeftReference(ulong node) => ref
55             ↳ Links[node].LeftAsTarget;

```

```

52
53     /// <summary>
54     /// <para>
55     /// Gets the right reference using the specified node.
56     /// </para>
57     /// <para></para>
58     /// </summary>
59     /// <param name="node">
60     /// <para>The node.</para>
61     /// <para></para>
62     /// </param>
63     /// <returns>
64     /// <para>The ref ulong</para>
65     /// <para></para>
66     /// </returns>
67     [MethodImpl(MethodImplOptions.AggressiveInlining)]
68     protected override ref ulong GetRightReference(ulong node) => ref
        ↳ Links[node].RightAsTarget;
69
70     /// <summary>
71     /// <para>
72     /// Gets the left using the specified node.
73     /// </para>
74     /// <para></para>
75     /// </summary>
76     /// <param name="node">
77     /// <para>The node.</para>
78     /// <para></para>
79     /// </param>
80     /// <returns>
81     /// <para>The ulong</para>
82     /// <para></para>
83     /// </returns>
84     [MethodImpl(MethodImplOptions.AggressiveInlining)]
85     protected override ulong GetLeft(ulong node) => Links[node].LeftAsTarget;
86
87     /// <summary>
88     /// <para>
89     /// Gets the right using the specified node.
90     /// </para>
91     /// <para></para>
92     /// </summary>
93     /// <param name="node">
94     /// <para>The node.</para>
95     /// <para></para>
96     /// </param>
97     /// <returns>
98     /// <para>The ulong</para>
99     /// <para></para>
100    /// </returns>
101    [MethodImpl(MethodImplOptions.AggressiveInlining)]
102    protected override ulong GetRight(ulong node) => Links[node].RightAsTarget;
103
104    /// <summary>
105    /// <para>
106    /// Sets the left using the specified node.
107    /// </para>
108    /// <para></para>
109    /// </summary>
110    /// <param name="node">
111    /// <para>The node.</para>
112    /// <para></para>
113    /// </param>
114    /// <param name="left">
115    /// <para>The left.</para>
116    /// <para></para>
117    /// </param>
118    [MethodImpl(MethodImplOptions.AggressiveInlining)]
119    protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsTarget =
        ↳ left;
120
121    /// <summary>
122    /// <para>
123    /// Sets the right using the specified node.
124    /// </para>
125    /// <para></para>
126    /// </summary>
127    /// <param name="node">

```

```

128     /// <para>The node.</para>
129     /// <para></para>
130     /// </param>
131     /// <param name="right">
132     /// <para>The right.</para>
133     /// <para></para>
134     /// </param>
135     [MethodImpl(MethodImplOptions.AggressiveInlining)]
136     protected override void SetRight(ulong node, ulong right) => Links[node].RightAsTarget =
        ↪ right;

137
138     /// <summary>
139     /// <para>
140     /// Gets the size using the specified node.
141     /// </para>
142     /// <para></para>
143     /// </summary>
144     /// <param name="node">
145     /// <para>The node.</para>
146     /// <para></para>
147     /// </param>
148     /// <returns>
149     /// <para>The ulong</para>
150     /// <para></para>
151     /// </returns>
152     [MethodImpl(MethodImplOptions.AggressiveInlining)]
153     protected override ulong GetSize(ulong node) => Links[node].SizeAsTarget;
154
155     /// <summary>
156     /// <para>
157     /// Sets the size using the specified node.
158     /// </para>
159     /// <para></para>
160     /// </summary>
161     /// <param name="node">
162     /// <para>The node.</para>
163     /// <para></para>
164     /// </param>
165     /// <param name="size">
166     /// <para>The size.</para>
167     /// <para></para>
168     /// </param>
169     [MethodImpl(MethodImplOptions.AggressiveInlining)]
170     protected override void SetSize(ulong node, ulong size) => Links[node].SizeAsTarget =
        ↪ size;

171
172     /// <summary>
173     /// <para>
174     /// Gets the tree root.
175     /// </para>
176     /// <para></para>
177     /// </summary>
178     /// <returns>
179     /// <para>The ulong</para>
180     /// <para></para>
181     /// </returns>
182     [MethodImpl(MethodImplOptions.AggressiveInlining)]
183     protected override ulong GetTreeRoot() => Header->RootAsTarget;
184
185     /// <summary>
186     /// <para>
187     /// Gets the base part value using the specified link.
188     /// </para>
189     /// <para></para>
190     /// </summary>
191     /// <param name="link">
192     /// <para>The link.</para>
193     /// <para></para>
194     /// </param>
195     /// <returns>
196     /// <para>The ulong</para>
197     /// <para></para>
198     /// </returns>
199     [MethodImpl(MethodImplOptions.AggressiveInlining)]
200     protected override ulong GetBasePartValue(ulong link) => Links[link].Target;
201
202     /// <summary>
203     /// <para>

```

```

    /// Determines whether this instance first is to the left of second.
    /// </para>
    /// <para></para>
    /// </summary>
    /// <param name="firstSource">
    /// <para>The first source.</para>
    /// <para></para>
    /// </param>
    /// <param name="firstTarget">
    /// <para>The first target.</para>
    /// <para></para>
    /// </param>
    /// <param name="secondSource">
    /// <para>The second source.</para>
    /// <para></para>
    /// </param>
    /// <param name="secondTarget">
    /// <para>The second target.</para>
    /// <para></para>
    /// </param>
    /// <returns>
    /// <para>The bool</para>
    /// <para></para>
    /// </returns>
    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    protected override bool FirstIsToLeftOfSecond(ulong firstSource, ulong firstTarget,
        ↪ ulong secondSource, ulong secondTarget)
        => firstTarget < secondTarget || (firstTarget == secondTarget && firstSource <
            ↪ secondSource);

    /// <summary>
    /// <para>
    /// Determines whether this instance first is to the right of second.
    /// </para>
    /// <para></para>
    /// </summary>
    /// <param name="firstSource">
    /// <para>The first source.</para>
    /// <para></para>
    /// </param>
    /// <param name="firstTarget">
    /// <para>The first target.</para>
    /// <para></para>
    /// </param>
    /// <param name="secondSource">
    /// <para>The second source.</para>
    /// <para></para>
    /// </param>
    /// <param name="secondTarget">
    /// <para>The second target.</para>
    /// <para></para>
    /// </param>
    /// <returns>
    /// <para>The bool</para>
    /// <para></para>
    /// </returns>
    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    protected override bool FirstIsToTheRightOfSecond(ulong firstSource, ulong firstTarget,
        ↪ ulong secondSource, ulong secondTarget)
        => firstTarget > secondTarget || (firstTarget == secondTarget && firstSource >
            ↪ secondSource);

    /// <summary>
    /// <para>
    /// Clears the node using the specified node.
    /// </para>
    /// <para></para>
    /// </summary>
    /// <param name="node">
    /// <para>The node.</para>
    /// <para></para>
    /// </param>
    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    protected override void ClearNode(ulong node)
    {
        ref var link = ref Links[node];
        link.LeftAsTarget = OUL;
        link.RightAsTarget = OUL;
    }

```



```

278         link.SizeAsTarget = OUL;
279     }
280 }
281 }

```

1.110 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64UnitedMemoryLinks.cs

```

1  using System;
2  using System.Runtime.CompilerServices;
3  using Platform.Memory;
4  using Platform.Singletons;
5  using Platform.Data.Doublets.Memory.United.Generic;
6
7  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
8
9  namespace Platform.Data.Doublets.Memory.United.Specific
10 {
11     /// <summary>
12     /// <para>Represents a low-level implementation of direct access to resizable memory, for
13     ///     organizing the storage of links with addresses represented as <see cref="ulong">
14     ///     </para>
15     /// <para>Представляет низкоуровневую реализация прямого доступа к памяти с переменным
16     ///     размером, для организации хранения связей с адресами представленными в виде <see
17     ///     cref="ulong"> </para>
18     /// </summary>
19     public unsafe class UInt64UnitedMemoryLinks : UnitedMemoryLinksBase<ulong>
20     {
21         private readonly Func<ILinksTreeMethods<ulong>> _createSourceTreeMethods;
22         private readonly Func<ILinksTreeMethods<ulong>> _createTargetTreeMethods;
23         private LinksHeader<ulong>* _header;
24         private RawLink<ulong>* _links;
25
26         /// <summary>
27         /// <para>
28         ///     Initializes a new <see cref="UInt64UnitedMemoryLinks"/> instance.
29         /// </para>
30         /// <para></para>
31         /// </summary>
32         /// <param name="address">
33         /// <para>A address.</para>
34         /// <para></para>
35         /// </param>
36         [MethodImpl(MethodImplOptions.AggressiveInlining)]
37         public UInt64UnitedMemoryLinks(string address) : this(address, DefaultLinksSizeStep) { }
38
39         /// <summary>
40         /// <para>Создаёт экземпляр базы данных Links в файле по указанному адресу, с указанным
41         ///     минимальным шагом расширения базы данных.
42         /// </para>
43         /// </summary>
44         /// <param name="address">Полный путь к файлу базы данных.</param>
45         /// <param name="memoryReservationStep">Минимальный шаг расширения базы данных в
46         ///     байтах.</param>
47         [MethodImpl(MethodImplOptions.AggressiveInlining)]
48         public UInt64UnitedMemoryLinks(string address, long memoryReservationStep) : this(new
49         FileMappedResizableDirectMemory(address, memoryReservationStep),
50         memoryReservationStep) { }
51
52         /// <summary>
53         /// <para>
54         ///     Initializes a new <see cref="UInt64UnitedMemoryLinks"/> instance.
55         /// </para>
56         /// <para></para>
57         /// </summary>
58         /// <param name="memory">
59         /// <para>A memory.</para>
60         /// <para></para>
61         /// </param>
62         [MethodImpl(MethodImplOptions.AggressiveInlining)]
63         public UInt64UnitedMemoryLinks(IResizableDirectMemory memory) : this(memory,
64         DefaultLinksSizeStep) { }
65
66         /// <summary>
67         /// <para>
68         ///     Initializes a new <see cref="UInt64UnitedMemoryLinks"/> instance.
69         /// </para>
70         /// <para></para>
71         /// </summary>
72         /// <param name="memory">
73         /// <para>A memory.</para>
74         /// <para></para>
75         /// </param>

```

```

65     /// </param>
66     /// <param name="memoryReservationStep">
67     /// <para>A memory reservation step.</para>
68     /// <para></para>
69     /// </param>
70     [MethodImpl(MethodImplOptions.AggressiveInlining)]
71     public UInt64UnitedMemoryLinks(IResizableDirectMemory memory, long
        ↳ memoryReservationStep) : this(memory, memoryReservationStep,
        ↳ Default<LinksConstants<ulong>>.Instance, IndexTreeType.Default) { }

72
73     /// <summary>
74     /// <para>
75     /// Initializes a new <see cref="UInt64UnitedMemoryLinks"/> instance.
76     /// </para>
77     /// <para></para>
78     /// </summary>
79     /// <param name="memory">
80     /// <para>A memory.</para>
81     /// <para></para>
82     /// </param>
83     /// <param name="memoryReservationStep">
84     /// <para>A memory reservation step.</para>
85     /// <para></para>
86     /// </param>
87     /// <param name="constants">
88     /// <para>A constants.</para>
89     /// <para></para>
90     /// </param>
91     /// <param name="indexTreeType">
92     /// <para>A index tree type.</para>
93     /// <para></para>
94     /// </param>
95     [MethodImpl(MethodImplOptions.AggressiveInlining)]
96     public UInt64UnitedMemoryLinks(IResizableDirectMemory memory, long
        ↳ memoryReservationStep, LinksConstants<ulong> constants, IndexTreeType indexTreeType)
        ↳ : base(memory, memoryReservationStep, constants)
97     {
98         if (indexTreeType == IndexTreeType.SizedAndThreadedAVLBalancedTree)
99         {
100             _createSourceTreeMethods = () => new
                ↳ UInt64LinksSourcesAvlBalancedTreeMethods(Constants, _links, _header);
101             _createTargetTreeMethods = () => new
                ↳ UInt64LinksTargetsAvlBalancedTreeMethods(Constants, _links, _header);
102         }
103         else if (indexTreeType == IndexTreeType.SizeBalancedTree)
104         {
105             _createSourceTreeMethods = () => new
                ↳ UInt64LinksSourcesSizeBalancedTreeMethods(Constants, _links, _header);
106             _createTargetTreeMethods = () => new
                ↳ UInt64LinksTargetsSizeBalancedTreeMethods(Constants, _links, _header);
107         }
108         else
109         {
110             _createSourceTreeMethods = () => new
                ↳ UInt64LinksSourcesRecursionlessSizeBalancedTreeMethods(Constants, _links,
                ↳ _header);
111             _createTargetTreeMethods = () => new
                ↳ UInt64LinksTargetsRecursionlessSizeBalancedTreeMethods(Constants, _links,
                ↳ _header);
112         }
113         Init(memory, memoryReservationStep);
114     }
115
116     /// <summary>
117     /// <para>
118     /// Sets the pointers using the specified memory.
119     /// </para>
120     /// <para></para>
121     /// </summary>
122     /// <param name="memory">
123     /// <para>The memory.</para>
124     /// <para></para>
125     /// </param>
126     [MethodImpl(MethodImplOptions.AggressiveInlining)]
127     protected override void SetPointers(IResizableDirectMemory memory)
128     {
129         _header = (LinksHeader<ulong>*)memory.Pointer;

```

```

130     _links = (RawLink<ulong>*)memory.Pointer;
131     SourcesTreeMethods = _createSourceTreeMethods();
132     TargetsTreeMethods = _createTargetTreeMethods();
133     UnusedLinksListMethods = new UInt64UnusedLinksListMethods(_links, _header);
134 }
135
136 /// <summary>
137 /// <para>
138 /// Resets the pointers.
139 /// </para>
140 /// <para></para>
141 /// </summary>
142 [MethodImpl(MethodImplOptions.AggressiveInlining)]
143 protected override void ResetPointers()
144 {
145     base.ResetPointers();
146     _links = null;
147     _header = null;
148 }
149
150 /// <summary>
151 /// <para>
152 /// Gets the header reference.
153 /// </para>
154 /// <para></para>
155 /// </summary>
156 /// <returns>
157 /// <para>A ref links header of ulong</para>
158 /// <para></para>
159 /// </returns>
160 [MethodImpl(MethodImplOptions.AggressiveInlining)]
161 protected override ref LinksHeader<ulong> GetHeaderReference() => ref *_header;
162
163 /// <summary>
164 /// <para>
165 /// Gets the link reference using the specified link index.
166 /// </para>
167 /// <para></para>
168 /// </summary>
169 /// <param name="linkIndex">
170 /// <para>The link index.</para>
171 /// <para></para>
172 /// </param>
173 /// <returns>
174 /// <para>A ref raw link of ulong</para>
175 /// <para></para>
176 /// </returns>
177 [MethodImpl(MethodImplOptions.AggressiveInlining)]
178 protected override ref RawLink<ulong> GetLinkReference(ulong linkIndex) => ref
179     ↪ _links[linkIndex];
180
181 /// <summary>
182 /// <para>
183 /// Determines whether this instance are equal.
184 /// </para>
185 /// <para></para>
186 /// </summary>
187 /// <param name="first">
188 /// <para>The first.</para>
189 /// <para></para>
190 /// </param>
191 /// <param name="second">
192 /// <para>The second.</para>
193 /// <para></para>
194 /// </param>
195 /// <returns>
196 /// <para>The bool</para>
197 /// <para></para>
198 /// </returns>
199 [MethodImpl(MethodImplOptions.AggressiveInlining)]
200 protected override bool AreEqual(ulong first, ulong second) => first == second;
201
202 /// <summary>
203 /// <para>
204 /// Determines whether this instance less than.
205 /// </para>
206 /// <para></para>
207 /// </summary>

```

```

207     /// <param name="first">
208     /// <para>The first.</para>
209     /// <para></para>
210     /// </param>
211     /// <param name="second">
212     /// <para>The second.</para>
213     /// <para></para>
214     /// </param>
215     /// <returns>
216     /// <para>The bool</para>
217     /// <para></para>
218     /// </returns>
219     [MethodImpl(MethodImplOptions.AggressiveInlining)]
220     protected override bool LessThan(ulong first, ulong second) => first < second;
221
222     /// <summary>
223     /// <para>
224     /// Determines whether this instance less or equal than.
225     /// </para>
226     /// <para></para>
227     /// </summary>
228     /// <param name="first">
229     /// <para>The first.</para>
230     /// <para></para>
231     /// </param>
232     /// <param name="second">
233     /// <para>The second.</para>
234     /// <para></para>
235     /// </param>
236     /// <returns>
237     /// <para>The bool</para>
238     /// <para></para>
239     /// </returns>
240     [MethodImpl(MethodImplOptions.AggressiveInlining)]
241     protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;
242
243     /// <summary>
244     /// <para>
245     /// Determines whether this instance greater than.
246     /// </para>
247     /// <para></para>
248     /// </summary>
249     /// <param name="first">
250     /// <para>The first.</para>
251     /// <para></para>
252     /// </param>
253     /// <param name="second">
254     /// <para>The second.</para>
255     /// <para></para>
256     /// </param>
257     /// <returns>
258     /// <para>The bool</para>
259     /// <para></para>
260     /// </returns>
261     [MethodImpl(MethodImplOptions.AggressiveInlining)]
262     protected override bool GreaterThan(ulong first, ulong second) => first > second;
263
264     /// <summary>
265     /// <para>
266     /// Determines whether this instance greater or equal than.
267     /// </para>
268     /// <para></para>
269     /// </summary>
270     /// <param name="first">
271     /// <para>The first.</para>
272     /// <para></para>
273     /// </param>
274     /// <param name="second">
275     /// <para>The second.</para>
276     /// <para></para>
277     /// </param>
278     /// <returns>
279     /// <para>The bool</para>
280     /// <para></para>
281     /// </returns>
282     [MethodImpl(MethodImplOptions.AggressiveInlining)]
283     protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;
284

```

```

285     /// <summary>
286     /// <para>
287     /// Gets the zero.
288     /// </para>
289     /// <para></para>
290     /// </summary>
291     /// <returns>
292     /// <para>The ulong</para>
293     /// <para></para>
294     /// </returns>
295     [MethodImpl(MethodImplOptions.AggressiveInlining)]
296     protected override ulong GetZero() => 0UL;
297
298     /// <summary>
299     /// <para>
300     /// Gets the one.
301     /// </para>
302     /// <para></para>
303     /// </summary>
304     /// <returns>
305     /// <para>The ulong</para>
306     /// <para></para>
307     /// </returns>
308     [MethodImpl(MethodImplOptions.AggressiveInlining)]
309     protected override ulong GetOne() => 1UL;
310
311     /// <summary>
312     /// <para>
313     /// Converts the to int 64 using the specified value.
314     /// </para>
315     /// <para></para>
316     /// </summary>
317     /// <param name="value">
318     /// <para>The value.</para>
319     /// <para></para>
320     /// </param>
321     /// <returns>
322     /// <para>The long</para>
323     /// <para></para>
324     /// </returns>
325     [MethodImpl(MethodImplOptions.AggressiveInlining)]
326     protected override long ConvertToInt64(ulong value) => (long)value;
327
328     /// <summary>
329     /// <para>
330     /// Converts the to address using the specified value.
331     /// </para>
332     /// <para></para>
333     /// </summary>
334     /// <param name="value">
335     /// <para>The value.</para>
336     /// <para></para>
337     /// </param>
338     /// <returns>
339     /// <para>The ulong</para>
340     /// <para></para>
341     /// </returns>
342     [MethodImpl(MethodImplOptions.AggressiveInlining)]
343     protected override ulong ConvertToAddress(long value) => (ulong)value;
344
345     /// <summary>
346     /// <para>
347     /// Adds the first.
348     /// </para>
349     /// <para></para>
350     /// </summary>
351     /// <param name="first">
352     /// <para>The first.</para>
353     /// <para></para>
354     /// </param>
355     /// <param name="second">
356     /// <para>The second.</para>
357     /// <para></para>
358     /// </param>
359     /// <returns>
360     /// <para>The ulong</para>
361     /// <para></para>
362     /// </returns>

```

```

363 [MethodImpl(MethodImplOptions.AggressiveInlining)]
364 protected override ulong Add(ulong first, ulong second) => first + second;
365
366 /// <summary>
367 /// <para>
368 /// Subtracts the first.
369 /// </para>
370 /// <para></para>
371 /// </summary>
372 /// <param name="first">
373 /// <para>The first.</para>
374 /// <para></para>
375 /// </param>
376 /// <param name="second">
377 /// <para>The second.</para>
378 /// <para></para>
379 /// </param>
380 /// <returns>
381 /// <para>The ulong</para>
382 /// <para></para>
383 /// </returns>
384 [MethodImpl(MethodImplOptions.AggressiveInlining)]
385 protected override ulong Subtract(ulong first, ulong second) => first - second;
386
387 /// <summary>
388 /// <para>
389 /// Increments the link.
390 /// </para>
391 /// <para></para>
392 /// </summary>
393 /// <param name="link">
394 /// <para>The link.</para>
395 /// <para></para>
396 /// </param>
397 /// <returns>
398 /// <para>The ulong</para>
399 /// <para></para>
400 /// </returns>
401 [MethodImpl(MethodImplOptions.AggressiveInlining)]
402 protected override ulong Increment(ulong link) => ++link;
403
404 /// <summary>
405 /// <para>
406 /// Decrements the link.
407 /// </para>
408 /// <para></para>
409 /// </summary>
410 /// <param name="link">
411 /// <para>The link.</para>
412 /// <para></para>
413 /// </param>
414 /// <returns>
415 /// <para>The ulong</para>
416 /// <para></para>
417 /// </returns>
418 [MethodImpl(MethodImplOptions.AggressiveInlining)]
419 protected override ulong Decrement(ulong link) => --link;
420 }
421 }

```

1.111 ./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64UnusedLinksListMethods.cs

```

1 using System.Runtime.CompilerServices;
2 using Platform.Data.Doublets.Memory.United.Generic;
3
4 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6 namespace Platform.Data.Doublets.Memory.United.Specific
7 {
8     /// <summary>
9     /// <para>
10    /// Represents the int 64 unused links list methods.
11    /// </para>
12    /// <para></para>
13    /// </summary>
14    /// <seealso cref="UnusedLinksListMethods{ulong}" />
15    public unsafe class UInt64UnusedLinksListMethods : UnusedLinksListMethods<ulong>
16    {
17        private readonly RawLink<ulong>* _links;
18        private readonly LinksHeader<ulong>* _header;

```

```

19
20     /// <summary>
21     /// <para>
22     /// Initializes a new <see cref="UInt64UnusedLinksListMethods"/> instance.
23     /// </para>
24     /// <para></para>
25     /// </summary>
26     /// <param name="links">
27     /// <para>A links.</para>
28     /// <para></para>
29     /// </param>
30     /// <param name="header">
31     /// <para>A header.</para>
32     /// <para></para>
33     /// </param>
34     [MethodImpl(MethodImplOptions.AggressiveInlining)]
35     public UInt64UnusedLinksListMethods(RawLink<ulong>* links, LinksHeader<ulong>* header)
36         : base((byte*)links, (byte*)header)
37     {
38         _links = links;
39         _header = header;
40     }
41
42     /// <summary>
43     /// <para>
44     /// Gets the link reference using the specified link.
45     /// </para>
46     /// <para></para>
47     /// </summary>
48     /// <param name="link">
49     /// <para>The link.</para>
50     /// <para></para>
51     /// </param>
52     /// <returns>
53     /// <para>A ref raw link of ulong</para>
54     /// <para></para>
55     /// </returns>
56     [MethodImpl(MethodImplOptions.AggressiveInlining)]
57     protected override ref RawLink<ulong> GetLinkReference(ulong link) => ref _links[link];
58
59     /// <summary>
60     /// <para>
61     /// Gets the header reference.
62     /// </para>
63     /// <para></para>
64     /// </summary>
65     /// <returns>
66     /// <para>A ref links header of ulong</para>
67     /// <para></para>
68     /// </returns>
69     [MethodImpl(MethodImplOptions.AggressiveInlining)]
70     protected override ref LinksHeader<ulong> GetHeaderReference() => ref *_header;
71 }
72 }

```

1.112 ./csharp/Platform.Data.Doublets/PropertyOperators/PropertiesOperator.cs

```

1  using System.Collections.Generic;
2  using System.Runtime.CompilerServices;
3  using Platform.Interfaces;
4
5  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7  namespace Platform.Data.Doublets.PropertyOperators
8  {
9      /// <summary>
10     /// <para>
11     /// Represents the properties operator.
12     /// </para>
13     /// <para></para>
14     /// </summary>
15     /// <seealso cref="LinksOperatorBase{TLinkAddress}"/>
16     /// <seealso cref="IProperties{TLinkAddress, TLinkAddress, TLinkAddress}"/>
17     public class PropertiesOperator<TLinkAddress> : LinksOperatorBase<TLinkAddress>,
18         ↪ IProperties<TLinkAddress, TLinkAddress, TLinkAddress> where TLinkAddress : struct
19     {
20         private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
21         ↪ EqualityComparer<TLinkAddress>.Default;
22
23         /// <summary>

```

```

22     /// <para>
23     /// Initializes a new <see cref="PropertiesOperator"/> instance.
24     /// </para>
25     /// <para></para>
26     /// </summary>
27     /// <param name="links">
28     /// <para>A links.</para>
29     /// <para></para>
30     /// </param>
31     [MethodImpl(MethodImplOptions.AggressiveInlining)]
32     public PropertiesOperator(ILinks<TLinkAddress> links) : base(links) { }
33
34     /// <summary>
35     /// <para>
36     /// Gets the value using the specified object.
37     /// </para>
38     /// <para></para>
39     /// </summary>
40     /// <param name="@object">
41     /// <para>The object.</para>
42     /// <para></para>
43     /// </param>
44     /// <param name="property">
45     /// <para>The property.</para>
46     /// <para></para>
47     /// </param>
48     /// <returns>
49     /// <para>The link</para>
50     /// <para></para>
51     /// </returns>
52     [MethodImpl(MethodImplOptions.AggressiveInlining)]
53     public TLinkAddress GetValue(TLinkAddress @object, TLinkAddress property)
54     {
55         var links = _links;
56         var objectProperty = links.SearchOrDefault(@object, property);
57         if (_equalityComparer.Equals(objectProperty, default))
58         {
59             return default;
60         }
61         var constants = links.Constants;
62         var any = constants.Any;
63         var query = new Link<TLinkAddress>(any, objectProperty, any);
64         var valueLink = links.SingleOrDefault(query);
65         if (valueLink == null)
66         {
67             return default;
68         }
69         return links.GetTarget(links.GetIndex(valueLink));
70     }
71
72     /// <summary>
73     /// <para>
74     /// Sets the value using the specified object.
75     /// </para>
76     /// <para></para>
77     /// </summary>
78     /// <param name="@object">
79     /// <para>The object.</para>
80     /// <para></para>
81     /// </param>
82     /// <param name="property">
83     /// <para>The property.</para>
84     /// <para></para>
85     /// </param>
86     /// <param name="value">
87     /// <para>The value.</para>
88     /// <para></para>
89     /// </param>
90     [MethodImpl(MethodImplOptions.AggressiveInlining)]
91     public void SetValue(TLinkAddress @object, TLinkAddress property, TLinkAddress value)
92     {
93         var links = _links;
94         var objectProperty = links.GetOrCreate(@object, property);
95         links.DeleteMany(links.AllIndices(links.Constants.Any, objectProperty));
96         links.GetOrCreate(objectProperty, value);
97     }
98 }
99 }

```


1.113 ./csharp/Platform.Data.Doublets/PropertyOperators/PropertyOperator.cs

```

1  using System.Collections.Generic;
2  using System.Runtime.CompilerServices;
3  using Platform.Interfaces;
4
5  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7  namespace Platform.Data.Doublets.PropertyOperators
8  {
9      /// <summary>
10     /// <para>
11     /// Represents the property operator.
12     /// </para>
13     /// <para></para>
14     /// </summary>
15     /// <seealso cref="LinksOperatorBase{TLinkAddress}"/>
16     /// <seealso cref="IProperty{TLinkAddress, TLinkAddress}"/>
17     public class PropertyOperator<TLinkAddress> : LinksOperatorBase<TLinkAddress>,
18     ↪ IProperty<TLinkAddress, TLinkAddress> where TLinkAddress : struct
19     {
20         private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
21         ↪ EqualityComparer<TLinkAddress>.Default;
22         private readonly TLinkAddress _propertyMarker;
23         private readonly TLinkAddress _propertyValueMarker;
24
25         /// <summary>
26         /// <para>
27         /// Initializes a new <see cref="PropertyOperator"/> instance.
28         /// </para>
29         /// <para></para>
30         /// </summary>
31         /// <param name="links">
32         /// <para>A links.</para>
33         /// <para></para>
34         /// </param>
35         /// <param name="propertyMarker">
36         /// <para>A property marker.</para>
37         /// <para></para>
38         /// </param>
39         /// <param name="propertyValueMarker">
40         /// <para>A property value marker.</para>
41         /// <para></para>
42         /// </param>
43         [MethodImpl(MethodImplOptions.AggressiveInlining)]
44         public PropertyOperator(ILinks<TLinkAddress> links, TLinkAddress propertyMarker,
45         ↪ TLinkAddress propertyValueMarker) : base(links)
46         {
47             _propertyMarker = propertyMarker;
48             _propertyValueMarker = propertyValueMarker;
49         }
50
51         /// <summary>
52         /// <para>
53         /// Gets the link.
54         /// </para>
55         /// <para></para>
56         /// </summary>
57         /// <param name="link">
58         /// <para>The link.</para>
59         /// <para></para>
60         /// </param>
61         /// <returns>
62         /// <para>The link</para>
63         /// <para></para>
64         /// </returns>
65         [MethodImpl(MethodImplOptions.AggressiveInlining)]
66         public TLinkAddress Get(TLinkAddress link)
67         {
68             var property = _links.SearchOrDefault(link, _propertyMarker);
69             return GetValue(GetContainer(property));
70         }
71
72         [MethodImpl(MethodImplOptions.AggressiveInlining)]
73         private TLinkAddress GetContainer(TLinkAddress property)
74         {
75             var valueContainer = default(TLinkAddress);
76             if (_equalityComparer.Equals(property, default))
77             {
78                 return valueContainer;
79             }
80         }
81     }
82 }

```

```

76     var links = _links;
77     var constants = links.Constants;
78     var countinueConstant = constants.Continue;
79     var breakConstant = constants.Break;
80     var anyConstant = constants.Any;
81     var query = new Link<TLinkAddress>(anyConstant, property, anyConstant);
82     links.Each(candidate =>
83     {
84         var candidateTarget = links.GetTarget(candidate);
85         var valueTarget = links.GetTarget(candidateTarget);
86         if (_equalityComparer.Equals(valueTarget, _propertyValueMarker))
87         {
88             valueContainer = links.GetIndex(candidate);
89             return breakConstant;
90         }
91         return countinueConstant;
92     }, query);
93     return valueContainer;
94 }
95 [MethodImpl(MethodImplOptions.AggressiveInlining)]
96 private TLinkAddress GetValue(TLinkAddress container) =>
97     ↪ _equalityComparer.Equals(container, default) ? default : _links.GetTarget(container);
98
99 /// <summary>
100 /// <para>
101 /// Sets the link.
102 /// </para>
103 /// <para></para>
104 /// </summary>
105 /// <param name="link">
106 /// <para>The link.</para>
107 /// <para></para>
108 /// </param>
109 /// <param name="value">
110 /// <para>The value.</para>
111 /// <para></para>
112 /// </param>
113 [MethodImpl(MethodImplOptions.AggressiveInlining)]
114 public void Set(TLinkAddress link, TLinkAddress value)
115 {
116     var links = _links;
117     var property = links.GetOrCreate(link, _propertyMarker);
118     var container = GetContainer(property);
119     if (_equalityComparer.Equals(container, default))
120     {
121         links.GetOrCreate(property, value);
122     }
123     else
124     {
125         links.Update(container, property, value);
126     }
127 }
128 }

```

1.114 ./csharp/Platform.Data.Doublets/Stacks/Stack.cs

```

1  using System.Collections;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Collections.Stacks;
5
6  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8  namespace Platform.Data.Doublets.Stacks
9  {
10     /// <summary>
11     /// <para>
12     /// Represents the stack.
13     /// </para>
14     /// <para></para>
15     /// </summary>
16     /// <seealso cref="LinksOperatorBase{TLinkAddress}" />
17     /// <seealso cref="IStack{TLinkAddress}" />
18     public class Stack<TLinkAddress> : LinksOperatorBase<TLinkAddress>, IStack<TLinkAddress>
19     {
20         ↪ where TLinkAddress : struct
21         {
22             private static readonly EqualityComparer<TLinkAddress> _equalityComparer =
23                 ↪ EqualityComparer<TLinkAddress>.Default;
24             private readonly TLinkAddress _stack;
25         }
26     }
27 }

```

```

22
23     /// <summary>
24     /// <para>
25     /// Gets the is empty value.
26     /// </para>
27     /// <para></para>
28     /// </summary>
29     public bool IsEmpty
30     {
31         [MethodImpl(MethodImplOptions.AggressiveInlining)]
32         get => _equalityComparer.Equals(Peek(), _stack);
33     }
34
35     /// <summary>
36     /// <para>
37     /// Initializes a new <see cref="Stack"/> instance.
38     /// </para>
39     /// <para></para>
40     /// </summary>
41     /// <param name="links">
42     /// <para>A links.</para>
43     /// <para></para>
44     /// </param>
45     /// <param name="stack">
46     /// <para>A stack.</para>
47     /// <para></para>
48     /// </param>
49     [MethodImpl(MethodImplOptions.AggressiveInlining)]
50     public Stack(ILinks<TLinkAddress> links, TLinkAddress stack) : base(links) => _stack =
51     => stack;
52     [MethodImpl(MethodImplOptions.AggressiveInlining)]
53     private TLinkAddress GetStackMarker() => _links.GetSource(_stack);
54     [MethodImpl(MethodImplOptions.AggressiveInlining)]
55     private TLinkAddress GetTop() => _links.GetTarget(_stack);
56
57     /// <summary>
58     /// <para>
59     /// Peeks this instance.
60     /// </para>
61     /// <para></para>
62     /// </summary>
63     /// <returns>
64     /// <para>The link</para>
65     /// <para></para>
66     /// </returns>
67     [MethodImpl(MethodImplOptions.AggressiveInlining)]
68     public TLinkAddress Peek() => _links.GetTarget(GetTop());
69
70     /// <summary>
71     /// <para>
72     /// Pops this instance.
73     /// </para>
74     /// <para></para>
75     /// </summary>
76     /// <returns>
77     /// <para>The element.</para>
78     /// <para></para>
79     /// </returns>
80     [MethodImpl(MethodImplOptions.AggressiveInlining)]
81     public TLinkAddress Pop()
82     {
83         var element = Peek();
84         if (!_equalityComparer.Equals(element, _stack))
85         {
86             var top = GetTop();
87             var previousTop = _links.GetSource(top);
88             _links.Update(_stack, GetStackMarker(), previousTop);
89             _links.Delete(top);
90         }
91         return element;
92     }
93
94     /// <summary>
95     /// <para>
96     /// Pushes the element.
97     /// </para>
98     /// <para></para>
99     /// </summary>

```

```

99     /// <param name="element">
100    /// <para>The element.</para>
101    /// <para></para>
102    /// </param>
103    [MethodImpl(MethodImplOptions.AggressiveInlining)]
104    public void Push(TLinkAddress element) => _links.Update(_stack, GetStackMarker(),
    ↪ _links.GetOrCreate(GetTop(), element));
105 }
106 }

```

1.115 ./csharp/Platform.Data.Doublets/Stacks/StackExtensions.cs

```

1  using System.Runtime.CompilerServices;
2
3  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5  namespace Platform.Data.Doublets.Stacks
6  {
7      /// <summary>
8      /// <para>
9      /// Represents the stack extensions.
10     /// </para>
11     /// <para></para>
12     /// </summary>
13     public static class StackExtensions
14     {
15         /// <summary>
16         /// <para>
17         /// Creates the stack using the specified links.
18         /// </para>
19         /// <para></para>
20         /// </summary>
21         /// <typeparam name="TLinkAddress">
22         /// <para>The link.</para>
23         /// <para></para>
24         /// </typeparam>
25         /// <param name="links">
26         /// <para>The links.</para>
27         /// <para></para>
28         /// </param>
29         /// <param name="stackMarker">
30         /// <para>The stack marker.</para>
31         /// <para></para>
32         /// </param>
33         /// <returns>
34         /// <para>The stack.</para>
35         /// <para></para>
36         /// </returns>
37         [MethodImpl(MethodImplOptions.AggressiveInlining)]
38         public static TLinkAddress CreateStack<TLinkAddress>(this ILinks<TLinkAddress> links,
    ↪ TLinkAddress stackMarker) where TLinkAddress : struct
39         {
40             var stackPoint = links.CreatePoint();
41             var stack = links.Update(stackPoint, stackMarker, stackPoint);
42             return stack;
43         }
44     }
45 }

```

1.116 ./csharp/Platform.Data.Doublets/SynchronizedLinks.cs

```

1  using System;
2  using System.Collections.Generic;
3  using System.Runtime.CompilerServices;
4  using Platform.Data.Doublets;
5  using Platform.Delegates;
6  using Platform.Threading.Synchronization;
7
8  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
9
10 namespace Platform.Data.Doublets
11 {
12     /// <remarks>
13     /// TODO: Autogeneration of synchronized wrapper (decorator).
14     /// TODO: Try to unfold code of each method using IL generation for performance improvements.
15     /// TODO: Or even to unfold multiple layers of implementations.
16     /// </remarks>
17     public class SynchronizedLinks<TLinkAddress> : ISynchronizedLinks<TLinkAddress> where
    ↪ TLinkAddress : struct
18     {

```

```

19     /// <summary>
20     /// <para>
21     /// Gets the constants value.
22     /// </para>
23     /// <para></para>
24     /// </summary>
25     public LinksConstants<TLinkAddress> Constants
26     {
27         [MethodImpl(MethodImplOptions.AggressiveInlining)]
28         get;
29     }
30
31     /// <summary>
32     /// <para>
33     /// Gets the sync root value.
34     /// </para>
35     /// <para></para>
36     /// </summary>
37     public ISynchronization SyncRoot
38     {
39         [MethodImpl(MethodImplOptions.AggressiveInlining)]
40         get;
41     }
42
43     /// <summary>
44     /// <para>
45     /// Gets the sync value.
46     /// </para>
47     /// <para></para>
48     /// </summary>
49     public ILinks<TLinkAddress> Sync
50     {
51         [MethodImpl(MethodImplOptions.AggressiveInlining)]
52         get;
53     }
54
55     /// <summary>
56     /// <para>
57     /// Gets the unsync value.
58     /// </para>
59     /// <para></para>
60     /// </summary>
61     public ILinks<TLinkAddress> Unsync
62     {
63         [MethodImpl(MethodImplOptions.AggressiveInlining)]
64         get;
65     }
66
67     /// <summary>
68     /// <para>
69     /// Initializes a new <see cref="SynchronizedLinks"/> instance.
70     /// </para>
71     /// <para></para>
72     /// </summary>
73     /// <param name="links">
74     /// <para>A links.</para>
75     /// <para></para>
76     /// </param>
77     [MethodImpl(MethodImplOptions.AggressiveInlining)]
78     public SynchronizedLinks(ILinks<TLinkAddress> links) : this(new
79     ↪ ReaderWriterLockSynchronization(), links) { }
80
81     /// <summary>
82     /// <para>
83     /// Initializes a new <see cref="SynchronizedLinks"/> instance.
84     /// </para>
85     /// <para></para>
86     /// </summary>
87     /// <param name="synchronization">
88     /// <para>A synchronization.</para>
89     /// <para></para>
90     /// </param>
91     /// <param name="links">
92     /// <para>A links.</para>
93     /// <para></para>
94     /// </param>
95     [MethodImpl(MethodImplOptions.AggressiveInlining)]
96     public SynchronizedLinks(ISynchronization synchronization, ILinks<TLinkAddress> links)
97     {

```

```

97         SyncRoot = synchronization;
98         Sync = this;
99         Unsync = links;
100        Constants = links.Constants;
101    }
102
103    /// <summary>
104    /// <para>
105    /// Counts the restriction.
106    /// </para>
107    /// <para></para>
108    /// </summary>
109    /// <param name="restriction">
110    /// <para>The restriction.</para>
111    /// <para></para>
112    /// </param>
113    /// <returns>
114    /// <para>The link address</para>
115    /// <para></para>
116    /// </returns>
117    [MethodImpl(MethodImplOptions.AggressiveInlining)]
118    public TLinkAddress Count(IList<TLinkAddress>? restriction) =>
119        ↪ SyncRoot.ExecuteReadOperation(restriction, Unsync.Count);
120
121    /// <summary>
122    /// <para>
123    /// Eaches the handler.
124    /// </para>
125    /// <para></para>
126    /// </summary>
127    /// <param name="handler">
128    /// <para>The handler.</para>
129    /// <para></para>
130    /// </param>
131    /// <param name="restriction">
132    /// <para>The substitution.</para>
133    /// <para></para>
134    /// </param>
135    /// <returns>
136    /// <para>The link address</para>
137    /// <para></para>
138    /// </returns>
139    [MethodImpl(MethodImplOptions.AggressiveInlining)]
140    public TLinkAddress Each(IList<TLinkAddress>? restriction, ReadHandler<TLinkAddress>?
141        ↪ handler) => SyncRoot.ExecuteReadOperation(restriction, handler, Unsync.Each);
142
143    /// <summary>
144    /// <para>
145    /// Creates the substitution.
146    /// </para>
147    /// <para></para>
148    /// </summary>
149    /// <param name="substitution">
150    /// <para>The substitution.</para>
151    /// <para></para>
152    /// </param>
153    /// <returns>
154    /// <para>The link address</para>
155    /// <para></para>
156    /// </returns>
157    [MethodImpl(MethodImplOptions.AggressiveInlining)]
158    public TLinkAddress Create(IList<TLinkAddress>? substitution,
159        ↪ WriteHandler<TLinkAddress>? handler) => SyncRoot.ExecuteWriteOperation(substitution,
160        ↪ handler, Unsync.Create);
161
162    /// <summary>
163    /// <para>
164    /// Updates the substitution.
165    /// </para>
166    /// <para></para>
167    /// </summary>
168    /// <param name="restriction">
169    /// <para>The substitution.</para>
170    /// <para></para>
171    /// </param>
172    /// <param name="substitution">
173    /// <para>The substitution.</para>
174    /// <para></para>
175    /// </param>

```

```

171     /// </param>
172     /// <returns>
173     /// <para>The link address</para>
174     /// <para></para>
175     /// </returns>
176     [MethodImpl(MethodImplOptions.AggressiveInlining)]
177     public TLinkAddress Update(IList<TLinkAddress>? restriction, IList<TLinkAddress>?
        ↳ substitution, WriteHandler<TLinkAddress>? handler) =>
        ↳ SyncRoot.ExecuteWriteOperation(restriction, substitution, handler, Unsync.Update);

178
179     /// <summary>
180     /// <para>
181     /// Deletes the substitution.
182     /// </para>
183     /// <para></para>
184     /// </summary>
185     /// <param name="restriction">
186     /// <para>The substitution.</para>
187     /// <para></para>
188     /// </param>
189     [MethodImpl(MethodImplOptions.AggressiveInlining)]
190     public TLinkAddress Delete(IList<TLinkAddress>? restriction, WriteHandler<TLinkAddress>?
        ↳ handler) => SyncRoot.ExecuteWriteOperation(restriction, handler, Unsync.Delete);

191
192     //public T Trigger(IList<T> restriction, Func<IList<T>, IList<T>, T> matchedHandler,
        ↳ IList<T> substitution, Func<IList<T>, IList<T>, T> substitutedHandler)
193     //{
194     //    if (restriction != null && substitution != null &&
        ↳ !substitution.EqualTo(restriction))
195     //        return SyncRoot.ExecuteWriteOperation(restriction, matchedHandler,
        ↳ substitution, substitutedHandler, Unsync.Trigger);
196
197     //    return SyncRoot.ExecuteReadOperation(restriction, matchedHandler, substitution,
        ↳ substitutedHandler, Unsync.Trigger);
198     //}
199 }
200 }

```

1.117 ./csharp/Platform.Data.Doublets/UInt64LinksExtensions.cs

```

1  using System;
2  using System.Text;
3  using System.Collections.Generic;
4  using System.Runtime.CompilerServices;
5  using Platform.Singletons;
6
7  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
8
9  namespace Platform.Data.Doublets
10 {
11     /// <summary>
12     /// <para>
13     /// Represents the int 64 links extensions.
14     /// </para>
15     /// <para></para>
16     /// </summary>
17     public static class UInt64LinksExtensions
18     {
19         /// <summary>
20         /// <para>
21         /// The instance.
22         /// </para>
23         /// <para></para>
24         /// </summary>
25         public static readonly LinksConstants<ulong> Constants =
            ↳ Default<LinksConstants<ulong>>.Instance;

26
27         /// <summary>
28         /// <para>
29         /// Determines whether any link is any.
30         /// </para>
31         /// <para></para>
32         /// </summary>
33         /// <param name="links">
34         /// <para>The links.</para>
35         /// <para></para>
36         /// </param>
37         /// <param name="sequence">
38         /// <para>The sequence.</para>

```

```

39  /// <para></para>
40  /// </param>
41  /// <returns>
42  /// <para>The bool</para>
43  /// <para></para>
44  /// </returns>
45  [MethodImpl(MethodImplOptions.AggressiveInlining)]
46  public static bool AnyLinkIsAny(this ILinks<ulong> links, params ulong[] sequence)
47  {
48      if (sequence == null)
49      {
50          return false;
51      }
52      var constants = links.Constants;
53      for (var i = 0; i < sequence.Length; i++)
54      {
55          if (sequence[i] == constants.Any)
56          {
57              return true;
58          }
59      }
60      return false;
61  }
62
63  /// <summary>
64  /// <para>
65  /// Formats the structure using the specified links.
66  /// </para>
67  /// <para></para>
68  /// </summary>
69  /// <param name="links">
70  /// <para>The links.</para>
71  /// <para></para>
72  /// </param>
73  /// <param name="linkIndex">
74  /// <para>The link index.</para>
75  /// <para></para>
76  /// </param>
77  /// <param name="isElement">
78  /// <para>The is element.</para>
79  /// <para></para>
80  /// </param>
81  /// <param name="renderIndex">
82  /// <para>The render index.</para>
83  /// <para></para>
84  /// </param>
85  /// <param name="renderDebug">
86  /// <para>The render debug.</para>
87  /// <para></para>
88  /// </param>
89  /// <returns>
90  /// <para>The string</para>
91  /// <para></para>
92  /// </returns>
93  [MethodImpl(MethodImplOptions.AggressiveInlining)]
94  public static string FormatStructure(this ILinks<ulong> links, ulong linkIndex,
95  ↪ Func<Link<ulong>, bool> isElement, bool renderIndex = false, bool renderDebug =
96  ↪ false)
97  {
98      var sb = new StringBuilder();
99      var visited = new HashSet<ulong>();
100      links.AppendStructure(sb, visited, linkIndex, isElement, (innerSb, link) =>
101      ↪ innerSb.Append(link.Index), renderIndex, renderDebug);
102      return sb.ToString();
103  }
104
105  /// <summary>
106  /// <para>
107  /// Formats the structure using the specified links.
108  /// </para>
109  /// <para></para>
110  /// </summary>
111  /// <param name="links">
112  /// <para>The links.</para>
113  /// <para></para>
114  /// </param>
115  /// <param name="linkIndex">
116  /// <para>The link index.</para>

```



```

114     /// <para></para>
115     /// </param>
116     /// <param name="isElement">
117     /// <para>The is element.</para>
118     /// <para></para>
119     /// </param>
120     /// <param name="appendElement">
121     /// <para>The append element.</para>
122     /// <para></para>
123     /// </param>
124     /// <param name="renderIndex">
125     /// <para>The render index.</para>
126     /// <para></para>
127     /// </param>
128     /// <param name="renderDebug">
129     /// <para>The render debug.</para>
130     /// <para></para>
131     /// </param>
132     /// <returns>
133     /// <para>The string</para>
134     /// <para></para>
135     /// </returns>
136     [MethodImpl(MethodImplOptions.AggressiveInlining)]
137     public static string FormatStructure(this ILinks<ulong> links, ulong linkIndex,
    ↪ Func<Link<ulong>, bool> isElement, Action<StringBuilder, Link<ulong>> appendElement,
    ↪ bool renderIndex = false, bool renderDebug = false)
138     {
139         var sb = new StringBuilder();
140         var visited = new HashSet<ulong>();
141         links.AppendStructure(sb, visited, linkIndex, isElement, appendElement, renderIndex,
    ↪ renderDebug);
142         return sb.ToString();
143     }
144
145     /// <summary>
146     /// <para>
147     /// Appends the structure using the specified links.
148     /// </para>
149     /// <para></para>
150     /// </summary>
151     /// <param name="links">
152     /// <para>The links.</para>
153     /// <para></para>
154     /// </param>
155     /// <param name="sb">
156     /// <para>The sb.</para>
157     /// <para></para>
158     /// </param>
159     /// <param name="visited">
160     /// <para>The visited.</para>
161     /// <para></para>
162     /// </param>
163     /// <param name="linkIndex">
164     /// <para>The link index.</para>
165     /// <para></para>
166     /// </param>
167     /// <param name="isElement">
168     /// <para>The is element.</para>
169     /// <para></para>
170     /// </param>
171     /// <param name="appendElement">
172     /// <para>The append element.</para>
173     /// <para></para>
174     /// </param>
175     /// <param name="renderIndex">
176     /// <para>The render index.</para>
177     /// <para></para>
178     /// </param>
179     /// <param name="renderDebug">
180     /// <para>The render debug.</para>
181     /// <para></para>
182     /// </param>
183     /// <exception cref="ArgumentNullException">
184     /// <para></para>
185     /// <para></para>
186     /// </exception>
187     [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

188 public static void AppendStructure(this ILinks<ulong> links, StringBuilder sb,
    ↳ HashSet<ulong> visited, ulong linkIndex, Func<Link<ulong>, bool> isElement,
    ↳ Action<StringBuilder, Link<ulong>> appendElement, bool renderIndex = false, bool
    ↳ renderDebug = false)
189 {
190     if (sb == null)
191     {
192         throw new ArgumentNullException(nameof(sb));
193     }
194     if (linkIndex == Constants.Null || linkIndex == Constants.Any || linkIndex ==
    ↳ Constants.Itself)
195     {
196         return;
197     }
198     if (links.Exists(linkIndex))
199     {
200         if (visited.Add(linkIndex))
201         {
202             sb.Append('(');
203             var link = new Link<ulong>(links.GetLink(linkIndex));
204             if (renderIndex)
205             {
206                 sb.Append(link.Index);
207                 sb.Append(':');
208             }
209             if (link.Source == link.Index)
210             {
211                 sb.Append(link.Index);
212             }
213             else
214             {
215                 var source = new Link<ulong>(links.GetLink(link.Source));
216                 if (isElement(source))
217                 {
218                     appendElement(sb, source);
219                 }
220                 else
221                 {
222                     links.AppendStructure(sb, visited, source.Index, isElement,
    ↳ appendElement, renderIndex);
223                 }
224             }
225             sb.Append(' ');
226             if (link.Target == link.Index)
227             {
228                 sb.Append(link.Index);
229             }
230             else
231             {
232                 var target = new Link<ulong>(links.GetLink(link.Target));
233                 if (isElement(target))
234                 {
235                     appendElement(sb, target);
236                 }
237                 else
238                 {
239                     links.AppendStructure(sb, visited, target.Index, isElement,
    ↳ appendElement, renderIndex);
240                 }
241             }
242             sb.Append(')');
243         }
244         else
245         {
246             if (renderDebug)
247             {
248                 sb.Append('*');
249             }
250             sb.Append(linkIndex);
251         }
252     }
253     else
254     {
255         if (renderDebug)
256         {
257             sb.Append('~');
258         }
259         sb.Append(linkIndex);

```

```

260     }
261 }
262 }
263 }

```

1.118 ./csharp/Platform.Data.Doublets/UInt64LinksTransactionsLayer.cs

```

1  using System;
2  using System.Linq;
3  using System.Collections.Generic;
4  using System.IO;
5  using System.Runtime.CompilerServices;
6  using System.Threading;
7  using System.Threading.Tasks;
8  using Platform.Disposables;
9  using Platform.Timestamps;
10 using Platform.Unsafe;
11 using Platform.IO;
12 using Platform.Data.Doublets.Decorators;
13 using Platform.Delegates;
14 using Platform.Exceptions;
15 using TLinkAddress = System.UInt64;
16
17 #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
18
19 namespace Platform.Data.Doublets
20 {
21     /// <summary>
22     /// <para>
23     /// Represents the int 64 links transactions layer.
24     /// </para>
25     /// <para></para>
26     /// </summary>
27     /// <seealso cref="LinksDisposableDecoratorBase{TLinkAddress}"/>
28     public class UInt64LinksTransactionsLayer : LinksDisposableDecoratorBase<TLinkAddress>
29     {
30         // --V3073 where TLinkAddress : struct
31         {
32             /// <remarks>
33             /// Альтернативные варианты хранения трансформации (элемента транзакции):
34             ///
35             /// private enum TransitionType
36             /// {
37             ///     Creation,
38             ///     UpdateOf,
39             ///     UpdateTo,
40             ///     Deletion
41             /// }
42             ///
43             /// private struct Transition
44             /// {
45             ///     public TLinkAddress TransactionId;
46             ///     public UniqueTimestamp Timestamp;
47             ///     public TransactionItemType Type;
48             ///     public Link Source;
49             ///     public Link Linker;
50             ///     public Link Target;
51             /// }
52             /// Или
53             ///
54             public struct TransitionHeader
55             {
56                 public TLinkAddress TransactionIdCombined;
57                 public TLinkAddress TimestampCombined;
58             }
59             public TLinkAddress TransactionId
60             {
61                 get
62                 {
63                     return (TLinkAddress) mask & TransactionIdCombined;
64                 }
65             }
66             public UniqueTimestamp Timestamp
67             {
68                 get
69                 {
70                     return (UniqueTimestamp) mask & TransactionIdCombined;
71                 }
72             }
73         }
74     }
75 }

```

```

73     ///
74     public TransactionItemType Type
75     {
76         ///     get
77         ///     {
78             ///         // Использовать по одному биту из TransactionId и Timestamp,
79             ///         // для значения в 2 бита, которое представляет тип операции
80             ///         throw new NotImplementedException();
81         }
82     }
83 }
84 ///
85 private struct Transition
86 {
87     public TransitionHeader Header;
88     public Link Source;
89     public Link Linker;
90     public Link Target;
91 }
92 ///
93 </remarks>
94 public struct Transition : IEquatable<Transition>
95 {
96     /// <summary>
97     /// <para>
98     /// The size.
99     /// </para>
100    /// <para></para>
101    /// </summary>
102    public static readonly long Size = Structure<Transition>.Size;
103
104    /// <summary>
105    /// <para>
106    /// The transaction id.
107    /// </para>
108    /// <para></para>
109    /// </summary>
110    public readonly TLinkAddress TransactionId;
111    /// <summary>
112    /// <para>
113    /// The before.
114    /// </para>
115    /// <para></para>
116    /// </summary>
117    public readonly Link<TLinkAddress> Before;
118    /// <summary>
119    /// <para>
120    /// The after.
121    /// </para>
122    /// <para></para>
123    /// </summary>
124    public readonly Link<TLinkAddress> After;
125    /// <summary>
126    /// <para>
127    /// The timestamp.
128    /// </para>
129    /// <para></para>
130    /// </summary>
131    public readonly Timestamp Timestamp;
132
133    /// <summary>
134    /// <para>
135    /// Initializes a new <see cref="Transition"/> instance.
136    /// </para>
137    /// <para></para>
138    /// </summary>
139    /// <param name="uniqueTimestampFactory">
140    /// <para>A unique timestamp factory.</para>
141    /// <para></para>
142    /// </param>
143    /// <param name="transactionId">
144    /// <para>A transaction id.</para>
145    /// <para></para>
146    /// </param>
147    /// <param name="before">
148    /// <para>A before.</para>
149    /// <para></para>
150    /// </param>

```

```

151     /// <param name="after">
152     /// <para>A after.</para>
153     /// <para></para>
154     /// </param>
155     [MethodImpl(MethodImplOptions.AggressiveInlining)]
156     public Transition(UniqueTimestampFactory uniqueTimestampFactory, TLinkAddress
        ↳ transactionId, Link<TLinkAddress> before, Link<TLinkAddress> after)
157     {
158         TransactionId = transactionId;
159         Before = before;
160         After = after;
161         Timestamp = uniqueTimestampFactory.Create();
162     }
163
164     public Transition(UniqueTimestampFactory uniqueTimestampFactory, TLinkAddress
        ↳ transactionId, IList<TLinkAddress> before, IList<TLinkAddress> after) :
        ↳ this(uniqueTimestampFactory, transactionId, new Link<TLinkAddress>(before), new
        ↳ Link<TLinkAddress>(after)) { }
165
166     /// <summary>
167     /// <para>
168     /// Initializes a new <see cref="Transition"/> instance.
169     /// </para>
170     /// <para></para>
171     /// </summary>
172     /// <param name="uniqueTimestampFactory">
173     /// <para>A unique timestamp factory.</para>
174     /// <para></para>
175     /// </param>
176     /// <param name="transactionId">
177     /// <para>A transaction id.</para>
178     /// <para></para>
179     /// </param>
180     /// <param name="before">
181     /// <para>A before.</para>
182     /// <para></para>
183     /// </param>
184     [MethodImpl(MethodImplOptions.AggressiveInlining)]
185     public Transition(UniqueTimestampFactory uniqueTimestampFactory, TLinkAddress
        ↳ transactionId, Link<TLinkAddress> before) : this(uniqueTimestampFactory,
        ↳ transactionId, before, default) { }
186
187     /// <summary>
188     /// <para>
189     /// Initializes a new <see cref="Transition"/> instance.
190     /// </para>
191     /// <para></para>
192     /// </summary>
193     /// <param name="uniqueTimestampFactory">
194     /// <para>A unique timestamp factory.</para>
195     /// <para></para>
196     /// </param>
197     /// <param name="transactionId">
198     /// <para>A transaction id.</para>
199     /// <para></para>
200     /// </param>
201     [MethodImpl(MethodImplOptions.AggressiveInlining)]
202     public Transition(UniqueTimestampFactory uniqueTimestampFactory, TLinkAddress
        ↳ transactionId) : this(uniqueTimestampFactory, transactionId, default, default) {
        ↳ }
203
204     /// <summary>
205     /// <para>
206     /// Returns the string.
207     /// </para>
208     /// <para></para>
209     /// </summary>
210     /// <returns>
211     /// <para>The string</para>
212     /// <para></para>
213     /// </returns>
214     [MethodImpl(MethodImplOptions.AggressiveInlining)]
215     public override string ToString() => $"{Timestamp} {TransactionId}: {Before} =>
        ↳ {After}";
216
217     /// <summary>
218     /// <para>
219     /// Determines whether this instance equals.

```

```

220     /// </para>
221     /// <para></para>
222     /// </summary>
223     /// <param name="obj">
224     /// <para>The obj.</para>
225     /// <para></para>
226     /// </param>
227     /// <returns>
228     /// <para>The bool</para>
229     /// <para></para>
230     /// </returns>
231     [MethodImpl(MethodImplOptions.AggressiveInlining)]
232     public override bool Equals(object obj) => obj is Transition transition ?
        ↳ Equals(transition) : false;

233
234     /// <summary>
235     /// <para>
236     /// Gets the hash code.
237     /// </para>
238     /// <para></para>
239     /// </summary>
240     /// <returns>
241     /// <para>The int</para>
242     /// <para></para>
243     /// </returns>
244     [MethodImpl(MethodImplOptions.AggressiveInlining)]
245     public override int GetHashCode() => (TransactionId, Before, After,
        ↳ Timestamp).GetHashCode();

246
247     /// <summary>
248     /// <para>
249     /// Determines whether this instance equals.
250     /// </para>
251     /// <para></para>
252     /// </summary>
253     /// <param name="other">
254     /// <para>The other.</para>
255     /// <para></para>
256     /// </param>
257     /// <returns>
258     /// <para>The bool</para>
259     /// <para></para>
260     /// </returns>
261     [MethodImpl(MethodImplOptions.AggressiveInlining)]
262     public bool Equals(Transition other) => TransactionId == other.TransactionId &&
        ↳ Before == other.Before && After == other.After && Timestamp == other.Timestamp;

263
264     [MethodImpl(MethodImplOptions.AggressiveInlining)]
265     public static bool operator ==(Transition left, Transition right) =>
        ↳ left.Equals(right);

266
267     [MethodImpl(MethodImplOptions.AggressiveInlining)]
268     public static bool operator !=(Transition left, Transition right) => !(left ==
        ↳ right);

269 }

270
271 /// <remarks>
272 /// Другие варианты реализации транзакций (атомарности):
273 /// 1. Разделение хранения значения связи ((Source Target) или (Source Linker
274   ↳ Target)) и индексов.
275 /// 2. Хранение трансформаций/операций в отдельном хранилище Links, но дополнительно
276   ↳ потребуется решить вопрос
277   ↳ со ссылками на внешние идентификаторы, или как-то иначе решить вопрос с
278   ↳ пересечениями идентификаторов.
279 ///
280 /// Где хранить промежуточный список транзакций?
281 ///
282 /// В оперативной памяти:
283 /// Минусы:
284 /// 1. Может усложнить систему, если она будет функционировать самостоятельно,
285   ↳ так как нужно отдельно выделять память под список трансформаций.
286   ↳ 2. Выделенной оперативной памяти может не хватить, в том случае,
287   ↳ если транзакция использует слишком много трансформаций.
288   ↳ -> Можно использовать жёсткий диск для слишком длинных транзакций.
289   ↳ -> Максимальный размер списка трансформаций можно ограничить / задать
290   ↳ константой.
291 /// 3. При подтверждении транзакции (Commit) все трансформации записываются разом
292   ↳ создавая задержку.

```

```

288 ///
289 /// На жёстком диске:
290 /// Минусы:
291 /// 1. Длительный отклик, на запись каждой трансформации.
292 /// 2. Лог транзакций дополнительно наполняется отменёнными транзакциями.
293 /// -> Это может решаться упаковкой/исключением дублирующих операций.
294 /// -> Также это может решаться тем, что короткие транзакции вообще
295 /// не будут записываться в случае отката.
296 /// 3. Перед тем как выполнить отмену операций транзакции нужно дождаться пока все
    -> операции (трансформации)
297 /// будут записаны в лог.
298 ///
299 </remarks>
300 public class Transaction : DisposableBase
301 {
302     private readonly Queue<Transition> _transitions;
303     private readonly UInt64LinksTransactionsLayer _layer;
304     /// <summary>
305     /// <para>
306     /// Gets or sets the is committed value.
307     /// </para>
308     /// <para></para>
309     /// </summary>
310     public bool IsCommitted { get; private set; }
311     /// <summary>
312     /// <para>
313     /// Gets or sets the is reverted value.
314     /// </para>
315     /// <para></para>
316     /// </summary>
317     public bool IsReverted { get; private set; }
318
319     /// <summary>
320     /// <para>
321     /// Initializes a new <see cref="Transaction"/> instance.
322     /// </para>
323     /// <para></para>
324     /// </summary>
325     /// <param name="layer">
326     /// <para>A layer.</para>
327     /// <para></para>
328     /// </param>
329     /// <exception cref="NotSupportedException">
330     /// <para>Nested transactions not supported.</para>
331     /// <para></para>
332     /// </exception>
333     [MethodImpl(MethodImplOptions.AggressiveInlining)]
334     public Transaction(UInt64LinksTransactionsLayer layer)
335     {
336         _layer = layer;
337         if (_layer._currentTransactionId != 0)
338         {
339             throw new NotSupportedException("Nested transactions not supported.");
340         }
341         IsCommitted = false;
342         IsReverted = false;
343         _transitions = new Queue<Transition>();
344         SetCurrentTransaction(layer, this);
345     }
346
347     /// <summary>
348     /// <para>
349     /// Commits this instance.
350     /// </para>
351     /// <para></para>
352     /// </summary>
353     [MethodImpl(MethodImplOptions.AggressiveInlining)]
354     public void Commit()
355     {
356         EnsureTransactionAllowsWriteOperations(this);
357         while (_transitions.Count > 0)
358         {
359             var transition = _transitions.Dequeue();
360             _layer._transitions.Enqueue(transition);
361         }
362         _layer._lastCommittedTransactionId = _layer._currentTransactionId;
363         IsCommitted = true;
364     }

```

```

365 [MethodImpl(MethodImplOptions.AggressiveInlining)]
366 private void Revert()
367 {
368     EnsureTransactionAllowsWriteOperations(this);
369     var transitionsToRevert = new Transition[_transitions.Count];
370     _transitions.CopyTo(transitionsToRevert, 0);
371     for (var i = transitionsToRevert.Length - 1; i >= 0; i--)
372     {
373         _layer.RevertTransition(transitionsToRevert[i]);
374     }
375     IsReverted = true;
376 }
377
378 /// <summary>
379 /// <para>
380 /// Sets the current transaction using the specified layer.
381 /// </para>
382 /// <para></para>
383 /// </summary>
384 /// <param name="layer">
385 /// <para>The layer.</para>
386 /// <para></para>
387 /// </param>
388 /// <param name="transaction">
389 /// <para>The transaction.</para>
390 /// <para></para>
391 /// </param>
392 [MethodImpl(MethodImplOptions.AggressiveInlining)]
393 public static void SetCurrentTransaction(UInt64LinksTransactionsLayer layer,
394     ↪ Transaction transaction)
395 {
396     layer._currentTransactionId = layer._lastCommittedTransactionId + 1;
397     layer._currentTransactionTransitions = transaction._transitions;
398     layer._currentTransaction = transaction;
399 }
400
401 /// <summary>
402 /// <para>
403 /// Ensures the transaction allows write operations using the specified transaction.
404 /// </para>
405 /// <para></para>
406 /// </summary>
407 /// <param name="transaction">
408 /// <para>The transaction.</para>
409 /// <para></para>
410 /// </param>
411 /// <exception cref="InvalidOperationException">
412 /// <para>Transation is committed.</para>
413 /// <para></para>
414 /// </exception>
415 /// <exception cref="InvalidOperationException">
416 /// <para>Transation is reverted.</para>
417 /// <para></para>
418 /// </exception>
419 [MethodImpl(MethodImplOptions.AggressiveInlining)]
420 public static void EnsureTransactionAllowsWriteOperations(Transaction transaction)
421 {
422     if (transaction.IsReverted)
423     {
424         throw new InvalidOperationException("Transation is reverted.");
425     }
426     if (transaction.IsCommitted)
427     {
428         throw new InvalidOperationException("Transation is committed.");
429     }
430 }
431
432 /// <summary>
433 /// <para>
434 /// Disposes the manual.
435 /// </para>
436 /// <para></para>
437 /// </summary>
438 /// <param name="manual">
439 /// <para>The manual.</para>
440 /// <para></para>
441 /// </param>
442 /// <param name="wasDisposed">

```



```

442     /// <para>The was disposed.</para>
443     /// <para></para>
444     /// </param>
445     [MethodImpl(MethodImplOptions.AggressiveInlining)]
446     protected override void Dispose(bool manual, bool wasDisposed)
447     {
448         if (!wasDisposed && _layer != null && !_layer.Disposable.IsDisposed)
449         {
450             if (!IsCommitted && !IsReverted)
451             {
452                 Revert();
453             }
454             _layer.ResetCurrentTransation();
455         }
456     }
457 }
458
459     /// <summary>
460     /// <para>
461     /// The from seconds.
462     /// </para>
463     /// <para></para>
464     /// </summary>
465     public static readonly TimeSpan DefaultPushDelay = TimeSpan.FromSeconds(0.1);
466     private readonly string _logAddress;
467     private readonly FileStream _log;
468     private readonly Queue<Transition> _transitions;
469     private readonly UniqueTimestampFactory _uniqueTimestampFactory;
470     private Task _transitionsPusher;
471     private Transition _lastCommittedTransition;
472     private TLinkAddress _currentTransactionId;
473     private Queue<Transition> _currentTransactionTransitions;
474     private Transaction _currentTransaction;
475     private TLinkAddress _lastCommittedTransactionId;
476
477     /// <summary>
478     /// <para>
479     /// Initializes a new <see cref="UInt64LinksTransactionsLayer"/> instance.
480     /// </para>
481     /// <para></para>
482     /// </summary>
483     /// <param name="links">
484     /// <para>A links.</para>
485     /// <para></para>
486     /// </param>
487     /// <param name="logAddress">
488     /// <para>A log address.</para>
489     /// <para></para>
490     /// </param>
491     /// <exception cref="ArgumentNullException">
492     /// <para></para>
493     /// <para></para>
494     /// </exception>
495     /// <exception cref="NotSupportedException">
496     /// <para>Database is damaged, autorecovery is not supported yet.</para>
497     /// <para></para>
498     /// </exception>
499     [MethodImpl(MethodImplOptions.AggressiveInlining)]
500     public UInt64LinksTransactionsLayer(ILinks<TLinkAddress> links, string logAddress)
501         : base(links)
502     {
503         if (string.IsNullOrEmpty(logAddress))
504         {
505             throw new ArgumentNullException(nameof(logAddress));
506         }
507         // В первой строке файла хранится последняя законченную транзакцию.
508         // При запуске это используется для проверки удачного закрытия файла лога.
509         // In the first line of the file the last committed transaction is stored.
510         // On startup, this is used to check that the log file is successfully closed.
511         var lastCommittedTransition = FileHelpers.ReadFirstOrDefault<Transition>(logAddress);
512         var lastWrittenTransition = FileHelpers.ReadLastOrDefault<Transition>(logAddress);
513         if (!lastCommittedTransition.Equals(lastWrittenTransition))
514         {
515             Dispose();
516             throw new NotSupportedException("Database is damaged, autorecovery is not
517                 ↳ supported yet.");
518         }
519         if (lastCommittedTransition == default)

```

```

519     {
520         FileHelpers.WriteFirst(logAddress, lastCommittedTransition);
521     }
522     _lastCommittedTransition = lastCommittedTransition;
523     // TODO: Think about a better way to calculate or store this value
524     var allTransitions = FileHelpers.ReadAll<Transition>(logAddress);
525     _lastCommittedTransactionId = allTransitions.Length > 0 ? allTransitions.Max(x =>
526         ↪ x.TransactionId) : 0;
527     _uniqueTimestampFactory = new UniqueTimestampFactory();
528     _logAddress = logAddress;
529     _log = FileHelpers.Append(logAddress);
530     _transitions = new Queue<Transition>();
531     _transitionsPusher = new Task(TransitionsPusher);
532     _transitionsPusher.Start();
533 }
534
535 /// <summary>
536 /// <para>
537 /// Gets the link value using the specified link.
538 /// </para>
539 /// </summary>
540 /// <param name="link">
541 /// <para>The link.</para>
542 /// </param>
543 /// <returns>
544 /// <para>A list of TLinkAddress</para>
545 /// </returns>
546 [MethodImpl(MethodImplOptions.AggressiveInlining)]
547 public IList<TLinkAddress> GetLinkValue(TLinkAddress link) => _links.GetLink(link);
548
549 /// <summary>
550 /// <para>
551 /// Creates the substitution.
552 /// </para>
553 /// </summary>
554 /// <param name="substitution">
555 /// <para>The substitution.</para>
556 /// </param>
557 /// <returns>
558 /// <para>The created link index.</para>
559 /// </returns>
560 [MethodImpl(MethodImplOptions.AggressiveInlining)]
561 public override TLinkAddress Create(IList<TLinkAddress>? substitution,
562     ↪ WriteHandler<TLinkAddress>? handler)
563 {
564     return _links.Create(new Link<TLinkAddress>(), (before, after) =>
565     {
566         CommitTransition(new Transition(_uniqueTimestampFactory, _currentTransactionId,
567             ↪ new Link<TLinkAddress>(before), new Link<TLinkAddress>(after)));
568         return handler?.Invoke(before, after) ?? Links.Constants.Continue;
569     });
570 }
571
572 /// <summary>
573 /// <para>
574 /// Updates the substitution.
575 /// </para>
576 /// </summary>
577 /// <param name="restriction">
578 /// <para>The substitution.</para>
579 /// </param>
580 /// <param name="substitution">
581 /// <para>The substitution.</para>
582 /// </param>
583 /// <returns>
584 /// <para>The link index.</para>
585 /// </returns>
586 [MethodImpl(MethodImplOptions.AggressiveInlining)]

```

```

594 public override TLinkAddress Update(IList<TLinkAddress>? restriction,
    ↳ IList<TLinkAddress>? substitution, WriteHandler<TLinkAddress>? handler)
595 {
596     return _links.Update(restriction, substitution, (before, after) =>
597     {
598         CommitTransition(new Transition(_uniqueTimestampFactory,
    ↳ _currentTransactionId, new Link<TLinkAddress>(before), new
    ↳ Link<TLinkAddress>(after)));
        return handler?.Invoke(before, after) ?? Constants.Continue;
599     }
600 );
601 }
602
603
604 /// <summary>
605 /// <para>
606 /// Deletes the substitution.
607 /// </para>
608 /// <para></para>
609 /// </summary>
610 /// <param name="restriction">
611 /// <para>The substitution.</para>
612 /// </param>
613 [MethodImpl(MethodImplOptions.AggressiveInlining)]
614 public override TLinkAddress Delete(IList<TLinkAddress>? restriction,
    ↳ WriteHandler<TLinkAddress>? handler)
615 {
616     var link = this.GetIndex(restriction);
617     return _links.Delete(restriction, (before, after) =>
618     {
619         CommitTransition(new Transition(_uniqueTimestampFactory, _currentTransactionId,
    ↳ before, after));
        return handler?.Invoke(before, after) ?? Constants.Continue;
620     });
621 }
622
623 [MethodImpl(MethodImplOptions.AggressiveInlining)]
624 private Queue<Transition> GetCurrentTransitions() => _currentTransactionTransitions ??
    ↳ _transitions;
625 [MethodImpl(MethodImplOptions.AggressiveInlining)]
626 private void CommitTransition(Transition transition)
627 {
628     if (_currentTransaction != null)
629     {
630         Transaction.EnsureTransactionAllowsWriteOperations(_currentTransaction);
631     }
632     var transitions = GetCurrentTransitions();
633     transitions.Enqueue(transition);
634 }
635 [MethodImpl(MethodImplOptions.AggressiveInlining)]
636 private void RevertTransition(Transition transition)
637 {
638     if (transition.After.IsNull()) // Revert Deletion with Creation
639     {
640         _links.Create();
641     }
642     else if (transition.Before.IsNull()) // Revert Creation with Deletion
643     {
644         _links.Delete(transition.After.Index);
645     }
646     else // Revert Update
647     {
648         _links.Update(new[] { transition.After.Index, transition.Before.Source,
    ↳ transition.Before.Target });
649     }
650 }
651 [MethodImpl(MethodImplOptions.AggressiveInlining)]
652 private void ResetCurrentTransation()
653 {
654     _currentTransactionId = 0;
655     _currentTransactionTransitions = null;
656     _currentTransaction = null;
657 }
658 [MethodImpl(MethodImplOptions.AggressiveInlining)]
659 private void PushTransitions()
660 {
661     if (_log == null || _transitions == null)
662     {
663         return;
664     }

```

```

665     }
666     for (var i = 0; i < _transitions.Count; i++)
667     {
668         var transition = _transitions.Dequeue();
669
670         _log.Write(transition);
671         _lastCommittedTransition = transition;
672     }
673 }
674 [MethodImpl(MethodImplOptions.AggressiveInlining)]
675 private void TransitionsPusher()
676 {
677     while (!Disposable.IsDisposed && _transitionsPusher != null)
678     {
679         Thread.Sleep(DefaultPushDelay);
680         PushTransitions();
681     }
682 }
683
684 /// <summary>
685 /// <para>
686 /// Begins the transaction.
687 /// </para>
688 /// <para></para>
689 /// </summary>
690 /// <returns>
691 /// <para>The transaction</para>
692 /// <para></para>
693 /// </returns>
694 [MethodImpl(MethodImplOptions.AggressiveInlining)]
695 public Transaction BeginTransaction() => new Transaction(this);
696 [MethodImpl(MethodImplOptions.AggressiveInlining)]
697 private void DisposeTransitions()
698 {
699     try
700     {
701         var pusher = _transitionsPusher;
702         if (pusher != null)
703         {
704             _transitionsPusher = null;
705             pusher.Wait();
706         }
707         if (_transitions != null)
708         {
709             PushTransitions();
710         }
711         _log.DisposeIfPossible();
712         FileHelpers.WriteFirst(_logAddress, _lastCommittedTransition);
713     }
714     catch (Exception ex)
715     {
716         ex.Ignore();
717     }
718 }
719
720 #region DisposalBase
721
722 /// <summary>
723 /// <para>
724 /// Disposes the manual.
725 /// </para>
726 /// <para></para>
727 /// </summary>
728 /// <param name="manual">
729 /// <para>The manual.</para>
730 /// <para></para>
731 /// </param>
732 /// <param name="wasDisposed">
733 /// <para>The was disposed.</para>
734 /// <para></para>
735 /// </param>
736 [MethodImpl(MethodImplOptions.AggressiveInlining)]
737 protected override void Dispose(bool manual, bool wasDisposed)
738 {
739     if (!wasDisposed)
740     {
741         DisposeTransitions();
742     }

```

```

743         base.Dispose(manual, wasDisposed);
744     }
745
746     #endregion
747 }
748 }

```

1.119 ./csharp/Platform.Data.Doublets.Tests/GenericLinksTests.cs

```

1  using System;
2  using System.IO;
3  using Platform.Data.Doublets.Decorators;
4  using Xunit;
5
6  using Platform.Memory;
7
8  using Platform.Data.Doublets.Memory.United.Generic;
9
10 namespace Platform.Data.Doublets.Tests
11 {
12     public static class GenericLinksTests
13     {
14         [Fact]
15         public static void CRUDTest()
16         {
17             Using<byte>(links => links.TestCRUDOperations());
18             Using<ushort>(links => links.TestCRUDOperations());
19             Using<uint>(links => links.TestCRUDOperations());
20             Using<ulong>(links => links.TestCRUDOperations());
21         }
22
23         [Fact]
24         public static void RawNumbersCRUDTest()
25         {
26             Using<byte>(links => links.TestRawNumbersCRUDOperations());
27             Using<ushort>(links => links.TestRawNumbersCRUDOperations());
28             Using<uint>(links => links.TestRawNumbersCRUDOperations());
29             Using<ulong>(links => links.TestRawNumbersCRUDOperations());
30         }
31
32         [Fact]
33         public static void MultipleRandomCreationsAndDeletionsTest()
34         {
35             Using<byte>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().Test
36                 ↳ MultipleRandomCreationsAndDeletions(16)); // Cannot use more because current
37                 ↳ implementation of tree cuts out 5 bits from the address space.
38             Using<ushort>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().Te
39                 ↳ stMultipleRandomCreationsAndDeletions(100));
40             Using<uint>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().Test
41                 ↳ MultipleRandomCreationsAndDeletions(100));
42             Using<ulong>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().Tes
43                 ↳ tMultipleRandomCreationsAndDeletions(100));
44         }
45         private static void Using<TLinkAddress>(Action<ILinks<TLinkAddress>> action) where
46             ↳ TLinkAddress : struct
47         {
48             var unitedMemoryLinks = new UnitedMemoryLinks<TLinkAddress>(new
49                 ↳ HeapResizableDirectMemory());
50             using (var logFile = File.Open("linksLogger.txt", FileMode.Create, FileAccess.Write))
51             {
52                 LoggingDecorator<TLinkAddress> links = new(unitedMemoryLinks, logFile);
53                 action(links);
54             }
55
56             File.Delete("db.links");
57             using var ffiLinks = new FFI.UnitedMemoryLinks<TLinkAddress>("db.links");
58             action(ffiLinks);
59         }
60     }
61 }

```

1.120 ./csharp/Platform.Data.Doublets.Tests/ILinksBasicTests.cs

```

1  using System.IO;
2  using Platform.Data.Doublets.Memory.United.Generic;
3  using Platform.Memory;
4  using Xunit;
5
6
7  namespace Platform.Data.Doublets.Tests
8  {

```

```

9     public static class ILinksBasicTests
10    {
11        [Fact]
12        public static void DeleteAllUsages()
13        {
14            var mem = new HeapResizableDirectMemory();
15            var links = new UnitedMemoryLinks<uint>(mem);
16
17            var root = links.CreatePoint();
18
19            var a = links.CreatePoint();
20            var b = links.CreatePoint();
21
22            links.CreateAndUpdate(a, root);
23            links.CreateAndUpdate(b, root);
24
25            Assert.Equal(5U, links.Count());
26
27            links.DeleteAllUsages(root);
28
29            Assert.Equal(3U, links.Count());
30        }
31
32        [Fact]
33        public static void FfiDeleteAllUsages()
34        {
35            File.Delete("db.links");
36            var links = new FFI.UnitedMemoryLinks<uint>("db.links");
37
38            var root = links.CreatePoint();
39
40            var a = links.CreatePoint();
41            var b = links.CreatePoint();
42
43            links.CreateAndUpdate(a, root);
44            links.CreateAndUpdate(b, root);
45
46            Assert.Equal(5U, links.Count());
47
48            links.DeleteAllUsages(root);
49
50            Assert.Equal(3U, links.Count());
51        }
52    }
53 }

```

1.121 ./csharp/Platform.Data.Doublets.Tests/LinksConstantsTests.cs

```

1  using Xunit;
2
3  namespace Platform.Data.Doublets.Tests
4  {
5      public static class LinksConstantsTests
6      {
7          [Fact]
8          public static void ExternalReferencesTest()
9          {
10              LinksConstants<ulong> constants = new LinksConstants<ulong>((1, long.MaxValue),
11                  ↪ (long.MaxValue + 1UL, ulong.MaxValue));
12
13              //var minimum = new Hybrid<ulong>(0, isExternal: true);
14              var minimum = new Hybrid<ulong>(1, isExternal: true);
15              var maximum = new Hybrid<ulong>(long.MaxValue, isExternal: true);
16
17              Assert.True(constants.IsExternalReference(minimum));
18              Assert.True(constants.IsExternalReference(maximum));
19          }
20      }
21  }

```

1.122 ./csharp/Platform.Data.Doublets.Tests/ResizableDirectMemoryLinksTests.cs

```

1  using System.IO;
2  using Xunit;
3  using Platform.Singletons;
4  using Platform.Memory;
5  using Platform.Data.Doublets.Memory.United.Specific;
6
7  namespace Platform.Data.Doublets.Tests
8  {
9      public static class ResizableDirectMemoryLinksTests
10     {

```

```

11 private static readonly LinksConstants<ulong> _constants =
    ↳ Default<LinksConstants<ulong>>.Instance;
12
13 [Fact]
14 public static void BasicFileMappedMemoryTest()
15 {
16     var tempFilename = Path.GetTempFileName();
17     using (var memoryAdapter = new UInt64UnitedMemoryLinks(tempFilename))
18     {
19         memoryAdapter.TestBasicMemoryOperations();
20     }
21     File.Delete(tempFilename);
22 }
23
24 [Fact]
25 public static void BasicHeapMemoryTest()
26 {
27     using (var memory = new
    ↳ HeapResizableDirectMemory(UInt64UnitedMemoryLinks.DefaultLinksSizeStep))
28     using (var memoryAdapter = new UInt64UnitedMemoryLinks(memory,
    ↳ UInt64UnitedMemoryLinks.DefaultLinksSizeStep))
29     {
30         memoryAdapter.TestBasicMemoryOperations();
31     }
32 }
33 private static void TestBasicMemoryOperations(this ILinks<ulong> memoryAdapter)
34 {
35     var link = memoryAdapter.Create();
36     memoryAdapter.Delete(link);
37 }
38
39 [Fact]
40 public static void NonexistentReferencesHeapMemoryTest()
41 {
42     using (var memory = new
    ↳ HeapResizableDirectMemory(UInt64UnitedMemoryLinks.DefaultLinksSizeStep))
43     using (var memoryAdapter = new UInt64UnitedMemoryLinks(memory,
    ↳ UInt64UnitedMemoryLinks.DefaultLinksSizeStep))
44     {
45         memoryAdapter.TestNonexistentReferences();
46     }
47 }
48 private static void TestNonexistentReferences(this ILinks<ulong> memoryAdapter)
49 {
50     var link = memoryAdapter.Create();
51     memoryAdapter.Update(link, ulong.MaxValue, ulong.MaxValue);
52     var resultLink = _constants.Null;
53     memoryAdapter.Each(foundLink =>
54     {
55         resultLink = memoryAdapter.GetIndex(foundLink);
56         return _constants.Break;
57     }, _constants.Any, ulong.MaxValue, ulong.MaxValue);
58     Assert.True(resultLink == link);
59     Assert.True(memoryAdapter.Count(ulong.MaxValue) == 0);
60     memoryAdapter.Delete(link);
61 }
62 }
63 }

```

1.123 ./csharp/Platform.Data.Doublets.Tests/ScopeTests.cs

```

1 using Xunit;
2 using Platform.Scopes;
3 using Platform.Memory;
4 using Platform.Data.Doublets.Decorators;
5 using Platform.Reflection;
6 using Platform.Data.Doublets.Memory.United.Generic;
7 using Platform.Data.Doublets.Memory.United.Specific;
8
9 namespace Platform.Data.Doublets.Tests
10 {
11     public static class ScopeTests
12     {
13         [Fact]
14         public static void SingleDependencyTest()
15         {
16             using (var scope = new Scope())
17             {
18                 scope.IncludeAssemblyOf<IMemory>();
19                 var instance = scope.Use<IDirectMemory>();

```

```

20         Assert.IsType<HeapResizableDirectMemory>(instance);
21     }
22 }
23
24 [Fact]
25 public static void CascadeDependencyTest()
26 {
27     using (var scope = new Scope())
28     {
29         scope.Include<TemporaryFileMappedResizableDirectMemory>();
30         scope.Include<UInt64UnitedMemoryLinks>();
31         var instance = scope.Use<ILinks<ulong>>();
32         Assert.IsType<UInt64UnitedMemoryLinks>(instance);
33     }
34 }
35
36 [Fact(Skip = "Would be fixed later.")]
37 public static void FullAutoResolutionTest()
38 {
39     using (var scope = new Scope(autoInclude: true, autoExplore: true))
40     {
41         var instance = scope.Use<UInt64Links>();
42         Assert.IsType<UInt64Links>(instance);
43     }
44 }
45
46 [Fact]
47 public static void TypeParametersTest()
48 {
49     using (var scope = new Scope<Types<HeapResizableDirectMemory,
50 ↪ UnitedMemoryLinks<ulong>>>())
51     {
52         var links = scope.Use<ILinks<ulong>>();
53         Assert.IsType<UnitedMemoryLinks<ulong>>(links);
54     }
55 }
56 }

```

1.124 ./csharp/Platform.Data.Doublets.Tests/SplitMemoryGenericLinksTests.cs

```

1  using System;
2  using Xunit;
3  using Platform.Memory;
4  using Platform.Data.Doublets.Memory.Split.Generic;
5  using Platform.Data.Doublets.Memory;
6
7  namespace Platform.Data.Doublets.Tests
8  {
9      public unsafe static class SplitMemoryGenericLinksTests
10     {
11         [Fact]
12         public static void CRUDTest()
13         {
14             Using<byte>(links => links.TestCRUDOperations());
15             Using<ushort>(links => links.TestCRUDOperations());
16             Using<uint>(links => links.TestCRUDOperations());
17             Using<ulong>(links => links.TestCRUDOperations());
18         }
19
20         [Fact]
21         public static void RawNumbersCRUDTest()
22         {
23             UsingWithExternalReferences<byte>(links => links.TestRawNumbersCRUDOperations());
24             UsingWithExternalReferences<ushort>(links => links.TestRawNumbersCRUDOperations());
25             UsingWithExternalReferences<uint>(links => links.TestRawNumbersCRUDOperations());
26             UsingWithExternalReferences<ulong>(links => links.TestRawNumbersCRUDOperations());
27         }
28
29         [Fact]
30         public static void MultipleRandomCreationsAndDeletionsTest()
31         {
32             Using<byte>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().Test
33 ↪ MultipleRandomCreationsAndDeletions(16)); // Cannot use more because current
34 ↪ implementation of tree cuts out 5 bits from the address space.
35             Using<ushort>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().Te
36 ↪ stMultipleRandomCreationsAndDeletions(100));
37             Using<uint>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().Test
38 ↪ MultipleRandomCreationsAndDeletions(100));

```



```

35         Using<ulong>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().TestMultipleRandomCreationsAndDeletions(100));
36     }
37     private static void Using<TLinkAddress>(Action<ILinks<TLinkAddress>> action) where
38     ↪ TLinkAddress : struct
39     {
40         using (var dataMemory = new HeapResizableDirectMemory())
41         using (var indexMemory = new HeapResizableDirectMemory())
42         using (var memory = new SplitMemoryLinks<TLinkAddress>(dataMemory, indexMemory))
43         {
44             action(memory);
45         }
46     }
47     private static void
48     ↪ UsingWithExternalReferences<TLinkAddress>(Action<ILinks<TLinkAddress>> action) where
49     ↪ TLinkAddress : struct
50     {
51         var constants = new LinksConstants<TLinkAddress>(enableExternalReferencesSupport:
52         ↪ true);
53         using (var dataMemory = new HeapResizableDirectMemory())
54         using (var indexMemory = new HeapResizableDirectMemory())
55         using (var memory = new SplitMemoryLinks<TLinkAddress>(dataMemory, indexMemory,
56         ↪ SplitMemoryLinks<TLinkAddress>.DefaultLinksSizeStep, constants))
57         {
58             action(memory);
59         }
60     }
61 }
62 }

```

1.125 ./csharp/Platform.Data.Doublets.Tests/SplitMemoryUInt32LinksTests.cs

```

1  using System;
2  using Xunit;
3  using Platform.Memory;
4  using Platform.Data.Doublets.Memory.Split.Specific;
5  using TLinkAddress = System.UInt32;
6
7  namespace Platform.Data.Doublets.Tests
8  {
9      public unsafe static class SplitMemoryUInt32LinksTests
10     {
11         [Fact]
12         public static void CRUDTest()
13         {
14             Using(links => links.TestCRUDOperations());
15         }
16
17         [Fact]
18         public static void RawNumbersCRUDTest()
19         {
20             UsingWithExternalReferences(links => links.TestRawNumbersCRUDOperations());
21         }
22
23         [Fact]
24         public static void MultipleRandomCreationsAndDeletionsTest()
25         {
26             Using(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().TestMultipleRandomCreationsAndDeletions(500));
27         }
28         private static void Using(Action<ILinks<TLinkAddress>> action)
29         {
30             using (var dataMemory = new HeapResizableDirectMemory())
31             using (var indexMemory = new HeapResizableDirectMemory())
32             using (var memory = new UInt32SplitMemoryLinks(dataMemory, indexMemory))
33             {
34                 action(memory);
35             }
36         }
37         private static void UsingWithExternalReferences(Action<ILinks<TLinkAddress>> action)
38         {
39             var constants = new LinksConstants<TLinkAddress>(enableExternalReferencesSupport:
40             ↪ true);
41             using (var dataMemory = new HeapResizableDirectMemory())
42             using (var indexMemory = new HeapResizableDirectMemory())
43             using (var memory = new UInt32SplitMemoryLinks(dataMemory, indexMemory,
44             ↪ UInt32SplitMemoryLinks.DefaultLinksSizeStep, constants))
45             {
46                 action(memory);
47             }
48         }
49     }
50 }

```

```

45     }
46 }
47 }
48 }

```

1.126 ./csharp/Platform.Data.Doublets.Tests/SplitMemoryUInt64LinksTests.cs

```

1  using System;
2  using Xunit;
3  using Platform.Memory;
4  using Platform.Data.Doublets.Memory.Split.Specific;
5  using TLinkAddress = System.UInt64;
6
7  namespace Platform.Data.Doublets.Tests
8  {
9      public unsafe static class SplitMemoryUInt64LinksTests
10     {
11         [Fact]
12         public static void CRUDTest()
13         {
14             Using(links => links.TestCRUDOperations());
15         }
16
17         [Fact]
18         public static void RawNumbersCRUDTest()
19         {
20             UsingWithExternalReferences(links => links.TestRawNumbersCRUDOperations());
21         }
22
23         [Fact]
24         public static void MultipleRandomCreationsAndDeletionsTest()
25         {
26             Using(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().TestMultipleRandomCreationsAndDeletions(500));
27         }
28         private static void Using(Action<ILinks<TLinkAddress>> action)
29         {
30             using (var dataMemory = new HeapResizableDirectMemory())
31             using (var indexMemory = new HeapResizableDirectMemory())
32             using (var memory = new UInt64SplitMemoryLinks(dataMemory, indexMemory))
33             {
34                 action(memory);
35             }
36         }
37         private static void UsingWithExternalReferences(Action<ILinks<TLinkAddress>> action)
38         {
39             var constants = new LinksConstants<TLinkAddress>(enableExternalReferencesSupport:
40                 true);
41             using (var dataMemory = new HeapResizableDirectMemory())
42             using (var indexMemory = new HeapResizableDirectMemory())
43             using (var memory = new UInt64SplitMemoryLinks(dataMemory, indexMemory,
44                 UInt64SplitMemoryLinks.DefaultLinksSizeStep, constants))
45             {
46                 action(memory);
47             }
48         }
49     }
50 }

```

1.127 ./csharp/Platform.Data.Doublets.Tests/TestExtensions.cs

```

1  using System.Collections.Generic;
2  using Xunit;
3  using Platform.Ranges;
4  using Platform.Numbers;
5  using Platform.Random;
6  using Platform.Setters;
7  using Platform.Converters;
8
9  namespace Platform.Data.Doublets.Tests
10 {
11     public static class TestExtensions
12     {
13         public static void TestCRUDOperations<T>(this ILinks<T> links) where T : struct
14         {
15             var constants = links.Constants;
16
17             var equalityComparer = EqualityComparer<T>.Default;
18
19             var zero = default(T);
20             var one = Arithmetic.Increment(zero);

```

```

21
22 // Create Link
23 Assert.True(equalityComparer.Equals(links.Count(), zero));
24
25 var setter = new Setter<T>(constants.Null);
26 links.Each(constants.Any, constants.Any, setter.SetAndReturnTrue);
27
28 Assert.True(equalityComparer.Equals(setter.Result, constants.Null));
29
30 var linkAddress = links.Create();
31
32 var link = new Link<T>(links.GetLink(linkAddress));
33
34 Assert.True(link.Count == 3);
35 Assert.True(equalityComparer.Equals(link.Index, linkAddress));
36 Assert.True(equalityComparer.Equals(link.Source, constants.Null));
37 Assert.True(equalityComparer.Equals(link.Target, constants.Null));
38
39 Assert.True(equalityComparer.Equals(links.Count(), one));
40
41 // Get first link
42 setter = new Setter<T>(constants.Null);
43 links.Each(constants.Any, constants.Any, setter.SetAndReturnFalse);
44
45 Assert.True(equalityComparer.Equals(setter.Result, linkAddress));
46
47 // Update link to reference itself
48 links.Update(linkAddress, linkAddress, linkAddress);
49
50 link = new Link<T>(links.GetLink(linkAddress));
51
52 Assert.True(equalityComparer.Equals(link.Source, linkAddress));
53 Assert.True(equalityComparer.Equals(link.Target, linkAddress));
54
55 // Update link to reference null (prepare for delete)
56 var updated = links.Update(linkAddress, constants.Null, constants.Null);
57
58 Assert.True(equalityComparer.Equals(updated, linkAddress));
59
60 link = new Link<T>(links.GetLink(linkAddress));
61
62 Assert.True(equalityComparer.Equals(link.Source, constants.Null));
63 Assert.True(equalityComparer.Equals(link.Target, constants.Null));
64
65 // Delete link
66 links.Delete(linkAddress);
67
68 Assert.True(equalityComparer.Equals(links.Count(), zero));
69
70 setter = new Setter<T>(constants.Null);
71 links.Each(constants.Any, constants.Any, setter.SetAndReturnTrue);
72
73 Assert.True(equalityComparer.Equals(setter.Result, constants.Null));
74 }
75
76 public static void TestRawNumbersCRUDOperations<T>(this ILinks<T> links) where T : struct
77 {
78 // Constants
79 var constants = links.Constants;
80 var equalityComparer = EqualityComparer<T>.Default;
81
82 var zero = default(T);
83 var one = Arithmetic.Increment(zero);
84 var two = Arithmetic.Increment(one);
85
86 var h106E = new Hybrid<T>(106L, isExternal: true);
87 var h107E = new Hybrid<T>(-char.ConvertFromUtf32(107)[0]);
88 var h108E = new Hybrid<T>(-108L);
89
90 Assert.Equal(106L, h106E.AbsoluteValue);
91 Assert.Equal(107L, h107E.AbsoluteValue);
92 Assert.Equal(108L, h108E.AbsoluteValue);
93
94 // Create Link (External -> External)
95 var linkAddress1 = links.Create();
96
97 links.Update(linkAddress1, h106E, h108E);
98
99 var link1 = new Link<T>(links.GetLink(linkAddress1));
100

```

```

101 Assert.True(equalityComparer.Equals(link1.Source, h106E));
102 Assert.True(equalityComparer.Equals(link1.Target, h108E));
103
104 // Create Link (Internal -> External)
105 var linkAddress2 = links.Create();
106
107 links.Update(linkAddress2, linkAddress1, h108E);
108
109 var link2 = new Link<T>(links.GetLink(linkAddress2));
110
111 Assert.True(equalityComparer.Equals(link2.Source, linkAddress1));
112 Assert.True(equalityComparer.Equals(link2.Target, h108E));
113
114 // Create Link (Internal -> Internal)
115 var linkAddress3 = links.Create();
116
117 links.Update(linkAddress3, linkAddress1, linkAddress2);
118
119 var link3 = new Link<T>(links.GetLink(linkAddress3));
120
121 Assert.True(equalityComparer.Equals(link3.Source, linkAddress1));
122 Assert.True(equalityComparer.Equals(link3.Target, linkAddress2));
123
124 // Search for created link
125 var setter1 = new Setter<T>(constants.Null);
126 links.Each(h106E, h108E, setter1.SetAndReturnFalse);
127
128 Assert.True(equalityComparer.Equals(setter1.Result, linkAddress1));
129
130 // Search for nonexistent link
131 var setter2 = new Setter<T>(constants.Null);
132 links.Each(h106E, h107E, setter2.SetAndReturnFalse);
133
134 Assert.True(equalityComparer.Equals(setter2.Result, constants.Null));
135
136 // Update link to reference null (prepare for delete)
137 var updated = links.Update(linkAddress3, constants.Null, constants.Null);
138
139 Assert.True(equalityComparer.Equals(updated, linkAddress3));
140
141 link3 = new Link<T>(links.GetLink(linkAddress3));
142
143 Assert.True(equalityComparer.Equals(link3.Source, constants.Null));
144 Assert.True(equalityComparer.Equals(link3.Target, constants.Null));
145
146 // Delete link
147 links.Delete(linkAddress3);
148
149 Assert.True(equalityComparer.Equals(links.Count(), two));
150
151 var setter3 = new Setter<T>(constants.Null);
152 links.Each(constants.Any, constants.Any, setter3.SetAndReturnTrue);
153
154 Assert.True(equalityComparer.Equals(setter3.Result, linkAddress2));
155 }
156
157 public static void TestMultipleCreationsAndDeletions<TLinkAddress>(this
↪ ILinks<TLinkAddress> links, int numberOfOperations)
158 {
159     for (int i = 0; i < numberOfOperations; i++)
160     {
161         links.Create();
162     }
163     for (int i = 0; i < numberOfOperations; i++)
164     {
165         links.Delete(links.Count());
166     }
167 }
168
169 public static void TestMultipleRandomCreationsAndDeletions<TLinkAddress>(this
↪ ILinks<TLinkAddress> links, int maximumOperationsPerCycle) where TLinkAddress :
↪ struct
170 {
171     var comparer = Comparer<TLinkAddress>.Default;
172     var addressToUInt64Converter = CheckedConverter<TLinkAddress, ulong>.Default;
173     var uint64ToAddressConverter = CheckedConverter<ulong, TLinkAddress>.Default;
174     for (var N = 1; N < maximumOperationsPerCycle; N++)
175     {
176         var random = new System.Random(N);
177         var created = 0UL;

```

```

178     var deleted = 0UL;
179     for (var i = 0; i < N; i++)
180     {
181         var linksCount = addressToUInt64Converter.Convert(links.Count());
182         var createPoint = random.NextBoolean();
183         if (linksCount >= 2 && createPoint)
184         {
185             var linksAddressRange = new Range<ulong>(1, linksCount);
186             TLinkAddress source = uInt64ToAddressConverter.Convert(random.NextUInt64
187                 ↪ (linksAddressRange));
188             TLinkAddress target = uInt64ToAddressConverter.Convert(random.NextUInt64
189                 ↪ (linksAddressRange));
190             ↪ //-V3086
191             var resultLink = links.GetOrCreate(source, target);
192             if (comparer.Compare(resultLink,
193                 ↪ uInt64ToAddressConverter.Convert(linksCount)) > 0)
194             {
195                 created++;
196             }
197         }
198         else
199         {
200             links.Create();
201             created++;
202         }
203     }
204     Assert.True(created == addressToUInt64Converter.Convert(links.Count()));
205     for (var i = 0; i < N; i++)
206     {
207         TLinkAddress link = uInt64ToAddressConverter.Convert((ulong)i + 1UL);
208         if (links.Exists(link))
209         {
210             links.Delete(link);
211             deleted++;
212         }
213     }
214     Assert.True(addressToUInt64Converter.Convert(links.Count()) == 0L);
215 }
216 }
217 }
218 }

```

1.128 ./csharp/Platform.Data.Doublets.Tests/UInt64LinksExtensionsTests.cs

```

1  using Platform.Data.Doublets.Memory;
2  using Platform.Data.Doublets.Memory.United.Generic;
3  using Platform.Data.Numbers.Raw;
4  using Platform.Memory;
5  using Platform.Numbers;
6  using Xunit;
7  using Xunit.Abstractions;
8  using TLinkAddress = System.UInt64;
9
10 namespace Platform.Data.Doublets.Tests
11 {
12     public class UInt64LinksExtensionsTests
13     {
14         public static ILinks<TLinkAddress> CreateLinks() => CreateLinks<TLinkAddress>(new
15             ↪ Platform.IO.TemporaryFile());
16
17         public static ILinks<TLinkAddress> CreateLinks<TLinkAddress>(string dataDBFilename)
18             ↪ where TLinkAddress : struct
19         {
20             var linksConstants = new
21                 ↪ LinksConstants<TLinkAddress>(enableExternalReferencesSupport: true);
22             return new UnitedMemoryLinks<TLinkAddress>(new
23                 ↪ FileMappedResizableDirectMemory(dataDBFilename),
24                 ↪ UnitedMemoryLinks<TLinkAddress>.DefaultLinksSizeStep, linksConstants,
25                 ↪ IndexTreeType.Default);
26         }
27
28         [Fact]
29         public void FormatStructureWithExternalReferenceTest()
30         {
31             ILinks<TLinkAddress> links = CreateLinks();
32             TLinkAddress zero = default;
33             var one = Arithmetic.Increment(zero);
34             var markerIndex = one;
35             var meaningRoot = links.GetOrCreate(markerIndex, markerIndex);
36             var numberMarker = links.GetOrCreate(meaningRoot, Arithmetic.Increment(ref
37                 ↪ markerIndex));
38         }
39     }
40 }

```

```

30         AddressToRawNumberConverter<TLinkAddress> addressToNumberConverter = new();
31         var numberAddress = addressToNumberConverter.Convert(1);
32         var numberLink = links.GetOrCreate(numberMarker, numberAddress);
33         var linkNotation = links.FormatStructure(numberLink, link => link.IsFullPoint(),
34             ↪ true);
35         Assert.Equal("(3:(2:1 2) 18446744073709551615)", linkNotation);
36     }
37 }

```

1.129 ./csharp/Platform.Data.Doublets.Tests/UnitedMemoryUInt32LinksTests.cs

```

1  using System;
2  using Xunit;
3  using Platform.Reflection;
4  using Platform.Memory;
5  using Platform.Scopes;
6  using Platform.Data.Doublets.Memory.United.Specific;
7  using TLinkAddress = System.UInt32;
8
9  namespace Platform.Data.Doublets.Tests
10 {
11     public unsafe static class UnitedMemoryUInt32LinksTests
12     {
13         [Fact]
14         public static void CRUDTest()
15         {
16             Using(links => links.TestCRUDOperations());
17         }
18
19         [Fact]
20         public static void RawNumbersCRUDTest()
21         {
22             Using(links => links.TestRawNumbersCRUDOperations());
23         }
24
25         [Fact]
26         public static void MultipleRandomCreationsAndDeletionsTest()
27         {
28             Using(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().TestMultipleRandomCreationsAndDeletions(100));
29         }
30         private static void Using(Action<ILinks<TLinkAddress>> action)
31         {
32             using (var scope = new Scope<Types<HeapResizableDirectMemory,
33                 ↪ UInt32UnitedMemoryLinks>>())
34             {
35                 action(scope.Use<ILinks<TLinkAddress>>());
36             }
37         }
38     }

```

1.130 ./csharp/Platform.Data.Doublets.Tests/UnitedMemoryUInt64LinksTests.cs

```

1  using System;
2  using Xunit;
3  using Platform.Reflection;
4  using Platform.Memory;
5  using Platform.Scopes;
6  using Platform.Data.Doublets.Memory.United.Specific;
7  using TLinkAddress = System.UInt64;
8
9  namespace Platform.Data.Doublets.Tests
10 {
11     public unsafe static class UnitedMemoryUInt64LinksTests
12     {
13         [Fact]
14         public static void CRUDTest()
15         {
16             Using(links => links.TestCRUDOperations());
17         }
18
19         [Fact]
20         public static void RawNumbersCRUDTest()
21         {
22             Using(links => links.TestRawNumbersCRUDOperations());
23         }
24
25         [Fact]
26         public static void MultipleRandomCreationsAndDeletionsTest()

```

```

27     {
28         Using(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().TestMultip
            ↳ leRandomCreationsAndDeletions(100));
29     }
30     private static void Using(Action<ILinks<TLinkAddress>> action)
31     {
32         using (var scope = new Scope<Types<HeapResizableDirectMemory,
            ↳ UInt64UnitedMemoryLinks>>())
33         {
34             action(scope.Use<ILinks<TLinkAddress>>());
35         }
36     }
37 }
38 }

```

Index

`./csharp/Platform.Data.Doublets.Tests/GenericLinksTests.cs`, 461
`./csharp/Platform.Data.Doublets.Tests/ILinksBasicTests.cs`, 461
`./csharp/Platform.Data.Doublets.Tests/LinksConstantsTests.cs`, 462
`./csharp/Platform.Data.Doublets.Tests/ResizableDirectMemoryLinksTests.cs`, 462
`./csharp/Platform.Data.Doublets.Tests/ScopeTests.cs`, 463
`./csharp/Platform.Data.Doublets.Tests/SplitMemoryGenericLinksTests.cs`, 464
`./csharp/Platform.Data.Doublets.Tests/SplitMemoryUInt32LinksTests.cs`, 465
`./csharp/Platform.Data.Doublets.Tests/SplitMemoryUInt64LinksTests.cs`, 466
`./csharp/Platform.Data.Doublets.Tests/TestExtensions.cs`, 466
`./csharp/Platform.Data.Doublets.Tests/UInt64LinksExtensionsTests.cs`, 469
`./csharp/Platform.Data.Doublets.Tests/UnitedMemoryUInt32LinksTests.cs`, 470
`./csharp/Platform.Data.Doublets.Tests/UnitedMemoryUInt64LinksTests.cs`, 470
`./csharp/Platform.Data.Doublets/CriterionMatchers/TargetMatcher.cs`, 1
`./csharp/Platform.Data.Doublets/Decorators/LinksCascadeUniquenessAndUsagesResolver.cs`, 1
`./csharp/Platform.Data.Doublets/Decorators/LinksCascadeUsagesResolver.cs`, 2
`./csharp/Platform.Data.Doublets/Decorators/LinksDecoratorBase.cs`, 3
`./csharp/Platform.Data.Doublets/Decorators/LinksDisposableDecoratorBase.cs`, 5
`./csharp/Platform.Data.Doublets/Decorators/LinksInnerReferenceExistenceValidator.cs`, 7
`./csharp/Platform.Data.Doublets/Decorators/LinksItselfConstantToSelfReferenceResolver.cs`, 8
`./csharp/Platform.Data.Doublets/Decorators/LinksNonExistentDependenciesCreator.cs`, 9
`./csharp/Platform.Data.Doublets/Decorators/LinksNullConstantToSelfReferenceResolver.cs`, 10
`./csharp/Platform.Data.Doublets/Decorators/LinksUniquenessResolver.cs`, 11
`./csharp/Platform.Data.Doublets/Decorators/LinksUniquenessValidator.cs`, 13
`./csharp/Platform.Data.Doublets/Decorators/LinksUsagesValidator.cs`, 13
`./csharp/Platform.Data.Doublets/Decorators/LoggingDecorator.cs`, 14
`./csharp/Platform.Data.Doublets/Decorators/NonNullContentsLinkDeletionResolver.cs`, 15
`./csharp/Platform.Data.Doublets/Decorators/UInt32Links.cs`, 16
`./csharp/Platform.Data.Doublets/Decorators/UInt64Links.cs`, 18
`./csharp/Platform.Data.Doublets/Decorators/UniLinks.cs`, 20
`./csharp/Platform.Data.Doublets/Doublet.cs`, 26
`./csharp/Platform.Data.Doublets/DoubletComparer.cs`, 28
`./csharp/Platform.Data.Doublets/FFI/UInt32UnitedMemoryLinks.cs`, 28
`./csharp/Platform.Data.Doublets/FFI/UnitedMemoryLinks.cs`, 30
`./csharp/Platform.Data.Doublets/ILinks.cs`, 39
`./csharp/Platform.Data.Doublets/ILinksExtensions.cs`, 40
`./csharp/Platform.Data.Doublets/ISynchronizedLinks.cs`, 60
`./csharp/Platform.Data.Doublets/Link.cs`, 61
`./csharp/Platform.Data.Doublets/LinkExtensions.cs`, 68
`./csharp/Platform.Data.Doublets/LinksOperatorBase.cs`, 69
`./csharp/Platform.Data.Doublets/Memory/ILinksListMethods.cs`, 70
`./csharp/Platform.Data.Doublets/Memory/ILinksTreeMethods.cs`, 70
`./csharp/Platform.Data.Doublets/Memory/IndexTreeType.cs`, 72
`./csharp/Platform.Data.Doublets/Memory/LinksHeader.cs`, 72
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksRecursionlessSizeBalancedTreeMethodsBase.cs`, 74
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksSizeBalancedTreeMethodsBase.cs`, 81
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods.cs`, 88
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksSourcesSizeBalancedTreeMethods.cs`, 92
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods.cs`, 96
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/ExternalLinksTargetsSizeBalancedTreeMethods.cs`, 100
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksRecursionlessSizeBalancedTreeMethodsBase.cs`, 104
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksSizeBalancedTreeMethodsBase.cs`, 109
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksSourcesLinkedListMethods.cs`, 115
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksSourcesRecursionlessSizeBalancedTreeMethods.cs`, 120
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksSourcesSizeBalancedTreeMethods.cs`, 123
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksTargetsRecursionlessSizeBalancedTreeMethods.cs`, 127
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/InternalLinksTargetsSizeBalancedTreeMethods.cs`, 131
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/SplitMemoryLinks.cs`, 134
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/SplitMemoryLinksBase.cs`, 138
`./csharp/Platform.Data.Doublets/Memory/Split/Generic/UnusedLinksListMethods.cs`, 156
`./csharp/Platform.Data.Doublets/Memory/Split/RawLinkDataPart.cs`, 159
`./csharp/Platform.Data.Doublets/Memory/Split/RawLinkIndexPart.cs`, 160
`./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksRecursionlessSizeBalancedTreeMethodsBase.cs`, 162
`./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksSizeBalancedTreeMethodsBase.cs`, 168
`./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods.cs`, 174
`./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksSourcesSizeBalancedTreeMethods.cs`, 178

./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods.cs, 182
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32ExternalLinksTargetsSizeBalancedTreeMethods.cs, 186
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksRecursionlessSizeBalancedTreeMethodsBase.cs, 190
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksSizeBalancedTreeMethodsBase.cs, 196
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksSourcesLinkedListMethods.cs, 202
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksSourcesRecursionlessSizeBalancedTreeMethods.cs, 203
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksSourcesSizeBalancedTreeMethods.cs, 206
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksTargetsRecursionlessSizeBalancedTreeMethods.cs, 210
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32InternalLinksTargetsSizeBalancedTreeMethods.cs, 214
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32SplitMemoryLinks.cs, 218
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt32UnusedLinksListMethods.cs, 224
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksRecursionlessSizeBalancedTreeMethodsBase.cs, 225
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksSizeBalancedTreeMethodsBase.cs, 231
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksSourcesRecursionlessSizeBalancedTreeMethods.cs, 237
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksSourcesSizeBalancedTreeMethods.cs, 241
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksTargetsRecursionlessSizeBalancedTreeMethods.cs, 245
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64ExternalLinksTargetsSizeBalancedTreeMethods.cs, 249
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksRecursionlessSizeBalancedTreeMethodsBase.cs, 253
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksSizeBalancedTreeMethodsBase.cs, 258
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksSourcesLinkedListMethods.cs, 264
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksSourcesRecursionlessSizeBalancedTreeMethods.cs, 265
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksSourcesSizeBalancedTreeMethods.cs, 269
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksTargetsRecursionlessSizeBalancedTreeMethods.cs, 273
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64InternalLinksTargetsSizeBalancedTreeMethods.cs, 276
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64SplitMemoryLinks.cs, 280
./csharp/Platform.Data.Doublets/Memory/Split/Specific/UInt64UnusedLinksListMethods.cs, 286
./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksAvlBalancedTreeMethodsBase.cs, 287
./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksRecursionlessSizeBalancedTreeMethodsBase.cs, 297
./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksSizeBalancedTreeMethodsBase.cs, 303
./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksSourcesAvlBalancedTreeMethods.cs, 310
./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksSourcesRecursionlessSizeBalancedTreeMethods.cs, 315
./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksSourcesSizeBalancedTreeMethods.cs, 319
./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksTargetsAvlBalancedTreeMethods.cs, 323
./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksTargetsRecursionlessSizeBalancedTreeMethods.cs, 328
./csharp/Platform.Data.Doublets/Memory/United/Generic/LinksTargetsSizeBalancedTreeMethods.cs, 332
./csharp/Platform.Data.Doublets/Memory/United/Generic/UnitedMemoryLinks.cs, 335
./csharp/Platform.Data.Doublets/Memory/United/Generic/UnitedMemoryLinksBase.cs, 338
./csharp/Platform.Data.Doublets/Memory/United/Generic/UnusedLinksListMethods.cs, 351
./csharp/Platform.Data.Doublets/Memory/United/RawLink.cs, 354
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksRecursionlessSizeBalancedTreeMethodsBase.cs, 356
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksSizeBalancedTreeMethodsBase.cs, 362
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksSourcesRecursionlessSizeBalancedTreeMethods.cs, 367
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksSourcesSizeBalancedTreeMethods.cs, 371
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksTargetsRecursionlessSizeBalancedTreeMethods.cs, 375
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32LinksTargetsSizeBalancedTreeMethods.cs, 378
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32UnitedMemoryLinks.cs, 382
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt32UnusedLinksListMethods.cs, 388
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksAvlBalancedTreeMethodsBase.cs, 389
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksRecursionlessSizeBalancedTreeMethodsBase.cs, 396
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksSizeBalancedTreeMethodsBase.cs, 401
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksSourcesAvlBalancedTreeMethods.cs, 407
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksSourcesRecursionlessSizeBalancedTreeMethods.cs, 412
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksSourcesSizeBalancedTreeMethods.cs, 416
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksTargetsAvlBalancedTreeMethods.cs, 420
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksTargetsRecursionlessSizeBalancedTreeMethods.cs, 425
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64LinksTargetsSizeBalancedTreeMethods.cs, 429
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64UnitedMemoryLinks.cs, 433
./csharp/Platform.Data.Doublets/Memory/United/Specific/UInt64UnusedLinksListMethods.cs, 438
./csharp/Platform.Data.Doublets/PropertyOperators/PropertiesOperator.cs, 439
./csharp/Platform.Data.Doublets/PropertyOperators/PropertyOperator.cs, 441
./csharp/Platform.Data.Doublets/Stacks/Stack.cs, 442
./csharp/Platform.Data.Doublets/Stacks/StackExtensions.cs, 444

./csharp/Platform.Data.Doublets/SynchronizedLinks.cs, 444
./csharp/Platform.Data.Doublets/UInt64LinksExtensions.cs, 447
./csharp/Platform.Data.Doublets/UInt64LinksTransactionsLayer.cs, 451