

Name _____

CSCI 332, Fall 2026
Exam 1 Practice 1

This exam consists of the following sections:

1. Stable Matching
2. Algorithm Analysis
3. Recursion
4. 1D Dynamic Programming

You may use a double sided 3x5 handwritten notecard of notes during the test but no other resources.

For BUBBLE SHEET sub sections, fill in your answers on the provided bubble sheet. Some questions may have multiple correct answers; be sure to select all that apply.

For HANDWRITTEN subsections, write your answers on the exam paper.

Good luck!

Section 1 (Stable Matching)

Bubble sheet

1. Is $\{(h_1, s_4), (h_2, s_1), (h_3, s_3), (h_4, s_2)\}$ a stable matching for the given preference lists?

Hospital	Preferences	Student	Preferences
h_1	s_2, s_3, s_4, s_1	s_1	h_3, h_1, h_2, h_4
h_2	s_1, s_3, s_2, s_4	s_2	h_2, h_3, h_4, h_1
h_3	s_3, s_4, s_2, s_1	s_3	h_3, h_2, h_4, h_1
h_4	s_1, s_3, s_2, s_4	s_4	h_4, h_1, h_3, h_2

Select A for yes and B for no.

2. Given the matching $\{(h_4, s_1), (h_1, s_3), (h_3, s_4), (h_2, s_2)\}$ and the preference lists below, select all unstable pairs from the list.

Hospital	Preferences	Student	Preferences
h_1	s_1, s_2, s_3, s_4	s_1	h_3, h_2, h_1, h_4
h_2	s_1, s_2, s_4, s_3	s_2	h_1, h_2, h_3, h_4
h_3	s_2, s_1, s_3, s_4	s_3	h_1, h_3, h_4, h_2
h_4	s_4, s_2, s_3, s_1	s_4	h_3, h_4, h_2, h_1

- A. (h_4, s_1)
- B. (h_2, s_4)
- C. (h_2, s_1)
- D. (h_3, s_3)
- E. (h_1, s_2)

The following questions refer to the Gale-Shapley algorithm for stable matching.

Gale-Shapley(preference lists for n hospitals and n students)

Let M be an empty matching

While some hospital h is unmatched and hasn't proposed to every student:

Let s be the first student on h 's list to whom h has not yet proposed

If s is unmatched:

Add (h, s) to M

Else s is matched to h' :

If s prefers h to h' :

Remove (h', s) from M

Add (h, s) to M

Else s prefers h' to h :

Do nothing

Return M

3. Does the Gale-Shapley algorithm always terminate with a stable matching? Select A for yes and B for no.

4. Are there inputs for which the Gale-Shapley algorithm runs in $\Theta(n)$ time? Select A for yes and B for no.
5. Are there inputs for which the Gale-Shapley algorithm runs in $\Theta(n^2)$ time? Select A for yes and B for no.
6. Are there inputs for which the Gale-Shapley algorithm runs in $\Theta(n^3)$ time? Select A for yes and B for no.
7. What is the stable matching returned by the Gale-Shapley algorithm on the following preference list?

Hospital	Preferences	Student	Preferences
h_1	s_1, s_2, s_3, s_4	s_1	h_3, h_2, h_1, h_4
h_2	s_1, s_2, s_4, s_3	s_2	h_1, h_2, h_3, h_4
h_3	s_2, s_1, s_3, s_4	s_3	h_1, h_3, h_4, h_2
h_4	s_4, s_2, s_3, s_1	s_4	h_3, h_4, h_2, h_1

- A. $\{(h_1, s_1), (h_2, s_1), (h_3, s_2), (h_4, s_4)\}$
 - B. $\{(h_1, s_1), (h_2, s_2), (h_3, s_3), (h_4, s_4)\}$
 - C. $\{(h_1, s_4), (h_2, s_3), (h_3, s_1), (h_4, s_2)\}$
 - D. $\{(h_1, s_2), (h_2, s_3), (h_3, s_1), (h_4, s_4)\}$
 - E. $\{(h_1, s_3), (h_2, s_1), (h_3, s_4), (h_4, s_2)\}$
8. (5 points) True or false? In every instance of the Stable Matching Problem, there is a stable matching containing a pair (m, w) such that m is ranked first on the preference list of w and w is ranked first on the preference list of m . Select A for true and B for false.

Section 2 (Algorithm Analysis)

Bubble sheet

9. Recall that the definition of big O is as follows: $f(n)$ is $O(g(n))$ if there exist positive constants c and n_0 such that for all $n \geq n_0$, $f(n) \leq c \cdot g(n)$. Which n_0 and c can be used to show that $9n^2 + n + 10$ is $O(n^3)$?
- A. $n_0 = 1, c = 4$
 - B. $n_0 = 1, c = 10$
 - C. $n_0 = 1, c = 1000$
 - D. $n_0 = 10, c = 4$
 - E. $n_0 = 100, c = 1$
10. Select all of the true statements below.
- A. $\log(100 \cdot n^{5n})$ is $\Theta(n \log n)$
 - B. $\log(100 \cdot n^{5n})$ is $\Theta(n^n)$
 - C. $\log(100 \cdot n^{5n})$ is $\Theta(5^n)$
 - D. $\log(100 \cdot n^{5n})$ is $\Theta(n^n \log n)$
 - E. $\log(100 \cdot n^{5n})$ is $\Theta(n^5 \log 100)$
11. Select all the functions that are $O(n^2)$.
- A. $5n^2 + 3n + 20$
 - B. $n \log n$
 - C. $n^2 + n \log n$
 - D. $0.5n^2 - 10n + 2000$
 - E. n^3
12. Select all functions that are $\Omega(n^2)$.
- A. $5n^2 + 3n + 20$
 - B. $n \log n$
 - C. $n^2 + n \log n$
 - D. $0.5n^2 - 10n + 2000$
 - E. n^3
13. Select all functions that are $\Theta(n^2)$.
- A. $5n^2 + 3n + 20$
 - B. $n \log n$
 - C. $n^2 + n \log n$
 - D. $0.5n^2 - 10n + 2000$

E. n^3

14. Select all functions $f(n)$ such that the worst-case runtime of Algorithm-1 below is $\Theta(f(n))$.

```
Algorithm-1(array A of length n):
    Result = 0
    For each i in 1 to n:
        For each j in 1 to i:
            Set Result to A[j] times Result
    Return Result
```

- A. n
B. $\log n$
C. n^2
D. n^3
E. $n!$

Handwritten

15. (10 points) You suspect that in the most recent update to your favorite software package, the implementation of your favorite function `do-stuff` was replaced by a $\Theta(n^2)$ algorithm, whereas it was a $\Theta(n^3)$ algorithm before. Whatever the runtime is, you know that it is the same for all input classes (that is, the worst case and best case runtimes are equal). Unfortunately, the package is closed-source and you cannot inspect the source code; you can only run the function on various-sized inputs and record its runtime on those inputs. Describe an experiment that you could run to verify your hunch. That is, tell us what kinds of input sizes you will run `do-stuff` on and how you will use their runtimes to determine whether the algorithm is $\Theta(n^2)$ or $\Theta(n^3)$.
16. (10 points) Consider the following algorithm to determine whether a number can be written as the sum of two perfect squares. For example, $40 = 4 + 36 = 2^2 + 6^2$, so `SumOfSquares(40)` returns true, whereas `SumOfSquares(42)` returns false, because there are no integers a, b so that $42 = a^2 + b^2$.

```
SumOfSquares(n):
    a = 0
    b =  $\lfloor \sqrt{n} \rfloor$ 
    while a <= b:
        s =  $a^2 + b^2$ 
        if s == n:
            return true
        if s < n:
            a = a + 1
        else:
            b = b - 1
    return false
```

- (a) Describe the class of best-case inputs and give the simplest $f(n)$ so that their runtime is $\Theta(f(n))$.
- (b) Describe the class of worst-case inputs and give the simplest $f(n)$ so that their runtime is $\Theta(f(n))$.

Section 3 (Recursion)

Handwritten

17. (10 points) Given the following (meaningless) divide and conquer algorithm, what is the recurrence relation that describes its running time?

```

wut(integer array A of length n):
  if  $n \leq 1$ :
    return A
  else:
    Let  $A_1, A_2, A_3$  be the first third, middle third, and last third of A
     $X_1 = \text{wut}(A_1)$ 
     $X_2 = \text{wut}(A_2)$ 
     $X_3 = \text{wut}(A_3)$ 
    let array C be a new array of length n
    for i from 1 to n:
      for j from 1 to n:
         $C[i \% j] = \text{first element of } X_1 + \text{middle element of } X_2 + \text{last element of } X_3$ 
    return C

```

$$T(1) = \underline{\hspace{2cm}}$$

$$T(n) = \frac{\text{work done by recursive calls}}{\text{work done by recursive calls}} + \frac{\text{nonrecursive work}}{\text{nonrecursive work}}$$

18. (15 points)

Consider the recurrence $T(n) = 4T(n/3) + n, T(1) = 1$.

- (a) (5 points) In the left boxes, draw the first three levels of this recursion tree. In the boxes next to them, write the total work on that level.

Level 0	Sum level 0
Level 1	Sum level 1
Level 2	Sum level 2

(b) (3 points) What is the work per level in terms of level ℓ ?

(c) (2 points) Is the work per level (circle one)

- increasing (work is dominated by leaves)
- decreasing (work is dominated by root)
- the same (work is the same at every level)

(d) (3 points) What is the total number of levels in the tree? (fill in the base and the argument of the logarithm)

number of levels = $\log$ _____ (_____)

(e) (2 points) What is the overall non-recursive runtime of the recurrence?

19. (10 points total) In this problem you will write a **divide and conquer** algorithm for the following problem: you are given an array A of n integers (which may be positive, negative, or zero). You know that the array is *unimodal*, meaning that there is an index i^* such that $A[1] < A[2] < \dots < A[i^*]$ and $A[i^*] > A[i^* + 1] > \dots > A[n]$. Your task is to find the index i^* (the index of the maximum element) in $O(\log n)$ time. Assume that the indices start at 1.

For example, if $A = [-1, 3, 3, 5, 8, 12, 4, 2]$, then the output should be 6 since $A[6] = 12$ is the maximum element.

- (a) (2 points) In order to achieve an $O(\log n)$ runtime, you can only make one recursive call per level of recursion, and it must take only constant time. You decide that you will divide the array in half at each step. How will you decide which half on which to make your next recursive call?

(b) (6 points) Write a **recursive** algorithm to find i^* that runs in $O(\log n)$ time.

Max(unimodal array A of length n):

Section 4 (1D Dynamic Programming)

Handwritten

20. (10 points) Given the following (meaningless) recursive definition of a subproblem, draw the recursion tree for a call to $huh(5)$ with each node labeled with the value of the argument to huh .

$$huh(i) = \begin{cases} 4 & \text{if } i = 1 \\ -100 & \text{if } i = 2 \\ 0 & \text{if } i = 3 \\ \min(2 + huh(i-1), huh(i-3)) & \text{if } i > 3 \end{cases}$$

The first node is provided for you.

$huh(5)$

21. (10 points) In this problem, you will need to write the formal recursive definition for the subproblem (step two of our four steps for writing dynamic programming algorithms) for the following problem.

The problem. In your country, there are only coins of denominations 1, 3, and 4. Given a positive integer n , what is the fewest number of coins you can use to represent n ?

To solve this problem, we first write the English definition of the subproblem.

1. **The subproblem.** Let $MinCoins(i)$ be the minimum number of coins needed to represent the amount i .

Next, we think about the recursive relationship between subproblems. You notice that in order to make i , you could either have made $i-1$ and added a 1-coin, or made $i-3$ and added a 3-coin, or made $i-4$ and added a 4-coin. Using this observation, fill in the formal recursive definition for $MinCoins(i)$ below.

2. **The recursive definition.** The recursive relationship can be expressed as: (fill in both recursive case(s) and base case(s). You may not need every line provided!)

$$MinCoins(i) = \begin{cases} \underline{\hspace{10em}} & \text{if } i \underline{\hspace{1em}} \\ \underline{\hspace{10em}} & \text{if } i \underline{\hspace{1em}} \\ \underline{\hspace{10em}} & \text{if } i \underline{\hspace{1em}} \\ \underline{\hspace{10em}} & \text{if } i \underline{\hspace{1em}} \\ \underline{\hspace{10em}} & \text{if } i \underline{\hspace{1em}} \end{cases}$$

22. (10 points) In this problem, you will need to write algorithm pseudocode (step four of our four steps for writing dynamic programming algorithms) for the following problem.

The problem. You are given a rod of length n and a price list $p_1, p_2, \dots, p_n$, where p_i is the price of a rod piece of length i . You may cut the rod into any number of integer-length pieces, or leave it uncut. Each piece of length i sells for p_i , and making cuts has no cost. Describe an algorithm to determine the maximum revenue obtainable from the rod.

To solve this problem, we first write the English definition of the subproblems.

- 1. The subproblem.** Let $MaxRevenue(i)$ be the maximum revenue obtainable from a rod of length i .

Next, we think about the recursive relationship between subproblems. For a rod of length i , the first piece can have any length j from 1 to i . Selling that piece earns p_j , and the remaining rod has length $i - j$. Using this observation, write the formal recursive definition for $MaxRevenue(i)$ below.

- 2. The recursive definition.**

$$MaxRevenue(i) = \begin{cases} 0 & \text{if } i = 0 \\ \max_{1 \leq j \leq i} (p_j + MaxRevenue(i - j)) & \text{if } i > 0 \end{cases}$$

- 3. How to memoize.** We can use an array of length $n + 1$ to store the values of $MaxRevenue(i)$ for $0 \leq i \leq n$ and fill it in increasing order.

- 4. Write the algorithm.** Using the above information, finish the pseudocode to find the maximum revenue obtainable from a rod of length n , given the price list $p[1..n]$.

RodCutting($p[1..n], n$):

Let array R be an array of length $n + 1$

what is the base case?

how should we fill in the rest of the array?

what should we return to get the final answer?