RAJALAKSHMI ENGINEERING COLLEGE

Hari Vignesh L 251801083-2025-AIDS

H2

Started on	Sunday, 30 August 2026, 9:13 PM
State	Finished
Completed on	Sunday, 30 August 2026, 9:14 PM
Time taken	12 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int findMajorityElement(int nums[], int n) {
    int candidate = 0;
    int count = 0;

    // Boyer-Moore Voting Algorithm
    for (int i = 0; i < n; i++) {
        if (count == 0) {
            candidate = nums[i];
            count = 1;
        } else if (nums[i] == candidate) {
            count++;
        } else {
            count--;
        }
    }

    return candidate;
}

int main() {
    int n;
    if (scanf("%d", &n) != 1) return 0;

    int nums[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &nums[i]);
    }

    printf("%d\n", findMajorityElement(nums, n));
    return 0;
}
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course