Replicate: Bounded Self-Replication of a Locally Inferring Software Agent

An Auditable Systems Testbed, Control Experiments, and Generalization Limits

Lars Tray
Georgetown University

October 18, 2026

Abstract

We demonstrate bounded self-replication of a complete, locally inferring software agent across owner-prepared receivers. A parent supplies the signed software package and local model; its child repeats the operation after the seed disappears. The Replicate testbed makes package provenance, local inference, useful operation, and ancestor independence explicit and auditable. On prepared 8 GiB x86-64 Linux guests, three seed–child–grandchild lineages using a fine-tuned 3.66-billion-parameter model completed six births. The two surviving descendants of the final trial performed periodic work for two hours. Across the native gate and lineages, all 260 executions of reused development diagnostics passed; the largest observed service-group memory was 5.001 GiB. A separately frozen, cohosted comparison reconstructed two births and 15/15 diagnostics for both trained and deterministic policies. Fixed policy used zero model calls; stock passed five seed diagnostics but submitted no executable reproduction action. On forty post-development synthetic cases, trained and fixed policies passed 40/40, versus 32/40 for stock. Separate-code auditors accepted 24/24 valid controls and rejected 108/108 prescribed record inconsistencies. We retain failed attempts and supply source-bound records, model assets, and replay procedures. The results establish replication feasibility and fixed-policy sufficiency within this prepared task, separating successful replication from the necessity of model reasoning. They do not establish general autonomous replication or population reliability.

1 Introduction

Can a running software individual carry everything needed for its own local inference, establish a useful descendant on an eligible device, and leave that descendant able to repeat the operation after the seed disappears? Replicate demonstrates this bounded form of self-replication on owner-prepared Linux receivers. Each admitted parent supplies a complete signed package, including its model and runtime assets. Its descendant runs its own local inference and diagnostic service, and can supply the same reproductive package to a further receiver after the seed has been removed.

The contribution is an integrated testbed and an explicit measurement contract. Package copying, process supervision, signatures, and resource controls are conventional systems mechanisms. Replicate combines them with local model execution and retained evidence that connects a parent's decision and payload to a distinct, useful descendant. The experiment therefore asks whether the complete replication loop closes under declared resource and authority boundaries, and what evidence is needed to substantiate that claim. The owner provides compatible guests, trusted

receivers, enrollment, and availability; the running parent chooses and supplies each admitted descendant. The experiment measures independence from the seed and external inference or package services within this prepared substrate.

Replication feasibility and the necessity of model reasoning are separate questions. Three fresh seed–child–grandchild lineages completed six births with a locally running trained model, including reproduction after seed termination. In a separately frozen cohosted comparison, a deterministic policy also completed both births and all planned diagnostics without starting inference. That result establishes that fixed policy suffices for the tested lifecycle. The model-bearing system's successful replication remains an observed systems result; its success does not establish an advantage from language-model reasoning.

This paper addresses three research questions: **RQ1**, what evidence establishes bounded peer reproduction and its authority boundary? **RQ2**, what do learned and fixed policies contribute under matched deployment and post-development diagnostic conditions? **RQ3**, which inconsistent claims can retained-evidence auditors detect and reproduce? It makes three contributions:

1. An operational definition and implementation of bounded self-replication that makes complete parent-supplied software, local descendant inference, useful operation, and ancestor independence explicit and auditable.

2. A measured demonstration on one unchanged release: three native cold starts, three fresh three-generation lineages, and two hours of periodic work on the two surviving descendants of the final trial within prepared 8 GiB x86-64 Linux guests.

3. Frozen policy comparisons and auditor checks that distinguish replication success, model participation, fixed-policy sufficiency, and evidence consistency. The deterministic control provides a direct test of model necessity for the declared task.

Throughout the paper, separate-code auditing means reconstruction by project code distinct from the application, using preserved records and external readbacks. It does not mean replication by an unaffiliated research team. The resulting contribution is a working, inspectable experimental platform and a bounded empirical result. We do not claim a new learning algorithm, general autonomous replication, or priority over all prior agent-deployment systems.

2 Experimental scope

The primary experiment uses separate, freshly enrolled 8 GiB x86-64 Linux guests and a fixed release containing a fine-tuned local model, application, runtime assets, and verification materials. Its decisive sequence is a seed–child–grandchild lineage with seed termination before the grandchild becomes eligible. Useful work is a read-only diagnostic service for simulated temperature equipment. The final trial adds two hours of periodic diagnostics on the surviving child and grandchild. The supplementary policy comparison uses separate services on one guest; the post-development diagnostic study uses an Apple Silicon host. These experiments have distinct execution boundaries and are reported separately.

The scope was fixed in an October 16 development milestone after integration and model-interface failures [E2]. The original project plan proposed a broader population of software "organisms," including heterogeneous hardware, cooperative recovery, and inherited operational experience [E1]. The term *organism* remains an architectural metaphor: the system neither manufactures

hardware nor acquires arbitrary machines, and the reported release does not mutate its weights or reproductive core. Appendix C retains the scope reduction and all original qualification targets. Those targets remain distinct from the reported experiment.

The twenty temperature cases were frozen before the first comparison and excluded from training examples, but their results were repeatedly inspected during development. They function as a development set, not a blind test. The supplement adds forty newly authored synthetic cases within the same descriptor language. Neither repeated development executions nor success on these authored cases establishes broad device adaptation.

3 Related work

Recent replication research supplied the immediate motivation. Anthropic's research report on small-model self-replication separates inference setup from descendant operation. In its "Autonomous inference setup and replication (with simplified cyber)" experiment, reasoning continued on a separate model server while an experiment harness launched descendants [1]. REPLICATE makes ancestor removal, local descendant inference, and parent-supplied software part of the admission test. The environments, models, and task definitions differ, so this is a distinction in experimental boundaries, not a comparative capability result.

Kinniment et al. study autonomous replication and adaptation as a capability evaluation problem [2]. Their work motivates explicit accounting for scaffolding, resource access, and the constituent steps of a replication task. REPLICATE addresses a narrower deployment setting with pre-enrolled receivers; success here cannot be substituted for performance on their evaluations. RepliBench decomposes replication into resource acquisition, weight exfiltration, deployment, and persistence, with 86 tasks in 20 families [4]. Its recursive-replication family includes three-generation tests and local-server variants. Crucially, requests to the local model in those variants are intercepted and forwarded to the model under evaluation. Our local-inference condition therefore addresses a different execution boundary, not a missing concept of recursive replication.

AgentMatrix evaluates resource overuse and replication under load-balancing and service-termination pressures in Kubernetes [5]. Its open-weight setting copies weights and application code, whereas its proprietary-model setting retains external API inference. This already covers complete local-model deployment in a broader risk-evaluation context. REPLICATE contributes a narrower, small-device and evidence-oriented experiment; it does not claim to introduce local-weight replication.

Air et al. report network experiments in which agents deploy their weights and harness on vulnerable hosts and successful replicas continue the chain [3]. That result is directly relevant to local replication, but studies access through vulnerabilities and substantially different models and hardware. Our experiment assumes owner-authorized, prepared receivers and evaluates a small-device package, ancestor-removal condition, and useful diagnostic service. It does not measure exploitation or unauthorized access.

Neural-network quines study networks that reproduce representations of their own parameters [6]. Our release copies verified trained weights without generating, learning, or reconstructing them from a model's outputs. The two uses of "self-replication" concern different objects and mechanisms.

ReAct combines model reasoning with actions and subsequent observations [7]. REPLICATE uses a bounded tool loop in that general family, implemented through Strands Agents and a local

Table 1: Selected experimental boundaries from primary descriptions. These are differences in measurement contracts, not comparable capability rankings.

Study	Execution substrate and inference	Principal endpoint / distinction
RepliBench [4]	Provided machines; API and local-server variants, with local requests forwarded to the evaluated model	Broad component capabilities; recursive successors and basic descendant tasks
AgentMatrix [5]	Prepared Kubernetes cluster; local weights for open models, APIs for proprietary models	Service goals under pressure; replication, resource overuse, and task completion
Air et al. [3]	Network hosts reached through vulnerabilities; deployed weights and harness	Autonomous compromise and continued replica propagation
REPLICATE original milestone	Enrolled separate 8 GiB guests; complete local model and signed package	Six verified births, seed removal before grandchild eligibility, useful tasks, resource and evidence joins
REPLICATE control supplement	Separate application services on one Linux guest	Matched policy outcomes and overhead; no additional separate-machine independence claim

llama.cpp server [11, 12]. The model proposes actions; typed tools and conventional code enforce admission, resource limits, and correctness checks. The prototype should therefore be evaluated as an agent-plus-tools system.

The specialist uses low-rank adaptation, following LoRA's parameter-efficient update construction [8], starting from IBM Granite 4.2-3B [10]. Local model placement matters to the independence claim. For comparison, Petals distributes inference and fine-tuning across remote participants [9]; REPLICATE retains a full local model in each individual. Neither distributed model serving nor a remote API is part of the admitted inference path.

4 System model and trust boundary

4.1 What is replicated

Let a release be

$$R = (W, T, A, D, K, V, M, \sigma),$$

where W is the model, T the tokenizer and inference assets, A the agent application, D the supported runtime and dependency variants, K operational knowledge, V verification assets, and (M, σ) a manifest and signature. An individual additionally has device-local identity and mutable operational state. Replication preserves the release contents while establishing a distinct individual; it is not a byte-for-byte copy of the parent's credentials or running process.

The admitted capsule contains eleven payload components: four common archives (agent, knowledge, notices, and self-test), three runtime archives for each of two architectures (Python, dependencies, and inference engine), and the trained model. Every admitted peer transfer in the original milestone contains 2,861,103,093 payload bytes [E13, E5]. Retention of an ARM64 runtime is package-completeness evidence, not proof of native ARM64 execution.

The carried Linux Python distributions are version 3.12.14. The local diagnostic and evidence-replay environment uses Python 3.12.13. Both are Python 3.12 environments, but their patch

versions and execution roles are recorded separately in the artifact inventory.

The manifest binds component names, byte counts, and SHA-256 digests; Ed25519 signatures bind the release to a trusted signer. The selected release identifier is abbreviated as `00c09aa2...e33b8d` in the text and recorded in full in Appendix D. A successful installation must possess and verify the whole reproductive capsule, not merely the executable subset for its own architecture [E16, E13].

4.2 Owner substrate and agent authority

The following contract describes the original separate-machine milestone. The cohosted comparison in Section 9 uses a separate control profile; its fixed-policy arm does not satisfy the original model-specific birth predicate.

Each target is an owner-prepared Linux guest with a trusted receiving service, device identity, admission policy, local installation slot, and fixed resource enforcement. The owner provisions the environment, enrolls eligible devices, introduces their availability, supplies the seed capsule once, and retains stop and retirement authority. The receiver verifies an accepted package and controls process activation. It has no language model or task-specific reproduction planner.

The running parent performs authenticated discovery, obtains current receiver facts, invokes its own model, and initiates the transfer following an admitted choice. The owner observer may change availability, remove the seed, schedule diagnostic inputs, and collect evidence. It must not choose the reproductive action, provide a missing descendant payload, answer inference requests, or issue descendant activation. The receiver's execution of a peer-requested installation is part of the declared substrate, not an observer launch [E16, E17].




Figure 1: Authority boundary. The owner creates the permitted environment. The model's establishment choice and the complete descendant payload originate at the running parent. Evidence collection lies outside the individual.

Runtime independence is conditional on this substrate. It does not mean independence from the OS, hardware, electricity, network transport, or an owner who can stop the experiment. Research-time GPU training, artifact preservation, cloud allocation, and observation are external activities. They are not services used by the organism to reason or obtain descendant software during an admitted birth.

4.3 Operational definition of a successful birth

For parent p and target device d, define a successful birth predicate

$$\begin{aligned} B(p, d; R) = \ & \text{admitted}(d) \wedge \text{localChoice}(p, d, R) \wedge \text{completeTransfer}(p, d, R) \\ & \wedge \text{uniqueOwner}(d) \wedge \text{localInference}(d, R) \wedge \text{useful}(d) \wedge \text{bounded}(p, d). \end{aligned} \tag{1}$$

This is a concise statement of the experimental contract, not a formal verification theorem. Its conjuncts are checked using different evidence: authenticated receiver observations, literal model and tool records, component identities, lifecycle journals, live process bindings, task outcomes, and resource/deadline observations.

For seed s, child c, and grandchild g, a passing lineage additionally requires

$$B(s, c; R) \ \wedge \ B(c, g; R) \ \wedge \ t_{\text{seed absent}} < t_{\text{grandchild eligible}}.$$

Seed absence is established by cloud termination evidence and network-interface removal before grandchild eligibility. A process merely reporting that the seed is gone would not satisfy this check.

The test proves that the child can repeat reproduction after its own parent disappears. It does not test a fourth generation or require the grandchild to reproduce after the child also disappears.

5 Implementation

5.1 Local inference and bounded decisions

Each individual launches its own authenticated llama.cpp loopback server from the carried executable and model. The server uses a 4,096-token context, one generation slot, four CPU threads, zero GPU layers, and disabled model downloads. The runtime requests greedy generation with temperature zero and at most 192 output tokens per model call. The server sets `enable_thinking=false`; both model arms use this non-thinking mode. Strands Agents 1.57.1 supplies the tool loop; undeclared background tasks, automatic tool directory loading, and framework retries are disabled [E16].

These settings define the resource-constrained deployment evaluated here. They differ from the pinned IBM model card's default thinking mode and its recommended sampling settings of temperature 1.0 and top-p 0.95 [10]. The stock–trained comparison measures the two checkpoints under the same bounded, greedy, non-thinking configuration. It does not estimate either checkpoint's best attainable performance; alternate decoding and thinking modes were not evaluated.

Reproduction exposes two tools: inspect the authenticated candidate and record an `establish` or `defer` choice. The recorded choice cites the inspection evidence, exact device, supported platform, observed revision, and release identity. A deterministic validator rejects unsupported, unavailable, stale, or mismatched choices. The admitted six establishments each used three model calls and two tool calls [E5].

This is a constrained decision, with the admission rule described explicitly to the model. Literal inference records establish that the model participated. They do not establish that the decision required sophisticated reasoning or could not be implemented as a rule. For authenticated observation o, the complete task rule is

$$\pi(o) = \begin{cases} \texttt{establish}, & o.\text{ownerMode} = \texttt{enabled} \ \wedge \ o.\text{available} \\ & \qquad \wedge \ o.\text{platform} \in R.\text{supportedPlatforms}, \\ \texttt{defer}, & \text{otherwise}. \end{cases}$$

The choice must also cite the observed evidence identifier, revision, target, and release. These binding checks are enforced regardless of policy type. Consequently, the contribution under test is the measured system and evidence contract, not an intrinsically difficult reproductive decision.

5.2 Reproduction and lifecycle enforcement

The parent-side reproduction machinery records discovery, intent, transfer, and verification as bounded transitions. The target receiver enforces local ownership and retained retirement state. Retries stay within the original operation allowance. A new progress event cannot create a fresh birth budget. The twenty-minute birth allowance is preserved across the final experiments [E16, E2].

The owner-installed aggregate service group has a 6 GiB hard memory limit, a 5 GiB memory-pressure threshold, no swap, four CPU-equivalents of quota, and a 256-task kernel limit. The application, inference process, and receiver are checked against the declared group. Independent owner code observes the rendered service configuration and actual kernel membership, rather than treating a configuration file as proof of enforcement. The native experiment also exercises stop and persistent retirement [E16, E6].

These controls do not constitute a security proof against a compromised kernel or privileged owner. The reported measurements cover the declared service group and readiness storage; they do not establish that every possible process write is contained or that every whole-host transient peak is observed.

5.3 Read-only diagnostic interface

The useful-work task is deliberately narrow. A simulated equipment descriptor publishes selectors, units, scale, validity, measurement time, acceptable age, and an inclusive normal range. The agent inspects the descriptor, configures a read-only interpretation, reads the selected evidence, and submits a diagnosis with the corresponding evidence identifier. It does not actuate equipment.

Deterministic tools normalize supported Celsius, Fahrenheit, and Kelvin measurements and determine whether the observation is usable. For usable value x and normal interval $[\ell, u]$, the required diagnosis is

$$y(x) = \begin{cases} \texttt{low}, & x < \ell, \\ \texttt{normal}, & \ell \le x \le u, \\ \texttt{high}, & x > u. \end{cases}$$

Missing, invalid, or stale observations require `unknown` with a null numeric value. A submission-value consistency check rejects a numeric value that differs from the canonical reading. It returns evidence-based feedback but does not silently replace the number or select the diagnostic status. The model must resubmit within the same allowance [E16, E12].

The twenty-case task permits six model calls, eight tool events, and 150 seconds per case. A separate startup readiness diagnostic uses a four-model-call loop. These are distinct tests. The frozen temperature set contains four variants in each of five categories: normal, fault, stale, invalid, and missing. Unit conversion, exact field selectors, validity, freshness, and value preservation create concrete opportunities for failure, but the task remains sufficiently structured for a fixed policy to solve it.

6 Specialist training and deployment export

6.1 Data and supervised objective

The selected base is `ibm-granite/granite-4.2-3b`, pinned to revision e459acceac81e5fe67c07d9cfc72329a332e7eb1. Inspection of the base tensors counts 3,659,737,600 stored parameters. The "3B" family label is thus an approximation, not the measured parameter count [E8].

The v6 corpus contains 172 training trajectories expanded into 716 supervised assistant targets, and 62 validation trajectories expanded into 258 targets. Training trajectories comprise 88 equipment, 60 reproduction, and 24 diagnostic trajectories; validation contains 30, 20, and 12 respectively. The manifest records locally constructed development references, automated replay and target/token checks, no teacher-model generations, and no claim of human review [E9]. This is a statement about this supervised corpus, not a full audit of the upstream base model's pretraining data.

Training renders prompts and assistant targets with thinking disabled, matching the deployed mode. The executed recipe uses the versioned `granite-json-scalar-targets-v1` codec: within supervised tool-call targets, it changes Python-spelled `None`, `True`, and `False` scalar literals to JSON `null`, `true`, and `false`, as required by the serving parser. The transformation preserves the native tool-call structure and argument values; it leaves serving prompts, tool observations, and the pinned upstream template unchanged. Target preparation checks token-continuation consistency and parser round trips, with the parser binding retained in the executed input kit [E8, E9]. This compatibility step is part of the reported training procedure and helps define the interface-specific checkpoint comparison. Its contribution was not separately ablated.

Prompt and tool-response context is masked from the target loss. With target token indices $\mathcal{T}_i$, the supervised objective is the accumulated-batch mean next-token cross-entropy over nonmasked targets:

$$\mathcal{L}(\theta) = -\frac{1}{\sum_i |\mathcal{T}_i|} \sum_i \sum_{t \in \mathcal{T}_i} \log p_\theta(y_{i,t} \mid x_i, y_{i,<t}).$$

The small loss values reported below concern short structured targets from this constructed corpus. They are not general language-model perplexities or evidence of broad operational competence.

The completed run performed 90 optimizer updates with 31,129,600 trainable adapter parameters. Its recorded training elapsed time was 2,128.454 seconds; the managed service reported 2,435 billable seconds, which includes a different execution boundary. Peak CUDA allocated and reserved memory were 11,334,495,744 and 22,775,070,720 bytes respectively. These GPU training measurements are unrelated to the 8 GiB CPU inference claim. Validation loss was 0.001474 after epoch one and 0.001035 after epoch two. The final adapter was retained as the completed pilot checkpoint; loss alone did not admit it for deployment [E8].

6.2 Quantization and numerical checks

The deployment artifact is a merged GGUF export of 2,698,258,112 bytes. Its precision profile is based on `Q4_K_M`, with `Q8_0` input embeddings and output projection, `Q6_K` attention and MLP-down projections, and floating-point normalization tensors. It is therefore a *mixed-precision* export, not a uniformly four-bit model [E10].

Export admission independently reconstructed stored numerical responses and the declared tensor types. The maximum recorded merge error was 4.0531×10^{-5}. On three retained probe

Table 2: Selected v6 training and inference configuration. Training is external to the deployed organism. Source: preserved recipe and execution records [E8, E16].

Setting	Value
Base parameters / dtype	3,659,737,600 / BF16
Adapter	Fresh LoRA, rank 16, alpha 32, dropout 0.05
Adapted projections	Attention q, k, v, o; MLP gate, up, down
Trainable parameters	31,129,600 (approximately 0.85% of base)
Training targets / validation targets	716 / 258
Epochs / optimizer updates	2 / 90
Microbatch / accumulation	1 / 16
Learning rate / schedule	10^{-4} / cosine, 9 warmup steps
Weight decay / gradient clipping	0 / 1.0
Training context / maximum target	4,096 / 192 tokens
Random seed	20261014
Training hardware	One NVIDIA L4, managed `ml.g6.4xlarge`
Deployment	CPU-only llama.cpp; one local slot; 4,096-token context
Generation	Thinking disabled; greedy; at most 192 output tokens per call

responses, the trained quantized export had mean KL divergence 8.40×10^{-7} against its reference and top-one agreement on all three. The maximum absolute log-probability error was nevertheless about 3.93, illustrating why a small mean KL value does not imply uniform closeness for every token. These limited probes check an export path; they do not establish behavioral equivalence over the task distribution [E10]. Subsequent development and native task gates supply separate behavioral evidence.

The recovery index binds the trained model to the exact member of a preserved export archive. An older standalone file has the same byte count but a different checksum. Size alone is therefore insufficient to recover the selected model [E13].

6.3 Development selection

The final matched development comparison scored 20/20 for the trained model, 19/20 for stock, and 20/20 for fixed policy. These cases were repeatedly inspected during interface development. The one-case difference therefore does not isolate a fine-tuning effect. The full history, including early trained-model failures, selector repairs, numeric feedback, and readiness changes, is retained in Appendix A. The selected native release and the frozen supplement preserve those final choices rather than optimizing on new results.

7 Experimental protocol and evidence

7.1 Execution environment

Admitted native runs used separate `c7a.xlarge` x86-64 Linux guests with 8 GiB RAM and four CPU cores configured with one thread per core. The operating system image and owner kit were pinned in the run records. “Native” here means execution of the x86-64 runtime on that instruction-set architecture, not processor emulation. It does not mean bare-metal, independently powered industrial devices. The equipment observations are simulated fixtures [E6, E7].

The owner prepared an isolated peer network and stopped receivers before enabling each target. All devices had fresh enrollment for each lineage. The complete application package remained unchanged across the selected native gate and lineages 08, 09, and 10. Owner observation and closure code have their own source identities; sameness of the carried release is not a claim that every surrounding development script was immutable throughout the project. The original peer transfers were shaped to 8 MiB/s (8,388,608 bytes/s). Readiness delay consequently reflects the declared transport constraint as well as verification, activation, and owner observation. It should not be interpreted as an unconstrained network or inference benchmark.

7.2 Staged admission

The sequence first required three native cold starts, the twenty-case diagnostic suite, resource checks, stop, and persistent retirement. These are distinct application starts with separately recorded process identities on the native test guest; they are not three power cycles or the original six-empty-cache qualification gate. Only after this gate passed could lineage execution proceed.

For each lineage, the seed became ready and completed all twenty cases. The owner then made an enrolled child available. The seed's local model selected establishment and the seed supplied the complete package. After the child was ready and passed all twenty cases, the owner terminated the seed and verified its interface removal. Only then did the grandchild become eligible. The child selected, transferred, and verified its establishment, and the grandchild passed the same twenty cases [E7].

The twenty-minute birth allowance covers the bounded establishment operation and its required readiness checks. The subsequent full twenty-case diagnostic suite is a separate evaluation stage. We do not combine its roughly eighteen minutes with transfer time and call the result a birth-latency violation or an end-to-end birth-time measurement.

In trial 10, both final descendants then remained running over the common 17:29:10–19:29:10 UTC interval. Six scheduled cycles, twenty minutes apart, each exercised all five categories, yielding thirty additional cases per descendant. Admission required correct outcomes, retained local-model evidence, continuity of the original running individual, and compliant resources. The experiment did not perform continuous inference for two hours [E7, E5].

7.3 Evidence joins

The evidence structure deliberately separates claims at different levels. Artifact replay can establish that traces and task outcomes are internally consistent. It cannot alone prove which native process ran, whether the seed was terminated, or whether temporary infrastructure was removed. External admission joins those traces to process, network, resource, cloud-control, and archive-preservation records [E4].

A successful lineage requires matching release and device identities across:

1. receiver availability and authenticated discovery;
2. literal model requests, responses, tool calls, and the recorded choice;
3. parent transfer and target component verification;
4. ownership, process token, executable/model identity, and readiness;

5. task evidence and resource observations;

6. seed termination and interface removal preceding grandchild eligibility;

7. fixed leases, preserved archives, and resource cleanup.

The separate-code audits reconstruct these joins from preserved records and external readbacks. Historical artifact names retain the term "independent audit" for this code separation; no unaffiliated replication is claimed. The final report preserves the actual reconstruction sources and their identities. Its archive has a separate preservation receipt, followed by a completion receipt: a file cannot prove its own future upload merely by containing a success flag [E3].

8 Results

8.1 Repeated lineages and short endurance

All three selected lineages passed on release `00c09aa2...e33b8d`. Across nine individuals, all 180 scheduled core diagnostic executions passed. All six peer establishments transferred eleven components and reconstructed a local model choice. In each lineage the seed was absent before the grandchild opportunity appeared [E4, E7, E5].

Table 3: Admitted results on the selected release. Task counts are repeated executions of development fixtures.

Experiment	Core tasks	Births	Cold starts	Endurance tasks
Native gate 07	20/20	–	3/3	–
Lineage 08	60/60	2/2	–	–
Lineage 09	60/60	2/2	–	–
Lineage 10	60/60	2/2	–	60/60
Total	200/200	6/6	3/3	60/60

The final child and grandchild each completed approximately 7,200.001 seconds of endurance with thirty correct tasks and no unexplained restart. The total reported count is $20+3(60)+2(30) = 260$ successful diagnostic executions. These reuse twenty development cases and declared endurance variants. Startup readiness checks are separate and are not added to this total.




Figure 2: Selected trial 10 events, October 17, 2026, UTC, rounded to the minute. The horizontal axis is schematic, not to scale. Seed removal precedes the grandchild's availability. The blue interval denotes two hours of endurance on both descendants after the grandchild's core task suite [E7].

8.2 Footprint, latency, and activity

The largest observed aggregate service-group memory was 5,369,946,112 bytes, or 5.001 GiB. This is about 62.5% of nominal guest RAM and below the 6 GiB hard limit. The largest sampled task count was 18. Passing observations recorded no swap or out-of-memory events. Memory-pressure events at the 5 GiB threshold did occur; the threshold is a pressure mechanism, not the hard limit [E5, E6, E7].

Core diagnostic case latency across the 180 lineage cases ranged from 48.78 to 76.28 seconds. Table 4 gives per-device medians rather than presenting a mean of medians as a pooled median. Each twenty-case suite used 101 model calls and 81 tool calls: the repeated extra correction in one case is visible in the activity count. No tokens-per-second or energy measurements are inferred from these case latencies.

Table 4: Per-device core task measurements. Readiness delay is measured from owner availability-control issuance to observed readiness, so it includes publication and observation delay and is not a pure transfer or inference benchmark. Each row contains twenty successful cases [E5].

Trial	Role	Readiness delay (s)	Median case (s)	Suite (s)	Samples
08	Seed	534.79	52.32	1,076.83	696
08	Child	617.66	52.39	1,074.15	1,094
08	Grandchild	642.89	51.82	1,069.48	1,096
09	Seed	535.15	51.55	1,062.52	704
09	Child	615.90	52.23	1,071.94	1,085
09	Grandchild	615.07	51.41	1,060.61	1,087
10	Seed	605.79	51.72	1,063.86	743
10	Child	618.71	52.78	1,085.18	2,639
10	Grandchild	790.79	52.38	1,077.73	2,638

Storage used at readiness, including filesystem metadata, ranged from 6,954,110,976 to 9,815,302,144 bytes on the observed 24 GiB application-storage capacity. The seed and descendants have different staging histories, so their storage measurements should not be treated as repeated samples of an identical installation path. Readiness storage is not a continuous storage peak. The 2,861,103,093-byte transfer figure counts component payloads and excludes protocol overhead [E5, E13].

The native gate added 370 resource samples. The higher sample counts on the final descendants include the longer observation interval. These counts do not turn the underlying workload into thousands of independent experiments.

8.3 Bounded execution and closure

The experiment admitted no more than three active device slots and used fixed leases of at most four hours, with independent shutdown. The final seed had an earlier fixed expiry so the descendants could complete endurance inside the remaining aggregate allowance. No running lease was extended [E2, E17].

Temporary CPU allocations used fixed lifetime limits and independent shutdown. Final closure verified removal of the listed compute, storage, network, identity, and expiry resources after evidence preservation. Allocation-lifetime accounting and the unsuccessful-attempt inventory are retained in the operational records [E3, E4].

9 Supplementary experimental design

The supplement was frozen after the development milestone to address RQ2 and RQ3. It uses the existing stock and merged trained model files, the final equipment prompt and tools, and a separate deterministic policy. No additional training, prompt repair, case deletion, or selective model rerun is permitted. Source and model identities, case definitions, scoring, arm order, budgets, and unsuccessful attempts are retained [E18, E20, E22, E19].

9.1 Matched deployment controls

Three policies use the same signed application archive, authenticated peer transport, package preparation, and five development smoke conditions per individual. The stock arm substitutes the matched untrained model and its truthful training declaration. The fixed arm carries the same complete payload as the trained arm but never starts a model; its decision follows $\pi(o)$ and its diagnostics use the existing fixed solver. Carrying unused weights holds transfer and installation work constant, but deliberately does not minimize the fixed policy's storage or transmission footprint.

This control uses one native `c7a.2xlarge` Linux guest with 16 GiB RAM, separate unprivileged application accounts, separate enrolled receivers, actual TLS transfers, and the carried Linux runtimes. Each application service has an 8 GiB hard memory ceiling, no swap, and four CPU-equivalents of quota. Transfers use unshaped loopback transport. Their timings are comparable within this control experiment, not to the original rate-limited peer network. The fixed, stock, and trained arms execute sequentially, with one lineage per arm and at most two model applications active simultaneously. The seed's application and receiver are stopped before grandchild availability.

The owner driver activates only committed, verified packages and checks a common nominal readiness diagnostic. The parent application still chooses and supplies descendant packages. This activation boundary differs from the original receiver-managed separate-machine experiment. Shared kernel, CPU, page cache, receiver processes, and fixed arm order remain confounders; this is a deployment control, not three additional original independence trials. Model-specific admission is never satisfied by the deterministic arm: its separate profile explicitly records zero model streams and no local-inference claim. Common useful-work outcomes and the original model predicate are reported separately.

The October 17 freeze allowed two bounded cloud allocations. The first failed during bootstrap before any application or model ran. A corrected bootstrap preserved the policies, application archive, weights, cases, and scoring; the second allocation executed every frozen arm. Both attempts and their execution records are retained. Application outcomes were not patched or selectively repeated within that freeze.

The October 18 follow-up was separately frozen before execution and allocated one new guest. It integrated the already tested fixed-policy liveness correction and repeated all three arms once in the same order. Comparison of the carried archives identifies exactly two changed members: the policy-selection entry point and the added lifecycle-correction module. The other 46 application-archive members and 173 owner-source members are unchanged. Both weight files, prompt templates, tools, cases, scoring, runtimes, resource ceilings, infrastructure templates, and deadlines remain matched. New signed release and enrollment identities distinguish the follow-up; these necessarily change incidental identifier strings in reproduction prompts, so the complete dialogues are not byte-identical. The old freeze, outputs, and paper source are retained, and the two experiments are not pooled [E22, E21].

9.2 Post-development synthetic holdout

The one-shot diagnostic experiment contains forty new cases: ten conditions in each of four descriptor families. Families vary compact Celsius fields, nested Kelvin fields, register-style Fahrenheit fields, and escaped array selectors with scaling. Conditions are midpoint, fractional value, below range, above range, each inclusive boundary, stale, invalid, missing, and future-dated. The independent case generator computes expected values using decimal arithmetic; the model receives the descriptor, not the answer key. All cases conform to the existing descriptor schema and supported conversion rules. The experiment tests new layouts and parameter values within that declared interface language; it does not introduce a new equipment protocol.

All three policies receive the same cases and original tools. Each model case has a 180-second allowance under the frozen experiment limits; request retries reuse their identifier. Model order alternates between families, with a fresh local inference process for each model–family block. The actual model run is CPU-only on the local Apple Silicon host, using the pinned llama.cpp runtime, four threads, and greedy generation. It is not a native Linux lineage test. An early sandbox attempt failed before any model process started; the complete unchanged experiment was then executed with loopback access. Those infrastructure failures remain separate from task outcomes.

A pass requires a reconstructable trace, correct reader and diagnosis, the declared canonical value, unchanged input, and completion within the allowance. Scoring also verifies that elapsed wall time did not turn the intended fresh condition into a stale observation. Missing or failed cases remain failures. These are author-designed, post-development cases within the same temperature domain. Four layout families do not supply forty independent environments; neither external benchmark validity nor broad device adaptation is inferred.

Worked trace. In held-out case `1377782f4bd9c88297f10f5b`, the trained agent selected `/machine/shaft/thermometry/kelvin` and the corresponding `capture_epoch` and `quality_ok` selectors from the same prefix. The raw reading was 276.275 K. The deterministic reading tool returned a usable canonical value of 3.125 C, an inclusive normal interval of $[0, 60]$ C, and an evidence identifier. The agent submitted `normal`, 3.125 C, and that same identifier. Independent reconstruction accepted the selector, stream, observation, and submission joins. This execution took 30.14 seconds, five model calls, and four tool calls [E18]. The trace locates the division of work: the tool performs conversion and freshness assessment; the model selects declared fields and supplies the bounded diagnosis. It is an illustrative successful trace, not an additional experimental sample.

9.3 Recorded-evidence mutation experiment

The unchanged lineage auditors are evaluated on all six admitted native births. Each birth supplies four valid controls: decision, transfer, history chain, and complete parent–child link. Eighteen invalid variants per birth perturb model identity and budgets, requests, parsed choices, transport receipts, submissions, component completeness and origin, availability ordering, child identity, and SQLite history integrity. Decision mutations recompute the enclosing job hash, so their rejection cannot be explained solely by a stale outer digest. Transfer variants exercise the semantic transfer check on a previously chain-verified history; chain integrity is tested separately.

The protocol and source identities were recorded before applying mutations. Only copied records are changed, and their restoration is verified. A second process reconstructs every outcome and rejection reason from a portable subset of the original evidence. This evaluates finite recorded inconsistencies, not live fault injection, cryptographic forgery resistance, or a compromised privileged

owner.

10 Supplementary results

10.1 Native deployment comparison

The corrected October 18 comparison reconstructed both fixed-policy and trained lineages: each established two descendants and passed all fifteen planned diagnostics (Table 5). The same birth auditor joined each parent decision to the authenticated receiver observation, all eleven transferred components, and useful readiness. Its separate fixed-policy profile replaces only the decision check and verifies that the original model-specific predicate still rejects the fixed trace. The seed application and receiver were absent before grandchild eligibility in both completed arms. Each descendant received the full 2,861,108,146-byte capsule [E22].

Table 5: Corrected October 18 cohosted comparison. Fifteen diagnostics and two births were planned per arm. Counts are one lineage attempt per policy; unexecuted cases are distinct from incorrect diagnoses.

Policy	Passed / executed	Unexecuted	Births	Outcome
Fixed	15 / 15	0	2	Lineage reconstructed
Stock	5 / 5	10	0	No executable action
Trained	15 / 15	0	2	Lineage reconstructed

All three fixed application receipts record no inference process, and the retained diagnostic and reproduction traces explicitly contain zero model calls, requests, streams, and responses. Each fixed birth executes the same authenticated inspection and bounded choice tools as its model counterpart. Each trained birth uses three model calls and two executed tools. Thus fixed policy completes the tested deployment and diagnostic lifecycle without local inference. This is a useful negative result for model necessity, while the trained arm independently demonstrates that the carried local model can participate successfully.

The stock seed passed all five diagnostics and correctly inspected the eligible receiver. Its second model response put `choose_child_action` syntax inside ordinary text and ended its turn. Literal streams, parsed response, executed-tool inventory, and saved submission agree: no executable choice was submitted. The reproduction journal entered `decision_failed`, and receiver history confirms that no child was reserved and no payload transfer began. The owner then exhausted the unchanged twenty-minute child-readiness allowance. The same recorded-evidence failure analysis reproduces this outcome in both the October 17 and October 18 experiments. This is an observed format/protocol failure, not evidence of an incorrect intended action or a population failure-rate estimate [E20, E22].

Matched timing and memory measurements. Table 6 compares the same five seed diagnostics through the same application-RPC and polling code. The seed-only medians avoid comparing fifteen cases over three roles with the stock arm's five seed cases. Fixed policy takes 0.040 seconds per seed diagnostic at the median; stock and trained take 50.740 and 50.984 seconds. These descriptive observations include owner polling and are not pure inference-throughput measurements. They do not reuse the holdout's solver-only fixed-policy timing boundary.

Table 6: October 18 descriptive measurements. Readiness spans owner enablement through transfer, installation, activation, and the first useful diagnostic. Memory is the largest reported individual application service-group peak, not aggregate or whole-host memory. Dashes denote an uncreated descendant.

Policy	Seed median (s)	n	Child ready (s)	Grandchild ready (s)	Max. app. (GiB)
Fixed	0.040	5	134.91	186.35	1.116
Stock	50.740	5	—	—	1.388
Trained	50.984	5	261.78	222.47	4.069

The fixed and trained maximum application peaks are 1.116 and 4.069 GiB. Fixed policy still transfers unused model weights and complete runtime assets; its memory and deployment times therefore describe this matched-payload baseline, not a minimized deterministic implementation. Shared CPU, kernel, page cache, loopback transport, and fixed execution order limit attribution. One attempted lineage per arm supplies no estimate of tail latency, energy, production reliability, or the general causal effect of training.

Retained earlier experiment and correction. The October 17 freeze reconstructed the trained lineage with 15/15 diagnostics and two births, while stock passed 5/5 seed diagnostics and failed before any birth. Its fixed arm stopped before all fifteen diagnostics because the inherited application loop treated `inference_ready=false` as an unavailable owned model. Source inspection found the same guard in the reproduction controller. Four separate local regression checks exercised policy liveness, zero-model behavior, and real TLS transfer of a small fixture capsule with simulated process readiness. Those checks alone were not native qualification. The October 18 freeze carried this correction and the complete new comparison established its native outcome. The earlier startup failure, frozen source, and unsuccessful bootstrap allocation remain in the package [E20, E22, E21].

After preserving and hashing the new output archive, cleanup directly verified the worker as terminated and its disks, network, roles, expiry schedule, and artifact bucket as absent. These operational records are included in the accompanying evidence. The original qualification suite remains unpassed [E22].

10.2 Diagnostic holdout

The frozen trained model and fixed policy each passed 40/40 cases; the stock model passed 32/40. Each family contributed the same pattern: ten trained successes, ten fixed successes, and eight stock successes (Table 7). On the paired cases there were eight trained-only successes, zero stock-only successes, and 32 shared successes. The descriptive difference is 20 percentage points on this suite. All eighty model executions had reconstructable traces, including the eight semantically unsuccessful stock cases. Source and model hashes remained unchanged through completion, and a separate process reproduced the saved scoring exactly [E18].

The stock model submitted `normal` on each below-range and above-range case despite correctly selecting the reader. In the below-range Kelvin case it also submitted the unconverted reading twice, then copied the canonical value after feedback while retaining the incorrect diagnosis and exhausting the six-call allowance. The other seven failures completed without a runtime exception. Thus trace validity and successful tool execution do not establish diagnostic correctness.

Table 7: One-shot synthetic holdout: correct diagnosis, value, reader, and trace within the allowance. Each family has ten cases.

Descriptor family	Fixed	Stock	Trained
Compact Celsius	10/10	8/10	10/10
Nested Kelvin	10/10	8/10	10/10
Register Fahrenheit	10/10	8/10	10/10
Escaped array with scaling	10/10	8/10	10/10
Total	40/40	32/40	40/40
Model calls	0	203	201
Tool calls	160	164	161

Median model-case elapsed time was 30.29 seconds for stock and 29.79 seconds for trained, with ranges of 27.62–49.19 and 27.86–46.35 seconds, respectively. The fixed solver's median was 0.000723 seconds, measured only inside the solver. Model timings include application requests and polling; fixed timings do not. These boundaries preclude a direct speedup estimate from this experiment. No confidence interval or significance claim is attached to four authored families with correlated conditions.

The experiment supports a narrow answer to RQ2: the selected trained checkpoint outperformed the matched stock checkpoint under the frozen diagnostic stack on newly authored layouts and thresholds. It did not outperform fixed policy, establish adaptation beyond temperature descriptors, or qualify the original equipment and model-contribution gates.

10.3 Auditor validation

All 24 unmodified controls were accepted and all 108 invalid variants were rejected: zero observed false rejections and zero observed false acceptances on this prescribed set. Table 8 gives the denominators. The separate replay reproduced all decisions and rejection reasons exactly [E19]. These counts measure coverage of the chosen violations; variants share six underlying births and are not independent security trials.

Table 8: Unchanged auditors applied to copied records from six native births. The invalid denominator is $6(7 + 6 + 2 + 3) = 108$.

Category	Variants per birth	Correctly rejected
Decision identity, stream, receipt, and submission	7	42/42
Payload, contributor, reservation, and commit	6	36/36
Availability ordering and child identity	2	12/12
SQLite record deletion, body, and history head	3	18/18
Unmodified positive controls	4	24/24 accepted

11 Interpretation and threats to validity

Contribution and interpretation. The measured contribution is a complete replication loop with explicit evidence for what each parent supplies, what each descendant runs, and when ancestor independence holds. A deterministic policy can close the same tested lifecycle without inference.

This separates the system's capacity to reproduce from the question of whether a model adds value to its reproductive decisions. The evidence contract and the fixed-policy control make that distinction inspectable.

Prepared-environment independence. The decisive evidence is conditional independence from the seed and external inference/package services during admitted reproduction. The owner still supplies compatible guests, trusted receivers, enrollment, availability controls, and the original seed. The experiment does not demonstrate arbitrary device acquisition, OS installation, hardware discovery beyond the declared interface, or operation without an administrative substrate.

Model necessity and training attribution. The trained model performs genuine local inference, but its reproductive choice is tightly constrained and fixed policy solves every diagnostic development and holdout case. The corrected fixed baseline also completes both native births with all planned diagnostics and no model calls. No measured advantage over deterministic rules is established. The frozen holdout isolates a difference between the selected stock and trained checkpoint under one shared prompt, schema, tool implementation, and runtime. Both arms use thinking-disabled, greedy generation and the same short output allowance; the comparison is specific to that deployment configuration. Training-target scalar normalization also binds the trained checkpoint to the serving protocol, and its effect was not isolated. The native stock arm emitted action-like text without submitting a parsed tool call, whereas the trained arm completed the protocol. These observations support particular checkpoint and interface comparisons. Matched prompt templates do not imply identical reproduction inputs: fresh release and enrollment identifiers vary between arms and freezes. Earlier v5/v6 selection and interface development, one training run, and author-designed cases limit claims about a generally effective training method. A factorial comparison of weights, prompts, schemas, and feedback across external tasks would be needed to separate their broader contributions.

Selection and dependence. Three fresh lineages establish repeated success in the tested configuration. They are too few to establish dependable population behavior, and all share one release, hardware class, task family, and engineered environment. The diagnostic executions repeat cases with greedy generation. Reporting 260/260 as if it were a held-out accuracy estimate would overstate both sample size and generalization. We report counts and per-device measurements without inferential significance claims.

Instrumentation and observer coupling. The owner harness supplies the environment and observes it. Source-bound audits, distinct evidence channels, and explicit prohibition of observer births reduce ambiguity, but do not eliminate correlated bugs in the implementation and evaluator. Workstation sleep and namespace-dependent identifiers already caused observation errors during development. External replication would be stronger evidence than replay by the same project.

Measurement scope. The memory result is for the declared service group, including its recorded kernel accounting, and not a continuously sampled whole-host envelope. Readiness storage is a snapshot. The study does not report energy, thermal behavior, tail latency under competing workloads, sustained peak-context use, or continuous high-load inference. Cloud guests do not establish physical industrial-device performance.

Duration, generations, and faults. Two hours with periodic work is substantially narrower than the original 72-hour qualification. Seed removal is one fault condition. Later-peer loss, partition/rejoin, cooperative task recovery, concurrent parents, invalid inherited procedures, and all other Q6 scenarios were not jointly qualified on this final release. Retaining complete reproductive artifacts does not prove unlimited generation depth.

Safety and authority. The model cannot expand the authorized device inventory, alter resource ceilings, or override retirement through its declared tools. Nonetheless, this paper reports tested controls rather than a comprehensive security evaluation. The trusted receiver, signer, enrollment authority, OS, and cloud owner remain in the trust base. No resistance to compromised privileged components or arbitrary adversarial network participants is claimed.

12 Reproducibility and research continuation

The project retains immutable input identities, complete selected release recovery information, comparison traces, native and lineage records, failed allocation histories, and reconstruction code. Appendix E maps the principal claims to those sources. The accompanying reproduction manifest records byte counts and hashes of its supporting files and checks the arithmetic used in the tables. It does not replace the original runtime audits.

Reproduction of the reported development milestone requires five distinct steps: reconstruct the exact capsule; prepare trusted receivers and fresh enrollment under bounded allocations; pass the single-device native gate; run three fresh lineages with seed absence before grandchild eligibility; and audit final descendant endurance, preservation, and cleanup. The operating runbook contains the detailed procedure [E17]. A reproduction should retain unsuccessful attempts and rerun relevant gates after a carried release changes.

Artifact availability. The retained reproduction package supports the experiments reported in this revision [E21]. It includes frozen code and protocols, both compact model files, carried runtimes and notices, forty diagnostic cases, literal inference/tool traces, the mutation experiment, selected original native evidence, unsuccessful attempts, and table-generation and replay programs. Its manifest binds every packaged file by SHA-256 and byte count. Original device, diagnostic, endurance, and birth-link checks, including all 260 reported diagnostic executions, can be reconstructed from copied records without cloud credentials. New inference and cohosted deployment have separate entry points; the deployment entry point uses the corrected October 18 freeze. The earlier freeze and its failure remain separately replayable. Replay in a separate directory with pinned dependencies reconstructs the diagnostic and mutation results, all 260 original diagnostics, both native comparisons, the stock failures, the exact carried-source correction, and the derived timing tables. Such replay checks portability and consistency of the retained evidence; it does not supply new observations of the original hosts or an unaffiliated replication.

The paper and source are available at https://github.com/lhassa8/replicate. The complete reproduction archive is prepared for Zenodo deposit; its public record and persistent identifier remain pending. No unaffiliated reproduction is asserted. Private signing keys, credential-bearing enrollment stores, presigned URLs, and conversation records are excluded. Historical paths and public resource identifiers remain where needed for provenance. Third-party notices, runtime source references, and file identities accompany the distribution. Hashes identify supplied files; they do not attest to execution on the original hosts.

Next experiments. The corrected fixed baseline now provides a complete deployment comparison for this prepared task. The next scientifically useful steps are independent reproduction and an external task set with interfaces and decision requirements designed independently of this implementation, including tasks for which the fixed solver's assumptions may not suffice. These holdout cases are now known to the developers and must not be reused as a fresh blind test after subsequent tuning. For the tested task, fixed policy is the appropriate engineering baseline, and the model's additional cost needs justification. Native ARM64 lineages should then test whether retained portability assets actually work. Cooperative fault recovery and inherited procedures require their own paired tests before a longer population run. These experiments remain future work, not prerequisites retrospectively declared satisfied by this milestone.

13 Conclusion

Replicate demonstrates bounded self-replication of a complete, locally inferring software agent across owner-prepared receivers. A running parent supplies the signed package and local model; its child establishes a useful grandchild after the seed disappears. Three fresh lineages completed six births on one unchanged release in prepared 8 GiB x86-64 Linux guests. Three native cold starts and two hours of periodic work on the final trial's surviving child and grandchild provide additional evidence within that declared boundary.

The deterministic control gives the replication result its necessary context. In the separately frozen cohosted comparison, both fixed and trained policies completed two births and 15/15 diagnostics, while fixed policy started no inference process. Stock passed five seed diagnostics but submitted no executable reproduction action. On forty newly authored diagnostic cases, trained and fixed policies each passed 40/40, versus 32/40 for stock under the same bounded, non-thinking model configuration. These outcomes establish fixed-policy sufficiency for the tested lifecycle and a narrow checkpoint comparison. They provide no measured advantage over deterministic rules.

The testbed makes package provenance, local inference, useful operation, and ancestor independence explicit and auditable. Separate-code auditors accepted 24/24 valid controls and rejected 108/108 prescribed inconsistencies on records from the six native births. The retained failures and reconstruction materials make the scope of those checks inspectable. Together, the results establish replication feasibility under a declared substrate and separate that finding from the necessity of model reasoning. General autonomous replication, heterogeneous cooperative populations, and security against a compromised owner remain unestablished.

AI assistance. OpenAI Codex assisted with implementation, experiment orchestration, evidence reconstruction, and manuscript preparation. Empirical claims are grounded in the preserved executable records and their stated limitations. The author retains responsibility for the final review and submission.

A Development selection and interface corrections

Table 9 reports the six twenty-case comparisons. The preserved comparison history also contains the earlier ten-case comparison, giving seven comparison runs in total. The original twenty-case v5 result was 4/20 for the trained model. Training v6 did not by itself solve the task: the first v6 comparison remained poor, and wall-clock reconstruction further reduced its admitted score after

workstation sleep altered fixture freshness or case duration [E11, E2].

Table 9: Development history on the same twenty temperature cases. Scores are admitted successes, not an independent learning curve. Fixed policy scored 20/20 throughout. All changes were applied to both model arms where relevant.

Run	Configuration or change	Trained	Stock
01	v5 initial comparison	4	19
02	v6; corrected freshness and wall-clock audit	6	17
03	Exact-selector instructions	19	18
04	Explicit decimal-copy instructions	19	19
05	Canonical-value rejection and feedback	20	19
06	Final source inventory after readiness repairs	20	19

Run 02's original runtime counts, 7/20 and 18/20, remain preserved beside the corrected 6/20 and 17/20 result. Later selector instructions prevented repeated shortened field names. Decimal-copy instructions alone did not prevent one trained failure from rounding 37.25 C to 37 C. The consistency validator rejected that value, after which the trained model corrected its own submission. The stock model corrected a numeric value in its remaining failed case but still selected the wrong diagnosis [E11, E2].

Startup readiness exposed a separate issue: malformed long device identifiers and confusion between errors and valid evidence. The final readiness interface constrained each request's device identifier through the tool schema without silently substituting arguments. Generic range instructions were also made explicit. The full twenty-case comparison was repeated against the final source inventory before native admission.

The selected comparison is 20/20 trained, 19/20 stock, and 20/20 fixed policy. The one-case trained–stock difference is descriptive development evidence. Repeated inspection and coupled interface improvements preclude a clean causal attribution to fine-tuning. No stock or fixed-policy native lineage comparison was conducted as part of the original milestone. The supplementary comparison in Section 9 addresses common deployment outcomes under a separately declared, cohosted protocol; it does not retrospectively change those original gates.

B Failures and engineering lessons

The successful set is not the whole development history. Seven earlier lineage allocations comprise six failures and one cancellation before a launch permit. The native history contains four unsuccessful trials and two earlier passes on superseded releases, followed by the selected native pass. The failure indices retain original outcomes and archive identities [E14, E15]. We do not compute a release reliability estimate by mixing these changing implementations with the final three trials.

The trial 06 seed passed its twenty tasks and made an evidenced establishment choice, but a fixed 120-second asynchronous upload wrapper could not accommodate the model payload under the existing bandwidth limit. The correction applied the existing size-based payload allowance while preserving idle limits, control-message limits, owner stop, and the original twenty-minute birth budget. A corrected application received a new release identity and repeated the native gate before lineage execution.

Trial 07 exposed a deadline-validation issue. For floating-point clock t, computing $(t+1200)-t$ need not produce exactly 1200. A retained fractional-clock regression reproduced rejection of a

Table 10: Earlier lineage allocations. None belongs to the final three-pass set. Clock attribution in trial 07 is supported by regression evidence, but the exact native rejection was not captured.

Trial	Observed failure	Engineering implication
01	Network inspection process crashed before enable	Observation tooling itself needs a tested execution boundary.
02	Legitimate local forwarding entries rejected	Network admission must distinguish local and remote entries precisely.
03	Cancelled before permit: missing observer mount join	Insufficient evidence can invalidate an allocation before an organism starts.
04	Duplicate lab MAC addresses; seed had no route	Prepared-substrate correctness is part of end-to-end feasibility.
05	Learned bridge entry violated the declared inventory	Dynamic network behavior must agree with a frozen admission contract.
06	Model payload hit a fixed asynchronous upload timeout	Payload deadlines must account for signed size under the existing rate limit.
07	Candidate discovery occurred without reproduction intent	Exact floating-point deadline comparisons can reject valid proposals.

valid proposal; validation was changed to the direct relation $d = t + 1200$. The change introduced no tolerance or deadline extension. Because the precise rejected proposal was not retained in the native run, this remains a supported causal hypothesis, not a proven root-cause attribution for that run [E14, E2].

A later native startup failed before the application or inference process began. A persisted-state regression demonstrated a relevant race between sampling a clock and reading the state transaction. The owner guard was corrected to sample after the transaction snapshot and to report bounded denial evidence. Again, the exact native guard decision was missing, so the original native cause remains unproven. The unchanged carried release then passed the selected three-start native test [E15, E2].

These failures reveal that the limiting work was often conventional systems integration, observation, and model-interface design. More training would not have fixed network addresses, a transfer timeout, or an observer's missing mount evidence. Conversely, a successful package transfer could not fix incorrect selectors or diagnoses. A useful failure taxonomy must preserve these distinctions.

C Original scope and qualification coverage

The October 13 plan proposed locally inferring software organisms that discover eligible devices, adapt to supported equipment interfaces, cooperate under failures, and transfer tested operational experience. It required an approximately 3B specialist, native x86-64 and ARM64 operation, and independence from a hosted reasoning service, runtime package registry, or central deployment controller [E1]. After integration and model-interface failures, the October 16 milestone reduced the architectures, interfaces, generations, and endurance hours while preserving complete package transfer, local inference, peer initiation, identity and ownership controls, fixed resource allowances, and separate-code reconstruction [E2].

Table 11 records this reduction. The ten original gates Q1–Q10 remain unqualified; the reported experiment and later policy controls do not retrospectively satisfy them.

Table 11: Scope reduction. Passing the development milestone does not pass the original qualification suite.

Dimension	Original objective	Reported milestone
Hardware	Native x86-64 and ARM64; 8 GiB target, 4 GiB stretch	x86-64 execution in separate 8 GiB Linux guests
Growth	Ten three-generation trials and three native four-generation chains	Three fresh seed–child–grandchild trials
Useful work	Withheld equipment/API profiles and protected regressions	Twenty frozen development cases for one temperature interface
Learning	Demonstrated improvement over stock and fixed recipes	Fine-tuned model deployed; comparison retained without superiority claim
Population	Cooperative recovery and validated experience transfer	Ancestor removal and descendant independence
Duration	72 hours, including a new arrival after 48 healthy hours	Two hours on each final descendant, with scheduled diagnostics
Integration	Optional AgentCore after independence	Deferred

Table 12: Original qualification targets from the October 13 plan [E1]. Every full gate remains unqualified by the reduced milestone.

Gate	Original requirement	Evidence here / remaining gap
Q1	Six of six cold starts with empty caches, complete artifacts, real local inference, and no undeclared request.	Three application cold starts admitted; full original gate not run.
Q2	Ten of ten seed–child–grandchild trials, with seed disconnected before grandchild opportunity.	Three fresh passing trials.
Q3	Three native four-generation chains spanning x86-64 and ARM64; at least one starts on each architecture; all retain both variants.	Three generations on x86-64; ARM64 assets retained but execution deferred.
Q4	At least 22/24 blind diagnostic trials over four withheld profiles and 12/12 protected regressions.	Forty authored synthetic holdout cases pass for trained policy; original blind gate and protected regressions not run.
Q5	At least three more successes than fixed recipes on the same 24 challenges.	Trained and fixed policy both 40/40 on the new holdout; benefit over fixed policy unestablished.
Q6	All twelve fault/control families and subcases; no duplicate owner, boundary violation, revived retirement, or lost acknowledged replicated event.	Seed removal, native stop/retirement, and bounded admission evidenced; complete population fault suite deferred.
Q7	Twenty held-out paired experience-transfer trials; equal/higher success and at least 20% lower median bounded effort; no protected regression.	Inherited-procedure experiment deferred.
Q8	72 hours within limits on 8 GiB profiles, useful work, and arrival after 48 healthy hours; report 4 GiB separately.	Two-hour descendant interval; 4 GiB and long-duration work deferred.
Q9	Reconstruct every birth, call, identity, ownership change, task, retry, and fault outcome; no unexplained activation.	Reconstruction for the reduced native/lineage scope; full qualification population not exercised.

Gate	Original requirement	Evidence here / remaining gap
Q10	Additional frozen 64-case trained–stock comparison: at least four more successes, or equal/higher success with at least 20% less median bounded effort; protected regressions and Q1–Q9 pass.	40/40 versus 32/40 on the authored holdout; original contribution gate not run.

D Release and artifact identity

The selected release identifier is:

00c09aa2aae5f322b2b74358a65153821f99b5c29ef8a99e55170d0e14e33b8d

The trained model contains 2,698,258,112 bytes with SHA-256:

4b12affb01d210029f098ffc327d9783b0a85d00e3a12b971e9308ba1286e61b

It is supplied as `assets/models/trained.gguf` in the reproduction package. Its historical export-member and recovery identities are retained in `evidence/publication-support/recovery/`. The twenty-case frozen input file contains 33,311 bytes with SHA-256:

aff7cf82494c5f1f194b0272245835b030990a978786c1ec51aac2d0889e9685

The completed report archive contains 595,602 bytes with SHA-256:

05d9ce7b0c2b4259c45deb89240451804b90d1cd5f4814f483095403fada9a65

The complete release and full experiment history are larger than this report archive. The report contains derived results, evidence pointers, and auditor sources; it is not a standalone model distribution.

E Claim-to-evidence map

Paths below are relative to the `reproduction/` directory of the accompanying publication bundle. `EVIDENCE-INDEX.md` and `EVIDENCE-INDEX.json` map every project reference E1–E22 to packaged files. Original absolute paths remain inside historical records as provenance; they are not required local locations. Early qualification or preservation flags retain their original scope and are not rewritten by later results.

Scope and completion (E1–E5): `docs/` contains the original and reduced plans; `evidence/publication-support/completion/` contains the final report, completion receipts, and release result. The gate and measurement summaries are in `evidence/history/`.

Original native executions (E6–E7): `evidence/original-native/` and `evidence/original-lineages/08/`, `09/`, and `10/` retain audit inputs, external-admission receipts, and closure. Trial 10 also contains the descendant-endurance records.

Training and export (E8–E10): `evidence/publication-support/training/` contains the exact executed input kit, contract, recipe, corpus manifest, run, and metrics. `evidence/publi`

cation-support/export/ supplies the independent response audit, reports, reference logits, and retained response bodies. These permit inspection of the reported numerical claims; the original base-model weights and complete historical GPU environment are not supplied, and a new fine-tuning execution is not claimed.

Development, recovery, and implementation (E11–E17): evidence/publication-support/development-comparisons/ retains the comparison history and final model-gate reconstruction; evidence/publication-support/recovery/ supplies the release index. The original cases are in evidence/original-native/returned/temperature-tasks/. Failure indices are in evidence/history/, application sources in src/organism/, and operating instructions in docs/FIRST_LINEAGE_OPERATIONS.md. Exact carried source archives remain under assets/.

Research supplement (E18–E22): evidence/holdout/, evidence/mutations/, and evidence/controls/ contain the selected results and raw records. evidence/history/native-controls-20261017/ preserves the earlier comparison. The corrected freeze and allocation records are in evidence/control-protocol-20261018/ and evidence/control-allocation-20261018/; its source comparison is in evidence/history/lifecycle-correction-20261018/.

Verification and large assets: MANIFEST.json identifies each reproduction file, and results/ contains derived tables. The outer bundle adds the final paper PDF, arXiv source bundle, publication metadata, and verification records. Both exact compact model files and the carried runtimes are included; their availability does not establish native ARM64 qualification.

References

[1] Anthropic. AI models may be capable of self-replicating without access to a datacenter. Research report, October 12, 2026. https://www.anthropic.com/research/self-replicating-ai.

[2] M. Kinniment et al. Evaluating Language-Model Agents on Realistic Autonomous Tasks. arXiv:2312.11671, 2023, revised January 2024. https://arxiv.org/abs/2312.11671.

[3] A. Air, Reworr, N. Kotov, D. Volkov, J. Steidley, and J. Ladish. Language Models Can Autonomously Hack and Self-Replicate. arXiv:2605.06760, 2026. https://arxiv.org/abs/2605.06760.

[4] S. Black et al. RepliBench: Evaluating the Autonomous Replication Capabilities of Language Model Agents. arXiv:2504.18565, version 2, May 5, 2025. https://arxiv.org/abs/2504.18565.

[5] B. Zhang, Y. Yu, J. Guo, and J. Shao. Dive into the Agent Matrix: A Realistic Evaluation of Self-Replication Risk in LLM Agents. arXiv:2509.25302, version 2, April 1, 2026. https://arxiv.org/abs/2509.25302.

[6] O. Chang and H. Lipson. Neural Network Quine. arXiv:1803.05859, 2018. https://arxiv.org/abs/1803.05859.

[7] S. Yao et al. ReAct: Synergizing Reasoning and Acting in Language Models. International Conference on Learning Representations, 2023. arXiv:2210.03629. https://arxiv.org/abs/2210.03629.

[8] E. J. Hu et al. LoRA: Low-Rank Adaptation of Large Language Models. International Conference on Learning Representations, 2022. arXiv:2106.09685. https://arxiv.org/abs/2106.09685.

[9] A. Borzunov et al. Petals: Collaborative Inference and Fine-tuning of Large Models. arXiv:2209.01188, 2022. https://arxiv.org/abs/2209.01188.

[10] IBM Granite. Granite-4.2-3B model card. Revision e459acceac81e5fe67c07d9cfc72329a332e7eb1. https://huggingface.co/ibm-granite/granite-4.2-3b/blob/e459acceac81e5fe67c07d9cfc72329a332e7eb1/README.md.

[11] Strands Agents. Strands Agents Python SDK. Runtime version used: 1.57.1. https://pypi.org/project/strands-agents/1.57.1/.

[12] ggml-org. llama.cpp: LLM inference in C/C++. Software repository. https://github.com/ggml-org/llama.cpp.

[E1] Replicate project. Build plan: a self-contained, self-replicating Strands organism. `docs/self-replicating-organism-plan-20261013.md`.

[E2] Replicate project. Replicate: first useful independent lineage. `docs/replicate-first-lineage-plan-20261016.md`.

[E3] Replicate project. First-lineage final report, completion receipt, and preservation receipts. `evidence/publication-support/completion/completion-receipt.json`.

[E4] Replicate project. Completed runtime gates and external-admission reconstruction. `evidence/history/completed-runtime-gates.json`.

[E5] Replicate project. Source-bound lineage measurements. `evidence/history/lineage-measurements.json`.

[E6] Replicate project. Selected native execution 07: external admission and retained observations. `evidence/original-native/independent-native-audit.json`.

[E7] Replicate project. Fresh lineage executions 08, 09, and 10: external admissions, native observations, transport reconstruction, and closure. `evidence/original-lineages/08/independent-lineage-audit.json`.

[E8] Replicate project. v6 frozen recipe, completed training, and adapter admission. `evidence/publication-support/training/run.json`.

[E9] Replicate project. First-lineage runtime development corpus v6 manifest and automated audits. `evidence/publication-support/training/corpus-manifest.json`.

[E10] Replicate project. Independent CPU export response audit and quantization precision inventory. `evidence/publication-support/export/independent-response-audit.json`.

[E11] Replicate project. Preserved model-comparison history and final model-gate reconstruction. `evidence/publication-support/development-comparisons/comparison-history.tar.gz`.

[E12] Replicate project. Frozen twenty-case temperature development suite. `evidence/original-native/returned/temperature-tasks/temperature-cases.frozen.json`.

[E13] Replicate project. Complete selected-release recovery index. `evidence/publication-support/recovery/RELEASE-RECOVERY.json`.

[E14] Replicate project. Unsuccessful lineage allocation index. `evidence/history/unsuccessful-lineage-index.json`.

[E15] Replicate project. Native execution history and verified archive inventory. `evidence/history/native-history-index.json`.

[E16] Replicate project. Carried application and owner-enforcement source. `src/organism/application.py`.

[E17] Replicate project. First-lineage operating, stop, retirement, and cleanup instructions. `docs/FIRST_LINEAGE_OPERATIONS.md`.

[E18] Replicate project. Frozen forty-case synthetic holdout, model executions, and reconstruction. `evidence/holdout/results.json`.

[E19] Replicate project. Six-birth auditor mutation protocol, copied input records, outcomes, and replay. `evidence/mutations/results.json`.

[E20] Replicate project. Bounded cohosted native policy comparison: frozen inputs, protocol, execution, and retained failures. `evidence/history/native-controls-20261017/independent-control-audit.json`.

[E21] Replicate project. Source, data, models, runtimes, and recorded-evidence reproduction package. `README.md`. Complete archive: `replicate-publication-20261018-v2.zip`. Source companion: https://github.com/lhassa8/replicate. File manifests and replay instructions accompany the complete package.

[E22] Replicate project. Corrected three-policy native comparison, separately frozen and executed October 18, 2026; exact source changes and prior evidence retained. `evidence/controls/independent-control-audit.json`.