

Hortonworks DataFlow

Security

(November 9, 2017)

Hortonworks DataFlow: Security

Copyright © 2012-2017 Hortonworks, Inc. Some rights reserved.



Except where otherwise noted, this document is licensed under
Creative Commons Attribution ShareAlike 4.0 License.
<http://creativecommons.org/licenses/by-sa/4.0/legalcode>

Table of Contents

1. Enabling Kerberos	1
1.1. Installing and Configuring the KDC	1
1.1.1. Use an Existing MIT KDC	1
1.1.2. Use an Existing Active Directory	2
1.1.3. Use Manual Kerberos Setup	2
1.1.4. (Optional) Install a new MIT KDC	3
1.2. Installing the JCE	6
1.2.1. Install the JCE	6
1.3. Enabling Kerberos on Ambari	7
1.4. Cluster Component Configuration Updates	8
2. NiFi Authentication with SSL	11
2.1. Enabling SSL with a NiFi Certificate Authority	12
2.2. Enabling SSL with Existing Certificates	13
2.3. (Optional) Setting Up Identity Mapping	14
2.4. Generating Client Certificates	15
2.5. Logging into NiFi After Enabling SSL	16
3. Proxying NiFi with Apache Knox-TECHNICAL PREVIEW	17
3.1. Prerequisites	17
3.1.1. Installing NiFi on a New HDP Cluster	18
3.1.2. Installing NiFi on an Upgraded HDP Cluster	18
3.2. Configuring Knox for NiFi	19
3.3. Accessing NiFi Via Knox	20
4. SAM Authentication	22
4.1. Logging into SAM for the First Time	22
4.2. Logging In as a Different User	23
5. Installing Ranger	24
5.1. Ranger Installation Prerequisites	24
5.2. Setting up Databases for Ranger	24
5.2.1. Configuring MySQL for Ranger	24
5.2.2. Configuring PostgreSQL for Ranger	26
5.2.3. Configuring Oracle for Ranger	27
5.3. Installing Ranger	28
5.3.1. Start the Installation	28
5.3.2. Customize Services	31
5.3.3. Complete the Ranger Installation	55
5.3.4. Advanced Usersync Settings	56
5.3.5. Configuring Ranger for LDAP SSL	59
5.3.6. Setting up Database Users Without Sharing DBA Credentials	59
5.3.7. Updating Ranger Admin Passwords	60
5.3.8. Enabling Ranger Plugins	61
5.4. Adding Users to Ranger	70
6. Authorization with Ranger	72
6.1. Creating Policies for NiFi Access	72
6.1.1. Creating Policies to View NiFi	72
6.1.2. Allowing Users Read and Write Access	74
6.2. Create a Kafka Policy	74
6.3. Create a Storm Policy	76
7. NiFi Authorization	79

7.1. Authorizer Configuration	79
7.2. Authorizers.xml Setup	79
7.2.1. Initial Admin Identity (New NiFi Instance)	80
7.2.2. Legacy Authorized Users (NiFi Instance Upgrade)	81
7.2.3. Cluster Node Identities	82
7.3. Configuring Users & Access Policies	83
7.3.1. Creating Users and Groups	83
7.3.2. Access Policies	85
7.3.3. Access Policy Configuration Examples	87
8. SAM Authorization	100
8.1. Roles and Permissions	100
8.2. Creating Users and Assigning Them to Roles	102
8.3. Sharing Resources	103
8.3.1. Sharing an Environment	103
8.4. Sharing an Application	103
8.5. SAM Authorization Limitations	104
9. Deploying SAM Applications in a Secure Cluster	105
9.1. Connecting to a Secure Service that Supports Delegation Tokens	105
9.2. Connecting to Secure Kafka	106
9.3. Securing SAM – An End-to-End Workflow	107
9.3.1. Understanding the End-to-End Workflow	107

List of Tables

2.1. Identity mapping values	15
5.1. Ranger DB Host	32
5.2. Driver Class Name	33
5.3. Ranger DB Username Settings	33
5.4. JDBC Connect String	33
5.5. DBA Credential Settings	34
5.6. UNIX User Sync Properties	41
5.7. LDAP/AD Common Configs	42
5.8. LDAP/AD User Configs	43
5.9. LDAP/AD Group Configs	44
5.10. UNIX Authentication Settings	49
5.11. LDAP Authentication Settings	50
5.12. AD Settings	53
5.13. LDAP Advanced ranger-ugsync-site Settings	57
5.14. AD Advanced ranger-ugsync-site Settings	58
5.15. Advanced ranger-ugsync-site Settings for LDAP and AD	58
6.1. Policy Details	75
6.2. Allow Conditions	75
6.3. Policy Details	77
6.4. Allow Conditions	77
6.5. Storm User and Group Permissions	78
8.1. Role and Permission Matrix	101

1. Enabling Kerberos

To enable Kerberos on Ambari, complete the following steps:

1. [Installing and Configuring the KDC \[1\]](#)
2. [Installing the JCE \[6\]](#)
3. [Enabling Kerberos on Ambari \[7\]](#)
4. [Cluster Component Configuration Updates \[8\]](#)

1.1. Installing and Configuring the KDC

Ambari is able to configure Kerberos in the cluster to work with an existing MIT KDC, or existing Active Directory installation. This section describes the steps necessary to prepare for this integration.



Note

If you do not have an existing KDC (MIT or Active Directory), [Install a new MIT KDC](#). Installing a KDC on a cluster host **after** installing the Kerberos client may overwrite the krb5.conf file generated by Ambari.

You can choose to have Ambari connect to the KDC and automatically create the necessary Service and Ambari principals, generate and distribute the keytabs ("Automated Kerberos Setup"). Ambari also provides an advanced option to manually configure Kerberos. If you choose this option, you must create the principals, generate and distribute the keytabs. Ambari will not do this automatically ("Manual Kerberos Setup").

- [Use an Existing MIT KDC \[1\]](#)
- [Use an Existing Active Directory \[2\]](#)
- [Use Manual Kerberos Setup \[2\]](#)

For convenience, use the instructions to [\(Optional\) Install a new MIT KDC](#) if you do not have an existing KDC available.

1.1.1. Use an Existing MIT KDC

To use an existing MIT KDC for the cluster, you must prepare the following:

- Ambari Server and cluster hosts have network access to both the KDC and KDC admin hosts.
- KDC administrative credentials are on-hand.



Note

You will be prompted to enter the KDC Admin Account credentials during the Kerberos setup so that Ambari can contact the KDC and perform the necessary

principal and keytab generation. By default, Ambari will not retain the KDC credentials unless you have configured Ambari for encrypted passwords.

1.1.2. Use an Existing Active Directory

To use an existing Active Directory domain for the cluster with Automated Kerberos Setup, you must prepare the following:

- Ambari Server and cluster hosts have network access to, and be able to resolve the DNS names of, the Domain Controllers.
- Active Directory secure LDAP (LDAPS) connectivity has been configured.
- Active Directory User container for principals has been created and is on-hand. For example, "OU=Hadoop,OU=People,dc=apache,dc=org"
- Active Directory administrative credentials with delegated control of "Create, delete, and manage user accounts" on the previously mentioned User container are on-hand.



Note

You will be prompted to enter the KDC Admin Account credentials during the Kerberos setup so that Ambari can contact the KDC and perform the necessary principal and keytab generation. By default, Ambari will not retain the KDC credentials unless you have configured Ambari for encrypted passwords.



Note

If Centrify is installed and being used on any of the servers in the cluster, it is critical that you refer to Centrify's integration guide before attempting to enable Kerberos Security on your cluster. The documentation can be found in the Centrify Server Suite documentation library, with a direct link to the Hortonworks specific PDF [here](#).

1.1.3. Use Manual Kerberos Setup

To perform Manual Kerberos Setup, you must prepare the following:

- Cluster hosts have network access to the KDC.
- Kerberos client utilities (such as kinit) have been installed on every cluster host.
- The Java Cryptography Extensions (JCE) have been setup on the Ambari Server host and all hosts in the cluster.
- The Service and Ambari Principals will be manually created in the KDC before completing this wizard.
- The keytabs for the Service and Ambari Principals will be manually created and distributed to cluster hosts before completing this wizard.

1.1.4. (Optional) Install a new MIT KDC

The following gives a very high level description of the KDC installation process. To get more information see specific Operating Systems documentation, such as [RHEL documentation](#), [CentOS documentation](#), or [SLES documentation](#).



Note

Because Kerberos is a time-sensitive protocol, all hosts in the realm must be time-synchronized, for example, by using the Network Time Protocol (NTP). If the local system time of a client differs from that of the KDC by as little as 5 minutes (the default), the client will not be able to authenticate.

Install the KDC Server

1. Install a new version of the KDC server:

RHEL/CentOS/Oracle Linux

```
yum install krb5-server krb5-libs krb5-workstation
```

SLES

```
zypper install krb5 krb5-server krb5-client
```

Ubuntu/Debian

```
apt-get install krb5-kdc krb5-admin-server
```

2. Using a text editor, open the KDC server configuration file, located by default here:

```
vi /etc/krb5.conf
```

3. Change the [realms] section of this file by replacing the default "kerberos.example.com" setting for the kdc and admin_server properties with the Fully Qualified Domain Name of the KDC server host. In the following example, "kerberos.example.com" has been replaced with "my.kdc.server".

```
[realms]
EXAMPLE.COM = {
    kdc = my.kdc.server
    admin_server = my.kdc.server
}
```

4. Some components such as HUE require renewable tickets. To configure MIT KDC to support them, ensure the following settings are specified in the libdefaults section of the /etc/krb5.conf file.

```
renew_lifetime = 7d
```



Note

For Ubuntu/Debian, the setup of the default realm for the KDC and KDC Admin hostnames is performed during the KDC server install. You can re-run

setup using `dpkg-reconfigure krb5-kdc`. Therefore, Steps 2 and 3 above are not needed for Ubuntu/Debian.

Create the Kerberos Database

- Use the utility `kdb5_util` to create the Kerberos database.

RHEL/CentOS/Oracle Linux

```
kdb5_util create -s
```

SLES

```
kdb5_util create -s
```

Ubuntu/Debian

```
krb5_newrealm
```

Start the KDC

- Start the KDC server and the KDC admin server.

RHEL/CentOS/Oracle Linux 6

```
/etc/rc.d/init.d/krb5kdc start
```

```
/etc/rc.d/init.d/kadmin start
```

RHEL/CentOS/Oracle Linux 7

```
systemctl start krb5kdc
```

```
systemctl start kadmin
```

SLES

```
rckrb5kdc start
```

```
rckadmind start
```

Ubuntu/Debian

```
service krb5-kdc restart
```

```
service krb5-admin-server restart
```

Important



When installing and managing your own MIT KDC, it is **very important** to set up the KDC server to auto-start on boot. For example:

RHEL/CentOS/Oracle Linux 6

```
chkconfig krb5kdc on
```

```
chkconfig kadmin on
```

RHEL/CentOS/Oracle Linux 7

```
systemctl enable krb5kdc
```

```
systemctl enable kadmin
```

SLES

```
chkconfig rckrb5kdc on
```

```
chkconfig rckadmind on
```

Create a Kerberos Admin

Kerberos principals can be created either on the KDC machine itself or through the network, using an "admin" principal. The following instructions assume you are using the KDC machine and using the `kadmin.local` command line administration utility. Using `kadmin.local` on the KDC machine allows you to create principals without needing to create a separate "admin" principal before you start.



Note

You will need to provide these admin account credentials to Ambari when enabling Kerberos. This allows Ambari to connect to the KDC, create the cluster principals and generate the keytabs.

1. Create a KDC admin by creating an admin principal.

```
kadmin.local -q "addprinc admin/admin"
```

2. Confirm that this admin principal has permissions in the KDC ACL. Using a text editor, open the KDC ACL file:

RHEL/CentOS/Oracle Linux

```
vi /var/kerberos/krb5kdc/kadm5.acl
```

SLES

```
vi /var/lib/kerberos/krb5kdc/kadm5.acl
```

Ubuntu/Debian

```
vi /etc/krb5kdc/kadm5.acl
```

3. Ensure that the KDC ACL file includes an entry so to allow the admin principal to administer the KDC for your specific realm. When using a realm that is different than EXAMPLE.COM, **be sure there is an entry for the realm you are using**. If not present, principal creation will fail. For example, for an `admin/admin@HADOOP.COM` principal, you should have an entry:

```
*/admin@HADOOP.COM *
```

4. After editing and saving the kadm5.acl file, you must restart the kadmin process.

RHEL/CentOS/Oracle Linux 6

```
/etc/rc.d/init.d/kadmin restart
```

RHEL/CentOS/Oracle Linux 7

```
systemctl restart kadmin
```

SLES

```
rckadmind restart
```

Ubuntu/Debian

```
service krb5-admin-server restart
```

1.2. Installing the JCE

Before enabling Kerberos in the cluster, you must deploy the Java Cryptography Extension (JCE) security policy files on the Ambari Server and on all hosts in the cluster.

**Important**

If you are using Oracle JDK, **you must distribute and install the JCE on all hosts** in the cluster, including the Ambari Server. **Be sure to restart Ambari Server after installing the JCE.** If you are using OpenJDK, some distributions of the OpenJDK come with unlimited strength JCE automatically and therefore, installation of JCE is not required.

1.2.1. Install the JCE

1. On the Ambari Server, obtain the JCE policy file appropriate for the JDK version in your cluster.

- For Oracle JDK 1.8:

<http://www.oracle.com/technetwork/java/javase/downloads/jce8-download-2133166.html>

- For Oracle JDK 1.7:

<http://www.oracle.com/technetwork/java/javase/downloads/jce-7-download-432124.html>

2. Save the policy file archive in a temporary location.
3. On Ambari Server and on each host in the cluster, add the unlimited security policy JCE jars to \$JAVA_HOME/jre/lib/security/.

For example, run the following to extract the policy jars into the JDK installed on your host:


```
unzip -o -j -q jce_policy-8.zip -d /usr/jdk64/jdk1.8.0_60/jre/lib/security/
```

4. Restart Ambari Server.

1.3. Enabling Kerberos on Ambari

Once you have completed the prerequisites, you are ready to enable Kerberos for Ambari.

1. From the Ambari UI, click **Admin**, and select **Kerberos**.



2. Click **Enable Kerberos** to launch the **Enable Kerberos Wizard**.
3. From the **Get Started** screen, select the type of KDC you want to use.
4. Provide information about the KDC and admin account.
 - a. In the **KDC** section, enter the following information:
 - In the **KDC Host** field, the IP address or FQDN for the KDC host. Optionally a port number may be included.
 - In the **Realm name** field, the default realm to use when creating service principals.
 - (Optional) In the **Domains** field, provide a list of patterns to use to map hosts in the cluster to the appropriate realm. For example, if your hosts have a common domain in their FQDN such as host1.hortonworks.local and host2.hortonworks.local, you would set this to:

.hortonworks.local, hortonworks.local
 - b. In the **Kadmin** section, enter the following information:
 - In the **Kadmin Host** field, the IP address or FQDN for the KDC administrative host. Optionally a port number may be included.
 - The **Admin principal** and **password** that will be used to create principals and keytabs.
 - (Optional) If you have configured Ambari for encrypted passwords, the **Save Admin Credentials** option will be enabled. With this option, you can have Ambari store the KDC Admin credentials to use when making cluster changes.


5. From the **Install and Test Kerberos Client** page, proceed with the install. Click **Next** when complete.
6. From the **Configure Identities** page, you can customize the Kerberos identities as needed, and proceed to kerberize the cluster.

Be sure to review the principal names, particularly the **Ambari Principals** on the **General** tab. These principal names, by default, append the name of the cluster to each of the Ambari principals. You can leave this as default or adjust these by removing the "-\${cluster-name}" from principal name string.

Click the **Advanced** tab to review the principals and keytabs for each service.

7. Confirm your configurations, and click next to proceed kerberizing your cluster.

Enable Kerberos Wizard



1.4. Cluster Component Configuration Updates

After you have enabled Kerberos, some cluster components require additional configuration updates.

Storm Configuration Changes

After kerborizing your cluster in Ambari, select the **Storm Service**, then **Configs**.

Replace the `nimbus.impersonation.acl` text:

```
{ {{storm_bare_jaas_principal}} : {hosts: ['*'], groups: ['*']} }
```

With this text:

```
{ {{storm_bare_jaas_principal}} : {hosts: ['*'], groups: ['*']} ,
streamline-$REPLACE_WITH_YOUR_CLUSTER_NAME_LOWER_CASE :
{hosts: ['*'], groups: ['*']} }
```

Example

If your cluster name is STREAMANALYTICS, the updated nimbus.impersonation.acl is:

```
{ {{storm_bare_jaas_principal}} : {hosts: ['*'], groups: ['*']},
streamline-streamanalytics :
{hosts: ['*'], groups: ['*']} }
```

After make this change, restart Storm. Then go into any Service Pools that are using this storm cluster and refresh them.

Druid Configuration Changes

Update the Druid property druid.hadoop.security.spnego.excludedPaths to the following value:

```
[ "/status", "/druid/worker/v1", "/druid/indexer/v1" ]
```

HDFS Configuration Changes

If you are going to use the HDFS processor in your application in secure mode, add the following properties in the HDFS service under `custom_core-site.xml`.

Property Name	Value
hadoop.proxyuser.\$principal_you_configured_in_sam_app_settings.groups	*
hadoop.proxyuser.\$principal_you_configured_in_sam_app_settings.hosts	*

Example

In SAM, you have configured the following principal and keytab under Application Settings:

Application Configuration

GENERAL SECURITY ADVANCED

Clusters Security Config +

CLUSTER NAME *

PRINCIPAL *

KEYTAB PATH *

The configuration for the 2 HDFS properties is:

```
hadoop.proxyuser.storm-streamanalytics.hosts=*
hadoop.proxyuser.storm-streamanalytics.groups=*
```

HBase Configuration

In the HBase service, under custom `hbase-site.xml` add the following properties

- `hbase.thrift.support.proxyuser=true`
- `hbase.regionserver.thrift.http=true`

In HDFS service, add the following under custom `core-site.xml`

- `hadoop.proxyuser.streamline-streamanalytics.hosts=*`
- `hadoop.proxyuser.streamline-streamanalytics.groups=*`

2. NiFi Authentication with SSL

After you have installed Ambari and the HDF stack, you have 2 options for enabling SSL for your NiFi services.

- [Enabling SSL with a NiFi Certificate Authority \[12\]](#)
- [Enabling SSL with Existing Certificates \[13\]](#)

You can use the NiFi service Configs tab Advanced nifi-ambari-ssl-config dialog to configure security for these options.

To access the NiFi SSL configuration dialog:

1. From the Ambari services column, click NiFi.
2. Click the Configs tabs.
3. Click Advanced nifi-ambari-ssl-config.

Advanced nifi-ambari-ssl-config

Initial Admin Identity	CN=hdf-qe-docs-1.openstacklocal, OU=HORTONWORKS				
Enable SSL?	<input checked="" type="checkbox"/>				
Key password	Type password	Retype Password			
Keystore path	{{nifi_config_dir}}/keystore.jks				
Keystore password	Type password	Retype Password			
Keystore type					
Clients need to authenticate?	<input type="checkbox"/>				
Truststore path	{{nifi_config_dir}}/truststore.jks				
Truststore password	Type password	Retype Password			
Truststore type					
NiFi CA DN prefix	CN=				
NiFi CA DN suffix	, OU=HORTONWORKS				
NiFi CA Certificate Duration	1095				
NiFi Certificate Authority port	10443				
NiFi CA Force Regenerate?	<input type="checkbox"/>				
NiFi CA Token	
Node Identities	<p><!-- Provide the identity (typically a DN) of each node when clustered (see tool tip for detailed description of Node Identity). Must be specified when Ranger NiFi plugin will not be used for authorization. --></p> <pre><property name="Node Identity 1">CN=hdf-qe-docs-1.openstacklocal, OU=HORTONWORKS</property> <property name="Node Identity 2">CN=hdf-qe-docs-2.openstacklocal, OU=HORTONWORKS</property> <property name="Node Identity 3">CN=hdf-qe-docs-3.openstacklocal, OU=HORTONWORKS</property></pre>				

2.1. Enabling SSL with a NiFi Certificate Authority

When you enable SSL with the NiFi Certificate Authority (CA) installed, the NiFi CA generates new client certificates for you through Ambari. If you want to enable SSL with a NiFi CA installed, and are planning to use Ranger to manage authorization:

1. Select the **Enable SSL?** box.
2. Specify the **NiFi CA token**.

If you want to enable SSL with a NiFi CA installed, and are not yet using Ranger to manage authorization:

1. Check the **Enable SSL?** box.
2. Specify the **NiFi CA Token**.
3. Verify that the `authorizations.xml` file on each node does not contain policies. The `authorizations.xml` is located in `{nifi_internal_dir}/conf`. By default, this location is `/var/lib/nifi/conf/`, and the value of `{nifi_internal_dir}` is specified in the **NiFi internal dir** field under **Advanced nifi-ambari-config**.



Note

If `authorizations.xml` does contain policies, you must delete it from each node. If you do not, your **Initial Admin Identity** and **Node Identities** changes do not take effect.

4. Specify the **Initial Admin Identity**. The **Initial Admin Identity** is the identity of an initial administrator and is granted access to the UI and has the ability to create additional users, groups, and policies. **This is a required value** when you are not using the Ranger plugin for NiFi for authorization.

The **Initial Admin Identity** format is `CN=admin, OU=NIFI`.

After you have added the **Initial Admin Identity**, you must immediately generate certificate for this user.

5. Specify the **Node Identities**. This indicates the identity of each node in a NiFi cluster and allows clustered nodes to communicate. **This is a required value** when you are not using the Ranger plugin for NiFi for authorization.

```
<property name="Node Identity 1">CN=node1.fqdn, OU=NIFI</property>
<property name="Node Identity 2">CN=node2.fqdn, OU=NIFI</property>
<property name="Node Identity 3">CN=node3.fqdn, OU=NIFI</property>
```

Replace `node1.fqdn`, `node2.fqdn`, and `node3.fqdn` with their respective fully qualified domain names.

2.2. Enabling SSL with Existing Certificates

If you want to enable SSL with existing certificates, and plan to use Ranger for authorization:

1. Check the **Enable SSL?** box.
2. Set **Keystore path**, **Keystore password**, and **Keystore type** values.

The keystore path is similar to: `/etc/security/nifi-certs/keystore.jks`

3. Set the **Truststore path**, **Truststore password**, and **Truststore type** values.

The truststore path is similar to: `/etc/security/nifi-certs/truststore.jks`

4. Check **Clients need to authenticate?** if you want to ensure that nodes in the cluster are authenticated and are required to have certificates that are trusted by the truststores.

If you want to enable SSL with existing certificates, and are not yet using Ranger for authorization:

1. Check the **Enable SSL?** box.
2. Set **Keystore path**, **Keystore password**, and **Keystore type** values.

The keystore path is similar to: /etc/security/nifi-certs/keystore.jks

3. Set the **Truststore path**, **Truststore password**, and **Truststore type** values.

The truststore path is similar to: /etc/security/nifi-certs/truststore.jks

4. Check **Clients need to authenticate?** to ensure that nodes in the cluster are authenticated and are required to have certificates that are trusted by the Truststores.
5. Specify the **Initial Admin Identity**. The **Initial Admin Identity** is the identity of an initial administrator and is granted access to the UI and has the ability to create additional users, groups, and policies. **This is a required value** when you are not using the Ranger plugin for NiFi for authorization.

The **Initial Admin Identity** format is CN=admin, OU=NIFI.

After you have added the **Initial Admin Identity**, you must immediately generate certificate for this user.

6. Specify the **Node Identities**. This indicates the identity of each node in a NiFi cluster and allows clustered nodes to communicate. **This is a required value** when you are not using the Ranger plugin for NiFi for authorization.

```
<property name="Node Identity 1">CN=node1.fqdn, OU=NIFI</property>
<property name="Node Identity 2">CN=node2.fqdn, OU=NIFI</property>
<property name="Node Identity 3">CN=node3.fqdn, OU=NIFI</property>
```

Replace node1.fqdn, node2.fqdn, and node3.fqdn with their respective fully qualified domain names.

2.3. (Optional) Setting Up Identity Mapping

About This Task

You can use identity mapping properties to normalize user identities. Once you set up identity mapping, NiFi treats identities authenticated by different identity providers (certificates, LDAP, Kerberos) the same. This allows you to avoid creating duplicate users. Additionally, you only need to set up user-specific configurations such as authorizations once per user.

Steps

1. From the NiFi service **Configs** tab, click **Advanced nifi-properties**.
2. Use the Filter box to search for nifi.security.identity.mapping.pattern.
3. Enter the following values:

Table 2.1. Identity mapping values

Field	Sample value
nifi.security.identity.mapping.pattern.dn	^CN=(.*?), OU=(.*?)\$
nifi.security.identity.mapping.value.dn	\$1@\$2
nifi.security.identity.mapping.pattern.kerb	^(.*?)/instance@(.*?)\$
nifi.security.identity.mapping.value.kerb	\$1@\$2

4. Click **Save**.

5. Restart NiFi using the **Restart all Required** option from the **Action** menu.

Example

The following examples demonstrate normalizing DNs from certificates and principals from Kerberos:

```
nifi.security.identity.mapping.pattern.dn=^CN=( . *?) , OU=( . *?) , O=( . *?) , L=( . *?
) , ST=( . *?) , C=( . *?)$  

nifi.security.identity.mapping.value.dn=$1@$2  

nifi.security.identity.mapping.pattern.kerb=^(.*?)/instance@(.*?)$  

nifi.security.identity.mapping.value.kerb=$1@$2
```

2.4. Generating Client Certificates

If you are using a CA, you can use the TLS Toolkit provided in the HDF management pack to generate the required client certificates so that you can log into NiFi after enabling SSL.

1. Navigate the TLS Toolkit directory, which will be similar to:

```
cd /var/lib/ambari-agent/cache/common-services/NIFI/1.0.0/package/files/
nifi-toolkit-$version
```

For example:

```
cd /var/lib/ambari-agent/cache/common-services/NIFI/1.0.0/package/files/
nifi-toolkit-1.1.0.2.1.3.0-6
```

2. From the command line, run the following:

```
bin/tls-toolkit.sh client
-c <CA host name>
-D "<distinguished name>"
-p <CA host port>
-t <NiFi CA token>
-T <keystore type>
```

Your command should look similar to:

```
bin/tls-toolkit.sh client
-c nifi.cert.authority.example.com
-D "CN=admin, OU=NIFI"
-t nifi
-p 10443
-T pkcs12
```

3. To get your keystore password, enter:

```
cat config.json
```

4. Verify that the installation directory contains the following two files:

- keystore.pkcs12
- nifi-cert.pem

5. To double-click your keystore file to launch your OS certificate management application, change keystore.pkcs12 to keystore.p12.

6. Import the nifi-cert.pem file as your trusted CA.

7. Import keystore.pkcs12 as the client certificate.

Re-running the TLS Toolkit generates a new set of keystore and configuration files. To avoid having your files overwritten, save the keystore and configuration files to an alternate location before re-running the TLS Toolkit.

For more information about the TLS Toolkit, see [TLS Generation Toolkit](#) in the *Administration Guide*.

2.5. Logging into NiFi After Enabling SSL

Now that you have set up SSL, you need to enable logging into NiFi with a certificate:

1. Launch NiFi from the Ambari **Quick Links** menu.
2. Select the certificate you just imported from the browser prompt.
3. Log in with the user name and password you created during installation.



Note

When you are running NiFi on a host with Ambari and with SSL enabled, the default URL becomes secured <https://<local-host>:9091/nifi>.

3. Proxying NiFi with Apache Knox- TECHNICAL PREVIEW

You can use the Apache Knox gateway to provide authentication access security for your NiFi services. The Apache Knox Gateway ("Knox") is a system to extend the reach of Apache™ Hadoop® services to users outside of a Hadoop cluster without reducing Hadoop Security. Knox also simplifies Hadoop security for users who access the cluster data and execute jobs. Knox integrates with Identity Management and SSO systems used in enterprises and allows identity from these systems to be used for access to Hadoop clusters. For more information about Knox, see [Apache Knox Gateway Overview](#).



Note

HA and SSO are not currently supported for proxying NiFi in Knox in HDF 3.0.2.

Installing NiFi authentication with Knox requires the following steps:

- [Prerequisites \[17\]](#)
- [Configuring Knox for NiFi \[19\]](#)
- [Accessing NiFi Via Knox \[20\]](#)

3.1. Prerequisites

To use NiFi with Apache Knox, you must meet the following prerequisites:

Install HDP

Apache Knox is part of the HDP stack. For information on installing HDP, see [Getting Ready](#).

Install Knox on an HDP cluster

For information on installing services using Ambari, see [Choose Services](#).

Install NiFi on the HDP cluster



Important

We recommend that NiFi is installed on a different server than Knox.

The procedure for installing NiFi on a HDP cluster depends on whether the HDP installation is a new one or an upgrade. See the following section that is appropriate for your setup:

- [Installing NiFi on a New HDP Cluster \[18\]](#)
- [Installing NiFi on an Upgraded HDP Cluster \[18\]](#)

Configure Knox on the HDP cluster

Prior to enabling access to NiFi, you must configure Knox on the HDP cluster. See the following for information on [Configuring the Knox Gateway](#).

Configure Knox authentication	You need to define policies for the Knox node user and any users accessing NiFi through Knox to allow NiFi to authorize the requests from Knox. For information on configuring Knox authentication, see Configuring Authentication .
-------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

3.1.1. Installing NiFi on a New HDP Cluster

If you are installing NiFi on a new HDP installation, as opposed to an upgraded HDP installation, follow the instructions at [Installing NiFi on a New HDP Cluster](#).

In addition to other settings for the **Advanced nifi-ambari-ssl-config**, you must add a node identify for the Knox node.

For example:

- <property name="Node Identity1">CN=\$NIFI_HOSTNAME, OU=NIFI</property>
- <property name="Node Identity2">CN=\$NIFI_HOSTNAME, OU=NIFI</property>
- <property name="Node Identity3">CN=\$NIFI_HOSTNAME, OU=NIFI</property>
- <property name="Node Identity4">CN=\$KNOX_HOSTNAME, OU=KNOX</property>

3.1.2. Installing NiFi on an Upgraded HDP Cluster

If your HDP installation is an upgrade rather than a new installation, follow the instructions at [Installing HDF Services on an Existing HDP Cluster](#).

You will also need to manually edit policies for the users who are going to log into Knox and for the Knox node itself to be authorized as a proxy. At a minimum, the Knox node should be added to the policy for proxying user requests. To do this, complete the steps in one of the following sections:

- [Adding a Policy Using NiFi \[18\]](#)
- [Adding a Policy Using Ranger \[18\]](#)

3.1.2.1. Adding a Policy Using NiFi

If you are using native NiFi, complete the following steps to add a policy for the Knox node user. For more information, see [Configuring Users and Access Policies](#).

1. Add a user for the Knox node.
2. For the component level policies, on the root group, add permissions to "view the data policy" and to "modify the data".

3.1.2.2. Adding a Policy Using Ranger

If you are using Ranger, complete the following steps to add a policy for the Knox node user. For more information, see [Creating Policies to View NiFi](#).

1. Add a user for the Knox node.

2. For the component level policies, on the root group, add permissions to "view the data policy" and to "modify the data".

To add these permissions:

- Set WRITE to /proxy
- Set READ and WRITE to /data/process-group/<root-group-id>

3.2. Configuring Knox for NiFi

1. Create a config.json file in a location accessible to Knox.

For example, create the file on the Knox server at /home/knox.

2. Populate the config.json file with the following information:

Look up the NiFi CA port value before populating the config.json file which is in the **Advanced nifi-ambari-ssl.config**.

```
{  
  "dn" : "CN=$KNOX_HOST_NAME, OU=KNOX",  
  "keyStore" : "/home/knox/knox-nifi-keystore.jks",  
  "keyStoreType" : "jks",  
  "keyStorePassword" : "$KEY_STORE_PASSWORD",  
  "keyPassword" : "$KEY_PASSWORD",  
  "token" : "$NIFI_CA_TOKEN_VALUE",  
  "caHostname" : "$NIFI_CA_HOSTNAME",  
  "port" : $NIFI_CA_PORT,  
  "trustStore" : "/home/knox/knox-nifi-truststore.jks",  
  "trustStorePassword" : "$TRUSTSTORE_PASSWORD",  
  "trustStoreType" : "jks"  
}
```

The keyStorePassword, keyPassword, and trustStorePassword can be set to the Knox Master Password to make it easier to import the keyStore and trustStore created by the NiFi Certificate Authority into Knox's keystore.

3. Confirm that the variables in the json.config file from [step 2](#) are set to the values from the **Advanced nifi-ambari-ssl-config**.
4. To create the keystore and truststore used by Knox when proxying NiFi, start the NiFi TLS Toolkit. For the location of the TLS Toolkit, see [Release Notes](#) for OS-specific information.

For example:

```
/var/lib/ambari-agent/cache/common-services/NIFI/1.0.0/package/  
files/nifi-toolkit-1.2.0.3.0.2.0-71/bin/tls-toolkit.sh client --  
subjectAlternativeNames "CN=$HOST_DN_NAME, OU=KNOX" -F -f /home/  
knox/config.json
```

The toolkit requests a new certificate and creates two new files containing the keystore and truststore:

```
/home/knox/knox-nifi-keystore.jks
```

```
/home/knox/knox-nifi-truststore.jks
```

5. Import the Knox certificate for NiFi into Knox's gateway.jks file:

```
keytool -importkeystore -srckeystore /home/knox/knox-nifi-keystore.jks -destkeystore /usr/hdp/current/knox-server/data/security keystores/gateway.jks -deststoretype JKS -srcstorepass $KEYSTORE_PASSWORD -deststorepass $KNOX_MASTER_PASSWORD
```

The gateway.jks file should now contain a PrivateKeyEntry for NiFi.

6. Import NiFi CA's truststore into Knox's gateway.jks file:

```
keytool -importkeystore -srckeystore /home/knox/knox-nifi-truststore.jks -destkeystore /usr/hdp/current/knox-server/data/security keystores/gateway.jks -deststoretype JKS -srcstorepass $KEYSTORE_PASSWORD -deststorepass $KNOX_MASTER_PASSWORD
```

The gateway.jks file should now contain a trustedCertEntry for NiFi.

Knox uses the gateway.jks to look up certificates in the truststore that it can trust.

7. If you have not already done so, verify the proper keys are in the gateway.jks file:

```
keytool -keystore /usr/hdp/current/knox server/data/security/keystores/gateway.jks -storepass $KEYSTORE_PASSWORD -list -v
```

8. In the /usr/hdp/current/\$KNOX_SERVER/data/services/nifi/1.4.0/service.xml file, make sure the dispatch element contains the following:

```
<dispatch  
classname="org.apache.hadoop.gateway.dispatch.NiFiDispatch" use-  
two-way-ssl="true" />
```

9. In the **Advanced topology** section in Ambari, add the following service definition. Add it to the list of services.

```
<service>  
    <role>NIFI</role>  
    <url>https://$NIFI_HOSTNAME:$NIFI_HTTPS_PORT/</url>  
    <param name="useTwoWaySsl" value="true" />  
</service>
```

Where:

- <url> Points to the host and port that NiFi is listening on from the nifi-properties configuration site.

10 Save the configuration and restart Knox.

3.3. Accessing NiFi Via Knox

To launch NiFi via Knox, complete the following steps:

1. Enter the following url in a browser:

`https://$KNOX_HOST:$KNOX_PORT/$GATEWAY_CONTEXT/default/nifi-app/nifi`

Where:

- `$KNOX_HOST:$KNOX_PORT` is the Knox host:gateway port
- `$GATEWAY_CONTEXT` is the gateway context, defined in the gateway-site configuration in Knox

2. When prompted, enter your NiFi username and password to be authenticated by Knox.

Knox proxies the NiFi UI.

4. SAM Authentication

After you Kerborize the cluster and try to access the SAM UI for the first time, an Authentication Required message displays. To log into SAM for the first time and to create other users, you must log in with the streamline principal and keytab. Ambari creates the streamline principal and keytab during the Kerberos process.

Details of the principal and the keyab:

- The ketab is called `streamline.service.keytab` and islocated on the node where SAM is installed. It is located under `/etc/security`.
- The principal name has the following convention: `streamline-<cluster_name_lower_case>`

After you have logged into SAM as the streamline user, you can create other users

4.1. Logging into SAM for the First Time

About This Task

To log into SAM for the first time and to create other users, you must log in with the streamline principal and keytab.

Steps

1. Use Ambari to download the Kerboros client your local machine:
 - a. In Ambari, select **Hosts**, and select a host.
 - b. Click **Host Actions**, then **Download Client Configs**, then **Kerberos Client**.
 - c. Run the following command:

```
tar -zxvf KERBEROS_CLIENT-configs.tar
```

- d. Copy the `krb5.conf` to `/etc`.

2. Copy the Keytab for the streamline user.

Copy the key tab from `$FQDN_SAM_NODE:/etc/security/keytabs/streamline.service.keytab` to you local machine.

3. Log in as the streamline user:

```
kinit -kt streamline.service.keytab streamline-<your_cluster_name>@<REALM_NAME>
```

Result

You are now able to access the SAM UI securely, and can proceed with creating additional users.

More Information

See Managing Users and Assigning them to Roles

4.2. Logging In as a Different User

If you want to log in as one of the users you have created, enter:

```
kinit <user-name>@<REALM_NAME>
```

Example

After the user solson is created, to log in as that user, perform a kinit as solson. After successful kinit, when the user solson goes to the SAM UI, they see the following:

The screenshot shows the Hortonworks DataFlow Configuration / Authorizer interface. On the left is a sidebar with icons for Home, Applications, Service Pool, Environments, and Help. The main area has a header "Configuration / Authorizer" and tabs for "USERS" and "ROLES". The "USERS" tab is active, displaying a list of users with their icons, names, and the number of roles assigned:

User	Roles
solson	1
streamline-streamanalytics	1
gvtticaden	1
harsha	1
suresh	1
guru	1
dan	1

A modal dialog is open on the right side for creating a new user. The fields shown are:

- NAME *: solson
- EMAIL *: solson@hortonworks.com
- ROLES: ROLE_ADMIN

At the bottom of the modal are "SAVE" and "CANCEL" buttons.

5. Installing Ranger

Apache Ranger can be installed either manually or using the Ambari UI. Unlike the manual installation process, which requires you to perform a number of installation steps, installing Ranger using the Ambari UI is simpler and easier. Once Ambari has been installed and configured, you can use the **Add Service** wizard to install the following components:

- Ranger Admin
- Ranger UserSync
- Ranger Key Management Service

5.1. Ranger Installation Prerequisites

Before you install Ranger, make sure your cluster meets the following requirements:

- You have installed Log Search or have an external Solr running.
- A MySQL, Oracle, or PostgreSQL database instance must be running and available to be used by Ranger. Configuration of the database instance for Ranger is described in the following sections for some of the databases supported by Ranger.
 - [Configuring MySQL for Ranger \[24\]](#)
 - [Configuring PostgreSQL for Ranger \[26\]](#)
 - [Configuring Oracle for Ranger \[27\]](#)
- If you choose not to provide system Database Administrator (DBA) account details to the Ambari Ranger installer, you can use the `dba_script.py` Python script to create Ranger DB database users without exposing DBA account information to the Ambari Ranger installer. You can then run the normal Ambari Ranger installation without specifying a DBA user name and password. For more information see [Setting up Database Users Without Sharing DBA Credentials](#).
- The Ranger installation creates two new users (default names: rangeradmin and rangerlogger) and two new databases (default names: ranger and ranger_audit).

5.2. Setting up Databases for Ranger

- [Configuring MySQL for Ranger \[24\]](#)
- [Configuring PostgreSQL for Ranger \[26\]](#)
- [Configuring Oracle for Ranger \[27\]](#)

5.2.1. Configuring MySQL for Ranger

1. The MySQL database administrator should be used to create the Ranger databases.

The following series of commands could be used to create the rangerdba user with password rangerdba.

- Log in as the root user, then use the following commands to create the rangerdba user and grant it adequate privileges.

```
CREATE USER 'rangerdba'@'localhost' IDENTIFIED BY 'rangerdba';

GRANT ALL PRIVILEGES ON *.* TO 'rangerdba'@'localhost';

CREATE USER 'rangerdba'@'%' IDENTIFIED BY 'rangerdba';

GRANT ALL PRIVILEGES ON *.* TO 'rangerdba'@'%';

GRANT ALL PRIVILEGES ON *.* TO 'rangerdba'@'localhost' WITH GRANT OPTION;

GRANT ALL PRIVILEGES ON *.* TO 'rangerdba'@'%' WITH GRANT OPTION;

FLUSH PRIVILEGES;
```

- Use the `exit` command to exit MySQL.
- You should now be able to reconnect to the database as rangerdba using the following command:

```
mysql -u rangerdba -prangerdba
```

After testing the rangerdba login, use the `exit` command to exit MySQL.

- Use the following command to confirm that the `mysql-connector-java.jar` file is in the Java share directory. This command must be run on the server where Ambari server is installed.

```
ls /usr/share/java/mysql-connector-java.jar
```

If the file is not in the Java share directory, use the following command to install the MySQL connector .jar file.

RHEL/CentOS/Oracle Linux

```
yum install mysql-connector-java*
```

SLES

```
zypper install mysql-connector-java*
```

- Use the following command format to set the `jdbc/driver/path` based on the location of the MySQL JDBC driver .jar file. This command must be run on the server where Ambari server is installed.

```
ambari-server setup --jdbc-db={database-type} --jdbc-driver={/jdbc/driver/
path}
```

For example:

```
ambari-server setup --jdbc-db=mysql --jdbc-driver=/usr/share/java/mysql-
connector-java.jar
```

5.2.2. Configuring PostgreSQL for Ranger

1. On the PostgreSQL host, install the applicable PostgreSQL connector.

RHEL/CentOS/Oracle Linux

```
yum install postgresql-jdbc*
```

SLES

```
zypper install -y postgresql-jdbc
```

2. Confirm that the .jar file is in the Java share directory.

```
ls /usr/share/java/postgresql-jdbc.jar
```

3. Change the access mode of the .jar file to 644.

```
chmod 644 /usr/share/java/postgresql-jdbc.jar
```

4. The PostgreSQL database administrator should be used to create the Ranger databases.

The following series of commands could be used to create the `rangerdba` user and grant it adequate privileges.

```
echo "CREATE DATABASE $dbname;" | sudo -u $postgres psql -U $postgres
echo "CREATE USER $rangerdba WITH PASSWORD '$passwd';" | sudo -u $postgres
    psql -U $postgres
echo "GRANT ALL PRIVILEGES ON DATABASE $dbname TO $rangerdba;" | sudo -u
    $postgres psql -U $postgres
```

Where:

- `$postgres` is the Postgres user.
- `$dbname` is the name of your PostgreSQL database
- `$passwd` is the password for your Ranger Admin user
- `$rangerdba` is the username for your Ranger Admin user

5. Use the following command format to set the `jdbc/driver/path` based on the location of the PostgreSQL JDBC driver .jar file. This command must be run on the server where Ambari server is installed.

```
ambari-server setup --jdbc-db={database-type} --jdbc-driver={/jdbc/driver/
path}
```

For example:

```
ambari-server setup --jdbc-db=postgres --jdbc-driver=/usr/share/java/
postgresql-jdbc.jar
```

6. Run the following command:

```
export HADOOP_CLASSPATH=${HADOOP_CLASSPATH}: ${JAVA_JDBC_LIBS} :/connector jar
path
```

7. Add Allow Access details for Ranger users:

- (Optional) Use the following command to find the location of `postgresql.conf` and `pg_hba.conf`:

```
echo "SHOW config_file;" | sudo -u $postgres psql -U $postgres
```

- change `listen_addresses='localhost'` to `listen_addresses='*' ('*' = any)` to listen from all IPs in `postgresql.conf`.
- Add the Ranger Admin user to the appropriate line in the `pg_hba.conf` file, the following provides an example:

#	TYPE	DATABASE	USER	CIDR-ADDRESS	METHOD
	local	all	<code>postgres,rangeradmin,rangerlogger</code>		<code>trust</code>
	host	all	<code>postgres,rangeradmin,rangerlogger</code>	<code>0.0.0.0/0</code>	<code>trust</code>
	host	all	<code>postgres,rangeradmin,rangerlogger</code>	<code>::/0</code>	<code>trust</code>
				<code>"/var/lib/pgsql/data/pg_hba.conf"</code>	<code>74L, 3445C</code>

8. After editing the `pg_hba.conf` file, run the following command to refresh the PostgreSQL database configuration:

```
sudo -u postgres /usr/bin/pg_ctl -D $PGDATA reload
```

For example, if the `pg_hba.conf` file is located in the `/var/lib/pgsql/data` directory, the value of `$PGDATA` is `/var/lib/pgsql/data`.

5.2.3. Configuring Oracle for Ranger

1. On the Oracle host, install the appropriate JDBC .jar file.

- Download the Oracle JDBC (OJDBC) driver from <http://www.oracle.com/technetwork/database/features/jdbc/index-091264.html>.
- For **Oracle Database 11g**: select Oracle Database 11g Release 2 drivers > `ojdbc6.jar`.
- For **Oracle Database 12c**: select Oracle Database 12c Release 1 driver > `ojdbc7.jar`.
- Copy the .jar file to the Java share directory. For example:

```
cp ojdbc7.jar /usr/share/java
```



Note

Make sure the .jar file has the appropriate permissions. For example:

```
chmod 644 /usr/share/java/ojdbc7.jar
```

-
2. The Oracle database administrator should be used to create the Ranger databases.

The following series of commands could be used to create the RANGERDBA user and grant it permissions using SQL*Plus, the Oracle database administration utility:

```
# sqlplus sys/root as sysdba
CREATE USER $RANGERDBA IDENTIFIED BY $RANGERDBAPASSWORD;
GRANT SELECT_CATALOG_ROLE TO $RANGERDBA;
GRANT CONNECT, RESOURCE TO $RANGERDBA;
QUIT;
```

3. Use the following command format to set the jdbc/driver/path based on the location of the Oracle JDBC driver .jar file. This command must be run on the server where Ambari server is installed.

```
ambari-server setup --jdbc-db={database-type} --jdbc-driver={/jdbc/driver/
path}
```

For example:

```
ambari-server setup --jdbc-db=oracle --jdbc-driver=/usr/share/java/ojdbc6.
jar
```

5.3. Installing Ranger

To install Ranger using Ambari:


1. Start the Installation []
2. Customize Services [31]
3. Complete the Ranger Installation [55]

Related Topics

- [Setting up Database Users Without Sharing DBA Credentials \[59\]](#)
- [Updating Ranger Admin Passwords \[60\]](#)

5.3.1. Start the Installation

1. Log into your Ambari cluster with your designated user credentials. The main Ambari Dashboard page will be displayed.
2. From the main Ambari Dashboard page, click **Actions**, then select **Add Service**.



3. On the Choose Services page, select **Ranger**, then click **Next**.

Add Service Wizard

ADD SERVICE WIZARD

Choose Services

Assign Masters
Assign Slaves and Clients
Customize Services
Configure Identities
Review
Install, Start and Test
Summary

Choose Services

Choose which services you want to install on your cluster.

Service	Version	Description
ZooKeeper	3.4.6.2.0	Centralized service which provides highly reliable distributed coordination
Storm	1.0.1.2.0	Apache Hadoop Stream processing framework
Ambari Infra	0.1.0	Core shared service used by Ambari managed components.
Ambari Metrics	0.1.0	A system for metrics collection that provides storage and retrieval capability for metrics collected from the cluster
Kafka	0.10.0.2.0	A high-throughput distributed messaging system
Log Search	0.5.0	Log aggregation, analysis, and visualization for Ambari managed services. This service is Technical Preview .
Ranger	0.6.0.2.0	Comprehensive security for Hadoop
NiFi	1.0.0.2.0	Apache NiFi is an easy to use, powerful, and reliable system to process and distribute data.

Next →

4. The Ranger Requirements page appears. Ensure that you have met all of the installation requirements, then select the "I have met all the requirements above" check box and click **Proceed**.

Ranger Requirements

1. You must have an **MySQL/Oracle/Postgres/MSSQL/SQL Anywhere Server** database instance running to be used by Ranger.
2. In Assign Masters step of this wizard, you will be prompted to specify which host for the Ranger Admin. On that host, you **must have DB Client installed** for Ranger to access to the database. (Note: This is applicable for only Ranger 0.4.0)
3. Ensure that the access for the DB Admin user is enabled in DB server from any host.
4. Execute the following command on the Ambari Server host. Replace **database-type** with **mysql|oracle|postgres|mssql|sqlanywhere** and **/jdbc/driver/path** based on the location of corresponding JDBC driver:

```
ambari-server setup --jdbc-db={database-type} --jdbc-driver={/jdbc/driver/path}
```

I have met all the requirements above.

Cancel

Proceed


5. From the **Assign Masters** page, you are then prompted to select the host where you want to install Ranger Admin. This host must have DB admin access to the Ranger DB host and User Sync.

Make a note of the Ranger Admin host for use in subsequent installation steps. Click **Next** when finished to continue with the installation.



Note

The Ranger Admin and Ranger User Sync services must be installed on the same cluster node.



6. From the **Assign Slaves and Clients** page, click **Next**.
7. The Customize Services page appears. These settings are described in the next section.

5.3.2. Customize Services

The next step in the installation process is to specify Ranger settings on the Customize Services page.

- [Ranger Admin Settings \[31\]](#)
- [Configure Ranger User Sync \[40\]](#)
- [Specify Plugins to Enable \[46\]](#)
- [Ranger Audit Settings \[47\]](#)
- [Configure Ranger Authentication \[48\]](#)

5.3.2.1. Ranger Admin Settings

1. On the Customize Services page, select the Ranger Admin tab, then use the **DB Flavor** drop-down to select the database type that you are using with Ranger.

Add Service Wizard

The screenshot shows the 'Customize Services' step of the 'Add Service Wizard'. On the left, a sidebar lists steps: Choose Services, Assign Masters, Assign Slaves and Clients, **Customize Services**, Configure Identities, Review, Install, Start and Test, and Summary. The 'Customize Services' step is selected. The main area is titled 'Customize Services' with a sub-instruction: 'We have come up with recommended configurations for the services you selected. Customize them as you see fit.' Below this are tabs: ZooKeeper, Storm, Ambari Infra, Ambari Metrics, Kafka, Log Search, **Ranger** (highlighted), NIFI, and Misc. A message indicates 'There are 3 configuration changes in 3 services' with a 'Show Details' link. Below the tabs is a 'Manage Config Groups' section with a 'Group' dropdown set to 'Default (3)', a 'Manage Config Groups' button, and a 'Filter...' button. Underneath are links for Ranger Admin (highlighted), Ranger User Info, Ranger Plugin, Ranger Audit, Ranger Tagsync, and Advanced. The 'Ranger Admin' section contains fields: 'DB FLAVOR' dropdown set to 'MySQL' (highlighted with a blue box), 'Ranger DB host' input field, 'Ranger DB name' input field set to 'ranger', and 'Driver class name for a JDBC Ranger database' input field set to 'com.mysql.jdbc.Driver'.

2. Enter the database server address in the **Ranger DB Host** box.

Table 5.1. Ranger DB Host

DB Flavor	Host	Example
MySQL	<HOST[:PORT]>	c6401.ambari.apache.org or c6401.ambari.apache.org:3306
Oracle	<HOST:PORT:SID>	c6401.ambari.apache.org:1521:ORCL
	<HOST:PORT/Service>	c6401.ambari.apache.org:1521/XE
PostgreSQL	<HOST[:PORT]>	c6401.ambari.apache.org or c6401.ambari.apache.org:5432
MS SQL	<HOST[:PORT]>	c6401.ambari.apache.org or c6401.ambari.apache.org:1433
SQLA	<HOST[:PORT]>	c6401.ambari.apache.org or c6401.ambari.apache.org:2638

3. **Ranger DB name** – The name of the Ranger Policy database, i.e. ranger_db. Please note that if you are using Oracle, you must specify the Oracle tablespace name here.

4. Driver class name for a JDBC Ranger database – the driver class name is automatically generated based on the selected DB Flavor. The table below lists the default driver class settings. Currently Ranger does not support any third party JDBC driver.

Table 5.2. Driver Class Name

DB Flavor	Driver class name for a JDBC Ranger database
MySQL	com.mysql.jdbc.Driver
Oracle	oracle.jdbc.driver.OracleDriver
PostgreSQL	org.postgresql.Driver
MS SQL	com.microsoft.sqlserver.jdbc.SQLServerDriver
SQLA	sap.jdbc4.sqlanywhere.IDriver

5. **Ranger DB username** and **Ranger DB Password** – Enter the user name and passwords for your Ranger database server. The following table describes these settings in more detail. You can use the MySQL database that was installed with Ambari, or an external MySQL, Oracle, PostgreSQL, MS SQL or SQL Anywhere database.

Table 5.3. Ranger DB Username Settings

Property	Description	Default Value	Example Value	Required?
Ranger DB username	The username for the Policy database.	rangeradmin	rangeradmin	Yes
Ranger DB password	The password for the Ranger Policy database user.		PassWORd	Yes

6. JDBC connect string



Important

Currently the Ambari installer generates the JDBC connect string using the `jdbc:oracle:thin:@//host:port/db_name` format. You must replace the connection string as described in the following table:

Table 5.4. JDBC Connect String

DB Flavor	Syntax	Example Value
MySQL	<code>jdbc:mysql://DB_HOST:PORT/db_name</code>	<code>jdbc:mysql://c6401.ambari.apache.org:3306/ranger_db</code>
Oracle	For Oracle SID: <code>jdbc:oracle:thin:@DB_HOST:PORT:SID</code>	<code>jdbc:oracle:thin:@c6401.ambari.apache.org:1521:ORCL</code>
	For Oracle Service Name: <code>jdbc:oracle:thin:@//DB_HOST[:PORT]/[ServiceName]</code>	<code>jdbc:oracle:thin:@//c6401.ambari.apache.org:1521/XE</code>
PostgreSQL	<code>jdbc:postgresql://DB_HOST/db_name</code>	<code>jdbc:postgresql://c6401.ambari.apache.org:5432/ranger_db</code>
MS SQL	<code>jdbc:sqlserver://DB_HOST;databaseName=db_name</code>	<code>jdbc:sqlserver://c6401.ambari.apache.org:1433;databaseName=ranger_db</code>
SQLA	<code>jdbc:sqlanywhere:host=DB_HOST;dataBaseName=db_name</code>	<code>jdbc:sqlanywhere:host=c6401.ambari.apache.org:2638;dataBaseName=ranger_db</code>

7. Setup Database and Database User

- If set to **Yes** – The Database Administrator (DBA) user name and password will need to be provided as described in the next step.



Note

Ranger does not store the DBA user name and password after setup. Therefore, you can clear these values in the Ambari UI after the Ranger setup is complete.

- If set to **No** – A **No** indicates that you do not wish to provide Database Administrator (DBA) account details to the Ambari Ranger installer. Setting this to No continues the Ranger installation process without providing DBA account details. In this case, you must perform the system database user setup as described in [Setting up Database Users Without Sharing DBA Credentials](#), and then proceed with the installation.



Note

If **No** is selected and the UI still requires you to enter a user name and password in order to proceed, you can enter any value – the values do not need to be the actual DBA user name and password.

8. Database Administrator (DBA) username and Database Administrator (DBA) password

The DBA username and password are set when the database server is installed. If you do not have this information, contact the database administrator who installed the database server.

Table 5.5. DBA Credential Settings

Property	Description	Default Value	Example Value	Required?
Database Administrator (DBA) username	The Ranger database user that has administrative privileges to create database schemas and users.	root	root	Yes
Database Administrator (DBA) password	The root password for the Ranger database user.		root	Yes

If the Oracle DB root user Role is SYSDBA, you must also specify that in the **Database Administrator (DBA) username** parameter. For example, if the DBA user name is `orcl_root` you must specify `orcl_root AS SYSDBA`.



Note

As mentioned in the note in the previous step, if **Setup Database and Database User** is set to **No**, a placeholder DBA username and password may still be required in order to continue with the Ranger installation.

The following images show examples of the DB settings for each Ranger database type.



Note

To test the DB settings, click **Test Connection**. If a Ranger database has not been pre-installed, **Test Connection** will fail even for a valid configuration.

MySQL

The screenshot shows the 'Ranger Admin' configuration page for MySQL. The top navigation bar includes links for Ranger Admin, Ranger User Info, Ranger Plugin, Ranger Audit, Ranger Tagsync, and Advanced. The main section is titled 'Ranger Admin' and contains the following fields:

DB FLAVOR	MYSQL	Ranger DB host	c6402.ambari.apache.org
Ranger DB name	ranger	Driver class name for a JDBC Ranger database	com.mysql.jdbc.Driver
Ranger DB username	rangeradmin	Ranger DB password	*****
JDBC connect string for a Ranger database	jdbc:mysql://c6402.ambari.apache.org:3306/ranger		
Setup Database and Database User			
Yes			
Database Administrator (DBA) username	rangerdba	Database Administrator (DBA) password	***
JDBC connect string for root user	jdbc:mysql://c6402.ambari.apache.org:3306/ranger	***	***

Oracle – if the Oracle instance is running with a Service name.

Ranger Admin Ranger User Info Ranger Plugin Ranger Audit Ranger Tagsync Advanced

Ranger Admin

DB FLAVOR	ORACLE	Ranger DB host
Ranger DB name	ranger	Driver class name for a JDBC Ranger database
Ranger DB username	rangeradmin	Ranger DB password
JDBC connect string for a Ranger database	//c6402.ambari.apache.org:1521/XE/ranger	
Setup Database and Database User		
Database Administrator (DBA) username	Database Administrator (DBA) password	
rangerdba
JDBC connect string for root user	cthn:@//c6402.ambari.apache.org:1521/XE	

Oracle – if the Oracle instance is running with a SID.

Ranger Admin Ranger User Info Ranger Plugin Ranger Audit Ranger Tagsync Advanced

Ranger Admin

DB FLAVOR	ORACLE	Ranger DB host	c6402.ambari.apache.org:1521:ORCL
Ranger DB name	ranger	Driver class name for a JDBC Ranger database	
Ranger DB username	rangeradmin	Ranger DB password	
JDBC connect string for a Ranger database	
Setup Database and Database User			
Database Administrator (DBA) username		Database Administrator (DBA) password	
rangerdba	
JDBC connect string for root user		
jdbc:oracle:thin:@//c6402.ambari.apache.or	

PostgreSQL

Ranger Admin Ranger User Info Ranger Plugin Ranger Audit Ranger Tagsync Advanced

Ranger Admin

DB FLAVOR	POSTGRES	Ranger DB host	c6402.ambari.apache.org:5432
Ranger DB name	ranger	Driver class name for a JDBC Ranger database	org.postgresql.Driver
Ranger DB username	rangeradmin	Ranger DB password	*****
JDBC connect string for a Ranger database	sql://c6402.ambari.apache.org:5432/ranger		
<hr/> <p>Setup Database and Database User</p> <p><input checked="" type="radio"/> Yes</p> <hr/>			
Database Administrator (DBA) username	rangerdba	Database Administrator (DBA) password	***** *****
JDBC connect string for root user	jdbc://c6402.ambari.apache.org:5432/postgres		

MS SQL

Ranger Admin Ranger User Info Ranger Plugin Ranger Audit Ranger Tagsync Advanced

Ranger Admin

DB FLAVOR	MSSQL	Ranger DB host	c6402.ambari.apache.org:1433
Ranger DB name	ranger	Driver class name for a JDBC Ranger database	com.microsoft.sqlserver.jdbc.SQLServerC
Ranger DB username	rangeradmin	Ranger DB password	***** *****
JDBC connect string for a Ranger database	ari.apache.org:1433;databaseName=ranger		

Setup Database and Database User

Yes

Database Administrator (DBA) username	rangerdba	Database Administrator (DBA) password	***** *****
JDBC connect string for root user	sqlserver://c6402.ambari.apache.org:1433;		

SQL Anywhere

The screenshot shows the 'Ranger Admin' configuration page. At the top, there are tabs: 'Ranger Admin' (selected), 'Ranger User Info', 'Ranger Plugin', 'Ranger Audit', 'Ranger Tagsync', and 'Advanced'. The main section is titled 'Ranger Admin'.

DB FLAVOR: SQL Anywhere

Ranger DB host: c6402.ambari.apache.org:2638

Ranger DB name: ranger

Driver class name for a JDBC Ranger database: sap.jdbc4.sqlanywhere.IDriver

Ranger DB username: rangeradmin

Ranger DB password: [REDACTED]

JDBC connect string for a Ranger database: !:ambari.apache.org:2638;database=ranger

Setup Database and Database User: Yes

Database Administrator (DBA) username: rangerdba

Database Administrator (DBA) password: [REDACTED]

JDBC connect string for root user: !here:host=c6402.ambari.apache.org:2638;

5.3.2.2. Configure Ranger User Sync

This section describes how to configure Ranger User Sync for either UNIX or LDAP/AD.

- [Configuring Ranger User Sync for UNIX \[40\]](#)
- [Configuring Ranger User Sync for LDAP/AD \[41\]](#)

5.3.2.2.1. Configuring Ranger User Sync for UNIX

Use the following steps to configure Ranger User Sync for UNIX.

1. On the Customize Services page, select the **Ranger User Info** tab.
2. Click **Yes** under Enable User Sync.
3. Use the **Sync Source** drop-down to select UNIX, then set the following properties.

Table 5.6. UNIX User Sync Properties

Property	Description	Default Value
Sync Source	Only sync users above this user ID.	500
Password File	The location of the password file on the Linux server.	/etc/passwd
Group File	The location of the groups file on the Linux server.	/etc/group

Add Service Wizard

The screenshot shows the 'Add Service Wizard' interface. On the left, there's a navigation bar with 'Review', 'Install, Start and Test', and 'Summary'. In the center, a message says 'There are 6 configuration changes in 4 services' with a 'Show Details' link. Below this, there are tabs for 'Group', 'Default (3)', 'Manage Config Groups', and a 'Filter...' dropdown. The 'Ranger Admin' tab is active. The main area is titled 'Ranger User Info' and contains the following configuration fields:

- Enable User Sync:** A button labeled 'Yes' is selected.
- Sync Source:** A dropdown menu shows 'UNIX' selected.
- Minimum User ID:** A text input field contains the value '500'.
- Password File:** A text input field contains the path '/etc/passwd'.

5.3.2.2.2. Configuring Ranger User Sync for LDAP/AD

Use the following steps to configure Ranger User Sync for LDAP/AD.

1. On the Customize Services page, select the **Ranger User Info** tab.
2. Click **Yes** under Enable User Sync.
3. Use the **Sync Source** drop-down to select LDAP/AD.
4. Set the following properties on the Common Configs tab.

Table 5.7. LDAP/AD Common Configs

Property	Description	Default Value	Sample Values
LDAP/AD URL	Add URL depending upon LDAP/AD sync source	ldap:///{host}:{port}	ldap:/// ldap.example.com:389 or ldaps:/// ldap.example.com:636
Bind Anonymous	If Yes is selected, the Bind User and Bind User Password are not required.	NO	
Bind User	The location of the groups file on the Linux server.	The full distinguished name (DN), including common name (CN), of an LDAP/AD user account that has privileges to search for users. The LDAP bind DN is used to connect to LDAP and query for users and groups.	cn=admin,dc=example,dc=com or admin@example.com
Bind User Password	The password of the Bind User.		

Add Service Wizard

Group Default (1) Manage Config Groups Filter... Ranger Admin Ranger User Info Ranger Plugin Ranger Audit Ranger Tagsync Advanced

Ranger User Info

Enable User Sync: Yes

Sync Source: LDAP/AD

User Configs Group Configs

LDAP/AD URL: ldap://172.22.126.180:389

Bind Anonymous: No

Bind User: cn=Manager,dc=qe,dc=hortonworks,dc=com

Bind User Password: [Masked]

5. Set the following properties on the User Configs tab.

Table 5.8. LDAP/AD User Configs

Property	Description	Default Value	Sample Values
Group User Map Sync	Sync specific groups for users.	Yes	Yes
Username Attribute	The LDAP user name attribute.		sAMAccountName for AD, uid or cn for OpenLDAP
User Object Class	Object class to identify user entries.	person	top, person, organizationalPerson, user, or posixAccount
User Search Base	Search base for users. Ranger can search multiple OUs in AD. Ranger UserSync module performs a user search on each configured OU and adds all the users into single list. Once all the OUs are processed, a user's group membership is computed based on the group search.		cn=users,dc=example,dc=com;ou=example1,ou=example2,dc=example,dc=com
User Search Filter	Optional additional filter constraining the users selected for syncing.		Sample filter to retrieve all the users: cn=* Sample filter to retrieve all the users who are members of groupA or groupB: ((memberof=CN=GroupA,OU=groups,DC=example,DC=com)(memberof=CN=GroupB,OU=groups,DC=example,DC=com))
User Search Scope	This value is used to limit user search to the depth from search base.	sub	base, one, or sub
User Group Name Attribute	Attribute from user entry whose values would be treated as group values to be pushed into the Access Manager database. You can provide multiple attribute names separated by commas.	memberof,ismemberof	memberof, ismemberof, or gidNumber
Enable User Search	This option is available only when the "Enable Group Search First" option is selected.	No	Yes

Add Service Wizard

Ranger User Info

Enable User Sync
 Yes

Sync Source
 LDAP/AD

Common Configs User Configs Group Configs

Username Attribute
 uid

User Object Class
 person

User Search Base
 dc=q;dc=hortonworks;dc=com

User Search Filter
 sub

User Search Scope
 sub

User Group Name Attribute
 memberof, ismemberof

Group User Map Sync
 Yes

Enable User Search
 Yes

6. Set the following properties on the Group Configs tab.

Table 5.9. LDAP/AD Group Configs

Property	Description	Default Value	Sample Values
Enable Group Sync	If Enable Group Sync is set to No, the group names the users belong to are derived from "User Group Name Attribute". In this case no additional group filters are applied.	No	Yes

Property	Description	Default Value	Sample Values
	If Enable Group Sync is set to Yes, the groups the users belong to are retrieved from LDAP/AD using the following group-related attributes.		
Group Member Attribute	The LDAP group member attribute name.		member
Group Name Attribute	The LDAP group name attribute.		distinguishedName for AD, cn for OpenLdap
Group Object Class	LDAP Group object class.		group, groupofnames, or posixGroup
Group Search Base	Search base for groups. Ranger can search multiple OUs in AD. Ranger UserSync module performs a user search on each configured OU and adds all the users into single list. Once all the OUs are processed, a user's group membership is computed based on the group search configuration. Each OU segment needs to be separated by a ; (semi-colon).		ou=groups,DC=example,DC=com;ou=group1;ou=
Group Search Filter	Optional additional filter constraining the groups selected for syncing.		Sample filter to retrieve all groups: cn=* Sample filter to retrieve only the groups whose cn is Engineering or Sales: ((cn=Engineering)(cn=Sales))
Enable Group Search First	When Enable Group Search First is selected, there are two possible ways of retrieving users: <ul style="list-style-type: none">• If Enable User Search is not selected: users are retrieved from the "member" attribute of the group.• If Enable User Search is selected: user membership is computed by performing an LDAP search based on the user configuration.	No	Yes

Add Service Wizard

Ranger Admin Ranger User Info **Ranger Plugin** Ranger Audit Advanced

Ranger User Info

Enable User Sync:

Sync Source: LDAPvAD

Common Configs User Configs **Group Configs**

Enable Group Sync:

Group Member Attribute: member

Group Name Attribute: cn

Group Object Class: groupOfNames

Group Search Base: dc=ge;dc=hortonworks;dc=com

Group Search Filter: cn=%

Enable Group Search First:

ON ON ON ON ON ON ON ON

5.3.2.3. Specify Plugins to Enable

From the **Ranger Plugin** tab, use the **ON/OFF** slider to indicate which plugins you want to enable. You can also enable plugins at a later time.

If you select the Storm or Kafka plugins here, they are not enabled until you also enable Kerberos.


The screenshot shows the 'Add Service Wizard' interface. On the left, a sidebar lists steps: 'Assign Slaves and Clients', 'Customize Services' (which is selected and highlighted in dark grey), 'Configure Identities', 'Review', 'Install, Start and Test', and 'Summary'. The main panel has a header: 'We have come up with recommended configurations for the services you selected. Customize them as you see fit.' Below this is a navigation bar with tabs: ZooKeeper, Storm, Ambari Infra, Ambari Metrics, Kafka, Log Search, Ranger (with a red notification badge '1'), NiFi, and Misc. A yellow banner at the top states: 'There are 12 configuration changes in 4 services Show Details'. Below the banner is a search/filter bar with 'Group', 'Default (3)', 'Manage Config Groups', 'Filter...', and a dropdown. The main content area is titled 'Ranger Plugin' and contains three sections: 'NIPI Ranger Plugin' (ON), 'Storm Ranger Plugin' (ON), and 'Kafka Ranger Plugin' (ON). At the bottom of this section is a warning: '⚠ Attention: Some configurations need your attention before you can proceed. Show me properties with issues'. At the very bottom are 'Back' and 'Next →' buttons.

5.3.2.4. Ranger Audit Settings

Apache Ranger uses Apache Solr to store audit logs and provides UI searching through the audit logs. Solr must be installed and configured before installing Ranger Admin or any of the Ranger component plugins. The default configuration for Ranger Audits to Solr uses the shared Solr instance provided under the Ambari Infra service. Solr is both memory and CPU intensive. If your production system has high volume of access requests, make sure that the Solr host has adequate memory, CPU, and disk space.

SolrCloud is the preferred setup for production usage of Ranger. SolrCloud, which is deployed with the Ambari Infra service, is a scalable architecture that can run as a single node or multi-node cluster. It has additional features such as replication and sharding, which is useful for high availability (HA) and scalability. You should plan your deployment based on your cluster size. Because audit records can grow dramatically, plan to have at least 1 TB of free space in the volume on which Solr will store the index data. Solr works well with a minimum of 32 GB of RAM. You should provide as much memory as possible to the Solr process. It is highly recommended to use SolrCloud with at least two Solr nodes running on different servers with replication enabled. SolrCloud also requires Apache ZooKeeper.

1. On the Customize Services page, select the **Ranger Audit** tab.
2. Under Audit to Solr, click **OFF** under SolrCloud to enable SolrCloud. The button label will change to **ON**, and the SolrCloud configuration settings will be loaded automatically.



5.3.2.5. Configure Ranger Authentication

This section describes how to configure Ranger authentication for UNIX, LDAP, and AD.

- [Configuring Ranger UNIX Authentication \[48\]](#)
- [Configuring Ranger LDAP Authentication \[49\]](#)
- [Configuring Ranger Active Directory Authentication \[52\]](#)

5.3.2.5.1. Configuring Ranger UNIX Authentication

Use the following steps to configure Ranger authentication for UNIX.

1. Select the Advanced tab on the Customize Services page.
2. Under Ranger Settings, specify the Ranger Access Manager/Service Manager host address in the **External URL** box in the format `http://<your_ranger_host>:6080`.
3. Under Ranger Settings, select **UNIX**.

HTTP is enabled by default – if you disable HTTP, only HTTPS is allowed.

4. Under UNIX Authentication Settings, set the following properties.

Table 5.10. UNIX Authentication Settings

Property	Description	Default Value	Example Value
Allow remote Login	Flag to enable/disable remote login. Only applies to UNIX authentication.	true	true
ranger.unixauth.service.hostname	The address of the host where the UNIX authentication service is running.	<code>{ {ugsync_h{ost}sync_host} }</code>	
ranger.unixauth.service.port	The port number on which the UNIX authentication service is running.	5151	5151

**Note**

Properties with value `{ {xyz} }` are macro variables that are derived from other specified values in order to streamline the configuration process. Macro variables can be edited if required – if you need to restore the original value, click the Set Recommended symbol at the right of the property box.

5.3.2.5.2. Configuring Ranger LDAP Authentication

Use the following steps to configure Ranger authentication for LDAP.

1. Select the Advanced tab on the Customize Services page.
2. Under Ranger Settings, specify the Ranger Access Manager/Service Manager host address in the **External URL** box in the format `http://<your_ranger_host>:6080`.

3. Under Ranger Settings, select **LDAP**.
4. Under LDAP Settings, set the following properties.

Table 5.11. LDAP Authentication Settings

Property	Description	Default Value	Example Value
ranger.ldap.base_dn	The Distinguished Name (DN) of the starting point for directory server searches.	dc=example,dc=com	dc=example,dc=com
Bind User	The full Distinguished Name (DN), including Common Name (CN) of an LDAP user account that has privileges to search for users. This is a macro variable value that is derived from the Bind User value from Ranger User Info > Common Configs.	<code>{}{ranger_ug_ldap_bind_dn}{{ranger_ug_ldap_bind_dn}}</code>	
Bind User Password	Password for the Bind User. This is a macro variable value that is derived from the Bind User Password value from Ranger User Info > Common Configs.		
ranger.ldap.group.roleattribute	The LDAP group role attribute.	cn	cn
ranger.ldap.referral	See description below.	ignore	follow ignore throw
LDAP URL	The LDAP server URL. This is a macro variable value that is derived from the LDAP/AD URL value from Ranger	<code>{}{ranger_ug_ldap_url}</code>	<code>{}{ranger_ug_ldap_url}</code>

Property	Description	Default Value	Example Value
	User Info > Common Configs.		
ranger.ldap.user.dnpattern	The user DN pattern is expanded when a user is being logged in. For example, if the user "ldapadmin" attempted to log in, the LDAP Server would attempt to bind against the DN "uid=ldapadmin,ou=users,dc=example,dc=com" using the password the user provided>	uid={0},ou=users,dc=xasecure,dc=net	cn=ldapadmin,ou=Users,dc=example,dc=com
User Search Filter	The search filter used for Bind Authentication. This is a macro variable value that is derived from the User Search Filter value from Ranger User Info > User Configs.	{ {ranger_ug_ldap_user_sea{<filter>}ug_ldap_user_searchfilter} }	



Note

Properties with value { {xyz} } are macro variables that are derived from other specified values in order to streamline the configuration process. Macro variables can be edited if required – if you need to restore the original value, click the Set Recommended symbol at the right of the property box.


There are three possible values for `ranger.ldap.referral`: `follow`, `throw`, and `ignore`. The recommended setting is `follow`.

When searching a directory, the server might return several search results, along with a few continuation references that show where to obtain further results. These results and references might be interleaved at the protocol level.

- When this property is set to `follow`, the LDAP service provider processes all of the normal entries first, and then follows the continuation references.
- When this property is set to `throw`, all of the normal entries are returned in the enumeration first, before the `ReferralException` is thrown. By contrast, a

"referral" error response is processed immediately when this property is set to `follow` or `throw`.

- When this property is set to `ignore`, it indicates that the server should return referral entries as ordinary entries (or plain text). This might return partial results for the search.



5.3.2.5.3. Configuring Ranger Active Directory Authentication

Use the following steps to configure Ranger authentication for Active Directory.

- Select the Advanced tab on the Customize Services page.
- Under Ranger Settings, specify the Ranger Access Manager/Service Manager host address in the External URL box in the format `http://<your_ranger_host>:6080`.
- Under Ranger Settings, select **ACTIVE_DIRECTORY**.
- Under AD Settings, set the following properties.

Table 5.12. AD Settings

Property	Description	Default Value	Example Value
ranger.ldap.ad.base_dn	The Distinguished Name (DN) of the starting point for directory server searches.	dc=example,dc=com	dc=example,dc=com
ranger.ldap.ad.bind_dn	The full Distinguished Name (DN), including Common Name (CN) of an LDAP user account that has privileges to search for users. This is a macro variable value that is derived from the Bind User value from Ranger User Info > Common Configs .	<code>{ {ranger_ug_ldap_bind_dn} }{ {ranger_ug_ldap_bind_dn} }</code>	
ranger.ldap.ad.bind.password	Password for the bind_dn. This is a macro variable value that is derived from the Bind User Password value from Ranger User Info > Common Configs .		
Domain Name (Only for AD)	The domain name of the AD Authentication service.		dc=example,dc=com
ranger.ldap.ad.referral	See description below.	ignore	follow ignore throw
ranger.ldap.ad.url	The AD server URL. This is a macro variable value that is derived from the LDAP/AD URL value from Ranger User Info > Common Configs .	<code>{ {ranger_ug_ldap_url} }</code>	<code>{ {ranger_ug_ldap_url} }</code>
ranger.ldap.ad.user.searchfilter	The search filter used for Bind Authentication. This is a macro variable value that is derived from the User Search Filter value from Ranger User Info > User Configs .	<code>{ {ranger_ug_ldap_user_searchfilter} }</code>	<code>{ {ranger_ug_ldap_user_searchfilter} }</code>



Note


Properties with value `{ {xyz} }` are macro variables that are derived from other specified values in order to streamline the configuration process. Macro variables can be edited if required – if you need to restore the original value, click the Set Recommended symbol at the right of the property box.

There are three possible values for `ranger.ldap.ad.referral`: `follow`, `throw`, and `ignore`. The recommended setting is `follow`.

When searching a directory, the server might return several search results, along with a few continuation references that show where to obtain further results. These results and references might be interleaved at the protocol level.


- When this property is set to `follow`, the AD service provider processes all of the normal entries first, and then follows the continuation references.

- When this property is set to `throw`, all of the normal entries are returned in the enumeration first, before the `ReferralException` is thrown. By contrast, a "referral" error response is processed immediately when this property is set to `follow` or `throw`.
- When this property is set to `ignore`, it indicates that the server should return referral entries as ordinary entries (or plain text). This might return partial results for the search. In the case of AD, a `PartialResultException` is returned when referrals are encountered while search results are processed.



When you have finished configuring all of the Customize Services Settings, click **Next** at the bottom of the page to continue with the installation.

5. When you save the authentication method as Active Directory, a Dependent Configurations pop-up may appear recommending that you set the authentication method as LDAP. This recommended configuration should not be applied for AD, so you should clear (un-check) the `ranger.authentication.method` check box, then click **OK**.



5.3.3. Complete the Ranger Installation

1. On the Review page, carefully review all of your settings and configurations. If everything looks good, click **Deploy** to install Ranger on the Ambari server.

Add Service Wizard

The screenshot shows the 'Review' step of the 'Add Service Wizard'. On the left, a sidebar lists steps: Choose Services, Assign Masters, Assign Slaves and Clients, Customize Services, Configure Identities, Review (which is highlighted), Install, Start and Test, and Summary. The main area is titled 'Review' and contains the following information:

- Admin Name :** admin
- Cluster Name :** HDF
- Total Hosts :** 3 (0 new)
- Repositories:**
 - debian7 (#HDF-2.0):
http://s3.amazonaws.com/dev.hortonworks.com/HDF/debian7/2.x/BUILDS/2.0.0.0-567
 - debian7 (#HDP-UTILS-1.1.0.21):
http://public-repo-1.hortonworks.com/HDP-UTILS-1.1.0.21/repos/debian6
 - redhat6 (#HDF-2.0):
http://s3.amazonaws.com/dev.hortonworks.com/HDF/centos6/2.x/BUILDS/2.0.0.0-567
 - redhat6 (#HDP-UTILS-1.1.0.21):
http://public-repo-1.hortonworks.com/HDP-UTILS-1.1.0.21/repos/centos6
 - redhat7 (#HDF-2.0):
http://s3.amazonaws.com/dev.hortonworks.com/HDF/centos7/2.x/BUILDS/2.0.0.0-567
 - redhat7 (#HDP-UTILS-1.1.0.21):
http://public-repo-1.hortonworks.com/HDP-UTILS-1.1.0.21/repos/centos7
 - suse11 (#HDF-2.0):
http://s3.amazonaws.com/dev.hortonworks.com/HDF/suse11sp3/2.x/BUILDS/2.0.0.0-567

At the bottom right are 'Print' and 'Deploy' buttons.

2. When you click **Deploy**, Ranger is installed on the specified host on your Ambari server. A progress bar displays the installation progress.

The screenshot shows the 'Install, Start and Test' step of the 'Add Service Wizard'. The sidebar shows 'Install, Start and Test' is selected. The main area displays a progress bar and a table of host status:

Host	Status	Message
c6401.ambari.apache.org	8%	Installing Ranger Admin
c6402.ambari.apache.org	33%	Install complete (Waiting to start)
c6403.ambari.apache.org	33%	Install complete (Waiting to start)

Below the table, it says '3 of 3 hosts showing - Show All'. At the bottom right is a 'Next >' button.

3. When the installation is complete, a Summary page displays the installation details. You may need to restart services for cluster components after installing Ranger.



Note

If the installation fails, you should complete the installation process, then reconfigure and reinstall Ranger.

5.3.4. Advanced Usersync Settings

To access Usersync settings, select the **Advanced** tab on the Customize Service page. Usersync pulls in users from UNIX, LDAP, or AD and populates Ranger's local user tables with these users.

5.3.4.1. UNIX Usersync Settings

If you are using UNIX authentication, the default values for the Advanced ranger-ugsync-site properties are the settings for UNIX authentication.

Advanced ranger-ugsync-site

ranger.usersync.ldap.bindkeystore	<input type="text"/>		
ranger.usersync.ldap.bindpassword	Type password <input type="password"/> Retype Password <input type="password"/>		
ranger.usersync.group.memberattributename	<input type="text"/>		
ranger.usersync.group.nameattribute	<input type="text"/>		
ranger.usersync.group.objectclass	<input type="text"/>		
ranger.usersync.group.searchbase	<input type="text"/>		
ranger.usersync.group.searchenabled	false <input type="text"/>		
ranger.usersync.group.searchfilter	<input type="text"/>		
ranger.usersync.group.searchscope	<input type="text"/>		
ranger.usersync.group.usermodelsyncenabled	false <input type="text"/>		
ranger.usersync.ldap.searchBase	dc=hadoop,dc=apache,dc=org <input type="text"/>		
ranger.usersync.source.impl.class	org.apache.ranger.ugsync.process.UnixUserGroupBuilder <input type="text"/>		
ranger.usersync.credstore.filename	/usr/hdp/current/ranger-usersync/conf/ugsync.jceks <input type="text"/>		
ranger.usersync.enabled	true <input type="text"/>		
ranger.usersync.filesource.file	/tmp/Usergroup.txt <input type="text"/>		
ranger.usersync.filesource.text.delimiter	. <input type="text"/>		
ranger.usersync.keystore.file	/usr/hdp/current/ranger-usersync/conf/unixauthservice.jks <input type="text"/>		

5.3.4.2. Required LDAP and AD Usersync Settings

If you are using LDAP authentication, you must update the following Advanced ranger-ugsync-site properties.

Table 5.13. LDAP Advanced ranger-ugsync-site Settings

Property Name	LDAP Value
ranger.usersync.ldap.bindkeystore	Set this to the same value as the ranger.usersync.credstore.filename property, i.e, the default value is /usr/hdp/current/ranger-usersync/conf/ugsync.jceks
ranger.usersync.ldap.bindalias	ranger.usersync.ldap.bindalias

Property Name	LDAP Value
ranger.usersync.source.impl.class	ldap

Table 5.14. AD Advanced ranger-ugsync-site Settings

Property Name	LDAP Value
ranger.usersync.source.impl.class	ldap

5.3.4.3. Additional LDAP and AD Usersync Settings

If you are using LDAP or Active Directory authentication, you may need to update the following properties, depending upon your specific deployment characteristics.

Table 5.15. Advanced ranger-ugsync-site Settings for LDAP and AD

Property Name	LDAP ranger-ugsync-site Value	AD ranger-ugsync-site Value
ranger.usersync.ldap.url	ldap://127.0.0.1:389	ldap://ad-conrowoller-hostname:389
ranger.usersync.ldap.binddn	cn=ldapadmin,ou=users,dc=example,dc=com	cn=adadmin,cn=Users,dc=example,dc=com
ranger.usersync.ldap ldapbindpassword	secret	secret
ranger.usersync.ldap.searchBase	dc=example,dc=com	dc=example,dc=com
ranger.usersync.source.impl.class	org.apache.ranger.ladpusync.process.LdapUserGroupBuilder	
ranger.usersync.ldap.user.searchbase	ou=users, dc=example, dc=com	dc=example,dc=com
ranger.usersync.ldap.user.searchscope	sub	sub
ranger.usersync.ldap.user.objectclass	person	person
ranger.usersync.ldap.user.searchfilter	Set to single empty space if no value. Do not leave it as "empty"	(objectcategory=person)
ranger.usersync.ldap.user.nameattribute	uid or cn	sAMAccountName
ranger.usersync.ldap.user.groupnameattribute	memberof,ismemberof	memberof,ismemberof
ranger.usersync.ldap.username.caseconversion	none	none
ranger.usersync.ldap.groupname.caseconversion	none	none
ranger.usersync.group.searchenabled *	false	false
ranger.usersync.group.usermodelsyncenabled *	false	false
ranger.usersync.group.searchbase *	ou=groups, dc=example, dc=com	dc=example,dc=com
ranger.usersync.group.searchscope *	sub	sub
ranger.usersync.group.objectclass *	groupofnames	groupofnames

Property Name	LDAP ranger-ugsync-site Value	AD ranger-ugsync-site Value
ranger.usersync.group.searchfilter *	needed for AD authentication	(member=CN={0}, OU=MyUsers, DC=AD-HDF, DC=COM)
ranger.usersync.group.nameattribute *	cn	cn
ranger.usersync.group.memberattributename *	member	member
ranger.usersync.pagedresultsenabled *	true	true
ranger.usersync.pagedresultssize *	500	500
ranger.usersync.user.searchenabled *	false	false
ranger.usersync.group.search.first.enabled *	false	false

* Only applies when you want to filter out groups.

After you have finished specifying all of the settings on the Customize Services page, click **Next** at the bottom of the page to continue with the installation.

5.3.5. Configuring Ranger for LDAP SSL

You can use the following steps to configure LDAP SSL using self-signed certs in the default Ranger User Sync TrustStore.

1. The default location is /usr/hdf/current/ranger-usersync/conf/mytruststore.jks for the ranger.usersync.truststore.file property.
2. Alternatively, copy and edit the self-signed ca certs.
3. Set the ranger.usersync.truststore.file property to that new cacert file.

```
cd /usr/hdp/<version>/ranger-usersync
service ranger-usersync stop
service ranger-usersync start
```

Where cert.pem has the LDAPS cert.

5.3.6. Setting up Database Users Without Sharing DBA Credentials

If do not wish to provide system Database Administrator (DBA) account details to the Ambari Ranger installer, you can use the dba_script.py Python script to create Ranger DB database users without exposing DBA account information to the Ambari Ranger installer. You can then run the normal Ambari Ranger installation without specify a DBA user name and password.

To create Ranger DB users using the dba_script.py script:

1. Download the Ranger rpm using the yum install command.

```
yum install ranger-admin
```

2. You should see one file named `dba_script.py` in the `/usr/hdf/current/ranger-admin` directory.
3. Get the script reviewed internally and verify that your DBA is authorized to run the script.
4. Execute the script by running the following command:

```
python dba_script.py
```

5. Pass all values required in the argument. These should include `db flavor`, `JDBC jar`, `db host`, `db name`, `db user`, and other parameters.

- If you would prefer not to pass runtime arguments via the command prompt, you can update the `/usr/hdf/current/ranger-admin/install.properties` file and then run:

- ```
python dba_script.py -q
```

When you specify the `-q` option, the script will read all required information from the `install.properties` file

- You can use the `-d` option to run the script in "dry" mode. Running the script in dry mode causes the script to generate a database script.

```
python dba_script.py -d /tmp/generated-script.sql
```

Anyone can run the script, but it is recommended that the system DBA run the script in dry mode. In either case, the system DBA should review the generated script, but should only make minor adjustments to the script, for example, change the location of a particular database file. No major changes should be made that substantially alter the script – otherwise the Ranger install may fail.

The system DBA must then run the generated script.

6. Run the Ranger Ambari install procedure, but set **Setup Database and Database User** to **No** in the Ranger Admin section of the Customize Services page.

### 5.3.7. Updating Ranger Admin Passwords

For the following users, if you update the passwords on the Ranger Configs page, you must also update the passwords on the Configs page of each Ambari component that has the Ranger plugin enabled. Individual Ambari component configurations are not automatically updated – the service restart will fail if you do not update these passwords on each component.

- Ranger Admin user – The credentials for this user are set in **Configs > Advanced ranger-env** in the fields labeled **admin\_username** (default value: `admin`) and **admin\_password** (default value: `admin`).
- Admin user used by Ambari to create repo/policies – The user name for this user is set in **Configs > Admin Settings** in the field labeled **Ranger Admin username for Ambari** (default value: `amb_ranger_admin`). The password for this user is set in the field labeled **Ranger Admin user's password for Ambari**. This password is specified during the Ranger installation.

The following image shows the location of these settings on the Ranger Configs page:

The screenshot shows the 'Ranger Configs' page with the 'Ranger' tab selected. A purple arrow points from the text 'amb\_ranger\_admin user details' to the 'ranger\_admin\_username' field, which contains 'amb\_ranger\_admin'. Another orange arrow points from the text 'Ranger 'admin' user details' to the 'admin\_username' field, which also contains 'admin'. The page displays various configuration sections like Admin Settings, DB Settings, Ranger Settings, Unix Authentication Settings, AD Settings, LDAP Settings, Advanced ranger-admin-site, and Advanced ranger-env.

## 5.3.8. Enabling Ranger Plugins

If you did not enable Ranger plugins during the initial Ranger installation, you can enable them later. This section describes how to enable each of these plugins. For performance reasons, it is recommended that you store audits in Solr, and not in a database.

If you are using a Kerberos-enabled cluster, there are a number of additional steps you must follow to ensure that you can use the Ranger plugins on a Kerberos cluster.

The following Ranger plugins are available:

- [Kafka \[61\]](#)
- [Storm \[65\]](#)
- [NiFi \[68\]](#)

### 5.3.8.1. Kafka

Use the following steps to enable the Ranger Kafka plugin.


1. On the Ranger Configs page, select the **Ranger Plugin** tab.

The screenshot shows the Ambari interface with the 'Ranger' service selected in the sidebar. The main panel displays the 'Ranger Plugin' configuration. Under the 'Ranger Plugin' section, there are six plugin configurations: HDFS Ranger Plugin (ON), YARN Ranger Plugin (ON), Hive Ranger Plugin (ON), Hbase Ranger Plugin (ON), Storm Ranger Plugin (OFF), and Atlas Ranger Plugin (OFF). A note at the bottom of the configuration area states: "admin authored on Fri, Jul 22, 2016 19:25". At the top right, there are 'Discard' and 'Save' buttons.

2. Under Kafka Ranger Plugin, select **On**, then click **Save** in the black menu bar.

This screenshot shows the same 'Ranger Plugin' configuration page as above, but with a red box highlighting the 'ON' button for the 'Kafka Ranger Plugin'. The other five plugins remain in their previous states: HDFS, YARN, and Hive are ON; Hbase and Storm are OFF.

3. A Save Configuration pop-up appears. Type in a note describing the changes you just made, then click **Save**.




4. A Dependent Configuration pop-up appears. Click **OK** to confirm the configuration updates.

A screenshot of a 'Dependent Configurations' dialog box. It shows a table of configuration changes recommended by Ambari. The table has columns: Property, Service, Config Group, File Name, Current Value, and Recommended Value. Two rows are listed:

| Property                                                  | Service | Config Group | File Name    | Current Value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Recommended Value                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-----------------------------------------------------------|---------|--------------|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> authorizer.class.name | Kafka   | Default      | kafka-broker |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | org.apache.ranger.authorization.kafka.authorizer.RangerKafkaAuthorizer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <input checked="" type="checkbox"/> content               | Kafka   | Default      | kafka-log4j  | # Licensed to the Apache Software Foundation (ASF) under one or more contributor license agreements. See the NOTICE file distributed with this work for additional information regarding copyright ownership. The ASF licenses this file to you under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at <a href="http://www.apache.org/licenses/LICENSE-2.0">http://www.apache.org/licenses/LICENSE-2.0</a> Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License. | # Licensed to the Apache Software Foundation (ASF) under one or more contributor license agreements. See the NOTICE file distributed with this work for additional information regarding copyright ownership. The ASF licenses this file to you under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at <a href="http://www.apache.org/licenses/LICENSE-2.0">http://www.apache.org/licenses/LICENSE-2.0</a> Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License. |

At the bottom right of the dialog box are 'Cancel' and 'OK' buttons, with 'OK' being highlighted with a red box.


5. Click **OK** on the Save Configuration Changes pop-up.



6. Select **Kafka** in the navigation menu, then select **Restart > Restart All Affected** to restart the Kafka service and load the new configuration.

A screenshot of the Ambari web interface. The left sidebar shows various services: HDFS, MapReduce2, YARN, Tez, Hive, HBase, Pig, Sqoop, Oozie, ZooKeeper, Falcon, Storm, Fume, Accumulo, Ambari Metrics, and Atlas. The "Kafka" service is selected and highlighted with a dark gray background. The main content area shows the "Configs" tab for the Kafka Broker. It displays configuration parameters like "Kafka Broker host" (c6403.ambari.apache.org), "zookeeper.connect" (c6403.ambari.apache.org:2181), "log.dirs" (/kafka-logs), "log.retention.hours" (168), "log.roll.hours" (168), and "listeners" (PLAINTEXT://localhost:6667). Above the configuration table, a yellow banner says "Restart Required: 1 Component on 1 Host". To the right of the banner, there is a "Service Actions" dropdown with an orange "Restart" button. Below the configuration table, there are "Discard" and "Save" buttons. A red box highlights the "Restart All Affected" button in the "Service Actions" dropdown.

7. Click **Confirm Restart All** on the confirmation pop-up to confirm the Kafka restart.



8. After Kafka restarts, the Ranger plugin for Kafka will be enabled.

### 5.3.8.2. Storm


Use the following steps to enable the Ranger Storm plugin.

1. On the Ranger Configs page, select the **Ranger Plugin** tab.


A screenshot of the Ambari interface showing the Ranger Configs page. The left sidebar has a "Ranger" section selected. The main area shows the "Configs" tab is active, displaying configuration groups V3, V2, and V1. Below this, the "Ranger Plugin" tab is selected. The "Ranger Plugin" section contains several configuration items with "ON" status indicators:

| Plugin              | Status |
|---------------------|--------|
| HDFS Ranger Plugin  | ON     |
| YARN Ranger Plugin  | ON     |
| Hbase Ranger Plugin | ON     |
| Storm Ranger Plugin | OFF    |
| Knox Ranger Plugin  | ON     |
| Kafka Ranger Plugin | ON     |
| Hive Ranger Plugin  | ON     |
| Atlas Ranger Plugin | OFF    |


2. Under Storm Ranger Plugin, select **On**, then click **Save** in the black menu bar.




3. A Save Configuration pop-up appears. Type in a note describing the changes you just made, then click **Save**.



4. A Dependent Configuration pop-up appears. Click **OK** to confirm the configuration updates.




5. Click **OK** on the Save Configuration Changes pop-up.



6. Select **Storm** in the navigation menu, then select **Restart > Restart All Affected** to restart the Storm service and load the new configuration.

7. Click **Confirm Restart All** on the confirmation pop-up to confirm the Storm restart.



8. After Storm restarts, the Ranger plugin for Storm will be enabled.


### 5.3.8.3. NiFi

Use the following steps to enable the Ranger NiFi plugin.

1. On the Ranger Configs page, select the **Ranger Plugin** tab.
2. Under NiFi Ranger Plugin, select **ON**, then click **Save** in the black menu bar.

A screenshot of the Ambari Ranger Configs interface. The left sidebar shows various services: ZooKeeper, Storm, Ambari Infra, Ambari Metrics, Kafka, Log Search, Ranger (selected), Kerberos, and NiFi. The main area has tabs for Summary and Configs, with Summary selected. Below is a "Manage Config Groups" section showing three groups: V3, V3, and V1, each with an "admin" author and "6 days ago" timestamp. A note at the bottom says "admin authored on Thu, Sep 08, 2016 18:54". Below this are tabs for Ranger Admin, Ranger User Info, Ranger Plugin (selected), Ranger Audit, Ranger Tagsync, and Advanced. The Ranger Plugin section shows three configurations: NIFI Ranger Plugin (ON), Storm Ranger Plugin (ON), and Kafka Ranger Plugin (ON). The "NIFI Ranger Plugin" row is highlighted with a blue border.

3. A Save Configuration pop-up appears. Type in a note describing the changes you just made, then click **Save**.
4. A Dependent Configuration pop-up appears. Click **OK** to confirm the configuration updates.
5. Click **OK** on the **Save Configuration Changes** pop-up.



- From the left navigation menu click **Actions**, then **Restart All Required** to restart NiFi and any additional plugins you have enabled.

The Ambari interface shows the 'Services' tab selected. The 'NIFI' service is highlighted in the tree view. In the 'Actions' dropdown, the option 'C Restart All Required' is highlighted with a red box.

- Click **Confirm Restart All** on the confirmation pop-up to confirm the NiFi restart along with any other services requiring a restart.

## Confirmation

You are about to restart Kafka, NiFi, Storm

This will trigger alerts as the service is restarted. To suppress alerts, turn on Maintenance Mode for services listed above prior to running Restart All Required

- After your services restart, the Ranger plugin is enabled.

## 5.4. Adding Users to Ranger

After installing Ranger and enabling the Ranger plugins, add users to Ranger.

- From the Ranger UI, click **Settings**, then **Users/Groups**.

| User Name                                      | Email Address | Role  | User Source | Groups               | Visibility |
|------------------------------------------------|---------------|-------|-------------|----------------------|------------|
| admin                                          |               | Admin | Internal    | -                    | Visible    |
| rangerusersync                                 |               | Admin | Internal    | -                    | Visible    |
| rangertagync                                   |               | Admin | Internal    | -                    | Visible    |
| logsearch                                      |               | User  | External    | logsearch            | Visible    |
| storm                                          |               | User  | External    | storm                | Visible    |
| infra-svr                                      |               | User  | External    | infra-svr            | Visible    |
| zookeeper                                      |               | User  | External    | zookeeper            | Visible    |
| amr                                            |               | User  | External    | amr                  | Visible    |
| ambari-qa                                      |               | User  | External    | qa, ambari-qa        | Visible    |
| kafka                                          |               | User  | External    | kafka                | Visible    |
| ranger                                         |               | User  | External    | ranger, hadoop       | Visible    |
| edfi                                           |               | User  | External    | edfi, hadoop         | Visible    |
| centos                                         |               | User  | External    | centos, john, centos | Visible    |
| amb_ranger_admin                               |               | Admin | Internal    | -                    | Visible    |
| abqwe-hdf-qe-docs-1.openstacklocal@Hortonworks |               | User  | Internal    | users                | Visible    |
| abqwe-hdf-qe-docs-2.openstacklocal@Hortonworks |               | User  | Internal    | users                | Visible    |
| abqwe-hdf-qe-docs-3.openstacklocal@Hortonworks |               | User  | Internal    | users                | Visible    |
| storm-hdf                                      |               | User  | External    | -                    | Visible    |
| stormtestuser                                  |               | User  | External    | -                    | Visible    |
| rangerlookup                                   |               | User  | External    | -                    | Visible    |

- Click **Add New User**.

- In the **User Detail** screen, provide:

- User Name in the `CN=<host> OU=<realm>` format. If you have set up identity mapping, use the `<host>@<realm>` format.
- The password the user will use to access Ranger.
- The Role you want the user to have.
- The Group you want the user to be part of.

**Ranger**   Access Manager   Audit   Settings

Users/Groups > User Create

### User Detail

User Name \*

New Password \*

Password Confirm \*

First Name \*

Last Name

Email Address

Select Role \*

Group *Please select*

**Save** **Cancel**

## 6. Authorization with Ranger

### 6.1. Creating Policies for NiFi Access

Once you have set up Ranger to manage NiFi authorization, you must create policies so that users can access and operate on the NiFi canvas.

- [Creating Policies to View NiFi \[72\]](#)
- [Allowing Users Read and Write Access \[74\]](#)

#### 6.1.1. Creating Policies to View NiFi

To allow users to view the NiFi UI, create the following policies for each host:

- /flow – read
- /proxy – read/write

To create policies:

1. From the Ranger console, click the NiFi Ranger plugin.



2. From the **List of Policies** page, click **Add New Policy**.
3. In the **Policy Details** dialog, create the /flow and /proxy policies.

**Create Policy**

**Policy Details :**

Policy Type: **Access**

Policy Name \*:

NiFi Resource Identifier \*:  **Include**

Audit Logging: **YES**

Description:

**Allow Conditions :**

| Select Group                                | Select User                                | Permissions                                             | Delegate Admin           |
|---------------------------------------------|--------------------------------------------|---------------------------------------------------------|--------------------------|
| <input type="button" value="Select Group"/> | <input type="button" value="Select User"/> | <b>Add Permissions</b> <input type="button" value="+"/> | <input type="checkbox"/> |
| <b>Add</b> <b>Cancel</b>                    |                                            |                                                         |                          |

4. To create the /flow policy:

a. Provide the following information:

- **Policy Name** – /flow
- **NiFi Resource Identifier**- /flow
- Select Users and Groups you want to immediately add.
- Add **Read** permission

b. Click **Add**.

5. To create the /proxy policy:

a. Provide the following information:

- **Policy Name** – /proxy
- **NiFi Resource Identifier**- /proxy
- Select Users and Groups you want to immediately add.
- Add **Read** and **Write** permissions.

b. Click **Add**.

## 6.1.2. Allowing Users Read and Write Access


To allow users complete read and write access to NiFi:

1. From the **Policy Details** page, select the global NiFi policy.
  - **Policy Name** – all - nifi-resource
  - **NiFi Resource Identifier** – x
2. Add users.
3. Add **Read** and **Write** permissions.

## 6.2. Create a Kafka Policy

To add a new policy to an existing Kafka service:

1. On the Service Manager page, select an existing service under Kafka.



The List of Policies page appears.

A screenshot of a 'List of Policies' page. The top navigation bar includes tabs for 'Ranger', 'Access Manager', 'Audit', 'Settings', and a user 'admin'. Below the navigation, a breadcrumb trail shows 'Service Manager &gt; Example-Service Policies'. The main area is titled 'List of Policies : Example-Service'. It features a search bar and a green 'Add New Policy' button. A table lists policies with columns: Policy ID, Policy Name, Status, Audit Logging, Groups, Users, and Action. One row is visible, showing Policy ID 13, Policy Name 'Example-Service-1-20160211205602', Status 'Enabled', Audit Logging 'Enabled', Groups empty, Users 'admin', and Action buttons.

2. Click **Add New Policy**.

The Create Policy page appears.

The screenshot shows the 'Create Policy' page in the Ranger Access Manager. The 'Policy Type' is set to 'Access'. The 'Policy Name' field is empty. The 'Topic' field contains 'topic1'. The 'Audit Logging' field is set to 'YES'. The 'Description' field is empty. The 'Allow Conditions' section includes tabs for 'Select Group', 'Select User', 'Policy Conditions', 'Permissions', and 'Delegate Admin'. Under 'Select Group', there is a 'Select Group' button and a '+' button. Under 'Select User', there is a 'Select User' button and a '+' button. Under 'Policy Conditions', there is a 'Add Conditions' button with a '+' icon. Under 'Permissions', there is a 'Add Permissions' button with a '+' icon. At the bottom of the page are 'Add' and 'Cancel' buttons.

3. Complete the Create Policy page as follows:

**Table 6.1. Policy Details**

| Field         | Description                                                                                                  |
|---------------|--------------------------------------------------------------------------------------------------------------|
| Policy Name   | Enter an appropriate policy name. This name cannot be duplicated across the system. This field is mandatory. |
| Topic         | A topic is a category or feed name to which messages are published.                                          |
| Description   | (Optional) Describe the purpose of the policy.                                                               |
| Audit Logging | Specify whether this policy is audited. (De-select to disable auditing).                                     |

**Table 6.2. Allow Conditions**

| Label             | Description                                                                                                                                                                                                                                                                                                                                 |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Select Group      | Specify the group to which this policy applies. To designate the group as an Administrator for the chosen resource, specify Admin permissions. (Administrators can create child policies based on existing policies).<br><br>The <b>public</b> group contains all users, so granting access to the public group grants access to all users. |
| Select User       | Specify a particular user to which this policy applies (outside of an already-specified group) OR designate a particular user as Admin for this policy. (Administrators can create child policies based on existing policies).                                                                                                              |
| Policy Conditions | Specify IP address range.                                                                                                                                                                                                                                                                                                                   |
| Permissions       | Add or edit permissions: Read, Write, Create, Admin, Select/Deselect All.                                                                                                                                                                                                                                                                   |


| Label          | Description                                                                                                                                                                                                                        |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Delegate Admin | When a policy is assigned to a user or a group of users those users become the delegated admin. The delegated admin can update, delete the policies. It can also create child policies based on the original policy (base policy). |

4. You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.
5. Click **Add**.

## 6.3. Create a Storm Policy

To add a new policy to an existing Storm service:

1. On the Service Manager page, select an existing service under Storm.



The List of Policies page appears.

The screenshot shows a 'List of Policies' page for 'Example-Service'. At the top, there is a navigation bar with tabs for 'Ranger', 'Access Manager', 'Audit', and 'Settings'. The 'admin' user is logged in. Below the navigation bar, the breadcrumb path shows 'Service Manager > Example-Service Policies'. The main area is titled 'List of Policies : Example-Service'. It features a search bar labeled 'Search for your policy...' and a green 'Add New Policy' button. A table lists one policy entry:

| Policy ID | Policy Name                      | Status  | Audit Logging | Groups | Users | Action |
|-----------|----------------------------------|---------|---------------|--------|-------|--------|
| 13        | Example-Service-1-20160211205602 | Enabled | Enabled       |        | admin |        |

2. Click **Add New Policy**.

The Create Policy page appears.

The screenshot shows the 'Create Policy' page in the Ranger Access Manager. At the top, there are tabs for 'Access Manager', 'Audit', and 'Settings'. The 'Access Manager' tab is selected. Below the tabs, the breadcrumb navigation shows 'Service Manager > Storm\_topologies Policies > Create Policy'. The main form is titled 'Create Policy' and contains the following fields:

- Policy Details:**
  - Policy Type:** Access (selected)
  - Policy Name \***: A text input field.
  - enabled**: A toggle switch set to 'enabled'.
  - Storm Topology \***: A text input field.
  - include**: A toggle switch set to 'include'.
  - Description**: A text input field.
  - Audit Logging**: A toggle switch set to 'YES'.
- Allow Conditions :** This section contains a table for defining access rules. The columns are: Select Group, Select User, Permissions, and Delegate Admin. There is also a 'Add Permissions' button and a '+' button to add new rows. The table currently has one row where both 'Select Group' and 'Select User' fields are empty, and the 'Permissions' column has a plus sign icon.
- Deny Conditions :** This section contains a table for defining denial rules. The columns are: Select Group, Select User, Permissions, and Delegate Admin. There is also a 'Add Permissions' button and a '+' button to add new rows. The table currently has one row where both 'Select Group' and 'Select User' fields are empty, and the 'Permissions' column has a plus sign icon.

At the bottom of the form are two buttons: 'Add' and 'Cancel'.

3. Complete the Create Policy page as follows:

**Table 6.3. Policy Details**

| Label          | Description                                                                                                     |
|----------------|-----------------------------------------------------------------------------------------------------------------|
| Policy Name    | Enter an appropriate policy name. This name is cannot be duplicated across the system. This field is mandatory. |
| Storm Topology | Enter an appropriate Topology Name.                                                                             |
| Description    | (Optional) Describe the purpose of the policy.                                                                  |
| Audit Logging  | Specify whether this policy is audited. (De-select to disable auditing).                                        |

**Table 6.4. Allow Conditions**

| Label          | Description                                                                                                                                                                                                                                                                                                                                 |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Select Group   | Specify the group to which this policy applies. To designate the group as an Administrator for the chosen resource, specify Admin permissions. (Administrators can create child policies based on existing policies).<br><br>The <b>public</b> group contains all users, so granting access to the public group grants access to all users. |
| Select User    | Specify a particular user to which this policy applies (outside of an already-specified group) OR designate a particular user as Admin for this policy. (Administrators can create child policies based on existing policies).                                                                                                              |
| Permissions    | Add or edit permissions: Read, Write, Create, Admin, Select/Deselect All.                                                                                                                                                                                                                                                                   |
| Delegate Admin | When a policy is assigned to a user or a group of users those users become the delegated admin. The delegated                                                                                                                                                                                                                               |

| Label | Description                                                                                                          |
|-------|----------------------------------------------------------------------------------------------------------------------|
|       | admin can update, delete the policies. It can also create child policies based on the original policy (base policy). |

Since Storm does not provide a command line methodology for assigning privileges or roles to users, the User and Group Permissions portion of the Storm Create Policy form is especially important.

**Table 6.5. Storm User and Group Permissions**

| Actions               | Description                                       |
|-----------------------|---------------------------------------------------|
| File upload           | Allows a user to upload files.                    |
| Get Nimbus Conf       | Allows a user to access Nimbus configurations.    |
| Get Cluster Info      | Allows a user to get cluster information.         |
| File Download         | Allows a user to download files.                  |
| Kill Topology         | Allows a user to kill the topology.               |
| Rebalance             | Allows a user to rebalance topologies.            |
| Activate              | Allows a user to activate a topology.             |
| Deactivate            | Allows a user to deactivate a topology.           |
| Get Topology Conf     | Allows a user to access a topology configuration. |
| Get Topology          | Allows a user to access a topology.               |
| Get User Topology     | Allows a user to access a user topology.          |
| Get Topology Info     | Allows a user to access topology information.     |
| Upload New Credential | Allows a user to upload a new credential.         |
| Admin                 | Provides a user with delegated admin access.      |

4. You can use the Plus (+) symbol to add additional conditions. Conditions are evaluated in the order listed in the policy. The condition at the top of the list is applied first, then the second, then the third, and so on.

5. Click **Add**.

## 7. NiFi Authorization

After you have configured NiFi to run securely and with an authentication mechanism, you must configure who has access to the system, and the level of their access. You can do this using *multi-tenant authorization*. Multi-tenant authorization enables multiple groups of users (tenants) to command, control, and observe different parts of the dataflow, with varying levels of authorization. When an authenticated user attempts to view or modify a NiFi resource, the system checks whether the user has privileges to perform that action. These privileges are defined by policies that you can apply system-wide or to individual components.

### 7.1. Authorizer Configuration

An *authorizer* grants users the privileges to manage users and policies by creating preliminary authorizations at startup.

Authorizers are configured using two properties in the *nifi.properties* file:

- The `nifi.authorizer.configuration.file` property specifies the configuration file where authorizers are defined. By default, the *authorizers.xml* file located in the root installation conf directory is selected.
- The `nifi.security.user.authorizer` property indicates which of the configured authorizers in the *authorizers.xml* file to use.

### 7.2. Authorizers.xml Setup

The *authorizers.xml* file is used to define and configure available authorizers. The default authorizer is the FileAuthorizer, however, you can develop additional authorizers as extensions. The FileAuthorizer has the following properties:

- Authorizations File - The file where the FileAuthorizer stores policies. By default, the *authorizations.xml* in the *conf* directory is chosen.
- Users File - The file where the FileAuthorizer stores users and groups. By default, the *users.xml* in the *conf* directory is chosen.
- Initial Admin Identity - The identity of an initial admin user that is granted access to the UI and given the ability to create additional users, groups, and policies. This property is only used when there are no other users, groups, and policies defined.
- Legacy Authorized Users File - The full path to an existing *authorized-users.xml* that is automatically converted to the multi-tenant authorization model. This property is only used when there are no other users, groups, and policies defined.
- Node Identity - The identity of a NiFi cluster node. When clustered, a property for each node should be defined, so that every node knows about every other node. If not clustered, these properties can be ignored.

## 7.2.1. Initial Admin Identity (New NiFi Instance)

If you are setting up a secured NiFi instance for the first time, you must manually designate an "Initial Admin Identity" in the *authorizers.xml* file. This initial admin user is granted access to the UI and given the ability to create additional users, groups, and policies. The value of this property could be a DN (when using certificates or LDAP) or a Kerberos principal. If you are the NiFi administrator, add yourself as the "Initial Admin Identity".

Here is an example LDAP entry using the name John Smith:

```
<authorizer>
 <identifier>file-provider</identifier>
 <class>org.apache.nifi.authorization.FileAuthorizer</class>
 <property name="Authorizations File">./conf/authorizations.xml</property>
 <property name="Users File">./conf/users.xml</property>
 <property name="Initial Admin Identity">cn=John Smith,ou=people,dc=example,dc=com</property>
 <property name="Legacy Authorized Users File"></property>
 <!--
 <property name="Node Identity 1"></property>
 <property name="Node Identity 2"></property>
 -->
</authorizer>
</authorizers>
```

Here is an example Kerberos entry using the name John Smith and realm NIFI.APACHE.ORG:

```
<authorizer>
 <identifier>file-provider</identifier>
 <class>org.apache.nifi.authorization.FileAuthorizer</class>
 <property name="Authorizations File">./conf/authorizations.xml</property>
 <property name="Users File">./conf/users.xml</property>
 <property name="Initial Admin Identity">johnsmith@NIFI.APACHE.ORG</property>
 <property name="Legacy Authorized Users File"></property>
 <!--
 <property name="Node Identity 1"></property>
 <property name="Node Identity 2"></property>
 -->
</authorizer>
</authorizers>
```

After you have edited and saved the *authorizers.xml* file, restart NiFi. The "Initial Admin Identity" user and administrative policies are added to the *users.xml* and *authorizations.xml* files during restart. Once NiFi starts, the "Initial Admin Identity" user is able to access the UI and begin managing users, groups, and policies.



### Note

For a brand new secure flow, providing the "Initial Admin Identity" gives that user access to get into the UI and to manage users, groups and policies. But if that user wants to start modifying the flow, they need to grant

themselves policies for the root process group. The system is unable to do this automatically because in a new flow the UUID of the root process group is not permanent until the `flow.xml.gz` is generated. If the NiFi instance is an upgrade from an existing `flow.xml.gz` or a 1.x instance going from unsecure to secure, then the "Initial Admin Identity" user is automatically given the privileges to modify the flow.

## 7.2.2. Legacy Authorized Users (NiFi Instance Upgrade)

If you are upgrading from a 0.x NiFi instance, you can convert your previously configured users and roles to the multi-tenant authorization model. In the `authorizers.xml` file, specify the location of your existing `authorized-users.xml` file in the "Legacy Authorized Users File" property.

Here is an example entry:

```
<authorizers>
 <authorizer>
 <identifier>file-provider</identifier>
 <class>org.apache.nifi.authorization.FileAuthorizer</class>
 <property name="Authorizations File">./conf/authorizations.xml</property>
 <property name="Users File">./conf/users.xml</property>
 <property name="Initial Admin Identity"></property>
 <property name="Legacy Authorized Users File">/Users/johnsmith/config_files/authorized-users.xml</property>
 </authorizer>
</authorizers>
```

After you have edited and saved the `authorizers.xml` file, restart NiFi. Users and roles from the `authorized-users.xml` file are converted and added as identities and policies in the `users.xml` and `authorizations.xml` files. Once the application starts, users who previously had a legacy Administrator role can access the UI and begin managing users, groups, and policies.

Here is a summary of policies assigned to each legacy role if the NiFi instance has an existing `flow.xml.gz`:

	Admin	DFM	Monitor	Provenance	NiFi	Proxy
view the UI	*	*	*			
view the controller	*	*	*		*	
modify the controller		*				
view system diagnostics		*	*			
view the dataflow	*	*	*			
modify the dataflow		*				
view the users/groups	*					
modify the users/groups	*					

	Admin	DFM	Monitor	Provenance	NiFi	Proxy
<b>view policies</b>	*					
<b>modify policies</b>	*					
<b>query provenance</b>				*		
<b>access restricted components</b>		*				
<b>view the data</b>		*		*		*
<b>modify the data</b>		*				*
<b>retrieve site-to-site details</b>					*	
<b>send proxy user requests</b>						*

For details on the policies in the table, see [Access Policies](#).

NiFi fails to restart if values exist for both the "Initial Admin Identity" and "Legacy Authorized Users File" properties. You can specify only one of these values to initialize authorizations.

Do not manually edit the *authorizations.xml* file. Create authorizations only during initial setup and afterwards using the NiFi UI.

### 7.2.3. Cluster Node Identities

If you are running NiFi in a clustered environment, you must specify the identities for each node. The authorization policies required for the nodes to communicate are created during startup.

For example, if you are setting up a 2 node cluster with the following DNs for each node:

```
cn=nifi-1,ou=people,dc=example,dc=com
cn=nifi-2,ou=people,dc=example,dc=com
```

```
<authorizer>
 <identifier>file-provider</identifier>
 <class>org.apache.nifi.authorization.FileAuthorizer</class>
 <property name="Authorizations File">./conf/authorizations.xml</property>
 <property name="Users File">./conf/users.xml</property>
 <property name="Initial Admin Identity">johnsmith@NIFI.APACHE.ORG</property>
 <property name="Legacy Authorized Users File"></property>
 <property name="Node Identity 1">cn=nifi-1,ou=people,dc=example,dc=com</property>
 <property name="Node Identity 2">cn=nifi-2,ou=people,dc=example,dc=com</property>
</authorizer>
</authorizers>
```

In a cluster, all nodes must have the same *authorizations.xml*. If a node has a different *authorizations.xml*, it cannot join the cluster. The only exception is if a node has an empty

*authorizations.xml*. In this scenario, the node inherits the *authorizations.xml* from the cluster.

Now that initial authorizations have been created, additional users, groups and authorizations can be created and managed in the NiFi UI.

## 7.3. Configuring Users & Access Policies


This section describes:

- How to create users and groups
- How access policies are used to define authorizations
- How to configure access policies by walking through specific examples

Instructions requiring interaction with the UI assume the application is being accessed by User1, a user with administrator privileges, such as the "Initial Admin Identity" user or a converted legacy admin user (see [Authorizers.xml Setup](#)).

### 7.3.1. Creating Users and Groups

From the UI, select "Users" from the Global Menu. This opens a dialog to create and manage users and groups.




Click the Add icon




).

To create a user, enter the *Identity* information relevant to the authentication method chosen to secure your NiFi instance. Click OK.



To create a group, select the "Group" radio button, enter the name of the group and select the users to be included in the group. Click OK.



### 7.3.2. Access Policies

You can manage the ability for users and groups to view or modify NiFi resources using *access policies*. There are two types of access policies that can be applied to a resource:

- View - If a view policy is created for a resource, only the users or groups that are added to that policy are able to see the details of that resource.
- Modify - If a resource has a modify policy, only the users or groups that are added to that policy can change the configuration of that resource.

You can create and apply access policies on both global and component levels.

#### 7.3.2.1. Global Access Policies

Global access policies govern the following system level authorizations:

Policy	Privilege	Global Menu Selection
view the UI	Allow users to view the UI	N/A

Policy	Privilege	Global Menu Selection
access the controller	Allows users to view/modify the controller including Reporting Tasks, Controller Services, and Nodes in the Cluster	Controller Settings
query provenance	Allows users to submit a Provenance Search and request Event Lineage	Data Provenance
access restricted components	Allows users to create/modify restricted components assuming otherwise sufficient permissions	N/A
access all policies	Allows users to view/modify the policies for all components	Policies
access users/user groups	Allows users to view/modify the users and user groups	Users
retrieve site-to-site details	Allows other NiFi instances to retrieve Site-To-Site details	N/A
view system diagnostics	Allows users to view System Diagnostics	Summary
proxy user requests	Allows proxy machines to send requests on the behalf of others	N/A
access counters	Allows users to view/modify Counters	Counters

### 7.3.2.2. Component Level Access Policies

Component level access policies govern the following component level authorizations:

Policy	Privilege
view the component	Allows users to view component configuration details
modify the component	Allows users to modify component configuration details
view the data	Allows user to view metadata and content for this component through provenance data and flowfile queues in outbound connections
modify the data	Allows user to empty flowfile queues in outbound connections and submit replays
view the policies	Allows users to view the list of users who can view/modify a component
modify the policies	Allows users to modify the list of users who can view/modify a component
retrieve data via site-to-site	Allows a port to receive data from NiFi instances
send data via site-to-site	Allows a port to send data from NiFi instances

You can apply access policies to all component types except connections. Connection authorizations are inferred by the individual access policies on the source and destination components of the connection, as well as the access policy of the process group containing the components. This is discussed in more detail in the [Creating a Connection](#) and [Editing a Connection](#) examples below.

### 7.3.2.3. Access Policy Inheritance

An administrator does not need to manually create policies for every component in the dataflow. To reduce the amount of time admins spend on authorization management, policies are inherited from parent resource to child resource. For example, if a user is given access to view and modify a process group, that user can also view and modify the

components in the process group. Policy inheritance enables an administrator to assign policies at one time and have the policies apply throughout the entire dataflow.

You can override an inherited policy (as described in the [Moving a Processor](#) example below). Overriding a policy removes the inherited policy, breaking the chain of inheritance from parent to child, and creates a replacement policy to add users as desired. Inherited policies and their users can be restored by deleting the replacement policy.


"View the policies" and "modify the policies" component-level access policies are an exception to this inherited behavior. When a user is added to either policy, they are added to the current list of administrators. They do not override higher level administrators. For this reason, only component specific administrators are displayed for the "view the policies" and "modify the policies" access policies.

You cannot modify the users/groups on an inherited policy. Users and groups can only be added or removed from a parent policy or an override policy.


### 7.3.3. Access Policy Configuration Examples

The most effective way to understand how to create and apply access policies is to walk through some common examples. The following scenarios assume User1 is an administrator and User2 is a newly added user that has only been given access to the UI.

Let's begin with two processors on the canvas as our starting point: GenerateFlowFile and LogAttribute.




User1 can add components to the dataflow and is able to move, edit and connect all processors. The details and properties of the root process group and processors are visible to User1.



User1 wants to maintain their current privileges to the dataflow and its components.

User2 is unable to add components to the dataflow or move, edit, or connect components. The details and properties of the root process group and processors are hidden from User2.



### 7.3.3.1. Moving a Processor

To allow User2 to move the GenerateFlowFile processor in the dataflow and only that processor, User1 performs the following steps:

1. Select the GenerateFlowFile processor so that it is highlighted.


2. Select the Access Policies icon



)


from the Operate palette and the Access Policies dialog opens.

3. Select "modify the component" from the policy drop-down.



The "modify the component" policy that currently exists on the processor (child) is the "modify the component" policy inherited from the root process group (parent) on which User1 has privileges.

4. Select the Override link in the policy inheritance message. When creating the replacement policy, you are given a choice to override with a copy of the inherited policy or an empty policy.




Select the Override button to create a copy.

1. On the replacement policy that is created, select the Add User icon




).

Find or enter User2 in the User Identity field and select OK.



With these changes, User1 maintains the ability to move both processors on the canvas. User2 can now move the GenerateFlowFile processor but cannot move the LogAttribute processor.



### 7.3.3.2. Editing a Processor

In the "Moving a Processor" example above, User2 was added to the "modify the component" policy for GenerateFlowFile. Without the ability to view the processor properties, User2 is unable to modify the processor's configuration. In order to edit a component, a user must be on both the "view the component" and "modify the component" policies. To implement this, User1 performs the following steps:


1. Select the GenerateFlowFile processor.

2. Select the Access Policies icon



from the Operate palette and the Access Policies dialog opens.

3. Select "view the component" from the policy drop-down.




The "view the component" policy that currently exists on the processor (child) is the "view the component" policy inherited from the root process group (parent) on which User1 has privileges.

4. Select the Override link in the policy inheritance message, keep the default of Copy policy and select the Override button.


5. On the override policy that is created, select the Add User icon



Find or enter User2 in the User Identity field and select OK.




With these changes, User1 maintains the ability to view and edit the processors on the canvas. User2 can now view and edit the GenerateFlowFile processor.




### 7.3.3.3. Creating a Connection

With the access policies configured as discussed in the previous two examples, User1 is able to connect GenerateFlowFile to LogAttribute:



User2 cannot make the connection:



This is because:

- User2 does not have modify access on the process group.
- Even though User2 has view and modify access to the source component (GenerateFlowFile), User2 does not have an access policy on the destination component (LogAttribute).

To allow User2 to connect GenerateFlowFile to LogAttribute, as User1:

1. Select the root process group. The Operate palette is updated with details for the root process group.


2. Select the Access Policies icon



from the Operate palette and the Access Policies dialog opens.

)

3. Select "modify the component" from the policy drop-down.




4. Select the Add User icon



Find or enter User2 and select OK.

).




By adding User2 to the "modify the component" policy on the process group, User2 is added to the "modify the component" policy on

the LogAttribute processor by policy inheritance. To confirm this, highlight the LogAttribute processor and select the Access Policies icon





)

from the Operate palette:




With these changes, User2 can now connect the GenerateFlowFile processor to the LogAttribute processor.






### 7.3.3.4. Editing a Connection


Assume User1 or User2 adds a ReplaceText processor to the root process group:



User1 can select and change the existing connection (between GenerateFlowFile to LogAttribute) to now connect GenerateFlowFile to ReplaceText:




User 2 is unable to perform this action.



To allow User2 to connect GenerateFlowFile to ReplaceText, as User1:

1. Select the root process group. The Operate palette is updated with details for the root process group.
2. Select the Access Policies icon .

3. Select "view the component" from the policy drop-down.




4. Select the Add User icon




( ).

Find or enter User2 and select OK.



Being added to both the view and modify policies for the process group, User2 can now connect the GenerateFlowFile processor to the ReplaceText processor.



## 8. SAM Authorization

After you have logged in as the streamline user, you can access the SAM UI. The streamline user is assigned the **Admin** role and can manage users and security permissions. After logging in with this user, go to the menu item **Configuration** and select **Authorizer**.

You can use the **Authorizer** dialog to create users and assign them to roles.

The screenshot shows the 'Configuration / Authorizer' screen. On the left is a vertical sidebar with icons for Streamline, Configuration, Applications, and Help. The main area has tabs for 'USERS' and 'ROLES', with 'USERS' currently selected. A table lists seven users:

User	Roles
solson	1
streamline-streamanalytics	1
gvtticaden	1
harsha	1
suresh	1
guru	1
dan	1

### 8.1. Roles and Permissions

SAM provides four out of the box roles which map to the three different personas that SAM provides capabilities for and then a Admin user.

- Admin Role – The Admin Role is a super user who has access to all of SAM's system roles and privileges.
- Application Developer Role – The Application Developer Role has the privileges necessary to create and submit applications.

- Operations Role – The Operations Role has the privileges necessary to create service pools and environments and to submit applications.
- Analyst Role – The Analyst Role has access to specific applications and dashboards.

A role provides permissions (Read, Write, Execute) to 5 different resources in SAM:

- Applications
- Service Pools
- Environments
- User Management / Security
- Dashboards

**Table 8.1. Role and Permission Matrix**

Resources	Admin Role Access	Application Developer Role Access	Operations Role Access	Analyst Role Access
<b>Streamline Resources</b>				
User Mgmt	All Access	No Access	No Access	No Access
Role Mgmt	All Access	No Access	No Access	No Access
Topology	All Access	U: R W X	All: R W X	No Access
Customer Processor	All Access	U: R W	All: R W	No Access
Service Pools	All Access	All: R	All: R W	No Access
Environments	All Access	U: R W	All: R W	No Access
System Artifacts: Notifier UDF UDAF Component Defs	All Access (includes edit access to component defs)	Read to All	Read to All	No Access
Custom Artifacts: Notifier UDF UDAF Dashboards	All Access	U: R, W	All: R W	No Access
<b>Schema Registry Resources</b>				
Schemas		All: R W	All: R W	All: -
<b>Model Registry Resources</b>				
Models	All: R	U: R W O: R		

## 8.2. Creating Users and Assigning Them to Roles

Using the streamline user to initially go into SAM, you can create other admin roles in the system that can administer user accounts for the rest of the organization. To create new admin account for user gvettecaden, perform the following steps:

1. From Menu, select **Configuration** and then **Authorizer**.
2. From the **Users** tab, select the + icon.
3. Enter information about the new user account.

The screenshot shows the 'Configuration / Authorizer' interface with the 'USERS' tab selected. On the left, there is a vertical sidebar with icons for Home, Cluster, Database, and a wrench. The main area displays a list of users with their icons, names, and role counts. The users listed are: New User (0 roles), solson (1 role), streamline-streamanalytics (1 role), gvettecaden (1 role), harsha (1 role), suresh (1 role), guru (1 role), and dan (1 role). Each user entry has a small edit icon next to it.

User	Roles
New User	0
solson	1
streamline-streamanalytics	1
gvettecaden	1
harsha	1
suresh	1
guru	1
dan	1

4. Click **Save**.

### Result

You are able to see the user you just created in the user list, on the left side of the **SAM Configuration | Authorizer** view.

You do not have to provide any password. This is because SAM relies on a Kerberos/KDC to do the authentication. The principal is then passed to SAM when accessing the SAM UI. The principal name as part of the kerberos ticket must match a user in SAM. Then SAM looks up the role for that user and provides access based on the roles permissions.

## 8.3. Sharing Resources

SAM allows users to share different resources with other users to provide a collaborative team environment. A user who has edit access to a resource can share that resource with another user. When a resource is shared, the user can configure if the resource being shared can be just viewed or edited.

SAM allows the following resources to be shared:

- Environments
- Applications

### 8.3.1. Sharing an Environment

#### About This Task

By default, only the user who created an environment can see that environment. However, it is common for environments to be shared amongst a group of users. To do this, the user who created the environment must share that environment with other users.

#### Steps

1. From the left-hand menu select **Configuration**, then **Environment**.
2. From the environment you want to share, click the **Configuration** ellipses at the top right and click **Share**.
3. In the **Share Environment** dialog, select the users with whom you want to share the environment.
4. Specify whether you want to give them **View** or **Edit** privileges and click **Ok**.

## 8.4. Sharing an Application

#### About This Task

By default, only the user who created an application can see that it. However, it is common for applications to be shared amongst a group of users. To do this, the user who created the application must share that it with other users.

#### Steps

1. From the left-hand menu select **My Applications**.
2. From the application you want to share, click the **Configuration** ellipses at the top right and click **Share**.

3. In the **Share Application** dialog, select the users with whom you want to share the application.
4. Specify whether you want to give them **View** or **Edit** privileges and click **Ok**.

## 8.5. SAM Authorization Limitations

- SAM's roles and access control policies are maintained in SAM. Ranger support for SAM is not available in HDF 3.0.
- Creation of users and assignment to roles must be done using the SAM UI. In the HDF 3.0 release, there is no support to import users from KDC/AD.
- Role assignment is at a user level. Assigning roles to a group is not supported in HDF 3.0 release.
- New Roles or editing the out of the box role cannot be allows. However, the collaboration sharing features allow you to share each of the 5 resources across users meeting most use case requirements.

# 9. Deploying SAM Applications in a Secure Cluster

In a secure/kerberized env, SAM will deploy an application to kerberized Storm cluster and that app has to talk to secure services (e.g: Secure Kafka, HBase, HDFS, Hive, etc..). Deploying secure streaming apps that talks to secure services has been traditionally very difficult to configure. SAM makes it considerably easier to deploy secure streaming apps.

## 9.1. Connecting to a Secure Service that Supports Delegation Tokens

### About This Task

SAM uses *delegation tokens* when possible, when talking to secure streaming services. The concept of delegation token is introduced to avoid frequent authentication checks against Kerberos(AD/MIT). After the initial authentication against Namenode using Kerberos, subsequent authentication are done without a Kerberos service ticket(TGT). Once the client authentication with Kerberos for Namenode is successful, the client receives a delegation token from the Namenode. This token has an expiration and max issue date but can be reviewed.

A delegation token is secret key shared with the Storm/NameNode/HBase which provides a mechanism for Storm/NameNode/HBase to impersonate a user to perform an operation. Delegation tokens are supported for the following services: Storm, HDFS, Hive, HBase.

You can use Storm's Nimbus service to get delegation tokens on behalf of the topology submitter user. Nimbus can get HDFS, HBase and other delegation tokens associated with the user who submitted the topology and can push it to the users stream application. This decreases operational/deployment complexity because you do not have to distribute keytabs to all possible key tabs.

### Example


If your application is going to interact with secure HBase, your bolts/states needs to be authenticated by HBase. Typically, you are required to have `storm.keytab.file` on all the potential worker hosts. If you have multiple topologies on a cluster, each with different user, you will have to create multiple keytabs and distribute it to all workers.

With SAM, you can configure Nimbus to automatically get delegation tokens on behalf of the topology submitter user. To do this in SAM, you can configure a single principal and keytab in SAM for a given application and this principal is used by Nimbus to impersonate the user/app. The only requirement is that the keytab for this principal must reside on the host where Nimbus is located. To configure this single principal that will be used by Nimbus to impersonate the user/app when connecting to secure big data services like HBase, HDFS, Hive, do the following:

### Steps

1. Click into your stream application, and then click **Edit**.

2. Click the **Configure** icon () located on top right of the stream application.
3. Select the **Security** tab.
4. Select the principal and Keytab path. SAM automatically populates all the principal and key tabs located on the Nimbus Host to make this easier. Then click **Ok**.



### Result

When user X deploys the application, Nimbus uses the principal and the keytab configured above to impersonate user X when interacting with the big data services in the application.

## 9.2. Connecting to Secure Kafka

### About This Task

Kafka does not support delegation tokens. You must configure the Kafka source/sink processor with the principal and keytab used to authenticate the stream applications with Kafka. Use these steps to configure SAM to communicate with a secure Kafka service.

### Steps

1. Double click on the Kafka source/sink component on the canvas.
2. Select the **Security** tab.
3. Configure the Kerberos client principal, Kerberos keytab file, and the Kafka service name. The client principal and keytab selected must exist on all the worker nodes in the cluster. Using the `storm-<cluster-name>` principal is recommended because Ambari creates that keytab on each worker node when running the Ambari Kerberos Wizard . Set the Kafka service name to "kafka".

**TruckSpeedEvent**

REQUIRED	SECURITY	OPTIONAL	NOTES
KERBEROS CLIENT PRINCIPAL *	storm-streamanalytics@STREAMANALYTICS		
KERBEROS KEYTAB FILE *	/etc/security/keytabs/storm.headless.keytab		
KAFKA SERVICE NAME *	kafka		
SSL KEYSTORE LOCATION			
SSL KEYSTORE PASSWORD			
SSL KEY PASSWORD			
<input type="button" value="Cancel"/> <input type="button" value="Ok"/>			

**Output**

- eventTime\*
- STRING
- eventSource\*
- STRING
- truckId\*
- INTEGER
- driverId\*
- INTEGER
- driverName\*
- STRING
- routId\*
- INTEGER
- route\*
- STRING
- speed\*
- INTEGER

## 9.3. Securing SAM – An End-to-End Workflow


To help understand how all of this fits together, let's walk through a use case to see how SAM deploys applications in a secure cluster.

The use case details are the following:

- An organization has a secure HDFS/HDP cluster and all cluster services have been kerborized.
- User gvticaden is a developer and part of the release engineering team, builds a streaming application that includes of the following capabilities:
  - Creating streams from a set of Kafka topics from a secure Kafka Broker.
  - Doing analytics on the stream.
  - Persisting different events to following secure data stores: HDFS, HBase, Hive
- User gvticaden wants to deploy the streaming application to a secure storm Service.

### 9.3.1. Understanding the End-to-End Workflow

The below image provides an explanation on how SAM functions for the above use case.



SAM communicates with Storm Streaming Engine to deploy the stream application using the streamline principal/keytab. SAM is functioning as a client submitting a job to Secure Storm. The internal streamline user will impersonate gvetticaden when it talks to Storm. Hence ACLs within Ranger for Storm can be configured for gvetticaden, the person deploying the streaming application.

*Principal/Keytab Used to Connect:* The streamline principal/keytab is used to connect, and user gvetticaden is impersonated.

#### **Step 4: Communication with Secured Big Data Services**

When SAM deploys the application, it passes the application principal and keytab to Nimbus. Nimbus uses this principal to authenticate to big data services that support tokens. The principal impersonates gvetticaden. The result is that all Ranger ACLs for HBase, Hive, and HDFS are configured for gvetticaden, the user deploying the streaming application.

#### **Step 5: Communication with Secured Big Data Services that do not Support Delegation Tokens**

If the application uses a Kafka Source or Sink, then the application uses the principal and keytab configured under the Kafka component security settings.

*Principal/Keytab Used to Connect::* The principal/keytab configured in Kafka are used to connect.