Rockchip TEE SDK Developer Guide

ID: RK-KF-YF-851

Release Version: V2.1.0

Release Date: 2026-02-13

Security Level: □Top-Secret □Secret □Internal ■Public

DISCLAIMER

THIS DOCUMENT IS PROVIDED “AS IS”. ROCKCHIP ELECTRONICS CO., LTD.(“ROCKCHIP”)DOES NOT PROVIDE ANY WARRANTY OF ANY KIND, EXPRESSED, IMPLIED OR OTHERWISE, WITH RESPECT TO THE ACCURACY, RELIABILITY, COMPLETENESS,MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR NON-INFRINGEMENT OF ANY REPRESENTATION, INFORMATION AND CONTENT IN THIS DOCUMENT. THIS DOCUMENT IS FOR REFERENCE ONLY. THIS DOCUMENT MAY BE UPDATED OR CHANGED WITHOUT ANY NOTICE AT ANY TIME DUE TO THE UPGRADES OF THE PRODUCT OR ANY OTHER REASONS.

Trademark Statement

"Rockchip", "瑞芯微", "瑞芯" shall be Rockchip’s registered trademarks and owned by Rockchip. All the other trademarks or registered trademarks mentioned in this document shall be owned by their respective owners.

All rights reserved. ©2026. Rockchip Electronics Co., Ltd.

Beyond the scope of fair use, neither any entity nor individual shall extract, copy, or distribute this document in any form in whole or in part without the written approval of Rockchip.

Rockchip Electronics Co., Ltd.

No.18 Building, A District, No.89, software Boulevard Fuzhou, Fujian,PRC

Website: www.rock-chips.com

Customer service Tel: +86-4007-700-590

Customer service Fax: +86-591-83951833

Customer service e-Mail: fae@rock-chips.com

Preface

Overview

This document mainly introduces Rockchip TEE architecture, TEE environment construction, CA/TA development test, TA signature method, Encrypt TA, TA anti-rollback, Solution of optional strong or weak security levels, TA debugging method, Secure storage, TA API description, PTA description.

Intended Audience

This document is mainly applicable to the following engineers:

Technical Support Engineer

Software Development Engineer

Revision History

Version	Author	Date	Change Description
V1.00	ZZJ	2018-4-26	Initial Version
V1.10	ZZJ	2019-3-18	Add description of TEE in U-Boot; Distinguishing between V1 and V2 versions
V1.20	hisping	2019-6-4	Add description of secure storage
V1.30	hisping	2019-7-4	Modify description of secure storage
V1.40	hisping	2019-7-11	Add description of parameter.txt; Add description of kernel node which relate to TEE
V1.50	hisping	2019-8-8	Add description of error when compile rk_tee_user
V1.60	hisping	2021-1-27	Add description of changes to optee v1 kernel driver
V1.61	hisping	2021-3-4	Add description of unsupported error for rkfs
V1.70	hisping	2021-5-13	Add description of SECSTOR TA
V1.71	WXB	2021-5-14	Upgrade the CA/TA test program developed by RK, Update the description of the document
V1.72	hisping	2021-6-4	Modify description of TEE Macro in U-Boot
V1.73	hisping	2021-6-4	Add description of ENCRYPT TA
V1.74	WXB	2021-6-17	Add description of anti rollback for REE FS TA
V1.75	hisping	2021-7-5	Add description of TA debug method
V1.76	hisping	2021-7-8	Add description of TA view function call stack method
V1.77	hisping	2021-9-3	Revise TA signature chapter
V1.78	hisping	2021-9-6	Add description of secure storage performance test
V1.79	ZZJ	2021-9-10	Optimize partial format
V1.80	WXB	2021-9-10	Add description of TA API

Version	Author	Date	Change Description
V1.81	hisping	2021-10-12	Modify description of secure storage performance test
V1.82	WXB	2021-10-15	Add more API in TA API section
V1.83	ZZJ	2021-10-18	Optimize partial format
V1.84	WXB	2021-11-22	Add description of strong and weak security level , Update CA/TA description
V1.85	WXB	2021-11-26	Add OTP description chapter, Update OTP API, Adjust CA/TA description
V1.86	WXB	2021-11-30	Add reading guide chapter
V1.87	hisping	2022-06-22	Add rk_tee_service chapter
V1.9.0	hisping	2023-05-29	Supplement the details of each chapter, Add Step By Step chapter, Update Memory description, Update Secure Storage, Update OTP description.
V1.10.0	ZZJ	2023-06-02	Optimize partial format
V1.11.0	hisping	2024-01-23	Add description of U-Boot Run User TA, Add description of print secure memory, Add description of Test xtest Add description of HW Crypto API, Add description of Derive Key API
V1.12.0	hisping	2024-07-30	Supplement the details of Encrypt TA, Add description of soft ta encryption key.
V1.13.0	hisping	2024-11-15	Supplement the details of each chapter, add the Step By Step chapter with TA signature.
V1.14.0	hisping	2024-12-06	Additional explanation on how to compile firmware for 32-bit platforms that supports running User TA.
V1.15.0	hisping	2025-02-26	Add PTA chapter
V1.15.1	hisping	2025-04-09	Additional supported platforms
V1.16.0	hisping	2025-04-14	Add rk_keylad_cipher interface in TA API description section
V1.16.1	LJH	2025-10-27	Add Trusted Key chapter

Version	Author	Date	Change Description
V2.0.0	hisping	2026-01-12	Add OP-TEE V3 description
V2.1.0	hisping	2026-02-13	Add TA Subkey chapter

Contents

Rockchip TEE SDK Developer Guide

1. Reading Guide
2. Introduction to TrustZone
   - 2.1 What is TrustZone
   - 2.2 Architecture
     - 2.2.1 Hardware architecture
     - 2.2.2 Software architecture
     - 2.2.3 TrustZone and TEE
3. TEE Environment
   - 3.1 OP-TEE Version Description
   - 3.2 Parameter.txt
   - 3.3 TEE firmware
   - 3.4 TEE driver in U-Boot
     - 3.4.1 Macro Definition
     - 3.4.2 Shared Memory
     - 3.4.3 Secure Storage Test
       - 3.4.3.1 Test method
       - 3.4.3.2 Troubleshooting
     - 3.4.4 U-Boot Run User TA
   - 3.5 TEE driver in kernel
     - 3.5.1 OP-TEE V1
     - 3.5.2 OP-TEE V2 and OP-TEE V3
     - 3.5.3 Confirm TEE drive is enabled
   - 3.6 Enabling the Trusted Key Feature
     - 3.6.1 Enabling Kernel Trusted Key Support
     - 3.6.2 Enabling Trusted Key in OP-TEE OS
     - 3.6.3 Using the Feature
   - 3.7 TEE Library
4. CA/TA Development And Test
   - 4.1 Environment
   - 4.2 CA/TA demo
   - 4.3 Android
     - 4.3.1 Directory Introduction
     - 4.3.2 Compile
     - 4.3.3 Run
     - 4.3.4 Step By Step
     - 4.3.5 Develop CA/TA
   - 4.4 Linux
     - 4.4.1 Directory Introduction
     - 4.4.2 Compile
     - 4.4.3 Run
     - 4.4.4 Step By Step
     - 4.4.5 Develop CA/TA
   - 4.5 rk_tee_service
     - 4.5.1 Introduction
     - 4.5.2 Component
     - 4.5.3 Demo
   - 4.6 Test xtest
5. TA Signature
   - 5.1 Principle
   - 5.2 Replace the public key
   - 5.3 TA Signature Step By Step
6. TA Subkey
   - 6.1 Principle
   - 6.2 Sign TA using TA Subkey

6.3 TA Subkey Certificate Chain
7. Built-in TA into secure storage
7.1 Principle
7.2 Reference implementation
8. Encrypt TA
8.1 Method of encrypting TA
8.2 Burn TA encryption key
8.3 Decrypt and run the TA
8.4 Soft TA encryption key
9. REE FS TA anti-rollback
9.1 TA anti-rollback usage
10. Solution of optional strong or weak security levels
10.1 Scope
10.2 Notes
10.3 Solution description
11. TA debugging methods
11.1 OP-TEE v1 platforms
11.2 OP-TEE v2 and OP-TEE v3 platforms
11.3 Call stack
12. Memory description
12.1 OP-TEE V1
12.2 OP-TEE V2
12.3 OP-TEE V3
13. Secure Storage
13.1 Partition
13.2 Performance testing
14. OTP description
15. TA API description
15.1 Overview
15.2 API return value
15.3 API description
15.3.1 Crypto API
15.3.1.1 rk_crypto_malloc_ctx
15.3.1.2 rk_crypto_free_ctx
15.3.1.3 rk_hash_crypto
15.3.1.4 rk_hash_begin
15.3.1.5 rk_hash_update
15.3.1.6 rk_hash_finish
15.3.1.7 rk_cipher_crypto
15.3.1.8 rk_set_padding
15.3.1.9 rk_cipher_begin
15.3.1.10 rk_cipher_update
15.3.1.11 rk_cipher_finish
15.3.1.12 rk_ae_begin
15.3.1.13 rk_ae_update
15.3.1.14 rk_ae_finish
15.3.1.15 rk_gen_rsa_key
15.3.1.16 rk_rsa_crypto
15.3.1.17 rk_rsa_sign
15.3.1.18 rk_set_sign_mode
15.3.1.19 rk_rsa_begin
15.3.1.20 rk_rsa_finish
15.3.1.21 rk_gen_ec_key
15.3.1.22 rk_ecdh_genkey
15.3.1.23 rk_ecdsa_sign
15.3.1.24 rk_ecdsa_begin
15.3.1.25 rk_ecdsa_finish
15.3.1.26 rk_sm2_pke

15.3.1.27 rk_sm2_dsa_sm3
15.3.1.28 rk_sm2_kep_genkey
15.3.1.29 rk_mac_crypto
15.3.1.30 rk_mac_begin
15.3.1.31 rk_mac_update
15.3.1.32 rk_mac_finish
15.3.1.33 rk_hkdf_genkey
15.3.1.34 rk_pkcs5_pbkdf2_hmac
15.3.2 HW Crypto API
15.3.2.1 rk_user_ta_cipher
15.3.2.2 rk_keylad_hmac
15.3.2.3 rk_keylad_cipher
15.3.3 TRNG API
15.3.3.1 rk_get_trng
15.3.4 Derive Key API
15.3.4.1 rk_derive_ta_unique_key
15.3.5 OTP API
15.3.5.1 rk_otp_size
15.3.5.2 rk_otp_read
15.3.5.3 rk_otp_write
15.3.5.4 rk_write_oem_otp_key
15.3.5.5 rk_is_oem_otp_key_written
15.3.5.6 rk_oem_otp_key_set_read_lock
16. PTA description
16.1 Overview
16.2 PTA function
16.2.1 Secure Storage
16.2.2 OTP R&W
16.2.3 Hardware Crypto
16.2.4 Hardware random number
16.2.5 Hardware unique key derivation
16.3 Call PTA method
17. Reference

1. Reading Guide

The following steps describes the document structure and how to use TEE on Rockchip SoCs. It can be used as a guide for developers.

1. Understand the basics of TEE, See Introduction to TrustZone section.
2. Confirm requirements and config functions
    - Confirm OP-TEE version, See OP-TEE Version Description section.
    - Strong and weak security level configuration, See Solution of optional strong or weak security levels section.
    - TA signature key, See TA Signature section.
    - Additional protection mechanism of TA, See Built-in TA into secure storage, Encrypt TA, REE FS TA anti-rollback sections.
    - Secure storage and performance test, See secure storage section.
    - OTP description, See OTP description section.
3. TEE environment
    - Configure secure storage file system, See OTP description and Parameter.txt section.
    - Enable TEE firmware, See TEE firmware section.
    - Enable TEE for U-Boot, See TEE driver in U-Boot section.
    - Enable TEE for kernel, See TEE driver in kernel section.
4. Test CA/TA
    - Confirm the environment and project directory, See TEE library, Environment, Android, Linux sections.
    - Understand the demo provided by RK and compile it, See CA/TA demo, Android, Linux sections.
    - Install library and CA TA demo, See Android, Linux sections.
    - Test demo, See Android, Linux sections.
5. Develop CA/TA
    - Understand TA debugging methods, See TA debugging methods section.
    - Refer to demo and TA API to develop CA/TA, See CA/TA demo, TA API description sections.

2. Introduction to TrustZone

2.1 What is TrustZone

ARM TrustZone technology is a system wide security method for a large number of applications on high-performance computing platforms, including secure payment, digital rights management (DRM), enterprise services and web-based services.

TrustZone Technology and Cortex ™- A Processor is tightly integrated and expanded in the system through AMBA-AXI bus and specific TrustZone system IP block. This system approach means that peripherals such as secure memory, encryption blocks, keyboards, and screens can be protected from software attacks.

The devices developed according to the recommendations of the TrustZone Ready Program and utilizing the TrustZone technology provide a platform that can support a fully trusted execution environment (TEE) as well as security aware applications and security services.

The latest devices such as smart phones and tablets provide consumers with a high-value experience based on an extended service set. Mobile devices have developed into an open software platform that can download various large-scale applications from the Internet. These applications are usually verified by the device OEM to ensure quality, but not all functions can be tested, and attackers are constantly creating more and more malicious code targeting such devices.

At the same time, the demand for mobile devices to handle important services is increasing. From being able to pay, download and watch the latest Hollywood blockbusters in a specific period of time to being able to pay bills and manage bank accounts remotely through mobile phones, all these indicate that new business models have begun to emerge.

These development trends have made mobile phones likely to become the next software attack target of malware, Trojan horses, rootkits and other viruses. However, by applying advanced security technology based on ARM TrustZone technology and integrating SecurCore ™ Anti tamper elements can be used to develop devices that can provide an open operating environment with rich functions and powerful security solutions.


The trusted application adopts the SoC (running trusted execution environment) based on TrustZone technology, which is separated from the main OS to prevent software/malware attacks. TrustZone can be switched to safe mode to provide isolation supported by hardware. Trusted applications are usually containable, such as allowing trusted applications from different payment companies to coexist on one device. The processor supports ARM TrustZone technology, which is the basic function of all Cortex - A processors, and is introduced through the security extension of ARM architecture. These extensions provide a consistent programmer model across vendors, platforms, and applications, while providing a real hardware supported security environment.

2.2 Architecture

2.2.1 Hardware architecture

The TrustZone hardware architecture is designed to provide a security framework that enables devices to withstand the many specific threats they will encounter. TrustZone technology provides an infrastructure that allows SoC designers to choose from a large number of components that can implement specific functions in a secure environment, without providing a fixed and unchanging security solution.

The main security goal of the architecture is to support the construction of a programmable environment to prevent specific attacks on the confidentiality and integrity of assets. Platforms with these features can be used to build a wide range of security solutions, which are time-consuming and laborious to build using traditional methods.



System security can be ensured by isolating all SoC hardware and software resources so that they are located in two areas (a secure area for security subsystems and a normal area for storing all other content). AMBA3 AXI supporting TrustZone ™ , The hardware logic in the bus construction can ensure that normal area components cannot access security area resources, thus building a strong boundary between the two areas. The design of placing sensitive resources in a secure area, as well as running software reliably in a secure processor core, ensures that assets can withstand numerous potential attacks, including those that are often difficult to protect (for example, entering passwords using a keyboard or touch screen). By isolating security sensitive peripherals in the hardware, designers can limit the number of subsystems that need to pass the security assessment, thus saving costs when submitting security certification equipment.


The second aspect of the TrustZone hardware architecture is the extension implemented in some ARM processor cores. With these additional extensions, a single physical processor core can safely and effectively execute code from both the normal area and the security area in a time slice manner. In this way, a dedicated security processor core is not required, which saves chip area and energy, and allows high-performance security software to run together with the general regional operating environment.

After changing the currently running virtual processor, the two virtual processors perform context switching through the new processor mode (called monitor mode).

The mechanisms used by the physical processor to enter the monitor mode from the normal area are closely controlled, and these mechanisms are always regarded as exceptions of the monitor mode software. The items to be monitored can be triggered by the software executing special instructions (security monitor call (SMC) instructions), or by a subset of the hardware exception mechanism. IRQ, FIQ, external data abort, and external prefetch abort exceptions can be configured to switch the processor to monitor mode.

The software executed in the monitor mode is implementation defined, but it usually saves the state of the current area and restores the state of the area location to which it will switch. It then performs the operation returned from the exception to restart the processing in the restored area. The last aspect of the TrustZone hardware architecture is the security aware debugging infrastructure, which can control the access to security zone debugging without weakening the debugging visualization of common zones.

2.2.2 Software architecture



Implementing security zones in SoC hardware requires that certain security software be run in them and that sensitive assets stored in them be utilized.

There may be many software architectures that can be implemented by the security zone software stack on the processor core that supports TrustZone. The most advanced software architecture is the dedicated security zone operating system; The simplest is the synchronized code base placed in the security zone. There are many intermediate options between these two extreme architectures.

A dedicated security kernel can be a complex but powerful design. It can simulate the concurrent execution of multiple independent security zone applications, the runtime download of new security applications, and security zone tasks that are completely independent of the general zone environment.

These designs are very similar to the software stack you will see in the SoC, which uses two separate physical processors in an asymmetric multiprocessing (AMP) configuration. The software running on each virtual processor is an independent operating system, and each region uses hardware interrupts to preempt the currently running region and obtain processor time.

A tightly integrated design using communication protocols that associate secure area tasks with normal area threats that request them can provide many advantages of symmetric multiprocessing (SMP) designs. For example, in these designs, a security zone application can inherit the priority of common zone tasks it supports. This will result in some form of soft real-time response to the media application.

Security extension is an open component of ARM architecture, so any developer can create a customized security zone software environment to meet its requirements.

2.2.3 TrustZone and TEE

Applications such as payment, online banking, content protection, and enterprise authentication can improve their integrity, functionality, and user experience by leveraging three key elements provided by TrustZone technology enhanced devices:

1. Software secure execution environment to prevent malware attacks from rich operating systems
2. The hardware trust root can check the integrity of data and applications in the rich operation field to ensure that the security environment is not damaged
3. Access security peripherals on demand, such as memory, keyboard/touch screen, and even monitor

The device based on ARM TrustZone technology is combined with open APIs to provide a trusted execution environment (TEE). Developers need a new type of software to achieve its functions and consistency: this software is a trusted application. A typical trusted application can contain part of the code in both the normal area and the security area, for example, handling critical storage and manipulation. TEE also provides isolation from other trusted applications, enabling multiple trusted services to coexist.

The standardization of TEE API (managed by GlobalPlatform) will enable service providers, operators and OEMs to market interoperable trusted applications and services.

ARM TrustZone technology does not require separate security hardware to verify the integrity of devices or users. It does this by providing a true hardware trust root in the main handset chipset.

In order to ensure the integrity of the application, TrustZone also provides a secure execution environment (i.e., trust execution environment (TEE)), in which only trusted applications can run, so as to prevent attacks in the form of hackers/viruses/malware.

The TrustZone hardware provides isolation between TEE and software attack media. Hardware isolation can be extended to protect data input and output from physical peripherals (including keyboard/touch screen, etc.).

With these key functions, the chipset using TrustZone technology provides many opportunities to redefine the services that users can access (more and better services), how to access services (faster and easier), and where to access services (anytime, anywhere).

On most Android devices, the Android Boot loader does not verify the authenticity of the device kernel. Users who want to further control their devices may install the cracked Android kernel to root their devices. The cracked kernel allows super users to access all data files, applications and resources. Once the kernel is broken, the service will be rejected. If the kernel contains malware, the security of enterprise data will be compromised.

Secure Boot can effectively prevent the above problems. Secure Boot is a security mechanism that can prevent unauthorized boot loaders and kernels from being loaded during startup. Firmware images (such as operating systems and system components) that are encrypted and signed by a trusted, known authority are considered authorized firmware. The security boot component can form the first line of defense to prevent malicious software from attacking the device.

3. TEE Environment

3.1 OP-TEE Version Description

Android 7.1 and higher SDKs in Rockchip platform support TEE environment by default, TEE environment is not supported by default in versions earlier than Android 7.1

Linux SDK does not enable TEE environment by default, But you can refer to the following chapters to manually configure the TEE environment.

The TEE solution on Rockchip platform is OP-TEE, and the TEE API conforms to the GlobalPlatform standard.

At present, there are three versions of OP-TEE running on the rockchip platform, OP-TEE V1, OP-TEE V2, OP-TEE V3.

1. OP-TEE V1: RK312x, RK322x, RK3288, RK3328, RK322xh, RK3368, RK3399, RK3399Pro

2. OP-TEE V2: RK3326/PX30, RK3358, RK3308, RK1808, RV1109/RV1126, RK3566/RK3568, RK3588, RK3528, RK3562, RV1106, RK3576, RK3506, RV1103B, RV1126B

3.OP-TEE V3: RK3538 and subsequent new platforms

TEE library files, TA files, and TEE firmware is different between the three versions, Select TEE components according to the specific platform.

Platforms that are not listed in the OP-TEE V1 and OP-TEE V2 list can be considered platforms that adopt OP-TEE V3.

3.2 Parameter.txt

OP-TEE supports multiple secure storage file systems, as detailed in the "Secure Storage" section. Security partition is one of them. To use security partition, it is necessary to confirm that the partition is defined in the parameter.txt file which records the location and size information of each image. Security partition can be set by adding 0x00002000@0x000xxxxx(security) in parameter.txt, 0x00002000 indicates the size of 4M, 0x000xxxxx indicates the starting address, modify according to the actual parameter.txt

3.3 TEE firmware

TEE firmware can also be called TEE binary, Secure OS firmware, and on 64 bit platforms, it can also be called BL32.

The source code of TEE Secure OS is not open source by default, TEE binary file locat in directory `u-boot/tools/rk_tools/bin` or `rkbin/bin`.

1. The TEE binary of ARMv7 platform is packaged into trust.img by the tool `u-boot/tools/loaderimage`, The name of TEE binary is as follows:

   ```
   <platform>_tee_[ta]_<version>.bin
   such as: rkbin/bin/rk35/rk3506_tee_v1.26.bin
   such as: rkbin/bin/rk35/rk3506_tee_ta_v1.00.bin
   ```

   The name with [ta] support running user TA application, the name without [ta] do not support running user TA application.

   During U-Boot compilation,TOS.ini is used by default for firmware package, If config has defined CONFIG_TRUST_INI, Packaging firmware using the ini files.

   Taking RK3506 as an example, RK3506TOS.Ini is used by default for firmware packaging during compilation. RK3506TOS.Ini points to firmware without ta, so RK3506 does not support running User TA by default. If developers need to run User TA, they need to define CONFIG_TRUST_INI="RK3506TOS_TA.ini" in the config, which points to firmware with ta.

   The RK3506 quick start solution defaults to running TEE but not U-Boot, U-Boot cannot automatically reserve secure memory for TEE, So when using firmware with ta, it is necessary to add the following configuration under the reserved_memory node in the Kernel dts file, in order to reserve secure memory for TEE.

   ```
   trust@1 {
       reg = <0x3c00000 0x140000>;
   };
   ```

   For other platforms, U-Boot automatically reserves secure memory for TEE, without the need for additional configuration of Kernel dts.

2. The TEE binary of ARMv8 platform is packaged into trust.img by the tool `u-boot/tools/trust_merger`, The name of TEE binary is as follows:

   ```
   <platform>_bl32_<version>.bin
   such as: rkbin/bin/rk35/rk3588_bl32_v1.18.bin
   ```

3. If [BL32_OPTION] SEC=0 in rkbin/RKTRUST/.ini, It needs to be changed to SEC=1, Otherwise trust.img will not contain Secure OS and cannot run TEE services.
4. RK3566/RK3568, RK3588, RK3528, RK3562, RV1106, and subsequent new platforms will package the TEE binary into uboot.img without generating trust.img firmware.

The following print indicates that the OPTEE V1 platform TEE firmware has been run.

```
INF [0x0] TEE-CORE:init_primary_helper:337: Initializing (1.1.0-278-gef70f120a
#9 Fri Sep 17 09:39:24 UTC 2021 aarch64)
INF [0x0] TEE-CORE:init_primary_helper:338: Release version: 1.2
INF [0x0] TEE-CORE:init_teecore:83: teecore inits done
INFO:    BL31: Preparing for EL3 exit to normal world
INFO:    Entry point address = 0x200000
INFO:    SPSR = 0x3c9
```

The following print indicates that the OPTEE V2 platform TEE firmware has been run.

```
I/TC: OP-TEE version: 3.13.0-897-g5813e173a
I/TC: OP-TEE memory: TEEOS 0x200000 TA 0xc00000 SHM 0x200000
I/TC: Primary CPU initializing
I/TC: Primary CPU switching to normal world boot
INFO:    BL31: Preparing for EL3 exit to normal world
INFO:    Entry point address = 0x200000
INFO:    SPSR = 0x3c9
```

The following print indicates that the OPTEE V3 platform TEE firmware has been run.

```
I/TC: OP-TEE version: 4.6.0-147-gc7541e294
I/TC: OP-TEE memory size: TEEOS 0x200000 TA 0x400000 SHM 0x200000
I/TC: Primary CPU initializing
I/TC: Primary CPU switching to normal world boot
INFO:    BL31: Preparing for EL3 exit to normal world
INFO:    Entry point address = 0x200000
INFO:    SPSR = 0x3c9
```

3.4 TEE driver in U-Boot

At present, some safe operations need to be performed at the U-Boot level, For example, OP-TEE must be used to read some secure data.

The OP-TEE driver and OP-TEE API is implemented in U-Boot, U-Boot can communicate with OP-TEE through this interface, API conforms to GP specification.

U-Boot next-dev branch: The OP-TEE driver and OP-TEE API are located in the lib/optee_client directory.

U-Boot v5 branch: The OP-TEE driver is located in drivers/tee, and the OP-TEE API is located in lib/optee.

3.4.1 Macro Definition

U-Boot next-dev branch:

`CONFIG_OPTEE_CLIENT`, OP-TEE function main config.

`CONFIG_OPTEE_V1`, set by OP-TEE V1 platform.

`CONFIG_OPTEE_V2`, set by OP-TEE V2 platform.

U-Boot v5 branch:

`CONFIG_TEE` and `CONFIG_OPTEE`, OP-TEE function main config.

`CONFIG_ROCKCHIP_OPTEE_V2`, set by OP-TEE V2 platform.

`CONFIG_ROCKCHIP_OPTEE_V3`, set by OP-TEE V3 platform.

The following is the common configuration for OP-TEE V1, OP-TEE V2, and OP-TEE V3:

`CONFIG_OPTEE_ALWAYS_USE_SECURITY_PARTITION`, The secure storage area will be selected according to the hardware if this macro is not enabled, use rpmb if device use EMMC, use security partition if device use NAND. After the macro is enabled, data is fixed store in the security partition, Not store in rpmb . The scope of this macro is the U-Boot stage, It do not affect the kernel and UserSpace.

RPMB has higher security and stability than security partition, but less convenience than security partition. If the device is replaced with another device's EMMC to this device, or if the CPU is replaced, all you need to do is use the burning tool to erase the flash and reburn the firmware when using security partitions, the burning tool cannot clear rpmb data and special firmware is needed to clear rpmb data when using rpmb. Please weigh the convenience and security of whether to enable this macro. Some platforms will default to enabling this macro, If you have high security requirements, you can remove this macro yourself.

3.4.2 Shared Memory

When U-Boot communicates with OP-TEE, the data must be stored in shared memory, the shared memory size of each platform is different, and it is recommended that it should not exceed 1M, If it exceeds, it is recommended to split the data and transfer it for many times, When the OP-TEE V2 and OP-TEE V3 platforms boot up, they will print out the memory usage, where SHM indicates the size of shared memory.

```
I/TC: OP-TEE memory: TEEOS 0x200000 TA 0xc00000 SHM 0x200000
```

3.4.3 Secure Storage Test

3.4.3.1 Test method

Follow the steps below to perform the secure storage test. When testing RPMB, it is necessary to confirm that the CONFIG_SUPPORT_EMMC_RPMB macro has been enabled.

1. Enter the U-Boot command line: Device serial port connecting to PC, press ctrl+c in PC, Start device, It will stop at uboot.
2. The U-Boot next-dev branch executes the following test commands. This test case will perform a cyclic test on the secure storage function. The test program will automatically check the hardware. When the

hardware uses eMMC, it will test both RPMB and security partition for secure storage. When the hardware uses NAND, it will only test the security partition for secure storage.

```
=> mmc testsecurestorage
```

3. The U-Boot v5 branch executes the following test commands, and this test case can separately test the secure storage of RPMB and security partitions.

   ```
   => optee_storage rpmb_write file0 test_data
   => optee_storage rpmb_read file0 10
   => optee_storage security_write file0 test_data
   => optee_storage security_read file0 10
   ```

3.4.3.2 Troubleshooting

```
"TEEC: Could not find device"
```

The emmc or nand device is not found. Please check the driver in the U-Boot or the hardware.

```
"TEEC: Could not find security partition"
```

When the security partition is used for secure storage, the encrypted data will be stored in this partition. Please check whether the security partition is defined in parameter.txt

```
"TEEC: verify [%d] fail, cleanning ...."
```

When the security partition is used for secure storage for the first time, or the security partition data is illegally tampered, the security partition will be completely cleared.

```
"TEEC: Not enough space available in secure storage !"
```

There is not enough storage.

```
INF [0x0] TEE-CORE:storage_read_obj:201: Warning! head data not find!
ERR [0x0] TEE-CORE:storage_read_obj:210: cpu or emmc was replaced!
```

During U-Boot startup, key data will be stored by calling TEE, Key data is encrypted by TEE and stored in security partition or rpmb, And the encryption key is bound to the CPU; If the CPU is replaced, key data cannot be decrypted normally, resulting in U-Boot startup failure; If the emmc is replaced and used before, Old data exists in the security partition or rpmb, This error will also occur which causing U-Boot start fail; The solution is to clear the old data in the security partition or rpmb, format emmc directly if the security partition is used, If you use rpmb, you need to contact technical support to provide special firmware to clear the old data in rpmb.

```
“optee check api revision fail”
```

The U-Boot version does not match the TEE version, the U-Boot version is higher than the TEE version, The solution is as follows (choose one) :

1. Fallback U-Boot version to `cf13b78438 (tag: android-10.0-mid-rkr9) rockchip: spl: add rollback index check with otp`.

2. Revert the following commit:

   `396e3049bd  rochchip: board: only map op-tee share memory as dcache enabled`

   `7a349fdcbd lib: optee_client: add optee initialize flag`

   `74eb602743 lib: optee_client: update to new optee msg for optee v1 platform`

   `102dfafc4a rochchip: board: map op-tee memory as dcache enabled`

Normally, the versions of Uboot and OP-TEE in released SDK are matched.

```
"optee api revision mismatch with u-boot/kernel, panic"
```

If it is printed in the U-Boot startup, It mean the U-Boot version does not match the TEE version, U-Boot version is lower than TEE version, Upgradeable U-Boot version to `396e3049bd (tag: android-10.0-mid-rkr11, tag: android-10.0-mid-rkr10) rochchip: board: only map op-tee share memory as dcache enabled` at least.

If it is printed at the startup stage of Android system, Then upgrade `android/vendor/rockchip/common` version to `8bc7bf97 (tag: android-10.0-mid-rkr10) vpu: librockit: add Rockit MetadataRetriever` at least.

If printing in the startup phase of the Linux system, Then upgrade `linux/external/security/bin` version to `f59085c optee_v1: lib: arm&arm64: update binary and library` at least.

Normally, the versions of Uboot and OP-TEE in released SDK are matched.

3.4.4 U-Boot Run User TA

Some developer need to run their TA in the U-Boot, which can be referred to in this chapter.

1. U-Boot next-dev branch nend confirm if the feature is included. If not, please update the U-Boot code. U-Boot v5 branch is already supported.

```
436fc6d8486 lib: optee_clientApi: support load user ta for optee v1
4d4c5043204 lib: optee_clientApi: add user ta test demo
b122ee17db0 lib: optee_clientApi: support load user ta
deb4d4879d5 lib: optee_clientApi: support pack TA to image
```

2. U-Boot next-dev branch developer should copy TA files to u-boot/lib/optee_clientApi/userta,

   U-Boot v5 branch developer should copy TA files to u-boot/lib/optee/userta,

   This directory supports storing multiple TA files, and by default, rktest TA files are already stored for testing.

3. Execute the following command to package the TA file and generate the userta.img firmware.

```
./tabinary_to_img.py --tadir ./userta --out ./userta/userta.img
```

4. Modify parameter.txt to add a new userta partition, with a partition size greater than the userta.img firmware size.
5. Use the burning tool to burn parameter.txt and userta.img.
6. U-Boot next-dev branch can call trusty_oem_user_ta_transfer and trusty_oem_user_ta_storage to test rktest ta.

   U-Boot v5 branch can call optee_oem_user_ta_transfer and optee_oem_user_ta_storage to test rktest ta.

Developer can refer to these two functions and call their own TA.

3.5 TEE driver in kernel

TEE kernel driver under `security/optee_linuxdriver/` or `drivers/tee/`

3.5.1 OP-TEE V1

The driver of the chips using OP-TEE V1 is located at `security/optee_linuxdriver/`, All are enabled by default. The method to enable is as follows:

Add the following configurations in config:

```
CONFIG_TEE_SUPPORT=y
```

At present, we will gradually abandon the TEE kernel driver of OP-TEE V1, OP-TEE V1 platform will use the TEE kernel driver of OP-TEE V2.

If version>=v2.00 in the TEE binary file name in the rkbin/bin directory, you also need to enable the TEE kernel driver of OP-TEE V2.

Android 10 and above and Linux released after August 2020 use the TEE kernel driver of OP-TEE V2 by default.

3.5.2 OP-TEE V2 and OP-TEE V3

The driver of the chips using OP-TEE V2 or OP-TEE V3 is located at `drivers/tee/`, the method to enable is as follows:
Confirm that the following nodes have been added to the platform dtsi file:

```
    firmware {
        optee: optee {
            compatible = "linaro,optee-tz";
            method = "smc";
            #status = "disabled";
        };
    };
```

This node is added to all platforms by default, However, some platforms will set **status = "disabled"**, Just remove **status = "disabled"** if you want to enable the optee driver.

Add the following two configurations in config:

```
CONFIG_TEE=y
CONFIG_OPTEE=y
```

3.5.3 Confirm TEE drive is enabled

If the `/dev/opteearmtz00` node appears, it indicates that the TEE kernel driver of optee v1 is enabled.
If the `/dev/tee0` and `/dev/teepriv0` node appears, it indicates that the TEE kernel driver of optee v2 or optee v3 is enabled.

3.6 Enabling the Trusted Key Feature

The trusted key is a secure key management mechanism provided by the Linux kernel. It leverages a Trusted Execution Environment (TPM or TEE) to protect keys, ensuring that their contents are never exposed in normal memory or user space.

3.6.1 Enabling Kernel Trusted Key Support

Add the following configurations in your kernel config:

```
CONFIG_TRUSTED_KEYS=y
CONFIG_TRUSTED_KEYS_TEE=y
```

3.6.2 Enabling Trusted Key in OP-TEE OS

1. This feature requires BL32 support to be enabled. The currently supported chip platforms and BL32 versions are as follows:

Chip Platform	Version
RK3588	>= rk3588_bl32_v1.21.bin

2. Verify that the feature is enabled. If the `trusted_key` backend in TEE is active, you should see the following messages:

```
root@linaro-alip:/# dmesg | grep trusted
[    1.814593] Initialise system trusted keyrings
[    2.456306] Key type trusted registered
```

3.6.3 Using the Feature

On an Ubuntu platform, you need to install the keyutils tool first:

```
sudo apt-get install keyutils
```

Test adding a key with the following commands:

```
root@linaro-alip:/# keyctl add trusted test_key "new 32" @u
1028348999
root@linaro-alip:/#
root@linaro-alip:/# keyctl list @u
1 key in keyring:
1028348999: --alswrv      0      0 trusted: test_key
root@linaro-alip:/#
root@linaro-alip:/# keyctl unlink 1028348999 @u
root@linaro-alip:/#
```

3.7 TEE Library

- **Android**

TEE environment components are in the Android project directory `vendor/rockchip/common/security` or `hardware/rockchip/optee` (Including OP-TEE V1, OP-TEE V2 and OP-TEE V3) :

1. lib: Includes tee-supplicant, libteec.so and keymaster/gatekeeper library compiled from 32bit and 64bit platforms.
2. ta: Store the compiled keymaster/gatekeeper TA file.

- **Linux**

TEE environment components are in the Linux project directory `external/security/bin` (Including OP-TEE V1, OP-TEE V2 and OP-TEE V3) :

1. lib: Includes tee-supplicant, libteec.so and other librarys compiled from 32bit and 64bit platforms.
2. ta: Store the compiled TA file.

4. CA/TA Development And Test

4.1 Environment

1. If the compilation reports an error: `No module named Crypto.Signature`, The reason is Python algorithm library is not installed on the development computer, Execute the following command:

   ```
   pip uninstall Crypto
   pip uninstall pycrypto
   pip install pycrypto
   ```

2. If the compilation reports an error: `ModuleNotFoundError: No module named 'Cryptodome'` Please install python package on the development computer: `pip3 install [--user] pycryptodomex`

4.2 CA/TA demo

RK provides a series of CA/TA demo, The purpose is to:

- Provide reference for developers
- Directly used to test TEE environment

The source code of CA/TA demo is in the Android project `external/rk_tee_user`, Or Linux project `external/security/rk_tee_user`.

CA/TA demo contains “rktest” and “xtest”, "xtest" is the open-source test code of OPTEE, Including more complete test items. Generally, if it is used to test TEE environment or reference development, "rktest" can basically meet.

The following describes the functions of rktest.

The CA name of the rktest demo is "rktest", TA named “1db57234-dacd-462d-9bb1ae79de44e2a5.ta” or “1db57234-dacd-462d-9bb1-ae79de44e2a5.ta”.When running the CA program, you need to enter parameters to select the corresponding functions. Enter CA program name+space+any character, The available parameters will be prompted. The test functions implemented by rktest are shown in the following table.

Note: The test program only involves some commonly used functions and does not cover all functions supported by OPTEE.

parameters	function	notes
transfer_data	Test the parameter transfer between CA and TA	
storage	Test the secure storage	Before testing the Secure Storage function, ensure that the corresponding node of the kernel exists, security partition need `/dev/block/by-name/security`; rpmb secure storage need `/dev/block/mmcblk%u`, `/dev/block/mmcblk%urpmb`, `/sys/class/mmc_host/mmc%u/mmc%u:0001/cid`, %u value is any one of 0, 1 and 2; If the node does not exist, please link to the corresponding node.

parameters	function	notes
storage_speed	Test the secure storage speed	
property	Test get property	
crypto_sha	Test SHA algorithm	
crypto_aes	Test AES algorithm	
crypto_rsa	Test RSA encryption and decryption, signature verification	
secstor_ta	Test Built-in TA into secure storage	
otp_read	Test read OEM_S_OTP	The test program hides the otp test item by default, modify /host/rk_test/main.c if you want enable it. OTP characteristics are shown below “OTP Description” chapter.
otp_write	Test write OEM_S_OTP	
otp_size	Get OEM_S_OTP size	
otp_ns_read	Test read OEM_NS_OTP	
otp_ns_write	Test write OEM_NS_OTP	
trng	Get trng data	
socket	Test socket communication between CA and TA	

Execute the test program. The command is as follows:

```
# rktest transfer_data
# rktest [command]
```

The successful execution of CA program prompts PASS, and the failure prompts Fail.

4.3 Android

4.3.1 Directory Introduction

TEE CA/TA development environment locate in Android project directory `external/rk_tee_user`:

1. Android.mk: Decide the compilation tool and the CA file to be compiled.
2. host: CA source files.
3. ta: TA source files.
4. export*: The environment which TA compilation depends on.

4.3.2 Compile

If there are v1/ v2/ v3/ directories under `external/rk_tee_user`, It indicates that the master branch has been merged into the develop-next branch, The master branch will be discarded, Merge point is master branch `492f1cbf testapp: support new OP-TEE MSG`, Execute the following command to start compiling.

```
#For OP-TEE V1 platform
cd external/rk_tee_user/v1
#For OP-TEE V2 platform
cd external/rk_tee_user/v2
#For OP-TEE V3 platform
cd external/rk_tee_user/v3
rm -rf out/
./build.sh ta
mm
```

If there are no v1/ v2/ v3/ directories under `external/rk_tee_user`, It indicates that two branches are still used, please switch to the master branch for OP-TEE V1 platform, please switch to the develop-next branch for OP-TEE V2 platform, Execute the following command to start compiling.

```
cd external/rk_tee_user/
rm -rf out/
./build.sh ta (run if git log contain "Android.mk: remove build ta from
android", otherwise, do not need execute)
mm
```

The execution program will be obtained after successful compilation, The execution program contains CA (Client Application, run on normal world) and TA (Trust Application, run on secure world) .

- CA is a Android execution file, which is generated in the Android project out directory after compilation.
- TA is a file with the file name uuid.ta, Generated in one of the directories rk_tee_user/ta, rk_tee_user/out/ta, rk_tee_user/v1/out/ta, rk_tee_user/v2/out/ta, rk_tee_user/v3/out/ta.

4.3.3 Run

1. Enter the device by using adb shell

2. Install TEE library files, CA and TA into the device. For Android 7: push libteec.so into `/system/lib` or `/system/lib64`; push tee-supplicant and CA into /system/bin; create `/system/lib/optee_armtz` directory, push TA into /system/lib/optee_armtz`.

   For Android 8 and later: push libteec.so into `/vendor/lib` or `/vendor/lib64`; push tee-supplicant and CA into `/vendor/bin`; create `/vendor/lib/optee_armtz` directory, push TA into /vendor/lib/optee_armtz`.

   (If tee-supplicant starts automatically after startup, tee-supplicant and libteec.so do not need to push any more. These two files already exist in the system; libteec.so and tee-supplicant should distinguish between OP-TEE V1, OP-TEE V2, and OP-TEE V3, Distinguish between 32-bit and 64-bit;

   After push, check whether the tee-supplicant and CA programs have execution permissions.)

3. If the tee-supplicant is not automatically run when the machine is turned on, you need to manually run tee-supplicant in the background with root permission:

   ```
   # tee-supplicant &
   ```

   If print `tee_supp_rk_fs_init: unsupported`, It means security partition is not defined in parameter.txt, Please refer to "parameter.txt" Section for details, If the developer only uses the rpmb or REE file system for secure storage, the error print can be ignored.

4. run CA/TA, test TEE functions. rktest can be used to directly test the basic functions of TEE, execute:

   ```
   # rktest [command]
   ```

5. If rktest run successfully, Then TEE environment is normal, TEE development is available.

   please check the drive and components if error occurs.

   It may also be caused by the mismatch between the rk_tee_user version and the TEE OS version, The following are common matching relationships:

   OP-TEE V1:

   version >= v2.00 of TEE binary name under rkbin/bin directory,

   match `492f1cbf testapp: support new OP-TEE MSG`

   version < v2.00 of TEE binary name under rkbin/bin directory,

   match `e8d7215d Android.mk: support build in android R`

   or match `466515ec add tools for user to resign TA`

   OP-TEE V2:

   Serial port printing "OP-TEE version: 3.13.0" during TEE startup, `a566557 - v2: update to keep up with v3.13.0 of optee_test`

   Serial port printing "OP-TEE version: 3.6.0" during TEE startup, `1aa969e2 Android.mk: support build in android R`

   Serial port printing "OP-TEE version: 3.3.0" during TEE startup, `aa0a0c00 Android.mk: remove build ta from android`

   Serial port printing "OP-TEE version: 2.5.0" during TEE startup, `1ec9913a add tools for user to resign TA`

   OP-TEE V3:

   Serial port printing "OP-TEE version: 4.6.0" during TEE startup, `087ffdd add support for optee v3`

4.3.4 Step By Step

Here is an example of the arm64 platform using OP-TEE V2 on Android 12

```
//Compile CA TA
cd /home1/xxxx/rk_android_12
source build/envsetup.sh
lunch rk3568_s-userdebug
cd /home1/xxxx/rk_android_12/external/rk_tee_user/v2
./build.sh ta
mm

//Push TEE library files and CA TA to devices
adb root && adb remount
adb push Y:\rk_android_12\hardware\rockchip\optee\v2\arm64\libteec.so
/vendor/lib64
adb push Y:\rk_android_12\hardware\rockchip\optee\v2\arm64\tee-supplicant
/vendor/bin
adb push Y:\rk_android_12\out\target\product\rk3568_s\vendor\bin\rktest
/vendor/bin
adb push Y:\rk_android_12\external\rk_tee_user\v2\out\ta\rk_test\1db57234-dacd-
462d-9bb1-ae79de44e2a5.ta /vendor/lib/optee_armtz

//Run CA TA
# tee-supplicant &  //This step can be ignored if tee-supplicant is already
running, Android platform is running by default.
# rktest transfer_data
```

Here is an example of the arm64 platform using OP-TEE V3 on Android 14

```
//Compile CA TA
cd /home1/xxxx/rk_android_14
source build/envsetup.sh
lunch rk3538_u-userdebug
cd /home1/xxxx/rk_android_14/external/rk_tee_user/v3
./build.sh ta
mm

//Push TEE library files and CA TA to devices
adb root && adb remount
adb push Y:\rk_android_14\hardware\rockchip\optee\v3\arm64\libteec.so
/vendor/lib64
adb push Y:\rk_android_14\hardware\rockchip\optee\v3\arm64\tee-supplicant
/vendor/bin
adb push Y:\rk_android_14\out\target\product\rk3538_u\vendor\bin\rktest
/vendor/bin
adb push Y:\rk_android_14\external\rk_tee_user\v3\out\ta\rk_test\1db57234-dacd-
462d-9bb1-ae79de44e2a5.ta /vendor/lib/optee_armtz

//Run CA TA
# tee-supplicant &  //This step can be ignored if tee-supplicant is already
running, Android platform is running by default.
# rktest transfer_data
```

4.3.5 Develop CA/TA

Refer to Makefile about CA TA, the UUID of the header file needs to be modified to a new UUID, It can be generated with the uuidgen command.

head and stack size are defined in user_ta_header_defines.h under include directory, head szie is 32KB (TA_DATA_SIZE) , stack size is 2KB (TA_STACK_SIZE) . Generally, it is better not to modify it. If it cannot meet the needs, it can be appropriately enlarged, The heap size should not exceed 1MB, and the stack size should not exceed 64KB.

```
#define TA_STACK_SIZE                (2 * 1024)
#define TA_DATA_SIZE                 (32 * 1024)
```

4.4 Linux

4.4.1 Directory Introduction

TEE CA/TA development environment locate in Linux project directory `external/security/rk_tee_user`:

1. build.sh: Compile script, please refer to the notes in the script for compilation instructions.
2. Makefile: Decide the compilation tool and the CA file to be compiled.
3. host: CA source files.
4. ta: TA source files.
5. export*: The environment which TA compilation depends on.

4.4.2 Compile

If there are v1/ v2/ v3/ directories under `external/security/rk_tee_user`, It indicates that the master branch has been merged into the develop-next branch, The master branch will be discarded, Merge point is master branch `492f1cbf testapp: support new OP-TEE MSG`, Execute the following command to start compiling.

```
#For OP-TEE V1 platform
cd external/security/rk_tee_user/v1
#For OP-TEE V2 platform
cd external/security/rk_tee_user/v2
#For OP-TEE V3 platform
cd external/security/rk_tee_user/v3
rm -rf out/
./build.sh 3232 (For 32-bit platform, CA 32bits, TA 32bits)
./build.sh 6432 (For 64-bit platform, CA 64bits, TA 32bits)
```

If there are no v1/ v2/ v3/ directories under `external/security/rk_tee_user`, It indicates that two branches are still used, please switch to the master branch for OP-TEE V1 platform, please switch to the develop-next branch for OP-TEE V2 platform, Execute the following command to start compiling.

```
cd external/security/rk_tee_user/
rm -rf out/
./build.sh 3232 (For 32-bit platform, CA 32bits, TA 32bits)
./build.sh 6432 (For 64-bit platform, CA 64bits, TA 32bits)
```

The execution program will be obtained after successful compilation, The execution program contains CA (Client Application, run on normal world) and TA (Trust Application, run on secure world) .

- CA is a Linux execution file, which is generated in one of the directories rk_tee_user/out, rk_tee_user/v1/out, rk_tee_user/v2/out.
- TA is a file with the file name uuid.ta, Generated in one of the directories rk_tee_user/ta, rk_tee_user/out/ta, rk_tee_user/v1/out/ta, rk_tee_user/v2/out/ta, rk_tee_user/v3/out/ta.

4.4.3 Run

1. Enter the device by using adb shell.
2. Install TEE library files, CA and TA into the device. push libteec.so* into /lib or /lib64; push tee-supplicant and CA into /usr/bin; create /lib/optee_armtz directory, push TA into /lib/optee_armtz.

   (If tee-supplicant starts automatically after startup, tee-supplicant and libteec.so do not need to push again. These two files already exist in the system; libteec.so and tee-supplicant should distinguish between OP-TEE V1, OP-TEE V2, and OP-TEE V3, Distinguish between 32-bit and 64-bit;

   After push, check whether the tee-supplicant and CA programs have execution permissions.)
3. Other steps are the same as Android platform. See the "Android" chapter above.

4.4.4 Step By Step

Here is an example of the arm64 platform using OP-TEE V2 on Linux

```
//Compile CA TA
cd /home1/xxxx/rk_px30_linux/external/security/rk_tee_user/v2
rm -rf out/
./build.sh 6432

//Create optee_armtz directory, it is used to store TA files
# mkdir -p /lib/optee_armtz

//Push TEE library files and CA TA to devices
adb push Y:\rk_px30_linux\external\security\bin\optee_v2\lib\arm64\libteec.so
/lib64
adb push Y:\rk_px30_linux\external\security\bin\optee_v2\lib\arm64\libteec.so.1
/lib64
adb push Y:\rk_px30_linux\external\security\bin\optee_v2\lib\arm64\tee-
supplicant /usr/bin
adb push Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\rk_test\rktest
/usr/bin
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\rk_test\1db57234-dacd-
462d-9bb1-ae79de44e2a5.ta /lib/optee_armtz

//Add executable permissions
# chmod +x /usr/bin/tee-supplicant
```

```
# chmod +x /usr/bin/rktest

//Run CA TA
# tee-supplicant &  //this step can be ignored if tee-supplicant is already
running
# rktest transfer_data
```

Here is an example of the arm64 platform using OP-TEE V3 on Linux

```
//Compile CA TA
cd /home1/xxxx/rk_linux/external/security/rk_tee_user/v3
rm -rf out/
./build.sh 6432

//Create optee_armtz directory, it is used to store TA files
# mkdir -p /lib/optee_armtz

//Push TEE library files and CA TA to devices
adb push Y:\rk_linux\external\security\bin\optee_v3\lib\arm64\libteec.so /lib64
adb push Y:\rk_linux\external\security\bin\optee_v3\lib\arm64\libteec.so.2
/lib64
adb push Y:\rk_linux\external\security\bin\optee_v3\lib\arm64\tee-supplicant
/usr/bin
adb push Y:\rk_linux\external\security\rk_tee_user\v3\out\rk_test\rktest
/usr/bin
adb push Y:\rk_linux\external\security\rk_tee_user\v3\out\ta\rk_test\1db57234-
dacd-462d-9bb1-ae79de44e2a5.ta /lib/optee_armtz

//Add executable permissions
# chmod +x /usr/bin/tee-supplicant
# chmod +x /usr/bin/rktest

//Run CA TA
# tee-supplicant &  //this step can be ignored if tee-supplicant is already
running
# rktest transfer_data
```

4.4.5 Develop CA/TA

Refer to Makefile about CA TA, the UUID of the header file needs to be modified to a new UUID, It can be generated with the uuidgen command.

head and stack size defined in user_ta_header_defines.h under include directory, head szie is 32KB (TA_DATA_SIZE) , stack size is 2KB (TA_STACK_SIZE) . Generally, it is better not to modify it. If it cannot meet the needs, it can be appropriately enlarged, The heap size should not exceed 1MB, and the stack size should not exceed 64KB.

```
#define TA_STACK_SIZE               (2 * 1024)
#define TA_DATA_SIZE                (32 * 1024)
```

4.5 rk_tee_service

4.5.1 Introduction

rk_tee_service is a security service developed based on TEE, which provides common security functions for developers. The simple and clear external interface greatly facilitates developers' use. rk_tee_service is essentially a CA TA application, Therefore, test the TEE environment is normal before using rk_tee_service.

Developers can directly call rk_ tee_service to encrypts and decrypts sensitive data. The encryption/decryption key is derived by TEE using the unique key HUK inside the device hardware, Therefore, the encryption and decryption keys of each device are different, Copying the sensitive data of device A to device B cannot be decrypted normally to ensure that the sensitive data will not be stolen. Due to the size of shared memory, it is recommended that the size of data encrypted and decrypted at a single time should not exceed 1M. It is recommended to encrypt and decrypt big data in multiple times.

At present, the OP-TEE V2 and OP-TEE V3 platform supports this function, while the OP-TEE V1 platform does not.

4.5.2 Component

Currently, it supports Linux platform and Android platform (Android 12 and higher).

OP-TEE V2 Component	Android directory	Linux directory
librk_tee_service.so	hardware/rockchip/optee/v2/arm hardware/rockchip/optee/v2/arm64	external/security/bin/optee_v2/lib/arm external/security/bin/optee_v2/lib/arm64
rk_tee_service.h	hardware/rockchip/optee/v2/include	external/security/bin/optee_v2/include
4367fd45-4469-42a6-925d-3857b952704a.ta	hardware/rockchip/optee/v2/ta	external/security/bin/optee_v2/ta

OP-TEE V3 Component	Android directory	Linux directory
librk_tee_service.so	hardware/rockchip/optee/v3/arm hardware/rockchip/optee/v3/arm64	external/security/bin/optee_v3/lib/arm external/security/bin/optee_v3/lib/arm64
rk_tee_service.h	hardware/rockchip/optee/v3/include	external/security/bin/optee_v3/include
4367fd45-4469-42a6-925d-3857b952704a.ta	hardware/rockchip/optee/v3/ta	external/security/bin/optee_v3/ta

The Userspace application can directly call librk_tee_service.so, Parameter of function please refer to rk_tee_service.h, Push 4367fd45-4469-42a6-925d-3857b952704a.ta into /lib/optee_armtz for Linux platform , Push 4367fd45-4469-42a6-925d-3857b952704a.ta into /vendor/lib/optee_armtz for Android platform.

4.5.3 Demo

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include "rk_tee_service.h"

int main(int argc, char *argv[])
{
```

```
    unsigned char plain[256];
    unsigned int plain_len;
    unsigned char cipher[256];
    unsigned int cipher_len;
    int res;

    memset((void *)plain, 0xab, sizeof(plain));
    cipher_len = 256;
    res = rk_encrypt_data(plain, sizeof(plain), cipher, &cipher_len);
    printf("res=0x%x cipher_len=%d\n", res, cipher_len);

    memset((void *)plain, 0, sizeof(plain));
    plain_len = 256;
    res = rk_decrypt_data(cipher, cipher_len, plain, &plain_len);
    printf("res=0x%x plain_len=%d\n", res, plain_len);

    return 0;
}
```

4.6 Test xtest

Xtest is an open-source testing code for OPTEE, which includes relatively complete testing items. Customers can refer to this chapter to test xtest.

Here is an example of the arm64 platform using OP-TEE V2 on Android 13:

```
//build CA TA
cd /home1/xxxx/rk_android_13
source build/envsetup.sh
lunch rk3568_t-userdebug
cd /home1/xxxx/rk_android_13/external/rk_tee_user/v2
./build.sh ta
mm

//create plugins directory on device
# mkdir -p /vendor/lib64/tee-supplicant/plugins/

//push TEE library and CA TA to device
adb root && adb remount
adb push Y:\rk_android_13\hardware\rockchip\optee\v2\arm64\libteec.so
/vendor/lib64
adb push Y:\rk_android_13\hardware\rockchip\optee\v2\arm64\tee-supplicant
/vendor/bin
adb push Y:\rk_android_13\out\target\product\rk3568_t\vendor\bin\xtest
/vendor/bin
adb push Y:\rk_android_13\external\rk_tee_user\v2\out\ta\crypt\cb3e5ba0-adf1-
11e0-998b-0002a5d5c51b.ta /vendor/lib/optee_armtz
adb push Y:\rk_android_13\external\rk_tee_user\v2\out\ta\concurrent\e13010e0-
2ae1-11e5-896a-0002a5d5c51b.ta /vendor/lib/optee_armtz
adb push
Y:\rk_android_13\external\rk_tee_user\v2\out\ta\create_fail_test\c3f6e2c0-3548-
11e1-b86c-0800200c9a66.ta /vendor/lib/optee_armtz
adb push Y:\rk_android_13\external\rk_tee_user\v2\out\ta\rpc_test\d17f73a0-36ef-
11e1-984a-0002a5d5c51b.ta /vendor/lib/optee_armtz
```

```
adb push Y:\rk_android_13\external\rk_tee_user\v2\out\ta\sims\e6a33ed4-562b-
463a-bb7e-ff5e15a493c8.ta /vendor/lib/optee_armtz
adb push
Y:\rk_android_13\external\rk_tee_user\v2\out\ta\concurrent_large\5ce0c432-0ab0-
40e5-a056-782ca0e6aba2.ta /vendor/lib/optee_armtz
adb push Y:\rk_android_13\external\rk_tee_user\v2\out\ta\miss\528938ce-fc59-
11e8-8eb2-f2801f1b9fd1.ta /vendor/lib/optee_armtz
adb push Y:\rk_android_13\external\rk_tee_user\v2\out\ta\socket\873bcd08-c2c3-
11e6-a937-d0bf9c45c61c.ta /vendor/lib/optee_armtz
adb push
Y:\rk_android_13\external\rk_tee_user\v2\out\ta\sims_keepalive\a4c04d50-f180-
11e8-8eb2-f2801f1b9fd1.ta /vendor/lib/optee_armtz
adb push Y:\rk_android_13\external\rk_tee_user\v2\out\ta\os_test\5b9e0e40-2636-
11e1-ad9e-0002a5d5c51b.ta /vendor/lib/optee_armtz
adb push Y:\rk_android_13\external\rk_tee_user\v2\out\ta\os_test_lib\ffd2bded-
ab7d-4988-95ee-e4962fff7154.ta /vendor/lib/optee_armtz
adb push
Y:\rk_android_13\external\rk_tee_user\v2\out\ta\os_test_lib_dl\b3091a65-9751-
4784-abf7-0298a7cc35ba.ta /vendor/lib/optee_armtz
//Test storage, The security partition space is limited, which can lead to test
failures.
//So delete security partition from parameter.txt, uboot do not define
CONFIG_OPTEE_ALWAYS_USE_SECURITY_PARTITION.
//Using the Android file system can pass the test.
adb push Y:\rk_android_13\external\rk_tee_user\v2\out\ta\storage\b689f2a7-8adf-
477a-9f99-32e90c0ad0a2.ta /vendor/lib/optee_armtz
adb push Y:\rk_android_13\external\rk_tee_user\v2\out\ta\storage2\731e279e-aafb-
4575-a771-38caa6f0cca6.ta /vendor/lib/optee_armtz
adb push
Y:\rk_android_13\external\rk_tee_user\v2\out\ta\storage_benchmark\f157cda0-550c-
11e5-a6fa-0002a5d5c51b.ta /vendor/lib/optee_armtz
adb push Y:\rk_android_13\external\rk_tee_user\v2\out\ta\supp_plugin\380231ac-
fb99-47ad-a689-9e017eb6e78a.ta /vendor/lib/optee_armtz
adb push Y:\rk_android_13\out\target\product\rk3568_t\vendor\lib64\tee-
supplicant\plugins\f07bfc66-958c-4a15-99c0-260e4e7375dd.plugin.so
/vendor/lib64/tee-supplicant/plugins/
adb push Y:\rk_android_13\hardware\rockchip\optee\v2\arm64\libckteec.so
/vendor/lib64
adb push Y:\rk_android_13\external\rk_tee_user\v2\export-ta_arm32\ta\fd02c9da-
306c-48c7-a49c-bbd827ae86ee.ta /vendor/lib/optee_armtz

//Run xtest
# tee-supplicant &  //this step can be ignored if tee-supplicant is already
running
# xtest
```

Here is an example of the arm64 platform using OP-TEE V2 on Linux:

```
//build CA TA
cd /home1/xxxx/rk_px30_linux/external/security/rk_tee_user/v2
rm -rf out/
./build.sh 6432

//create optee_armtz directory on device
# mkdir -p /lib/optee_armtz
//create plugins directory on device
# mkdir -p /usr/lib/tee-supplicant/plugins/
```

```
//push TEE library and CA TA to device
adb push Y:\rk_px30_linux\external\security\bin\optee_v2\lib\arm64\libteec.so
/lib64
adb push Y:\rk_px30_linux\external\security\bin\optee_v2\lib\arm64\libteec.so.1
/lib64
adb push Y:\rk_px30_linux\external\security\bin\optee_v2\lib\arm64\tee-
supplicant /usr/bin
adb push Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\xtest\xtest
/usr/bin
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\crypt\cb3e5ba0-adf1-
11e0-998b-0002a5d5c51b.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\concurrent\e13010e0-
2ae1-11e5-896a-0002a5d5c51b.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\create_fail_test\c3f6e2
c0-3548-11e1-b86c-0800200c9a66.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\rpc_test\d17f73a0-36ef-
11e1-984a-0002a5d5c51b.ta /lib/optee_armtz
adb push Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\sims\e6a33ed4-
562b-463a-bb7e-ff5e15a493c8.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\concurrent_large\5ce0c4
32-0ab0-40e5-a056-782ca0e6aba2.ta /lib/optee_armtz
adb push Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\miss\528938ce-
fc59-11e8-8eb2-f2801f1b9fd1.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\socket\873bcd08-c2c3-
11e6-a937-d0bf9c45c61c.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\sims_keepalive\a4c04d50
-f180-11e8-8eb2-f2801f1b9fd1.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\os_test\5b9e0e40-2636-
11e1-ad9e-0002a5d5c51b.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\os_test_lib\ffd2bded-
ab7d-4988-95ee-e4962fff7154.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\os_test_lib_dl\b3091a65
-9751-4784-abf7-0298a7cc35ba.ta /lib/optee_armtz
//Test storage, The security partition space is limited, which can lead to test
failures.
//So delete security partition from parameter.txt, uboot do not define
CONFIG_OPTEE_ALWAYS_USE_SECURITY_PARTITION.
//Using the Android file system can pass the test.
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\storage\b689f2a7-8adf-
477a-9f99-32e90c0ad0a2.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\storage2\731e279e-aafb-
4575-a771-38caa6f0cca6.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\storage_benchmark\f157c
da0-550c-11e5-a6fa-0002a5d5c51b.ta /lib/optee_armtz
```

```
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\ta\supp_plugin\380231ac-
fb99-47ad-a689-9e017eb6e78a.ta /lib/optee_armtz
adb push
Y:\rk_px30_linux\external\security\rk_tee_user\v2\out\supp_plugin\f07bfc66-958c-
4a15-99c0-260e4e7375dd.plugin /usr/lib/tee-supplicant/plugins/
adb push
Y:\rk_px30_linux\external\security\bin\optee_v2\lib\arm64\libckteec.so.0 /lib64
adb push  Y:\rk_px30_linux\external\security\rk_tee_user\v2\export-
ta_arm32\ta\fd02c9da-306c-48c7-a49c-bbd827ae86ee.ta /lib/optee_armtz

//Add executable permissions
# chmod +x /usr/bin/tee-supplicant
# chmod +x /usr/bin/xtest

//Run CA TA
# tee-supplicant &  //this step can be ignored if tee-supplicant is already
running
# xtest
```

5. TA Signature

5.1 Principle

When compiling TA, the compile script will automatically use the key in the `export-user_ta/keys` directory or `export-ta_arm32/keys` directory of the rk_tee_user project to sign TA application. The key is 2048 bits RSA key in pem format. Finally, the TA file in .ta format is generated.

There is an RSA public key stored in the TEE binary. When the TA is loaded and run, the TEE OS will use the public key to verify the validity of the TA. Only after the verification is passed, the TA application can run normally.

5.2 Replace the public key

To prevent developer A's TA application from running on developer B's board, it is recommended to replace the public key.

Developers can replace public keys in TEE binary with tools in the rk_tee_user project tools/ directory.

- Linux:

  ```
  ./change_puk  --teebin  <TEE binary>
  ```

  This command automatically generates a 2048 bits RSA key oemkey.pem in the current directory, and replaces the original public key in the TEE binary with the public key in this key.

  ```
  ./change_puk  --teebin  <TEE binary> --key oemkey.pem
  ```

Replace the original public key in the TEE binary with the public key specified by the developer. The key length must be 2048 bits.

- Windows:

  Open Windows_change_puk.exe and click "Generate oemkey.pem" to generate and save keys.

  Select the key and TEE binary you just generated, and click "Modify Public Key".

  (Since Windows_change_puk.exe invokes the BouncyCastle.Crypto.dll third-party library, make sure BouncyCastle.Crypto.dll is in the same directory as Windows_change_puk.exe)

After the public key is replaced, the developer needs to use the new TEE binary to replace the original TEE binary in the rkbin/ directory, recompile the U-Boot, and burn the new `trust.img` firmware. Part of the platforms have no `trust.img` because `trust.img` is packaged into `uboot.img`, so `uboot.img` is burned instead.

The developer needs to rename the key generated or specified by the previous tool to oem_privkey.pem and replace the key in the `export-user_ta/keys` or `export-ta_arm32/keys` directory of the rk_tee_user project. Recompile the CA and TA so that the resulting TA application can be properly loaded and run by the TEE binary (new public key). Any TA that is not signed with the correct private key is considered invalid and cannot be run.

5.3 TA Signature Step By Step

Here is an example of the arm64 platform using OP-TEE V2 on Android 12

```
cd /home1/xxxx/rk_android_12/external/rk_tee_user/v2/tools/change_puk_tool-
release/change_puk_linux

chmod +x change_puk

./change_puk --teebin
/home1/xxxx/rk_android_12/rkbin/bin/rk35/rk3588_bl32_v1.17.bin

cp oem_privkey.pem /home1/xxxx/rk_android_12/external/rk_tee_user/v2/export-
ta_arm32/keys/

cp oem_privkey.pem /home1/xxxx/rk_android_12/external/rk_tee_user/v2/export-
ta_arm64/keys/

//Recompile and burn the uboot firmware, recompile the CA TA application
```

6. TA Subkey

The previous chapter introduced that when compiling a TA using the rk_tee_user project, the compilation script directly uses the key from the `export-ta_arm32/keys` directory to sign the TA application. After obtaining the TA signing key, the developer can sign any TA application. The developer's authority is too great. Is there a way to restrict the developer to only sign specific TAs? This chapter introduces another method of signing TAs, using the TA Subkey to sign specific TAs.
Currently, this feature is only supported by OP-TEE V3, and is not supported by OP-TEE V1 and OP-TEE V2.

6.1 Principle

The TA signature key is managed by the key administrator, and developers cannot obtain the TA signature key. Developers generate a subkey named TA Subkey, which is signed by the key administrator using the TA signature key. The signing process appends the UUID parameter of TA. Developers obtain the TA Subkey certificate and use the TA Subkey and TA Subkey certificate to sign the specified TA. Developers can also use the TA Subkey and TA Subkey certificate to sign the next-level TA Subkey.

When verifying the validity of the TA, the TEE OS employs its internal RSA public key to authenticate the first-level TA Subkey certificate. It retrieves the first-level TA Subkey public key from the certificate and then uses it to validate the next-level TA Subkey certificate, obtaining the corresponding public key. This process is repeated until the validity of the last-level TA Subkey certificate is confirmed. From this certificate, the last-level TA Subkey public key is obtained, which is then utilized to verify the legitimacy of the TA application. During the verification of the TA Subkey certificates, the UUID parameter within the certificate is also checked, ensuring that only the designated TA application can operate.

6.2 Sign TA using TA Subkey

Here, we take the application rk_tee_user/v3/ta/subkey2 as an example, and execute the following command to sign the TA Subkey.

```
cd rk_tee_user/v3/export-ta_arm32/scripts

sign_encrypt.py sign-subkey \
    --uuid a720ccbb-51da-417d-b82e-e5445d474a7a \
    --key ../../export-ta_arm32/keys/oem_privkey.pem \
    --in ../../ta/identity_subkey2.pem \
    --out ../../ta/identity_subkey2.bin --max-depth 0 --name-size 0 \
    --subkey-version 1
```

Parameter description:

- uuid: Specify the UUID of the TA. The TA Subkey can only sign this TA
- key: TA signature key
- in: TA Subkey
- out: TA Subkey certificate
- max-depth: The maximum depth of the TA Subkey certificate chain. A value of 0 indicates that the TA Subkey can only sign TA applications and cannot sign the next level of TA Subkey.
- name-size: The maximum length of the next-level TA Subkey name
- subkey-version: The version number of the TA Subkey certificate

Specify the TA Subkey and TA Subkey certificate in rk_tee_user/v3/ta/subkey2/Makefile. When compiling the TA, the script will automatically use the TA Subkey to sign the TA application.

```
BINARY =  a720ccbb-51da-417d-b82e-e5445d474a7a

TA_SIGN_KEY = ../identity_subkey2.pem
TA_SUBKEY_BIN = ../identity_subkey2.bin
TA_SUBKEY_ARGS = --subkey $(TA_SUBKEY_BIN)
TA_SUBKEY_DEPS = $(TA_SUBKEY_BIN)

include ../ta_common.mk
```

6.3 TA Subkey Certificate Chain

Here, we take the application rk_tee_user/v3/ta/subkey1 as an example. Execute the following command to sign the TA Subkey and form a certificate chain.

```
cd rk_tee_user/v3/export-ta_arm32/scripts

sign_encrypt.py sign-subkey \
    --uuid f04fa996-148a-453c-b037-1dcfbad120a6 \
    --key ../../export-ta_arm32/keys/oem_privkey.pem \
    --in ../../ta/top_level_subkey.pem \
    --out ../../ta/top_level_subkey.bin --max-depth 4 --name-size 64 \
    --subkey-version 1

# Here, max-depth=4 indicates that the lower-level TA Subkey can be signed
# The maximum depth of the TA Subkey certificate chain is 4

sign_encrypt.py subkey-uuid \
    --in ../../ta/top_level_subkey.bin \
    --name mid_level_subkey

# Calculate the Next subkey UUID based on the Subkey UUID and mid_level_subkey
# Subkey UUID: f04fa996-148a-453c-b037-1dcfbad120a6
# Next subkey UUID: 1a5948c5-1aa0-518c-86f4-be6f6a057b16

sign_encrypt.py sign-subkey \
    --uuid 1a5948c5-1aa0-518c-86f4-be6f6a057b16 \
    --key ../../ta/top_level_subkey.pem \
    --subkey ../../ta/top_level_subkey.bin \
    --name-size 64 --subkey-version 1 \
    --name mid_level_subkey \
    --in ../../ta/mid_level_subkey.pem \
    --out ../../ta/mid_level_subkey.bin

# The parent TA Subkey signs the child TA Subkey
# mid_level_subkey.bin already contains the content of top_level_subkey.bin
# Forming a certificate chain

sign_encrypt.py subkey-uuid \
    --in ../../ta/mid_level_subkey.bin \
    --name subkey1_ta

# Calculate the Next subkey UUID using the Subkey UUID and subkey1_ta
# There is no lower-level Subkey, so this is the UUID of TA
# Subkey UUID: 1a5948c5-1aa0-518c-86f4-be6f6a057b16
# Next subkey UUID: 5c206987-16a3-59cc-ab0f-64b9cfc9e758
```

7. Built-in TA into secure storage

In normal cases, TA files are stored in plaintext in an non-secure file system after TA development. Some OEM that have high security requirements do not want TA files to be exposed in plaintext. To meet the OEM' requirements, OP-TEE V2 and OP-TEE V3 supports built-in TA files to secure storage (OP-TEE V1 does not support this).

7.1 Principle

The CA side reads TA files in the non-secure file system and sends TA data to the OP-TEE OS. After receiving TA data, the OP-TEE OS verifies the validity of TA. If TA is legal, it randomly generates TA encryption key and encrypts TA data with TA encryption key. Then the ciphertext TA data and TA encryption key are securely stored (For OP-TEE V2, If security partition is defined, it is stored in the security partition; if not defined, it is stored in the Android or Linux file system. For OP-TEE V3, it is stored in the Android or Linux file system). The key used for secure storage is derived from the unique key of the hardware, which is different for each device. Finally, the developer needs to delete TA files in the non-secure file system to prevent the plaintext TA from being exposed.

After the appeal step is complete, the CA can call the TA application normally. When the CA calls the TA in the secure storage, the OP-TEE OS searches for the TA in the secure storage according to the incoming uuid. If the TA is found, the OP-TEE OS decrypts and loads the TA; if the TA is not found in secure storage, the TA will be searched in the non-secure file system.

7.2 Reference implementation

Here is the CA-side code that lets you read the TA file and send the TA data to the OP-TEE OS using the `install_ta` function.

```
static void install_ta(void *buf, size_t blen)
{
    TEEC_Result res = TEEC_ERROR_GENERIC;
    uint32_t err_origin = 0;
    TEEC_UUID uuid = PTA_SECSTOR_TA_MGMT_UUID;
    TEEC_Operation op;
    TEEC_Context ctx = { };
    TEEC_Session sess = { };
    int i = 0;

    res = TEEC_InitializeContext(NULL, &ctx);
    if (res != TEEC_SUCCESS) {
        printf("TEEC_InitializeContext failed with code 0x%x\n", res);
        goto exit;
    }

    res = TEEC_OpenSession(&ctx, &sess, &uuid,
                   TEEC_LOGIN_PUBLIC, NULL, NULL, &err_origin);
    if (res != TEEC_SUCCESS) {
        printf("TEEC_Opensession failed with code 0x%x origin 0x%x\n",
               res, err_origin);
        goto exit;
    }

    memset(&op, 0, sizeof(op));
    op.paramTypes = TEEC_PARAM_TYPES(TEEC_MEMREF_TEMP_INPUT, TEEC_NONE,
```

```
                    TEEC_NONE, TEEC_NONE);
    op.params[0].tmpref.buffer = buf;
    op.params[0].tmpref.size = blen;

    res = TEEC_InvokeCommand(&sess, PTA_SECSTOR_TA_MGMT_BOOTSTRAP, &op,
                &err_origin);
    if (res != TEEC_SUCCESS) {
        printf("TEEC_InvokeCommand failed with code 0x%x origin 0x%x\n",
               res, err_origin);
        goto exit;
    }
    printf("Installing TAs done\n");

exit:
    TEEC_CloseSession(&sess);
    TEEC_FinalizeContext(&ctx);

    return;
}
```

8. Encrypt TA

Section in the previous chapter Built-in TA to secure storage introduce one way to avoid exposing clear TA file, but the built-in TA will take up secure storage space, If the secure storage data is abnormal, the built-in TA cannot be used, and TA's secret key is randomly generated, not the developers own encryption key, this chapter introduces another kind of encryption method of TA (OP - TEE V2 and OP - TEE V3 support, OP-TEE V1 is not currently supported).

8.1 Method of encrypting TA

If the developer has TA source code, the developer needs to enable the `CFG_ENCRYPT_TA` macro in `export-ta_arm32/mk/link.mk` and change `TA_ENC_KEY` to developer's own encryption key. After this macro is enabled, the script will automatically sign and encrypt TA when the developer compiles TA application.

If the developer does not have TA source code and only has TA binary files, they can use tools to encrypt the TA binary files. The required tools can be found in the rk_tee_user project tools/ directory.

Command to encrypt plaintext TA:

```
python3 ta_encrypt_tool.py --key oem_privkey.pem --in 1db57234-dacd-462d-9bb1-ae79de44e2a5.ta --enc_key 'b64d239b1f3c7d3b06506229cd8ff7c8af2bb4db2168621ac62c84948468c4f4'
```

Command to re-encrypt ciphertext TA:

```
python3 ta_encrypt_tool.py --key oem_privkey.pem --in 1db57234-dacd-462d-9bb1-ae79de44e2a5.ta --ori_enc_key 'b64d239b1f3c7d3b06506229cd8ff7c8af2bb4db2168621ac62c84948468c4f4' --enc_key 'c74d239b1f3c7d3b06506229cd8ff7c8af2bb4db2168621ac62c84948468c4f4'
```

Tool parameter description:

--key Point to the user's private asymmetric key file used for signing TA.

--in Point to TA file.

--enc_key The user's private symmetric key used to encrypt TA.


--ori_enc_key The original symmetric key used to encrypt TA.

8.2 Burn TA encryption key

The developer uses the `RKDevInfoWriteTool` tool (version no less than 1.2.8) in the RKTools directory of the SDK project to write TA encryption key.

Before use, the developer needs to create a new key file, open the file in hexadecimal format, edit the developer's 32-byte encryption key in the file, open the RKDevInfoWriteTool tool, select "TA encryption key", and click the button to select the key file created by the developer. After the device enters the LOADER mode, click the "Write" ("写入") button to write the key. The key will be written to the device OTP (the OTP area cannot be changed once written, so the key can only be written once on device).

To prevent TA encryption key disclosure, the tool does not support reading TA encryption key.



8.3 Decrypt and run the TA

The use of encrypted TA and plaintext TA is exactly the same. OP-TEE OS will automatically recognize that TA is encrypted when loading TA, and OP-TEE OS will automatically read TA encryption key in OTP and decrypt and run TA. This process is automatically completed by OP-TEE OS.

8.4 Soft TA encryption key

If developers do not want to add extra steps to burn the TA encryption key to the device OTP, they can use the Soft TA encryption key, which is a symmetric key built into the TEE binary.

If the developer has burned the TA encryption key to the device OTP, the OP-TEE OS will prioritize using the TA encryption key in the OTP to decrypt and run the TA, ensuring high security.

If the developer does not burn the TA encryption key to the device OTP, the OP-TEE OS will use the Soft TA encryption key to decrypt and run the TA, resulting in lower security.

Developers need to use tools to replace the Soft TA encryption key in the TEE binary. The required tools can be found in the rk_tee_user project tools/ directory.

Command to replace the default Soft TA encryption key in TEE binary:

```
./change_ta_enc_key --teebin <TEE binary> --takey
'b64d239b1f3c7d3b06506229cd8ff7c8af2bb4db2168621ac62c84948468c4f4'
```

Tool parameter description:

--teebin Provide the TEE binary firmware path.

--takey 32 bytes private key for developers, which must be consistent with the key used to encrypt TA.

9. REE FS TA anti-rollback

TA files are generally stored in the non-secure file system (REE FS). To prevent the TA version from being rolled back in a non-secure REE environment, the TA anti-rollback feature can be utilized. OP-TEE V2 and OP-TEE V3 platforms support TA anti-rollback, while OP-TEE V1 platform does not support it yet.

9.1 TA anti-rollback usage

The TA anti-rollback function of REE FS is always enabled. Developers can use the anti-rollback function by defining the TA version number in the Makefile.

If `CFG_TA_VERSION` is never defined in TA's Makefile, the system recognizes TA's version number as 0 and allows TA with the same version number to run.

If the Makefile of TA defines that the current `CFG_TA_VERSION` is greater than 0, as shown in the following example, the rollback of TA version is prevented.

```
# unsigned integer format
CFG_TA_VERSION=1
```

10. Solution of optional strong or weak security levels

10.1 Scope

Solution applies to:

The OP-TEE V2 platform includes the following SoCs: RK3588, RK3528, RK3562, RK3576, RK3506, RV1106, RV1103B, and RV1126B.

All platforms of OP-TEE V3.

10.2 Notes

Before using this solution, you should be aware of the following.

- Before downloading the firmware for the first time, confirm that the configuration items of uboot `CONFIG_OPTEE_SECURITY_LEVEL` configured as required. It only supports configuration once and cannot be modified later. The SDK is security level 0 as defaults. If the development board has already burned the leve0 firmware, burning the leve1 or level 2 firmware may not start properly. Therefore, it is recommended to test with a new device after changing the `CONFIG_OPTEE_SECURITY_LEVEL` .
- If you select "Strong Security Solution 1", download the OEM HUK using the tool `RKDevInfoWriteTool (V1.3.5 and above)` before using.

10.3 Solution description

The solution supports the configuration of the security level of OP-TEE by the developer, and the protection strength of eMMC/Secure Storage is different for each security levels.

Security level	**Description**	**CONFIG_OPTEE_SECURITY_LEVEL (uboot's configuration item)**
Strong Security Solution 2	CPU chip and eMMC/secure storage data are strongly bound, if the CPU chip is replaced, you should replace a new eMMC chip and erase securely stored data.	2
Strong Security Solution 1	CPU chip and eMMC/secure storage data are weakly bound, the OEM HUK which derives for protecting eMMC/secure storage is defined by developer, if you download the same OEM HUK after replacing the CPU chip, then you can use the original eMMC/secure storage data.	1
Weak Security Solution	CPU chip and eMMC/secure storage data are not bound, you can use the original eMMC/secure storage data after replacing the CPU chip.	0 or none

The difference between the above security levels is due to the difference between eMMC and Secure Storage related keys. The keys related to this solution are described below.

- HUK: for deriving RPMB Key, Secure Storage Key and other keys. Different HUK for different security levels. See figures below for details.
  Hard HUK is derived from the Device Root Key. Unique key in chips. Device Root Key was burned into secure OTP when chip is manufactured.
  OEM HUK is defined by developer and burned into secure OTP by developer.
  Soft HUK is defined by Rockchip and all chips have the same soft HUK. It is stored in firmware.
- RPMB Key: the storage protection key of the eMMC chip.
- Secure Storage Key: the key for secure storage.
- Other Key: other keys used in OP-TEE.

```
Strong Security Solution 2

                                    /------> RPMB Key
Device Root Key ---> Hard HUK ------> Secure Storage Key
                                    \------> Other Key

Strong Security Solution 1

Device Root Key ---> Hard HUK ------> Other Key

                      /------> RPMB Key
OEM HUK ---------------
                      \------> Secure Storage Key

Weak Security Solution

Device Root Key ---> Hard HUK ------> Other Key

                      /------> RPMB Key
Soft HUK ---------------
                      \------> Secure Storage Key
```

11. TA debugging methods

11.1 OP-TEE v1 platforms

When TA encounters a serious error condition, it prints diagnostic information as follows.

```
user TA data-abort at address 0x2a

 esr 0x92000021  ttbr0 0x400000852fc00   ttbr1 0x00000000   cidr 0x0

 cpu #4          cpsr 0x20000130

#For 32-bit platforms, print r0-r12, sp, lr, pc(402000a0)
#For 64-bit platforms, print x0-x30, sp_el0, elr(00000000402000a0)

Status of TA 8cccf200-2450-11e4-abe20002a5d5c52c (0x85109b0) (active)
```

```
- load addr : 0x40200000    ctx-idr: 4
- code area : 0x9200000 2097152
- stack: 0x9400000 stack:2048
TEEC_InvokeCommand failed with code 0xffff3024 origin 0x3
```

The `pc` or `elr` in the error condition is the virtual address that caused the exception. The `load addr` is the virtual address of the TA running in memory. We can konw the offset of the exception code in the TA is, elr - load addr = 0x402000a0 - 0x40200000 = 0xa0.

In the compiled directory, there is a file named by `uuid.dmp` in the same directory as the TA. The `uuid.dmp` is a disassembly file of the TA, which identifies the offset address of each function in the TA. Search for `a0` in the `uuid.dmp`, as follows, where `testapp_ta.c:97` indicates that the exception code is on line 97 of `testapp_ta.c`.

```
/home/xxx/android/vendor/optee_test/ta/testapp/testapp_ta.c:97
      98:   6823        ldr r3, [r4, #0]
      9a:   2202        movs    r2, #2
      9c:   2161        movs    r1, #97 ; 0x61
      9e:   4820        ldr r0, [pc, #128]  ; (120
<TA_InvokeCommandEntryPoint+0xa0>)
      a0:   681b        ldr r3, [r3, #0]
      a2:   4478        add r0, pc
      a4:   3033        adds    r0, #51 ; 0x33
      a6:   9301        str r3, [sp, #4]
      a8:   4b1e        ldr r3, [pc, #120]  ; (124
<TA_InvokeCommandEntryPoint+0xa4>)
      aa:   447b        add r3, pc
      ac:   9300        str r3, [sp, #0]
      ae:   2301        movs    r3, #1
      b0:   f002 fbc0   bl  2834 <trace_printf>
```

11.2 OP-TEE v2 and OP-TEE v3 platforms

When TA encounters a serious error condition, it prints diagnostic information as follows.

```
E/TC:? 0 User mode data-abort at address 0x2a (translation fault)
E/TC:? 0  esr 0x92000005  ttbr0 0x20000084a7020   ttbr1 0x00000000   cidr 0x0
E/TC:? 0  cpu #1          cpsr 0x20000130

#For 32-bit platforms, print r0-r12, sp, lr, pc(c00870a4)
#For 64-bit platforms, print x0-x30, sp_el0, elr(00000000c00870a4)

E/LD:  region  0: va 0xc0004000 pa 0x08600000 size 0x002000 flags rw-s (ldelf)
E/LD:  region  1: va 0xc0006000 pa 0x08602000 size 0x008000 flags r-xs (ldelf)
E/LD:  region  2: va 0xc000e000 pa 0x0860a000 size 0x001000 flags rw-s (ldelf)
E/LD:  region  3: va 0xc000f000 pa 0x0860b000 size 0x004000 flags rw-s (ldelf)
E/LD:  region  4: va 0xc0013000 pa 0x0860f000 size 0x001000 flags r--s
E/LD:  region  5: va 0xc0014000 pa 0x08625000 size 0x001000 flags rw-s (stack)
E/LD:  region  6: va 0xc0015000 pa 0x09201000 size 0x002000 flags rw-- (param)
E/LD:  region  7: va 0xc0087000 pa 0x00001000 size 0x009000 flags r-xs [0]
E/LD:  region  8: va 0xc0090000 pa 0x0000a000 size 0x00c000 flags rw-s [0]
E/LD:   [0] 8cccf200-2450-11e4-abe2-0002a5d5c52c @ 0xc0087000
E/LD:  Call stack:
E/LD:   0xc00870a4
```

```
E/LD:   0xc0088b21
E/LD:   0xc008d507
E/LD:   0xc008716c
```

The `pc` or `elr` in the error condition is the virtual address that caused the exception. The `region 0 - region 8` are the virtual address of the TA code running in memory. The exception code address `0xc00870a4` is in `region 7`. We can calculate the offset of the exception code as following, elr - region 7 : va = 0xc00870a4 - 0xc0087000 = 0xa4.

In the compiled directory, there is a file named by uuid.dmp in the same directory as the TA. The `uuid.dmp` is a disassembly file of the TA, which identifies the offset address of each function in the TA. Search for `a4` in the `uuid.dmp`, as follows, where `testapp_ta.c:101` indicates that the exception code is on line 101 of `testapp_ta.c`.

```
/home/xxx/rk_px30_linux/external/optee_test/ta/testapp/testapp_ta.c:101
      9c:   6823        ldr r3, [r4, #0]
      9e:   2202        movs    r2, #2
      a0:   4d28        ldr r5, [pc, #160]  ; (144
<TA_InvokeCommandEntryPoint+0xc4>)
      a2:   4e29        ldr r6, [pc, #164]  ; (148
<TA_InvokeCommandEntryPoint+0xc8>)
      a4:   681b        ldr r3, [r3, #0]
      a6:   447d        add r5, pc
      a8:   447e        add r6, pc
      aa:   3533        adds    r5, #51 ; 0x33
      ac:   4628        mov r0, r5
      ae:   9600        str r6, [sp, #0]
      b0:   9301        str r3, [sp, #4]
      b2:   2301        movs    r3, #1
      b4:   f000 f912   bl  2dc <trace_printf>
```

11.3 Call stack

If the exception code address is not enough for you and also need functions call stack, the script `export-ta_arm32\scripts\symbolize.py` in OP-TEE v2 or OP-TEE v3 provides to show call stack. Note that the OP-TEE v1 platform does not support the script.

Step 1, set the compiler path you are using.

```
#For 32-bit platforms, execute:
export PATH=/home1/hisping/rk_px30_linux/prebuilts/gcc/linux-x86/arm/gcc-linaro-
6.3.1-2017.05-x86_64_arm-linux-gnueabihf/bin:$PATH
export CROSS_COMPILE=arm-linux-gnueabihf-

#For 64-bit platforms, execute:
export PATH=/home1/hisping/rk_px30_linux/prebuilts/gcc/linux-x86/aarch64/gcc-
linaro-6.3.1-2017.05-x86_64_aarch64-linux-gnu/bin:$PATH
export CROSS_COMPILE=aarch64-linux-gnu-
```

Step 2, execute the script and `-d` parameter points to the TA compiled directory.

```
./export-ta_arm32/scripts/symbolize.py -d out/ta/testapp/
```

Step 3, the script will wait for the exception log, after input, you can get the following result including `Call stack`.

```
I/TA: Hello Test App!
E/TC:? 0
E/TC:? 0 User mode data-abort at address 0x2a (translation fault)
E/TC:? 0  esr 0x92000005  ttbr0 0x20000084a7020   ttbr1 0x00000000   cidr 0x0
E/TC:? 0  cpu #1          cpsr 0x20000130
E/TC:? 0  x0  00000000000069ee x1  0000000000000062
E/TC:? 0  x2  0000000000000002 x3  000000000000002a
E/TC:? 0  x4  00000000c0014f30 x5  00000000c0014f40
E/TC:? 0  x6  00000000c0074080 x7  00000000c0074308
E/TC:? 0  x8  00000000c00742e8 x9  00000000c0014f30
E/TC:? 0  x10 0000000000000065 x11 00000000c007f2d8
E/TC:? 0  x12 0000000000000773 x13 00000000c0014f00
E/TC:? 0  x14 00000000c006cb0d x15 0000000000000000
E/TC:? 0  x16 0000000000000000 x17 0000000000000000
E/TC:? 0  x18 0000000000000000 x19 0000000000000000
E/TC:? 0  x20 0000000000000000 x21 0000000000000000
E/TC:? 0  x22 0000000000000000 x23 0000000000000000
E/TC:? 0  x24 0000000000000000 x25 0000000000000000
E/TC:? 0  x26 0000000000000000 x27 0000000000000000
E/TC:? 0  x28 0000000000000000 x29 0000000000000000
E/TC:? 0  x30 0000000000000000 elr 00000000c006b0a4
E/TC:? 0  sp_el0 00000000c0014f80
E/LD:  Status of TA 8cccf200-2450-11e4-abe2-0002a5d5c52c
E/LD:   arch: arm
E/LD:  region  0: va 0xc0004000 pa 0x08600000 size 0x002000 flags rw-s (ldelf)
E/LD:  region  1: va 0xc0006000 pa 0x08602000 size 0x008000 flags r-xs (ldelf)
E/LD:  region  2: va 0xc000e000 pa 0x0860a000 size 0x001000 flags rw-s (ldelf)
E/LD:  region  3: va 0xc000f000 pa 0x0860b000 size 0x004000 flags rw-s (ldelf)
E/LD:  region  4: va 0xc0013000 pa 0x0860f000 size 0x001000 flags r--s
E/LD:  region  5: va 0xc0014000 pa 0x08625000 size 0x001000 flags rw-s (stack)
E/LD:  region  6: va 0xc0015000 pa 0x09201000 size 0x002000 flags rw-- (param)
E/LD:  region  7: va 0xc006b000 pa 0x00001000 size 0x009000 flags r-xs [0]
.ta_head .text .rodata .ARM.extab .ARM.exidx .dynsym .dynstr .hash
E/LD:  region  8: va 0xc0074000 pa 0x0000a000 size 0x00c000 flags rw-s [0]
.dynamic .got .rel.got .data .bss .rel.dyn
E/LD:   [0] 8cccf200-2450-11e4-abe2-0002a5d5c52c @ 0xc006b000
(out/ta/testapp/8cccf200-2450-11e4-abe2-0002a5d5c52c.elf)
E/LD:  Call stack:
E/LD:   0xc006b0a4 TA_InvokeCommandEntryPoint at ta/testapp/testapp_ta.c:98
E/LD:   0xc006cb0d entry_invoke_command at
/home/zhangzj/secure/optee_3.6.0/optee_os/lib/libutee/arch/arm/user_ta_entry.c:3
57
E/LD:   0xc00714f3 __ta_entry_c at export-ta_arm32/src/user_ta_header.c:48
E/LD:   0xc006b158 __ta_entry at export-ta_arm32/src/ta_entry_a32.S:20
```

12. Memory description

12.1 OP-TEE V1

platform	TEE_RAM	TA_RAM	SHMEM
RK312x	1M	12M	1M
RK322x	1M	12M	2M
RK3288	1M	12M	2M
RK3368	2M	24M	4M
RK3328/RK322xH	2M	24M	4M
RK3399/RK3399Pro	2M	24M	4M

Note: The secure OS runs in TEE_RAM. The TA runs in TA_RAM. SHMEM is the shared memory.

12.2 OP-TEE V2

platform	TEE_RAM	TA_RAM	SHMEM
RK3326/PX30	2M	4M	2M
RK3358	2M	4M	2M
RK3308	2M	1M	1M
RK1808	2M	1M	1M
RV1109/RV1126	760K	1M	512K
RK3566/RK3568	2M	12M	2M
RK3588	2M	12M	2M
RK3528	2M	4M	2M
RK3562	2M	4M	2M
RV1106	1M	1M	512K

Note: The secure OS runs in TEE_RAM. The TA runs in TA_RAM. SHMEM is the shared memory.

OP-TEE OS supports printing secure memory info, and developers can view the following information in the startup log.

```
I/TC: OP-TEE memory: TEEOS 0x200000 TA 0xc00000 SHM 0x200000
I/TC: Primary CPU initializing
I/TC: Primary CPU switching to normal world boot
```

If the size of the startup log printing does not match the above list, the printing shall prevail.

12.3 OP-TEE V3

OP-TEE OS supports printing secure memory info, and developers can view the following information in the startup log.

```
I/TC: OP-TEE memory size: TEEOS 0x200000 TA 0x400000 SHM 0x200000
I/TC: Primary CPU initializing
I/TC: Primary CPU switching to normal world boot
```

13. Secure Storage

13.1 Partition

1. Secure storage is one of the important functions of OP-TEE OS. It generally used to store private user data. Data is encrypted by OP-TEE OS and then stored in the security partition or rpmb partition or Android/Linux file system.

There are three types of TEE secure storage:

The first type, storing data in the RPMB partition

set storageID=TEE_STORAGE_PRIVATE_RPMB in TA code, then eMMC RPMB is used for secure storage. The RPMB size varies for each eMMC model, typically 4M.

The second type, storing data in the security partition

OP-TEE V1 and OP-TEE V2 platforms:

define security partition in parameter.txt and set storageID=TEE_STORAGE_PRIVATE_REE in TA code, then secure storage is stored in the security partition, which is currently available at 512k.

OP-TEE V3 platforms:

set storageID = TEE_STORAGE_PRIVATE_RKSS in TA code. Then secure storage is located in the security partition, security partition size is configurable, typically set to 1M, 2M, 4M, with a maximum support of 32M.

The third type, storing data in the file system

OP-TEE V1 and OP-TEE V2 platforms:

There is no security partition defined in parameter.txt and set storageID=TEE_STORAGE_PRIVATE_REE in TA code, then secure storage is stored in the Android/Linux file system /metadata/tee or /data/vendor/tee or /data/tee directory (please confirm that tee-supplicant has permission to access this directory), and the total space is not limited. The disadvantage is that it cannot define security partitions, and the security data during the U-Boot stage can only be stored in the eMMC RPMB.

OP-TEE V3 platforms:

set storageID=TEE_STORAGE_PRIVATE_REE in TA code, then secure storage is stored in the Android/Linux file system /data/vendor/tee or /data/tee directory, and the total space is not limited.

2. Secure storage on the Uboot side, please refer to the "TEE Driver in U-Boot" section.
3. Make sure that the device does not power down when writing data for secure storage. The reason is that although we have done power loss protection but do not ensure the integrity of file system. Therefore, it is recommended that developers reduce the number of writes to ensure data security. In theory, RPMB provides better power off protection than security and Android/Linux file systems.

13.2 Performance testing

Test environment: OP-TEE V1, RK3399 in Linux platform, CPU fixed frequency to 1200000, DDR fixed frequency to 200000000.

Storage area	Data size	Create an empty file	Write	Read	Delete the file
Linux file system	30K	16ms	67ms	61ms	19ms
Linux file system	4K	17ms	23ms	13ms	7ms
Linux file system	1K	18ms	16ms	7ms	6ms
Linux file system	32	23ms	16ms	7ms	7ms
security partition	30K	97ms	181ms	54ms	277ms
security partition	4K	101ms	74ms	14ms	101ms
security partition	1K	104ms	56ms	7ms	64ms
security partition	32	103ms	55ms	7ms	73ms
rpmb partition	30K	20ms	233ms	10ms	7ms
rpmb partition	4K	20ms	36ms	3ms	6ms
rpmb partition	1K	22ms	14ms	2ms	6ms
rpmb partition	32	27ms	8ms	2ms	6ms

Test environment: OP-TEE V2, RK356x in Linux platform, CPU fixed frequency to 1416000, DDR fixed frequency to 324000000.

Storage area	Data size	Create an empty file	Write	Read	Delete the file
Linux file system	30K	17ms	28ms	3ms	8ms
Linux file system	4K	17ms	11ms	1ms	8ms
Linux file system	1K	18ms	9ms	1ms	8ms
Linux file system	32	19ms	8ms	1ms	7ms
security partition	30K	12ms	12ms	4ms	12ms
security partition	4K	12ms	3ms	1ms	11ms
security partition	1K	13ms	2ms	1ms	11ms
security partition	32	15ms	3ms	1ms	14ms
rpmb partition	30K	23ms	287ms	16ms	5ms
rpmb partition	4K	24ms	50ms	7ms	6ms
rpmb partition	1K	23ms	22ms	5ms	6ms
rpmb partition	32	30ms	12ms	5ms	5ms

Test environment: OP-TEE V3, RK3538 in Android platform, CPU fixed frequency to 1416000, DDR fixed frequency to 400000000.

Storage area	Data size	Create an empty file	Write	Read	Delete the file
Linux file system	30K	18ms	24ms	1ms	5ms
Linux file system	4K	18ms	10ms	1ms	5ms
Linux file system	1K	18ms	8ms	1ms	5ms
Linux file system	32	18ms	7ms	1ms	5ms
security partition	30K	7ms	26ms	5ms	18ms
security partition	4K	7ms	4ms	1ms	12ms
security partition	1K	7ms	3ms	1ms	12ms
security partition	32	6ms	2ms	1ms	12ms
rpmb partition	30K	8ms	142ms	22ms	2ms
rpmb partition	4K	7ms	21ms	4ms	2ms
rpmb partition	1K	7ms	8ms	2ms	2ms
rpmb partition	32	7ms	5ms	1ms	2ms

14. OTP description

OTP is One Time Programmable Memory. The OTP region supports multiple reads but only written once.

Multiple different OEM Zone areas are reserved in Secure OTP to meet users' different usage needs.

OTP type	Description	supported platforms
OEM Cipher Key	This OEM Zone area is used to store user keys. Once the key is written, it cannot be changed. After the user burns the key, they can use the specified key for encryption and decryption operations.	rv1126, rv1109, rk3566, rk3568, rk3588, rk3576, rk3528, rk3562, rv1106, rv1103, rv1106b, rv1103b, rk3506, rv1126b
Protected OEM Zone	This OEM Zone area is only available for Trust Application (TA application) calls running on OP-TEE OS, and cannot be directly read or written to in non secure world. Please refer to rktest demo.	rk3308, px30, rk3326, rk3358, rk3566, rk3568, rk3588, rv1126, rv1109, rk3528, rk3562, rv1106, rv1103, rk3576, rv1106b, rv1103b, rk3506, rv1126b
Non-Protected OEM Zone	This OEM Zone area can be called by U-Boot and UserSpace, and the data will be exposed in non secure world memory.	rk3308, px30, rk3326, rk3358, rk3566, rk3568, rk3588, rv1106, rv1103, rk3528, rk3562, rk3576, rv1106b, rv1103b, rk3506

For more details, please refer to the document "Rockchip_Developer_Guide_OTP_EN.pdf"

15. TA API description

15.1 Overview

RK provides the following APIs for two purposes:

- For developers to refer to how to use the TEE Internal APIs
- For developers to use the APIs directly

15.2 API return value

The return value of APIs are:

- TEE_SUCCESS: if the function executes successfully
- TEE_ERROR_BAD_PARAMETERS: if the parameter is wrong
- Others: see `tee_api_defines.h`

15.3 API description

15.3.1 Crypto API

15.3.1.1 rk_crypto_malloc_ctx

```
crypto_ctx_t *rk_crypto_malloc_ctx(void);
```

Description

Request a crypto operation handle resource.

Parameters

- None.

15.3.1.2 rk_crypto_free_ctx

```
void rk_crypto_free_ctx(crypto_ctx_t **ctx);
```

Description

Release the crypto operation handle. It should be executed to release resources after algorithm is done.

Parameters

- ctx: crypto context

15.3.1.3 rk_hash_crypto

```
TEE_Result rk_hash_crypto(uint8_t *in, uint8_t *out, uint32_t in_len,
                          uint32_t out_len, uint32_t algo);
```

Description

The hash digest algorithm. If you need to input message multiple times, you can use the `rk_hash_begin/update/finish` interface.

Parameters

- in: input data
- in_len: the length of input
- out: output data
- out_len: the length of output
- algo: algorithm type, supports `TEE_ALG_MD5, TEE_ALG_SHA1, TEE_ALG_SHA224, TEE_ALG_SHA256, TEE_ALG_SHA384, TEE_ALG_SHA512`

15.3.1.4 rk_hash_begin

```
TEE_Result rk_hash_begin(crypto_ctx_t *ctx, uint32_t algo);
```

Description

The hash digest algorithm for multiple, initialization operation.

Parameters

- ctx: crypto context
- algo: algorithm type, supports `TEE_ALG_MD5, TEE_ALG_SHA1, TEE_ALG_SHA224, TEE_ALG_SHA256, TEE_ALG_SHA384, TEE_ALG_SHA512`

15.3.1.5 rk_hash_update

```
TEE_Result rk_hash_update(crypto_ctx_t *ctx, uint8_t *in, uint32_t in_len);
```

Description

The hash digest algorithm for multiple, calculates digest of the data inputed.

Parameters

- ctx: crypto context
- in: input data
- in_len: the length of input

15.3.1.6 rk_hash_finish

```
TEE_Result rk_hash_finish(crypto_ctx_t *ctx, uint8_t *in, uint8_t *out,
                          uint32_t in_len, uint32_t *out_len);
```

Description

The hash digest algorithm for multiple, calculates the digest of the last part and output the digest.

Parameters

- ctx: crypto context
- in: input data
- in_len: the length of input
- out: output data
- out_len: the length of output

15.3.1.7 rk_cipher_crypto

```
TEE_Result rk_cipher_crypto(uint8_t *in, uint8_t *out, uint32_t len,
                            uint8_t *key, uint32_t key_len, uint8_t *iv,
                            uint32_t algo, TEE_OperationMode mode);
```

Description

Symmetric encryption/decryption algorithm interface. If you need to input data multiple times, you can use the `rk_cipher_begin/update/finish` interface.

Parameters

- in: input data

- len: the length of input
- out: output data
- key: the key used for cipher
- key_len: the length of key, different algo may supports different key lengths
- iv: initialization vector
- algo: algorithm type, support the following(OP-TEE V1 dose not support the SM algorithm)

```
TEE_ALG_AES_ECB_NOPAD
TEE_ALG_AES_CBC_NOPAD
TEE_ALG_AES_CTR
TEE_ALG_AES_CTS
TEE_ALG_AES_XTS
TEE_ALG_SM4_ECB_NOPAD
TEE_ALG_SM4_CBC_NOPAD
TEE_ALG_SM4_CTR
TEE_ALG_DES_ECB_NOPAD
TEE_ALG_DES_CBC_NOPAD
TEE_ALG_DES3_ECB_NOPAD
TEE_ALG_DES3_CBC_NOPAD
```

- mode: the mode of cipher

15.3.1.8 rk_set_padding

```
TEE_Result rk_set_padding(crypto_ctx_t *ctx, int padding);
```

Description

Sets the padding mode for encrypted/decrypted data.

Parameters

- ctx: crypto context
- padding: see `rk_padding_t` for supported modes

15.3.1.9 rk_cipher_begin

```
TEE_Result rk_cipher_begin(crypto_ctx_t *ctx, uint8_t *key, uint32_t key_len,
                           uint8_t *iv, uint32_t algo, TEE_OperationMode mode);
```

Description

The initialization operation of the symmetric encryption/decryption algorithm for multiple.

Parameters

- ctx: crypto context
- key: the key used for cipher
- key_len: the length of key, different algo may supports different key lengths
- iv: initialization vector

- algo: algorithm type, support the following(OP-TEE V1 dose not support the SM algorithm)

```
TEE_ALG_AES_ECB_NOPAD
TEE_ALG_AES_CBC_NOPAD
TEE_ALG_AES_CTR
TEE_ALG_AES_CTS
TEE_ALG_AES_XTS
TEE_ALG_SM4_ECB_NOPAD
TEE_ALG_SM4_CBC_NOPAD
TEE_ALG_SM4_CTR
TEE_ALG_DES_ECB_NOPAD
TEE_ALG_DES_CBC_NOPAD
TEE_ALG_DES3_ECB_NOPAD
TEE_ALG_DES3_CBC_NOPAD
```

- mode: the mode of cipher

15.3.1.10 rk_cipher_update

```
TEE_Result rk_cipher_update(crypto_ctx_t *ctx, uint8_t *in, uint8_t *out,
                            uint32_t in_len, uint32_t *out_len);
```

Description

Encrypt/decrypt the input data of symmetric encryption/decryption algorithm for multiple.

Parameters

- ctx: crypto context
- in: input data
- in_len: the length of input
- out: output data
- out_len: the length of output

15.3.1.11 rk_cipher_finish

```
TEE_Result rk_cipher_finish(crypto_ctx_t *ctx, uint8_t *out, uint32_t *out_len);
```

Description

Finish the encryption/decryption operation of symmetric encryption/decryption algorithm for multiple.

Parameters

- ctx: crypto context
- out: output data
- out_len: the length of output

15.3.1.12 rk_ae_begin

```
TEE_Result rk_ae_begin(crypto_ctx_t *ctx, uint8_t *key, uint32_t key_len,
                       uint8_t *iv, uint32_t iv_len,
                       uint32_t add_len, uint32_t tag_len,
                       uint32_t payload_len, uint32_t algo, TEE_OperationMode
mode);
```

Description

Initialization operations of AES-CCM or AES-GCM algorithms.

Parameters

- ctx: crypto context
- key: the key for calculation
- key_len: the length of key, supports 16, 24, 32
- iv: initialization vector
- iv_len: the length of iv
- add_len: the ADD length of the AES-CCM
- tag_len: the tag length(bit), AES-GCM supports 128, 120, 112, 104, 96, and AES-CCM supports 128, 112, 96, 80, 64, 48, 32
- payload_len: the payload length of the AES-CCM
- algo: algorithm type, support `TEE_ALG_AES_GCM, TEE_ALG_AES_CCM`
- mode: encryption or decryption mode

15.3.1.13 rk_ae_update

```
TEE_Result rk_ae_update(crypto_ctx_t *ctx, uint8_t *in, uint8_t *out,
                        uint32_t in_len, uint32_t *out_len,
                        rk_ae_update_type_t is_aad);
```

Description

Encrypts/decrypts the input data for AES-CCM or AES-GCM algorithms.

Parameters

- ctx: crypto context
- in: input data
- in_len: the length of input
- out: output data
- out_len: the length of output
- is_add: identifies whether there is AAD(Additional Authentication Data)

15.3.1.14 rk_ae_finish

```
TEE_Result rk_ae_finish(crypto_ctx_t *ctx, uint8_t *in, uint8_t *out,
                        uint8_t *tag, uint32_t in_len,
                        uint32_t *out_len, uint32_t *tag_len);
```

Description

Complete the encryption/decryption operation for AES-CCM or AES-GCM algorithms.

Parameters

- ctx: crypto context
- in: the last input data
- in_len: the length of the last input data
- out: output data
- out_len: the length of output
- tag: output tag
- tag_len: the length of tag

15.3.1.15 rk_gen_rsa_key

```
TEE_Result rk_gen_rsa_key(rsa_key_t *rsa_key, uint32_t key_len,
                          uint64_t public_exponent);
```

Description

Randomly generate RSA key pairs.

Parameters

- rsa_key: the output RSA key pairs
- key_len: the length of RSA keys (byte), supports 32, 64, 96, 128, 192, 256, 384, 512
- public_exponent: public exponent, supports 3, 65537

15.3.1.16 rk_rsa_crypto

```
TEE_Result rk_rsa_crypto(uint8_t *in, uint8_t *out, uint32_t len,
                         rsa_key_t *key, uint32_t algo, TEE_OperationMode mode);
```

Description

RSA encryption/decryption algorithms. You can also use the `rk_rsa_begin/finish` interface.

Parameters

- in: input data
- len: the length of input
- out: output data
- key: the RSA key
- algo: the padding mode of RSA, supports:

  ```
  TEE_ALG_RSAES_PKCS1_V1_5
  TEE_ALG_RSAES_PKCS1_OAEP_MGF1_SHA1
  TEE_ALG_RSAES_PKCS1_OAEP_MGF1_SHA224
  TEE_ALG_RSAES_PKCS1_OAEP_MGF1_SHA256
  TEE_ALG_RSAES_PKCS1_OAEP_MGF1_SHA384
  TEE_ALG_RSAES_PKCS1_OAEP_MGF1_SHA512
  TEE_ALG_RSA_NOPAD
  ```

- mode: the mode of RSA, supports `TEE_MODE_ENCRYPT` and `TEE_MODE_DECRYPT`

15.3.1.17 rk_rsa_sign

```
TEE_Result rk_rsa_sign(uint8_t *digest, uint8_t *signature, uint32_t digest_len,
                       uint32_t *signature_len, rsa_key_t *key,
                       uint32_t salt_len, uint32_t algo, TEE_OperationMode
mode);
```

Description

RSA sign/verify algorithm. You can also use the `rk_rsa_begin/finish` interface.

Parameters

- digest: digest value
- signature: the output value of sign, or the input value to be verified
- digest_len: the length of digest
- signature_len: the length of signature
- key: RSA key
- salt_len: the length of salt, it is optional, if it is 0 then the salt length is equal to the digest length
- algo: algorithm, see `GPD_TEE_Internal_Core_API_Specification, Table 6-4` for details
- mode: the mode of RSA, supports `TEE_MODE_SIGN` and `TEE_MODE_VERIFY`

15.3.1.18 rk_set_sign_mode

```
TEE_Result rk_set_sign_mode(crypto_ctx_t *ctx, unsigned int mode);
```

Description

Set the RSA sign mode, sign data or sign digest.

Parameters

- ctx: crypto context
- mode: `SIGN_DATA` for signing data and `SIGN_DIGEST` for signing digest

15.3.1.19 rk_rsa_begin

```
TEE_Result rk_rsa_begin(crypto_ctx_t *ctx, rsa_key_t *key,
                        uint32_t algo, TEE_OperationMode mode);
```

Description

Initialization of RSA encryption/decryption/sign/verify.

Parameters

- ctx: crypto context
- key: RSA key
- algo: the padding mode of RSA, see `GPD_TEE_Internal_Core_API_Specification, Table 6-4` for details
- mode: algorithm type, support `TEE_MODE_ENCRYPT, TEE_MODE_DECRYPT, TEE_MODE_SIGN, TEE_MODE_VERIFY`

15.3.1.20 rk_rsa_finish

```
TEE_Result rk_rsa_finish(crypto_ctx_t *ctx, uint8_t *in, uint8_t *out,
                         uint32_t in_len, uint32_t *out_len, uint32_t salt_len);
```

Description

RSA algorithm executed after `rk_rsa_begin`.

Parameters

- ctx: crypto context
- in: input data
- in_len: the length of input
- out: output data
- out_len: the length of output
- salt_len: the length of salt, it is optional

15.3.1.21 rk_gen_ec_key

```
TEE_Result rk_gen_ec_key(ec_key_t *ec_key, uint32_t key_len, uint32_t curve);
```

Description

Randomly generate ECC key pairs.

Parameters

- ec_key: the output ECC key pairs
- key_len: the length of key (bit), supports 192, 224, 256, 384, 521
- curve: ECC curve, see `tee_api_defines.h` for details

15.3.1.22 rk_ecdh_genkey

```
TEE_Result rk_ecdh_genkey(uint8_t *private, uint8_t *publicx, uint32_t *publicy,
                          uint32_t algo,  uint32_t curve,
                          uint32_t keysize, uint8_t *out);
```

Description

Perform ECDH to negotiate symmetric key.

Parameters

- private: ECC private key
- publicx: X-coordinate of ECC public key
- publicy: Y-coordinate of ECC public key
- algo: algorithm, supports `TEE_ALG_ECDH_P192, TEE_ALG_ECDH_P224, TEE_ALG_ECDH_P256, TEE_ALG_ECDH_P384, TEE_ALG_ECDH_P521`
- curve: ECC curve, supports `TEE_ECC_CURVE_NIST_P192, TEE_ECC_CURVE_NIST_P224, TEE_ECC_CURVE_NIST_P256, TEE_ECC_CURVE_NIST_P384, TEE_ECC_CURVE_NIST_P521`
- keysize: the length of key (bit), supports 192, 224, 256, 384, 521
- out: output symmetric key

15.3.1.23 rk_ecdsa_sign

```
TEE_Result rk_ecdsa_sign(uint8_t *digest, uint8_t *signature,
                         uint32_t digest_len, uint32_t *signature_len,
                         ec_key_t *key, uint32_t algo, TEE_OperationMode mode);
```

Description

ECDSA sign/verify algorithm. You can also use the `rk_ecdsa_begin/finish` interface.

Parameters

- digest: input digest
- signature: output signature, or input signature for verified
- digest_len: the length of digest
- signature_len: the length of signature
- key: ECC key
- algo: algorithm, supports `TEE_ALG_ECDSA_P224, TEE_ALG_ECDSA_P256, TEE_ALG_ECDSA_P384, TEE_ALG_ECDSA_P521`
- mode: the mode of ECC, supports `TEE_MODE_SIGN, TEE_MODE_VERIFY`

15.3.1.24 rk_ecdsa_begin

```
TEE_Result rk_ecdsa_begin(crypto_ctx_t *ctx, ec_key_t *key,
                          uint32_t algo,TEE_OperationMode mode);
```

Description

Initialization operations of ECDSA.

Parameters

- ctx: crypto context
- key: ECC key
- algo: algorithm, supports `TEE_ALG_ECDSA_P224, TEE_ALG_ECDSA_P256, TEE_ALG_ECDSA_P384, TEE_ALG_ECDSA_P521`
- mode: mode, supports `TEE_MODE_SIGN, TEE_MODE_VERIFY`

15.3.1.25 rk_ecdsa_finish

```
TEE_Result rk_ecdsa_finish(crypto_ctx_t *ctx, uint8_t *in, uint8_t *out,
                           uint32_t in_len, uint32_t *out_len);
```

Description

ECDSA signs the input digest, or verifys the input digest and signature.

Parameters

- ctx: crypto context
- in: input digest
- out: output signature, or input signature for verified
- in_len: the length of input

- out_len: the length of output

15.3.1.26 rk_sm2_pke

```
TEE_Result rk_sm2_pke(uint8_t *in, uint32_t in_len, uint8_t *out,
                      uint32_t *out_len, ec_key_t *key,
                      uint32_t algo, TEE_OperationMode mode);
```

Description

SM2 encryption/decryption. OP-TEE V1 does not support this interface.

Parameters

- in: input data
- in_len: the length of input
- out: output data
- out_len: the length of output
- key: SM2 key
- algo: algorithm, supports `TEE_ALG_SM2_PKE`
- mode: mode, supports `TEE_MODE_ENCRYPT` and `TEE_MODE_DECRYPT`

15.3.1.27 rk_sm2_dsa_sm3

```
TEE_Result rk_sm2_dsa_sm3(uint8_t *digest, uint32_t digest_len,
                          uint8_t *signature, uint32_t *signature_len,
                          ec_key_t *key, uint32_t algo, TEE_OperationMode mode);
```

Description

SM2 sign/verify. OP-TEE V1 does not support this interface.

Parameters

- digest: SM3 digest
- digest_len: the length of SM3 digest, fixed to 32
- signature: output signature, or input signature for verified
- signature_len: the length of signature
- key: SM2 key
- algo: algorithm, supports `TEE_ALG_SM2_DSA_SM3`
- mode: mode, supports `TEE_MODE_SIGN` and `TEE_MODE_VERIFY`

15.3.1.28 rk_sm2_kep_genkey

```
TEE_Result rk_sm2_kep_genkey(rk_sm2_kep_parms *kep_parms, uint8_t *share_key,
                             uint32_t share_key_len, uint8_t *conf_out);
```

Description

ECDH algorithm based on SM2. OP-TEE V1 does not support this interface.

Parameters

- kep_parms: SM2 key infomation, contains the private key of A and the public key of B
- share_key: output symmetric key
- share_key_len: the length of share_key
- conf_out: information for validation

15.3.1.29 rk_mac_crypto

```
TEE_Result rk_mac_crypto(uint8_t *in, uint8_t *out, uint32_t in_len,
                         uint32_t *out_len, uint8_t *key, uint32_t key_len,
                         uint8_t *iv, uint32_t algo);
```

Description

MAC calculation. You can use the `rk_mac_begin/update/finish` interface for multiple calculations.

Parameters

- in: input data
- in_len: the length of input
- out: output data
- out_len: the length of output
- key: MAC key
- key_len: the length of key
- iv: initialization vector
- algo: MAC algorithm type, support the following(OP-TEE V1 dose not support the SM algorithm), `TEE_ALG_HMAC_MD5, TEE_ALG_HMAC_SHA1, TEE_ALG_HMAC_SHA256, TEE_ALG_AES_CMAC, TEE_ALG_HMAC_SM3`

15.3.1.30 rk_mac_begin

```
TEE_Result rk_mac_begin(crypto_ctx_t *ctx, uint8_t *key, uint32_t key_len,
                        uint8_t *iv, uint32_t algo);
```

Description

Initialization operation for MAC multiple calculation.

Parameters

- ctx: crypto context
- key: MAC key
- key_len: the length of key
- iv: initialization vector
- algo: MA Calgorithm type, support the following(OP-TEE V1 dose not support the SM algorithm), `TEE_ALG_HMAC_MD5, TEE_ALG_HMAC_SHA1, TEE_ALG_HMAC_SHA256, TEE_ALG_AES_CMAC, TEE_ALG_HMAC_SM3`

15.3.1.31 rk_mac_update

```
TEE_Result rk_mac_update(crypto_ctx_t *ctx, uint8_t *in, uint32_t in_len);
```

Description

Input data for MAC multiple calculation.

Parameters

- ctx: crypto context
- in: input data
- in_len: the length of input

15.3.1.32 rk_mac_finish

```
TEE_Result rk_mac_finish(crypto_ctx_t *ctx, uint8_t *in, uint8_t *mac,
                         uint32_t in_len, uint32_t *mac_len, rk_mac_mode_t
mode);
```

Description

Input the last part of data and calculate the MAC or Verify the MAC.

Parameters

- ctx: crypto context
- in: the last part of input data
- in_len: the length of in
- mac: `mode=RK_MAC_SIGN` - output calculate MAC value; `mode=RK_MAC_VERIFY` - input MAC value that is verified
- mac_len: the length of mac
- mode: see `mac`

15.3.1.33 rk_hkdf_genkey

```
TEE_Result rk_hkdf_genkey(uint8_t *ikm, uint32_t ikm_len,
                          uint8_t *salt, uint32_t salt_len,
                          uint32_t *info, uint32_t info_len,
                          uint32_t algo, uint32_t okm_len, uint8_t *okm);
```

Description

HKDF key derivation.

Parameters

- ikm: input password
- ikm_len: the length of ikm
- salt: input salt
- salt_len: the length of salt
- info: input info
- info_len: the length of info
- algo: algorithm, supports `TEE_ALG_HKDF_MD5_DERIVE_KEY, TEE_ALG_HKDF_SHA1_DERIVE_KEY, TEE_ALG_HKDF_SHA224_DERIVE_KEY, TEE_ALG_HKDF_SHA256_DERIVE_KEY, TEE_ALG_HKDF_SHA384_DERIVE_KEY, TEE_ALG_HKDF_SHA512_DERIVE_KEY`
- okm_len: the length of okm
- okm: output key

15.3.1.34 rk_pkcs5_pbkdf2_hmac

```
TEE_Result rk_pkcs5_pbkdf2_hmac(uint8_t *password, uint32_t password_len,
                                uint8_t *salt, uint32_t salt_len,
                                uint32_t iterations, uint32_t algo,
                                uint32_t key_len, uint8_t *out_key);
```

Description

Key derivation by specifying the salt, iteration count and the password.

Parameters

- password: input password
- password_len: the length of password
- salt: input salt
- salt_len: the length of salt
- iterations: input iteration count
- algo: algorithm, supports `TEE_ALG_PBKDF2_HMAC_SHA1_DERIVE_KEY`
- key_len: the length of key
- out_key: output key

15.3.2 HW Crypto API

15.3.2.1 rk_user_ta_cipher

```
TEE_Result rk_user_ta_cipher(rk_cipher_config *config, uint8_t *src, uint32_t
len)
```

Description

User TA use hardware Crypto for encryption and decryption.

Parameters

- config: Algorithm parameters, used to configure algorithm type, algorithm mode, key, etc
- src: Input and output data
- len: Data length

Source code

The reference code is located in the rk_tee_user project.

15.3.2.2 rk_keylad_hmac

```
TEE_Result rk_keylad_hmac(uint32_t algo, enum RK_OEM_OTP_KEYID otp_keyid,
                          uint32_t key_len, uint8_t *msg, uint32_t msg_len,
                          uint8_t *mac, uint32_t *mac_len)
```

Description

User TA uses the specified key in OTP and calls the hardware Crypto for HMAC calculation.

Please reference to OTP API to burn the key before calling this interface.

Only supported by some platforms, if the interface is not supported, `TEE_ERROR_NOT_SUPPORTED` is returned.

Parameters

- algo: Algorithm type
- otp_keyid: Key index in OTP
- key_len: Key length
- msg: Input message
- msg_len: Length of input message
- mac: Output data
- mac_len: Length of output data

Source code

The reference code is located in the rk_tee_user project.

15.3.2.3 rk_keylad_cipher

```
TEE_Result rk_keylad_cipher(enum RK_OEM_OTP_KEYID otp_keyid,
                            rk_cipher_config *config,
                            uint8_t *src, uint32_t len);
```

Description

User TA uses the specified key in OTP and calls the hardware Crypto for encryption and decryption.

Please reference to OTP API to burn the key before calling this interface.

Only supported by some platforms, if the interface is not supported, `TEE_ERROR_NOT_SUPPORTED` is returned.

Parameters

- otp_keyid: Key index in OTP
- config: Algorithm parameters, used to configure algorithm type, algorithm mode, key length, etc
- src: Input and output data
- len: Data length

Source code

The reference code is located in the rk_tee_user project.

15.3.3 TRNG API

15.3.3.1 rk_get_trng

```
TEE_Result rk_get_trng(uint8_t *buffer, uint32_t size);
```

Description

User TA get the hardware random number.
Only supported by some platforms, if the interface is not supported, `TEE_ERROR_NOT_SUPPORTED` is returned.

Parameters

- buffer: output random number
- size: the length of buffer

Source code

The reference code is located in the rk_tee_user project.

15.3.4 Derive Key API

15.3.4.1 rk_derive_ta_unique_key

```
TEE_Result rk_derive_ta_unique_key(uint8_t *extra, uint16_t extra_size, uint8_t
*key, uint16_t key_size)
```

Description

User TA obtain the key derived from the hardware unique key.

During the production of each chip, a hardware unique key is burned, and the key derived from this hardware unique key is unique.

Parameters

- extra: Input data for derive different keys
- extra_size: Input data length
- key: Derived key
- key_size: Key length

Source code

The reference code is located in the rk_tee_user project.

15.3.5 OTP API

15.3.5.1 rk_otp_size

```
TEE_Result rk_otp_size(uint32_t *otp_size);
```

Description

User TA gets the total size of the Protected OEM Zone in secure OTP.

Parameters

- otp_size: return OTP size

Source code

The reference code is located in the rk_tee_user project.

Please refer to the "Protected OEM Zone" section in 《Rockchip_Developer_Guide_OTP_EN.pdf》for details.

15.3.5.2 rk_otp_read

```
TEE_Result rk_otp_read(uint32_t offset, uint8_t *data, uint32_t len);
```

Description

User TA read data from Protected OEM Zone in secure OTP.

Parameters

- offset: the position offset of the OTP region to be read
- data: output data
- len: the length of data

Source code

The reference code is located in the rk_tee_user project.

Please refer to the "Protected OEM Zone" section in 《Rockchip_Developer_Guide_OTP_EN.pdf》for details.

15.3.5.3 rk_otp_write

```
TEE_Result rk_otp_write(uint32_t offset, uint8_t *data, uint32_t len);
```

Description

User TA write data to Protected OEM Zone in secure OTP.

Parameters

- offset: the position offset of the OTP region to be write
- data: input data
- len: the length of data

Source code

The reference code is located in the rk_tee_user project.

Please refer to the "Protected OEM Zone" section in 《Rockchip_Developer_Guide_OTP_EN.pdf》for details.

15.3.5.4 rk_write_oem_otp_key

```
TEE_Result rk_write_oem_otp_key(enum RK_OEM_OTP_KEYID key_id,
                                uint8_t *key, uint32_t key_len)
```

Description

User TA burns the key to OTP.

Parameters

- key_id: Key index
- key: Key to be written into OTP
- key_len: Length of key

Source code

The reference code is located in the rk_tee_user project.

Please refer to the "OEM Cipher Key" section in 《Rockchip_Developer_Guide_OTP_EN.pdf》for details.

15.3.5.5 rk_is_oem_otp_key_written

```
TEE_Result rk_is_oem_otp_key_written(enum RK_OEM_OTP_KEYID key_id, bool
*is_written)
```

Description

User TA checks if the key has been burned.

When the key is locked, this interface will return TEE_ERROR_ACCESS_DENIED error code.

Parameters

- key_id: Key index
- is_written: 0 not burned, 1 burned

Source code

The reference code is located in the rk_tee_user project.

Please refer to the "OEM Cipher Key" section in 《Rockchip_Developer_Guide_OTP_EN.pdf》for details.

15.3.5.6 rk_oem_otp_key_set_read_lock

```
TEE_Result rk_oem_otp_key_set_read_lock(enum RK_OEM_OTP_KEYID key_id)
```

Description

User TA locks the key. Once the key is locked, the CPU will not be able to access it, meaning that the software has no right to read or write the key and can only read and use it through hardware Crypto.
Only some platforms support lock key.

Parameters

- key_id: Key index

Source code

The reference code is located in the rk_tee_user project.

Please refer to the "OEM Cipher Key" section in 《Rockchip_Developer_Guide_OTP_EN.pdf》for details.

16. PTA description

16.1 Overview

PTA is an application embedded within TEE OS, also known as internal TA. PTA provides APIs to developers for two purposes:

- Implement features not available in TEE Internal API

- For developers to refer to calling methods or directly using APIs

16.2 PTA function

16.2.1 Secure Storage

This function is used to store important data, which is encrypted by TEE OS and stored in security partitions, rpmb partitions, and Android/Linux file systems.
By default, User TA calls TEE Internal API for secure storage, but U-Boot also needs to store critical data. Therefore, PTA has opened a secure storage interface for it, and the storage area can be selected through parameters within the interface.

16.2.2 OTP R&W

OTP is a one-time storage device that cannot be changed after data is written.

The TEE Internal API does not have OTP interfaces, so the PTA implements OTP read and write functions and provides interfaces to the outside world.

The PTA OTP interface can be used to program the following data:

OTP Data	Describe
Secure Boot Public Hash	Used to verify the legality of the public key during secure boot
AVB Attribute Hash	Used for verify the legitimacy of attribute certificates
OEM Cipher Key	Encryption and decryption keys used in hardware Crypto
Non-Protected OEM Zone	Used for storing non-sensitive data that can be accessed in a non-secure world
Protected OEM Zone	Used for storing OEM sensitive data, only for secure world access
TA Encrypt Key	When TEE OS loads encrypted TA, Use it to decrypts plaintext TA
OEM Encrypt Data	Used for anti copy board
OEM HUK	OEM hardware unique key, please refer to "Solution of optional strong or weak security levels" chapter

16.2.3 Hardware Crypto

The TEE Internal API provides software encryption and decryption functions by default, Hardware Crypto encryption and decryption functions are implemented through PTA and provide interfaces to the outside world.

The PTA Crypto interface supports DES, TDES, AES, SM4 symmetric encryption and decryption algorithms, and supports the use of specified keys in OTP.

The PTA Crypto interface supports HMAC algorithm and allows the use of keys specified in OTP.

16.2.4 Hardware random number

The TEE Internal API does not have a true random number interface, so the PTA implements the function of obtaining true random numbers and provides an interface to the outside world.

The PTA TRNG interface supports obtaining true random numbers of any length, which are generated by hardware and meet the requirements of true random numbers.

16.2.5 Hardware unique key derivation

The TEE Internal API does not have a hardware unique key derivation interface, so this function is implemented in PTA and an interface is provided to the outside world.

HUK is injected during the production of each chip, HUK is a random number generated by a true random number device, ensuring that the HUK of each chip is different,The key derived from HUK has uniqueness.

16.3 Call PTA method

The source code of U-Boot calling interface refers to u-boot/lib/optee_clientApi or u-boot/lib/optee, The interface description refers to the `Optee Client` chapter in the `Rockchip_Developer_Guide_UBoot_Nextdev_EN`.

The source code for UserSpace calling the interface refers to librkcrypto, The interface description refers to `Rockchip_Developer_Guide_Crypto_HWRNG_EN.pdf`.

The source code for User TA calling the interface refers to rk_tee_user, The interface description refers to `TA API description` section of this document.

17. Reference

ARM TrustZone:

https://developer.arm.com/ip-products/security-ip/trustzone

GlobalPlatform:

https://globalplatform.org/

This website can download CA development API reference documents: `TEE Client API Specification`

TA development API reference document: `TEE Internal Core API Specification`

And other architecture reference documents.