

§4 Functions

ENGG1111

Computer Programming and Applications

Dirk Schnieders

Outline

- Top-down design approach
- Function
- Local and global variables
- Scope of variables

Top-down design approach

Top-Down Design Approach

- A good way to design a program is to break down the task to be accomplished into a few sub-tasks
- Each sub-task might be further decomposed into smaller sub-tasks, and this process is repeated until all sub-tasks are small enough that their implementations become manageable
- This approach is called top-down design (aka divide and conquer)

Example - BMI




- Write a program that reads in the weight (in kg) and height (in meter) of a user, and outputs the Body Mass Index (BMI) category
 - $BMI = \text{weight} / \text{height}^2$

BMI	Category
<18.5	Underweight
[18.5, 22.9]	Normal
>22.9	Overweight

Example - BMI



- We tackle the problem by dividing our program into three sub-tasks
- We will treat each part as a smaller problem and tackle (conquer) the smaller problems one by one






Calculate BMI

Output BMI Category

Example - BMI



Function

Functions

- Preserving the top-down design structure in a program will make it easier to understand, write and change the program
- In C++ sub-tasks can be implemented as functions
 - A function is a group of statements that is executed when it is called from some point in program
- A program is composed of a collection of functions
- When a program is put into execution, it always starts at the main function, which may in turn call other functions

Function Definition



- Describes how a function computes the value it returns
- Consists of a function header followed by a function body
 - The function header specifies
 - the type of the return value
 - the function name (identifier), and
 - the list of parameters (with types and identifiers)
 - The function body consists of variable statements enclosed within a pair of braces { }

header → `type_ret func_name(type_1 par_1, type_2 par_2, ...) {`
body → `// statements ...`
`}`

type of the
return value



type of first
parameter



name of
first parameter



```
type_ret func_name(type_1 par_1, type_2 par_2, ...) {  
    // statements ...  
}
```

return statement

- The value returned by the function is determined when the function executes a return statement
- A return statement consist of the keyword return followed by an expression
- When a return statement is executed the function call ends
- Note that a function may contain more than one return statement

functions02.cpp

```
1  #include <iostream>
2  using namespace std;
3  double celsiusToFahrenheit(double celsius) {
4      return 9.0/5*celsius+32;
5  }
6  int main() {
7  }
8
```



return statement

- Note that the main function returns the value 0 if a return statement is missing

functions03.cpp

```
1  #include <iostream>
2  using namespace std;
3  int main() {
4      cout << "Hello World!" << endl;
5      return 0;
6  }
7
```



Function Call

- A function call (i.e., the process of calling a function) is made using the function name with the necessary parameters
- A function call is itself an expression, and can be put in any places where an expression is expected

functions04.cpp

```
1  #include <iostream>
2  using namespace std;
3  double celsiusToFahrenheit(double celsius) {
4      return 9.0/5*celsius+32;
5  }
6  int main() {
7      cout << celsiusToFahrenheit(28.0) << endl;
8  }
```

```
82.4
Press any key to continue...
```

Parameters and Arguments

- Parameters are variables that are part of the function definition
- The expressions used to pass values to a function during a function call are referred to as arguments
- When a function is called the computer substitutes the first argument with the first parameter, the second argument with the second parameter, and so forth


functions05.cpp

```
1  #include <iostream>
2  using namespace std;
3  int test(int a, int b, int c) {
4      cout << a <<" " << b <<" " << c << endl;
5      return a+b+c;
6  }
7  int main() {
8      cout << test(1, 3, 2) << endl;
9  }
```



Task

- What is the output of the following program?



```
1  #include <iostream>
2  using namespace std;
3  char test(int a) {
4      if (a<10)
5          return 'A';
6      else
7          return 'B';
8  }
9  int main() {
10     cout << test(5) << endl;
11 }
```

Arguments

- The arguments used in a function call can be constants, variables, expressions, or even function calls

functions06.cpp

```
1  #include <iostream>
2  using namespace std;
3  int test(int a, int b, int c) {
4      cout << a << " " << b << " " << c << endl;
5      return a+b+c;
6  }
7  int main() {
8      cout << test(test(1, 1, 1), 3-1, 2) << endl;
9  }
```



void Functions

- In some situations, a function returns no value
- In this case, we use the void type specifier
- A function with no return value is called a void function
- The return statement in a void function does not specify any return value
 - It is used to return the control to the calling function
- If a return statement is missing in a void function, the control will be returned to the calling function after the execution of the last statement in the function

functions08.cpp

```
1  #include <iostream>
2  using namespace std;
3  void test() {
4      cout << "test" << endl;
5  }
6  int main() {
7      test();
8  }
9
```

functions08.cpp 9:1



functions08

```
test
Press any key to continue...
```

functions09.cpp

```
1  #include <iostream>
2  using namespace std;
3  void test() {
4      cout << "test" << endl;
5      return;
6      cout << "test" << endl;
7  }
8  int main() {
9      test();
10 }
```


functions09.cpp 5:10




functions09

```
test
Press any key to continue...
```

calculateBMI()



outputCategory()



functions10.cpp

```
1  #include <iostream>
2  using namespace std;
3  double calculateBMI(double height, double weight) {
4      return weight / (height*height);
5  }
6  void outputCategory(double bmi) {
7      if (bmi<18.5)
8          cout << "Underweight" << endl;
9      if (bmi >= 18.5 && bmi <= 22.9)
10         cout << "Normal" << endl;
11     if (bmi > 22.9)
12         cout << "Overweight" << endl;
13 }
14 int main() {
15     double height, weight;
16     cin >> height >> weight;
17     double bmi = calculateBMI(height, weight);
18     outputCategory(bmi);
19 }
```

Function Definition

- A function must be defined before the function call is made

functions11.cpp

```
1 #include <iostream>
2 using namespace std;
3 void test() {
4
5 }
6 int main() {
7     test();
8 }
9
```

gcc-make-run: Running Command...

Close All

```
"g++" -pedantic-errors -std=c++11 "functions11.cpp" -o
"functions11"
```

✓ gcc-make-run: Build Success

functions12.cpp

```
1 #include <iostream>
2 using namespace std;
3 int main() {
4     test();
5 }
6 void test() {
7
8 }
9
```

gcc-make-run: Running Command... [Close All](#)

```
"g++" -pedantic-errors -std=c++11 "functions12.cpp" -o
"functions12"
```

gcc-make-run: Compile Error

```
functions12.cpp: In function 'int main()':
functions12.cpp:4:3: error: 'test' was not declared in
this scope
    test();
    ^~~~
functions12.cpp:4:3: note: suggested alternative: 'tzset'
    test();
    ^~~~
    tzset
```



Function Definition

- A function must be defined before the function call is made
 - Solution 1
 - Place the function definition before the function call in the source file
 - Solution 2
 - The function definition can be placed anywhere in the source file by including just the function declaration before the function call

functions13.cpp

```
1 #include <iostream>
2 using namespace std;
3 void test();
4 int main() {
5     test();
6 }
7 void test() {
8
9 }
10
```

gcc-make-run: Running Command...

Close All

"g++" -pedantic-errors -std=c++11 "functions13.cpp" -o
"functions13"

✓ gcc-make-run: Build Success



Local and Global Variables

Local Variables

- Variables declared within a function, including parameters, are local to that particular function
 - No other function can have access to them
- Local variables in a function come into existence only when the function is called, and disappear when the function is exited
- Local variables declared within the same function must have unique identifiers, whereas local variables of different functions may use the same identifier

functions14.cpp

```
1  #include <iostream>
2  using namespace std;
3  void test() {
4      int a = 7;
5      cout << a << endl;
6  }
7  int main() {
8      int a = 77;
9      test();
10     cout << a << endl;
11 }
```

functions14.cpp 11:2

functions14

```
7
77
Press any key to continue...
```

Global Variables

- Variables may also be declared outside all functions
 - Such variables are called global variables
 - They can be accessed by all functions
- Global variables remain in existence permanently
 - Retain their values even after the functions that set their values have returned
- Could be used instead of arguments to communicate data between functions
- **You must avoid using global variables**
 - Since the values of global variables can be changed by several functions they are very hard to trace

functions15.cpp

```
1  #include <iostream>
2  using namespace std;
3  int g = 1;
4  void doSomething() {
5      g = 2;
6  }
7  int main() {
8      g = 1;
9      doSomething();
10     // Programmer expects g to be 1
11     // doSomething() changed it to 2
12     if (g == 1) cout << "No threats detected" << endl;
13     else cout << "Launch nuclear missiles" << endl;
14 }
```

functions15.cpp

Launch nuclear missiles
Press any key to continue...

functions15

C++ 0 files

functions16.cpp

```
1  #include <iostream>
2  using namespace std;
3  int g = 1;
4  void doSomething() {
5      int g = 2;
6  }
7  int main() {
8      g = 1;
9      doSomething();
10     // Programmer expects g to be 1
11     // doSomething() changed it to 2
12     if (g == 1) cout << "No threats detected" << endl;
13     else cout << "Launch nuclear missiles" << endl;
14 }
```



Scope of Variables

Scope of Variables

- The scope of a variable is the portion of a program in which the variable can be used
 - A variable cannot be used beyond its scope
- The scope of a local variable starts from its declaration up to the end of the block
 - A block is delimited by a pair of braces { }
 - Variables declared in outer blocks can be referred to in an inner block
- Variables can be declared with the same identifier as long as they have different scopes
 - Variables in an inner block will hide any identically named variables in outer blocks

functions17.cpp

```
1  #include <iostream>
2  using namespace std;
3  int a;
4  void test() {
5      {
6          int b;
7      }
8      int c;
9  }
10 int main() {
11     int d;
12     {
13         int e;
14     }
15 }
```

functions18.cpp

```
1  #include <iostream>
2  using namespace std;
3  int main() {
4      int i = 0;
5      cout << "Outer block: i = " << i << endl;
6      {
7          int i = 100;
8          cout << "Inner block: i = " << i << endl;
9      }
10     cout << "Outer block: i = " << i << endl;
11 }
```

Pass by Value

- When a function call takes place, the values of the arguments are copied to the parameters of the function
- This mechanism of parameter-passing is known as pass by value

Task

- Write a function that takes two integers as arguments and swaps them
 - The function should be named swap
- Example
 - The following program, after completion, should output 21

```
1  #include <iostream>
2  using namespace std;
3  void swap(int x, int y) {
4      //your code here!
5  }
6  int main() {
7      int x = 1, y = 2;
8      swap(x,y);
9      cout << x << y << endl;
10 }
```

functions20.cpp

```
1  #include <iostream>
2  using namespace std;
3  void swap(int x, int y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10     swap(x,y);
11     cout << x << y << endl;
12 }
```

functions20.cpp 5:9



functions20

12

Press any key to continue...█



Pass by Value - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int x, int y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9  →   int x = 1, y = 2;
10     swap(x,y);
11     cout << x << y << endl;
12 }
```


Pass by Value - Analysis


```
1  #include <iostream>
2  using namespace std;
3  void swap(int x, int y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10 → swap(x, y);
11      cout << x << y << endl;
12 }
```

main()

x	y
1	2

Pass by Value - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int x, int y) {
4  →   int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10 →   swap(x, y);
11     cout << x << y << endl;
12 }
```



Pass by Value - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int x, int y) {
4      int tmp = x;
5  →  x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10 → swap(x, y);
11      cout << x << y << endl;
12  }
```

swap()

x	y	tmp
1	2	1

main()

x	y
1	2

Pass by Value - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int x, int y) {
4      int tmp = x;
5      x = y;
6  → y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10 → swap(x, y);
11      cout << x << y << endl;
12  }
```

swap()

x	y	tmp
2	2	1

main()

x	y
1	2

Pass by Value - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int x, int y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  → }
8  int main() {
9      int x = 1, y = 2;
10 → swap(x, y);
11      cout << x << y << endl;
12 }
```

swap()

x	y	tmp
2	1	1

main()

x	y
1	2

Pass by Value - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int x, int y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10 → swap(x, y);
11      cout << x << y << endl;
12 }
```

main()

x	y
1	2

Pass by Value - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int x, int y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10     swap(x,y);
11     cout << x << y << endl;
12 }
```

main()

x	y
1	2

Pass by Reference

- In order to allow a function to modify the variables in the calling function, another parameter-passing mechanism known as pass by reference should be used
- In pass by reference the function parameters will refer to the same variable

functions21.cpp

```
1  #include <iostream>
2  using namespace std;
3  void swap(int &x, int &y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10     swap(x,y);
11     cout << x << y << endl;
12 }
13
```

functions21.cpp 4:15

X

functions21

21

Press any key to continue...



Pass by Reference - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int &x, int &y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9  → int x = 1, y = 2;
10     swap(x,y);
11     cout << x << y << endl;
12 }
```

Pass by Reference - Analysis


```
1  #include <iostream>
2  using namespace std;
3  void swap(int &x, int &y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10 → swap(x,y);
11      cout << x << y << endl;
12 }
```

main()

x	y
1	2

Pass by Reference - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int &x, int &y) {
4  → int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10 → swap(x,y);
11      cout << x << y << endl;
12 }
```



Pass by Reference - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int &x, int &y) {
4      int tmp = x;
5  → x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10 → swap(x,y);
11      cout << x << y << endl;
12 }
```

swap()

x	y	tmp
1	2	1

main()

x	y
1	2

Pass by Reference - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int &x, int &y) {
4      int tmp = x;
5      x = y;
6  → y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10 → swap(x,y);
11      cout << x << y << endl;
12 }
```

swap()

x	y	tmp
2	2	1

main()

x	y
2	2

Pass by Reference - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int &x, int &y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  → }
8  int main() {
9      int x = 1, y = 2;
10 → swap(x,y);
11      cout << x << y << endl;
12 }
```

swap()

x	y	tmp
2	1	1

main()

x	y
2	1

Pass by Reference - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int &x, int &y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10 → swap(x,y);
11      cout << x << y << endl;
12 }
```

main()

x	y
2	1

Pass by Reference - Analysis

```
1  #include <iostream>
2  using namespace std;
3  void swap(int &x, int &y) {
4      int tmp = x;
5      x = y;
6      y = tmp;
7  }
8  int main() {
9      int x = 1, y = 2;
10     swap(x,y);
11     cout << x << y << endl;
12 }
```

main()

x	y
2	1

functions22.cpp

```
1  #include <iostream>
2  using namespace std;
3  void adjustSalary(double s) {
4      s *= 1.05;
5  }
6  int main() {
7      double salary = 20000;
8      cout << "original: " << salary << endl;
9      adjustSalary(salary);
10     cout << "new: " << salary << endl;
11 }
12
```



functions22.cpp

```
1  #include <iostream>
2  using namespace std;
3  void adjustSalary(double s) {
4      s *= 1.0;
5  }
6  int main()
7  {
8      double s;
9      cout << "original: 20000\n";
10     adjustSalary(s);
11     cout << "new: 20000\n";
12 }
```

functions22

```
original: 20000
new: 20000
Press any key to continue...
```

functions23.cpp

```
1  #include <iostream>
2  using namespace std;
3  void adjustSalary(double s) {
4      s *= 1.05;
5  }
6  int main() {
7      double salary = 20000;
8      cout << "original: " << salary << endl;
9      adjustSalary(&salary);
10     cout << "new: " << salary << endl;
11 }
12
```

Proposed Fix 1



functions23.cpp

```
1  #include <iostream>
2  using namespace std;
3  void adjustSalary(double s) {
4      s *= 1.05;
5  }
6  int main() {
7      double salary = 20000;
8      cout << "original: " << salary << endl;
9      adjustSalary(&salary);
10     cout << "new: " << salary << endl;
11 }
12
```

gcc-make-run: Running Command...

Close All

```
"g++" -pedantic-errors -std=c++11 "functions23.cpp" -o
"functions23"
```

gcc-make-run: Compile Error

```
functions23.cpp: In function 'int main()':
functions23.cpp:9:23: error: cannot convert 'double*' to
'double' for argument '1' to 'void adjustSalary(double)'
    adjustSalary(&salary);
                  ^
```

functions24.cpp

```
1  #include <iostream>
2  using namespace std;
3  void adjustSalary(double &s) {
4      &s *= 1.05;
5  }
6  int main() {
7      double salary = 20000;
8      cout << "original: " << salary << endl;
9      adjustSalary(salary);
10     cout << "new: " << salary << endl;
11 }
12
```

Proposed Fix 2

functions24.cpp* 4:4

LF UTF-8 C++ 0 files

functions24.cpp

```
1  #include <iostream>
2  using namespace std;
3  void adjustSalary(double &s) {
4      &s *= 1.05;
5  }
6  int main() {
7      double salary = 20000;
8      cout << "original: " << salary << endl;
9      adjustSalary(salary);
10     cout << "new: " << salary << endl;
11 }
12
```

gcc-make-run: Running Command...

Close All

```
"g++" -pedantic-errors -std=c++11 "functions24.cpp" -o
"functions24"
```

gcc-make-run: Compile Error

```
functions24.cpp: In function 'void
adjustSalary(double&)':
functions24.cpp:4:6: error: invalid operands of types
'double*' and 'double' to binary 'operator*'
    &s *= 1.05;
    ~^~~~~~
functions24.cpp:4:9: error:   in evaluation of
'operator*=(double*, double)'
    &s *= 1.05;
    ~^~
```


functions24.cpp

```
1  #include <iostream>
2  using namespace std;
3  void adjustSalary(double &s) {
4      s *= 1.05;
5  }
6  int main() {
7      double salary = 20000;
8      cout << "original: " << salary << endl;
9      adjustSalary(salary);
10     cout << "new: " << salary << endl;
11 }
12
```

gcc-make-run: Running Command...

Close All

"g++" -pedantic-errors -std=c++11 "functions24.cpp" -o "functions24"

✓ gcc-make-run: Build Success

functions24

```
original: 20000
new: 21000
Press any key to continue...
```



Task

- If you understand the concepts of pass by value and pass by reference, you should be able to work out the output of this program

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     outputXY(x,y);
12 }
13 int main() {
14     int x = 0, y = 4;
15     outputXY(x, y);
16     swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }
```

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     outputXY(x,y);
12 }
13 int main() {
14     → int x = 0, y = 4;
15     outputXY(x, y);
16     swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }
```

```

1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     outputXY(x,y);
12 }
13 int main() {
14     int x = 0, y = 4;
15     → outputXY(x, y);
16     swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }

```

main()

x	y
0	4

04

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     outputXY(x,y);
12 }
13 int main() {
14     int x = 0, y = 4;
15     outputXY(x, y);
16     → swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }
```

main()

x	y
0	4

04

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      → outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     outputXY(x,y);
12 }
13 int main() {
14     int x = 0, y = 4;
15     outputXY(x, y);
16     → swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }
```

swap()

x	y
0	4

main()

x	y
0	4

04
40

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     outputXY(x,y);
12 }
13 int main() {
14     int x = 0, y = 4;
15     outputXY(x, y);
16     swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }
```

swap()

x	y
4	0

main()

x	y
0	4

04
40

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      → x = y;
10     y = tmp;
11     outputXY(x,y);
12 }
13 int main() {
14     int x = 0, y = 4;
15     outputXY(x, y);
16     → swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }
```

swap()

x	y	tmp
4	0	4

main()

x	y
0	4

04
40

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     outputXY(x,y);
12 }
13 int main() {
14     int x = 0, y = 4;
15     outputXY(x, y);
16     swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }
```

swap()

x	y	tmp
0	0	4

main()

x	y
0	4

04
40

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     → outputXY(x,y);
12 }
13 int main() {
14     int x = 0, y = 4;
15     outputXY(x, y);
16     → swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }
```

swap()

x	y	tmp
0	4	4

main()

x	y
4	4

04
40
04

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     outputXY(x,y);
12 → }
13 int main() {
14     int x = 0, y = 4;
15     outputXY(x, y);
16 → swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }
```

swap()

x	y	tmp
0	4	4

main()

x	y
4	4

04
40
04

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     outputXY(x,y);
12 }
13 int main() {
14     int x = 0, y = 4;
15     outputXY(x, y);
16     swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }
```

main()

x	y
4	4

04
40
04
44
44

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     outputXY(x,y);
12 }
13 int main() {
14     int x = 0, y = 4;
15     outputXY(x, y);
16     swap(y,x);
17     if (x<5) swap (x,y);
18     → outputXY(x,y);
19 }
```

main()	
x	y
4	4

04
40
04
44
44
44

```
1  #include <iostream>
2  using namespace std;
3  void outputXY(int x, int y) {
4      cout << x << y << endl;
5  }
6  void swap(int x, int &y) {
7      outputXY(x,y);
8      int tmp = x;
9      x = y;
10     y = tmp;
11     outputXY(x,y);
12 }
13 int main() {
14     int x = 0, y = 4;
15     outputXY(x, y);
16     swap(y,x);
17     if (x<5) swap (x,y);
18     outputXY(x,y);
19 }
```

main()

x	y
4	4

Task

- What is the output of this program?

```
1  #include <iostream>
2  using namespace std;
3  void figureMeOut(int &x, int y, int &z) {
4      cout << x << " " << y << " " << z << endl;
5      x = 1;
6      y = 2;
7      z = 3;
8      cout << x << " " << y << " " << z << endl;
9  }
10 int main() {
11     int a=10, b=20, c=30;
12     figureMeOut(a, b, c);
13     cout << a << " " << b << " " << c << endl;
14 }
```