

Lecture 11-2

Generics




```
List<T>
```

HashMap

- Generic classes
- Wrapper classes
- Final example

HashMap



put(key , value)

value = **get**(key)

HashMap

A commonly used Java class that implements the mapping algorithm.

HashMap: Example 1

```
/** Represents a mapping of keys of type K on values of type V. */
public class HashMap<K,V> {

    /** Constructs an empty map with default capacity = 16. */
    public HashMap()

    /** Associates the given value with the given key. */
    public void put(K key, V value)

    /** Returns the value to which the given key is mapped. */
    public V get(K key)

    /** Returns true if the given key is contained in this map. */
    public boolean containsKey(K key)

    /** Returns a set of all the keys contained in this map. */
    public Set<K> keySet()

    /** Returns a set of all the values contained in this map. */
    public Set<V> values()
}
```


API

HashMap<K,V>

A *generic class*, designed for mapping objects *of any type K* on objects *of any type V*

Part of the *Java class library*;

Belongs to a package named `java.util`



moo



woof

We'll use a `HashMap` for mapping animals on the sounds that they make.

The sound can be a `String`, e.g. the name of a sound file.

HashMap: Example 1

```
/** Represents a mapping of keys of type K on values of type V. */
public class HashMap<K,V> {

    /** Constructs an empty map with default capacity = 16. */
    public HashMap()

    /** Associates the given value with the given key. */
    public void put(K key, V value)

    /** Returns the value to which the given key is mapped. */
    public V get(K key)

    /** Returns true if the given key is contained in this map. */
    public boolean containsKey(K key)

    /** Returns a set of all the keys contained in this map. */
    public Set<K> keySet()

    /** Returns a set of all the values contained in this map. */
    public Set<V> values()

}
```

API

```
// Client code for managing <animal , sound> mappings
```

```
import java.util.HashMap;

class HashMapDemo1 {
    ...
}
```

Technical note


If a class wants to use a class that belongs to some other package, it must **import** that class;

HashMap<K,V>

A *generic class*, designed for mapping objects *of any type K* on objects *of any type V*

Part of the *Java class library*;

Belongs to a package named **java.util**



moo



woof

HashMap: Example 1

```
/** Represents a mapping of keys of type K on values of type V. */
public class HashMap<K,V> {
    /** Constructs an empty map with default capacity = 16. */
    public HashMap()
    /** Associates the given value with the given key. */
    public void put(K key, V value)
    /** Returns the value to which the given key is mapped. */
    public V get(K key)
    /** Returns true if the given key is contained in this map. */
    public boolean containsKey(K key)
    /** Returns a set of all the keys contained in this map. */
    public Set<K> keySet()
    /** Returns a set of all the values contained in this map. */
    public Set<V> values()
}
```

API

HashMap<K,V>

A *generic class*, designed for mapping objects *of any type K* on objects *of any type V*

Part of the *Java class library*;

Belongs to a package named `java.util`



moo



woof

// Client code example

```
import java.util.HashMap;
class HashMapDemo1 {
    ...
    // Constructs a map of <animal, sound> pairs
    HashMap animalSound =
        new HashMap(<String,String>);
}
```

Note:

The map is an instance (object) of `HashMap<K,V>`;

When we construct this object, we must specify `K` and `V`;

In this example, `K` and `V` are both `String` objects;

In general, they can be objects of *any type*.

HashMap: Example 1


```
/** Represents a mapping of keys of type K on values of type V. */
public class HashMap<K,V> {
    /** Constructs an empty map with default capacity = 16. */
    public HashMap()
    /** Associates the given value with the given key. */
    public void put(K key, V value)
    /** Returns the value to which the given key is mapped. */
    public V get(K key)
    /** Returns true if the given key is contained in this map. */
    public boolean containsKey(K key)
    /** Returns a set of all the keys contained in this map. */
    public Set<K> keySet()
    /** Returns a set of all the values contained in this map. */
    public Set<V> values()
}
```

API


```
// Client code example
import java.util.HashMap;
class HashMapDemo1 {
    ...
    // Constructs a map of <animal, sound> pairs
    HashMap animalSound =
        new HashMap(<String,String>);
    // Stores key-value entries
    animalSound.put("cow", "moo");
    animalSound.put("dog", "woof");
    animalSound.put("mouse", "squeek");
    animalSound.put("cat", "miao");
    ...
}
```



moo



woof



HashMap: Example 1

```
/** Represents a mapping of keys of type K on values of type V. */
public class HashMap<K,V> {

    /** Constructs an empty map with default capacity = 16. */
    public HashMap()

    /** Associates the given value with the given key. */
    public void put(K key, V value)

    /** Returns the value to which the given key is mapped. */
    public V get(K key)

    /** Returns true if the given key is contained in this map. */
    public boolean containsKey(K key)

    /** Returns a set of all the keys contained in this map. */
    public Set<K> keySet()

    /** Returns a set of all the values contained in this map. */
    public Set<V> values()

}
```

API

```
// Client code example
...

// Prints some animals, and their sounds.
System.out.println("Cow goes " +
                    animalSound.get("cow"));

System.out.println("Mouse goes " +
                    animalSound.get("mouse"));


...
```

output


Cow goes moo
Mouse goes squeak



moo



woof



HashMap: Example 1

```
/** Represents a mapping of keys of type K on values of type V. */
public class HashMap<K,V> {

    /** Constructs an empty map with default capacity = 16. */
    public HashMap()

    /** Associates the given value with the given key. */
    public void put(K key, V value)

    /** Returns the value to which the given key is mapped. */
    public V get(K key)

    /** Returns true if the given key is contained in this map. */
    public boolean containsKey(K key)

    /** Returns a set of all the keys contained in this map. */
    public Set<K> keySet()

    /** Returns a set of all the values contained in this map. */
    public Set<V> values()

}
```


API

Set<V>


A generic, iterable, set of objects of any type V

also part of `java.util`;

Similar to the Set class that we wrote in lecture 9-2.



moo



woof


// Client code example

...

```
// Iterates over all the animals (keys) in the map;
// For each animal, prints the animal and its sound.
for (String animal : animalSound.keySet()) {
    String sound = animalSound.get(animal);
    System.out.println(animal + " goes " + sound);
}
```

output

```
dog goes woof
cat goes miao
cow goes moo
mouse goes squeak
```



HashMap: Example 2

```
/** Represents a mapping of keys of type K on values of type V. */
public class HashMap<K,V> {

    /** Constructs an empty map with default capacity = 16. */
    public HashMap()

    /** Associates the given value with the given key. */
    public void put(K key, V value)

    /** Returns the value to which the given key is mapped. */
    public V get(K key)

    /** Returns true if the given key is contained in this map. */
    public boolean containsKey(K key)

    /** Returns a set of all the keys contained in this map. */
    public Set<K> keySet()

    /** Returns a set of all the values contained in this map. */
    public Set<V> values()

}
```

Client code: Timing fib(x) function computations

```
Timer timer = new Timer();
System.out.println("Fibonacci(50) = " + fib(50) +
    "; execution time: " + timer.elapsedTime() + " ms");

timer.reset();
System.out.println("Fibonacci(50) = " + fib(50) +
    "; execution time: " + timer.elapsedTime() + " ms");
```

```
import java.util.HashMap;

public class HashMapDemo2 {

    // A hashmap for memoizing results of the Fibonacci function
    static HashMap<Integer,Long> memoFib
        = new HashMap<>();

    // Computes the Fibonacci function
    public static long fib(int n) {
        if (n <= 1) return n; // Base case

        // If already computed, returns the stored value
        if (memoFib.containsKey(n)) {
            return memoFib.get(n);
        }

        // Computes and stores the result
        long result = fib(n - 1) + fib(n - 2);
        memoFib.put(n, result);
        return result;
    }

}
```

output

```
Fibonacci(50) = 12586269025; execution time: 0.255894 ms
Fibonacci(50) = 12586269025; execution time: 0.007202 ms
```

Lecture plan

- HashMap



Generic classes

- Wrapper classes
- Final example

Designing a generic class

Regular class

```
/* A box that contains an int value. */
public class Box {
    private int x; // contents of this box

    /* Puts x in this box */
    public void set(int x) {
        this.x = x;
    }

    /* Returns the contents of this box */
    public int get() {
        return x;
    }

    /* Textual representation of the contents of this box */
    public String toString() {
        return "[" + x + "]";
    }
}
```

the data of this class
are values of type int

Designing a generic class

Generic class

```
/* A generic box that contains an object of type T. */
public class Box<T> {
    private T x; // contents of this box

    /* Puts x in this box */
    public void set(T x) {
        this.x = x;
    }

    /* Returns the contents of this box */
    public T get() {
        return x;
    }

    /* Textual representation of the contents of this box */
    public String toString() {
        // whatever x is, have it describe itself
        return "[" + x.toString() + "]";
    }
}
```

the data of this class are
objects of *any type T*

Regular class

```
/* A box that contains an int value. */
public class Box {
    private int x; // contents of this box

    /* Puts x in this box */
    public void set(int x) {
        this.x = x;
    }

    /* Returns the contents of this box */
    public int get() {
        return x;
    }

    /* Textual representation of the contents of this box */
    public String toString() {
        return "[" + x + "]";
    }
}
```

the data of this class
are values of type `int`

Generalizing to a
generic class

- Generic classes are compiled like any other class;
- The symbol `T` is a *placeholder*;
- Commonly used placeholder symbols: `S`, `T`, `U`, `V`, `N`, `E`, ...

Using a generic class

Generic class

```
/* A generic box that contains an object of type T. */
public class Box<T> {
    private T x; // contents of this box

    /* Puts x in this box */
    public void set(T x) {
        this.x = x;
    }

    /* Returns the contents of this box */
    public T get() {
        return x;
    }

    /* Textual representation of the contents of this box */
    public String toString() {
        // whatever x is, have it describe itself
        return "[" + x.toString() + "]";
    }
}
```

the data of this class are
objects of *any type* T

Using a generic class

Generic class

```
/* A generic box that contains an object of type T. */
public class Box<T> {
    private T x; // contents of this box

    /* Puts x in this box */
    public void set(T x) {
        this.x = x;
    }

    /* Returns the contents of this box */
    public T get() {
        return x;
    }

    /* Textual representation of the contents of this box */
    public String toString() {
        // whatever x is, have it describe itself
        return "[" + x.toString() + "]";
    }
}
```

the data of this class are
objects of *any type T*

Client code demo (example 1)

```
// Creates some boxes, each containing a different thing
Box<String> b1 = new Box<String>();
b1.set("banana");

Box<Fraction> b2 = new Box<Fraction>();
b2.set(new Fraction(5,7));

Box<BankAccount> b3 = new Box<BankAccount>();
b3.set(new BankAccount("Maya"));
```

We created several `Box<T>` objects, each holding an object of a different data type.

Using a generic class

Generic class

```
/* A generic box that contains an object of type T. */
public class Box<T> {
    private T x; // contents of this box

    /* Puts x in this box */
    public void set(T x) {
        this.x = x;
    }

    /* Returns the contents of this box */
    public T get() {
        return x;
    }

    /* Textual representation of the contents of this box */
    public String toString() {
        // whatever x is, have it describe itself
        return "[" + x.toString() + "]";
    }
}
```

the data of this class are
objects of *any type T*

Client code demo (example 1)

```
// Creates some boxes, each containing a different thing
Box<String> b1 = new Box<String>();
b1.set("banana");

Box<Fraction> b2 = new Box<Fraction>();
b2.set(new Fraction(5,7));

Box<BankAccount> b3 = new Box<BankAccount>();
b3.set(new BankAccount("Maya"));

// Prints the contents of the boxes
System.out.println(b1);
System.out.println(b2);
System.out.println(b3);

// Declares another box and puts the first box in it
Box<Box<String>> boxInaBox =
    new Box<Box<String>>();
boxInaBox.set(b1);
System.out.println(boxInaBox);
```

output

```
[banana]
[5/7]
[1 Maya 0.0]
[[banana]]
```

We created several `Box<T>` objects, each holding an object of a different data type.

Using a generic class

Generic class

```
/* A generic box that contains an object of type T. */
public class Box<T> {
    private T x; // contents of this box

    /* Puts x in this box */
    public void set(T x) {
        this.x = x;
    }

    /* Returns the contents of this box */
    public T get() {
        return x;
    }

    /* Textual representation of the contents of this box */
    public String toString() {
        // whatever x is, have it describe itself
        return "[" + x.toString() + "]";
    }
}
```

The type parameters *must be objects*,
not primitive types

Therefore: This code does not compile:

```
// Trying to create boxes that hold an int and a double values
Box<int> b1 = new Box<int>();
b1.set(17);

Box<double> b2 = new Box<double>();
b2.set(3.14159);
```

Workaround: Use *wrapper classes*:

```
// Creates boxes that hold an Integer object and a Double object
Box<Integer> b1 = new Box<Integer>();
b1.set(Integer.valueOf(17));

Box<Double> b2 = new Box<Double>();
b1.set(Double.valueOf(3.14159));
```

```
// Simpler syntax convention (explained later)
Box<Integer> b1 = new Box<Integer>();
b1.set(17);

Box<Double> b2 = new Box<Double>();
b1.set(3.14159);
```

Wrapper classes

Java features eight *wrapper classes*:

<u>Primitive types</u>	<u>Wrapper classes</u>
int	Integer
long	Long
byte	Byte
short	Short
float	Float
double	Double
boolean	Boolean
char	Character

Wrapper classes ...

- Provide workarounds for having generic classes handle primitive values
- Provide some useful, type-specific, constants and services.

Wrapper classes: Working with primitive values

// Creating a “boxed” value:

```
Integer xObj = Integer.valueOf(19); // Or simply Integer xObj = 19; (see last example below)
System.out.println(xObj);           // Prints "19" (via the Integer class's toString method)
```

// Down-casting (retrieving the primitive value from the Integer object):

```
int x = xObj; // sometimes called “unboxing”
```

// Up-casting (assigning a primitive value to an Integer object):

```
xObj = 17; // sometimes called “autoboxing”; Shorthand of xObj = Integer.valueOf(17)
```

Explanation

In the Java class library, data structures (Set, Stack, HashMap, ...) are implemented as *generic classes*;

These classes are widely-used;

Therefore, there is an ongoing need to set Integer objects to int values, and vice versa (and the same is true for all wrapper classes and primitive data types);

Therefore, Java makes the *boxing* / *unboxing* casting operations easier for the programmer.

Wrapper classes: Useful constants and services

Java's wrapper classes also provide useful type-specific services and constants.

Client code example (using some static services of the `Integer` class):

```
// Parsing strings to integers:
```

```
int x = Integer.parseInt("43"); // Converts the string "43" to the int 43
```

```
System.out.println(x + 2);      // Prints 45
```

```
// Converting integer to binary:
```

```
String xBin = Integer.toBinaryString(x); // Computes the binary representation of x
```

```
System.out.println(xb);          // Prints 101011
```

```
// Supplying the Min and Max values of int:
```

```
System.out.println(Integer.MIN_VALUE); // Prints -2147483648
```

```
System.out.println(Integer.MAX_VALUE); // Prints 2147483647
```

Endnotes / Side comments

Q: How does the compiler know that a class is designed to represent objects?

A: If the class features at least one method that is not `static`, it is designed for creating and managing objects;

Another way to tell:

The class declares private variables (fields).

```
/* A box that contains an int value. */  
public class Box {  
    private int x; // field declaration  
    /* Puts x in this box */  
    public void set(int x) {  
        this.x = x;  
    }  
    /* Returns the contents of this box */  
    public int get() {  
        return x;  
    }  
    ...  
}
```

Endnotes / Side comments

This class is designed to represent objects;
But... it has no *constructors*!
How can the class create objects?

When you don't write a constructor,
the compiler adds a default constructor.

Example:

```
public class AnyClass {  
    private int x;  
    ...  
}
```

As if you wrote:

```
/* A box that contains an int value. */  
public class Box {  
    private int x; // field declaration  
    /* Puts x in this box */  
    public void set(int x) {  
        this.x = x;  
    }  
    /* Returns the contents of this box */  
    public int get() {  
        return x;  
    }  
    ...  
}
```

```
public class AnyClass {  
    private int x;  
    // default constructor  
    public AnyClass() {  
    }  
    ...  
}
```

The default constructor is designed
to do one thing only: Create an
object of the class type.

Lecture plan


- HashMap
- Generic classes
- Wrapper classes



Final example

Generic List

In lecture 10-1 we built `Node` and `List` classes for representing lists of *integers*:



Can we generalize these classes to represent lists of *any data type*?


```
/** Represents a node containing an int value */
public class Node {
    int data;
    Node next;

    /** Constructs a node with the given data.
     * The new node will point to the next node. */
    public Node(int data, Node next) {
        this.data = data;
        this.next = next;
    }

    /** Constructs a node with the given data.
     * The new node will point to null. */
    public Node(int data) {
        this(data, null);
    }

    /** Textual representation of this node. */
    public String toString() {
        return "" + data;
    }
}
```

Lecture 10-2



Generic List

Generic node

```
/** Represents a generic node in a generic linked list. */
public class Node<T> {
    T data;          // an object of type T
    Node<T> next;

    /** Constructs a node with the given data.
     * The new node will point to the next node. */
    public Node(T data, Node<T> next) {
        this.data = data;
        this.next = next;
    }

    /** Constructs a node with the given data.
     * The new node will point to null. */
    public Node(T data) {
        this(data, null);
    }

    /** Textual representation of this node. */
    public String toString() {
        return "" + data;
    }
}
```

Generalizing to
a generic class


```
/** Represents a node containing an int value */
public class Node {
    int data;
    Node next;

    /** Constructs a node with the given data.
     * The new node will point to the next node. */
    public Node(int data, Node next) {
        this.data = data;
        this.next = next;
    }

    /** Constructs a node with the given data.
     * The new node will point to null. */
    public Node(int data) {
        this(data, null);
    }

    /** Textual representation of this node. */
    public String toString() {
        return "" + data;
    }
}
```

Lecture 10-2



Generic List

```
/** A list of integers. */
public class List {

    private Node first; // Pointer to the first list element
    private int size;   // Number of elements

    /** Constructs an empty list. */
    public List() {
        first = null;
        size = 0;
    }

    ...

    /** Adds the given int value to the end of this list. */
    public void add(int data) { // code omitted }

    /** Returns a string representation of this list,
     * in the form of (element element , ..., element) */
    public String toString() {
        String str = "(";
        Node current = first;
        while (current != null) {
            str += current.data + " ";
            current = current.next;
        }
        return str.substring(0, str.length()-1) + ")";
    }
}
```

Lecture 10-2

Generic List

Generic list

```
/** A generic list of objects of any type. */
public class List<T> {

    private Node<T> first; // Pointer to the first list element
    private int size;      // Number of elements

    /** Constructs an empty list. */
    public List() {
        first = null;
        size = 0;
    }

    ...

    /** Adds the given data (an object) to the end of this list. */
    public void add(T data) { // code omitted }

    /** Returns a string representation of this list,
     * in the form of (element element , ..., element) */
    public String toString() {
        String str = "(";
        Node<T> current = first;
        while (current != null) {
            str += current.data + " ";
            current = current.next;
        }
        return str.substring(0, str.length()-1) + ")";
    }
}
```

Generalizing to
a generic class

```
/** A list of integers. */
public class List {

    private Node first; // Pointer to the first list element
    private int size;   // Number of elements

    /** Constructs an empty list. */
    public List() {
        first = null;
        size = 0;
    }

    ...

    /** Adds the given int value to the end of this list. */
    public void add(int data) { // code omitted }

    /** Returns a string representation of this list,
     * in the form of (element element , ..., element) */
    public String toString() {
        String str = "(";
        Node current = first;
        while (current != null) {
            str += current.data + " ";
            current = current.next;
        }
        return str.substring(0, str.length()-1) + ")";
    }
}
```

Lecture 10-2

Generic List

Generic list

```
/** A generic list of objects of any type. */
public class List<T> {

    private Node<T> first; // Pointer to the first list element
    private int size;      // Number of elements

    /** Constructs an empty list. */
    public List() {
        first = null;
        size = 0;
    }

    ...


    /** Adds the given data (an object) to the end of this list. */
    public void add(T data) { // code omitted }

    /** Returns a string representation of this list,
     * in the form of (element element , ..., element) */
    public String toString() {
        String str = "(";
        Node<T> current = first;
        while (current != null) {
            str += current.data + " ";
            current = current.next;
        }
        return str.substring(0, str.length()-1) + ")";
    }
}
```

Client code (example)

```
...
List<String> cities = new List<String>();
cities.add("Haifa");
cities.add("LA");
cities.add("Paris");
System.out.println(cities)    // [Haifa, LA, Paris]
```

cities



Generic List

Generic list

```
/** A generic list of objects of any type. */
public class List<T> {

    private Node<T> first; // Pointer to the first list element
    private int size;      // Number of elements

    /** Constructs an empty list. */
    public List() {
        first = null;
        size = 0;
    }

    ...


    /** Adds the given data (an object) to the end of this list. */
    public void add(T data) { // code omitted }

    /** Returns a string representation of this list,
     * in the form of (element element , ..., element) */
    public String toString() {
        String str = "(";
        Node<T> current = first;
        while (current != null) {
            str += current.data + " ";
            current = current.next;
        }
        return str.substring(0, str.length()-1) + ")";
    }
}
```


Client code (example)

```
...
List<String> cities = new List<String>();
cities.add("Haifa");
cities.add("LA");
cities.add("Paris");
System.out.println(cities)    // (Haifa, LA, Paris)
...
List<Fraction> fList = new List<Fraction>();
fList.add(new Fraction(7,8));
fList.add(new Fraction(1,2));
fList.add(new Fraction(5,9));
System.out.println(fList);    // (7/8, 1/2, 5/9)
```

cities



fList



Generic List

Generic list

```
/** A generic list of objects of any type. */
public class List<T> {

    private Node<T> first; // Pointer to the first list element
    private int size;      // Number of elements

    /** Constructs an empty list. */
    public List() {
        first = null;
        size = 0;
    }

    ...

    /** Adds the given data (an object) to the end of this list. */
    public void add(T data) { // code omitted }

    /** Returns a string representation of this list,
     * in the form of (element element , ..., element) */
    public String toString() {
        String str = "(";
        Node<T> current = first;
        while (current != null) {
            str += current.data + " ";
            current = current.next;
        }
        return str.substring(0, str.length()-1) + ")";
    }
}
```

Client code (example)

```
...
// a list of int values

List<Integer> intList = new List<Integer>();
intList.add(Integer.valueOf(5));
intList.add(3); // (uses autoboxing)
intList.add(9);
System.out.println(intList); // (5, 3, 9)
```

intList

