

Secret Sharing

What is Secret Sharing?

The goal of secret sharing is dividing a secret S into n pieces (or *shares*) so that no fewer than $k \leq n$ pieces are sufficient for reassembling S . This is called a (k, n) -threshold scheme.

Why is Secret Sharing?

As Shamir puts it, “Threshold schemes are ideally suited to applications in which a group of mutually suspicious individuals with conflicting interests must cooperate.”

Some uses include flexibly enforcing consensus while granting veto power and allowing for packets to be sent over a network securely and efficiently.

How is Secret Sharing?

Shamir’s Secret Sharing (1979)¹

Shamir’s approach is based on polynomial interpolation. Say we want to share a secret among n people so that no fewer than k of them can recover the secret. Choose a big prime p and say our secret is an element $S \in \mathbb{Z}/p\mathbb{Z}$. Choose random elements $a_1, \dots, a_{k-1} \in \mathbb{Z}/p\mathbb{Z}$ and set

$$p(x) = S + a_1x + \dots + a_{k-1}x^{k-1}.$$

Issue to person i the share $D_i = (i, p(i))$, $1 \leq i \leq n$. If m people come together with their shares, $(i_j, p(i_j))$, $1 \leq j \leq m$ then they know that

$$\begin{array}{ccccccccc} S & + & a_1 \cdot i_1 & + & a_2 \cdot (i_1)^2 & + & \dots & + & a_{k-1}(i_1)^{k-1} & = & p(i_1) \\ S & + & a_1 \cdot i_2 & + & a_2 \cdot (i_2)^2 & + & \dots & + & a_{k-1}(i_2)^{k-1} & = & p(i_2) \\ & & & & & & \vdots & & & & \\ S & + & a_1 \cdot i_m & + & a_2 \cdot (i_m)^2 & + & \dots & + & a_{k-1}(i_m)^{k-1} & = & p(i_m) \end{array}$$

This represents a system of m equations in the k unknowns, S, a_1, \dots, a_{k-1} . Elementary linear algebra tells us that this system has a unique solution if and only if $m \geq k$. That is, we need at least k shares in order to uniquely determine S .

Main Disadvantage of Shamir’s Scheme

Each share is just as large as the secret. n shares means n -fold blowup in storage.

Improvements by Rabin and Krawczyk

Rabin - Information Dispersal (1989)²

We can split a file F into n pieces so that any $k \leq n$ pieces are sufficient for reconstructing F , with the added feature that each piece has size roughly $|F|/k$. With n shares, each of size roughly

¹A. Shamir, “How to share a secret”. Commun. ACM 22(11), 612613 (1979)

²M. O. Rabin, “Efficient Dispersal of Information for Security, Load Balancing, and Fault Tolerance”. In: Journal of the ACM, vol. 36, iss. 2, 1989, pp. 335-348

$|F|/k$ we get a blowup of around $\frac{n}{k}$, but this can be chosen to be close to 1. *Secrecy isn't the objective.*

Say the file F is composed of bytes, $F = b_1, b_2, \dots, b_N$, where each b_i is an integer $0 \leq b_i \leq 255$. Let p be a prime bigger than 255, such as $p = 257$. Choose n vectors, $a_i = (a_{i1}, \dots, a_{im})$, $1 \leq i \leq n$, in $(\mathbb{Z}/p\mathbb{Z})^m$ so that any subset of m different vectors is linearly independent (how this can be done is a non-obvious but still elementary exercise in linear algebra). Break the file into blocks of length m ,

$$F = (b_1, \dots, b_m), (b_{m+1}, \dots, b_{2m}), \dots = f_1, f_2, \dots,$$

where $f_1 = (b_1, \dots, b_m)$ is the first block of F , and so on. We set the i -th share to be $S_i = (a_i, F_i)$, $1 \leq i \leq n$ where

$$F_i = c_{i1}, \dots, c_{iN/m},$$

and

$$c_{ik} = a_i \cdot f_k = a_{i1} \cdot b_{(k-1)m+1} + \dots + a_{im} \cdot b_{km}.$$

Each share has length $|a_i| + |F_i| = m + \frac{|F|}{m}$. Now say we're given m shares, $(a_1, F_1), \dots, (a_m, F_m)$. We can reconstruct F as follows. Let A be the matrix whose rows are a_i , $1 \leq i \leq m$. Then by construction we have for $1 \leq j \leq m$

$$Af_1 = A \begin{bmatrix} b_1 \\ \vdots \\ b_m \end{bmatrix} = \begin{bmatrix} c_{11} \\ \vdots \\ c_{m1} \end{bmatrix} = F_1.$$

Since the rows of A are designed to be linearly independent, we can invert the above equation to obtain

$$f_1 = \begin{bmatrix} b_1 \\ \vdots \\ b_m \end{bmatrix} = A^{-1}F_1.$$

Krawczyk - Secret Sharing with Short Shares (1994)³

Combine the ideas of Shamir and Rabin. We want to set up a (k, n) threshold scheme with secret S . We start by encrypting S with some secure cipher using key K , $E = \text{Enc}(S, K)$. Using Rabin's information dispersal method, partition E into n shares, E_1, \dots, E_n so that any k of them can rebuild E . Using Shamir's method, generate n shares of the key, K_1, \dots, K_n so that any k of them can rebuild K . Send person i the pair (E_i, K_i) .

Now when k people come together, they can reassemble E through Rabin's matrix inversion method and K through polynomial interpolation. The k participants can then decrypt E with K to obtain S .

While Shamir's method didn't shrink the size of the key shares, Rabin's method shrinks the size of the secret shares.

³H. Krawczyk, "Secret Sharing Made Short". In: Stinson D.R. (eds) Advances in Cryptology CRYPTO 93. CRYPTO 1993. Lecture Notes in Computer Science, vol 773.