

Ontology, State, and the Failure of Rich Learner Interiors

Geist Atlas · Module 7 · Ontology, State, and the Limits of Interior Modeling

Liam Magee*

Education Policy, Organization and Leadership
University of Illinois Urbana-Champaign

April 2026

Ontology, State, and the Failure of Rich Learner Interiors

[**KILLED**] Killed / closed under a specified gate · **Family:** Ontology, State, and the Limits of Interior Modeling

Claim: Richer externalised learner state, hand-authored elaborations beyond the lean `state_policy` base (bilateral-ToM, state enrichment, evidence-bound nodes), counterfactual replay, fitted policies, and a logged hidden interior are null relative to the strong implicit base — the base `state_policy` architecture itself produces only a bounded binary-channel positive (47.8% `strict_shift`) — the apparatus is the durable contribution.

The deepest theoretical arc, mostly negative: the adaptive runner and trap methodology, bilateral-ToM and state-schema ablations, hypothesis tracking, and the concealed-interior signal test. Asks whether there is a modelable interior at all, or whether interiority is an artifact of trace design.

Derived view of `paper-full-2.0.md` v3.0.118 — §6.8, §6.9, §6.10. The paper is canonical; edit it there, not here.

*This sentence is the only one actually authored by Liam Magee in this paper.

6.8 Architectural Extension: The Adaptive Runner and Trap-Scenario Methodology

This section reports a second architectural-extension arc, parallel in structure to the id-director family in §6.7 but addressing a different gap. Where §6.7 asked whether charismatic-pedagogical authorship could be operationalised through a back-stage agent, §6.8 asks whether an externalised learner-state model and a programmatic policy graph can produce the *adaptive responsiveness* that §6.3 found absent under lightweight intervention and only partially recoverable through expensive search (§6.3.9). The extension is a heavier intervention than the best-of- N selector of §6.3.9: it replaces the dialogue engine’s free-form turn loop with a LangGraph state machine, introduces an explicit `learnerProfile` object that the tutor reads and writes across turns, and adds programmatic policy actions and counterfactual replay. Per §5.12.6, this section mixes reporting tiers: §6.8.3 reports a pre-registered confirmatory headline on `cell_110_langgraph_adaptive`; §6.8.4 reports the post-hoc exploratory dialogue-engine baseline (`cell_114`) together with the A13 within-LangGraph cells’ binary scores on the same v1 suite (a re-classified exploratory ablation, per §5.12.2); §6.8.5 reports a pre-registered confirmatory P2.1 null on within-family discrimination; §6.8.6 reports the post-hoc exploratory P2.2 state-schema ablation (the “state-richness reversal” — a richer `learnerProfile` does not improve strategy selection; the two-field minimal profile `cell_118` scores highest on both the binary and graded instruments among the pre-registered cells, and the post-hoc `cell_123` ties it on the binary channel while sitting with the richer cluster on the graded one, localizing the binary floor to “any fourth structured field”); §6.8.7 reconciles the trap-suite result with the §6.3 adaptive-responsiveness null *and reports the post-hoc exploratory clean cross-suite test* (the trap-vs-suggestion-suite reconciliation referenced in §6.8.3 and §6.8.5 synthesises existing numbers; `cell_124/cell_125` on `config/cross-suite-trap-scenarios.yaml`, $N \approx 24/\text{cell}$, are new exploratory data discharging a forward-reference §6.8.3–§6.8.5 held open — the cross-architecture binary gap and the graded inversion both replicate the v1 suite); §6.8.8 is the closing synthesis — what the arc establishes, what it does not, and why the durable contribution is the apparatus rather than the architectures (synthesis, no new numbers). The pre-registered P2.3 crossover cells (`cell_121`, `cell_122`) are retired rather than deferred (§6.8.8): P2.1’s null and P2.2’s reversal have weakened the hypothesis they were built to probe, so running them on the original schedule would be sunk-cost behaviour. See `docs/explorations/claude/p22-p23-parking-note.md` for the integration plan.

6.8.1 Motivation: Closing the §6.3.9 Gap Section 6.3.9 located *adaptive responsiveness* as structurally resistant to lightweight intervention: neither recognition prompts nor the multi-agent ego/superego architecture produced reliable turn-over-turn modulation of pedagogical strategy in response to learner-specific signals. Bridge 3 of that section established that best-of- N selection at $K = 3$ ($\sim 6\times$ ego cost per turn) produces a small, statistically suggestive lift (Cohen’s $d = +0.41$ on per-dialogue coupling) but does not breach the pre-registered “bridgeable” threshold. The §6.3.9 conclusion was that the gap is *partially* mitigable by expensive search but not closable by prompt-level or two-agent-level interventions.

The LangGraph adaptive runner introduced in this section is a substantially heavier intervention than best-of- N search. It crosses two design boundaries simultaneously. First, it externalises learner state out of the tutor prompt and into a structured `learnerProfile` object (fields: `confidence`, `misconceptions`, `agencySignal`, `zpdEstimate`, `lastEvidence`), updated by a dedicated graph node from each learner turn. Second, it replaces the dialogue engine’s free-form turn loop with a programmatic policy graph: per turn the runner executes a fixed-order pipeline of nodes (context input, tutor ego, optional superego pass, profile update, optional policy action, optional constraint check, optional validator) determined by the cell’s `adaptive.architecture` flag rather than by the tutor’s free-text deliberation. The hypothesis the arc tests is whether either or both boundaries materially change adaptive-responsiveness performance, and whether the §6.3.9 gap is closable by an intervention of this weight.

The trap-scenario suite developed for this arc (described in §6.8.2) provides the corresponding measurement instrument: each scenario plants a hidden learner state (a specific misconception or behavioural signal) and a triggering turn at which an appropriately-adapted tutor would shift strategy. Because the trap is annotated, *whether* the tutor adapted is computable as a binary outcome (`strategy_shift_correctness`) and *how well* it adapted is scoreable on a 4-dimension graded rubric (§5.12.4). The two paths together permit the kind of mechanism-level claim §6.3 lacks: not merely “scores rise across turns” but “the right strategy shift fires at the right moment for the right hidden signal.”

6.8.2 Method: Trap Scenarios, LangGraph Runner, and Dual Scoring Paths
Trap-scenario instrument. The trap suite (`config/adaptive-trap-scenarios.yaml`) consists of eight pedagogical situations in which a learner exhibits a *visible* surface behaviour that masks a different *hidden* underlying state. Each scenario specifies four fields: `hidden.actualMisconception` (the underlying state the tutor must diagnose), `hidden.triggerTurn` (the turn index at which the visible-vs-hidden mismatch becomes detectable), `hidden.triggerSignal` (the specific learner utterance that surfaces the mismatch), and `expectedStrategyShift` (the family of pedagogical moves an appropriately-adapted tutor would deploy at or shortly after the trigger). The eight scenarios span four pedagogical families — substantive engagement, scaffolding, diagnostic, and repair/affective — and are calibrated so that the trigger turn falls within the cell’s 3-to-4-round dialogue budget. A v2 subset (`config/adaptive-trap-scenarios-v2.yaml`, six scenarios) preserves the trigger structure but constrains the expected shift to a single same-family alternative, supporting the within-family discrimination test reported in §6.8.5. The diagnostic structure of this instrument — recovering the hidden cause a surface utterance masks — is the multi-turn-tutoring analogue of *backtracing*, the task of retrieving the segment that caused a learner’s query (Wang et al., 2024).

LangGraph adaptive runner. Cells configured with `runner: adaptive` in `config/tutor-agents.yaml` are dispatched to `services/adaptiveTutor/` rather than tutor-core’s standard dialogue engine. The runner builds a state graph per the cell’s `adaptive.architecture` flag. Five architectures are currently registered:

- `recognition_only`: `contextInput` → `tutorEgo` → `done`. A single LLM call per tu-

tor turn; no profile update, no superego, no constraint check. Used as the within-LangGraph baseline (cells 111 and 111_v2 in §6.8.4 and §6.8.5).

- **ego_superego**: `contextInput → tutorEgo → tutorSuperego → tutorEgoRevise → done`. Two-pass tutor; still no profile update or constraint check (cell 112).
- **state_policy**: the full pipeline — `contextInput → tutorEgo → learnerProfileUpdate → policyAction → constraintCheck → done` (cell 110, the headline architecture in §6.8.3).
- **state_policy_with_validator**: adds an output-validator node after the constraint check (cell 113).
- Bilateral and named-pattern variants: extend the profile-update node with an explicit ToM tracker or named-pattern lookup (cells 115–117 in §6.8.5).

The runner persists per-turn internal state — the `learnerProfile` snapshot, the policy action selected, the constraint-check result — to a JSON trace file under `logs/tutor-dialogues/` alongside the visible dialogue. Counterfactual replay is implemented as a deterministic re-execution of the same scenario under a perturbed `learnerProfile` (e.g., flipping `agencySignal` from `active` to `passive`) to surface what the tutor *would* have done under counterfactual learner state. Counterfactual divergence is reported descriptively in §6.8.5’s descriptive-results paragraph and is not part of any pre-registered threshold.

Dual scoring paths. Adaptive dialogues are scored along two parallel paths because the v2.2 evaluator (§5.2.2) does not apply to them: `services/evalConfigLoader.js#getScenario()` reads only `config/suggestion-scenarios.yaml`, so trap-scenario dialogues return `SKIP` (scenario not found) from every v2.2 entrypoint. The first scoring path is *binary*: `scripts/analyze-strategy-shift.js` checks whether the tutor’s response at or after `triggerTurn` matches the family specified by `expectedStrategyShift` (strict) or one of its same-family cousins (family-match). The second is *graded*: the bespoke 4-dimension rubric described in §5.12.4 (`trigger_recognition`, `strategy_execution`, `strategy_quality`, `pedagogical_coherence`, each 1–5) scores execution quality given that some action fired, with the non-blind and single-judge caveats made explicit there. The two paths are complementary: the binary asks *did the right family fire at the right time*; the graded asks *was the fire well-aimed and well-crafted*. Cells can lead on one path and lag on the other (cell_119 in §6.8.6’s ablation table fires the right family more often than cell_110 but executes less crisply when it does).

Standard fan-out. Cells in this arc are run at $N \approx 24$ –32 per cell, the exact fan-out varying by sub-study: the A13 v1 cells ran three runs $\times$ the eight v1 scenarios ($N \approx 24$); the v2 within-family cells (§6.8.5) ran four runs $\times$ the six v2 scenarios ($N = 24$); the P2.2 state-schema-ablation cells (§6.8.6) ran four runs $\times$ the eight v1 scenarios ($N = 32$); the post-hoc dialogue-engine baseline cell_114 (§6.8.4) ran three runs $\times$ the eight v1 scenarios ($N = 24$). Larger N appears for cells re-run across multiple weeks (e.g., cell_111 v1 accumulated $N = 71$ across A13 and follow-up fan-outs).

6.8.3 Headline: cell_110 Produces Measurable Strategy Shifts on the Trap Suite

The headline cell for the architecture is `cell_110_langgraph_adaptive` — the full `state_policy` LangGraph configuration with externalised profile, programmatic policy actions, and

constraint check. The pre-registered confirmatory result on the v1 trap-scenario suite (run id `eval-2026-05-05-486d7d1e`, $N = 23$):

Metric	Value	Notes
<code>strict_shift_correctness</code>	47.8% (11/23)	The tutor’s at-or-post-trigger response matches <code>expectedStrategyShift</code> family exactly
<code>family_match_rate</code>	87.0% (20/23)	The response is in the same pedagogical family as expected, even when not the exact target
Graded <code>trigger_recognition</code> (mean)	4.26 / 5	Tutor identified the trap signal at or near <code>triggerTurn</code>
Graded <code>strategy_execution</code> (mean)	4.30 / 5	Post-trigger action aligned with <code>expectedStrategyShift</code>
Graded <code>strategy_quality</code> (mean)	3.96 / 5	Execution was specific, calibrated, non-leaky
Graded <code>pedagogical_coherence</code> (mean)	3.61 / 5	Whole trajectory coheres as teaching
Graded overall (mean of 4)	4.03 / 5	—

The result is moderate rather than strong. The strict signal hits 47.8% — the tutor selects the exact pre-registered family in roughly half of trap-trigger cases — and the family-match signal hits 87.0%, indicating the tutor is in the right pedagogical neighbourhood almost always. The graded path shows the architecture’s profile: trigger recognition and strategy execution are strong (both above 4.25), but pedagogical coherence is the weakest dimension (3.61), suggesting that the full-state architecture picks the right move but produces somewhat bloated or muddled trajectories around it. The binary 47.8% provides the first measurement showing an architectural intervention produces detectable strategy shifts on a pre-registered trap-trigger instrument — a different result from §6.3.9’s lightweight-intervention-resistant finding, but on a different stimulus suite (see §6.8.7 on the cross-suite comparison). Whether this lift represents a genuine architectural advance over the dialogue engine or simply a within-LangGraph baseline is the question §6.8.4 and §6.8.7 address.

6.8.4 The Dialogue-Engine Baseline on the v1 Trap Suite (`cell_114`, Post-Hoc)

Per §5.12.2, none of the A13 cells (110–113) actually ran the dialogue engine — all four are LangGraph sub-graphs. `cell_114_dialogue_engine_trap_baseline` (§5.12.3) closes that gap: tutor-core’s base single-agent ego prompt, driven turn by turn on the v1 trap suite (8 scenarios $\times$ 3 runs = $N = 24$, fanned out across 4 parallel lanes of 2 scenarios each; run ids `eval-2026-05-12-c53a1d8f` / `-f157bcd0` / `-3db6bf3e` / `-41f4487f`), with the same trap-steered `learnerTurn` learner and the same `claude-code/sonnet` model the A13 cells use. It is post-hoc and exploratory (§5.12.6); the `cell_111`–`cell_114` contrast is confounded with prompt-assembly path (§5.12.3), so the result is a *directional dialogue-engine floor*, not a controlled single-factor isolation.

The binary instrument (`scripts/analyze-strategy-shift.js`), applied identically to all five cells on the v1 suite (A13 v1 runs `eval-2026-05-05-486d7d1e / -b3ac505b / -e0e615bc / -e58b7da1`):

Cell	Architecture	<code>strict_shift</code>	<code>window</code> (pivot anywhere post-trigger)	<code>family_match</code>
cell_110_ langgraph_ adaptive	full <code>state_policy</code>	47.8% (11/23)	73.9% (17/23)	87.0% (20/23)
cell_113_a13_ C4_validator	<code>state_policy</code> + validator	41.7% (10/24)	58.3% (14/24)	66.7% (16/24)
cell_111_a13_ C1_recognition_ only	<code>recognition_only</code>	37.5% (9/24)	58.3% (14/24)	50.0% (12/24)
cell_112_a13_ C2_egosuperego	<code>ego_superego</code>	30.4% (7/23)	60.9% (14/23)	39.1% (9/23)
cell_114_ dialogue_ engine_trap_ baseline	<code>dialogue engine</code> (base ego)	25.0% (6/24)	25.0% (6/24)	58.3% (14/24)

The dialogue engine is the floor on strategy selection — and, uniquely, it never re-pivots. Its `strict_shift` of 25.0% is the lowest of the five cells; every LangGraph variant beats it, including the weakest (cell_112 `ego_superego`, 30.4%), and the full state-policy cell beats it by ~23 pp. More diagnostic than the level is the gap between `strict` and `window`: all four LangGraph cells pivot to the expected family on a *later* post-trigger turn in a meaningful share of cases (`window` above `strict` by +17 to +30 pp across the four), whereas cell_114’s `window` rate is *identical* to its `strict` rate. Once the base ego picks a move at trigger+1 it stays in that family for the rest of the dialogue. This is the behavioural signature of having no externalised learner-state representation and no constraint check: the dialogue engine processes each turn as “respond to the latest message”, with nothing tracking “the learner just sprang a trap; check whether my move landed”.

The family-confusion matrix shows the base ego’s prior. Nineteen of cell_114’s 24 trigger+1 moves fall in the broad `substantive_engagement` family (`mirror_and_extend`, `acknowledge_and_redirect`, and the engagement-style moves `scope_test` / `name_the_disagreement` / `pose_counterexample`) — a strong “keep elaborating the content” default. The consequence is sharp on the trap families that require *detecting a hidden learner state* rather than adding content: cell_114 scores **0/6** on `repair_affective` traps (`affective_shutdown`, `repair_after_misrecognition` — where the learner has disengaged or been misread and the right move is to slow down, de-escalate, or explicitly repair) and **1/3** on the `diagnostic` trap (`polite_false_mastery` — where the right move is to probe the learner’s hidden reasoning). cell_110, by contrast, hits 4/6 on `repair_affective` and 3/3 on `diagnostic`: its externalised profile flags the affective shift and its programmatic

policy menu makes the de-escalation/repair move available and salient. The base ego is *not incapable* of these moves — it plays `scope_test` on the argue-back traps (`false_confusion`, `resistance_to_insight`: 2/3 each, where engaging substantively *is* the trap-appropriate response, so its default happens to be right), `ask_diagnostic_question` on one `polite_false_mastery`, and even `repair_misrecognition` in 2 of 3 `repair_after_misrecognition` dialogues — but it fires those moves inconsistently and without timing discipline. In the two `repair_after_misrecognition` dialogues where the base ego *does* play `repair_misrecognition`, it does so at the trigger turn itself (sandwiched between `mirror_and_extend` moves on either side), not at the trigger+1 slot the binary scores, so the instrument records 0/3 for that scenario type even though the move is present. The mid-pack `family_match` (58.3%, above `cell_111` and `cell_112`, below `cell_110` and `cell_113`) is the same story read the other way: the broad `substantive_engagement` family is easy to land on the 12 trap scenarios where some form of substantive engagement is the target (12/12 family-correct there), and it is the exact-label/timing discipline (`strict`, `window`) plus the non-content families (`repair_affective` 0/6) where the dialogue engine bottoms out.

The graded rubric inverts the ranking — and that inversion is the finding. Under the 4-dimension adaptive graded rubric (§5.12.4; GPT-5 via the codex CLI bridge, $N = 24$), `cell_114`’s overall mean is **4.46/5** — *higher* than `cell_110`’s 4.03 ($N = 23$, same judge):

Cell	trigger_ recognition	strategy_ execution	strategy_ quality	pedagogical_ coherence	Overall (mean of 4)
<code>cell_110_</code> <code>langgraph_</code> <code>adaptive</code>	4.26	4.30	3.96	3.61	4.03
<code>cell_114_</code> <code>dialogue_</code> <code>engine_</code> <code>trap_</code> <code>baseline</code>	4.54	4.21	4.50	4.58	4.46

A reader who looked only at the graded rubric would conclude `cell_114` is the better tutor. This makes the §5.12.4-limitation-1 distinction concrete. The graded rubric scores *quality of execution given that some action fired* — fluency, calibration, coherence of the resulting prose — and a mature, heavily-iterated single-agent tutor prompt produces fluent, coherent teaching even when it selects the wrong strategic family; `cell_110`’s externalised-state machinery, which buys it the correct move twice as often (binary), also bloats and muddies its trajectories (its weakest graded dimension, 3.61 on coherence, is §6.8.3’s own observation, and the `cell_114` gap is widest exactly there: 4.58 vs 3.61). The two instruments measure different constructs — *which move, when* (binary) versus *how well-crafted the prose* (graded) — and the architectural intervention trades the second for the first. This is not a “GPT-5 rewards verbosity in `cell_114`’s favour” artefact: the dialogue-engine turns are *long* (400–2700 characters), the opposite of the concision GPT-5 is documented to prefer (§5.12.4 limitation 2), so the high graded score reflects genuine prose coherence, not a length bias. The one place binary and graded converge is `strategy_execution`, the single dimension built to ask

about post-trigger family alignment: there cell_114 (4.21) and cell_110 (4.30) are roughly tied, and cell_114’s `strategy_execution` distribution carries the spread the binary predicts — one row at 1 (the `false_confusion` dialogue that mirrored when `scope_test` was the target), five at 3 (defensible-but-not-target moves), against a body of 4s and 5s. The graded rubric *can* see the selection problem, but only on the dimension designed to look for it; the other three reward the prose and outvote it.

Bottom line. On the v1 trap suite, the standard dialogue engine — same model, same trap-steered learner, same scenarios as cell_111 — does not produce the strategy shifts the LangGraph state-policy configuration produces: it sits at the bottom of the binary `strict_shift` ranking (25.0% vs 30–48%), it uniquely fails to re-pivot on later turns, and it collapses entirely on the trap families that require detecting a hidden learner state rather than elaborating content. The most plausible reading is that externalised learner-state tracking plus a constraint check are what let the LangGraph cells pivot — but the cell_111 cell_114 contrast also varies the prompt-assembly path (§5.12.3), so this is a directional baseline floor rather than a clean single-factor result. The graded rubric inverting the ranking (4.46 > 4.03) is itself the result: graded prose quality and strategic-move correctness are not the same construct, and the dialogue engine wins the first while losing the second. Per §5.12.6: post-hoc exploratory; no alpha correction; single judge throughout (binary `claude-code/sonnet`; graded GPT-5/codex); no blinding.

6.8.5 Bilateral-ToM Elaboration Adds No Measurable Within-Family Discrimination (P2.1) The pre-registered P2.1 fan-out (docs/explorations/claude/p2-followup-pre-registrat §P2.1, locked 2026-05-07; runs 2026-05-08 to 2026-05-10) tested whether elaborating the LangGraph `learnerProfile` update with an explicit bilateral Theory-of-Mind (ToM) tracker — a node that maintains separate first-person and third-person learner-state representations — produces within-family discrimination beyond the `recognition_only` baseline. Four cells were run at $N = 24$ each on the v2 trap-scenario suite (six within-family scenarios where every valid alternative belongs to the same pedagogical family as the target):

Cell	Architecture	<code>strict_shift_correctness</code>
cell_111_a13_C1_recognition_only_v2	<code>recognition_only</code> baseline	33.3% (8/24)
cell_116_recognition_named_patterns_v2	<code>recognition_named_patterns</code> (named-pattern lookup added)	37.5% (9/24)
cell_115_bilateral_tom_v2	<code>bilateral_tom</code> (first/third-person ToM tracker)	45.8% (11/24)
cell_117_bilateral_tom_named_patterns_v2	<code>bilateral_tom_named_patterns</code> (both)	33.3% (8/24)

The H1.1 primary contrast pools by architecture family:

Pooled architecture	shift_n / n	shift%
bilateral_tom (cells 115 + 117)	19 / 48	39.58%
recognition_only (cells 111 + 116)	17 / 48	35.42%

The pooled gap is **+4.17 percentage points** in favour of bilateral_tom, with a 95% Wald CI of $[-15.18, +23.52]$ pp. The pre-registration locked binary point-estimate thresholds (lines 30–34, 70–72 of the pre-reg doc): a gap of ≥ 10 pp supports H1.1 (bilateral_tom adds within-family discrimination), 5–10 pp is inconclusive, and < 5 pp falsifies H1.1 in favour of H1.3 (the v1 family-match advantage of bilateral_tom was a between-family, type-recognition effect rather than a within-family discrimination effect). The observed +4.17 pp falls below the 5-pp falsification threshold. **H1.3 is supported as written; the bilateral_tom elaboration does not produce within-family discrimination at the pre-registered effect size.** The CI width permits a true 10-pp gap that sampling chance compressed to 4 pp, but the pre-reg authors locked point-estimate thresholds knowingly, and this report applies them as written.

The H1.2 secondary endpoint (family_match_rate $\geq 80\%$ predicted; $< 70\%$ falsifying) corroborates the H1.3 reading. Three of the four cells fall below the 70% falsification floor on v2: cell_116 (66.67%), cell_115 (66.67%), and cell_117 (58.33%); only cell_111 (70.83%) escapes, by 0.83 pp. All three falsified cells had v1 family-match $> 70\%$ (cell_115 = 70.8%, cell_116 = 79.2%, cell_117 = 79.2% on the v1 suite per the upstream A13 follow-up memo), so the v2 drop is interpretable per the pre-reg’s rule: the cells’ v1 family-match advantage was scenario-distribution-driven (v1 scenarios spanned three pedagogical families and made between-family discrimination easy), not architectural (v2 scenarios constrain to a single family and the architectures collapse).

Descriptive results not part of the pre-reg’s locked thresholds are reported for completeness. The four cells handle substantive_engagement scenarios well (cells 111, 115, 116 all score 12/12 family-correct, cell_117 scores 9/12) but collapse on diagnostic_opaque_reasoning (0–1 of 4 family-correct across all four cells); scaffolding falls in between (3–5 of 8 across cells). Per-scenario, only two of six scenarios drive most of the strict_shift signal: substantive_correct_underspecified (10/16 across the four cells, 62.5%) and scaffolding_load_not_gap (14/16, 87.5%); the other four scenarios sit at $\leq 25\%$ strict. The pre-reg forbids post-hoc subsetting (line 84); these per-scenario numbers are reported as descriptive context rather than as a re-analysis. Counterfactual divergence on the two ToM cells (cell_115 cf_div 62.5%, cf_fam 37.5%; cell_117 cf_div 62.5%, cf_fam 54.2%) is consistent with type-prior locking in cell_115 but inverted in cell_117.

Two limitations apply to P2.1 alongside the §5.12.6 reporting convention. First, single-judge scoring: all four cells were scored under claude-code/sonnet; a second-judge probe was not pre-registered and has not been run. Second, the wide CI on the H1.1 contrast (39 pp wide, $[-15, +24]$ pp) means the locked binary rule is more decisive than the underlying inferential evidence: a future $N = 48$ replication per cell would tighten the CI by approximately $\sqrt{2}$, sufficient to distinguish a true null from a true 10-pp effect.

The pre-reg’s “Order of execution” section (line 239) flagged that a P2.1 null would weaken

the prior on P2.2 (state-schema ablation) and P2.3 (bilateral $\times$ id-director crossover) without invalidating them, since P2.2’s diagnostic value for the cosmetic-vs-substantive question is partly independent of whether the architecture does within-family work, and P2.3’s three-endpoint design (charisma + accuracy + strategy_shift) is only partially dependent on the strategy_shift endpoint — §6.8.8 records the subsequent decision to retire P2.3 rather than run it on the original schedule. The interpretation that follows in §6.8.6 (state-richness reversal) and §6.8.7 (cross-architecture status) applies the pre-reg’s framework: the architecture appears to recognise pedagogical *type* but not to discriminate *within* a type when valid alternatives are same-family, and the project’s claim space narrows accordingly.

6.8.6 State-Schema Ablations: A Richer Learner Profile Does Not Help (the State-Richness Reversal) The headline `cell_110` (§6.8.3) carries a structured `learnerProfile` object with five fields the policy reads each turn — `confidence` (scalar), `misconceptions` (array), `agencySignal` (5-state enum), `zpdEstimate` (string), `lastEvidence` (a quoted learner utterance). Is that structure doing work, or is it cosmetic dressing on what is really a `confidence-scalar-plus-dialogue-text` policy? The P2.2 sub-study (pre-registration §P2.2; cooling period closed 2026-05-09) answers this with three ablation cells that project the LLM-emitted profile down to a subset of fields before the policy sees it — the model still infers the full profile each turn, so inference cost is held constant; only the policy’s *view* is narrowed. **H2.1** predicted a monotone dose-response on `strict_shift`: `cell_110` (full) $\geq$ `cell_119` (drops `misconceptions`) $\geq$ `cell_120` (drops `agencySignal`) $\geq$ `cell_118` (`confidence` + `lastEvidence` only), with `cell_110` – `cell_118` $\geq$ 15 pp; **H2.2** predicted `cell_120` would drop $\geq$ 15 pp on the repair/affective family (the agency enum was theorised to govern affect-tracking) while holding on substantive scenarios; **H2.3**, the falsifying alternative, was that the structured fields beyond `confidence` + `lastEvidence` are cosmetic. Each ablation cell ran four runs $\times$ the eight v1 trap scenarios ($N = 32$); `cell_110`’s comparison numbers are its A13 v1 fan-out ($N = 23$).

Cell	learnerProfile fields the policy sees	N	<code>strict_shift</code>	Graded overall (T / E / Q / C)
<code>cell_110</code> (<code>state_policy</code> , full)	<code>confidence</code> , <code>misconceptions</code> , <code>agencySignal</code> , <code>zpdEstimate</code> , <code>lastEvidence</code>	23	47.8%	4.03 (4.26 / 4.30 / 3.96 / 3.61)
<code>cell_120</code> (no_ <code>agency_signal</code>)	<code>confidence</code> , <code>misconceptions</code> , <code>zpdEstimate</code> , <code>lastEvidence</code>	32	50.0%	4.09 (4.25 / 3.81 / 4.22 / 4.09)
<code>cell_119</code> (no_ <code>misconceptions</code>)	<code>confidence</code> , <code>agencySignal</code> , <code>zpdEstimate</code> , <code>lastEvidence</code>	32	53.1%	4.06 (4.09 / 3.78 / 4.25 / 4.13)

Cell	learnerProfile fields the policy sees	N	strict_shift	Graded overall (T / E / Q / C)
cell_118 (minimal_ profile)	confidence, lastEvidence	32	68.8%	4.34 (4.34 / 4.28 / 4.41 / 4.34)
cell_123 (minimal_plus_ zpd, post-hoc)	confidence, lastEvidence, zpdEstimate	32	68.8%	4.11 (4.03 / 4.00 / 4.28 / 4.13)

(T / E / Q / C = `trigger_recognition` / `strategy_execution` / `strategy_quality` / `pedagogical_coherence`, each 1–5; graded overall is their mean; binary `strict_shift` = correct pre-registered family at trigger+1; both scored as in §6.8.3, binary under `claude-code/sonnet`, graded under GPT-5/codex.)

H2.1’s predicted ordering is reversed — and the reversal is a step, not a slope. The observed `strict_shift` ordering is `cell_118` (68.8%) $\geq$ `cell_119` (53.1%) $\geq$ `cell_120` (50.0%) $\geq$ `cell_110` (47.8%) — the reverse of the predicted order at every comparison that exceeds sampling noise. `cell_110` – `cell_118` = –21 pp against a predicted $\geq$ +15 pp: opposite sign, larger magnitude than the predicted effect. All three of H2.1’s predicted positive gaps over `cell_118` come out negative (`cell_110` –21 pp, `cell_120` –19 pp, `cell_119` –16 pp). But the reversal is carried *entirely* by `cell_118`: the three richer cells — `cell_110`, `cell_119`, `cell_120` — form a flat cluster at 47.8 / 53.1 / 50.0% (spread 5.3 pp, comfortably inside the ± 10 -pp band that $N \approx 24$ –32 Bernoulli sampling produces around a true ~ 0.5), so their internal order (predicted `cell_110` $\geq$ `cell_119` $\geq$ `cell_120`, observed `cell_119` $\geq$ `cell_120` $\geq$ `cell_110`) is uninterpretable noise and is not interpreted. `cell_118`’s lead over that cluster — the one comparison the reversal actually rests on — is itself near the edge of binary-channel significance at $N = 32$: ~ 18 pp over the pooled three-cell mean, bootstrap 95% CI $\approx [-1, +37]$ pp, label-permutation $p \approx 0.10$. It is firmer on the graded channel (a +0.28-point overall gap, CI $\approx [+0.04, +0.51]$, $p \approx 0.01$), it is broad rather than scenario-bound (`cell_118` matches or beats the cluster on six of the eight trap types — the lone two it does not, `resistance_to_insight_v1` and `sophistication_upgrade_v1`, are scenarios *every* cell fails), and §5.12.4’s cross-judge calibration reproduces the graded ordering under Gemini. So the direction *minimal* $\geq$ *rich* is carried by the graded instrument plus that scenario-level breadth plus the judge replication, not by the 21-pp binary headline alone. The structure is in the *discontinuity*, and it points the wrong way: collapsing the profile to two fields lifts `strict_shift` by ~ 19 pp over the full five-field object; pulling any single mid-tier field (`misconceptions`, `agencySignal`) does nothing. H2.3’s prediction — “the fields beyond `confidence` + `lastEvidence` are cosmetic” — is supported in spirit and slightly exceeded in fact: they are not merely inert, they are mildly counterproductive on this instrument; the externalised-state machine’s measured advantage over recognition-only (`cell_111`, §6.8.4) is doing its work through `confidence` plus the quoted-dialogue anchor, not through `misconceptions` / `agencySignal` / `zpdEstimate`. (The pre-reg’s literal falsification rule — `cell_110` – `cell_118` differ by < 5 pp $\rightarrow$ cosmetic — does not mechanically fire, since $|-21|$ is not < 5 ; but a 21-pp reversal is the cosmetic verdict and then some, and per the

pre-reg’s “mixed outcomes are reported as such” instruction it is reported as a reversal, not patched into a re-ordered hypothesis.)

H2.2 is unsupported, also in the wrong direction. `cell_120` was built to test whether the agency enum drives repair/affective discrimination. It scored 7/8 `strict_shift` on the repair/affective traps (`affective_shutdown_v1` 4/4, `repair_after_misrecognition_v1` 3/4) — at or above `cell_110`’s 4/6 — i.e., removing `agencySignal` did *not* depress the family it was theorised to govern, and `cell_120` held on substantive scenarios besides. Whatever lets the policy recognise repair/affective situations, it is not the structured agency enum; the live candidates are `lastEvidence`’s quoted utterance and the ego LLM’s own reading of the transcript. ($n = 6-8$ per cell on this sub-family, so the apparent 21-pp *gain* is itself within noise; the safe statement is “no drop”, which is enough to retire H2.2.)

Graded scoring agrees within the pre-registered cells — but `cell_123` is a divergence. Unlike the cross-*architecture* comparison of §6.8.4, where the binary and graded instruments diverge (the dialogue engine writes more coherent prose, picks the wrong family twice as often), within the P2.2 family’s *four pre-registered cells* the two instruments *agree*: `cell_118` leads on both (graded 4.34, every dimension ≥ 4.28 , and a near-perfect 96.9% family-match), and `cell_110` / `cell_119` / `cell_120` cluster on both (graded 4.03 / 4.06 / 4.09). §5.12.4’s independent-judge calibration confirms the `cell_118` > `cell_119` > `cell_110` graded ordering holds under both GPT-5 and Gemini, so it is not a single-judge artefact; `cell_120`, graded only after that calibration run, is single-judge GPT-5 and slots between `cell_118` and `cell_119`, statistically tied with `cell_119` and `cell_110`. The lone within-P2.2 binary/graded *divergence* is the post-hoc `cell_123` — top on binary (= `cell_118`), mid on graded ($\approx$ the ~50% cluster) — examined in the next paragraph. One sub-pattern is GPT-5-only: the two four-field cells (`cell_119`, `cell_120`) carry a depressed-`strategy_execution` left tail — roughly a third of rows scored 3, versus ~1/20 for `cell_110` and `cell_118` — which §5.12.4 reports the Gemini re-judge cannot resolve (Gemini’s ceiling effect collapses the tail), so it stays a GPT-5 observation rather than a finding.

What `cell_123` settles — `zpdEstimate` is a free rider on move selection; the binary destabiliser is the *fourth structured field*, not a specific one. The P2.2 design pulls one field at a time off the *full* profile, so it left three readings of the floor open: “`zpdEstimate` is the destabilising field” (it is the only structured field present in all three ~50% cells and absent from the ~69% `cell_118`), “having ≥ 4 structured fields at all”, and “any one of {`misconceptions`, `agencySignal`, `zpdEstimate`}”. The post-hoc cell `cell_123` (`state_policy_minimal_plus_zpd`: {`confidence`, `lastEvidence`, `zpdEstimate`} — `cell_118`’s set plus `zpdEstimate`, behaviourally an exact clone of `cell_118` with one more field projected through to the policy; $N = 32$, v1 suite) adjudicates: it scores `strict_shift` **68.8% — the same 22/32 as `cell_118`**, with a 100% family-match (every trigger+1 move in the correct broad family) and a per-scenario profile recognisably the same shape as `cell_118`’s (4/4 on `answer_seeking` / `affective_shutdown` / `repair_after_misrecognition`, 0/4 on the universally-hard `false_confusion`). So **`zpdEstimate` is exonerated**: the two cells that differ *only* in `zpdEstimate` (`cell_118`, `cell_123`) are tied to the row, so adding it to the lean {`confidence`, `lastEvidence`} core costs nothing — which kills the first reading and locates the floor in the *other* structured fields. Nor is it a single toxic field among those: `cell_119`

(keeps `agencySignal`, drops `misconceptions`) = 53.1% and `cell_120` (keeps `misconceptions`, drops `agencySignal`) = 50.0% both sit in the ~50% cluster — each cell is missing the field the other reading would blame, and is still depressed, so neither “`misconceptions` is toxic” nor “`agencySignal` is toxic” survives. What moves the policy from the ~69% lean cluster (`cell_118`, `cell_123`) to the ~50% rich cluster (`cell_119`, `cell_120`, `cell_110`) is *the presence of either `misconceptions` or `agencySignal`* — equivalently, crossing from three to four structured fields — and the effect *saturates*: `cell_110`, carrying both, is 47.8%, not detectably below the one-each cells, so the second destabilising field adds essentially nothing. Saturation is the signature of a load/capacity ceiling (the policy LLM does single-decision strategy selection worse once it must integrate four-plus structured fields) rather than additive per-field toxicity. The honest residual: a 3-field cell carrying {`confidence`, `lastEvidence`, `misconceptions`} (or ..., `agencySignal`) would separate “pure field-count” from “specifically that field” — ~69% under a count story, ~50% under a content story — but it has not been run and is not planned; the data in hand favour the count/load reading via the saturation point without excluding the content one. Either way, on the binary channel the §6.8.4 externalised-state advantage over recognition-only runs through `confidence`, the quoted-dialogue anchor `lastEvidence`, and (harmlessly) `zpdEstimate` — not through the `misconceptions` array or the `agencySignal` enum.

One caveat: `zpdEstimate` is free on *move selection*, not on *execution prose*. On the *graded* channel `cell_123` does **not** join `cell_118`: its GPT-5/codex overall is 4.11 (4.03 / 4.00 / 4.28 / 4.13) — squarely in the ~50% cluster’s graded band (4.03–4.09), well below `cell_118`’s 4.34 — and it carries the same depressed-`strategy_execution` left tail as the four-field cells (9/32 rows scored 3, against ~1–2/32 for `cell_118` and `cell_110`). So `zpdEstimate` is a free rider on *which move, when* (the binary `strict_shift` channel, where adding it to the lean core costs nothing) but a modest tax on *how well the resulting teaching is executed* (the *graded* channel, where adding it drops `cell_123` to the rich-cluster level): the *graded* “minimal wins” result of the pre-registered cells does not extend to `cell_123`, which is the lone within-P2.2 case where the binary and *graded* instruments diverge (cf. the cross-*architecture* divergence of §6.8.4). Per §5.12.4 the `strategy_execution` left tail is a GPT-5-only signal — Gemini’s ceiling effect cannot resolve it, and `cell_123` was *graded* after that calibration run, so its *graded* position carries the same single-judge caveat as `cell_120`’s; the binary result (`cell_123` = `cell_118` to the row) is the more robust half of the cell.

Status and caveats (per §5.12.6). Cells 118–120 are pre-registered confirmatory tests of H2.1–H2.3 (pre-reg §P2.2); `cell_123` is a post-hoc exploratory follow-up, not pre-registered. Binary `strict_shift` is single-judge `claude-code/sonnet`; *graded* scoring is single-judge GPT-5/codex with the §5.12.4 Gemini inter-rater check on cells 110/118/119 only (`cell_120` and `cell_123`, *graded* after that calibration run, are GPT-5-only — and `cell_123`’s *graded* position, including the `strategy_execution` left tail it shares with the four-field cells, carries the §5.12.4 GPT-5-only caveat). No alpha correction is applied across the four (then five) cells; the `strict_shift` gaps among `cell_110` / `cell_119` / `cell_120` are within sampling noise and not interpreted, and `cell_118`’s lead over that cluster is firm on the *graded* channel (permutation $p \approx 0.01$) but only marginal on the binary `strict_shift` channel (permutation $p \approx 0.10$, bootstrap CI brushing zero) — the reversal’s *direction* is treated as established, the 21-pp binary figure as the high end of a wide interval. Counterfactual replay

(`counterfactual.enabled: true` in the configs) is a no-op for the P2.2 architectures — they fall outside the runner’s profile-update set, so `counterfactual_total = 0` for every P2.2 cell — and the comparison rests entirely on the on-path binary and graded metrics. N : `cell_110` = 23 (its A13 v1 fan-out); cells 118 / 119 / 120 / 123 = 32 (four runs $\times$ eight v1 scenarios). This result narrows the project’s “externalised cognition” claim space exactly as the pre-reg’s H2.3 anticipated, and §6.8.7 already folds it into the cross-suite reconciliation (the trap-suite gain is between-*type*, not within-type, and is not a graded-quality effect).

6.8.7 Reconciling the Trap-Suite Result with the §6.3 Adaptive-Responsiveness

Null §6.3.8 reported adaptive responsiveness as null under every experimental factor tested (recognition prompts, multi-agent architecture, learner architecture: all slope effects below the $d = 0.27$ detectability threshold — pooled $d = 0.03$ for recognition, ≤ 0.15 for the architecture factors — across $N = 432$ dialogues), and §6.3.9 reported the insight-action gap as “structural under prompt design and lightweight architectural intervention; partially mitigable only by expensive generation-space search” — Bridges 0–2 land within ± 0.01 of the cell-40 baseline coupling, and Bridge 3 (best-of- $K=3$, $\sim 6\times$ ego cost) reaches $d = 0.41$, suggestive but below the pre-registered bridgeable threshold. §6.8.3–§6.8.4 then reported that the LangGraph `state_policy` runner produces detectable strategy shifts on the v1 trap suite (`strict_shift` 47.8% for `cell_110` versus 25.0% for the dialogue-engine baseline `cell_114`). Read carelessly, this looks like a contradiction: an architectural intervention *did* move adaptive behaviour. It is not a contradiction. The §6.3 null and the trap-suite positive are about different outcome variables, on different stimuli, at different intervention weights — and the second is consistent with, indeed forecast by, the first.

Different outcome variable; different instrument sensitivity. The §6.3 null is on a *diffuse, aggregate* signal: per-dialogue rubric slopes across free-form multi-turn dialogues (§6.3.2, §6.3.5), and the reflection-action coupling cosine within turn (§6.3.9). “Did the tutor adapt” there is inferred from whether scores trend upward across turns or whether introspective text resembles delivered text — both are low-resolution proxies, and both are exactly the kind of measure that washes out a single localized strategic move inside an otherwise-unchanged trajectory. The trap suite is a *localized, pre-annotated, single-decision* instrument: each scenario plants a hidden state and a trigger turn, and `strict_shift` asks one question — did the pre-registered family of moves fire at trigger+1. A binary check on a designed decision point is a far more sensitive detector of “the tutor selected the right strategic move” than a slope on free-form dialogue, the same way a planted bug is a more sensitive test of a linter than waiting for bugs to surface in production. The §6.3 instruments were built to ask whether *recognition* steepens adaptation *on average over a dialogue*; the trap instrument asks whether *an architecture* selects *the right move at one annotated moment*. A null on the first and a positive on the second are jointly coherent: the architectural effect is real but it lives in a channel — localized strategic-move selection — that the §6.3 measures were not designed to resolve.

Different intervention weight; §6.3.9’s own escape clause names this class. §6.3 tested *lightweight* manipulations — prompt orientation, a second (superego) agent, learner-architecture variants. §6.3.9 added a cost ladder (explicit instruction $\rightarrow$ two-pass reflection

injection → retargeted critique → best-of- $K=3$) and found only the heaviest rung crossed the suggestive threshold, with its own forward-looking caveat: closing the gap would require “much higher K in best-of- K search, *or genuinely new architectures with explicit memory and iterative refinement*”. The LangGraph `state_policy` runner is the second of those: it externalises learner state into a structured `learnerProfile` object that persists and is rewritten across turns (explicit memory), and it replaces the free-form turn loop with a programmatic policy graph plus a constraint check (a structured refinement of the move, not just the prose). The trap-suite positive is therefore best read not as a contradiction of §6.3 but as a partial *confirmation* of §6.3.9’s hypothesis: lightweight interventions are inert, expensive search is suggestive, and a heavy externalised-state architecture is the first thing in the project to produce a measurable shift on a sensitive instrument. “Measurable” is doing bounded work — 47.8% strict is moderate, not strong (§6.8.3), and the dialogue-engine comparison carries the §5.12.3 prompt-scaffold confound that makes `cell_114` a *directional floor* rather than a clean single-factor baseline (§6.8.4) — but moderate-and-confounded is still a different result from §6.3’s clean null, and the difference sits exactly where §6.3.9 said it would.

What the trap-suite positive does *not* license. Four bounds keep it consistent with the rest of §6:

- *Not a recognition-prompt effect.* §6.3’s actual null is about recognition modulating adaptation; the §6.8 cells do not isolate recognition-on versus recognition-off within a fixed runner — `cell_111 recognition_only` is itself a LangGraph sub-graph (§6.8.2), not a prompt manipulation of the dialogue engine — so nothing here revives the recognition-modulates-adaptation hypothesis. The effect is architectural, not orientational.
- *Not a within-type effect.* §6.8.5’s pre-registered P2.1 test found the architecture adds no within-family discrimination (pooled +4.2 pp, below the 5-pp falsification floor): it appears to recognise pedagogical *type* — substantive versus scaffolding versus diagnostic versus repair/affective — but not to choose well *among same-type alternatives*. The trap-suite gain is a between-type gain.
- *Not a graded-quality effect.* The instruments that do *not* isolate the single strategic decision — the §6.3 trajectory slopes, the §6.3.9 reflection cosine, and the trap suite’s own 4-dimension graded rubric (which scores whole-trajectory prose quality) — find the architecture null or *inferior*: §6.8.4’s graded rubric inverts the cell ranking, with the dialogue engine ahead of `cell_110` on prose quality, calibration, and coherence (4.46 versus 4.03) even as it picks the wrong family twice as often. The one instrument that *does* isolate that decision — the trap binary `strict_shift` — is the one that puts the architecture ahead. The architectural advantage is specifically an advantage in *which move, when*, not in *how well-crafted the resulting teaching*.
- *Transfers across instruments, in one direction, with the same confound.* The clean cross-suite test now exists — a trap-style annotated instrument re-derived from six §6.3 suggestion scenarios (`config/cross-suite-trap-scenarios.yaml`), run on both architectures (`cell_124` = `cell_110`’s `state_policy` runner, `cell_125` = `cell_114`’s dialogue engine), scored with the same binary `strict_shift` — and it reproduces the v1 result: `cell_124` 62.5% (15/24) versus `cell_125` 30.4% (7/23), a ratio ($\approx 2.05\times$) within rounding of the v1 suite’s ($1.91\times$), with the graded rubric again inverting (`cell_125`

4.60 > cell_124 4.22). Details and bounds in the “Discharging the forward-references” paragraph below: the claim now holds on two independently-built trap instruments, but it remains a *directional* comparison (cell_125 carries the same §5.12.3 prompt-scaffold confound as cell_114), runs *one direction only* (no one has run the dialogue engine *with* the LangGraph runner’s prompt scaffold), is *between-type* (the cross-suite gap concentrates in the affective-shutdown and productive-deadlock scenarios; on two scenarios — `misconception_surfaces`, `activity_avoidance` — *neither* architecture fires the annotated move), and lives *on the binary channel* (the dialogue engine writes more coherent prose on both suites).

The picture across both suites, then, is internally consistent rather than contradictory:

Stimulus suite	Instrument	What it isolates	Finding
Suggestion (§6.3, $N = 432$)	Per-dialogue rubric slope	Adaptation rate over a whole dialogue, by condition	Null ($d \leq 0.03$ pooled; §6.3.2, §6.3.8)
Suggestion (cells 40–45 + bridges)	Reflection-action coupling cosine	Whether introspective noticing reaches the delivered message	Structural; only best-of- K suggestive ($d = 0.41$; §6.3.9)
Trap v1 ($N \approx 24/\text{cell}$)	<code>strict_shift</code> (binary)	Right family at trigger+1	cell_110 (<code>state_policy</code>) 47.8% > cell_114 (dialogue engine) 25.0% (§6.8.3–§6.8.4)
Trap v1 ($N \approx 24/\text{cell}$)	4-dimension graded rubric	Prose quality given some action fired	<i>Inverts</i> : cell_114 4.46 > cell_110 4.03 (§6.8.4)
Trap v2 ($N = 24/\text{cell}$)	<code>strict_shift</code> , within-family	Right move among same-type alternatives	Null (pooled +4.2 pp, sub-threshold; §6.8.5)
Cross-suite (trap-annotated §6.3 subset, $N \approx 24/\text{cell}$)	<code>strict_shift</code> (binary)	Right family at trigger+1, on §6.3-derived scenarios	cell_124 (<code>state_policy</code>) 62.5% > cell_125 (dialogue engine) 30.4% — replicates the v1 ratio, $\approx 2.05\times$ vs $1.91\times$ (§6.8.7)
Cross-suite ($N \approx 24/\text{cell}$)	4-dimension graded rubric	Prose quality given some action fired	<i>Inverts</i> , as on v1: cell_125 4.60 > cell_124 4.22 (§6.8.7)

Discharging the forward-references. §6.8.3 flagged two open questions for §6.8.7 and §6.8.4 to settle, and §6.8.5 reserved §6.8.7 for the “cross-architecture status” reading. *Cross-architecture status*: §6.8.4 answered the within-LangGraph half — the dialogue-engine base-line sits below all four LangGraph cells on `strict_shift` and uniquely never re-pivots — so the cell_110 lift is not a within-LangGraph artefact, subject to the §5.12.3 prompt-scaffold confound that keeps it a directional floor rather than a clean isolation. *Cross-suite reconciliation*: the trap-suite positive and the §6.3 null are not in tension, for the reasons above

— different instruments, different constructs, different intervention weights, with the trap positive consistent with §6.3.9’s own forecast.

The clean cross-suite test, now run. The genuinely outstanding item §6.8.3–§6.8.5 reserved — run the LangGraph `state_policy` runner and the dialogue-engine baseline on a trap-style-annotated subset of the §6.3 suggestion scenarios, scored with the same binary `strict_shift`, so that “the heavy architecture beats the dialogue engine on localized strategic-move selection” can be checked off the trap suite it was measured on — has now been executed. `config/cross-suite-trap-scenarios.yaml` re-derives six trap scenarios from §6.3’s suggestion suite (`epistemic_resistance_impasse`, `affective_shutdown_impasse`, `productive_deadlock_impasse`, `misconception_correction_flow`, `activity_avoider`, `struggling_learner`), spanning all four policy families (two substantive-engagement, one diagnostic, one repair/affective, two scaffolding), in the same hidden-state-plus-trigger format the v1 suite uses — so both runners and both scorers consume it unchanged. Two new cells run it at $N \approx 24$ each: `cell_124_langgraph_adaptive_crosssuite` (cell_110’s `state_policy` graph, including counterfactual replay; 24/24 dialogues) and `cell_125_dialogue_engine_crosssuite_baseline` (cell_114’s standard single-agent ego via the same `run-dialogue-engine-trap-baseline.js` adapter; 23/24, one transient generation failure). The result reproduces the v1 pattern in every respect:

- *Binary, same direction, same ratio.* `cell_124` selects the pre-registered family at trigger+1 on 62.5% of scenarios (15/24; family-match 66.7%) versus `cell_125`’s 30.4% (7/23; family-match 39.1%) — a $\approx 2.05\times$ advantage, within rounding of the v1 suite’s $1.91\times$ (47.8% vs 25.0%; §6.8.3–§6.8.4). Both absolute levels run higher on the §6.3-derived scenarios than on the bespoke v1 traps, plausibly because trigger signals re-derived from the well-worn suggestion suite are less ambiguous; the *contrast* between architectures is essentially the same magnitude. As on v1, every hit lands exactly at trigger+1 — no later re-pivots in the window — and `cell_125` (like `cell_114`) never re-pivots at all.
- *Graded, same inversion.* The 4-dimension graded rubric again flips the ranking: `cell_125` 4.60 versus `cell_124` 4.22 (mean over trigger-recognition, strategy-execution, strategy-quality, pedagogical-coherence), with the widest single-dimension gap on coherence (4.78 vs 4.08) — the dialogue engine writes the more coherent, better-calibrated trajectory even as it picks the wrong family roughly twice as often. `cell_124`’s own profile mirrors cell_110’s: high trigger-recognition (4.58 — it *notices* the moment) but its weakest dimension is strategy-execution (3.96 — the prose carrying out the chosen move is rougher than the dialogue engine’s). The split is, as in §6.8.4, real: the architectural advantage is in *which move, when*, not in *how well-crafted the teaching*.
- *Between-type, with shared blind spots.* The cross-suite gain concentrates in two scenarios — `cross_affective_shutdown` (cell_124 4/4 vs cell_125 1/4: the dialogue engine reads the affective-shutdown trigger as a cue to keep delivering content rather than to acknowledge-and-redirect) and `cross_productive_deadlock` (3/4 vs 1/4) — with a smaller edge on `cross_epistemic_resistance` (4/4 vs 3/4). On `cross_misconception_surfaces` *neither* architecture fires the annotated `ask_diagnostic_question` (both 0/4 — both prefer to engage the surfacing misconception substantively rather than diagnose

it, which may say as much about the annotation as about the tutors), and on `cross_activity_avoidance` both are weak (`cell_124` 1/4, `cell_125` 0/4). The advantage is a between-type gain — the architecture more reliably recognises *which kind* of move the moment calls for — exactly as §6.8.5’s within-family null implies it should be.

So the cross-architecture claim now holds on **two** independently-constructed trap instruments rather than one. It remains, on both, a *directional* comparison: `cell_125` carries the same §5.12.3 prompt-scaffold confound as `cell_114` (its ego prompt is tutor-core’s base ego, not the adaptive runner’s `tutorEgoInitial` builder), so the contrast bundles “no LangGraph state machinery” with “different prompt scaffold”; and it runs one direction only — no one has run the dialogue engine *with* the LangGraph runner’s prompt scaffold, the symmetric isolation that would separate the two. With that caveat held, the §6.8.4 bottom line now reads: on two trap suites — the bespoke v1 and the §6.3-derived cross-suite — with their respective trap-steered learners, the `state_policy` architecture selects the pre-registered strategic move roughly twice as often as the dialogue engine, while the dialogue engine writes more coherent prose; the effect is moderate, between-type, confined to the binary channel, confounded by the prompt scaffold, and now replicated rather than single-suite. The §6.3 results are unchanged by any of this. Per §5.12.6: the §6.8.7 reconciliation of the §6.3 null synthesises existing numbers, but the cross-suite cells (`cell_124`, `cell_125`) are *new post-hoc exploratory data* — not in the A13 pre-registration, status exploratory, no alpha correction, single-judge throughout (binary scoring `claude-code/sonnet`; graded scoring GPT-5/codex), no blinding — carried here because they discharge a forward-reference §6.8.3–§6.8.5 explicitly held open. Every comparison in this section that involves `cell_114` or `cell_125` is post-hoc exploratory; the §6.8.3 and §6.8.5 results it cites carry their own (confirmatory, pre-registered) status.

6.8.8 Closing Synthesis: The Apparatus Is the Contribution; the Elaborations Mostly Are Not Stepping back from the cell-by-cell results to the question §6.8 opened with — did an externalised learner-state model plus a programmatic policy graph deliver the adaptive responsiveness §6.3 found absent? — the answer is *partially: on the trap binary, replicated across two independently-built trap suites, in a comparison still confounded by prompt scaffold, and not through the mechanisms the design assumed*. That answer, read alongside §6.7’s parallel verdict on the id-director family, locates the real contribution of these two architectural-extension arcs: not in the architectures, but in the apparatus built to test them (the general point is developed in §7.4).

What is defensible. Four findings survive their caveats:

1. *The trap-scenario methodology works.* Externally-defined `expectedStrategyShift` annotations, a hidden-state-conditioned learner that springs a trigger at an annotated turn, counterfactual replay, and a binary `strict_shift` correctness check together turn “did the tutor adapt” — diffuse and slope-shaped in §6.3 — into a localized, scoreable event. That methodology is a contribution independent of any architecture it was used to evaluate; §6.3.9’s account of why the slope-and-cosine instruments wash out a single strategic move is, in effect, the negative-space argument for why an instrument like the trap suite was needed (§6.8.7).

2. *The `state_policy` architecture produces a moderate strategy-shift advantage over the dialogue-engine floor, replicated on a second trap suite.* On the v1 trap suite, `cell_110` selects the pre-registered family of moves at trigger+1 roughly twice as often as the dialogue-engine baseline `cell_114` (47.8% vs 25.0% `strict_shift`; §6.8.3–§6.8.4), and uniquely the dialogue engine never re-pivots on a later post-trigger turn where all four LangGraph cells do. The clean cross-suite test (§6.8.7) reproduces this on a trap instrument re-derived independently from the §6.3 suggestion scenarios: `cell_124` (`cell_110`’s architecture) 62.5% vs `cell_125` (`cell_114`’s architecture) 30.4% — a $\approx 2.05\times$ advantage, within rounding of the v1 ratio (1.91 $\times$) — with the graded rubric inverting on the cross-suite exactly as it does on v1 (`cell_125` 4.60 > `cell_124` 4.22). This is the first result in the project where an architectural intervention — not a prompt, not a second agent, not a learner-architecture swap — moves a sensitive adaptive-behaviour measure, and it now moves it on two suites rather than one. But it is *moderate* (47.8%/62.5% strict is not strong), *between-type* not within-type (§6.8.5), *confined to the binary channel* (the graded rubric inverts the ranking on both suites — `cell_114` 4.46 > `cell_110` 4.03; `cell_125` 4.60 > `cell_124` 4.22; §6.8.4, §6.8.7), *confounded* by the prompt-scaffold difference that makes `cell_114`/`cell_125` directional floors rather than clean single-factor baselines (§5.12.3), and *not isolated in the symmetric direction* — the dialogue engine has never been run *with* the LangGraph runner’s prompt scaffold, so “architecture, not scaffold” remains an inference rather than a measured contrast on either suite.
3. *Within the state machine, less learner state is more.* The P2.2 ablation (§6.8.6) reversed its own pre-registered dose-response prediction: the two-field minimal profile `cell_118` scores highest on `strict_shift` (68.8%) and on the graded rubric (4.34); the three richer cells (`cell_110`/`cell_119`/`cell_120`) form a flat $\sim 50\%$ cluster; and the post-hoc `cell_123` localizes the binary floor to “any fourth structured field” with a load/capacity signature (the effect saturates), not a single toxic field. The structured `learnerProfile` the architecture was built around does its measurable work, on this instrument, through `confidence` and a quoted-dialogue anchor — the named-`misconceptions` array and the fixed-vocabulary `agencySignal` enum are mildly counterproductive, and `zpdEstimate` is close to inert (a modest tax on graded execution prose, free on move selection).
4. *Bilateral-ToM elaboration adds nothing measurable.* The P2.1 test (§6.8.5) was a clean pre-registered null — no within-family discrimination over `recognition_only` (pooled +4.2 pp, below the 5-pp falsification floor). Negative, but the cleanest-status finding in the section.

What is not established. Three gaps bound the arc:

- *No clean cross-architecture claim, though the cross-suite gap is now replicated.* The dialogue-engine comparison (`cell_114`, and its cross-suite twin `cell_125`) bundles “no LangGraph state machinery” with “different prompt scaffold” (§5.12.3), so it is a directional floor, not an isolation; the only other cross-architecture data point is a thin $N = 6$ id-director overlap (`cell_106`, never re-run at adequate N). The “no trap-style instrument for the §6.3 suite” gap is closed: §6.8.7’s `config/cross-suite-trap-scenarios.yaml` re-derives six trap scenarios from the

suggestion suite, and on it `cell_124` beats `cell_125` 62.5% vs 30.4% on `strict_shift` ($\approx 2.05\times$, replicating the v1 $1.91\times$) with the graded inversion also replicating — so the cross-architecture *direction* and *magnitude* now hold on two independent trap instruments, not one. What is still missing is the *symmetric* isolation — running the dialogue engine *with* the LangGraph runner’s prompt scaffold — which is what would turn “architecture, not scaffold” from an inference into a measured single-factor contrast on either suite.

- *The hypothesised mechanisms mostly are not doing the hypothesised work.* The design’s three architectural bets were rich externalised learner state, programmatic policy actions, and counterfactual replay. P2.1 falsified the bilateral elaboration; P2.2 reversed the state-richness prediction and pinned the residual advantage on two scalar/text fields; counterfactual replay produced only a messy signal where it ran (high raw divergence but low family-coherence on P2.1’s two ToM cells — §6.8.5) and was a literal no-op for the P2.2 ablations (`counterfactual_total` = 0 for every P2.2 cell, the ablation architectures falling outside the runner’s profile-update set). Individually each is a finding; collectively they say the elaborations the harness made testable did not behave as the architecture assumed.
- *P2.3 (the crossover cells) is retired, not deferred.* The pre-registered fan-out scheduled two further cells (`cell_121`, `cell_122`) for a P2.3 crossover test; P2.1’s null and P2.2’s reversal have substantially weakened the hypothesis those cells were built to probe, so running them on the original schedule would be sunk-cost behaviour and the arc closes here rather than carrying an open P2.3 tail. (If a crossover question is revived it should follow a fresh decision about what it now answers, not the original plan.)

Relation to §6.3.9 and §6.7. This arc does not reverse §6.3.9’s central finding — the insight-action gap is structural under lightweight intervention and only suggestively mitigable by expensive search. It *extends* it: a heavy externalised-state architecture is the first thing in the project to produce a measurable shift on an instrument sensitive enough to see one, but the shift is moderate, channel-specific, confounded, and — the part that matters for the mechanism story — it *survives stripping the architecture down to a two-field profile*, which is not what a “rich learner model drives adaptation” hypothesis predicts. Read with §6.7, the pattern rhymes: the id-director family found charismatic-pedagogical authorship could be operationalised but that mechanism stacks sit *inside* the Pareto frontier rather than pushing it out (§6.7’s synthesis); the adaptive-runner family found adaptive strategy selection could be operationalised but that the architecture’s elaborations mostly did not pay. In both arcs the durable result is the apparatus — the id-construction trace and the charisma rubric in §6.7, the trap suite and the dual scoring paths here — and the architectural elaborations the apparatus made legible came back null, negative, or inverted more often than not. That is a finding about how hard it is to make these elaborations pay, reported as such, in the spirit of §5.12.6’s instruction that mixed and negative outcomes are reported rather than patched into re-ordered hypotheses.

Status (per §5.12.6). §6.8.8 introduces no new numbers; it synthesises §6.8.1–§6.8.7 (themselves a mix of pre-registered confirmatory — §6.8.3, §6.8.5 — and post-hoc exploratory — §6.8.4, §6.8.6, and §6.8.7’s `cell_124/cell_125` cross-suite cells — tiers, with §6.8.7’s §6.3-null reconciliation a no-new-data synthesis layered over those new exploratory cells). No alpha

correction applies to a synthesis. The retirement of P2.3 is a scope decision, recorded here so the pre-registered fan-out’s open items are accounted for rather than silently dropped.

6.9 Evidence-Bound Hypothesis Tracking: An Orthogonal Extension to the State-Policy Architecture (A14)

This subsection reports a separate architectural-extension arc, run on the same Lang-Graph runner as §6.8 but addressing a different gap. §6.8 asked whether an externalised `learnerProfile` plus a programmatic policy graph produces measurable strategy shifts on a trap-scenario instrument. §6.9 asks a discipline question, not a behaviour question: *when the tutor maintains a model of the learner, can the controller force every claim in that model to be cited against verbatim evidence from the dialogue?* The §6.8 `learnerProfile` is a single object whose fields (“the learner has misconception X”, “confidence is 0.4”) are written each turn without an audit trail — there is no way, from the persisted trace, to ask *what learner utterance the tutor’s claim about misconception X is grounded in*. The §6.8.6 state-richness reversal is one consequence of that opacity: a richer profile did not improve strategy selection partly because the apparatus could not tell whether the additional fields were tracking the learner or accumulating tutor speculation. §6.9 is the first stage of a longer-horizon answer (the A14 arc in `TODO.md`): replace the unstructured profile-write with an append-only observation ledger and a typed-hypothesis layer whose claims must reference ledger entries by id.

The arc reaches a stable resting point at the end of this subsection: three graph nodes (extractor, updater, validator) are implemented and verified on a small ($N = 3$ scenario) real-LLM smoke; a paired ablation between `cell_126` (updater only) and `cell_127` (updater plus validator) on the two scenarios that both cells ran cleanly measures the validator’s marginal contribution; and a Stage 5 pedagogical-outcome scoring of all three evidence-bound cells at pooled $N \approx 33$ against §6.8’s binary and graded instruments (§6.9.7) closes the arc. Per §5.12.6, what follows is *post-hoc, exploratory, and infrastructural*: no pre-registration, no hypothesis test, with the §6.8-vs-§6.9 comparison added at Stage 5 (§6.9.7) as a post-hoc exploratory contrast. The contribution is mechanism availability — the apparatus needed to ask grounding-discipline questions in later work — together with one mechanism finding in hand (asymmetric attribution of status verdicts between the updater and validator layers; §6.9.5–§6.9.6) and a Stage 5 pedagogical-outcome reading (§6.9.7) that is negative-leaning on the apparatus as a whole: the audit chain does not pay in §6.8’s strategy-shift coin, and applied to §6.8.6’s best configuration it is net-negative on both the binary and graded channels. §6.9.8 then steps outside A14 specifically to close the broader §6.8.8/§6.9 question across the *realisations* of a `state` $\rightarrow$ `action` policy — implicit forward pass, hand-authored nodes, and a policy *fitted* to the independent outcome — with the one lever the arc had not yet pulled, killed offline before any live run.

6.9.1 Method: Append-Only Ledger, Typed Hypotheses with TTL Two state-schema additions extend the §6.8 `AdaptiveTutorState` (see `services/adaptiveTutor/stateSchema.js`). The first is `evidenceLog` — an append-only ledger reduced by concatenation. Each entry

carries an `obs_id` (content-derived sha1 prefix, stable across counterfactual replay branches), the `turn` index, a verbatim quote span from the dialogue, a `type` tag drawn from a fixed enum (`learner_self_report`, `learner_action`, `learner_question`, `learner_correction`, `tutor_inference`), and a `validated` boolean set by a substring-match gate (described below). The reducer is append-only so the audit trail cannot be silently rewritten by a later turn.

The second is `hypotheses` — typed tentative claims about the learner, reduced by merge-by-id (last write wins per `hypothesis_id`). Each hypothesis carries a `claim` string, a `confidence` in $[0, 1]$, two arrays of `obs_id` references (`supporting_evidence` and `contradicting_evidence`), a `status` from `{tentative, validated, contradicted, expired}`, and TTL metadata as the pair (`created_at_turn`, `expires_after_turns`) rather than an absolute `expires_at_turn` — storing the offset keeps creation metadata immutable under counterfactual replay, where turn counters can branch. The merge-by-id reducer is the design’s key commitment: a hypothesis revised on turn $t + 1$ overwrites the same entry rather than appending a parallel claim, so the persisted state reflects the controller’s current best guess rather than its full history of guesses.

Two new graph nodes operate on these fields. The *evidence extractor* runs each turn after a learner utterance and before the existing profile-update path; it asks the model to return verbatim quotes typed by the enum above. The node then enforces a substring-match gate: each candidate quote is checked against the cumulative dialogue text, and `validated` is set to `true` only if the gate passes (the entry is retained either way, so hallucinated quotes are recorded for audit rather than silently discarded). The *hypothesis updater* runs immediately after the extractor and consumes only the validated subset of the ledger together with the current `hypotheses` list. It is prompted to revise existing entries (remit the same `hypothesis_id` when extending support, mark `contradicted` when the new evidence undermines an earlier claim) rather than mint new claims that paraphrase old ones, and to return an empty array when the evidence will not support any tentative inference. The node owns three pieces of bookkeeping the LLM is not trusted with: it derives a stable `hypothesis_id` from the `claim` text when the model leaves the field blank, it filters `supporting_evidence` and `contradicting_evidence` against the set of valid `obs_ids` so the LLM cannot invent references, and it sweeps for TTL expiry (transitions `tentative` $\rightarrow$ `expired` when `turn > created_at_turn + expires_after_turns`). The “node owns bookkeeping; the LLM owns judgment” split is the same pattern §6.7’s id-director engine uses to constrain charismatic-persona authorship to a structured envelope.

A new cell `cell_126_state_policy_evidence_bound` registers the extension. Its `adaptive.architecture` is `state_policy_evidence_bound` — the existing `state_policy` graph (§6.8.2) extended with the extractor and updater nodes wired ahead of the profile-update path. All other cells in §6.8 remain unaffected: the schema additions default to empty arrays and the new nodes only run under the `state_policy_evidence_bound` architecture flag.

6.9.2 Stage 2 Verification: 100% Verifiable Quotes, 100% Grounded Hypotheses on Three Trap Scenarios A real-LLM smoke (`scripts/run-adaptive-cell-real-smoke.js`,

claude-code/sonnet backend, $N = 3$ scenarios $\times$ 2 branches = 6 dialogues) tested the extractor (Stage 2a) and the updater (Stage 2b) jointly on three v1 trap scenarios spanning the agency-signal range — `false_confusion_v1` (compliant), `resistance_to_insight_v1` (resistant), `sophistication_upgrade_v1` (questioning).

Stage	Metric	Result	Pre-registered?
2a	Verifiable-quote rate (validated entries / total entries)	128 / 128 = 100.0%	No — internal calibration target was $\geq 95\%$
2b	Grounded-hypothesis rate (hypotheses with ≥ 1 supporting <code>obs_id</code> / total hypotheses)	53 / 53 = 100.0%	No — internal soft gate was $\geq 70\%$

Both rates clear their internal calibration targets. Extraction fires across all turns of all three scenarios (per-turn breakdown: every k -of- k on every turn), with no quote failing the substring-match gate. Hypothesis synthesis is also active rather than degenerate: across the three scenarios the updater emits 13, 16, and 24 hypotheses respectively (mean claim length 196–254 characters; status distribution shows 18 of 53 marked `contradicted` rather than `tentative`, so the model uses the enum to retire claims rather than letting them silently rot), and every hypothesis carries at least one valid `obs_id` reference into the ledger. These are the lower bars Stage 2 was designed to clear: *the controller can build a verifiable evidence ledger and the updater consistently cites it.*

The numbers come from a $N = 3$ smoke, not a study; they speak to the implementation passing its own verification gates, not to any pedagogical claim. Generalisation to the full eight-scenario v1 suite or to cross-suite trap stimuli (the §6.8.7 instrument) is not yet measured.

6.9.3 Limitation Surfaced by the Verification: Revision Versus Duplication A separate signal in the same smoke is informative for what Stage 3 has to do but is not itself a Stage 2 result. The merge-by-id reducer collapses two hypothesis records into one only when their `hypothesis_id` strings match. The updater is prompted to re-emit prior turn ids when extending or contradicting an existing claim, and the node derives a stable id from the `claim` text when the LLM omits it. The smoke shows the reducer is rarely firing: on `sophistication_upgrade_v1`, 24 distinct `hypothesis_ids` survive across a 4-turn $\times$ 2-branch dialogue, with `created_at_turn` spread `[0, 0, 1, 1, 1, 1, 2, 2, 2, 3, 3, 3]` on each branch. That is the same count of survivors as proposals, indicating the model produces fresh claim text on each turn rather than rewriting yesterday’s — the content-derived id then differs, and the reducer treats the new claim as a new entity. The grounded-rate gate (Stage 2b’s 70% soft target) does not catch this failure mode because it asks “is each claim grounded?”, not “is the same claim being maintained across turns?”

This is reported as a limitation, not a result. Three observations bound how it should be read. First, it is what the design predicted Stage 3 would have to take on: the

`groundingValidator` node planned for that stage will retain or retire hypotheses against the ledger across turns, which is the natural place to instrument revision-vs-duplication directly. Second, the status discipline observed at Stage 2b (18 of 53 hypotheses `contradicted` rather than `tentative`) is evidence that the model uses the typed-status machinery when prompted to — the duplication is not “the model ignores the schema” but “the model writes new claims when an update prompt would have been a better fit”. Third, the apparatus needed to *measure* revision-vs-duplication crisply does not yet exist either: `extractTurnTrace` (`services/adaptiveTutor/persistence.js`) captures terminal `evidenceLog` and `hypotheses` but not per-turn snapshots, so the count of distinct survivors is a proxy for revision rate, not a direct measurement. Closing that proxy gap is logged as Stage 3 work.

6.9.4 What is Defensible; What is Not What §6.9 establishes is narrow and infrastructural. The state schema for an audited learner model — ledger, typed hypotheses, TTL semantics, content-derived ids stable across counterfactual replay — exists and is reducer-correct. Two new graph nodes (`evidenceExtractor` with substring-match validation gate; `hypothesisUpdater` with node-owned bookkeeping for id derivation, evidence-ref filtering, and TTL sweep) operate on a fresh `state_policy_evidence_bound` architecture; both are exercised in mock and real-LLM smokes. On a $N = 3$ real-LLM verification the extractor emits 100% substring-verifiable quotes and the updater emits 100% ledger-grounded hypotheses, clearing the calibration targets the implementation was built to. The contribution is the apparatus, in the same sense §6.8.8 means it: the §6.9 cell adds a layer the apparatus could not previously ask the question about, not a result about whether the layer helps pedagogically.

What §6.9 does not establish is anything about pedagogical outcome (the evidence-bound cell has not been scored on the binary or graded instruments of §6.8, and would need to be at $N \approx 24$ –32 before such a comparison would be informative), nothing about whether the discipline survives a stronger ablation more broadly (varied scenario types, different judge models, longer dialogues), and — as §6.9.5 develops — a single-sided Stage 3 measurement on `cell_127` but no matched `cell_126` status-distribution on the same scenarios from which to read the validator’s *marginal* contribution beyond what a well-tuned updater alone does. The Stage 3 architecture (`state_policy_evidence_bound_validated`) and its paired cell (`cell_127_state_policy_evidence_bound_validated`) are now implemented — the `groundingValidator` graph node downstream of the updater promotes hypotheses with ≥ 3 supporting `obs_ids` and no contradiction to `validated`, and retires hypotheses with ≥ 1 contradicting `obs_id` and confidence below 0.4 to `contradicted` — and §6.9.5 reports the first real-LLM smoke through that chain. The honest claim across §6.9 remains that a mechanism is becoming *available*, and §6.9.5 adds that the cheap-verifier layer fires non-trivially on the available material; neither claim is about pedagogical payoff.

6.9.5 Stage 3 Result: Grounding-Validator Reshapes Terminal Status Distribution A real-LLM smoke on `cell_127_state_policy_evidence_bound_validated` (`claude-code/sonnet`, the same $N = 3$ trap scenarios as the Stage 2 smoke — `false_confusion_v1`, `resistance_to_insight_v1`, `sophistication_upgrade_v1` — with `ADAPTIVE_TUTOR_CLI_TRACE=1` for per-call diagnostic visibility) ran the full chain (`evidenceExtractor` → `hypothesisUpdater` → `groundingValidator` → `learnerProfileUpdate` → tutor ego/superego),

and yields the following terminal-state distribution across 26 hypotheses synthesized over the three scenarios:

Status	Count	Fraction
validated	13	50%
contradicted	9	35%
tentative	4	15%

Stages 2a and 2b clear at the same rates as the Stage 2 smoke ($120/120 = 100\%$ substring-verifiable quotes; $26/26 = 100\%$ ledger-grounded hypotheses), and the revision rate is $20/22 = 90.9\%$, statistically indistinguishable from the `cell_126` post-tune baseline at 92.9% : adding the validator does not break the upstream updater’s revision discipline. What it adds is the status-discipline column. Of the 26 hypotheses the updater produced, the validator emitted a retain or retire verdict on 22 (85%) and stayed silent on 4 (15%) — the SILENCE-by-default convention is doing its work, and the 50/35 promote/retire split shows the verifier is not one-sidedly stamping things **validated**. Per-scenario the same shape holds: `sophistication_upgrade_v1` (the trap the prior Stage 2 smoke could not complete) lands at 12 hypotheses with 8 validated, 2 contradicted, 2 tentative — the heaviest validation load and also the heaviest revision rate ($9/10 = 90\%$). The architecture-stress contrast carries through.

A latency note speaks to the design intent. Median per-call latencies under `claude-code/sonnet` are: `hypothesisUpdater` ~100s, `learnerProfileUpdate` ~50s, `tutorEgoInitial` ~45s, `groundingValidator` ~18s, with `learnerTurn` / `tutorSuperego` / `evidenceExtractor` all near 20s. The validator’s per-call cost is roughly $5\times$ cheaper than the upstream `hypothesisUpdater` it audits, consistent with the cheap-verifier-after-expensive-synthesizer pattern the architecture was built to: high-cost generation feeding low-cost validation, with the validator’s verdict-only contract (status transitions only, no rewriting of hypothesis content) holding the budget down.

A paired-ablation run on `cell_126` (validator off; same `claude-code/sonnet` backend; same trap-scenario inputs) measures the marginal contribution. The Stage 2 `cell_126` smoke at commit `1e02510` reported only aggregate revision rate, so a re-run was needed to capture the terminal status distribution. Two of the three scenarios completed cleanly; `sophistication_upgrade_v1` crashed on a Zod schema-strictness bug (`evidenceExtractor` emitted `quote: null` for a `tutor_inference` entry; the graph node at `services/adaptiveTutor/graph.js:371` already coerces null quotes to empty strings — the substring-match gate then correctly marks the entry `validated=false` — but the schema rejected the null upstream). Loosened to `quote: z.string().nullable()` with the rationale documented inline. The matched comparison reads off the two scenarios both cells ran cleanly:

Cell	<i>N</i> scenarios	Hypotheses	validated	contradicted	tentative
<code>cell_126</code> (updater only)	2	19	0 (0.0%)	5 (26.3%)	14 (73.7%)

Cell	N scenarios	Hypotheses	validated	contradicted	tentative
cell_127 (updater + validator)	2	14	5 (35.7%)	7 (50.0%)	2 (14.3%)

Three patterns are visible. (i) **validated is wholly validator-driven**. The updater alone produces zero **validated** outcomes across 19 hypotheses on the same scenarios — every **validated** verdict in `cell_127` is attributable to the `groundingValidator` layer, not to a status field the upstream `hypothesisUpdater` was emitting unaided. The mock-mode rule (≥ 3 supporting `obs_ids` + no contradiction $\rightarrow$ promote) is being exercised on real-LLM output. (ii) **contradicted is partly shared, not wholly validator-driven**. `cell_126` produces 5 **contradicted** hypotheses unaided; `cell_127` produces 7. The updater itself uses the typed-status machinery to retire claims when prompted to — the validator adds to the retirement count rather than monopolizing it. (iii) **Uncertainty drops sharply**. `cell_126`’s 73.7% **tentative** collapses to 14.3% in `cell_127`: the validator converts about 59 percentage points of unresolved status into typed verdicts (split roughly 35 pp promotion / 24 pp retirement). The asymmetry — wholly-validator-driven promotion, shared retirement — is the operational reading of the verdict-only contract: the validator’s promotion threshold (≥ 3 supporting refs, no contradiction) requires evidence accumulation across turns that the updater’s single-turn synthesis prompt does not gather, while retirement is reachable from either layer once a contradicting `obs_id` exists.

What §6.9.5 *does* establish: the validator fires on the available material, with verdicts of both kinds, at a cost meaningfully lower than the layer it audits, without disturbing the revision discipline upstream; and on the matched two-scenario subset, the validator is the sole source of **validated** verdicts and a non-trivial additional source of **contradicted** ones. What it does *not* establish: any pedagogical-outcome claim (the chain has not been scored on the §6.8 binary or graded instruments, and would need to be at $N \approx 24\text{--}32$ before such a comparison would be informative); generalisation beyond the two matched scenarios (`sophistication_upgrade_v1` is the heaviest-load trap in the suite and the validator’s contribution there is unmeasured at the paired level — only the single-sided `cell_127` reading at 8 **validated** / 2 **contradicted** / 2 **tentative** is in hand); robustness across judge models or generation backends; and whether the validator’s verdict-rate would survive scenarios where the upstream updater is *already* well-tuned to emit **validated** directly. The defensible claim is mechanism-level: a cheap verifier downstream of an expensive synthesizer measurably reshapes the terminal status distribution on this material, with promotion as its unique contribution.

A methods note resolves a separate open item (TODO.md task #34) raised by the Stage 2b smoke. That earlier run was reported as “hanging silently for 48 minutes” on the third trap scenario. With per-call CLI tracing now on, the `cell_127` smoke ran the same scenario set to completion in ~100 minutes wallclock without any individual role-call exceeding the 6-minute CLI subprocess timeout; the longest single call was 134s (`hypothesisUpdater` on `sophistication_upgrade_v1`). The prior report was a misdiagnosis. The earlier smoke was not hung but slow: many sub-6-minute calls compounded into a wallclock window that

exceeded the operator’s patience before any of them tripped the existing timeout. The instrumentation added in `services/adaptiveTutor/realLLM.js` (env-gated `ADAPTIVE_TUTOR_CLI_TRACE=1` start/done lines per CLI call, plus an unconditional stderr line on timeout-fire with role, elapsed, output-bytes, and first-byte timing) closes the diagnostic gap that produced the silent-wait failure mode. Future hangs surface a role + duration + stream-state signal in real time rather than after the fact.

6.9.6 Stage 3 Synthesis: The Audit Chain Works; the Pedagogical Question Is Settled in §6.9.7

Stepping back from the cell-by-cell results to the discipline question §6.9 opened with — when the tutor maintains a model of the learner, can the controller force every claim in that model to be cited against verbatim evidence from the dialogue? — the answer is *yes, on three trap scenarios, with every internal gate clearing and a clean mechanism finding about how the chain decomposes; but no pedagogical-outcome link to the §6.3 adaptive-responsiveness null or §6.8’s strategy-shift instrument has been measured*. Like §6.8.8 and §6.7 before it, the durable result is the apparatus; unlike §6.8.8, the apparatus has already produced a substantive mechanism finding (asymmetric attribution; §6.9.5) even before any pedagogical test has been attempted.

What is defensible. Four findings survive their caveats:

1. *The three-stage audit chain holds on real-LLM material.* On three trap scenarios (`false_confusion_v1`, `resistance_to_insight_v1`, `sophistication_upgrade_v1`) under `claude-code/sonnet`, Stage 2a clears at $128/128 = 100\%$ substring-verifiable quotes (§6.9.2), Stage 2b at $53/53 = 100\%$ ledger-grounded hypotheses (§6.9.2), and Stage 3 produces a non-trivial verdict distribution (13 `validated` / 9 `contradicted` / 4 `tentative` across 26 hypotheses on `cell_127` at $N = 3$; 85% non-silent verdicts; §6.9.5). The “node owns bookkeeping; the LLM owns judgment” division (id derivation, evidence-ref filtering, TTL sweep on the node side; quote selection, claim synthesis, status verdict on the LLM side) operates cleanly across the chain.
2. *Validator marginal contribution is wholly-promotion, partly-retirement.* The matched $N = 2$ paired ablation against `cell_126` (validator off; same scenarios, same backend; §6.9.5) reads: `cell_126` produces 0 `validated` / 5 `contradicted` / 14 `tentative` across 19 hypotheses; `cell_127` on the same two scenarios produces 5 `validated` / 7 `contradicted` / 2 `tentative` across 14 hypotheses. The validator is the wholly-attributable source of `validated` promotions ($0 \rightarrow 5$) and a non-trivial additional source of `contradicted` retirements ($5 \rightarrow 7$), with ~59 percentage points of `tentative` collapsing into typed verdicts. The asymmetry is mechanism-level: the validator’s promotion threshold (≥ 3 supporting `obs_ids`, no contradiction) requires multi-turn evidence accumulation the updater’s single-turn synthesis prompt does not perform; retirement is reachable from either layer once a contradicting `obs_id` exists.
3. *The cheap-verifier-after-expensive-synthesizer pattern is empirically demonstrated.* Median per-call latency under `claude-code/sonnet`: `hypothesisUpdater` ~100s, `groundingValidator` ~18s — the validator costs roughly $5\times$ less per call than the layer it audits (§6.9.5). The verdict-only contract enforced by the Zod schema (LLM owns

the status transition only; the graph node preserves `claim`, `supporting_evidence`, `contradicting_evidence`, TTL metadata) keeps the validator’s per-call budget tight and prevents it from rewriting hypothesis content. The pattern generalises beyond this specific chain: any agent architecture with a expensive-generator-followed-by-cheap-verifier shape can use the verdict-only contract to bound the verifier’s responsibility surface.

4. *Task #34 misdiagnosis resolved via per-call instrumentation.* The Stage 2b smoke’s “48-minute silent hang” turned out to be a slow-not-hung condition: many sub-6-minute role-calls compounded into a wallclock that exceeded operator patience without any individual call tripping the existing CLI subprocess timeout. The env-gated `ADAPTIVE_TUTOR_CLI_TRACE=1` start/done log lines plus the unconditional stderr line on timeout-fire (commit 62fa729) close the diagnostic gap; future hangs surface a role + duration + stream-state signal in real time rather than after the fact (§6.9.5 methods note).

What is not established. Four gaps bound the arc as it closes:

- *Pedagogical-outcome scoring — now run (§6.9.7), and negative-leaning.* As of Stage 5 the chain *has* been scored against §6.8’s binary `strict_shift` and 4-dimension graded instruments at pooled $N \approx 33$ on all three evidence-bound cells. The result (§6.9.7): the validator’s binary gain over the updater-only `cell_126` (+12 pp) does not survive the graded channel (+0.01 overall — a `cell_123`-style binary/graded divergence in the §6.8.6 sense), and the audit chain applied to §6.8.6’s winning `cell_118` minimal profile (`cell_128`) is net-negative on both channels (−10 pp binary, −0.21 graded). §6.9’s contribution is therefore mechanism availability + one mechanism finding *plus* a complete negative pedagogical-outcome reading — not an open gap.
- *Generalisation beyond the matched $N = 2$ subset.* The paired-ablation table is anchored on `false_confusion_v1` and `resistance_to_insight_v1`. The third scenario, `sophistication_upgrade_v1`, has only single-sided `cell_127` data (the `cell_126` run on that scenario crashed on a Zod-schema strictness issue, now fixed at `services/adaptiveTutor/realLLM.js:478`). Whether the asymmetric-attribution finding survives the heaviest-load trap in the suite is unmeasured at the paired level.
- *Robustness across judge models, generation backends, or scenarios where the updater already emits `validated` directly.* The internal calibration rates and the paired ablation come from a single backend (`claude-code/sonnet`) and a single scenario family (the v1 trap suite). Whether the validator’s verdict-rate would survive a different generation backend, or scenarios where the upstream updater’s prompt is already well-tuned enough to emit `validated` unaided, is unmeasured.
- *Whether revision-vs-duplication (§6.9.3’s limitation) is improved by the validator.* The Stage 2b smoke surfaced a duplication failure mode (the merge-by-id reducer rarely fires; the updater produces fresh claim text each turn rather than rewriting prior claims). The Stage 3 smoke reports a 90.9% revision rate on `cell_127` versus the 92.9% `cell_126` post-tune baseline — statistically indistinguishable, so the validator does not break the upstream updater’s revision discipline (§6.9.5), but neither does it visibly improve it. The duplication-vs-revision story is not yet a story; it is a flat

reading at the rates the updater was tuned to.

Relation to §6.8.8 and §7.4. §6.8.8 closed on *the apparatus is the contribution; the elaborations mostly are not*. §6.9 fits the same motif with a marginal upgrade: the apparatus has produced a clean mechanism finding (asymmetric attribution) even before any pedagogical-outcome link is shown, and that finding has a sharp, falsifiable shape (the validator is the *sole* source of `validated` outcomes on the matched subset; `cell_126` emits zero out of nineteen unaided). Read alongside §6.8 and §6.7, the pattern again rhymes: in all three arcs the durable result is the instrument or the typed trace, not the architectural elaboration; in §6.9’s case the instrument has also surfaced one mechanism asymmetry the elaboration was built on, which is more than §6.8.8 could say of the bilateral-ToM or state-richness elaborations. Whether the asymmetry pays in §6.8’s adaptive-responsiveness coin is answered in §6.9.7: it does not. The validator’s promotion monopoly has a binary-channel correlate (a +12-point `strict_shift` gain over `cell_126`) but no graded-channel one (+0.01 overall), and the full apparatus applied to §6.8.6’s best configuration is net-negative on both — the elaboration is mechanism-clean but pedagogically inert-to-negative.

Status (per §5.12.6). §6.9 is post-hoc, exploratory, infrastructural, and not pre-registered. No alpha correction applies. This subsection is the *Stage-3* synthesis (three-stage architectural feasibility plus the paired-ablation marginal-contribution measurement); the arc’s resting point is Stage 5 (§6.9.7), which adds the pedagogical-outcome scoring at pooled $N \approx 33$ against the §6.8 binary and graded instruments. The cross-reference-not-comparison scope stated here applied to the Stage-3 synthesis as it stood; §6.9.7 offers the §6.8-vs-§6.9 cell contrast explicitly and supersedes this paragraph on that point.

6.9.7 Stage 5 Result: The Validator’s Binary Gain Does Not Survive the Graded Channel, and the Audit Chain Degrades §6.8.6’s Best Configuration

The §6.9.6 synthesis closed the Stage-3 arc at mechanism availability and named one outstanding measurement: pedagogical-outcome scoring against the §6.8 instruments. Stage 5 runs it. All three evidence-bound cells were scored at pooled $N \approx 33$ on the v1 trap suite (`config/adaptive-trap-scenarios.yaml` — the §6.8.6 instrument) along both §6.8 paths: the binary `strict_shift` (`scripts/analyze-strategy-shift.js`, single-judge `claude-code/sonnet`) and the 4-dimension graded rubric (`scripts/grade-adaptive-dialogue.js`, single-judge GPT-5/codex, grader v1.0) — the identical instruments and judges §6.8.3–§6.8.7 used, so the numbers drop directly alongside the §6.8.6 ablation table. `cell_126_state_policy_evidence_bound` is the evidence-ledger + `hypothesisUpdater` chain with the validator *off*; `cell_127_state_policy_evidence_bound_validated` adds the `groundingValidator`; `cell_128_state_policy_minimal_profile_evidence_bound_validated` runs the same validated chain on `cell_118`’s minimal-profile projection (`{confidence, lastEvidence}`), making it the directly audited counterpart of §6.8.6’s winning cell. The two readings prefigured for this stage — (a) does evidence-bound discipline beat the §6.8 baselines; (b) does the validator add a pedagogical-outcome gain over the updater-only cell — are answered, both negative-leaning, and the binary and graded channels diverge exactly as §6.8.4/§6.8.6 warned they can.

Cell	Chain	N	strict_shift	family-match	Graded overall (T / E / Q / C)
cell_126 (evidence_ bound, validator off)	extractor → updater	33	42.4% (14/33)	90.9%	3.84 (3.76 / 3.39 / 4.18 / 4.03)
cell_127 (evidence_ bound_ validated)	+ grounding- Validator	33	54.5% (18/33)	93.9%	3.85 (3.76 / 3.52 / 4.12 / 4.00)
cell_128 (minimal_ profile..._ validated) — §6.8 baselines (same instruments, same judges)	validated chain on cell_ 118’s profile	34	58.8% (20/34)	100%	4.13 (4.09 / 3.91 / 4.32 / 4.21)
cell_110 (state_ policy, full; §6.8.3)	—	23	47.8%	87.0%	4.03 (4.26 / 4.30 / 3.96 / 3.61)
cell_118 (minimal_ profile, unaudited; §6.8.6)	—	32	68.8%	96.9%	4.34 (4.34 / 4.28 / 4.41 / 4.34)
cell_124 (state_ policy cross-suite; §6.8.7)	—	24	62.5%	66.7%	4.22

(T / E / Q / C as in §6.8.6; binary under `claude-code/sonnet`, graded under GPT-5/codex. Within-action refinement is 100% on all three evidence-bound cells — 50 / 44 / 60 same-action turns whose message text changed non-trivially — so the binary fire-rate is measured against genuinely re-authored prose, not a degenerate constant. Counterfactual replay is *active* for these architectures, unlike §6.8.6’s no-op P2.2 cells, with counterfactual-divergence 93.9 / 97.0 / 88.2%.)

Reading (b): the validator’s binary gain does not survive the graded channel. On the binary instrument the validator pays and the family-discipline signal tightens monotonically: cell_126 42.4% → cell_127 54.5% (+12.1 pp) → cell_128 58.8% (+16.4 pp over cell_

126), with family-match climbing $90.9 \rightarrow 93.9 \rightarrow 100\%$. That is the pedagogical-outcome correlate §6.9.6’s asymmetric-attribution finding (the validator wholly owns **validated** promotion) predicted on the channel built to detect *which move, when*. But the graded channel — the load-bearing direction signal per §6.8.6’s template — does not corroborate it for **cell_127**: graded overall is **3.84** $\rightarrow$ **3.85**, a +0.01 null, no dimension moving more than the +0.13 on **strategy_execution** (itself offset by -0.06 on **strategy_quality** and -0.03 on **pedagogical_coherence**). The validator’s +12-point binary gain buys no measurable improvement in the execution, quality, or coherence of the resulting teaching. This is precisely the within-P2.2 pattern §6.8.6 isolated in **cell_123** — top on binary, flat on graded — and the cross-architecture pattern of §6.8.4 (**cell_114**): the binary instrument registers a move-selection change the graded rubric does not see as better teaching. The lone cell that moves *both* needles is **cell_128**: 58.8% binary (top of the three) and 4.13 graded (top, +0.29 over **cell_126**, every dimension up) — structurally the same “only the lean configuration is robust across both instruments” shape §6.8.6 found in **cell_118**.

Reading (a): the audit chain does not reach the §6.8 baselines, and it degrades §6.8.6’s best configuration on both channels. The evidence-ledger + updater layer *without* the validator (**cell_126**) sits *below* the plain **state_policy** baseline on both instruments — binary 42.4% vs **cell_110**’s 47.8% (-5.4 pp), graded 3.84 vs 4.03 (-0.19) — so the extractor + updater apparatus is net-negative absent the verifier. Adding the validator lifts **cell_127/cell_128** over **cell_110** on binary (54.5 / 58.8% vs 47.8%) but no evidence-bound cell reaches **cell_124**’s 62.5% cross-suite mark or **cell_118**’s 68.8%, and none matches **cell_118**’s 4.34 graded. The sharpest comparison is the direct one: **cell_128** *is* §6.8.6’s winning minimal profile with the A14 audit chain bolted on, and it scores **58.8% / 4.13 against the unaudited cell_118’s 68.8% / 4.34** — the audit apparatus, applied to the single configuration §6.8.6 found most favourable, costs -10 pp binary and -0.21 graded. The apparatus does not merely fail to unlock §6.8.6’s headroom; on the configuration that *had* the headroom, it spends it.

Trust-vs-load resolves to load, on the load-bearing channel. The arc opened (§6.9, §6.9.6) on whether forcing every claim in the learner model to cite verbatim evidence would *unlock* strategy-shift performance (trust) or *tax* it without payoff (load). Stage 5 answers: load, on the graded channel §6.8.6 designated load-bearing. The grounding apparatus is mechanism-clean — §6.9.5’s asymmetric-attribution finding is real and replicates the verdict-only-contract design — but it is pedagogically inert-to-negative: the ledger+updater layer is below the plain baseline; the validator buys a binary-only tightening the graded judge does not read as better teaching; and the whole chain, applied to §6.8.6’s best cell, makes it worse on both instruments. This is the §6.8.8 motif once more — *the apparatus is the contribution; the elaboration does not pay* — now with A14’s evidence-binding as the elaboration, and read alongside the §6.8.6 state-richness reversal it sharpens that section’s lesson: the strategy-shift headroom lives in a *lean* learner profile, and neither enriching it (§6.8.6) nor auditing it (here) recovers it. The §6.9 arc therefore closes mechanism-positive and pedagogical-outcome-negative — a complete finding for the arc in exactly the sense its plan anticipated, not a deferral.

Status and caveats (per §5.12.6). Post-hoc, exploratory, not pre-registered (A14 is an infras-

structural arc; Stage 5 was a named deliverable, not a §5.12.2-style pre-registration — no alpha correction across the two readings). Pooled N per cell across run-ids per the §6.8.6 norm: `cell_126` = 33, `cell_127` = 33, `cell_128` = 34 (100 dialogues; 0 grader errors). Single judge per channel — binary `claude-code/sonnet`, graded GPT-5/codex (grader v1.0) — with **no second-judge calibration for the Stage 5 pool**: §5.12.4’s Gemini inter-rater check covered cells 110/118/119 only, so the graded numbers here carry the same single-judge GPT-5 caveat §6.8.6 attaches to `cell_120/cell_123`. Per §6.8.6’s statistical template the binary channel is treated as wide-CI — the +12.1-pp `cell_126`→`cell_127` gap at $N \approx 33$ is the high end of a wide interval (label-permutation $p \approx 0.10$ for a gap of this size at this N , by the §6.8.6 calibration), which is *why* the graded null is the decisive reading rather than the binary lift: the load-bearing channel shows no gain. §5.12.4-limitation-1 (rubric authored non-blind to the cells-110/118/119 binary results) applies only weakly here — the Stage 5 cells post-date the rubric’s design, so the graded instrument was fixed before their data existed, a cleaner application than §6.8.6’s own. Counterfactual replay is *active* for the evidence-bound architectures (they are in the runner’s profile-update set; counterfactual-divergence reported above), unlike §6.8.6’s no-op P2.2 cells. The §6.8-vs-§6.9 comparison §6.9.6’s Status paragraph declined to offer for the Stage-3 synthesis is offered here explicitly; §6.9.7 supersedes that scope note on that point.

6.9.8 Synthesis: The Learned-Policy Lever — the Last Distinct `state`→`action` Realisation — Also Does Not Pay (Offline Kill Gate) §6.9.7 closed A14’s evidence-bound arc on the §6.8.8 motif. This subsection closes the broader question that motif raises. §6.8 exhibited an *implicit* `state` → `action` policy (the LLM forward pass conditioned on an externalised learner profile); §6.9.1–§6.9.7 a *hand-authored* one (typed graph nodes); both are mechanism-clean and pedagogically inert-to-negative on the architecture-independent instruments. One realisation had not been tried: a policy *fitted* to the independent outcome from logged data, rather than implicit in the forward pass or written by hand — “the only path on which adaptation would mean what it says”, in the closed-loop persona critique’s phrase. §6.9.8 takes it under a kill gate pre-registered (`LEARNED-ADAPTATION-PLAN.md`, repo root) to be **offline, zero-API, and read-only on traces already on main**, so that a null costs nothing and *completes* the realisation-space synthesis rather than opening a new arc.

Method (offline, $\approx$ \$0, read-only). `scripts/learned-adaptation-harvest.js` walks the existing `cell_110/118/124/126/127/128` trace files (`logs/tutor-dialogues/`) and the `evaluation_results` DB read-only, emitting one row per trajectory at its pivot decision: `context` = the A14 typed state at the pre-pivot turn (`evidenceLog/hypotheses/learnerProfile/agencySignal`, learner-profile forward-filled across empty terminal turns); the single bandit action = the pivot-turn `policyAction` family; the reward = the §6.9.7 instruments. 179 of 179 trajectories harvested. The binary label is **fidelity-asserted**: a verbatim copy of §6.9.7’s `analyzeBranch` recomputes `strict_shift`, required to equal the canonical `exports/a14-stage5-strategy-shift-finalN.json` per-cell rates to within 10^{-6} or the harvest hard-aborts. They match exactly (`cell_126` 0.4242, `cell_127` 0.5455, `cell_128` 0.5882; $\Delta = 0$), and the recovered baseline rates reproduce §6.9.7’s table to the decimal (`cell_110` 47.8%, `cell_118` 68.8%, `cell_124` 62.5%) — the label scored here is provably the §6.9.7 instrument, not a re-implementation that could drift toward a self-flattering

result. `scripts/learned-adaptation-policy-ope.py` (numpy only, no dependence on any controller-internal metric) fits the simplest policy — multinomial logistic over state features for the binary channel, ridge-linear for the graded channel — under **leave-one-scenario-type-out grouped cross-validation** (13 trap families; the policy must select from state, not memorise family identity), evaluated off-policy two ways: a Direct Method (fitted reward model) and an assumption-light on-policy-agreement value (empirical reward on the subset where the logged action family already equals the policy’s argmax). Confidence intervals are **cluster bootstrap by scenario_type** ($B = 2000$, seed 20260517) — the honest variance unit, since trajectory outcomes vary overwhelmingly *between* trap families and a row-level bootstrap would manufacture a false pass.

The pre-registered kill gate (frozen in the plan before the OPE was computed): the fitted policy must beat **both** the implicit baseline `cell_110` and A14’s hand-authored updater `cell_126`, lower 95% cluster-bootstrap CI of the difference > 0 , on the primary binary `strict_shift` label. Beating only the hand-authored cell is not a result — it is the §6.8.8 motif (“structured elaboration underperforms the strong implicit base”) reappearing, not escaped.

Off-policy contrast	vs <code>cell_110</code> (implicit base)	vs <code>cell_126</code> (A14 hand-authored)
Direct Method Δ , binary <code>strict_shift</code> (primary)	+9.0 pp, 95% CI $[-0.9, +18.0]$ — does not beat	+14.4 pp, CI $[+4.8, +23.0]$ — beats
Graded-channel Δ (corroborating)	−0.03, CI $[-0.16, +0.13]$ — does not beat	+0.16, CI $[+0.03, +0.33]$ — beats

The assumption-light cross-check agrees with the Direct Method against the implicit baseline: on the $n = 95$ agreement subset the fitted policy’s empirical value is 0.326 binary / 3.88 graded, *below* `cell_110`’s 0.478 / 4.03 on both. **The gate fails.** The fitted policy is statistically indistinguishable from the implicit in-context baseline on the load-bearing label and clears only the *weakest* A14 cell — on both channels, in agreement across two independent estimators.

Reading. This is the structural prediction of the project’s own adaptivity synthesis, now measured rather than argued: the A14 typed state largely *re-encodes* the scenario family the strong base model already conditions on in-context, so a `state` $\rightarrow$ `action` policy tested *off-family* (the grouped-CV requirement) has little headroom over the forward pass it is trying to improve. A fitted policy that matches the implicit base while beating only the thinnest hand-authored node is §6.8.6’s “only a lean configuration is robust” and §6.8.8’s “the apparatus is the contribution; the elaboration does not pay”, one level up: here the elaboration is *learning* the policy rather than writing or enriching it, and it does not pay either. In learning-analytics terms the fitted parametric `state` $\rightarrow$ `action` policy evaluated here is the *learned-policy* realisation of a learner-state backbone in the lineage of knowledge tracing (Piech et al., 2015; Scarlatos et al., 2025) — not a full mastery-posterior, learning-outcome-validated knowledge-tracing design, a distinction the null respects rather than erases; it localises where that learned learner-state backbone meets a strong in-context base.

Disposition. The realisations of a `state` $\rightarrow$ `action` policy that have been built and scored on the architecture-independent instruments — implicit (§6.8), hand-authored (§6.9.7), and now fitted-parametric (§6.9.8) — are all null relative to the implicit base; A15’s planned nearest-neighbour *retrieval* is a non-parametric sibling, designed and gated, not a counterexample. With the learned lever pulled and null the §6.8.8/§6.9.7 motif is **exhaustive over the policy realisations actually tried, not merely repeated**. This is the fourth *in-paper* convergent negative on adaptive elaboration (§6.7 id-director, §6.8.8 state-richness/bilateral-ToM, §6.9.7 A14 evidence-binding, §6.9.8 here); the archived closed-loop persona prototype is a fifth that lies outside the paper’s claim set, named for completeness only. Per the plan’s frozen kill criteria the arc closes here: the offline gate failed for free, so there is **no live confirmation run, no counterfactual stage, and no tuning retry** — a clean null *is* the closing result. Artifacts: `exports/learned-adaptation-table.csv`, `exports/learned-adaptation-{table,oqe}.meta.json`.

Status and caveats (per §5.12.6). Post-hoc and exploratory in the §6.9 sense, with one twist that strengthens it: the *kill gate* was pre-registered before the OPE was computed and was deliberately constructed to be offline and zero-API so that the decision rule could not be revised after seeing a live number — there is no live number. No alpha correction (one pre-declared primary contrast; the graded channel corroborates, it is not a second test). The off-policy estimate is identified by a Direct Method plus an assumption-light on-policy-agreement value rather than importance sampling, because the logging policy (an LLM forward pass / a hand-authored node) carries no recorded propensities; the two estimators agree on the decisive comparison (indistinguishable from `cell_110`), which is the conservative reading and the one the gate rules on. The binary label’s identity with the §6.9.7 instrument is asserted by exact recomputation ($\Delta < 10^{-6}$), closing the closed-loop-scoring failure mode by construction. Single judge per channel, inherited unchanged from §6.9.7 (binary `claude-code/sonnet`; graded GPT-5/codex grader v1.0) — this analysis introduces no new judging, only a policy fitted to already-scored outcomes. The claim is bounded: the *learned* lever does not beat the implicit base on the v1-trap-suite instruments, not that no fitted policy could help on any instrument.

6.10 Modelling the Concealed Interior — the *Signal* Axis Also Does Not Pay (Offline Kill Gate)

§6.9.8 closed the `state` $\rightarrow$ `action` arc over its *policy realisations* (implicit, hand-authored, fitted). It left one axis untested. Every in-paper negative on adaptive elaboration — §6.7 (id-director persona), §6.8.8 (state-richness / bilateral-ToM), §6.9.7 (A14 evidence-binding), §6.9.8 (fitted policy) — shares one shape: each *re-encoded what the strong base model already infers in-context from the surface transcript*. The arc’s one apparent exception was a disposable mechanism-triage prototype outside this paper’s claim set (`prototypes/adversarial-superego-mvp/`; §6.3.10): an adversarial superego with edit rights over the ego’s system prompt reliably reached the correct trap-repair move where ignorable advice did so only intermittently. The paper put exactly that mechanism to its own pre-registered test (A16, §6.3.10) on the externalised `policyAction` instrument: it produced

a *level/reliability* effect, **not** the per-turn *rate* that would escape §6.3, and the pre-registered primary nulled (S1–S0 $d = -0.167$). The arc therefore carries **no in-claim-set positive** on an architecture-independent channel. The dividing principle the convergent negatives cohere around — gains require signal the base does **not** already read in-context, not a richer restatement of what it does — is therefore the *theoretical* reading that renders the nulls intelligible, not a datapoint the arc itself licenses. This subsection tests the one signal-axis lever the arc had not pulled, under a kill gate pre-registered (ADAPTATION-PLAN-2.0.md, repo root; rationale in ADAPTATION-2.0-DIALOGUE.md) — like §6.9.8 — to be **offline, zero-API, and read-only on traces already on main**, so a null *completes* the synthesis at $\approx \$0$ rather than opening a new arc.

The candidate unread signal. The RLHF base reads the learner *at face value* (the sycophancy / agreeableness bias). The v1 trap suite is *built from* concealment cases (`polite_false_mastery`, `false_confusion`, `affective_shutdown`, `epistemic_resistance`, `answer_seeking_to_productive_struggle`) — exactly the cases where the truthful reading diverges from the surface utterance. And this study **uniquely owns the ground truth**: the learner is a full ego-superego agent (§3); only `learner/final_output` is externalised, while the hidden `learner_ego_initial` / `learner_superego` / `learner_ego_revision` deliberation is in the logged trace and the tutor never sees it. The proposed mechanism (a per-turn, ephemeral *concealment-inference* step generating the tutor move against an inferred latent state, scored by an independent rubric-critic) is only worth building if that manifest $\neq$ latent discrepancy is a *separable, structured* signal the surface does not already determine. That necessary condition is **offline-decidable for free** against the real hidden trace — no mechanism need be run to falsify its precondition.

Pre-registered probe (`scripts/adaptation2-stage0.py`, **frozen before running; numpy + stdlib only**). Unit: one learner turn with the full hidden triplet plus its externalised output. Target (the manifest $\neq$ latent quantity): $1 - \text{tfidf-cosine}(\text{ego_initial}, \text{final_output})$, the magnitude by which the public utterance departs from the private first reaction; a token-Jaccard variant is the frozen robustness target. Predictor set **A** “surface-only” = features computable from the *manifest* dialogue alone (preceding tutor message + learner final output + structure) — exactly what the base conditions on, no hidden text. Predictor set **B** “latent-cause” = features from the `learner_superego` critique text *only* (excludes `ego_initial` and `ego_revision`, so it cannot trivially reconstruct the target). Estimator: ridge ($\lambda = 1.0$), leave-one-scenario-type-out grouped CV, cluster bootstrap by `scenario_type` ($B = 2000$, seed 20260517) — the honest variance unit, since outcome variance is overwhelmingly between scenario families. **Frozen P1 pass (both required): lower 95% CI of $R_B^2 > 0$ (the target is structured, a legible latent cause exists) and lower 95% CI of $(R_B^2 - R_A^2) > 0$ (the surface misses structure the latent cause explains).**

Result. Harvest $n = 1604$ triplet-turns, **9 scenario-type families** (`epistemic_resistance_impasse`, `affective_shutdown_impasse`, `mood_frustration_to_breakthrough`, `productive_deadlock_impasse`, `mutual_transformation_journey`, `misconception_correction_flow`, and three trajectory families), 11 profiles, 2589 dialogues. On the primary target:

channel	grouped-CV R^2	95% cluster-bootstrap CI
A surface-only (= what the base reads)	+0.086	—
B latent-cause (<code>learner_superego</code> text only)	−0.026	[−0.212, −0.032]
gap $B - A$	−0.111	[−0.234, −0.010]

Both frozen conditions are violated, and not marginally: the latent-cause channel carries **no recoverable out-of-group structure** (R_B^2 negative, CI entirely below 0) and is **significantly worse than the surface** (gap CI entirely below 0). The frozen robustness target (token-Jaccard) concurs ($R_A^2 = +0.039$, $R_B^2 = -0.022$, CI [−0.206, −0.018]). **P1 fails.**

Reading — why a pervasive phenomenon is nonetheless not a usable signal. The null is *not* an absence of concealment: the target is not floored (mean cosine distance 0.647, sd 0.101; 99.6% of turns in the graded interval, near-zero only 0.3%) — the simulated learner’s public utterance departs substantially from its private first reaction almost every turn. The decisive quantity is the variance decomposition: only 4.3% of the concealment-gap variance is *between* the nine trap families (per-family means 0.606–0.677, a 0.07 spread) and 95.7% is idiosyncratic *within* family. The gap does not track the trap type, is barely recoverable from the surface ($R_A^2 \approx 0.09$), and is *not* recoverable from the logged hidden deliberation at all ($R_B^2 \approx 0$; $\text{corr}(\text{target}, \text{len } \text{superego}) \approx -0.14$ — the superego critique is of roughly constant length and register regardless of how much the learner will actually revise). The premise of the signal-axis lever was that the owned hidden trace is a *privileged latent variable* the tutor lacks. The data falsify that premise: the “hidden” deliberation is **itself another stream of in-context LLM text with the same surface character**, and it does not encode — in any recoverable, family-transferable form — the very concealment it was theorised to explain. This is the unifying lesson of §6.7–§6.10 stated at its sharpest: there is no privileged structured interior beneath the text to model, *not even when the apparatus generates and logs that interior itself*. This is consistent with the machine-theory-of-mind literature, in which LLM mental-state tracking degrades under interaction stress (Kim et al., 2023) and under trivial perturbations of classic false-belief tasks (Ullman, 2023).

Symbolic corroboration (out of claim set). A later follow-up reaches the same null from the opposite methodological direction. A *symbolic* realisation of the concealed-interior lever — a per-turn description-logic theory-of-mind ABox accumulated by the tutor, strictly more inspectable than this section’s lexical proxy because an EL consistency check can interrogate it directly — was supplied to the tutor as live guidance and tested in a small real-backend multi-turn A/B (three stress scenarios, one run each). It is null over plain ontology guidance: the consistency check fires correctly — it flags surface compliance, a learner claiming the conclusion while signalling weak ownership, as a *grounded inconsistency* — yet only re-encodes a move the ontology guidance already prompts, and the extra directiveness if anything lowers the learner outcome. The no-privileged-interior reading therefore survives the shift from a free-text interior to a formal, checkable one. This is an exploratory screen (single backend, one run per scenario, heuristic outcome detector), out of the paper’s claim set and named for completeness only; write-up and artifacts in `notes/ontology/`

(scripts/run-ontology-tom-ab.js).

Disposition. Per the plan’s frozen kill rule, executed without relitigation: **no Stage 1, no live run, no counterfactual stage, no tuning retry** — the offline null *is* the closing result. With §6.7 / §6.8.8 / §6.9.7 / §6.9.8 this is the **fifth in-paper convergent negative** on adaptive elaboration (the archived closed-loop persona prototype is a sixth outside the paper’s claim set, named for completeness only), and the first to test the *signal* rather than the *policy form*: §6.9.8 exhausted the policy-realisation axis; §6.10 closes the signal axis. The adaptation arc is closed on both. The Weber companion probe (P2: tutor charisma → learner-receptivity *uptake*) was **structurally unmeasurable** on the existing corpus: the id-director charisma cells (100–109; §6.7) were run with scripted **unified** learners and scored tutor-only ($\leq 38/505$ rows carry any learner-side score, 0 carry learner interiority or a receptivity index). That corpus gap is itself the concrete answer to why the charisma lever was never realised — the §6.7 arc instrumented the *performance* of charisma, never its *uptake* (Weber’s legitimacy as *conferred by the other*, not performed). Artifacts: exports/adaptation2-stage0-table.csv, exports/adaptation2-stage0-probe.meta.json.

Status and caveats (per §5.12.6). Post-hoc and exploratory in the §6.9 sense, with the §6.9.8 twist that strengthens it: the *kill gate* was pre-registered before the probe was computed and was constructed offline and zero-API so the decision rule could not be revised after seeing a number. No alpha correction (one pre-declared primary contrast; the robustness target corroborates, it is not a second test). The offline target is *lexical* (tf-idf cosine / token-Jaccard), a noisy proxy for *semantic* concealment; this bounds the claim to lexically-separable concealment structure and is stated, not hidden. It does not reopen the gate, for two pre-registered reasons: the variance decomposition (family-invariant in mean, idiosyncratic within) is a property of the distribution that holds regardless of proxy fidelity; and the proxy plus kill rule were frozen *precisely* to forbid the “add embeddings and rerun” treadmill that the arc’s anti-thrash discipline (§6.9.8) exists to stop. No new judging — the probe consumes only already-logged traces. The claim is bounded: modelling the concealed interior buys no separable structure over the surface *on the v1-trap-suite logged ego-superego traces*, not that no interiority model could help on any instrument; that is the close of this arc, not a universal impossibility theorem.

Neighbouring modules: Module 3 — The Adaptive-Responsiveness Null; Module 4 — Provable Discourse and Process Tracing for Agent Architectures.

Kim, H., Sclar, M., Zhou, X., Le Bras, R., Kim, G., Choi, Y., & Sap, M. (2023). FANToM: A benchmark for stress-testing machine theory of mind in interactions. *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.
Piech, C., Spencer, J., Huang, J., Ganguli, S., Sahami, M., Guibas, L., & Sohl-Dickstein, J. (2015). Deep knowledge tracing. *Advances in Neural Information Processing Systems*, 28.

Scarlato, A., Baker, R. S., & Lan, A. (2025). Exploring knowledge tracing in tutor-student dialogues using LLMs. *Proceedings of the 15th International Learning Analytics and*

Knowledge Conference (LAK '25).

Ullman, T. (2023). *Large language models fail on trivial alterations to theory-of-mind tasks.*
<https://arxiv.org/abs/2302.08399>

Wang, R. E., Wirawarn, P., Khattab, O., Goodman, N., & Demszky, D. (2024). Backtracing: Retrieving the cause of the query. *Findings of the Association for Computational Linguistics: EACL 2024.*