Introduction to MPI

Lecture 2: Non-Blocking Communication & Master/Worker Parallelism

Liam Scarlett

liam.scarlett@curtin.edu.au

Class materials located at:

atom.curtin.edu.au/hpc

Or

```
git clone https://github.com/liamscarlett/intro-mpi
```

What if everyone posts Send then Recv?

Say we have a communication ring where each process sends some data to the next, and receives some data from the previous. (Not passing the same data around as we did last week).



It may appear that each process can call MPI_Send and then MPI_Recv, but let's see what happens:

0 waits until data has been received by 1
1 waits until data has been received by 2
2 waits until data has been received by 3
3 waits until data has been received by 0

But process 0 never calls MPI_Recv because it is still waiting for process 1 to signal it received its message.

Deadlock! **(Provided message size exceeds the size of the internal MPI buffer).**

What if everyone posts Send then Recv?

If the final process does not send a message back to process 0 then deadlock is avoided:



0 waits until data has been received by 1
1 waits until data has been received by 2
2 waits until data has been received by 3
3 signals it received the message from 2
2 signals it received the message from 1
1 signals it received the message from 0
Program continues

Asynchronous Communication

- Asynchronous send
  - send call returns immediately, send actually occurs later
  - if the sent data is to be modified, call a wait subroutine
- Asynchronous receive
  - receive call returns immediately.
  - when received data is needed, call a wait subroutine
- Asynchronous communication is used in attempt to overlap communication with computation
- Can help prevent deadlock

Caveat on asynchronous Communication

- Although asynchronous communications appear to give you the ability to overlap computation and communication, it may not *actually* happen:
  - On some parallel machines, the processor is actively involved in the communications and may not really be available to do other work
  - May only be able to perform reasonable computation for extremely large messages

Non-blocking Send with MPI_Isend

MPI_Isend (I for immediate return)

Fortran:

```
integer :: request
call MPI_Isend(data,count,datatype,destination,tag,communicator,request,ierr)
```

C:

```
MPI_Request request;
MPI_Isend(&data,count,datatype,destination,tag,communicator,&request);
```

The new output quantity `request` is a “handle” you can pass to other functions for checking the status of the communication, among other things.

You must not **alter** the information being sent (`data`) until the communication is complete.
The precise meaning of *complete* will depend on how MPI transmits the message (e.g. buffered or not)

Non-blocking Receive with MPI_Irecv

MPI_Irecv (I for immediate return)

Fortran:

```
integer :: request
call MPI_Irecv(data,count,datatype,source,tag,communicator,request,ierr)
```

C:

```
MPI_Request request;
MPI_Irecv(&data,count,datatype,source,tag,communicator,&request);
```

No `status` argument like there is for `MPI_Recv` as the status information is not known at the time we return from this function. Now the `request` handle can be used to extract status information later.

You must not **access** the information being received (`data`) until the communication is complete.

MPI_Wait

Input is a **request** from an **Isend** or **Irecv**

Fortran:

```
integer :: status(MPI_STATUS_SIZE)
Integer :: request
call MPI_Wait(request,status,ierr)
```

C:

```
MPI_Status status;
MPI_Request request;
MPI_Wait(&request,&status);
```

MPI_Wait blocks until the message specified by **request** completes

Completion of a **send** indicates the sender is now free to alter the data being sent

Completion of a **receive** indicates that the data array contains the received message

The **status** output contains the same information you'd get from the **status** output from an **MPI_Recv**. If you've called **MPI_Wait** on an **MPI_Isend** then the **status** is not of much use.

MPI_Waitall / MPI_Waitany

The idea is you have called multiple non-blocking communication routines and used request handles `requests[0]`, `requests[1]`, etc.

The output is an array of `status`es, each one corresponding to the request handle with the same index in the `requests` array.

Fortran:

```
Integer :: reqcount, index
integer :: statuses(MPI_STATUS_SIZE,count)
Integer :: requests(reqcount)
call MPI_Waitall(reqcount,requests,statuses,ierr)
call MPI_Waitany(reqcount,requests,index,statuses,ierr)
```

C:

```
int reqcount, index;
MPI_Status statuses[reqcount];
MPI_Request requests[reqcount];
MPI_Waitall(reqcount,&requests,&statuses);
MPI_Waitany(reqcount,&requests,&index,&statuses);
```

`MPI_Waitall` blocks until **all** operations specified in the `requests` array have completed.

`MPI_Waitany` blocks until **the first** operation specified in the `requests` array has completed.
- the output `index` specifies which operation completed.

Communication ring deadlock: Solution 1




```
#include <mpi.h>

MPI_Request requests[2];
MPI_Status statuses[2];

int next = (rank + 1) % nprocs;
int prev = (rank - 1 + nprocs) % nprocs;  //ensure non-negative result

MPI_Isend(&x, datacount, MPI_INT, next, tag, MPI_COMM_WORLD, &requests[0]);
//can do work here that doesn't modify x or use y
MPI_Irecv(&y, datacount, MPI_INT, prev, tag, MPI_COMM_WORLD, &requests[1]);

MPI_Waitall(reqcount, request, statuses);
//can do work here that modifies x and uses y
```

Why does this work? Now rank 0 can call its **MPI_Irecv** before it receives confirmation that the send operation completed. Once it receives the message from the final rank the confirmation of successful send is passed through the ring back to rank 0.

Communication ring deadlock: Solution 2




```
#include <mpi.h>

MPI_Request request;
MPI_Status status;

int next = (rank + 1) % nprocs;
int prev = (rank - 1 + nprocs) % nprocs;  //ensure non-negative result

MPI_Isend(&x, datacount, MPI_INT, next, tag, MPI_COMM_WORLD, &request);
//can do work here that doesn't modify x or use y
MPI_Recv(&y, datacount, MPI_INT, prev, tag, MPI_COMM_WORLD, &status);
//can do work here that uses y

MPI_Wait(request, status);
//can do work here that modifies x and uses y
```

All that we really needed was for the **send** operation to be non-blocking.
Using a **blocking receive** and then **wait** only on the **non-blocking send** is equivalent to the previous solution (except we can use y earlier!)

MPI_Test

```
logical :: flag
call MPI_Test(request,flag,status,ierr)
```

```
int flag;
MPI_Test(&request,&flag,&status);
```

- Similar to **`MPI_Wait`**, but does not block
- Allows for computation while the message is being received
- Value of **`flag`** signifies whether or not a message has been delivered
- In C: **`flag=0`** is false and **`flag=1`** is true

MPI_Test

```
MPI_Request request;
MPI_Status status;

MPI_Isend(&x,datacount,MPI_INTEGER,next,tag,MPI_COMM_WORLD,request,ierr);

int flag = 0;
while (!flag) {
  // sit in this loop and do some other
  // work waiting for send to complete

  MPI_Test(&request,&flag,&status)
}
```

There are also **MPI_Testany** and **MPI_Testall** routines for performing tests on collections of operations.

These are analogous to the **MPI_Waitany** and **MPI_Waitall** routines.

MPI_Test

```
MPI_Request request;
MPI_Status status;

MPI_Isend(&x,datacount,MPI_INTEGER,next,tag,MPI_COMM_WORLD,request,ierr);

int flag = 0;
while (!flag) {
  // sit in this loop and do some other
  // work waiting for send to complete

  MPI_Test(&request,&flag,&status)
}
```

There are also **MPI_Testany** and **MPI_Testall** routines for performing tests on collections of operations.

These are analogous to the **MPI_Waitany** and **MPI_Waitall** routines.

Workshop exercise:
Non-Blocking Communication

Synchronous send with MPI_Ssend

Fortran:

```
call MPI_Ssend(data,count,datatype,destination,tag,communicator,ierr)
```

C:

```
MPI_Ssend(&data,count,datatype,destination,tag,communicator);
```

The same as standard **`MPI_Send`**, but it *always* blocks until the receiver posts confirmation that the message was received.

Perhaps the MPI environment will still buffer the message for transport efficiency.

But from our perspective the communication proceeds the same as if there is no buffering

- The **`MPI_Ssend`** function does not return until the send/recv handshake is complete.

Synchronous send with MPI_Ssend

Fortran:

```
call MPI_Ssend(data,count,datatype,destination,tag,communicator,ierr)
```

C:

```
MPI_Ssend(&data,count,datatype,destination,tag,communicator);
```

Synchronous communications can be used to guarantee that no buffering is used. If your code is correctly written, you should be able to replace all calls to **`MPI_Send`** with **`MPI_Ssend`**.

This is an excellent way to make sure that your program is avoiding possible deadlocks. Will help you avoid any surprises when you port your code to another platform, in particular ones without default buffering for small messages

Non-blocking synchronous send with MPI_Issend

Fortran:

```
integer :: request
Call MPI_Ssend(data,count,datatype,destination,tag,communicator,request,ierr)
```

C:

```
MPI_Request request;
MPI_Ssend(&data,count,datatype,destination,tag,communicator,&request);
```

The same syntax as **`MPI_Isend`**, but *synchronous*.

Wait, what?

Let's clarify some terminology:

- **Blocking** operations **do not** return until the operation is ***complete*.**

- **Non-blocking** operations return immediately.
  You must check to see when the operation is *complete* later.

The above says nothing about what defines the ***completion*** of an operation.

- In an `MPI_Bsend` (user-requested buffered send), or an `MPI_Send` with default buffering, the operation is ***complete*** as soon as the data is copied into the MPI buffer. The sender is safe to modify the data without corrupting the message, but there is no guarantee if/when the message has been received.

- In an `MPI_Ssend`, or an `MPI_Send` with no default buffering, the operation is ***complete*** once the message is received by the destination rank.

Wait, what?

Let's clarify some terminology:

- **Blocking** operations **do not** return until the operation is ***complete*.**

- **Non-blocking** operations return immediately.
  You must check to see when the operation is *complete* later.

The above says nothing about what defines the ***completion*** of an operation.

- In an **`MPI_Isend`**, the definition of *complete* is the same as for **`MPI_Send`**. If the MPI environment decides to buffer the message, then **`MPI_Wait`** or **`MPI_Test`** will say the communication is complete as soon as the data is copied into the MPI buffer.

- In an **`MPI_Issend`**, the definition of *complete* is the same as for **`MPI_Ssend`**. Even if the MPI environment buffers the message, **`MPI_Wait`** and **`MPI_Test`** will not say the communication is complete until the message is received by the destination rank.

Workshop exercise:
Synchronous Communication

Designing parallel programs: Partitioning

- **Partitioning**
  - One of the first steps in designing a parallel program is to break the problem into discrete "chunks" of work that can be distributed to multiple tasks. This is known as decomposition or partitioning.
  - There are two basic ways to partition computational work among parallel tasks:
    - ***domain decomposition***
    - ***functional decomposition***

Designing parallel programs: Partitioning

- **Domain Decomposition**
  - In this type of partitioning, the *data* associated with a problem is decomposed.
  - Each parallel task then works on a separate portion of the data.
  - There are different ways to partition data
    - e.g. block, cyclic





Designing parallel programs: Partitioning

- **Functional Decomposition**

  - In this approach, the focus is on the computation that is to be performed rather than on the data manipulated by the computation.
    The problem is decomposed according to the work that must be done.
    Each task then performs a portion of the overall work.

  - Functional decomposition lends itself well to problems that can be split into different tasks



Designing parallel programs: Communications

- **You DON'T need communications**
  - Some types of problems can be decomposed and executed in parallel with virtually no need for tasks to share data.
    - E.g. imagine an image processing operation where every pixel in a black and white image needs to have its color reversed. The image data can be distributed to multiple tasks that then act independently of each other to do their portion of the work.
  - These types of problems are often called ***embarrassingly parallel*** because they are so straight-forward.
    Very little inter-task communication is required.

Designing parallel programs: Communications

- **You DO need communications**
  - Most parallel applications are not quite so simple, and do require tasks to share data with each other. For example, a 3-D heat diffusion problem requires that each task know the value of data held by the neighboring tasks.

- **Cost of communications**
  - Inter-task communication often implies overhead.
  - Machine cycles that could be used for computation are instead used to package and transmit data.
  - Communications frequently require synchronisation between tasks, which can result in tasks spending time "waiting" instead of doing work.

Designing parallel programs: Load balancing

- **Load Balancing**

  - the practice of distributing work among tasks so that *all* tasks are kept busy *all* of the time. It can be considered a minimisation of task idle time.



  - Load balancing is important to parallel programmes for performance reasons. For example, if all tasks are subject to a barrier synchronisation, the slowest task will determine the overall performance.

Designing parallel programs: Load balancing

- **Achieving Load Balance: Equally partition the work each task receives**

- For array/matrix operations where each task performs similar work, evenly distribute the data set among the tasks.

- For loop iterations where the work done in each iteration is similar, evenly distribute the iterations across the tasks.

- Load imbalance can be detected using performance analysis tools, or you can use timing functions (e.g. `MPI_Wtime`) to measure how long each task spends doing useful work.

Designing parallel programs: Load balancing

- **Load Balance: dynamic work assignment**

  - Certain classes of problems result in load imbalances even if data is evenly distributed
    - *Sparse arrays* - some tasks will have actual data to work on while others have mostly zeros
    - *Adaptive grid methods* - some tasks may need to refine their mesh while others don't
    - *N-body simulations* - some particles may migrate to/from their original task domain to another task's; where the particles owned by some tasks require more work than those owned by other tasks

  - Sometimes helpful to use a ***scheduler–task-pool*** approach. As each task finishes its work, it queues to get a new piece of work.

Designing parallel programs: Granularity

- **Computation / Communication Ratio**
  - In parallel computing, granularity is a qualitative measure of the ratio of computation to communication
  - Periods of computation are often separated from periods of communication by synchronisation events

  - **Fine-grain Parallelism**
    - Relatively small amounts of computational work are performed between communication events

  - **Coarse-grain Parallelism**
    - Relatively large amounts of computational work are performed between communication events

Designing parallel programs: Granularity

- **Fine-grain Parallelism**
  - Low computation to communication ratio
  - Facilitates load balancing
  - Implies high communication overhead and less opportunity for performance enhancement
  - If granularity is too fine it is possible that the overhead required for communications takes longer than the computation



Designing parallel programs: Granularity

- **Coarse-grain Parallelism**
  - High computation to communication ratio
  - Implies more opportunity for performance increase
  - Harder to load balance efficiently

- **Which is Best?**
  - Depends on the hardware and algorithm, but in most cases the overhead associated with communication is high relative to execution speed and so it is best to have coarse granularity



Designing parallel programs: Granularity

- ***Speedup*** is the time taken by the sequential solution divided by the time taken by the parallel solution
  - e.g. the serial version of a code takes 100 secs to run, while the parallel version takes 25 secs → speedup=4
  - Greater than 1. Ideally equal to number of processes

- **Amdahl's Law**
  - The maximum speedup is given by $$\frac{1}{(P/N) + S}$$

    where P = parallel fraction,
    N = number of processes and S = serial fraction.

  - Ultimately the speedup of your program is limited by the serial part.

Master/worker parallelism

- A simple programming model where one process acts as the "*master*" and distributes work to the "*worker*" processes



Master/worker parallelism: example

- Elements of A_i are distributed to workers which evaluate $B_i=f(A_i)$ and then pass results back to the master




```
master = 0
if (rank == master) {
   perform I/O, distribute work, collect
   results, etc.
}

if (rank != master) {
   receive work, do calculations, return
   results, etc.
}
```

Master/worker parallelism: Static decomposition

- Master process decides on the distribution of work at the start
- Excellent where the amount of time required for each parcel of work is known at the start of the simulation



Master/worker parallelism: Static decomposition

Calculating the work

```
if (rank == 0) { //only master determines work allocation
   numworkers = nprocs - 1;
   //how much work to give each process:
   chunksize = datasize/numworkers; //integer division

   remainder = datasize%numworkers;

   for(int dest=1; dest<=numworkers; dest++) {
      if (dest <= remainder) {
            //these tasks get extra work to cover the remainder
            portion[dest] = chunksize + 1;
      }
      else {
            portion(dest) = chunksize;
      }
   }
```

Master/worker parallelism: Static decomposition

Distributing the work

```
if (rank == 0) {
  index = 0;
  for(int dest=1; dest<=numworkers; dest++) {

    MPI_Send(&index,1,MPI_INT,dest,itag,MPI_COMM_WORLD);

    MPI_Send(&portion[dest],1,MPI_INT,dest,ptag,MPI_COMM_WORLD);

    MPI_Send(&x[index],portion[dest],MPI_INT,dest,atag,MPI_COMM_WORLD);

    index = index + portion[dest]

  }
}
```

Master/worker parallelism: Static decomposition

Collecting the results

```
if (rank == 0) {
  index = 0;
  for(int source=1; source<=numworkers; source++) {

    MPI_Recv(&index,1,MPI_INT,source,itag,&status,MPI_COMM_WORLD);

    MPI_Recv(&portion[dest],1,MPI_INT,source,ptag,&status,MPI_COMM_WORLD);

    MPI_Recv(&y[index],portion[dest],MPI_INT,source,atag,&status,MPI_COMM_WORLD);

    index = index + portion[dest]

  }
}
```

Master/worker parallelism: Static decomposition

On the worker processes

```
if (rank != 0) {
  MPI_Recv(&index,1,MPI_INT,0,itag,MPI_COMM_WORLD,&status);
  MPI_Recv(&portion[dest],1,MPI_INT,0,ptag,MPI_COMM_WORLD,&status);
  MPI_Recv(&x[index],portion[dest],MPI_INT,0,atag,MPI_COMM_WORLD,&status);

  //operate on x[index]..x[index+portion-1]

  MPI_Send(&index,1,MPI_INT,0,itag,MPI_COMM_WORLD);
  MPI_Send(&portion[dest],1,MPI_INT,0,ptag,MPI_COMM_WORLD);
  MPI_Send(&y[index],portion[dest],MPI_INT,0,atag,MPI_COMM_WORLD);
}
```

Master/worker parallelism: Static decomposition

Ways to simplify

- We could have all processors calculate their portion size and avoid one set of matching sends and receives.

- Do the workers really need to know the starting index of their array chunks?
  - master can keep a list of the index for each worker

- We also could use …
  - `MPI_Scatter` to distribute the work
  - `MPI_Gather` to collect the work
  - Need to use MPI_Scatterv and MPI_Gatherv when the data isn't distributed equally to each process

Master/worker parallelism: Dynamic decomposition

- Master processor distributes out new work as workers finish their previous tasks
  - Excellent for calculations where the work needed for solving each individual task varies significantly.
  - Example: iterative schemes where number of steps required for convergence can have a large variation.
- Make sure that parcels of work are large enough so that you don't spend all of your time in communications
- Make sure that parcels of work are small enough so that you achieve load balancing

Master/worker parallelism: Dynamic decomposition

Overview

MASTER

Read input data
Establish a chunksize
Loop over worker processes
    hand out initial parcel of work
While work remains to do
    get results from finished worker
    and hand out new parcel of work
Loop over worker processes
    collect outstanding work requests
Loop over worker processes
    tell all workers to quit

WORKERS

While work remains to do
    get work from master
    do work
    send results to master

Master/worker parallelism: Dynamic decomposition

Receiving the results

- The heart of the dynamic load balancing scheme:
  The master receives work back from whoever finishes first by posting a receive from any source

```
MPI_Recv(&indexrecv,1,MPI_INT,MPI_ANY_SOURCE,tag,MPI_COMM_WORLD,&status);
isource = status.MPI_SOURCE;

. . receive results from isource ...
. . send new work to isource ...
```

Assessable task: Mandelbrot set



- For every point κ on the complex plane define an iterative sequence

$$z_{i+1} = (z_i)^2 + \kappa$$

- Starting value is $z_0 = \kappa$, then:

$$\begin{aligned} z_1 &= (z_0)^2 + \kappa = \kappa^2 + \kappa \\ z_2 &= (z_1)^2 + \kappa = (\kappa^2 + \kappa)^2 + \kappa \\ z_3 &= (z_2)^2 + \kappa = [(\kappa^2 + \kappa)^2 + \kappa]^2 + \kappa \\ &\vdots \end{aligned}$$

- Keep in mind all quantities are complex when defining the squaring operation
- A point κ is **in** the Mandelbrot set if the sequence is bounded as $i \to \infty$

- It is known that the Mandelbrot is bounded by the disk $|\kappa| < 2$, so we only need to iterate until $|z_i| > 2$ to determine that a point is not in the set.

- In practice, have a maximum number of iterations **`MAXITER`**, and if the sequence does not leave the $|\kappa| < 2$ disk within that many iterations consider it in the set.
  - As you increase **`MAXITER`** you get more detail in the rendering



Just for interest:

Multibrot set: $z_{i+1} = (z_i)^r + \kappa$ for arbitrary r

mandelbrot.c - provided

Provided code will handle evaluating the Mandelbrot set and printing to file

```
// Iterate over 2-D grid: i covers N cols and j covers N rows
for (i=0; i<N; i++) {
  for (j=0; j<N; j++) {

    //kappa is the coordinate in the complex plane of the (i,j)th pixel
    //both the real and imaginary axis range from -2 to 2 (4 units)
    kappa = (4.0*(i-N/2))/N + (4.0*(j-N/2))/N * I;

    //z_0 = kappa, initial value of z before iteration begins
    z = kappa;

    //now we iterate until either the max number of iterations is reached
    //OR z leaves the circle of radius 2 centred at the origin
    k=1;
    while ((cabs(z)<=2) && (k++<MAXITER)) {
      z = z*z + kappa;
    }

    // Store the number of iterations required for this point to leave the Mandelbrot set.
    // If this point IS IN the Mandelbrot set, then k=MAXITER.
    x[i][j]=log((float)k) / log((float)MAXITER);
  }
}
```

`x` is a 2D array representing the complex plane. The number of iterations it took to leave the Mandelbrot set is used to colour the output

mandelbrot2.c - provided

This code collapses the 2D grid into a 1D array for ease of distributing work to different MPI ranks

```
//Loop over N^2 pixels
for (loop=0; loop<N*N; loop++) {
  // i:cols and j:rows

  // i=mod(loop,N) means i iterates from 0...N-1 then back to 0...N-1 etc.
  i=loop%N;

  // j=loop/N is integer division.
  // For the first  round of i=0...N-1, loop < N, and hence j=0.
  // For the second round of i=0...N-1, N <= loop < 2*N, and hence j=1.
  // This way we fix the row and iterate over all columns
  // and then increment the row the iterate over all columns again, etc...
  j=loop/N;

  //In here is the same evaluation of the Mandelbrot set as in mandelbrot.c

  x[loop]= log((float)k) / log((float)MAXITER);
}
```

`x` is a 1D array now

Partitioning

- In two of the tasks you will be required to implement a static domain decomposition.
- The work of evaluating the 1D array `x` should be distributed over the different MPI ranks.
- The different parts of `x` should then be compiled on rank 0 using **`MPI_Gather`**
- You will need to implement both BLOCK and CYCLIC distributions of the `x` array

E.g. let's say `x` has 12 elements which we distribute over 4 ranks with a chunk size of 3:

BLOCK:

0	1	2	3	4	5	6	7	8	9	10	11

CYCLIC:

0	1	2	3	4	5	6	7	8	9	10	11

	Rank 0
	Rank 1
	Rank 2
	Rank 3

BLOCK partitioning

	Rank 0
	Rank 1
	Rank 2
	Rank 3

BLOCK partitioning is simple to implement.

Each rank works on a contiguous section of the array:



Then **`MPI_Gather`** brings the sections back *in the proper order*

BLOCK partitioning

Some suggestions...

In the provided serial code there is an iterator **`loop`** that iterates over the elements of `x`:

	0	1	2	3	4	5	6	7	8	9	10	11
`loop:`	*0*	*1*	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*	*11*

You may implement the **block** partitioning task with each rank having an iterator **`l`** that goes from 0 to chunksize-1

	0	1	2	3	4	5	6	7	8	9	10	11
`rank`	*0*	*0*	*0*	*1*	*1*	*1*	*2*	*2*	*2*	*3*	*3*	*3*
`l:`	*0*	*1*	*2*	*0*	*1*	*2*	*0*	*1*	*2*	*0*	*1*	*2*
`loop:`	*0*	*1*	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*	*11*

It is straightforward to see the relationship between the three variables, which you can code so that each rank knows the value of the index **`loop`** in the global array for each index **`l`** in its local array.

Then you can reuse **`i=loop%N; j=loop/N;`** from the serial code to determine the pixel coordinates.

CYCLIC partitioning **requires some more thought…**

	Rank 0
	Rank 1
	Rank 2
	Rank 3

Each rank works on a **non-contiguous** section of the array.
In our case we don't need to **scatter** data for the ranks to work on.
Just need a way for each rank to know which parts of the array it is assigned



`MPI_Gather` brings the sections back ***in the wrong order.***

Need to **reorder** the array.

CYCLIC partitioning

Some suggestions...

You may implement the **cyclic** partitioning task with each rank having an iterator `l` that goes from 0 to chunksize-1

	0	**4**	**8**	**1**	**5**	**9**	**2**	**6**	**10**	**3**	**7**	**11**
`rank`	*0*	*0*	*0*	*1*	*1*	*1*	*2*	*2*	*2*	*3*	*3*	*3*
`l:`	*0*	*1*	*2*	*0*	*1*	*2*	*0*	*1*	*2*	*0*	*1*	*2*
`loop:`	*0*	*4*	*8*	*1*	*5*	*9*	*2*	*6*	*10*	*3*	*7*	*11*

Although it is more complicated now, you can still determine the relationship between the three variables

Then each rank knows the value of the index **`loop`** in the global array for each index **`l`** in its local array.

Then you can reuse **`i=loop%N;  j=loop/N;`** from the serial code to determine the pixel coordinates.

CYCLIC partitioning

Some suggestions…

The reordering process is simplest if you just **MPI_Gather** into a secondary array **y** and then copy elements into **x** in the right order. (This all happens on rank 0 only now).



You may like to have a nested loop over ranks and the index in the local arrays:

```
for (int r=0; r<nprocs; r++) {
  for (int l=0; l<chunksize; l++) {
    loop = ???; //same relationship between rank and local index you already found
    yind = ???;
    x[loop] = y[yind];
  }
}
```

yind is the index in the y array for a given rank and local index. This is a simple offset relation accounting for the local arrays being stacked side-by-side in the **y** array.

Master/worker

You will also be asked to implement a master/worker solution.
The simplest way you can approach this is:

- All worker ranks initially start work the chunk starting at `(rank-1)*chunksize`

- Master rank sits in a while loop, and at each iteration:
  - Master rank receives a chunk from MPI_ANY_SOURCE and saves it.
  - Master rank then sends the index of the next chunk to start work on to whichever worker sent last chunk.
  - The master rank therefore must keep track of and increment this index each time it sends a new request.

- Worker ranks are also sitting in a while loop, and at each iteration:
  - Send the chunk they have finished working on to the master rank.
  - Receive the index of the new chunk to work on from the master rank.

Master/worker

What should the conditions be on the `while` loops?

- If the master rank is updating the value of the chunk starting index every time it sends a new request, it will eventually reach a point where the index exceeds the number of pixels to work on.
  - When a worker receives an index outside the bounds of the pixel array it can interpret this as a message that the work is complete and exit its `while` loop.

- The master rank cannot simply exit its while loop once the index goes out of bounds, because it needs to send that "out of bounds index message" to all worker ranks to signal that work is finished.
  - The master rank needs to keep track of how many workers it has told to stop work and then exit its own while loop once everyone has been informed.

Timing visualisation

You'll be asked to make figures in the same format as shown here to indicate how long each task spends on:

- **Computation**: Performing the Mandelbrot algorithm
- **Waiting**: Waiting for other tasks to finish their Mandelbrot algorithm.
- **Communication**: Time spend in the blocking `MPI_Gather` routine.



Workshop exercise:
Understanding Memory

Then start on assignment