

NLP - Master Notes

June 13, 2021

1 Language Models

1.1 N-Gram Models

- Language (prediction) models which make the *Markov assumption* for an $(n - 1)^{th}$ order Markov Model; i.e. that only the previous n-1 words have a probabilistic dependence on the current word.
- Probability of words 1 to n: $P(w_1^n) = \prod_{k=1}^n P(w_k | w_{k-N+1}^{k-1})$

General steps for creating an n-gram model:

1. choose a vocabulary
2. add $< s >$ and $< /s >$ symbols
3. replace unknown words in the training corpus with $< UNK >$
4. calculate probabilities (on an as needs basis?)
5. calculate most probably words in order (until reaching end of sentence symbol) OR evaluate perplexity of test corpus using above formulas.

- *example:*

Text:

One cat sat. Three **cats sat**. Eight **cats sat**. The **cats** had nine lives.

$$P(\text{sat} \mid \text{cats sat}) = \frac{C(\text{cats}, \text{sat})}{C(\text{cat})} = \frac{2}{3}$$

- **Definition of a language model:** a model which assigns probabilities to sentences, based on the training corpus. The sum of all the probabilities of all possible sentences (of arbitrary length) should equal 1.

Trivial example:

- Training corpus contains two sentences:
 1. “a b”,
 2. “b a”

- Append $\langle \text{sos} \rangle$ and $\langle / \text{sos} \rangle$ to each:
 1. "s a b /s"
 2. "s b a /s"
- generate the probabilities of a bigram (N=2) language model:

$$\begin{aligned} P(a|s) &= \frac{1}{2} \\ P(b|s) &= \frac{1}{2} \\ P(b|a) &= \frac{1}{2} \\ P(a|b) &= \frac{1}{2} \\ P(/s|a) &= \frac{1}{2} \\ P(/s|b) &= \frac{1}{2} \end{aligned}$$

- To calculate the probability of ALL possible sentences, we take the prob of all sentences of length 1, all sentences of length 2, etc. Note when calculating this, the TEST sentences need to include $\langle s \rangle$ and $\langle /s \rangle$
 - For example: $P(a) = P(\langle s \rangle a \langle /s \rangle) = P(a | \langle s \rangle) * P(\langle /s \rangle | a) = 1/4$
 - Probability is same for b, so the sum of all probabilities of sentence length 1 = $\frac{1}{2}$
- The sum of all sentences will be the infinite series:

$$P(all) = \frac{1}{2} + \sum_{i=2}^{\infty} \frac{i!}{(i-2)!} \frac{1}{2}^{i+1}$$

Does this sum to 1? A proof would be cool.

- Sentence Generation: until you produce a $\langle /s \rangle$ symbol, continually generate words using: $\text{argmax}(w_k) \frac{C(w_{k-n+1}, \dots, w_k)}{C(w_{k-n+1}, \dots, w_{k-1})}$
- Perplexity: how well a model fits the data $PP(W) = P(w_1, \dots, w_N)^{-\frac{1}{N}}$, for N words in the test corpus. A perplexity of 1 would be the lowest possible.
- Smoothing:

- Laplace (add-one): $P(W_n | w_{n-N+1}^{n-1}) = \frac{C(w_{n-N+1}^{n-1} w) + 1}{c(w_{n-N+1}^{n-1}) + V}$, where V is the vocabulary size
- add δ , normalise by δV

- Interpolation: creating a linear combination of n-gram models of varying n: $\hat{P}(w_i | w_{i-1}, \dots, w_{i-n}) = \sum_{j=2}^n \lambda_j * P(w_i | w_{i-1}, \dots, w_{i-j})$, where $\sum_j \lambda_j = 1$
- Back-off: back-off to lower n models until data is available (does this mean you can have arbitrary n?)

2 Part of Speech Tagging

A Part of speech tagger assigns for every word w_i in a sentence $\{w_i, \dots, w_n\}$ a part of speech (POS) tag y_i . POS tags include parts of speech like verb (tag=V), noun, adverb etc.

Naive Baseline: More than half of words are ambiguous - i.e. they have more than one possible tag. If we count all the tags in a training set and produce $P(\text{tag}|\text{word})$ for each word, we can simply choose the most likely tag for the word. This baseline has an accuracy of about 92%, only 5% less than the state of the art.

All extra efforts in more complex models (e.g. CRF, HMM) are about squeezing out this last 5%.

Named entity tagging (e.g. Washington State) is harder - it assumes groups of words together refer to one particular proper noun.

2.1 Hidden Markov Models

Suppose there are T tags (hidden states). An HMM will require a transition matrix giving the probability of any tag occurring after any other tag. This will be an T x T matrix of probabilities (we can compute this similarly to the bigram model, using the bigram assumption) called the **transition matrix**. Suppose also there are N words. The HMM will also require probabilities of each word given a tag. This will be a T * N matrix. Again, this is computed using counts of word-tag pairs over total tag counts, called the **emission matrix**. “The goal of part-of-speech tagging is to find the most probable sequence of $t_1 \dots t_n$ tags given a sequence of N words $w_1 \dots w_n$.”

We achieve the goal of the HMM by the following equations:

$$\begin{aligned}
 t_{1:n} &= \operatorname{argmax}_{t_1 \dots t_n} P(t_1 \dots t_n | w_1 \dots w_n) && \text{max prb tags given words} \\
 t_{1:n} &= \operatorname{argmax}_{t_1 \dots t_n} \frac{P(w_1 \dots w_n | t_1 \dots t_n)}{P(w_1 \dots w_n)} && \text{by bayes rule} \\
 t_{1:n} &= \operatorname{argmax}_{t_1 \dots t_n} P(w_1 \dots w_n | t_1 \dots t_n) && \text{since argmax, can discard denom} \\
 t_{1:n} &= \operatorname{argmax}_{t_1 \dots t_n} \prod_{i=1}^n P(w_i | t_i) \prod_{i=1}^n P(t_i | t_{i-1}) && \text{by the HMM assumptions}
 \end{aligned} \tag{1}$$

Note: we also require an array of initial probabilities for each of the states.

We are interested in a tag sequence satisfying the above equation. Brute forcing would be possible, but would take $O(T^N)$ (infeasible).

The viterbi algorithm attempts to solve this problem in a feasible time.

The viterbi algorithm takes in the following inputs:

O: observation space, S: state space, π : initial probabilities, Y:sequence of observations, A: transition matrix, B: emission matrix.

Algorithm 1 Viterbi

```
1: procedure VITERBI ▷  
2:   while x do  
3:     x
```

3 Statistical Parsing

3.1 Overview

3.2 Parse Trees, CNF, CFG, PCFG

Parse Trees: show the groupings of words in a sentence to their syntactic group. E.g. Noun Phrase (NP), Verb Phrase (VP). This helps downstream NLP tasks to determine the meaning of sentences, perform translations, etc.

Converting to Chomsky Normal Form: Chomsky Normal Form means that the right hand side of each rule must expand to two non terminals, or one terminal. [1]

1. Copy all conforming rules to the new grammar unchanged
2. Convert terminals within rules to dummy non-terminals
3. Convert unit productions
4. Make all rules binary and add them to new grammar.

PCFG: each rule is assigned a probability, and the sum of all probabilities per non terminal (on the left hand side of the rule) = 1.

3.3 CKY Algorithm, Probabilistic CKY

CYK is a **bottom up** parser - i.e. we start with the words and build the tree to the top.

CKY algorithm requires a grammar to be normalised to Chomsky Normal Form. This will naturally result in an (likely unbalanced) binary tree when expanded.

The **time complexity** of CKY parsing is $O(n^3)$, since there are n^2 cells to fill, and each cell requires querying n split points (*not 100% sure about this point*).

4 Statistical Machine Translation

Linguistic issues with machine translation: *Lexical divergence (not all words in one language have a word in the other), syntactical divergence (e.g. SVO vs SOV), morphology*

Vauquous Triangle:

- Words
- parsing - syntactic structure

- SRL & WSD - Semantic Structure
- Semantic Parsing - Interlingua

5 Semantic Parsing

5.1 Semantic Role Labelling (SRL) - concepts

E.g. nominative and accusative. Some possible roles include: *Agent, Patient, Instrument, Beneficiary, Source, Destination* (roles aren't limited to people, they can be assigned to places, things etc.)

There *can* be syntactic clues (e.g. preposition words - "with", "for", "from" etc.), however ultimately very difficult to do.

Selectional Restrictions: by assigning a role to a concept, we imply certain characteristics of the concept. E.g.: a thing which is an "agent" should be animate (and not inanimate). Taxonomic abstraction hierarchies can be used to determine if such constraints are met (e.g. human = mammal = vertebrate = animate).

5.2 SRL Approaches

Idea: first apply a syntactic parse tree, then label the concepts

SRL \subset *Sequence Labelling*

Labels = Parse Tree Nodes

Can use a variety of supervised machine learning methods.

5.3 Predicate Calculus / Functional Query Language

$$\text{Sentence} \implies \text{Predicate Logic} \quad (2)$$

Sentence: What is the smallest state by area?

Predicate Logic: $\text{answer}(x_1, \text{smallest}(x_2, (\text{state}(x_1), \text{area}(x_1, x_2))))$

$$\text{Predicate Logic} \implies \text{Functional Query Language (variable free)} \quad (3)$$

FOL: $\text{answer}(x_1, \text{smallest}(x_2, (\text{state}(x_1), \text{area}(x_1, x_2))))$

FQL: $\text{answer}(\text{smallest_one}(\text{area_1}(\text{state}(\text{all}))))$

References

- [1] D. Jurafsky and J. H. Martin, "Speech and language processing (draft)," *Chapter A: Hidden Markov Models (Draft of September 11, 2018)*. Retrieved March, vol. 19, 2018.