
6.867: Homework 2

1. Logistic regression

In this section, we explore logistic regression with L1 and L2 regularization. We use gradient descent to compare the resulting weight vectors under different regularizers and regularization parameters, and we evaluate the effect of these choices in the context of multiple data sets.

1.1. L2 regularization

We first consider L2 regularization, in which the objective function to minimize is

$$E_{LR}(w, w_0) = \text{NLL}(w, w_0) + \lambda \|w\|_2^2$$

where

$$\text{NLL}(w, w_0) = \sum_i \log(1 + \exp(-y^{(i)}(wx^{(i)} + w_0)))$$

and in the case of L2 regularization,

$$\|w\| = \|w\|_2 = \sqrt{w_1^2 + \dots + w_n^2}$$

Gradient descent was run with this objective function on the training dataset `data1_train.csv` with $\lambda = 0$. We observed how the weight vector changed as a function of the number of iterations of gradient descent across various initial guesses, step sizes, and convergence criterion. There were three key findings that we were able to make. First, we saw that the ultimate convergence weight was heavily dependent on the initial guess. This actually makes a good deal of sense because of the fact that there are infinitely many ways to perfectly separate a dataset that's linearly separable. The second observation was that w_0 and w_1 always decreased as number of iterations increased whereas w_2 also increased. Finally, we saw that the convergence weight values were all within the same order of magnitude as the initial guess. This makes intuitive sense since we know from class that in the case of linearly separable data, the optimization aims to make the weights as large as possible.

When $\lambda = 1$, we see drastically different behavior in how the weight vector changes throughout the course of the gradient descent. The primary difference is the

Dataset	Best regularizer	Best λ	Test performance
1	5	6	1
2	5	6	1
3	5	6	1
4	5	6	1

Table 1. Optimal regularizer and λ for datasets

fact that w_0, w_1 , and w_2 all converge to much smaller values. For example, when we set the initial guesses to be 100 for all 3 components of the weight vector, the converged weights were two orders of magnitude less than the initial guesses. The reason for this phenomenon is due to the regularization penalty incurred when we set $\lambda = 1$

1.2. L1 regularization

In the case of L1 regularization, we get that in the above equation,

$$\|w\| = \|w\|_1 = \sum_{i=1}^n |w_i|$$

We can evaluate the different regularization techniques under different values of λ in the context of the weight vectors, the decision boundary, and the classification error rate in each of the training data sets.

1.2.1. WEIGHT VECTOR

1.2.2. DECISION BOUNDARY

1.2.3. CLASSIFICATION ERROR RATE

1.3. Optimization

By using the training and validation data sets, we can identify the best regularizer and value for λ for each of the four data sets. These results are presented in Table 1.

2. Support Vector Machine

In this section, we explore various versions of the dual form of support vector machines, first with slack variables and then with generalized kernel functions.

2.1. Dual form with slack variables

We here implement a dual form of linear SVMs with slack variables. More specifically, we solve the following optimization problem with respect to α :

$$\begin{aligned} \max_{\alpha} & -\frac{1}{2} \left| \sum_i \alpha_i y^{(i)} x^{(i)} \right|^2 + \sum_i \alpha_i \\ \text{s.t.} & \sum_i \alpha_i y^{(i)} = 0 \\ & 0 \leq \alpha_i \leq C, 1 \leq i \leq n \end{aligned}$$

Written another way, this maximization problem can be framed as a minimization problem:

$$\begin{aligned} \min_{\alpha} & \frac{1}{2} x^T P x + q^T x \\ \text{s.t.} & G x \leq h \\ & A x = b \end{aligned}$$

where $b = 0$ and

$$x = \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \vdots \\ \alpha_n \end{bmatrix}, q = \begin{bmatrix} -1 \\ -1 \\ \vdots \\ -1 \end{bmatrix}, A^T = \begin{bmatrix} y_0 \\ y_1 \\ \vdots \\ y_{n-1} \end{bmatrix}, G = \begin{bmatrix} I \\ -I \end{bmatrix},$$

where I and $-I$ are the identity and negative identity matrix respectively. Furthermore,

$$P = \begin{bmatrix} x_0^2 y_0^2 & x_0 y_0 x_1 y_1 & \dots & x_0 y_0 x_{n-1} y_{n-1} \\ x_1 y_1 x_0 y_0 & x_1^2 y_1^2 & \dots & x_1 y_1 x_{n-1} y_{n-1} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n-1} y_{n-1} x_0 y_0 & x_{n-1} y_{n-1} x_1 y_1 & \dots & x_{n-1}^2 y_{n-1}^2 \end{bmatrix},$$

$$h^T = [C \quad \dots \quad C \quad 0 \quad \dots \quad 0]$$

In the context of the four-point 2D problem, we seek to solve the following optimization:

$$\begin{aligned} \min_{\alpha} & \frac{1}{2} \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_2 \\ \alpha_3 \end{bmatrix}^T \begin{bmatrix} 16 & 24 & 0 & 24 \\ 24 & 36 & 0 & 36 \\ 0 & 0 & 0 & 0 \\ 24 & 36 & 0 & 36 \end{bmatrix} \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_2 \\ \alpha_3 \end{bmatrix} + \begin{bmatrix} -1 \\ -1 \\ -1 \\ -1 \end{bmatrix}^T \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_2 \\ \alpha_3 \end{bmatrix} \\ \text{s.t.} & \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ -1 & 0 & 0 & 0 \\ 0 & -1 & 0 & 0 \\ 0 & 0 & -1 & 0 \\ 0 & 0 & 0 & -1 \end{bmatrix} \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_2 \\ \alpha_3 \end{bmatrix} \leq \begin{bmatrix} C \\ C \\ C \\ C \\ 0 \\ 0 \\ 0 \\ 0 \end{bmatrix}, \begin{bmatrix} 2 \\ 3 \\ -1 \\ -2 \end{bmatrix} \begin{bmatrix} \alpha_0 \\ \alpha_1 \\ \alpha_2 \\ \alpha_3 \end{bmatrix} = 0 \end{aligned}$$

Solving for x when $C = 1$, we get that $[\alpha_0 \ \alpha_1 \ \alpha_2 \ \alpha_3]^T = [0.1875 \ 0 \ 0.3750 \ 0]^T$. This indicates that the first and third samples are support vectors because $0 \leq \alpha_i \leq C$.

Our implementation of the dual form of SVMs with slack variables was run on each of the four 2D datasets provided. With $C = 1$, the decision boundaries and classification error rates were determined. This information is illustrated and summarized in Figure 1 and Table 2, respectively. As can be seen from the classification error rates in training and validation, depending on the values of the trained parameters and the spread of the datasets, the classification error could be greater for the training data (as in dataset 2), for the validation data (as in dataset 4), or equal (as in dataset 1).




Figure 1. Training and validation decision boundary

Dataset	Training error rate	Validation error rate
1	0.0	0.0
2	0.1775	0.09
3	0.02	0.015
4	0.3	0.305

Table 2. Training and validation error rates

2.2. Dual form with kernels

3. Pegasos

4. Handwritten digit recognition