iptables: No chain/target/match error (with docker network create)

Asked 5 years ago Modified 2 years, 1 month ago Viewed 32k times



When creating a network (docker network create -d bridge my-nw), I obtained this error in response:





Error response from daemon: Failed to Setup IP tables: Unable to enable SKIP DNAT rule: (iptables failed: iptables --wait -t nat -I DOCKER -i br-bedba04c7349 -j RETURN: iptables: No chain/target/match by that name.




What do I need to do to go around? Docker or IP Table modifications?

docker networking iptables

Share Follow






3 Answers



Sorted by: Highest score (default)




\$



85

Share Follow







240k • 44 • 492 • 459

This command restarts the whole docker but you can just restart docker.socket – behrad Feb 1 at 7:09

@behrad Restarting the socket restarts the docker daemon, it's a dependency for running the engine. The code to reset the firewall settings is part of the engine startup. – BMitch Feb 1 at 14:48

That something in my case turned out to be temporarily disabling firewalld, but same as others restarting the docker service systemctl restart docker makes it work again – rugby2312 Oct 10 at 9:34



sudo systemctl restart docker.socket

prevent this from happening in the future.

23

Share Follow











indeed that fixes the issue, but that would even better if one could explain the root cause. - Baptiste Mille-Mathias Jan 11 at 9:09

stackoverflow.com/questions/35110146/... -@BaptisteMille-Mathias - Mohamed Farouk Jan 11 at 22:42

This will result in the docker engine being restarted. See the output of systemctl cat docker grep docker.socket to see the dependency. – BMitch Feb 1 at 14:50



This can happen when you accidently flush all your chains and tables, for example using iptables -- flush . Simply restart your docker daemon as mentioned by BMitch







