WS-90

Three-track lift & slide aluminium door

22 mm visible sightline, panels to 3.4 m, thermally broken polyamide.

SYSTEM	**WS-90 lift & slide, three tracks**
VISIBLE SIGHTLINE	**22 mm**
FRAME DEPTH	**160 mm**
MAX PANEL SIZE	**3.2 x 3.4 m**
GLASS BUILD-UP	**Double or triple IGU, 24-48 mm**
UW VALUE	**1.3 W/m2K (double, Low-E, argon)**
AIR PERMEABILITY	**Class 4 (EN 12207)**
WATER TIGHTNESS	**Class 9A (EN 12208)**
WIND RESISTANCE	**Class C5 / B5 (EN 12210)**
ACOUSTIC RATING	**38 dB (-1) Rw, double glazed**
DESIGN WIND LOAD	**5.0 kPa**
HARDWARE	**Stainless tandem rollers, 160 kg per panel**
FINISH	**Powder coat to RAL, 60-80 micron**
PROFILE ALLOY	**6063-T5 / T6, wall 2.0 mm**
THERMAL BREAK	**34 mm glass-fibre reinforced polyamide**
CERTIFICATION	**AS 2047, CE (EN 14351-1), NFRC tested**
MOQ	**4 m2 per size, mixed sizes accepted**
LEAD TIME	**25-35 days after drawing approval**

Notes

- Values are for the standard configuration and must be confirmed against the issued drawing.
- Colours on screen are approximate; finishes are matched to RAL or a physical sample.
- Quotation valid 30 days, subject to the Incoterm and payment terms stated on it.

Foshan Weinas Energy Saving Curtain Wall Doors and Windows Technology Co., Ltd.
No. 7, Dalingdi, Zhongxiu Second Village Group, Tangbian Village, Shishan Town, Foshan, Guangdong, China
+86 178 1881 9386 (WhatsApp) | liangjinhao0213@gmail.com | weinas.com

Rev. 2026-11