


1. 维数约简 (dimensionality reduction) -数据压缩 Data Compression

2D降低到1D :

Data Compression



Reduce data from
2D to 1D




$$\begin{aligned} x^{(1)} \in \mathbb{R}^2 &\rightarrow z^{(1)} \in \mathbb{R} \\ x^{(2)} \in \mathbb{R}^2 &\rightarrow z^{(2)} \in \mathbb{R} \\ &\vdots \\ x^{(m)} &\rightarrow z^{(m)} \end{aligned}$$

3D降低到2D :

Data Compression

10000 \rightarrow 1000

Reduce data from 3D to 2D



第二个应用=>可视化数据 (Data Visualization)

Data Visualization

$$x \in \mathbb{R}^{50}$$

$$x^{(i)} \in \mathbb{R}^{50}$$

| Country | x_1 GDP (trillions of US\$) | x_2 Per capita GDP (thousands of intl. \$) | x_3 Human Development Index | x_4 Life expectancy | x_5 Poverty Index (Gini as percentage) | x_6 Mean household income (thousands of US\$) | ... |
|-----------|-------------------------------------|--|----------------------------------|--------------------------|--|---|-----|
| Canada | 1.577 | 39.17 | 0.908 | 80.7 | 32.6 | 67.293 | ... |
| China | 5.878 | 7.54 | 0.687 | 73 | 46.9 | 10.22 | ... |
| India | 1.632 | 3.41 | 0.547 | 64.7 | 36.8 | 0.735 | ... |
| Russia | 1.48 | 19.84 | 0.755 | 65.5 | 39.9 | 0.72 | ... |
| Singapore | 0.223 | 56.69 | 0.866 | 80 | 42.5 | 67.1 | ... |
| USA | 14.527 | 46.86 | 0.91 | 78.3 | 40.8 | 84.3 | ... |
| ... | ... | ... | ... | ... | ... | ... | ... |

resources from en.wikipedia.org]

Andrew Ng

Data Visualization


| Country | z_1 | z_2 |
|-----------|-------|-------|
| Canada | 1.6 | 1.2 |
| China | 1.7 | 0.3 |
| India | 1.6 | 0.2 |
| Russia | 1.4 | 0.5 |
| Singapore | 0.5 | 1.7 |
| USA | 2 | 1.5 |
| ... | ... | ... |

$$z^{(i)} \in \mathbb{R}^2$$

Reduce data
from 50D
to 2D

你想要的这些二维新特征一个物理含义


Data Visualization



Andrew

2. 主成分分析 (PCA, Principal Component Analysis) : 寻找一个低维平面使得点投影到其上投影误差最小。



Principal Component Analysis (PCA) problem formulation



Principal Component Analysis (PCA) problem formulation

$$3D \rightarrow 2D$$

$$K = 2$$




Reduce from 2-dimension to 1-dimension: Find a direction (a vector $\underline{u^{(1)} \in \mathbb{R}^n}$) onto which to project the data so as to minimize the projection error.

Reduce from n -dimension to k -dimension: Find k vectors $\underline{u^{(1)}, u^{(2)}, \dots, u^{(k)}}$ onto which to project the data, so as to minimize the projection error.

PCA和线性回归比较：

PCA is not linear regression



使用PCA算法：

(1) 均值标准化和特征缩放；

Data preprocessing

Training set: $x^{(1)}, x^{(2)}, \dots, x^{(m)}$ \leftarrow

Preprocessing (feature scaling/mean normalization):

$$\mu_j = \frac{1}{m} \sum_{i=1}^m x_j^{(i)}$$


Replace each $x_j^{(i)}$ with $x_j - \mu_j$.

If different features on different scales (e.g., x_1 = size of house, x_2 = number of bedrooms), scale features to have comparable range of values.

$$x_j^{(i)} \leftarrow \frac{x_j^{(i)} - \mu_j}{s_j}$$

接下来就正式进入 PCA 的算法部分


Principal Component Analysis (PCA) algorithm



Reduce data from 2D to 1D

$$x^{(i)} \in \mathbb{R}^2 \rightarrow z^{(i)} \in \mathbb{R}$$

A 1D plot showing data points as 'x' marks along a horizontal axis. A red box labeled z_1 is at the end of the axis. An arrow points from the 2D plot to this 1D plot.



Reduce data from 3D to 2D

$$x^{(i)} \in \mathbb{R}^3 \rightarrow z^{(i)} \in \mathbb{R}^2$$
$$z = \begin{bmatrix} z_1 \\ z_2 \end{bmatrix}$$

Principal Component Analysis (PCA) algorithm

Reduce data from n -dimensions to k -dimensions

Compute "covariance matrix":

$$\Sigma = \frac{1}{m} \sum_{i=1}^n \underbrace{(x^{(i)})}_{n \times 1} \underbrace{(x^{(i)})^T}_{1 \times n} \quad \text{Sigma } n \times n$$

Compute "eigenvectors" of matrix Σ :

$$\rightarrow [U, S, V] = \text{svd}(\text{Sigma});$$

\rightarrow Singular value decomposition
 $\text{eig}(\text{Sigma})$

$n \times n$ matrix.

$$U = \begin{bmatrix} | & | & | & \dots & | \\ u^{(1)} & u^{(2)} & u^{(3)} & \dots & u^{(m)} \\ | & | & | & & | \end{bmatrix}$$

k 个方向

$$U \in \mathbb{R}^{n \times n}$$

$$u^{(1)}, \dots, u^{(k)}$$

Principal Component Analysis (PCA) algorithm

From $[U, S, V] = \text{svd}(\text{Sigma})$, we get:

$$\rightarrow U = \begin{bmatrix} | & | & & | \\ u^{(1)} & u^{(2)} & \dots & u^{(n)} \\ | & | & & | \end{bmatrix} \in \mathbb{R}^{n \times n}$$

k

$$x \in \mathbb{R}^n \rightarrow z \in \mathbb{R}^k$$

$$z^{(i)} = \underbrace{\begin{bmatrix} | & | & \dots & | \\ u^{(1)} & u^{(2)} & \dots & u^{(k)} \\ | & | & & | \end{bmatrix}^T}_{U_{\text{reduce}}} x^{(i)} = \underbrace{\begin{bmatrix} -(u^{(1)})^T & \\ \vdots & \\ -(u^{(k)})^T & \end{bmatrix}}_{k \times n} \underbrace{x^{(i)}}_{n \times 1}$$

$z \in \mathbb{R}^k$

降维得到的就是 $z(i)$

$k \times 1$

Principal Component Analysis (PCA) algorithm summary

→ After mean normalization (ensure every feature has zero mean) and optionally feature scaling:

$$\text{Sigma} = \frac{1}{m} \sum_{i=1}^m (x^{(i)})(x^{(i)})^T$$

$$X = \begin{bmatrix} - & x^{(1)T} & - \\ & \vdots & \\ - & x^{(m)T} & - \end{bmatrix}$$

$$\text{Sigma} = (1/m) * X' * X;$$

→ $[U, S, V] = \text{svd}(\text{Sigma});$

→ $\text{Ureduce} = U(:, 1:k);$

→ $z = \text{Ureduce}' * x;$

↑


↑

$x \in \mathbb{R}^n$

~~$x_0 = 1$~~

从压缩后的维重构高维：

Reconstruction from compressed representation



Andrew Ng

k选择：

Choosing k (number of principal components)

Average squared projection error: $\frac{1}{m} \sum_{i=1}^m \|x^{(i)} - x_{approx}^{(i)}\|^2$

Total variation in the data: $\frac{1}{m} \sum_{i=1}^m \|x^{(i)}\|^2$

Typically, choose k to be smallest value so that

$$\frac{\frac{1}{m} \sum_{i=1}^m \|x^{(i)} - x_{approx}^{(i)}\|^2}{\frac{1}{m} \sum_{i=1}^m \|x^{(i)}\|^2} \leq \frac{0.01}{0.10} \quad \frac{(1\%)}{(10\%)}$$

→ “99% of variance is retained”
~~95%~~ 90%
 为了保留99%的差异性

Choosing k (number of principal components)

Algorithm:

Try PCA with $k=1$ ~~$k=2$~~ ~~$k=3$~~ $k=4$


Compute $U_{reduce}, z^{(1)}, z^{(2)}, \dots, z^{(m)}, x_{approx}^{(1)}, \dots, x_{approx}^{(m)}$

Check if

$$\frac{\frac{1}{m} \sum_{i=1}^m \|x^{(i)} - x_{approx}^{(i)}\|^2}{\frac{1}{m} \sum_{i=1}^m \|x^{(i)}\|^2} \leq 0.01?$$

$k=17$

$$\rightarrow [U, S, V] = \text{svd}(\text{Sigma})$$



For given k

$$1 - \frac{\sum_{i=1}^k S_{ii}}{\sum_{i=1}^n S_{ii}} \leq 0.01$$

$$\frac{\sum_{i=1}^k S_{ii}}{\sum_{i=1}^n S_{ii}} \geq 0.99$$

Choosing k (number of principal components)

→ $[U, S, V] = \text{svd}(\text{Sigma})$

Pick smallest value of k for which

$$\frac{\sum_{i=1}^k S_{ii}}{\sum_{i=1}^m S_{ii}} \geq 0.99$$

$k=100$

(99% of variance retained)

3. 使用PCA加速学习算法。

监督学习加速：

Supervised learning speedup

→ $(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), \dots, (x^{(m)}, y^{(m)})$

Extract inputs:

Unlabeled dataset: $x^{(1)}, x^{(2)}, \dots, x^{(m)} \in \mathbb{R}^{10000}$

↓ PCA

$z^{(1)}, z^{(2)}, \dots, z^{(m)} \in \mathbb{R}^{1000}$

New training set:

$(z^{(1)}, y^{(1)}), (z^{(2)}, y^{(2)}), \dots, (z^{(m)}, y^{(m)})$

Note: Mapping $x^{(i)} \rightarrow z^{(i)}$ should be defined by running PCA only on the training set. This mapping can be applied as well to the examples $x_{cv}^{(i)}$ and $x_{test}^{(i)}$ 并扩展可以



$$h_{\theta}(z) = \frac{1}{1 + e^{-\theta^T z}}$$

$x \rightarrow z$

Bad use of PCA: To prevent overfitting

→ Use $z^{(i)}$ instead of $x^{(i)}$ to reduce the number of features to $k < n$. — 1000

Thus, fewer features, less likely to overfit.

Bad!

This might work OK, but isn't a good way to address overfitting. Use regularization instead.

$$\rightarrow \min_{\theta} \frac{1}{2m} \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)})^2 + \frac{\lambda}{2m} \sum_{j=1}^n \theta_j^2 \quad \leftarrow$$

我们使用正则化的方法来代替PCA方法

PCA is sometimes used where it shouldn't be

Design of ML system:

- - Get training set $\{(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), \dots, (x^{(m)}, y^{(m)})\}$
- - ~~Run PCA to reduce $x^{(i)}$ in dimension to get $z^{(i)}$~~
- - Train logistic regression on $\{(\cancel{z^{(1)}}), y^{(1)}), \dots, (\cancel{z^{(m)}}), y^{(m)})\}$
- - Test on test set: Map $x_{test}^{(i)}$ to $z_{test}^{(i)}$. Run $h_{\theta}(z)$ on $\{(z_{test}^{(1)}, y_{test}^{(1)}), \dots, (z_{test}^{(m)}, y_{test}^{(m)})\}$

→ How about doing the whole thing without using PCA?

> Before implementing PCA, first try running whatever you want to do with the original/raw data $x^{(i)}$. Only if that doesn't do what you want, then implement PCA and consider using $z^{(i)}$.

一开始不要将