

Lab Assignment 6

1. (20%) Please using the following declarations to complete this problem.

```
struct IntArray{
    int* ia;
    int n;
};

IntArray creatIntArray();
int findMax(const IntArray&);
void printIntArray(const IntArray&);
void deleteIntArray(IntArray&);
```

In this problem, the `IntArray` structure is used as the data to be passed around functions. The first function requires the dynamic allocation of an array of integers for the `ia` member of the `IntArray` structure. You will use the `new` keyword for the memory allocation. To prevent memory leak, you will deallocate the array in the function `deleteIntArray(IntArray&)`, using the `delete` keyword.

The following is the main method you cannot change.

```
int main(){
    IntArray intArray = creatIntArray();
    int i = findMax(intArray);
    cout << "Max value in integer array is: " << intArray.ia[i] <<
endl;
    printIntArray(intArray);
    deleteIntArray(intArray);

    return 0;
}
```

Example runs:

```
How many integers do you want to input: 5
Please input the integers: 1 2 3 4 5
Max value in integer array is: 5
Integer Array: 1 2 3 4 5
```

```
How many integers do you want to input: 3
Please input the integers: 1 3 2
Max value in integer array is: 3
Integer Array: 1 3 2
```

2. (20%) Create a class `RandomArray` that stores an int array's information:
- `n`: int, the number of elements in the array,
 - `ir`: `int*`, the pointer to the array,
 - `seed_time`: static `time_t`, the seed time for the random number generator initialized to `time(0)`.

Additionally, there are member functions:

`setSeed()`: static void, sets the seed for the random number generator, using the seed `seed_time`.

`loadArray()`: void, dynamically allocates array with new operator.

`printArray()`: void, prints the content of the array.

`freeArray()`: void, free the dynamic memory using the delete operator.

Please place the class in a separate header file with header guards, and its implementation .cpp file.

In this problem, please make data members all private and member functions all public.
The following is the main program you cannot change:

```
#include <iostream>
#include "RandomArray.h"

int main() {
    RandomArray ra(3);
    RandomArray::setSeed();

    std::cout << "Using array 1: \n";
    for(int i = 0; i < 5; i++){
        ra.loadArray();
        ra.printArray();
        ra.freeArray();
    }

    RandomArray ra2;
    ra2.loadArray();
    std::cout << "Array 2: \n";
    ra2.printArray();
    ra2.freeArray();
    return 0;
}
```

The following are sample runs:

```
Using array 1:
969    95    732
232    236   402
258    662   971
875    141   262
906    661   701
Array 2:
587    304   604   340   4
```

```
Using array 1:
881    785   136
584    940   813
962    593   622
514    299   726
720    686   846
Array 2:
459    419   268   898   149
```

3. (20%) Create a class `OOPClass`, with the following details:

`count`: static int, which counts how many objects have been created.

`printCount()`: static void, prints the current count value.

You will need to also have the appropriate constructors. In this problem, please make data members all private and member functions all public. The following is the main program you cannot change:

```
int main(){
    OOPClass a1;
    OOPClass a2;
    OOPClass a3;
    OOPClass::printCount();

    OOPClass a4;
    OOPClass a5;
    OOPClass::printCount();
}
```

The following is a sample run:

```
Instance of OOPClass created.
Instance of OOPClass created.
Instance of OOPClass created.
Instances of OOPClass: 3
Instance of OOPClass created.
Instance of OOPClass created.
Instances of OOPClass: 5
```

You should try to change the number of objects you create and see if the program can correctly display the number of created objects.