UK

Switching Power Supply User Manual

I. Warning

⚠ Do not use in damp environments to prevent electric shock

⚠ Before use, verify that the input voltage matches the device specifications

⚠ Do not disassemble or repair the unit yourself, as this may cause hazards

II. Brand

HONGPOE

III. Product Name

Switching Power Supply

IV. Instructions for Use

1. Power Connection: Insert the power cord into a wall socket
2. Device Connection: Connect the output terminals to the device requiring power
3. Power Activation: Press the power switch button to start operation

V. Precautions

1. Avoid overloading to prevent damage to the power supply
2. Ensure adequate ventilation; avoid high-temperature environments
3. Keep the power supply and plugs out of children’s reach

VI. Feature Overview

1. Stable Output: Delivers consistent voltage to safeguard connected equipment
2. Multiple Interfaces: Supports connection to various devices
3. Energy Efficiency: High-efficiency power conversion reduces energy consumption
4. Comprehensive Safety Protection: Short-circuit protection, overload protection, over-temperature protection, and over-current protection

VII. Troubleshooting

1. Unit does not operate: Verify proper connection and whether the power switch is turned on
2. Abnormal heating: May result from excessive load or inadequate ventilation
3. Failure to start: Confirm that the input voltage meets specified requirements

VIII. After-Sales Service

1. One-year warranty covering non-man-made defects with free repair service
2. For inquiries, contact customer service by phone
3. Nationwide warranty coverage available

IX. Safety Certifications

1. Complies with international mandatory safety standards (CE, UKCA, EAC)
2. Complies with electromagnetic compatibility standards (FCC)
3. Complies with hazardous substances restrictions (RoHS)
4. Complies with energy efficiency standards (DOE)



	Model	Dimensions
S-series switching power supplies	S-15-12	70*40*30MM
	S-25	85*58*38MM
	S-35	85*58*38MM
	HS-35	85*58*38MM
	S-50	111*78*36MM
	S-60	111*78*36MM
	S-75	111*78*36MM
	S-100	159*98*38MM
	S-100-5	198*98*38MM
	S-120	159*98*38MM
	S-150	198*98*38MM
	S-180	198*98*38MM
	S-200	199*110*50MM
	S-250	199*110*50MM
	S-300	215*115*50MM
	S-360	215*115*50MM
	S-400	215*115*50MM
	S-500	215*115*50MM

Note: Dimensions are measured manually and subject to slight variation.