

The Vegan Market API Documentation

Endpoint: **http://localhost:3000/api/**

| Description | Method + Path | Request / Response |
|--|---|--|
| Get all categories Endpoint: http://localhost:3000/api/ categories | GET / categories | Response: [{ id:"...", categoryName:"..." },{...}] |
| Get all products by category id Endpoint: http://localhost:3000/api/ products_of_category/:categoryId (Protected by session if user is logged in). | POST/ products_of_category/:categoryId | Request: categoryId - in params Response: [{ _id:"...", categoryId:"...", categoryName:"...", image:"...", productName:"...", price: number, },{...}] |
| Get all products by category id Endpoint: http://localhost:3000/api/ products_of_category/:categoryId (Protected by session if user is logged in). | POST/ products /:productName | Request: categoryId - in params Response: [{ _id:"...", categoryId:"...", categoryName:"...", image:"...", productName:"...", price: number, },{...}] |

| | | |
|--|----------------------|---|
| <p>Create new order</p> <p>Endpoint: http://localhost:3000/api/orders (Protected by session if user is logged in).</p> | <p>POST/ orders</p> | <p>Request:</p> <pre>{ city:"...", street:"...", deliveryDate:"...", creditCard: number }</pre> <p>Response:</p> <pre>{ status:" received", orderId:"..." }</pre> |
| <p>Edit product – for admin only</p> <p>Endpoint: http://localhost:3000/api/products (Protected by session if admin is logged in).</p> | <p>PUT/ products</p> | <p>Request:</p> <pre>{ _id:"...", newProduct:{ productName:"...", categoryId:"...", price: number, image:"..." } }</pre> <p>Response:</p> <pre>{ msg: "Product updated successfully." }</pre> |

| | | |
|--|----------------|--|
| Add product – for admin only Endpoint: http://localhost:3000/api/ products (Protected by session if admin is logged in). | POST/ products | Request: { productName:"...", categoryId:"...", price: number, image:"..." } Response: { msg: "Product added successfully." } |
|--|----------------|--|