

Buddy — iPhone Shortcut & Quick Capture Guide

Single endpoint, one API key, AI by default, flags to skip the AI. Updated 2026-05-13.

1. The new picture

Before: your **Todo** Shortcut posted text to `/functions/v1/quick-note`. That endpoint only saved *notes* with simple `-flag` sorting. No AI, no tasks, no reminders, no confirmation.

After: one Shortcut posts text to `/functions/v1/assistant` — the same backend the in-app chat uses. It supports:

- **Plain text** → AI classifies and routes (note, task, reminder, mood, journal, check-in, etc.).
- **Slash commands** (`/task` , `/remind` ...) → skip the AI, zero cost.
- **Dash flags** (`-task` , `-remind` ...) → same as slash commands, easier to type on mobile.
- **JSON response** with `action_taken` → show as an iPhone notification to confirm what fired.

2. Authentication (no change)

Keep using the API key from **Account** → **Quick Capture API**. The assistant endpoint accepts the exact same key (it looks up the same `quick_note_api_key` setting). You don't need to regenerate.

3. Rebuild the Shortcut

Open *Shortcuts*, edit your **Todo** shortcut, delete the two existing actions, and add these:

Step 1 — Ask for Input

Field	Value
Input Type	Text
Prompt	Capture (or anything you like)

Step 2 — Get Contents of URL

Field	Value
URL	<code>https://kdwgznfszbrysepsltua.supabase.co/functions/v1/assistant</code>
Method	POST

Headers	Content-Type = application/json
Request Body	JSON
JSON keys	input → <i>Provided Input</i> (the text from step 1) api_key → your API key from Account source → iphone

Your previous URL ended in `/quik-note` (typo) — that endpoint never worked. Use the URL above exactly, ending in `/assistant`.

Step 3 — Get Dictionary Value

From *Contents of URL*. Get value for key `action_taken`.

Step 4 — Show Notification

Field	Value
Title	Buddy
Body	Dictionary Value from step 3

Optional polish. Add an *If* branch after step 2: get the `success` key — if it's `true`, run step 3+4 with a check-mark title; otherwise grab `error` or `action_taken` and show a warning notification.

4. The flag system (refined)

Three tiers run before the AI; the first one to match wins. AI is the fallback.

1. **Slash command** — `/task fix bike by friday`
2. **Dash flag** — `-task fix bike by friday` (translates to `/task ...`)
3. **Regex rule** — natural-language patterns (e.g. "herinner me om 14:00...")
4. **AI** — anything else (default route)

Flag reference

Flag (EN)	Flag (NL)	Slash form	What it does	Example payload
<code>-task / -todo</code>	<code>-taak</code>	<code>/task</code>	Create a task. Accepts due date in text.	<code>-task fix bike by friday</code>
<code>-done</code>	<code>-klaar</code>	<code>/done</code>	Complete a task by title.	<code>-done fix bike</code>

-note	-notitie	/note	Create a smart note.	-note idea for chapter intro
-find	-zoek	/find	Search notes.	-find linear algebra
-shop	-boodschap / -boodschappen	/shop	Add to shopping list.	-shop milk, eggs
-remind / -reminder	-herinner / -herinnering	/remind	Schedule a reminder. Needs a time.	-remind 14:00 call dentist -remind in 2 uur opbellen
-mood	-stemming	/mood	Log mood (1-5 + note).	-mood 4 feeling good
-checkin	-meting	/checkin	Log tracker values.	-checkin sleep 7 energy 3
-journal	-dagboek	/journal	Write a journal entry.	-journal today I noticed...
-goal	-doel	/goal	Create a goal.	-goal read 20 books this year
-study	-studie	/study	Log a study session.	-study linear algebra 2h
-agenda	—	/agenda	Show today's calendar.	-agenda
-habits	-gewoontes	/habits	Streaks & open tasks.	-habits

Reminders & extras (the "-remind needs a time" case)

When a flag needs an extra (time, value, score), include it in the same line. Examples that work without AI:

```
-remind 14:00 call dentist
-remind 20:30 take supplements
-remind in 2 uur opbellen
-checkin sleep 7 energy 3 mood 4
-mood 4 long walk this morning
-study Linear algebra 90m
-goal Run 5km by 2026-09-01
```

If the backend can't parse the extra (e.g. `-remind buy milk` with no time), the response comes back as:

```
{
  "success": false,
  "action_taken": "Reminder needs a time. Try \"/remind 14:00 call dentist\" or \"in 2 uur opbellen\".",
  "data": { "needs_param": "time", "example": "/remind 14:00 call dentist" }
}
```

Your Shortcut already shows `action_taken` as a notification, so you'll see this on your lock screen and can try again. If you want, add a follow-up step for reminders specifically:

Two-step reminder Shortcut.

1. *Ask for Input* — "What should I remind you of?"
2. *Ask for Input* — "When?" (e.g. 14:00 or in 2 uur)
3. *Text action* — combine into `-remind {When} {What}`
4. *Get Contents of URL* — same as above, with that text as `input`.

This is the closest you can get to "iPhone prompts for extras". Shortcuts doesn't support reading a response and asking another question in one chain without you wiring it up explicitly.

5. Sample request & response

Request

```
POST /functions/v1/assistant
Content-Type: application/json
```

```
{
  "input": "-task buy groceries tomorrow",
  "api_key": "your-key-here",
  "source": "iphone"
}
```

Response (success)

```
{
  "success": true,
  "intent": "task.create",
  "domain": "planning",
  "action_taken": "Created task 'buy groceries' due 2026-05-14",
  "data": { "task_id": "...", "title": "buy groceries", "due_date":
```

```
"2026-05-14" }  
}
```

Response (free text → AI)

```
POST ... { "input": "remember to call mom on sunday", "api_key": "...",  
"source": "iphone" }
```

```
{  
  "success": true,  
  "intent": "task.create",  
  "domain": "planning",  
  "action_taken": "Created task 'call mom' due 2026-05-17",  
  "data": { ... }  
}
```

6. Multiple Shortcuts (optional)

You can keep ONE catch-all Shortcut, or build a few focused ones — same endpoint, same body, just prefilling the flag:

Shortcut name	Prefilled body
Buddy: Capture	<code>input</code> = Provided Input (no flag — AI routes it)
Buddy: Task	<code>input</code> = <code>-task</code> + Provided Input
Buddy: Remind	Two prompts (What? + When?) combined into <code>-remind {When} {What}</code>
Buddy: Shop	<code>input</code> = <code>-shop</code> + Provided Input
Buddy: Mood	<code>input</code> = <code>-mood</code> + Provided Input

Tip: back-tap on iPhone can only run one shortcut, so pick the catch-all for back-tap and put the focused ones on the home screen / Siri.

7. Troubleshooting

Symptom	Check
401 Authentication failed	API key wrong or not saved. Regenerate from Account.
400 input is required	Body JSON missing <code>input</code> . Verify Step 2 has Request Body set to JSON, not Form.

Notification shows raw JSON	Step 3 missing — add "Get Dictionary Value" for <code>action_taken</code> before "Show Notification".
Reminders never fire	You need a working push subscription. Open the web app once, allow notifications, confirm in Account.
Free text routed to wrong tool	Add a flag prefix to force routing — flags always beat the AI.

8. What changed in this rehaul

- **Endpoint switch:** Shortcut now points at `/functions/v1/assistant` (full backend) instead of `/functions/v1/quick-note` (notes only).
 - **Flag system expanded:** 14 new flag aliases (EN + NL) in `command-parser.ts` — every common slash command has a dash twin.
 - **Better reminder errors:** when a time is missing the response includes `needs_param: "time"` with a usable example.
 - **Account page docs:** updated to show new endpoint, body shape, and the full flag cheat sheet.
-

Edge function: `supabase/functions/assistant/` · Flag mapping: `core/command-parser.ts` · Reminder handler: `tools/notifications.tool.ts`