

**Solutions****6.1 Interrupts**

1) Consider the system diagram in Figure 1 of case study notes.

- The processor UART peripheral in its Serial I/O module is configured to receive data with format of 1 start-bit, 7 data-bits, 1 parity-bit and 1 stop-bit.
- Each time the UART peripheral receives a character, it'll store the data into a buffer.
- It will then interrupt the CPU to notify CPU that there is data available.
- The CPU will then execute the Interrupt Service Routine (ISR) to read the character received.
- Interrupt Latency is the term used to describe the time between interrupt request and entrance to ISR.
- The minimum interrupt latency for the CPU is 10  $\mu$ s and it takes 90  $\mu$ s for the CPU to execute the instructions in the ISR (read the received data from the buffer).
- Assume that the UART data is transferred back to back i.e. no delays between each UART packets.

What is the maximum baud rate that can be supported with this UART interface?

[Suggested Solution]

Sequence of event:

- External device send a character via UART to processor.
- Processors UART peripheral receive the character in its buffer and interrupt the CPU
- CPU proceed to execute the ISR corresponding to the UART interrupt to read and transfer the character to main memory.
- Total time required to transfer one character = Interrupt Latency + ISR execution.

$1 / (10+90) \mu\text{s} = 10000$  ISRs serviced per second

Each character transfer involved 10 bits on UART (S-7D-P-STP).

$10 \text{ bits} * 10000 = 100 \text{ Kbits per second}$

2) The specifications of the system in Figure 1 (case study notes) requires the buttons to be asserted 400 times over a 24-hour period. Given that the processor consumes 0.1mA current when it is idling and 50mA when it is in active mode i.e. running code, answer the following.

(a) Supposed polled IO technique is used to sample the button status. Given that the processor poll the buttons every 100ms, each poll requires the processor to be active for 10ms, what is the average current consumed over the 24-hour period?

**Solutions**

- (b) If interrupt-driven I/O is used to sample the button status, what is the average current consumed in the same 24-hour period? Given that it takes 20ms to service each interrupt, including interrupt latency and ISR execution.
- (c) Given that a battery with capacity of 2000mAh means that it can supply 2000mA continuously for 1 hour, or 1000mA continuously for 2 hours. How long would a battery of 2000mAh last when used in (a) and (b) above?

**[Suggested Solution]**

- (a) Polled every 100ms, each poll takes 10ms

⇒ 90ms(idle), 10ms(active).

⇒ Average current =  $0.9 \times 0.1\text{mA} + 0.1 \times 50\text{mA} = 5.09\text{mA}$

- (b) Interrupt mechanism.

⇒ Interrupted 400 times over 24-hour

⇒ Active time =  $400 \times 20\text{ms} = 8000\text{ms}$

⇒ Average current consumed over 24-hour

$$= [8 \times 50\text{mA} + ((24 \times 60 \times 60) - 8) \times 0.1\text{mA}] / [24 \times 60 \times 60]$$

$$= 0.1046\text{mA}$$

- (c) Use case (a) (Polling)

a. Average current consumed 5.09mA

b. Battery life =  $2000\text{mAh} / 5.09\text{mA} = 393 \text{ hours} = 16.4 \text{ days}$

- Use case (b) (Interrupt)

a. Average current consumed 0.1046 mA

b. Battery life =  $2000\text{mAh} / 0.1046\text{mA} = 19120 \text{ hours} = 797 \text{ days} = 2.2 \text{ years}$

**6.2 Direct Memory Access (DMA)**

- 3) Given that DMAC and CPU share one system bus, list four possible factors that might affect the transfer rate of a DMAC and explain how they affect the DMAC transfer rate.

**[Suggested Solution]**

- CPU competes with the DMAC (DMA Controller) where system bus utilization is concerned. Higher CPU utilization rate (of the system bus) means lesser chance for DMAC to use the same bus, hence DMA data transfer rate will be affected.
- The competition for resources is also affected by the priority of DMAC with respect to the CPU. Depending on processor design, priority of CPU with respect to DMAC can be fixed or configurable. The one with higher priority will have higher chance of hitting their maximum possible transfer rate.


**Solutions**

- Maximum Data transfer rate is limited by the slowest device in the whole data path consisting of the source device, DMAC and destination device. If there is a memory or I/O device that is slow, it'll affect the overall DMA transfer rate.
- All things equal, the mode of transfer used by the DMAC (burst, cycle stealing or transparent) will affect the DMAC transfer rate.

**Solutions**

4) Consider the system in Figure 1 (Case study notes). Given that

- The processor's system bus is capable of supporting simultaneous transfer of up to 3 bytes of data at one time.
- DMA is used to transfer video data from Memory to Display Controller module.
- Each video pixel data consist of three bytes (Red, Green, Blue) and are transferred simultaneously on the system bus on each bus cycle.
- Each transfer on the system bus takes 5ns and transfer of the bus control between the CPU and the DMAC takes 100ns.
- Assume that DMAC is using Fetch-and-Deposit DMA.
- Note that 1Kbyte = 1024 Byte.



(a) Given that the video is output at a rate of 30 frames per second and each video frame has a resolution of 1920x1080 pixels. If burst-mode was used by the DMAC to burst one frame of video data at a time, would the DMAC be able to transfer each video frame completely?

**[Suggested Solution]**

Each transfer of the system bus will transfer 3 bytes of video data (RGB) and take 2\*5ns.

Number of transfers in 1/30 seconds =  $1920 \times 1080 = 2073600$  transfers.

Total time taken

= Bus control request + actual transfer + Bus release

=  $100\text{ns} + 2073600 \times 2 \times 5\text{ns} + 100\text{ns} = 0.0207362 \text{ sec} < 1/30\text{sec}$

⇒ DMAC is able to transfer each frame of video before the start of the next frame request.

**Solutions**

- (b) Repeat the calculation if the DMAC is using cycle-stealing mode, assume that DMAC needs to wait at least 5 instructions before it could request for control of the system bus again.

[Suggested Solution]

Time taken for one transfer

= Bus control request + 1 transfer + Bus release + 5\*CPU Clock cycles wait

= 100ns + 2\*5ns + 100ns + 5\*(1/400Mhz) = 222.5ns

Total time taken for 2073600 transfers = 2073600\*222.5ns = 0.461376 sec > 1/30sec

⇒ DMAC will not be able to complete the transfer of one video frame before the next frame request comes in

Note that the last 5\*CPU clock cycles wait is added in the above calculation to simplify the calculation process. But it'll not meet the requirement (>100%) even if it is taken into account.

Note: the '400 Mhz' for CPU clock is taken from the processor information in the case study notes.