

General

源码管理

构建触发器

构建环境

构建

构建后操作

描述

[纯文本] 预览

GitLab Connection

gitlab

- ☐ This build requires lockable resources
- ☐ Throttle builds
- ☐ 丢弃旧的构建
- ☐ 参数化构建过程
- ☐ 关闭构建
- ☐ 在必要的时候开发构建



高级...

源码管理

- ☐ 无
- ☒ Git

Repositories

Repository URL

ssh://git@192.168.5.54:2224/dfk/hello.git

Credentials

- 无 -

添加

高级...

Add Repository

Branches to build

指定分支（为空时代表any）

*/master

增加分支

源码库浏览器

(自动)

Additional Behaviours

新增

- ☐ Subversion

构建触发器

- ☐ 触发远程构建 (例如,使用脚本)
- ☐ 其他工程构建后触发
- ☐ 定时构建
- ☒ Build when a change is pushed to GitLab. GitLab webhook URL: http://192.168.5.54:8080/project/zhoujun_h5

Enabled GitLab triggers

Push Events

Opened Merge Request Events

Accepted Merge Request Events

Closed Merge Request Events

Rebuild open Merge Requests

Never

Approved Merge Requests (EE-only)

Comments

Comment (regex) for triggering a build

Jenkins please retry a build

高级...

- ☐ 轮询 SCM

构建环境

- ☐ Delete workspace before build starts
- ☐ Use secret text(s) or file(s)
- ☒ Send files or execute commands over SSH before the build starts

SSH Publishers

SSH Server

Name

192.168.5.54

高级...

Transfers

Transfer Set

Source files

**/*

Remove prefix

Remote directory

/download/hell-\$BUILD_NUMBER

Exec command

cp /root/download/hell-\$BUILD_NUMBER/ /root

All of the transfer fields (except for Exec timeout) support substitution of [Jenkins environment variables](#)

高级...

Add Transfer Set

Add Server

高级...

- ☐ Send files or execute commands over SSH after the build runs
- ☐ Abort the build if it's stuck
- ☐ Add timestamps to the Console Output
- ☐ Execute shell script on remote host using ssh
- ☐ Inspect build log for published Gradle build scans
- ☐ With Ant

构建

Execute shell script on remote host using ssh

SSH site

root@192.168.5.54:22

Command

cd /root/download/hell-\$BUILD_NUMBER
mkdir good

Execute each line

Hide command from console output

增加构建步骤

构建后操作

增加构建后操作步骤