

General

源码管理

构建触发器

构建环境

构建

构建后操作

项目名称

【测试环境】v4\_app\_h5

描述

[Plain text] 预览

GitHub project

GitLab connection

gitlabServer

Throttle builds

丢弃旧的构建

参数化构建过程

关闭构建

在必要的时候并发构建

高级...

源码管理

None

Git

Repositories

Repository URL

git@192.168.5.130:zzh/app/app-h5.git

Credentials

- none -

高级...

Add Repository

Branches to build

Branch Specifier (blank for 'any')

\*/master

高级...

Add Branch

源码库浏览器

(自动)

高级...

Additional Behaviours

Add

Subversion

高级...

构建触发器

触发远程构建 (例如, 使用脚本)

Build after other projects are built

Build periodically

Build when a change is pushed to GitLab. GitLab CI Service URL: http://192.168.5.40:5600/project/%E3%80%90%E6%B5%8B%E8%AF%95%E7%8E%AF%E5%A2%83%E3%80%91v4\_app\_h5

Enabled GitLab triggers

Push Events

Opened Merge Request Events

Accepted Merge Request Events

Closed Merge Request Events

Rebuild open Merge Requests

Comments

Comment (regex) for triggering a build

Enable [ci-skip]

Ignore WIP Merge Requests

Set build description to build cause (eg. Merge request or Git Push )

Build on successful pipeline events

Allowed branches

Allow all branches to trigger this job

Filter branches by name

Filter branches by regex

Filter merge request by label

Secret token

69c474a280c127fbeb74fb3c48a75da9

Generate

Clear

GitHub hook trigger for GITScm polling

Poll SCM

构建环境

Delete workspace before build starts

Send files or execute commands over SSH before the build starts

SSH Publishers

SSH Server

Name

192.168.5.141

高级...

Transfers

Transfer Set

Source files

\*\*/\*.Dockerfile

Remove prefix

高级...

Remote directory

/download/v4/app\_h5/app\_h5-\${BUILD\_NUMBER}

高级...

Exec command

rm -r /root/web/v4/app\_h5/test/src  
cp -r /root/download/v4/app\_h5/app\_h5-\${BUILD\_NUMBER}/src/ /root/web/v4/app\_h5/test/  
cp -r /root/download/v4/app\_h5/app\_h5-\${BUILD\_NUMBER}/Dockerfile /root/web/v4/app\_h5/test/

高级...

Either Source files, Exec command or both must be supplied  
All of the transfer fields (except for Exec timeout) support substitution of [Jenkins environment variables](#)

Add Transfer Set

Add Server

Publish to other SSH servers if an error occurs

Fail the build if an error occurs

Always SSH from master

Parameterized publishing

Send files or execute commands over SSH after the build runs

Abort the build if it's stuck

Add timestamps to the Console Output

Execute shell script on remote host using ssh

Use secret text(s) or file(s)

With Ant

构建

Execute shell script on remote host using ssh

SSH site

root@192.168.5.141:22

Command

#if docker ps -a | grep -i pc\_gkcx; then  
docker rm -f app\_h5  
#fi  
#if docker images -a | grep -i zzh/pc\_gkcx; then  
docker rmi -f zzh/app\_h5  
#fi  
cd /root/web/v4/app\_h5/test  
docker build -t zzh/app\_h5 .  
docker run -dit --name app\_h5 -p 5027:80 zzh/app\_h5 latest

Execute each line

增加构建步骤

构建后操作

增加构建后操作步骤

生成 页面: 2020-5-14 下午02时32分32秒

REST API

Jenkins ver. 2.60.3