Polyspace Bug Finder

Detailed Report for Project: rx8025t

Report Author: LibDriver

Polyspace Bug Finder: Detailed Report for Project: rx8025t

by Report Author: LibDriver

Published 28-Apr-2026 01:33:28

Analysis Author(s): LibDriver

Polyspace Version(s): Polyspace Bug Finder 3.2 (R2020a)

Project Version(s): 1.0

Result Folder(s):

E:\Polyspace\rx8025t\Module\BF_Result

Table of Contents

Chapter 1. Polyspace Bug Finder Summary 1

Chapter 2. MISRA C:2012 Guidelines 3

MISRA C:2012 Guidelines Summary - Violations by File 3

MISRA C:2012 Guidelines Violations 3

Chapter 3. Defects 61

Defects 61

Chapter 4. Appendix 1 - Configuration Settings 62

Polyspace Settings 62

Coding Standard Configuration 63

Chapter 5. Appendix 2 - Definitions 71

Chapter 1. Polyspace Bug Finder Summary

Table 1.1. Project Summary

	Count	Reviewed	Unreviewed	Pass/Fail
MISRA C:2012 Guidelines	589	586	3	Pass
Defects	0	0	0	Pass
Total	**589**	**586**	**3**	**Pass**

Table 1.2. Summary By File

File	Defects (Reviewed)	MISRA C:2012 Guidelines (Reviewed)
E:\Github\rx8025t\example\driver_rx8025t_alarm.c	0 (0)	25 (25)
E:\Github\rx8025t\example\driver_rx8025t_alarm.h	0 (0)	0 (0)
E:\Github\rx8025t\example\driver_rx8025t_basic.c	0 (0)	24 (24)
E:\Github\rx8025t\example\driver_rx8025t_basic.h	0 (0)	0 (0)
E:\Github\rx8025t\example\driver_rx8025t_timer.c	0 (0)	24 (24)
E:\Github\rx8025t\example\driver_rx8025t_timer.h	0 (0)	0 (0)
E:\Github\rx8025t\interface\driver_rx8025t_interface.h	0 (0)	0 (0)
E:\Github\rx8025t\interface\driver_rx8025t_interface_template.c	0 (0)	11 (11)
E:\Github\rx8025t\src\driver_rx8025t.c	0 (0)	195 (195)
E:\Github\rx8025t\src\driver_rx8025t.h	0 (0)	0 (0)
E:\Github\rx8025t\test\driver_rx8025t_alarm_test.c	0 (0)	53 (51)
E:\Github\rx8025t\test\driver_rx8025t_alarm_test.h	0 (0)	0 (0)
E:\Github\rx8025t\test\driver_rx8025t_register_test.c	0 (0)	214 (214)

E:\Github\rx8025t\test\driver_rx8025t_register_test.h	0 (0)	0 (0)
E:\Github\rx8025t\test\driver_rx8025t_timer_test.c	0 (0)	43 (42)
E:\Github\rx8025t\test\driver_rx8025t_timer_test.h	0 (0)	0 (0)

Chapter 2. MISRA C:2012 Guidelines

MISRA C:2012 Guidelines Summary - Violations by File

File	Total
E:\Github\rx8025t\example\driver_rx8025t_alarm.c	25
E:\Github\rx8025t\example\driver_rx8025t_basic.c	24
E:\Github\rx8025t\example\driver_rx8025t_timer.c	24
E:\Github\rx8025t\interface\driver_rx8025t_interface_template.c	11
E:\Github\rx8025t\src\driver_rx8025t.c	195
E:\Github\rx8025t\test\driver_rx8025t_alarm_test.c	53
E:\Github\rx8025t\test\driver_rx8025t_register_test.c	214
E:\Github\rx8025t\test\driver_rx8025t_timer_test.c	43
Total	**589**

MISRA C:2012 Guidelines Violations

Table 2.1. E:\Github\rx8025t\example\driver_rx8025t_alarm.c

ID	Guideline	Message	Function	Severity	Status	Comment
509	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
437	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
454	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
275	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
406	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
381	2.2	There shall be no dead code.	File Scope	Low	Justified	print function.

		The call to function rx8025t_interface_debug_print has no effect.				
357	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
564	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
403	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
446	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
217	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type short shall not be cast to the wider essential type time_t.	rx8025t_alarm_set_timestamp()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
218	21.10	The Standard Library time and date functions shall not be used.	rx8025t_alarm_set_timestamp()	Low	Not a defect	We use this function to convert driver data and drivers guarantee the safety of the operation.
220	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category signed shall not be cast to the different essential type category unsigned.	rx8025t_alarm_set_timestamp()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
221	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_alarm_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
222	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_alarm_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of

						the operation.
224	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_alarm_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
227	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_alarm_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
225	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_alarm_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
228	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_alarm_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
226	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_alarm_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
583	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	rx8025t_alarm_get_timestamp()	Low	Justified	(handle == NULL)checked.
219	21.10	The Standard Library time and date functions shall not be used.	rx8025t_alarm_get_timestamp()	Low	Not a defect	We use this function to convert driver data and drivers guarantee the safety of the operation.
584	D4.7	If a function returns error information, then that error information shall be tested. A sensitive function returns error or state information. Check the return value before using it.	rx8025t_alarm_get_timestamp()	Low	Justified	We use this function to convert driver data and drivers guarantee the safety of the operation.

223	10.7	If a composite expression is used as one operand of an operator in which the usual arithmetic conversions are performed then the other operand shall not have wider essential type. The left operand of the - operator shall not have wider essential type (signed on 32 bits) than the right operand (signed on 16 bits) which is a composite expression	rx8025t_alarm_get_timestamp()	Low	Not a defect	We use this function to convert driver data and drivers guarantee the safety of the operation.
585	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	rx8025t_alarm_get_timestamp_time_zone()	Low	Justified	(handle == NULL)checked.

Table 2.2. E:\Github\rx8025t\example\driver_rx8025t_basic.c

ID	Guideline	Message	Function	Severity	Status	Comment
362	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
342	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
350	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
286	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
280	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
290	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
276	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
274	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
265	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
190	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type short shall not be cast to the wider essential type time_t.	rx8025t_basic_set_timestamp()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and

						drivers guarantee the safety of the operation.
192	21.10	The Standard Library time and date functions shall not be used.	rx8025t_basic_set_timestamp()	Low	Not a defect	We use this function to convert driver data and drivers guarantee the safety of the operation.
194	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category signed shall not be cast to the different essential type category unsigned.	rx8025t_basic_set_timestamp()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
191	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_basic_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
193	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_basic_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
195	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_basic_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
197	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_basic_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
199	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_basic_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of

						the operation.
196	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_basic_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
201	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_basic_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
571	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	rx8025t_basic_get_timestamp()	Low	Justified	(handle == NULL)checked.
198	21.10	The Standard Library time and date functions shall not be used.	rx8025t_basic_get_timestamp()	Low	Not a defect	We use this function to convert driver data and drivers guarantee the safety of the operation.
572	D4.7	If a function returns error information, then that error information shall be tested. A sensitive function returns error or state information. Check the return value before using it.	rx8025t_basic_get_timestamp()	Low	Justified	We use this function to convert driver data and drivers guarantee the safety of the operation.
200	10.7	If a composite expression is used as one operand of an operator in which the usual arithmetic conversions are performed then the other operand shall not have wider essential type. The left operand of the - operator shall not have wider essential type (signed on 32 bits) than the right operand (signed on 16 bits) which is a composite expression	rx8025t_basic_get_timestamp()	Low	Not a defect	We use this function to convert driver data and drivers guarantee the safety of the operation.
575	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	rx8025t_basic_get_timestamp_time_zone()	Low	Justified	(handle == NULL)checked.

Table 2.3. E:\Github\rx8025t\example\driver_rx8025t_timer.c

ID	Guideline	Message	Function	Severity	Status	Comment
560	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

492	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
558	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
567	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
555	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
414	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
546	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
552	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
533	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
250	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type short shall not be cast to the wider essential type time_t.	rx8025t_timer_set_timestamp()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
255	21.10	The Standard Library time and date functions shall not be used.	rx8025t_timer_set_timestamp()	Low	Not a defect	We use this function to convert driver data and drivers guarantee the safety of the operation.
252	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category signed shall not be cast to the different essential type category unsigned.	rx8025t_timer_set_timestamp()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
256	10.3	The value of an expression shall not be assigned to an object with a	rx8025t_timer_get_timestamp()	Low	Not a defect	Embedded drivers need

		narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)				this method to set or clear some bits and drivers guarantee the safety of the operation.
254	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_timer_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
253	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_timer_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
257	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_timer_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
251	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_timer_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
259	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_timer_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
258	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category unsigned) is assigned to an object with a different essential type category (signed)	rx8025t_timer_get_timestamp()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
580	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	rx8025t_timer_get_timestamp()	Low	Justified	(handle == NULL)checked.

260	21.10	The Standard Library time and date functions shall not be used.	rx8025t_timer_get_timestamp()	Low	Not a defect	We use this function to convert driver data and drivers guarantee the safety of the operation.
581	D4.7	If a function returns error information, then that error information shall be tested. A sensitive function returns error or state information. Check the return value before using it.	rx8025t_timer_get_timestamp()	Low	Justified	We use this function to convert driver data and drivers guarantee the safety of the operation.
261	10.7	If a composite expression is used as one operand of an operator in which the usual arithmetic conversions are performed then the other operand shall not have wider essential type. The left operand of the - operator shall not have wider essential type (signed on 32 bits) than the right operand (signed on 16 bits) which is a composite expression	rx8025t_timer_get_timestamp()	Low	Not a defect	We use this function to convert driver data and drivers guarantee the safety of the operation.
582	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	rx8025t_timer_get_timestamp_time_zone()	Low	Justified	(handle == NULL)checked.

Table 2.4. E:\Github\rx8025t\interface\driver_rx8025t_interface_template.c

ID	Guideline	Message	Function	Severity	Status	Comment
245	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_interface_receive_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
540	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
246	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_interface_receive_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
527	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
248	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category.	rx8025t_interface_receive_callback()	Low	Not a defect	Embedded drivers need this method to set or clear

		The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)				some bits and drivers guarantee the safety of the operation.
349	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
247	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_interface_receive_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
525	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
249	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_interface_receive_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
534	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
515	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

Table 2.5. E:\Github\rx8025t\src\driver_rx8025t.c

ID	Guideline	Message	Function	Severity	Status	Comment
1	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	a_rx8025t_bcd2hex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
4	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	a_rx8025t_bcd2hex()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
5	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential	a_week_convert()	Low	Not a defect	Embedded drivers need this method to set or

		type category signed.				clear some bits and drivers guarantee the safety of the operation.
2	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_temperature_compensation_interval()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
15	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_temperature_compensation_interval()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
35	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_temperature_compensation_interval()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
11	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_temperature_compensation_interval()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
7	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_temperature_compensation_interval()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
9	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_temperature_compensation_interval()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
20	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category enum.	rx8025t_set_temperature_compensation_interval()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

						safety of the operation.
22	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_temperature_compensation_interval()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
8	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_temperature_compensation_interval()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
26	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_temperature_compensation_interval()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
31	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_temperature_compensation_interval()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
99	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_update_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
150	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_update_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
185	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_update_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

						safety of the operation.
24	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_update_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
130	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_update_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
36	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_update_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
104	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_update_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
127	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category enum.	rx8025t_set_update_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
30	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_update_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
34	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_update_interrupt()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of

						the operation.
40	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_update_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
13	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_timer_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
27	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_timer_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
142	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_timer_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
123	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_timer_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
114	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_timer_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
41	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_timer_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
44	10.1	Operands shall not be of an inappropriate essential type.	rx8025t_set_timer_interrupt()	Low	Not a	Embedded drivers need

		The right operand of the |= operator is of an inappropriate essential type category enum.			defect	this method to set or clear some bits and drivers guarantee the safety of the operation.
131	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_timer_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
54	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_timer_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
47	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_timer_interrupt()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
62	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_timer_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
16	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_alarm_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
48	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_alarm_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

68	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_alarm_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
49	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_alarm_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
86	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_alarm_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
52	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category enum.	rx8025t_set_alarm_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
55	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_alarm_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
124	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_alarm_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
28	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_alarm_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
160	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type.	rx8025t_get_alarm_interrupt()	Low	Not a defect	We use enumeration to define driver

		The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.				configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
51	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_alarm_interrupt()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
33	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_stop()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
45	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_stop()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
94	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_stop()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
183	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_stop()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
43	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_stop()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
60	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type	rx8025t_stop()	Low	Not a	Embedded drivers need this method to set or

		category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially signed type.			defect	clear some bits and drivers guarantee the safety of the operation.
140	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category signed.	rx8025t_stop()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
166	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_stop()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
38	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_start()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
84	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_start()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
119	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_start()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
25	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_start()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
79	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_start()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

						safety of the operation.
46	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
63	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
65	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
179	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
64	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
42	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category enum.	rx8025t_set_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
57	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
139	10.3	The value of an expression shall not be assigned to an object with a	rx8025t_set_test()	Low	Not a	Embedded drivers need

		narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)			defect	this method to set or clear some bits and drivers guarantee the safety of the operation.
67	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
72	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_test()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
71	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
73	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_alarm_day_week()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
74	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_alarm_day_week()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
171	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_alarm_day_week()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

14	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_alarm_day_week()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
39	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_alarm_day_week()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
21	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_alarm_day_week()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
148	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category enum.	rx8025t_set_alarm_day_week()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
173	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_alarm_day_week()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
163	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_alarm_day_week()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
169	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_alarm_day_week()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.

168	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_alarm_day_week()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
267	5.8	Identifiers that define objects or functions with external linkage shall be unique. variable select conflicts with the function name select (select.h line 108).	File Scope	Low	Justified	Can't be.
76	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_update_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
146	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_update_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
161	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_update_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
75	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_update_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
19	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_update_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
59	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category.	rx8025t_set_update_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and

		The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.				drivers guarantee the safety of the operation.
70	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category enum.	rx8025t_set_update_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
78	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_update_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
180	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_update_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
387	5.8	Identifiers that define objects or functions with external linkage shall be unique. variable select conflicts with the function name select (select.h line 108).	File Scope	Low	Justified	Can't be.
80	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_update_select()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
81	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_update_select()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
83	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an	rx8025t_set_timer()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

		object with a different essential type category (unsigned)				safety of the operation.
111	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_timer()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
176	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_timer()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
82	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_timer()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
77	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_timer()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
50	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_timer()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
88	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_timer()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
98	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category enum.	rx8025t_set_timer()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
87	10.1	Operands shall not be of an inappropriate essential type.	rx8025t_set_timer()	Low	Not a	Embedded drivers need

		The left operand of the << operator is of an inappropriate essential type category enum.			defect	this method to set or clear some bits and drivers guarantee the safety of the operation.
126	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_timer()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
89	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_timer()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
53	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_square_wave_frequency()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
58	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_square_wave_frequency()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
91	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_square_wave_frequency()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
105	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_square_wave_frequency()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

90	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_square_wave_frequency()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
85	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_square_wave_frequency()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
96	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_square_wave_frequency()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
108	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category enum.	rx8025t_set_square_wave_frequency()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
92	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_square_wave_frequency()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
122	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_square_wave_frequency()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
100	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_square_wave_frequency()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

93	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_timer_clock()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
102	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_timer_clock()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
158	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_timer_clock()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
137	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_timer_clock()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
101	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_timer_clock()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
23	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_timer_clock()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
66	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category enum.	rx8025t_set_timer_clock()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
95	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category.	rx8025t_set_timer_clock()	Low	Not a defect	Embedded drivers need this method to set or

		The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)				clear some bits and drivers guarantee the safety of the operation.
134	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_timer_clock()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
10	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_timer_clock()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
113	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_timer_clock()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
164	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type unsigned on 16 bits) is assigned to an object with a narrower essential type (unsigned on 8 bits)	rx8025t_set_timer_counter()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
129	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_set_timer_counter()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
116	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type unsigned on 16 bits) is assigned to an object with a narrower essential type (unsigned on 8 bits)	rx8025t_set_timer_counter()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
103	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential	rx8025t_set_timer_counter()	Low	Not a	Embedded drivers need this method to set or

		type category signed.			defect	clear some bits and drivers guarantee the safety of the operation.
588	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	rx8025t_get_ram()	Low	Justified	(handle == NULL)checked.
589	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	rx8025t_set_time()	Low	Justified	(handle == NULL)checked.
177	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_time()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
112	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_time()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
109	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_get_time()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
188	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the + operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_get_time()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
110	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_time()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
115	10.1	Operands shall not be of an inappropriate essential type.	rx8025t_get_time()	Low	Not a	Embedded drivers need

		The right operand of the & operator is of an inappropriate essential type category signed.			defect	this method to set or clear some bits and drivers guarantee the safety of the operation.
121	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_time()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
69	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_time()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
147	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_time()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
17	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_time()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
141	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_minute_alarm()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
6	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_hour_alarm()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
106	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_date_alarm()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

						safety of the operation.
3	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_week_alarm()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
37	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_week_alarm()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
133	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_week_alarm()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
118	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_minute_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
120	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_minute_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
135	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_minute_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
107	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_minute_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
181	10.1	Operands shall not be of an inappropriate essential type.	rx8025t_set_minute_alarm_mask()	Low	Not a	Embedded drivers need

		The left operand of the << operator is of an inappropriate essential type category signed.			defect	this method to set or clear some bits and drivers guarantee the safety of the operation.
128	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_minute_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
132	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category enum.	rx8025t_set_minute_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
157	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_minute_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
117	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_minute_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
156	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_minute_alarm_mask()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
138	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_minute_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.

12	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_hour_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
18	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_hour_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
187	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_hour_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
32	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type category signed.	rx8025t_set_hour_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
61	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_hour_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
143	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_hour_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
159	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_hour_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
170	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential	rx8025t_set_hour_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or

		type category enum.				clear some bits and drivers guarantee the safety of the operation.
144	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_hour_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
151	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_hour_alarm_mask()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
186	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_get_hour_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
136	10.1	Operands shall not be of an inappropriate essential type. The right operand of the &= operator is of an inappropriate essential type category signed.	rx8025t_set_week_day_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
149	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the &= operator has essentially unsigned type while the right operand has essentially signed type.	rx8025t_set_week_day_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
152	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_week_day_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
178	10.1	Operands shall not be of an inappropriate essential type. The operand of the ~ operator is of an inappropriate essential type	rx8025t_set_week_day_alarm_mask()	Low	Not a	Embedded drivers need this method to set or

		category signed.			defect	clear some bits and drivers guarantee the safety of the operation.
145	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_set_week_day_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
154	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the |= operator has essentially unsigned type while the right operand has essentially enum type.	rx8025t_set_week_day_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
155	10.1	Operands shall not be of an inappropriate essential type. The right operand of the |= operator is of an inappropriate essential type category enum.	rx8025t_set_week_day_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
162	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	rx8025t_set_week_day_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
153	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category enum.	rx8025t_set_week_day_alarm_mask()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
165	10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type. The value of the composite expression of essential type category unsigned shall not be cast to the different essential type category enum.	rx8025t_get_week_day_alarm_mask()	Low	Not a defect	We use enumeration to define driver configuration, which is a friendly programming method and should be accepted and drivers guarantee the safety of the operation.
184	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential	rx8025t_get_week_day_alarm_mask()	Low	Not a	Embedded drivers need this method to set or

		type category signed.			defect	clear some bits and drivers guarantee the safety of the operation.
29	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_irq_handler()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
175	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_irq_handler()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
56	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_irq_handler()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
97	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_irq_handler()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
167	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_irq_handler()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
172	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_irq_handler()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
182	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_irq_handler()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the

						safety of the operation.
174	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_irq_handler()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
125	10.1	Operands shall not be of an inappropriate essential type. The right operand of the & operator is of an inappropriate essential type category signed.	rx8025t_irq_handler()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
189	10.1	Operands shall not be of an inappropriate essential type. The left operand of the << operator is of an inappropriate essential type category signed.	rx8025t_irq_handler()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
586	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	rx8025t_set_reg()	Low	Justified	(handle == NULL)checked.
587	D4.14	The validity of values received from external sources shall be checked. Dereferenced pointer is from an unsecure source. Pointer may be NULL or may point to unknown memory.	rx8025t_get_reg()	Low	Justified	(handle == NULL)checked.

Table 2.6. E:\Github\rx8025t\test\driver_rx8025t_alarm_test.c

ID	Guideline	Message	Function	Severity	Status	Comment
229	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	a_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
469	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
235	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an	a_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee

		object with a different essential type category (unsigned)				the safety of the operation.
308	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
230	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	a_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
536	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
231	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	a_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
532	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
236	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	a_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
455	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
360	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
407	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
315	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
479	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
279	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
502	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
497	2.2	There shall be no dead code.	File Scope	Low	Justified	print function.

		The call to function rx8025t_interface_debug_print has no effect.				
539	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
514	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
472	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
442	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
450	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
452	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
434	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
445	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
238	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_alarm_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
233	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_alarm_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
234	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_alarm_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
237	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_alarm_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
239	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category.	rx8025t_alarm_test()	Low	Not a defect	Embedded drivers need this method to set or clear some

		The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)				bits and drivers guarantee the safety of the operation.
448	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
272	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
474	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
500	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
318	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
386	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
358	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
481	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
444	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
314	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
544	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
423	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
531	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
476	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
232	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an	rx8025t_alarm_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee

		object with a different essential type category (unsigned)				the safety of the operation.
576	14.3	Controlling expressions shall not be invariant. If condition is always false.	rx8025t_alarm_test()	Low	Justified	Can't be.
577	2.1	A project shall not contain unreachable code. If-condition always evaluates to false. Dead branch from line 326 to line 328.	rx8025t_alarm_test()	Unset	Unreviewed	
520	2.2	There shall be no dead code. The call to function rx8025t_interface_delay_ms has no effect.	File Scope	Low	Justified	delay function.
578	14.3	Controlling expressions shall not be invariant. If condition is always false.	rx8025t_alarm_test()	Low	Justified	Can't be.
579	2.1	A project shall not contain unreachable code. If-condition always evaluates to false. Dead branch from line 339 to line 341.	rx8025t_alarm_test()	Unset	Unreviewed	
441	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
330	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
439	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

Table 2.7. E:\Github\rx8025t\test\driver_rx8025t_register_test.c

ID	Guideline	Message	Function	Severity	Status	Comment
271	5.8	Identifiers that define objects or functions with external linkage shall be unique. variable select conflicts with the function name select (select.h line 108).	File Scope	Low	Justified	Can't be.
559	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
537	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
319	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
430	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

384	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
270	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
421	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
490	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
513	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
464	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
419	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
293	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
518	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
440	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
322	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
510	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
432	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
420	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
334	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
428	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
208	10.3	The value of an expression shall not be assigned to an object with a	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this

		narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)				method to set or clear some bits and drivers guarantee the safety of the operation.
202	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
205	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
206	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
203	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
209	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
213	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
413	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
396	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
305	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
438	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

451	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
338	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
542	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
294	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
557	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
435	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
489	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
424	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
501	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
433	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
400	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
377	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
404	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
355	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
523	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
462	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
550	2.2	There shall be no dead code.	File Scope	Low	Justified	print function.

		The call to function rx8025t_interface_debug_print has no effect.				
545	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
370	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
488	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
306	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
269	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
543	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
326	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
412	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
331	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
389	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
378	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
395	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
411	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
388	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
263	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
561	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

503	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
486	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
429	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
324	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
535	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
470	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
548	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
376	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
356	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
313	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
369	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
361	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
303	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
468	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
379	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
375	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
528	2.2	There shall be no dead code.	File Scope	Low	Justified	print function.

		The call to function rx8025t_interface_debug_print has no effect.				
282	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
453	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
385	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
382	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
346	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
551	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
345	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
372	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
485	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
304	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
366	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
301	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
463	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
549	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
352	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
475	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

521	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
273	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
354	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
495	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
288	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
568	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
343	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
408	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
416	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
332	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
498	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
380	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
516	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
300	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
289	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
351	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
341	2.2	There shall be no dead code.	File Scope	Low	Justified	print function.

		The call to function rx8025t_interface_debug_print has no effect.				
394	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
397	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
415	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
321	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
340	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
426	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
563	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
337	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
285	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
491	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
556	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
409	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
383	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
505	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
333	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
436	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

506	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
553	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
418	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
541	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
364	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
344	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
277	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
268	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
526	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
422	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
425	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
517	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
211	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
210	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the % operator has essentially signed type while the right operand has essentially unsigned type.	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
398	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

335	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
291	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
449	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
431	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
215	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
207	10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category. The left operand of the % operator has essentially signed type while the right operand has essentially unsigned type.	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
292	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
538	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
310	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
484	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
323	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
204	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
348	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
466	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

284	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
328	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
393	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
212	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
311	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
297	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
390	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
336	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
482	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
214	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
402	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
401	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
524	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
327	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
410	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

216	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category signed) is assigned to an object with a different essential type category (unsigned)	rx8025t_register_test()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
473	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
417	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
566	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
295	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
317	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
278	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
296	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
427	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
287	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
264	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
373	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
316	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
399	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
547	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
529	2.2	There shall be no dead code.	File Scope	Low	Justified	print function.

		The call to function rx8025t_interface_debug_print has no effect.				
363	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
512	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
459	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
302	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
507	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
339	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
405	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
320	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
460	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
325	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
281	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
262	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
565	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
359	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
347	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
480	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

309	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
312	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
299	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
266	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
283	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
298	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
368	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

Table 2.8. E:\Github\rx8025t\test\driver_rx8025t_timer_test.c

ID	Guideline	Message	Function	Severity	Status	Comment
242	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	a_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
329	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
240	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	a_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
519	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
243	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	a_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
392	2.2	There shall be no dead code.	File Scope	Low	Justified	print function.

		The call to function rx8025t_interface_debug_print has no effect.				
241	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	a_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
511	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
244	10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category. The expression (of essential type category enum) is assigned to an object with a different essential type category (unsigned)	a_callback()	Low	Not a defect	Embedded drivers need this method to set or clear some bits and drivers guarantee the safety of the operation.
391	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
493	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
483	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
471	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
353	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
367	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
487	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
365	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
461	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
371	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
530	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

458	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
504	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
499	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
496	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
465	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
443	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
307	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
374	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
478	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
562	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
508	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
522	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
456	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
447	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
494	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
569	14.3	Controlling expressions shall not be invariant. If condition is always false.	rx8025t_timer_test()	Low	Justified	Can't be.
570	2.1	A project shall not contain unreachable code.	rx8025t_timer_test()	Low	Justified	Can't be.

		If-condition always evaluates to false. Dead branch from line 283 to line 285.				
477	2.2	There shall be no dead code. The call to function rx8025t_interface_delay_ms has no effect.	File Scope	Low	Justified	delay function.
573	14.3	Controlling expressions shall not be invariant. If condition is always false.	rx8025t_timer_test()	Low	Justified	Can't be.
574	2.1	A project shall not contain unreachable code. If-condition always evaluates to false. Dead branch from line 296 to line 298.	rx8025t_timer_test()	Unset	Unreviewed	
457	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
554	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.
467	2.2	There shall be no dead code. The call to function rx8025t_interface_debug_print has no effect.	File Scope	Low	Justified	print function.

Chapter 3. Defects

Defects

No defects were found.

Chapter 4. Appendix 1 - Configuration Settings

Polyspace Settings

Option	Value
-author	LibDriver
-bug-finder	true
-checkers	ALIGNMENT_CHANGE, ASSERT, ATOMIC_VAR_ACCESS_TWICE, ATOMIC_VAR_SEQUENCE_NOT_ATOMIC, BAD_EQUAL_EQUAL_USE, BAD_EQUAL_USE, BAD_FREE, BAD_LOCK, BAD_PTR_SCALING, BAD_UNLOCK, CHARACTER_MISUSE, CHAR_EOF_CONFUSED, CLOSED_RESOURCE_USE, CONSTANT_OBJECT_WRITE, DATA_RACE, DATA_RACE_STD_LIB, DEADLOCK, DECL_MISMATCH, DOUBLE_DEALLOCATION, DOUBLE_LOCK, DOUBLE_RESOURCE_CLOSE, DOUBLE_RESOURCE_OPEN, DOUBLE_UNLOCK, ERRNO_MISUSE, FILE_OBJECT_MISUSE, FLEXIBLE_ARRAY_MEMBER_STRUCT_MISUSE, FLOAT_ABSORPTION, FLOAT_CONV_OVFL, FLOAT_STD_LIB, FLOAT_ZERO_DIV, FREED_PTR, FUNC_CAST, IMPROPER_ARRAY_INIT, INLINE_CONSTRAINT_NOT_RESPECTED, INT_CONV_OVFL, INT_STD_LIB, INT_ZERO_DIV, INVALID_ENV_POINTER, INVALID_MEMORY_ASSUMPTION, INVALID_VA_LIST_ARG, IO_INTERLEAVING, LOCAL_ADDR_ESCAPE, MACRO_USED_AS_OBJECT, MEMCMP_PADDING_DATA, MEMCMP_STRINGS, MEM_STD_LIB, MISSING_ERRNO_RESET, MISSING_NULL_CHAR, MISSING_RETURN, NON_INIT_PTR, NON_INIT_VAR, NON_POSITIVE_VLA_SIZE, NULL_PTR, OPERATOR_PRECEDENCE, OTHER_STD_LIB, OUT_BOUND_ARRAY, OUT_BOUND_PTR, PARTIALLY_ACCESSED_ARRAY, PRE_DIRECTIVE_MACRO_ARG, PRE_UCNAME_JOIN_TOKENS, PTR_CAST, PTR_SIZEOF_MISMATCH, PTR_TO_DIFF_ARRAY, PUTENV_AUTO_VAR, READ_ONLY_RESOURCE_WRITE, RESOURCE_LEAK, SIDE_EFFECT_IGNORED, SIGN_CHANGE, SIG_HANDLER_CALLING_SIGNAL, SIG_HANDLER_COMP_EXCP_RETURN, SIG_HANDLER_ERRNO_MISUSE, SIG_HANDLER_SHARED_OBJECT, SIZEOF_MISUSE, STD_FUNC_ARG_MISMATCH, STREAM_WITH_SIDE_EFFECT, STRING_FORMAT, STRLIB_BUFFER_OVERFLOW, STRLIB_BUFFER_UNDERFLOW, STR_FORMAT_BUFFER_OVERFLOW, STR_STD_LIB, TEMP_OBJECT_ACCESS, TOO_MANY_VA_ARG_CALLS, TYPEDEF_MISMATCH, UINT_CONV_OVFL, UNPROTOTYPED_FUNC_CALL, UNREACHABLE, USELESS_IF, USELESS_WRITE, VAR_SHADOWING, VA_ARG_INCORRECT_TYPE, VA_START_INCORRECT_TYPE, VA_START_MISUSE
-compiler	iar
-D	__TID__=14,__SIZE_T_TYPE__=unsigned int,__PTRDIFF_T_TYPE__=signed int,__IAR_SYSTEMS_ICC=1
-date	28/04/2026
-dos	true
-I	E:\Github\rx8025t\src,E:\Github\rx8025t\interface,E:\Github\rx8025t\example,E:\Github\rx8025t\test
-import-comments	E:\Polyspace\rx8025t\Module\BF_Result\comments_bak
-lang	C

-little-endian	true
-logical-signed-right-shift	true
-misra3	mandatory-required
-prog	rx8025t
-results-dir	E:\Polyspace\rx8025t\Module\BF_Result
-sfr-types	sfr8=8,sfr16=16,sfr32=32,sfr=8
-target	mcpu
-verif-version	1.0

Coding Standard Configuration

Table 4.1. MISRA C:2012 Guidelines Configuration

Guideline	Description	Mode	Comment	Enabled
D1.1	Any implementation-defined behaviour on which the output of the program depends shall be documented and understood.	required	-	yes
D2.1	All source files shall compile without any compilation errors.	required	-	yes
D3.1	All code shall be traceable to documented requirements.	required	Not enforceable	no
D4.1	Run-time failures shall be minimized.	required	-	yes
D4.2	All usage of assembly language should be documented.	advisory	Not enforceable	no
D4.3	Assembly language shall be encapsulated and isolated.	required	-	yes
D4.4	Sections of code should not be "commented out".	advisory	Not implemented	no
D4.5	Identifiers in the same name space with overlapping visibility should be typographically unambiguous.	advisory	-	no
D4.6	typedefs that indicate size and signedness should be used in place of the basic numerical types.	advisory	-	no
D4.7	If a function returns error information, then that error information shall be tested.	required	-	yes
D4.8	If a pointer to a structure or union is never dereferenced within a translation unit, then the implementation of the object should be hidden.	advisory	-	no
D4.9	A function should be used in preference to a function-like macro where they are interchangeable.	advisory	-	no
D4.10	Precautions shall be taken in order to prevent the contents of a header file being included more than once.	required	-	yes

D4.11	The validity of values passed to library functions shall be checked.	required	-	yes
D4.12	Dynamic memory allocation shall not be used.	required	-	yes
D4.13	Functions which are designed to provide operations on a resource should be called in an appropriate sequence.	advisory	-	no
D4.14	The validity of values received from external sources shall be checked.	required	-	yes
1.1	The program shall contain no violations of the standard C syntax and constraints, and shall not exceed the implementation's translation limits.	required	-	yes
1.2	Language extensions should not be used.	advisory	-	no
1.3	There shall be no occurrence of undefined or critical unspecified behaviour.	required	-	yes
2.1	A project shall not contain unreachable code.	required	-	yes
2.2	There shall be no dead code.	required	-	yes
2.3	A project should not contain unused type declarations.	advisory	-	no
2.4	A project should not contain unused tag declarations.	advisory	-	no
2.5	A project should not contain unused macro declarations.	advisory	-	no
2.6	A function should not contain unused label declarations.	advisory	-	no
2.7	There should be no unused parameters in functions.	advisory	-	no
3.1	The character sequences /* and // shall not be used within a comment.	required	-	yes
3.2	Line-splicing shall not be used in // comments.	required	-	yes
4.1	Octal and hexadecimal escape sequences shall be terminated.	required	-	yes
4.2	Trigraphs should not be used.	advisory	-	no
5.1	External identifiers shall be distinct.	required	-	yes
5.2	Identifiers declared in the same scope and name space shall be distinct.	required	-	yes
5.3	An identifier declared in an inner scope shall not hide an identifier declared in an outer scope.	required	-	yes
5.4	Macro identifiers shall be distinct.	required	-	yes
5.5	Identifiers shall be distinct from macro names.	required	-	yes
5.6	A typedef name shall be a unique identifier.	required	-	yes
5.7	A tag name shall be a unique identifier.	required	-	yes
5.8	Identifiers that define objects or functions with external linkage shall be unique.	required	-	yes

5.9	Identifiers that define objects or functions with internal linkage should be unique.	advisory	-	no
6.1	Bit-fields shall only be declared with an appropriate type.	required	-	yes
6.2	Single-bit named bit fields shall not be of a signed type.	required	-	yes
7.1	Octal constants shall not be used.	required	-	yes
7.2	A "u" or "U" suffix shall be applied to all integer constants that are represented in an unsigned type.	required	-	yes
7.3	The lowercase character "l" shall not be used in a literal suffix.	required	-	yes
7.4	A string literal shall not be assigned to an object unless the object's type is "pointer to const-qualified char".	required	-	yes
8.1	Types shall be explicitly specified.	required	-	yes
8.2	Function types shall be in prototype form with named parameters.	required	-	yes
8.3	All declarations of an object or function shall use the same names and type qualifiers.	required	-	yes
8.4	A compatible declaration shall be visible when an object or function with external linkage is defined.	required	-	yes
8.5	An external object or function shall be declared once in one and only one file.	required	-	yes
8.6	An identifier with external linkage shall have exactly one external definition.	required	-	yes
8.7	Functions and objects should not be defined with external linkage if they are referenced in only one translation unit.	advisory	-	no
8.8	The static storage class specifier shall be used in all declarations of objects and functions that have internal linkage.	required	-	yes
8.9	An object should be defined at block scope if its identifier only appears in a single function.	advisory	-	no
8.10	An inline function shall be declared with the static storage class.	required	-	yes
8.11	When an array with external linkage is declared, its size should be explicitly specified.	advisory	-	no
8.12	Within an enumerator list, the value of an implicitly-specified enumeration constant shall be unique.	required	-	yes
8.13	A pointer should point to a const-qualified type whenever possible.	advisory	-	no
8.14	The restrict type qualifier shall not be used.	required	-	yes
9.1	The value of an object with automatic storage duration shall not be read before it has been set.	mandatory	-	yes
9.2	The initializer for an aggregate or union shall be enclosed in braces.	required	-	yes
9.3	Arrays shall not be partially initialized.	required	-	yes
9.4	An element of an object shall not be initialized more than once.	required	-	yes

9.5	Where designated initializers are used to initialize an array object the size of the array shall be specified explicitly.	required	-	yes
10.1	Operands shall not be of an inappropriate essential type.	required	-	yes
10.2	Expressions of essentially character type shall not be used inappropriately in addition and subtraction operations.	required	-	yes
10.3	The value of an expression shall not be assigned to an object with a narrower essential type or of a different essential type category.	required	-	yes
10.4	Both operands of an operator in which the usual arithmetic conversions are performed shall have the same essential type category.	required	-	yes
10.5	The value of an expression should not be cast to an inappropriate essential type.	advisory	-	no
10.6	The value of a composite expression shall not be assigned to an object with wider essential type.	required	-	yes
10.7	If a composite expression is used as one operand of an operator in which the usual arithmetic conversions are performed then the other operand shall not have wider essential type.	required	-	yes
10.8	The value of a composite expression shall not be cast to a different essential type category or a wider essential type.	required	-	yes
11.1	Conversions shall not be performed between a pointer to a function and any other type.	required	-	yes
11.2	Conversions shall not be performed between a pointer to an incomplete type and any other type.	required	-	yes
11.3	A cast shall not be performed between a pointer to object type and a pointer to a different object type.	required	-	yes
11.4	A conversion should not be performed between a pointer to object and an integer type.	advisory	-	no
11.5	A conversion should not be performed from pointer to void into pointer to object.	advisory	-	no
11.6	A cast shall not be performed between pointer to void and an arithmetic type.	required	-	yes
11.7	A cast shall not be performed between pointer to object and a non-integer arithmetic type.	required	-	yes
11.8	A cast shall not remove any const or volatile qualification from the type pointed to by a pointer.	required	-	yes
11.9	The macro NULL shall be the only permitted form of integer null pointer constant.	required	-	yes
12.1	The precedence of operators within expressions should be made explicit.	advisory	-	no
12.2	The right hand operand of a shift operator shall lie in the range zero to one less than the width in bits of the essential type of the left hand operand.	required	-	yes
12.3	The comma operator should not be used	advisory	-	no
12.4	Evaluation of constant expressions should not lead to unsigned integer wrap-around.	advisory	-	no
12.5	The sizeof operator shall not have an operand which is a function parameter declared as "array of	mandatory	-	yes

	type".			
13.1	Initializer lists shall not contain persistent side effects.	required	-	yes
13.2	The value of an expression and its persistent side effects shall be the same under all permitted evaluation orders.	required	-	yes
13.3	A full expression containing an increment (++) or decrement (--) operator should have no other potential side effects other than that caused by the increment or decrement operator.	advisory	-	no
13.4	The result of an assignment operator should not be used.	advisory	-	no
13.5	The right hand operand of a logical && or || operator shall not contain persistent side effects.	required	-	yes
13.6	The operand of the sizeof operator shall not contain any expression which has potential side effects.	mandatory	-	yes
14.1	A loop counter shall not have essentially floating type.	required	-	yes
14.2	A for loop shall be well-formed.	required	-	yes
14.3	Controlling expressions shall not be invariant.	required	-	yes
14.4	The controlling expression of an if statement and the controlling expression of an iteration-statement shall have essentially Boolean type.	required	-	yes
15.1	The goto statement should not be used.	advisory	-	no
15.2	The goto statement shall jump to a label declared later in the same function.	required	-	yes
15.3	Any label referenced by a goto statement shall be declared in the same block, or in any block enclosing the goto statement.	required	-	yes
15.4	There should be no more than one break or goto statement used to terminate any iteration statement.	advisory	-	no
15.5	A function should have a single point of exit at the end.	advisory	-	no
15.6	The body of an iteration-statement or a selection-statement shall be a compound-statement.	required	-	yes
15.7	All if ... else if constructs shall be terminated with an else statement.	required	-	yes
16.1	All switch statements shall be well-formed.	required	-	yes
16.2	A switch label shall only be used when the most closely-enclosing compound statement is the body of a switch statement.	required	-	yes
16.3	An unconditional break statement shall terminate every switch-clause.	required	-	yes
16.4	Every switch statement shall have a default label.	required	-	yes
16.5	A default label shall appear as either the first or the last switch label of a switch statement.	required	-	yes
16.6	Every switch statement shall have at least two switch-clauses.	required	-	yes

16.7	A switch-expression shall not have essentially Boolean type.	required	-	yes
17.1	The features of <stdarg.h> shall not be used.	required	-	yes
17.2	Functions shall not call themselves, either directly or indirectly.	required	-	yes
17.3	A function shall not be declared implicitly.	mandatory	-	yes
17.4	All exit paths from a function with non-void return type shall have an explicit return statement with an expression.	mandatory	-	yes
17.5	The function argument corresponding to a parameter declared to have an array type shall have an appropriate number of elements.	advisory	-	no
17.6	The declaration of an array parameter shall not contain the static keyword between the [ ].	mandatory	-	yes
17.7	The value returned by a function having non-void return type shall be used.	required	-	yes
17.8	A function parameter should not be modified.	advisory	-	no
18.1	A pointer resulting from arithmetic on a pointer operand shall address an element of the same array as that pointer operand.	required	-	yes
18.2	Subtraction between pointers shall only be applied to pointers that address elements of the same array.	required	-	yes
18.3	The relational operators >, >=, < and <= shall not be applied to objects of pointer type except where they point into the same object.	required	-	yes
18.4	The +, -, += and -= operators should not be applied to an expression of pointer type.	advisory	-	no
18.5	Declarations should contain no more than two levels of pointer nesting.	advisory	-	no
18.6	The address of an object with automatic storage shall not be copied to another object that persists after the first object has ceased to exist.	required	-	yes
18.7	Flexible array members shall not be declared.	required	-	yes
18.8	Variable-length array types shall not be used.	required	-	yes
19.1	An object shall not be assigned or copied to an overlapping object.	mandatory	-	yes
19.2	The union keyword should not be used.	advisory	-	no
20.1	#include directives should only be preceded by preprocessor directives or comments.	advisory	-	no
20.2	The ', " or \ characters and the /* or // character sequences shall not occur in a header file name.	required	-	yes
20.3	The #include directive shall be followed by either a <filename> or "filename"sequence.	required	-	yes
20.4	A macro shall not be defined with the same name as a keyword.	required	-	yes

20.5	#undef should not be used.	advisory	-	no
20.6	Tokens that look like a preprocessing directive shall not occur within a macro argument.	required	-	yes
20.7	Expressions resulting from the expansion of macro parameters shall be enclosed in parentheses.	required	-	yes
20.8	The controlling expression of a #if or #elif preprocessing directive shall evaluate to 0 or 1.	required	-	yes
20.9	All identifiers used in the controlling expression of #if or #elif preprocessing directives shall be #define'd before evaluation.	required	-	yes
20.10	The # and ## preprocessor operators should not be used.	advisory	-	no
20.11	A macro parameter immediately following a # operator shall not immediately be followed by a ## operator.	required	-	yes
20.12	A macro parameter used as an operand to the # or ## operators, which is itself subject to further macro replacement, shall only be used as an operand to these operators.	required	-	yes
20.13	A line whose first token is # shall be a valid preprocessing directive.	required	-	yes
20.14	All #else, #elif and #endif preprocessor directives shall reside in the same file as the #if, #ifdef or #ifndef directive to which they are related.	required	-	yes
21.1	#define and #undef shall not be used on a reserved identifier or reserved macro name.	required	-	yes
21.2	A reserved identifier or macro name shall not be declared.	required	-	yes
21.3	The memory allocation and deallocation functions of <stdlib.h> shall not be used.	required	-	yes
21.4	The standard header file <setjmp.h> shall not be used.	required	-	yes
21.5	The standard header file <signal.h> shall not be used.	required	-	yes
21.6	The Standard Library input/output functions shall not be used.	required	-	yes
21.7	The atof, atoi, atol, and atoll functions of <stdlib.h> shall not be used.	required	-	yes
21.8	The library functions abort, exit and system of <stdlib.h> shall not be used.	required	-	yes
21.9	The library functions bsearch and qsort of <stdlib.h> shall not be used.	required	-	yes
21.10	The Standard Library time and date functions shall not be used.	required	-	yes
21.11	The standard header file <tgmath.h> shall not be used.	required	-	yes
21.12	The exception handling features of <fenv.h> should not be used.	advisory	-	no
21.13	Any value passed to a function in <ctype.h> shall be representable as an unsigned char or be the value EOF.	mandatory	-	yes
21.14	The Standard Library function memcmp shall not be used to compare null terminated strings.	required	-	yes

21.15	The pointer arguments to the Standard Library functions memcpy, memmove and memcmp shall be pointers to qualified or unqualified versions of compatible types.	required	-	yes
21.16	The pointer arguments to the Standard Library function memcmp shall point to either a pointer type, an essentially signed type, an essentially unsigned type, an essentially Boolean type or an essentially enum type.	required	-	yes
21.17	Use of the string handling functions from <string.h> shall not result in accesses beyond the bounds of the objects referenced by their pointer parameters.	mandatory	-	yes
21.18	The size_t argument passed to any function in <string.h> shall have an appropriate value.	mandatory	-	yes
21.19	The pointers returned by the Standard Library functions localeconv, getenv, setlocale or, strerror shall only be used as if they have pointer to const-qualified type.	mandatory	-	yes
21.20	The pointer returned by the Standard Library functions asctime, ctime, gmtime, localtime, localeconv, getenv, setlocale or strerror shall not be used following a subsequent call to the same function.	mandatory	-	yes
22.1	All resources obtained dynamically by means of Standard Library functions shall be explicitly released.	required	-	yes
22.2	A block of memory shall only be freed if it was allocated by means of a Standard Library function.	mandatory	-	yes
22.3	The same file shall not be open for read and write access at the same time on different streams.	required	-	yes
22.4	There shall be no attempt to write to a stream which has been opened as read-only.	mandatory	-	yes
22.5	A pointer to a FILE object shall not be dereferenced.	mandatory	-	yes
22.6	The value of a pointer to a FILE shall not be used after the associated stream has been closed.	mandatory	-	yes
22.7	The macro EOF shall only be compared with the unmodified return value from any Standard Library function capable of returning EOF.	required	-	yes
22.8	The value of errno shall be set to zero prior to a call to an errno-setting-function.	required	-	yes
22.9	The value of errno shall be tested against zero after calling an errno-setting-function.	required	-	yes
22.10	The value of errno shall only be tested when the last function to be called was an errno-setting-function.	required	-	yes

Chapter 5. Appendix 2 - Definitions

Table 5.1. Abbreviations

Abbreviation	Definition
NA	Not Available