

Incremental Approximate Maxflow on Undirected Graphs in $m^{o(1)}$ Update Time

Li Chen (CMU)

SODA 2024

Joint work with




Jan van den
Brand
Georgia Tech



Rasmus Kyng
ETH



Yang P. Liu
IAS




Richard Peng
CMU



Maximilian
Probst Gutenberg
ETH




Sushant
Sachdeva
U. Toronto



Aaron Sidford
Stanford

Maxflow


Undirected graph $G = (V, E)$. m edges, n vertices, source s , sink t
edge *capacities* $u_e \geq 0$, integer in $[0, U]$, where $U = m^{O(1)}$



Maxflow

Undirected graph $G = (V, E)$. m edges, n vertices, source s , sink t
edge *capacities* $u_e \geq 0$, integer in $[0, U]$, where $U = m^{O(1)}$

Goal: Route maximum
flow from $s \rightarrow t$,
Subject to capacities u_e




Capacity constraint:
 $-u_e \leq f_e \leq u_e$

Maxflow

Undirected graph $G = (V, E)$. m edges, n vertices, source s , sink t
edge *capacities* $u_e \geq 0$, integer in $[0, U]$, where $U = m^{O(1)}$

Goal: Route maximum
flow from $s \rightarrow t$,
Subject to capacities u_e




Capacity constraint:
 $-u_e \leq f_e \leq u_e$

Min Congestion Flow

$$\text{Congestion of } f = \max_e \frac{|f_e|}{u_e} = \|u^{-1}f\|_\infty$$

Goal: Route 1 unit of flow from $s \rightarrow t$, minimize congestion




Min congestion
= $1 / \text{Maxflow}$

Min Congestion Flow

$$\min_{\substack{\text{unit } s-t \\ \text{flow } f}} \|u^{-1}f\|_{\infty}$$

Congestion



Min congestion
= 1 / Maxflow

P-Norm Flow

	$\min_{\substack{\text{unit } s-t \\ \text{flow } f}} \ Wf\ _p$	P-norm Energy
$p = \infty$	$\ u^{-1}f\ _\infty$	Min Cong Flow
$p = 2$	$\ Rf\ _2$	Electrical Flow
$p = 1$	$\ Wf\ _1$	Shortest Path
$p = O(\varepsilon^{-1} \log m)$	$\ u^{-1}f\ _p$	$(1 + \varepsilon)$ -Approx Min Cong Flow

$$\|x\|_\infty \leq \|x\|_p \leq m^{1/p} \|x\|_\infty$$

Result: Incremental Approx Maxflow

Corollary [Brand-C-Kyng-Liu-Peng-Probst Gutenberg-Sachdeva-Sidford]

After each edge insertion,

Maintain a $(1 + \varepsilon)$ -approx. min congestion flow f ,

in amortized $m^{o(1)} \varepsilon^{-3}$ update time

Randomized w.h.p. against oblivious adversary

Oblivious adversary: sequence of updates fixed beforehand

Subproblem: Incremental Thresholded L_p Flow

Theorem [Brand-C-Kyng-Liu-Peng-Probst Gutenberg-Sachdeva-Sidford]

For $p \geq 2$, $\delta > 0$, given a threshold F

After each edge insertion, either

- Certify $\min_{B^T f = d} \|Wf\|_p^p > F$, or
- Output a flow f s.t. $\|Wf\|_p^p \leq F + \delta$

in $\approx p^2 m^{1+o(1)} \log \frac{1}{\delta}$ total time w.h.p. against oblivious adversary

Related works


- Insertion/Deletion-only exact maxflow: (directed + unit-capacity) $\Omega(n)$ assuming the OMv conjecture [Dah16, HKNS15]
- Incremental + unit capacity + directed: $\sqrt{m}\varepsilon^{-1/2}$ per update [GH23]
 - Incremental augmenting path + lazy recompute
- Incremental + general min cost flow: $\sqrt{n}\varepsilon^{-1}$ per update [BLS23]
 - Continuous potential stable under insertions
 - Dynamic Min Ratio Cycle

Dynamic Algo via Optimization: ours & [\[BLS23\]](#)

- Maintain solution to a convex minimization problem that's
 - Relaxation of maxflow
 - Robust to insertions
- After each update, decrease the objective by updating current solution (implicitly)
- Data structure calls: $m^{1+o(1)}$ iterations of min ratio cycles

Min Ratio Cycle

$$\min_{B^T \Delta = 0} \frac{g^T \Delta}{\|L\Delta\|_1}$$




$$\|L\Delta\|_1 = 1 + 2 + 1 + 2 = 6$$

$$g^T \Delta = -4 + 1 + 3 + 1 = 1$$

Min Ratio Cycle

$$\min_{B^T \Delta = 0} \frac{g^T \Delta}{\|L\Delta\|_1}$$



Edges and lengths are undirected
Gradient has a direction

$$\|L\Delta\|_1 = 1 + 2 + 1 + 2 = 6$$

$$g^T \Delta = 4 - 1 - 3 - 1 = -1$$

Optimal solution is a simple cycle with ratio < 0

Dynamic Min Ratio Cycle w/ Restrictions

[CKLPPS22]

Assuming the min-ratio cycles **change slowly**,

A randomized data-structure that supports in $m^{o(1)}$ amortized time

1. Update g_e, L_e for an edge e
2. Return a $m^{o(1)}$ -approximate min-ratio cycle

Differences: Ours vs [BLS23]

- [BLS23]: gradients/lengths changes arbitrarily
 - \sqrt{n} update time for making [CKLPPS22] DS adaptive
- Ours: $m^{o(1)}$ phases, within each phase
 - Edge Lengths only go up
 - One circulation good for the entire phase
 - [CKLPPS22] DS works for free

P norm flow: small error from large error

- At current f , find Δ to minimize $\mathcal{E}(f + \Delta) = \|f + \Delta\|_p^p$
- [AKPS19]: "Only the 2nd and the p-th order terms matter"

Incremental for free:

After an edge insertion, f stays feasible
and $\mathcal{E}(f)$ stays the same

$$\mathcal{E}(f + \Delta) - \mathcal{E}(f) - \nabla \mathcal{E}(f)^T \Delta \approx \sum_e (r_e \Delta_e)^2 + |\Delta_e|^p = \|R\Delta\|_2^2 + \|\Delta\|_p^p$$

- Solve the *residual problem*: if $\min_f \mathcal{E}(f) \leq F$

$$\min_{\text{circulation } \Delta} \mathcal{R}(\Delta) = \nabla \mathcal{E}(f)^T \Delta + \|R\Delta\|_2^2 + \|\Delta\|_p^p \leq \frac{F - \mathcal{E}(f)}{100p} < 0$$

- $m^{o(1)}$ -approx. leads to $\approx pm^{o(1)} \log \frac{1}{\delta}$ iterations to find $\mathcal{E}(f) \leq F + \delta$

Approx. Residual Problem

- Solving the residual problem to $m^{o(1)}$ -approx. equivalent to
find circulation Δ s.t. $g^T \Delta = 1$, $\|R\Delta\|_2, \|\Delta\|_p \leq m^{o(1)}$
given: $\exists \Delta^*$ s.t. $\|R\Delta^*\|_2, \|\Delta^*\|_p \leq 1$
- Via MWU, reduce to $m^{1+o(1)}$ iterations of
find circulation Δ s.t. $g^T \Delta = 1$, $\|L\Delta\|_1 \leq m^{o(1)} \|\ell\|_1$
where $\|L\Delta^*\|_1 \leq \|\ell\|_1$
- The edge lengths are slowly increasing due to MWU

Can use Dynamic
Min Ratio Cycle
from [\[CKLPPS22\]](#)

Incremental Approx. Residual Problem

- $m^{1+o(1)}$ iterations of Min Ratio Cycle

find circulation Δ s.t. $g^T \Delta = 1$, $\|L\Delta\|_1 \leq m^{o(1)} \|\ell\|_1$

where $\|L\Delta^*\|_1 \leq \|\ell\|_1$

- If fail, e.g. $\|L\Delta\|_1 > m^{o(1)} \|\ell\|_1$, Δ^* does not exist

- $\min_{\text{circulation } \Delta} \mathcal{R}(\Delta)$ is large and $\min_{B^T f = d} \|f\|_p^p > F$

Recap

- Incremental approx. maxflow via incremental p-norm flow
- Iterative Refinement: $m^{o(1)} \log \frac{1}{\delta}$ iters of approx. residual problem
- MWU: $m^{o(1)}$ -approx. residual solution $\rightarrow m^{1+o(1)}$ iters of Min Ratio Cycles
- Lengths only increase, can use the restricted dynamic MRC from [\[CKLLPS22\]](#)
- When the output cycle has large ratio, $\min_{B^T f = d} \|f\|_p^p > F$

Future direction

- Adaptive Incremental maxflow?
 - Deterministic Dynamic Min Ratio Cycle in $m^{o(1)}$ update time [[CKLMP](#), [arXiv:2311.18295](#)]
- Decremental approx. maxflow?

- Adaptive Incremental maxflow?
 - I think we can [CKLMP, arXiv:2311.18295]
- Decremental approx. maxflow?

Thanks!!




Jan van den
Brand
Georgia Tech



Rasmus Kyng
ETH



Yang P. Liu
IAS




Richard Peng
CMU



Maximilian
Probst Gutenberg
ETH



Sushant
Sachdeva
U. Toronto



Aaron Sidford
Stanford