

Week-3: Code-along

Nicole Lim

2023-08-25

I. Code to edit and execute

To be submitted on canvas before attending the tutorial

Loading packages

```
# Load package tidyverse
library(tidyverse)
```

```
## — Attaching core tidyverse packages — tidyverse 2.0.0 —
## ✓ dplyr      1.1.2      ✓ readr      2.1.4
## ✓ forcats    1.0.0      ✓ stringr    1.5.0
## ✓ ggplot2     3.4.3      ✓ tibble     3.2.1
## ✓ lubridate  1.9.2      ✓ tidyr      1.3.0
## ✓ purrr       1.0.1
## — Conflicts — tidyverse_conflicts() —
## ✖ dplyr::filter() masks stats::filter()
## ✖ dplyr::lag()     masks stats::lag()
## i Use the http://conflicted.r-lib.org/ conflicted package http://conflicted.r-lib.org/ to force all co
nflicts to become errors
```

Assigning values to variables

```
# Example a.: execute this example
x <- 'A'
x
```

```
## [1] "A"
```

```
# Complete the code for Example b and execute it
x <- "Apple"
x
```

```
## [1] "Apple"
```

```
# Complete the code for Example c and execute it
x <- FALSE
x
```

```
## [1] FALSE
```

```
# Complete the code for Example d and execute it
x <- 5L
x
```

```
## [1] 5
```

```
# Complete the code for Example e and execute it
x <- 5
x
```

```
## [1] 5
```

```
# Complete the code for Example f and execute it
x <- 1i
x
```

```
## [1] 0+1i
```

Checking the type of variables

```
# Example a.: execute this example
x <- 'A'
typeof(x)
```

```
## [1] "character"
```

```
# Complete the code for Example b and execute it
x <- "Apple"
typeof(x)
```

```
## [1] "character"
```

```
# Complete the code for Example c and execute it
x <- FALSE
typeof(x)
```

```
## [1] "logical"
```

```
# Complete the code for Example d and execute it
x <- 5L
typeof(x)
```

```
## [1] "integer"
```

```
# Complete the code for Example e and execute it
x <- 5
typeof(x)
```

```
## [1] "double"
```

```
# Complete the code for Example f and execute it
x <- 1i
typeof(x)
```

```
## [1] "complex"
```

Need for data types

```
# import the cat-lovers data from the csv file you downloaded from canvas
cat_lovers <- read_csv("/Users/nic/Library/CloudStorage/OneDrive-NationalUniversityof
Singapore/NM2207/Week 3/cat-lovers.csv")
```

```
# Compute the mean of the number of cats: execute this command
mean(cat_lovers$number_of_cats)
```

```
## Warning in mean.default(cat_lovers$number_of_cats): argument is not numeric or
## logical: returning NA
```

```
## [1] NA
```

```
# Get more information about the mean() command using ? operator
?mean()
```

```
# Convert the variable number_of_cats using as.integer()
as.integer(cat_lovers$number_of_cats)
```

```
## Warning: NAs introduced by coercion
```

```
## [1] 0 0 1 3 3 2 1 1 0 0 0 0 1 3 3 2 1 1 0 0 1 1 0 0 4
## [26] 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 3 3 2 1 NA 0 0
## [51] 1 0 1 NA 1 1 1 0 0 2
```

```
# Display the elements of the column number_of_cats
cat_lovers$number_of_cats
```

```
## [1] "0"
## [2] "0"
## [3] "1"
## [4] "3"
## [5] "3"
## [6] "2"
## [7] "1"
## [8] "1"
## [9] "0"
## [10] "0"
## [11] "0"
## [12] "0"
## [13] "1"
## [14] "3"
## [15] "3"
## [16] "2"
## [17] "1"
## [18] "1"
## [19] "0"
## [20] "0"
## [21] "1"
## [22] "1"
## [23] "0"
## [24] "0"
## [25] "4"
## [26] "0"
## [27] "0"
## [28] "0"
## [29] "0"
## [30] "0"
## [31] "0"
## [32] "0"
## [33] "0"
## [34] "0"
## [35] "0"
## [36] "0"
## [37] "0"
## [38] "0"
## [39] "0"
## [40] "0"
## [41] "0"
## [42] "0"
## [43] "1"
## [44] "3"
## [45] "3"
## [46] "2"
## [47] "1"
## [48] "1.5 - honestly I think one of my cats is half human"
## [49] "0"
## [50] "0"
## [51] "1"
## [52] "0"
## [53] "1"
## [54] "three"
## [55] "1"
```

```
## [56] "1"
## [57] "1"
## [58] "0"
## [59] "0"
## [60] "2"
```

```
# Display the elements of the column number_of_cats after converting it using as.nu  
meric()  
as.numeric(cat_lovers$number_of_cats)
```

```
## Warning: NAs introduced by coercion
```

```
## [1] 0 0 1 3 3 2 1 1 0 0 0 0 1 3 3 2 1 1 0 0 1 1 0 0 4  
## [26] 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 1 3 3 2 1 NA 0 0  
## [51] 1 0 1 NA 1 1 1 0 0 2
```

Create an empty vector

```
# Empty vector  
x <- vector()  
# Type of the empty vector  
typeof(x)
```

```
## [1] "logical"
```

Create vectors of type logical

```
# Method 1  
x<-vector("logical",length=5)  
# Display the contents of x  
print(x)
```

```
## [1] FALSE FALSE FALSE FALSE FALSE
```

```
# Display the type of x  
print(typeof(x))
```

```
## [1] "logical"
```

```
# Method 2  
x<-logical(5)  
# Display the contents of x  
print(x)
```

```
## [1] FALSE FALSE FALSE FALSE FALSE
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "logical"
```

```
# Method 3
x<-c(TRUE,FALSE,TRUE,FALSE,TRUE)
# Display the contents of x
print(x)
```

```
## [1] TRUE FALSE TRUE FALSE TRUE
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "logical"
```

Create vectors of type character

```
# Method 1
x <- vector("character", length=2)
# Display the contents of x
print(x)
```

```
## [1] "" ""
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "character"
```

```
# Method 2
x <- character(2)
# Display the contents of x
print(x)
```

```
## [1] "" ""
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "character"
```

```
# Method 3
x <-c("t","i","o","t")
# Display the contents of x
print(x)
```

```
## [1] "t" "i" "o" "t"
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "character"
```

Create vectors of type integer

```
# Method 1
x <- vector("integer",length=4)
# Display the contents of x
print(x)
```

```
## [1] 0 0 0 0
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "integer"
```

```
# Method 2
x <- integer(4)
# Display the contents of x
print(x)
```

```
## [1] 0 0 0 0
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "integer"
```

```
# Method 3
x <- c(4L, 1L, 0L, 4L)
# Display the contents of x
print(x)
```

```
## [1] 4 1 0 4
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "integer"
```

```
# Method 4
x <- seq(from=1L, to=4L, by=1L)
# Display the contents of x
print(x)
```

```
## [1] 1 2 3 4
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "integer"
```

```
# Method 5
x<-1:5
# Display the contents of x
print(x)
```

```
## [1] 1 2 3 4 5
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "integer"
```

Create vectors of type double

```
# Method 1
x <- vector("double", length=4)
# Display the contents of x
print(x)
```

```
## [1] 0 0 0 0
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "double"
```



```
# Method 2
x <- double(4)
# Display the contents of x
print(x)
```

```
## [1] 0 0 0 0
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "double"
```

```
# Method 3
x<-c(1.15, 11.03, 11.27)
# Display the contents of x
print(x)
```

```
## [1] 1.15 11.03 11.27
```

```
# Display the type of x
print(typeof(x))
```

```
## [1] "double"
```

Implicit coercion

Example 1

```
# Create a vector
x <- c(1.15)
# Check the type of x
typeof(x)
```

```
## [1] "double"
```

```
# Add a character to the vector
x <- c(x, 'j')
# Check the type of x
typeof(x)
```

```
## [1] "character"
```

Example 2

```
# Create a vector
x <-c(TRUE)
# Check the type of x
typeof(x)
```

```
## [1] "logical"
```

```
# Add a number to the vector
x <- c(x,4)
# Check the type of x
typeof(x)
```

```
## [1] "double"
```

Example 3

```
# Create a vector
x <- c('b')
# Check the type of x
typeof(x)
```

```
## [1] "character"
```

```
# Add a logical value to the vector
x <- c(x,TRUE)
# Check the type of x
typeof(x)
```

```
## [1] "character"
```

Example 4

```
# Create a vector
x <- c(4L)
# Check the type of x
typeof(x)
```

```
## [1] "integer"
```

```
# Add a number to the vector
x<-c(x,18)
# Check the type of x
typeof(x)
```

```
## [1] "double"
```

Explicit coercion

Example 1

```
# Create a vector
x <- c(4L)
# Check the type of x
typeof(x)
```

```
## [1] "integer"
```

```
# Convert the vector to type character
x <- as.character(x)
# Check the type of x
typeof(x)
```

```
## [1] "character"
```

Example 2

```
# Create a vector
x <- c('J')
# Check the type of x
typeof(x)
```

```
## [1] "character"
```

```
# Convert the vector to type double
x <- as.numeric(x)
```

```
## Warning: NAs introduced by coercion
```

```
print(x)
```

```
## [1] NA
```

```
# Check the type of x
typeof(x)
```

```
## [1] "double"
```

Accessing elements of the vector

```
# Create a vector
x <- c(1,10,9,8,1,3,5)
```

```
# Access one element with index 3
x[3]
```

```
## [1] 9
```

```
# Access elements with consecutive indices, 2 to 4: 2,3,4
x[2:4]
```

```
## [1] 10 9 8
```

```
# Access elements with non-consecutive indices, 1,3,5
x[c(1,3,5)]
```

```
## [1] 1 9 1
```

```
# Access elements using logical vector
x[c(TRUE,FALSE,FALSE,TRUE,FALSE,FALSE,TRUE)]
```

```
## [1] 1 8 5
```

```
# Access elements using the conditional operator <
x[x>9]
```

```
## [1] 10
```

Examining vectors

```
# Display the length of the vector
print(length(x))
```

```
## [1] 7
```

```
# Display the type of the vector
print(typeof(x))
```

```
## [1] "double"
```

```
# Display the structure of the vector
print(str(x))
```

```
## num [1:7] 1 10 9 8 1 3 5
## NULL
```

Lists

```
# Initialise a named list
my_pie = list(type="key lime", diameter=7, is.vegetarian=TRUE)
# display the list
my_pie
```

```
## $type
## [1] "key lime"
##
## $diameter
## [1] 7
##
## $is.vegetarian
## [1] TRUE
```

```
# Print the names of the list
names(my_pie)
```

```
## [1] "type"          "diameter"      "is.vegetarian"
```

```
# Retrieve the element named type
my_pie$type
```

```
## [1] "key lime"
```

```
# Retrieve a truncated list
my_pie["type"]
```

```
## $type
## [1] "key lime"
```

```
# Retrieve the element named type
my_pie[["type"]]
```

```
## [1] "key lime"
```

Exploring data-sets

```
# Install package
#install.packages("openintro")
# Load the package
library(openintro)
```

```
## Loading required package: airports
```

```
## Loading required package: cherryblossom
```

```
## Loading required package: usdata
```

```
# Load package  
library(tidyverse)
```

```
# Catch a glimpse of the data-set: see how the rows are stacked one below another  
glimpse(loans_full_schema)
```

```

## Rows: 10,000
## Columns: 55
## $ emp_title                <chr> "global config engineer ", "warehouse...
## $ emp_length               <dbl> 3, 10, 3, 1, 10, NA, 10, 10, 10, 3, 1...
## $ state                    <fct> NJ, HI, WI, PA, CA, KY, MI, AZ, NV, I...
## $ homeownership            <fct> MORTGAGE, RENT, RENT, RENT, RENT, OWN...
## $ annual_income             <dbl> 90000, 40000, 40000, 30000, 35000, 34...
## $ verified_income           <fct> Verified, Not Verified, Source Verifi...
## $ debt_to_income            <dbl> 18.01, 5.04, 21.15, 10.16, 57.96, 6.4...
## $ annual_income_joint       <dbl> NA, NA, NA, NA, 57000, NA, 155000, NA...
## $ verification_income_joint <fct> , , , , Verified, , Not Verified, , ,...
## $ debt_to_income_joint      <dbl> NA, NA, NA, NA, 37.66, NA, 13.12, NA,...
## $ delinq_2y                 <int> 0, 0, 0, 0, 0, 1, 0, 1, 1, 0, 0, 0, 0...
## $ months_since_last_delinq  <int> 38, NA, 28, NA, NA, 3, NA, 19, 18, NA...
## $ earliest_credit_line       <dbl> 2001, 1996, 2006, 2007, 2008, 1990, 2...
## $ inquiries_last_12m        <int> 6, 1, 4, 0, 7, 6, 1, 1, 3, 0, 4, 4, 8...
## $ total_credit_lines         <int> 28, 30, 31, 4, 22, 32, 12, 30, 35, 9,...
## $ open_credit_lines          <int> 10, 14, 10, 4, 16, 12, 10, 15, 21, 6,...
## $ total_credit_limit         <int> 70795, 28800, 24193, 25400, 69839, 42...
## $ total_credit_utilized      <int> 38767, 4321, 16000, 4997, 52722, 3898...
## $ num_collections_last_12m   <int> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0...
## $ num_historical_failed_to_pay <int> 0, 1, 0, 1, 0, 0, 0, 0, 0, 0, 1, 0, 0...
## $ months_since_90d_late      <int> 38, NA, 28, NA, NA, 60, NA, 71, 18, N...
## $ current_accounts_delinq     <int> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0...
## $ total_collection_amount_ever <int> 1250, 0, 432, 0, 0, 0, 0, 0, 0, 0, 0,...
## $ current_installment_accounts <int> 2, 0, 1, 1, 1, 0, 2, 2, 6, 1, 2, 1, 2...
## $ accounts_opened_24m        <int> 5, 11, 13, 1, 6, 2, 1, 4, 10, 5, 6, 7...
## $ months_since_last_credit_inquiry <int> 5, 8, 7, 15, 4, 5, 9, 7, 4, 17, 3, 4,...
## $ num_satisfactory_accounts   <int> 10, 14, 10, 4, 16, 12, 10, 15, 21, 6,...
## $ num_accounts_120d_past_due  <int> 0, 0, 0, 0, 0, 0, 0, 0, NA, 0, 0, 0, 0, ...
## $ num_accounts_30d_past_due  <int> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0...
## $ num_active_debit_accounts   <int> 2, 3, 3, 2, 10, 1, 3, 5, 11, 3, 2, 2,...
## $ total_debit_limit           <int> 11100, 16500, 4300, 19400, 32700, 272...
## $ num_total_cc_accounts       <int> 14, 24, 14, 3, 20, 27, 8, 16, 19, 7, ...
## $ num_open_cc_accounts        <int> 8, 14, 8, 3, 15, 12, 7, 12, 14, 5, 8,...
## $ num_cc_carrying_balance     <int> 6, 4, 6, 2, 13, 5, 6, 10, 14, 3, 5, 3...
## $ num_mort_accounts           <int> 1, 0, 0, 0, 0, 3, 2, 7, 2, 0, 2, 3, 3...
## $ account_never_delinq_percent <dbl> 92.9, 100.0, 93.5, 100.0, 100.0, 78.1...
## $ tax_liens                  <int> 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0...
## $ public_record_bankrupt      <int> 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0...
## $ loan_purpose                  <fct> moving, debt_consolidation, other, de...
## $ application_type            <fct> individual, individual, individual, i...
## $ loan_amount                 <int> 28000, 5000, 2000, 21600, 23000, 5000...
## $ term                        <dbl> 60, 36, 36, 36, 36, 36, 60, 60, 36, 3...
## $ interest_rate               <dbl> 14.07, 12.61, 17.09, 6.72, 14.07, 6.7...
## $ installment                 <dbl> 652.53, 167.54, 71.40, 664.19, 786.87...
## $ grade                       <fct> C, C, D, A, C, A, C, B, C, A, C, B, C...
## $ sub_grade                   <fct> C3, C1, D1, A3, C3, A3, C2, B5, C2, A...
## $ issue_month                  <fct> Mar-2018, Feb-2018, Feb-2018, Jan-201...
## $ loan_status                  <fct> Current, Current, Current, Current, C...
## $ initial_listing_status       <fct> whole, whole, fractional, whole, whol...
## $ disbursement_method         <fct> Cash, Cash, Cash, Cash, Cash, Cash, C...
## $ balance                     <dbl> 27015.86, 4651.37, 1824.63, 18853.26,...
## $ paid_total                   <dbl> 1999.330, 499.120, 281.800, 3312.890,...
## $ paid_principal               <dbl> 984.14, 348.63, 175.37, 2746.74, 1569...

```

```
## $ paid_interest          <dbl> 1015.19, 150.49, 106.43, 566.15, 754.1...
## $ paid_late_fees          <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0...
```

```
# Selecting numeric variables
```

```
loans <- loans_full_schema %>% # <-- pipe operator
  select(paid_total, term, interest_rate,
         annual_income, paid_late_fees, debt_to_income)
# View the columns stacked one below another
glimpse(loans)
```

```
## Rows: 10,000
## Columns: 6
## $ paid_total      <dbl> 1999.330, 499.120, 281.800, 3312.890, 2324.650, 873.130...
## $ term            <dbl> 60, 36, 36, 36, 36, 36, 60, 60, 36, 36, 60, 60, 36, 60,...
## $ interest_rate   <dbl> 14.07, 12.61, 17.09, 6.72, 14.07, 6.72, 13.59, 11.99, 1...
## $ annual_income   <dbl> 90000, 40000, 40000, 30000, 35000, 34000, 35000, 110000...
## $ paid_late_fees  <dbl> 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0...
## $ debt_to_income  <dbl> 18.01, 5.04, 21.15, 10.16, 57.96, 6.46, 23.66, 16.19, 3...
```

```
# Selecting categoric variables
```

```
loans <- loans_full_schema %>%
  select(grade, state, homeownership, disbursement_method ) # type the chosen columns
as in the lecture slide
# View the columns stacked one below another
glimpse(loans)
```

```
## Rows: 10,000
## Columns: 4
## $ grade           <fct> C, C, D, A, C, A, C, B, C, A, C, B, C, B, D, D, D,...
## $ state           <fct> NJ, HI, WI, PA, CA, KY, MI, AZ, NV, IL, IL, FL, SC...
## $ homeownership   <fct> MORTGAGE, RENT, RENT, RENT, RENT, OWN, MORTGAGE, M...
## $ disbursement_method <fct> Cash, Cash, Cash, Cash, Cash, Cash, Cash, Cash, Ca...
```