

Integrating WordNet and Wiktionary with lemon

John McCrae¹. Elena Montiel-Ponsoda² and Philipp Cimiano¹

 $^{
m l}$ Cognitive Interaction Technology Exzellenzcluster, Universität Bielefeld

Ontology Engineering Group, Universidad Politécnica de Madrid





























Outline

Introduction

From Data Silos to Linked Data

Lemon

WordNet to lemon

Wiktionary to lemon

Linking

Conclusion

Introduction

From Data Silos to Linked Data

Lemon

WordNet to lemon

Wiktionary to lemon

Linking

Conclusion

Introduction 2/28



The need for lexical linked data

- Much lexical data is in "data silos"
 - Proprietary formats
 - Restricted access
- The Linking Open Data project fosters:
 - Publication using RDF
 - Linking between resources
- ▶ We need **open** and **RDF-native** formats for language resources
 - ▶ lemon Lexicon Model for Ontologies
 - Development under W3C OntoLex community group

Introduction 2/28

Outline

Introduction

From Data Silos to Linked Data

Lemon

WordNet to lemon


Wiktionary to lemon

Linking

Conclusion




Stage 0: Data silos






Stage 1: Syntactically interoperable






Stage 2: Linked



From Data Silos to Linked Data



Stage 3: Structurally interoperable





Stage 4: Semantically interoperable

```
:edema a lemon:LexicalEntry;
       lemon:canonicalForm [
         lemon:writtenRep "edema"@en
                           lem⊛n
       onto:pos "NP" .
penn-syntax.owl
           :edema a lemon:LexicalEntry __onto:Noun
             lemon:canonicalForm [ _ -
               lemon:writtenRep - "edema"@en
                      DC-1333
             lemon:otherForm
               lemon:writtenRep "edemata"@en ;
               schema:number schema:plural
```

Outline

Introduction

From Data Silos to Linked Data

Lemon

WordNet to lemon

Wiktionary to lemon


Linking

Conclusion

Lemon 8/28



The core of lemon



Lemon 8/28



lemon's origins

- Lexical Markup Framework (ISO 24613)
 - Standard for representing lexicons
 - XML, UML (primarily)
- LexInfo, LIR
 - Represent lexical information relative to an ontology
 - OWL
- SKOS (W3C Standard)
 - Designed for Taxonomy/Vocabulary representation
 - ▶ RDF

Lemon 9/28



Design goals

- ► RDF(S)
- Conciseness
- Not prescriptive
 - ► i.e., uses data categories
- Semantics by reference
 - i.e., uses ontologies
- Extensible

Lemon 10 / 28

Why lemon: RDF(S)

- ▶ RDF models are labelled directed graphs
 - Better representation
- Each entry has a URI
 - Queriable on the web using standards
 - Clear ownership of data
- Linking possible between different lexica
 - Reuse of lexicon data
- Some induction possible (subproperties, classes etc.)



Lemon 11/28



Why lemon: Conciseness

- ► Small models (i.e., fewer links, fewer kB)
- Easier to understand
- "Open-world": Not necessary to state all facts
 - Multiple points of view




Lemon 12 / 28



Why lemon: Semantics by Reference

- The web of data is full of ontologies in OWL, RDFS, RIF...
- Meaning of a word given by reference
- Reference (generally an ontology)
 capable of representing more complex
 semantic information
- Disambiguation is performed relative to the ontology
- No (traditional) word senses
 - No clashing of word senses in cross-lingual mappings



Lemon 13/28



Why lemon: Modular and extensible

- RDF(S) extensibility allows representation of
 - Subtle differences
 - Unexpected data categories
- Modularity
 - Different modules for different user requirements
 - New modules can be added later without affecting core



Lemon 14 / 28

Introduction

From Data Silos to Linked Data

Lemon

WordNet to lemon

Wiktionary to lemon

Linking

Conclusion

WordNet to lemon 15 / 28



Methodology

- Start with RDF-WordNet 2.0
- Mapped synsets to references
 - ► Hence synsets are treated as ontology classes
- Sense and Word correspond to lemon
- Canonical form introduced as new node, other forms extracted from WordNet files (not in RDF!)
- Part-of-Speech tags mapped to LexInfo

WordNet to lemon 15/28

Example

```
lwn:marmoset-noun-entry rdf:type lemon:LexicalEntry ;
  lexinfo:partOfSpeech lexinfo:noun ;
  lemon:sense lwn:sense-marmoset-noun-1;
 lemon:canonicalForm lwn:word-marmoset-canonicalForm .
lwn:sense-marmoset-noun-1
  lemon:reference wn20:synset-marmoset-noun-1 .
lwn:word-marmoset-canonicalForm
  lemon:writtenRep "Marmoset"@en .
```

WordNet to lemon 16 / 28

Outline

Introduction

From Data Silos to Linked Data

Lemon

WordNet to lemon


Wiktionary to lemon

Linking

Conclusion


Wiktionary to lemon 17/28






Wiktionary to lemon 17 / 28





Wiktionary to lemon 18/28





Wiktionary to lemon 19 / 28



Wiktionary to lemon 20 / 28

Example

Wiktionary:


```
<page>
<title>free</title>
<text>
==English==
===Adjective===
{{en-adi}}
# Not [[imprisoned]] or [[enslaved]].
# Obtainable without any [[payment]].
====Synonyms====
* {{sense|obtainable without payment}}:
   [[free of charge]], [[gratis]]
====Translations====
{{trans-top|not imprisoned}}
* German: {{t+|de|frei}}
{{trans-bot}}
</text>
</page>
```

lemon:

```
:free_en_adj lemon:canonicalForm [
 lemon:writtenRep "free"@en 1 :
 lexinfo:partOfSpeech lexinfo:adjective :
 lemon:sense :free_en_adj_sense0 ;
 lemon:sense :free_en_adj_sense1 ;
 lemon:sense :free en sense def .
:free_en_adj_sense0 lemon:definition [
 lemon: value "Not imprisoned or enslaved "@en ] :
 lemon:reference
   <http://en.wiktionary.org/wiki/free> ;
 lexinfo:translation :frei de sense def .
:free_en_adj_sense1 lemon:definition [
 lemon:value "Obtainable without any payment"@en ] ;
 lemon:reference
   <http://en.wiktionary.org/wiki/free> ;
 lexinfo:synonym :free of charge en sense def .
```

Wiktionary to lemon 21/28

Mapping algorithm



Wiktionary to lemon 22 / 28

Sense mapping

- ► (English) Wiktionary uses different glosses to link pages
 - "Not imprisoned or enslaved" vs. "Not imprisoned"
 - "Obtainable without any payment" vs. "Obtainable without payment"
- We merge information on the same Wiktionary page
 - IF The secondary gloss is a substring of the primary gloss
 - OR The Levenshtein distance between the glosses exceeds some λ
 - AND The Levenshtein distance is maximal among candidates

Wiktionary to lemon 23/28



Sense mapping results

λ	Merged	Coverage	Precision	Harmonic Mean
Substring	36595	37.8%	99.5%	54.8%
0.9	6842	44.9%	100%	62.0%
0.8	3398	48.4%	99%	65.0%
0.7	2669	51.2%	99%	67.5%
0.6	3243	54.5%	97%	69.8%
0.5	7128	61.9%	97%	75.6%
0.4	4612	66.6%	98%	79.3%
0.3	6295	73.1%	91%	81.1%
0.2	7983	81.4%	92%	86.4%
0.1	6934	88.5%	73%	80.0%
0.0	3862	92.5%	71%	80.3%

Wiktionary to lemon 24 / 28

Outline

Introduction

From Data Silos to Linked Data

Lemon

WordNet to lemon

Wiktionary to lemon

Linking

Conclusion

Linking 25 / 28

Linking WordNet and Wiktionary

- We used the following criteria:
 - ▶ The canonical (lemma) form is equivalent
 - ▶ Part-of-speech is the same
 - Do not assert different values for the same property
 - Do not have a different non-canonical form with the same properties
 - e.g., German: "Banken" versus "Bänke"
- Results:

	#Entries	Percent (WN)	Percent (Wikt)
Linked	63,478	21.0%	26.9%
Not Linked (Wiktionary)	172,674	-	73.1%
Not Linked (WordNet)	238,408	79.0%	-
Ambiguous	1,741	0.6%	0.7%

Linking 25 / 28

Sample of failed links

(in Wiktionary not in WordNet)

- 28: In WordNet
- 9 ("polysemic", "abaciscus" (pictured)): Omissions
- ▶ 10 ("false friend", "apples and pears"): Idioms not covered by WordNet
- 2 ("raven" (adj), "to minute" (verb)): Not with same part-of-speech
- ▶ 1 ("wares"): Other



Outline

Introduction

From Data Silos to Linked Data

Lemon

WordNet to lemon

Wiktionary to lemon

Linking

Conclusion

Conclusion 27/28



Conclusion

- Conversion of WordNet easy due to model interoperability (... even stage 1 helps!)
- Wiktionary much harder
- ▶ **lemon** is an adequate model for representing Wiktionary and WordNet
- Wiktionary's data model is flawed!
- Overlap between WordNet and Wiktionary quite low (~25%)
- Linking these resources can create a "virtual" resource with much higher coverage

Conclusion 27/28

Learn more

- ► http://monnetproject.deri.ie/lemonsource: Data sets from the presentation
- http://www.lexinfo.net/lemon-cookbook.pdf: The lemon cookbook (technical manual)
- http://www.w3.org/community/ontolex: OntoLex Community group
- ▶ http://www.monnet-project.eu/lemon: lemon Ontology

Conclusion 28 / 28