

1. In Packet Tracer, open the **firstInitialLastNameT3RIP-OSPF** and save it as **firstInitialLastNameT3OSPF-EIGRP**.

Redistribute bgp

The screenshot displays the Cisco Packet Tracer interface. On the left, a network diagram shows a central 'Main-Office-Router' connected to several switches and PCs. The switches are labeled 'Switch-PT-Empty', 'Switch-PT-Empty', 'Switch-PT-Empty', and 'Switch-PT-Empty'. The PCs are labeled 'Engineering-PC1 (10.10.42.18)', 'Sales-PC1 (10.10.42.34)', 'Admin-PC1 (10.10.42.50)', and 'Engineering-PC2 (10.10.42.19)'. The diagram also shows a 'Server-PT' and 'Laptop-PT' connected to the switches. A legend indicates VLANs: VLAN 1 - ADMIN, VLAN 15 - ENGINEERING, VLAN 20 - DHCP SERVERS, and VLAN 25 - EVERYTHING ELSE.

On the right, the 'Main-Office-Router' CLI window is open, showing the following configuration commands:

```
translating rip
% Unknown command or computer name, or unable to find computer address
Main-Office-Router>en
Main-Office-Router#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Main-Office-Router(config)#router rip
Main-Office-Router(config-router)#version 2
Main-Office-Router(config-router)#network 192.168.2.0
Main-Office-Router(config-router)#router eigrp 100
Main-Office-Router(config-router)#redistribute bgp 1234 metric
% Incomplete command.
Main-Office-Router(config-router)#redistribute bgp 1234 metric ?
<1-4294967295> Bandwidth metric in Kbits per second
Main-Office-Router(config-router)#redistribute bgp 1234 metric 10000 ?
<0-4294967295> EIGRP delay metric, in 10 microsecond units
Main-Office-Router(config-router)#redistribute bgp 1234 metric 10000
% Incomplete command.
Main-Office-Router(config-router)#redistribute bgp 1234 metric 10000 ?
<0-4294967295> EIGRP delay metric, in 10 microsecond units
Main-Office-Router(config-router)#redistribute bgp 1234 metric 10000 107
% Incomplete command.
Main-Office-Router(config-router)#redistribute bgp 1234 metric 10000 10 255 ?
<1-255> EIGRP Effective bandwidth metric (Loading) where 255 is 100% loaded
Main-Office-Router(config-router)#redistribute bgp 1234 metric 10000 10 255 255?
<1-255>
Main-Office-Router(config-router)#redistribute bgp 1234 metric 10000 10 255 255 1500
Main-Office-Router(config-router)#
```

The bottom of the screen shows the 'Realtime' simulation mode with a timeline and a table of events. The table has columns for 'Fire', 'Last Status', 'Source', 'Destination', 'Type', 'Color', 'Time(sec)', 'Periodic', 'Num', 'Edit', and 'Delete'. The timeline shows a sequence of events with IP addresses: 4331, 4321, 1941, 2901, 2911, 81910X, 81910W, 829, 1240, PT-Empty, PT-Empty, 1841, 26200N, 26.

on Main-Office-Router

Physical Config CLI Attributes

IOS Command Line Interface

```
ip address 10.10.42.49 255.255.255.240
!
interface GigabitEthernet8/0.10
 encapsulation dot1Q 10
 ip address 10.10.42.33 255.255.255.240
 ip helper-address 10.10.42.82
!
interface GigabitEthernet8/0.15
 encapsulation dot1Q 15
 ip address 10.10.42.17 255.255.255.240
 ip helper-address 10.10.42.82
!
interface GigabitEthernet8/0.20
 encapsulation dot1Q 20
 ip address 10.10.42.81 255.255.255.240
 ip helper-address 10.10.42.82
!
interface GigabitEthernet8/0.25
 encapsulation dot1Q 25
 ip address 10.10.42.65 255.255.255.240
 ip helper-address 10.10.42.82
!
router eigrp 100
 redistribute bgp 1234 metric 10000 10 255 255 1500
 network 192.168.255.0 0.0.0.3
 network 192.168.255.4 0.0.0.3
 network 192.168.255.8 0.0.0.3
 network 192.168.255.12 0.0.0.3
 network 192.168.255.16 0.0.0.3
 network 192.168.255.20 0.0.0.3
 network 192.168.255.24 0.0.0.3
 network 10.10.42.16 0.0.0.15
 network 10.10.42.32 0.0.0.15
 network 10.10.42.48 0.0.0.15
 network 10.10.42.64 0.0.0.15
 network 10.10.42.80 0.0.0.15
 network 192.168.200.0 0.0.0.3
 no auto-summary
!
ip classless
!
ip flow-export version 9
!
!
!
!
```

Ctrl+F6 to exit CLI focus

Copy Paste

☐ Top

Cisco Packet Tracer - C:\Users\jlela\Downloads\ITT-216-RS-ITT116FinalProject\PresleyOSPF.pkt

File Edit Options View Tools Extensions Window Help

Logical Physical x: 1472, y: 472

NewLocation4

Physical Config CLI Attributes

IOS Command Line Interface

```
clock rate 2000000
!
interface GigabitEthernet6/0
no ip address
duplex auto
speed auto
!
interface GigabitEthernet9/0
ip address 192.168.4.1 255.255.255.0
duplex auto
speed auto
!
router eigrp 100
network 192.168.4.0
network 192.168.255.0
network 192.168.4.0 0.0.0.3
network 192.168.255.20 0.0.0.3
no auto-summary
!
ip classless
!
ip flow-export version 9
!
!
--More--
Ctrl+F6 to exit CLI focus
Copy Paste

Time: 01:02:16



Realtime Simulation



Scenario 0



Fire Last Status Source Destination Type Color Time(sec) Periodic Num Edit Delete



New Delete



Toggle PDU List Window



41°F Clear



Search



1841



11:27 PM 4/18/2023


```

Cisco Packet Tracer - C:\Users\jlela\Downloads\ITT-216-RS-ITT116FinalProject\PresleyOSPF.pkt

File Edit Options View Tools Extensions Window Help

Logical Physical x: 1865, y: 269

NewLocation5

Physical Config CLI Attributes

IOS Command Line Interface

```
!
duplex auto
speed auto
shutdown
!
interface GigabitEthernet9/0
ip address 192.168.5.1 255.255.255.0
duplex auto
speed auto
!
router eigrp 100
network 192.168.5.0
network 192.168.255.24 0.0.0.3
network 192.168.5.0 0.0.0.3
no auto-summary
!
ip classless
!
ip flow-export version 9
!
!
--More--
Ctrl+F6 to exit CLI focus
Copy Paste

Time: 01:01:35



Realtime Simulation



Scenario 0



Fire Last Status Source Destination Type Color Time(sec) Periodic Num Edit Delete



New Delete



Toggle PDU List Window



41°F Clear



Search



1841



11:26 PM 4/18/2023


```



Main-Office-Router

Physical Config CLI Attributes

IOS Command Line Interface

```
state to up

Main-Office-Router>en
Main-Office-Router#sh ip eigrp topology
IP-EIGRP Topology Table for AS 100/ID(192.168.255.25)

Codes: P - Passive, A - Active, U - Update, Q - Query, R - Reply,
       r - Reply status

P 10.10.42.16/28, 1 successors, FD is 28160
   via Connected, GigabitEthernet8/0.15
P 10.10.42.32/28, 1 successors, FD is 28160
   via Connected, GigabitEthernet8/0.10
P 10.10.42.48/28, 1 successors, FD is 28160
   via Connected, GigabitEthernet8/0.1
P 10.10.42.64/28, 1 successors, FD is 28160
   via Connected, GigabitEthernet8/0.25
P 10.10.42.80/28, 1 successors, FD is 28160
   via Connected, GigabitEthernet8/0.20
P 192.168.255.0/30, 1 successors, FD is 2169856
   via Connected, Serial0/0
P 192.168.255.4/30, 1 successors, FD is 2169856
   via Connected, Serial1/0
P 192.168.255.8/30, 1 successors, FD is 2169856
   via Connected, Serial2/0
P 192.168.255.12/30, 1 successors, FD is 2169856
--More--
```

Ctrl+F6 to exit CLI focus

☐ Top

Pinging from one of the workstations but didn't work.

