

CHECKLIST FOR SPOT UV JOBS

You may find this checklist useful if you have any orders which requires Spot UV finishing.

Preparing artwork may be complicated. To reduce any possible error or delays, we hereby prepared a checklist to assist you on your artwork preparation. Please ensure all steps stated has been complied in your artwork.

IMAGES

- ☐ The Spot UV image can be either a vector graphic, text, shape, solid colour, or picture. If its a picture, you might just need to trace out the Spot UV section.
- ☐ All vital elements are kept within the Safe Zone
- ☐ Fill the Spot UV area with K=100. No tint or gradient applied.
- ☐ Registration of image are accurately aligned with the offset printing artwork.
- ☐ No Spot UV has been applied to outlines. It will make misalignment more obvious.
- ☐ No Spot UV applied on gluing zones.

TEXT

- ☐ Font size are not smaller than 4pts (based on Arial Fonts types)
- ☐ Logos that contain wordings are not lesser than 4pts.
- ☐ No usage of font with sharp edges like Serif.

LINE

- ☐ Line Thickness are not lesser than 0.5pts

ARTWORK FILE

- ☐ Spot UV can be printed on single sides or both sides options. Make sure you prepared two sets of artwork files if there are both sides printing.
- ☐ Artwork is prepared in the correct Product Template.
- ☐ All guidelines in the Product Templates are removed.
- ☐ Artwork is saved in PDF only.
- ☐ Artwork resolution is 300dpi or more.
- ☐ Select only CMYK colour mode for your artwork.
- ☐ 2 PDF files are prepared for each set. File 1 for artwork without Spot UV, and File 2 for Spot UV only.
- ☐ Zip or combine the files into one file only.
- ☐ Artwork is arranged according to Printoka specification and converted into PDF file.